点击事件

//////////////////////////写法1

Click Here

```
<script type="text/javascript">
var btnClick = document.getElementById('btnClick');
btnClick.onclick = function showMessage(e) {
    console.log(this.id);
  console.log(e);
};
</script>
////////////////////////////////////写法2
<input id="btnClick" type="button" value="Click Here" />
<script type="text/javascript">
var btnClick = document.getElementById('btnClick');
btnClick.addEventListener('click', function() {
    alert(this.id);
}, false);
</script>
<input id="btnClick" type="button" value="Click Here" />
<script type="text/javascript">
var btnClick = document.getElementById('btnClick');
btnClick.addEventListener('click', function() {
    console.log(this.id);
}, false);
btnClick.addEventListener('click', function() {
    console.log('Hello!');
}, false);
</script>
////////////////////////////////移除
<input id="btnClick" type="button" value="Click Here" />
<script type="text/javascript">
var btnClick = document.getElementById('btnClick');
var handler=function() {
    alert(this.id);
}
btnClick.addEventListener('click', handler, false);
```

```
btnClick.removeEventListener('click', handler, false);
</script>
///////jQuery
$('#ct').on('click', function(){});
<!DOCTYPE html>
<html>
<head>
  <meta charset="utf-8">
  <title>JS Bin</title>
  <style>
   .ct{
     width: 200px;
     height: 80px;
     border:1px solid #ccc;
   }
  </style>
</head>
<body>
  <div class="ct">
  </div>
  <button id="btn1">蓝色</button>
  <button id="btn2">红色</button>
  <script type="text/javascript">
     var btn1 = document.querySelector('#btn1'),
         btn2 = document.querySelector('#btn2'),
         ct = document.querySelector('.ct');
     btn1.addEventListener('click', function(){
       ct.style.backgroundColor = 'blue';
       //getComputedStyle('ct').width
     });
     btn2.addEventListener('click', function(){
       ct.style.backgroundColor = 'red';
     });
  </script>
</body>
</html>
<!DOCTYPE html>
<html>
<head>
  <script src="https://code.jquery.com/jquery-3.1.1.min.js"></script>
  <meta charset="utf-8">
  <title>JS Bin</title>
  <style>
```

```
.ct{
      width: 200px;
      height: 80px;
      border:1px solid #ccc;
    }
    .state1{
     width: 100px;
      height: 100px;
      background: blue;
      border: 1px solid #ccc;
    .state2{
     width: 200px;
      height: 100px;
     background: yellow;
      border: 1px dotted #ccc;
    }
  </style>
</head>
<body>
  <div class="ct"></div>
  <button id="btn1">蓝色</button>
  <button id="btn2">红色</button>
  <script>
    $(document).ready(function(){
     $("#btn1").click(function(){
     $(".ct").removeClass("state2");
      $(".ct").addClass("state1");
   });
     $("#btn2").click(function(){
      $(".ct").removeClass("state1");
     $(".ct").addClass("state2");
   });
   });
      var btn1 = document.querySelector('#btn1');
      var btn2 = document.querySelector('#btn2');
      var ct = document.querySelector('.ct');
      btn1.addEventListener('click', function(){
        removeClass(ct, 'state2');
        addClass(ct, 'state1');
      });
      btn2.addEventListener('click', function(){
        removeClass(ct, 'state1');
```

```
addClass(ct, 'state2');
});
</script>
</body>
</html>
```

科学///////////

```
<!DOCTYPE html>
<html>
<head>
  <meta charset="utf-8">
  <title>JS Bin</title>
</head>
<body>
  <button id="btn">点我</button>
  <script>
    var app = {
  init:function(){
    this.target = document.querySelector('#btn');
    this.bind();
},
  bind:function(){
    var _this = this;
    this.target.addEventListener('click', function(){
     var self = this;
     this.innerText = '我被点了';
      _this.sayHello();
       setTimeout(function(){
    self.innerText = '点我';
         _this.sayGoodBye();
  },1000)
   });
  },
  sayHello: function(){
    console.log("hello...");
  },
  sayGoodBye: function(){
    console.log("bye bye...");
  }
};
```

```
app.init();
  </script>
  </body>
  </html>
```