log: hector_mapping 20210629

log: hector_mapping 20210629

```
    in response to 5044:
        reply for 1
        reply for 2
        reply for 3
    attempts and modifications on new launch file
        1. launch file: hector_slam_rfans_tf_1.launch
        2. launch file: hector_slam_rfans_tf_2.launch
```

1. in response to 5044:

reply for 1

Islidar_c16_tf.launch file used.

```
<launch>
 1
 2
 3
      <!-- launch lslidar_c16 -->
      <node pkg="lslidar_c16_driver"</pre>
 4
             type="lslidar_c16_driver_node"
 6
             name="lslidar_c16_driver_node"
             output="screen">
         <param name="lidar_ip" value="192.168.1.200"/>
 8
9
        <param name="device_port" value="2368"/>
           <param name="add_multicast" value="false"/>
10
11
           <param name="group_ip" value="224.1.1.2"/>
12
      </node>
13
14
      <node pkg="lslidar_c16_decoder"</pre>
             type="lslidar_c16_decoder_node"
15
16
             name="lslidar_c16_decoder_node"
             output="screen">
17
         <param name="frame_id" value="laser_link"/>
18
         <!-- <param name="point_num" value="2000"/> -->
19
```

```
<param name="point_num" value="5000"/>
20
21
        <param name="channel_num" value="8"/>
        <param name="angle_disable_min" value="0"/>
22
        <param name="angle_disable_max" value="0"/>
23
        <param name="angle3_disable_min" value="0"/>
24
        <param name="angle3_disable_max" value="0"/>
25
26
        <param name="min_range" value="0.15"/>
27
        <param name="max_range" value="150.0"/>
        <!-- <param name="frequency" value="10.0"/> -->
28
29
        <param name="frequency" value="100.0"/>
        <param name="publish_point_cloud" value="true"/>
30
31
        <param name="publish_scan" value="true"/>
        <param name="use_gps_ts" value="false"/>
32
      </node>
33
34
35
      <!-- TF monitoring -->
36
      <node pkg="tf" type="static_transform_publisher" name="base_to_laser"</pre>
37
38
             args="0.0 0.0 1.4 0.0 0.0 0.0 base_link laser_link 100">
39
      </node>
40
41
42
      <!-- visualize point cloud -->
      <node name="rviz" pkg="rviz" type="rviz"</pre>
43
             args="-d $(find
    hector_slam_pkg)/rviz/config_rviz_lslidar_tf_fixBase_0629.rviz"
45
            output="screen"/>
46
47
    </launch>
```

CLI output: roslaunch hector_slam_pkg lslidar_c16_tf.launch --screen

```
1
    $ roslaunch hector_slam_pkg lslidar_c16_tf.launch --screen
 2
    ... logging to /home/ds16v2/.ros/log/4f973c76-d8d7-11eb-851e-
 3
    a0c589ac1e85/roslaunch-ds16v2-14552.log
   Checking log directory for disk usage. This may take awhile.
5
    Press Ctrl-C to interrupt
    Done checking log file disk usage. Usage is <1GB.
6
   started roslaunch server http://ds16v2:36779/
8
9
10
    SUMMARY
11
    =======
12
    PARAMETERS
13
14
     * /lslidar_c16_decoder_node/angle3_disable_max: 0
     * /lslidar_c16_decoder_node/angle3_disable_min: 0
15
16
     * /lslidar_c16_decoder_node/angle_disable_max: 0
17
     * /lslidar_c16_decoder_node/angle_disable_min: 0
     * /lslidar_c16_decoder_node/channel_num: 8
18
19
     * /lslidar_c16_decoder_node/frame_id: laser_link
     * /lslidar_c16_decoder_node/frequency: 100.0
20
21
     * /lslidar_c16_decoder_node/max_range: 150.0
     * /lslidar_c16_decoder_node/min_range: 0.15
22
```

```
23
     * /lslidar_c16_decoder_node/point_num: 5000
24
     * /lslidar_c16_decoder_node/publish_point_cloud: True
     * /lslidar c16 decoder node/publish scan: True
25
     * /lslidar_c16_decoder_node/use_gps_ts: False
26
27
     * /lslidar_c16_driver_node/add_multicast: False
     * /lslidar_c16_driver_node/device_port: 2368
28
29
     * /lslidar_c16_driver_node/group_ip: 224.1.1.2
     * /lslidar_c16_driver_node/lidar_ip: 192.168.1.200
30
     * /rosdistro: kinetic
31
     * /rosversion: 1.12.17
32
33
   NODES
34
35
        base_to_laser (tf/static_transform_publisher)
36
37
        lslidar_c16_decoder_node (lslidar_c16_decoder/lslidar_c16_decoder_node)
        lslidar_c16_driver_node (lslidar_c16_driver/lslidar_c16_driver_node)
38
39
        rviz (rviz/rviz)
40
41
   auto-starting new master
42
    process[master]: started with pid [14562]
    ROS_MASTER_URI=http://localhost:11311
43
44
45
    setting /run_id to 4f973c76-d8d7-11eb-851e-a0c589ac1e85
   process[rosout-1]: started with pid [14575]
46
47
    started core service [/rosout]
48
   process[lslidar_c16_driver_node-2]: started with pid [14582]
    process[lslidar_c16_decoder_node-3]: started with pid [14593]
49
    process[base_to_laser-4]: started with pid [14595]
50
   [ INFO] [1624970483.673167284]: namespace is /lslidar_c16_driver_node
51
    process[rviz-5]: started with pid [14616]
   [ INFO] [1624970483.685240866]: Opening UDP socket: address 192.168.1.200
54
    [ INFO] [1624970483.685269686]: Opening UDP socket: port 2368
   [ INFO] [1624970483.685288398]: expected frequency: 833.333 (Hz)
55
   [ INFO] [1624970483.686908285]: Opening UDP socket: port 2368
    [ INFO] [1624970483.686940262]: Initialised Islidar c16 without error
   [ WARN] [1624970483.694945045]: discard Point cloud angle from 0.00 to 0.00
    [ WARN] [1624970483.694994583]: switch angle from 6.28 to 6.28 in left hand
    rule
   [ WARN] [1624970483.703158191]: Using GPS timestamp or not 0
60
61
    [ INFO] [1624970483.703196361]: require to publish scan type message
    [ INFO] [1624970483.792509752]: rviz version 1.12.17
62
    [ INFO] [1624970483.792550719]: compiled against Qt version 5.5.1
64
    [ INFO] [1624970483.792559324]: compiled against OGRE version 1.9.0
    (Ghadamon)
65
   [ INFO] [1624970483.912675746]: default channel is 8
    [ INFO] [1624970484.219912713]: Stereo is NOT SUPPORTED
    [ INFO] [1624970484.219981682]: OpenGl version: 4.6 (GLSL 4.6).
68
   ^C[rviz-5] killing on exit
   [base_to_laser-4] killing on exit
69
70
   [lslidar_c16_decoder_node-3] killing on exit
71
   [lslidar_c16_driver_node-2] killing on exit
    [rosout-1] killing on exit
73
   [master] killing on exit
74
    shutting down processing monitor...
    ... shutting down processing monitor complete
75
76
77
    ds16v2@ds16v2:~/catkin_x/lslidar_slam_ws$ roslaunch hector_slam_pkg
    lslidar_c16_tf.launch --screen
```

```
78 ... logging to /home/ds16v2/.ros/log/339fdc84-d8d8-11eb-851e-
     a0c589ac1e85/roslaunch-ds16v2-14827.log
 79
     Checking log directory for disk usage. This may take awhile.
     Press Ctrl-C to interrupt
     Done checking log file disk usage. Usage is <1GB.
 82
     started roslaunch server http://ds16v2:43831/
 83
 84
 85
     SUMMARY
 86
     =======
 87
 88
    PARAMETERS
      * /lslidar_c16_decoder_node/angle3_disable_max: 0
 89
 90
      * /lslidar_c16_decoder_node/angle3_disable_min: 0
 91
      * /lslidar_c16_decoder_node/angle_disable_max: 0
      * /lslidar_c16_decoder_node/angle_disable_min: 0
 92
      * /lslidar_c16_decoder_node/channel_num: 8
 93
      * /lslidar_c16_decoder_node/frame_id: laser_link
 94
 95
      * /lslidar_c16_decoder_node/frequency: 100.0
      * /lslidar_c16_decoder_node/max_range: 150.0
 97
      * /lslidar_c16_decoder_node/min_range: 0.15
      * /lslidar_c16_decoder_node/point_num: 5000
 98
      * /lslidar_c16_decoder_node/publish_point_cloud: True
 99
100
      * /lslidar_c16_decoder_node/publish_scan: True
101
      * /lslidar_c16_decoder_node/use_gps_ts: False
102
      * /lslidar_c16_driver_node/add_multicast: False
      * /lslidar_c16_driver_node/device_port: 2368
103
      * /lslidar_c16_driver_node/group_ip: 224.1.1.2
104
105
      * /lslidar_c16_driver_node/lidar_ip: 192.168.1.200
106
      * /rosdistro: kinetic
107
      * /rosversion: 1.12.17
108
     NODES
109
110
     /
111
         base_to_laser (tf/static_transform_publisher)
112
         lslidar_c16_decoder_node (lslidar_c16_decoder/lslidar_c16_decoder_node)
         lslidar_c16_driver_node (lslidar_c16_driver/lslidar_c16_driver_node)
113
114
         rviz (rviz/rviz)
115
116
     auto-starting new master
117
     process[master]: started with pid [14837]
     ROS_MASTER_URI=http://localhost:11311
119
120
     setting /run_id to 339fdc84-d8d8-11eb-851e-a0c589ac1e85
121
     process[rosout-1]: started with pid [14850]
122
     started core service [/rosout]
     process[lslidar_c16_driver_node-2]: started with pid [14857]
124
     process[lslidar_c16_decoder_node-3]: started with pid [14868]
    [ INFO] [1624970866.253656925]: namespace is /lslidar_c16_driver_node
125
     process[base_to_laser-4]: started with pid [14878]
126
     [ INFO] [1624970866.263323714]: Opening UDP socket: address 192.168.1.200
127
     [ INFO] [1624970866.263357449]: Opening UDP socket: port 2368
129
     [ INFO] [1624970866.263378204]: expected frequency: 833.333 (Hz)
     [ INFO] [1624970866.264967737]: Opening UDP socket: port 2368
130
     [ INFO] [1624970866.264997584]: Initialised lslidar c16 without error
131
     process[rviz-5]: started with pid [14897]
132
133
     [ WARN] [1624970866.276564385]: discard Point cloud angle from 0.00 to 0.00
```

```
134 [ WARN] [1624970866.276614127]: switch angle from 6.28 to 6.28 in left hand
     rule
    [ WARN] [1624970866.283796490]: Using GPS timestamp or not 0
135
136 [ INFO] [1624970866.283822872]: require to publish scan type message
    [ INFO] [1624970866.375069769]: rviz version 1.12.17
138 [ INFO] [1624970866.375115846]: compiled against Qt version 5.5.1
    [ INFO] [1624970866.375129498]: compiled against OGRE version 1.9.0
139
     (Ghadamon)
140 [ INFO] [1624970866.492806518]: default channel is 8
    [ INFO] [1624970866.792206008]: Stereo is NOT SUPPORTED
    [ INFO] [1624970866.792286412]: OpenGl version: 4.6 (GLSL 4.6).
142
143
144
```

```
auto-starting new master
process[master]: started with pid [9417]
ROS_MASTER_URI=http://localhost:11311

setting /run_id to 19521c60-d8ca-1leb-85le-a0c589acle85
process[rosout-1]: started with pid [9430]
started core service [/rosout]
process[lslidar_c16_driver_node-2]: started with pid [9437]
process[lslidar_c16_decoder_node-3]: started with pid [9448]
[ INFO] [1624964809.1503412256]: namespace is /lslidar_c16_driver_node
process[rviz-4]: started with pid [9458]
[ INFO] [1624964809.170676833]: Opening UDP socket: address 192.168.1.200
[ INFO] [1624964809.170715141]: Opening UDP socket: port 2368
[ INFO] [1624964809.17073507]]: expected frequency: 833.333 (Hz)
[ INFO] [1624964809.172144538]: Opening UDP socket: port 2368
[ INFO] [1624964809.1721349]: Initialised Islidar c16 without error
[ WARN] [1624964809.178980294]: discard Point cloud angle from 0.00 to 0.00
[ WARN] [1624964809.179029846]: switch angle from 6.28 to 6.28 in left hand rule
[ WARN] [1624964809.184273260]: Using GPS timestamp or not 0
[ INFO] [1624964809.275655555]: compiled against 0t version 5.5.1
[ INFO] [1624964809.275655555]: compiled against 0GRE version 1.9.0 (Ghadamon)
[ INFO] [1624964809.729855292]: Open60 version: 4.6 (GLSL 4.6).
```


CLI output: rostopic list


```
ds16v2@ds16v2:~/catkin_x/lslidar_slam_ws$ rostopic list
clicked point/
/diagnostics
/initialpose
/layer_num
/lslidar_packet
/lslidar point cloud
/lslidar_sweep
/move_base_simple/goal
/rosout
/rosout agg
/scan channel
/statistics
                                                            perimental
/tf
/tf static
ds16v2@ds16v2:~/catkin_x/lslidar_slam ws$ ■ 1195词
                                                               31 fps
```


reply for 2


note: when adding tf package node in .launch file


again run rqt, the /tf node will be displayed in rqt graph.












reply for 3


in **plugin --> visualization**, only **image view** and **plot** options are there, there is no **TF trees** on drop down menu.

when add package TF in .launch file, we can get the tf tree through rviz



2. attempts and modifications on new launch file

1. launch file: hector_slam_rfans_tf_1.launch



```
[ WARN] [16249771098.787258149]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977100, 797389046]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977101.879287971]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977102.988428362]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977103.990604131]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977105.073386801]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977105.073386801]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977107.081840015]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977108.089150879]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977109.162250901]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977110.177657412]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977112.182128786]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977113.20419786]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977113.20419786]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977113.20419786]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977113.20419786]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977113.20419786]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977113.20419786]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977113.29934336]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977113.399372412]; Can't transform pointcloud from frame laser frame to base link
[ WARN] [1624977115.283984336]; Can't transform pointcloud from frame laser frame to base link
```

```
ds16v2:~/catkin x/lslidar slam ws$ rostopic list
clicked point
/diagnostics
/front/scan base link
/initialpose base link
/layer_num
/lslidar_packet
/lslidar_point_cloud
/lslidar_sweep
/map metadata ase link
/move base simple/goal
poseupdate base link
(rosoute to base linkfrom
rosout agg base link
/scan to base link
/scan channel
/slam cloud base link
/slam_out_pose seasink link ]: Dr
/statistics
/syscommand
/tf
tf static
ds16v2@ds16v2:~/catkin x/lslidar slam ws$
```

2. launch file: hector_slam_rfans_tf_2.launch

