


Practical No. 2

Aim: Using Packet Tracer, create a basic network of two computers using appropriate network wire through Static IP address allocation and verify connectivity.

Program:



1st PC:

PC0

Physical Config **Desktop** Programming Attributes

IP Configuration

Interface: FastEthernet0

IP Configuration

☐ DHCP ☒ Static

IP Address: 192.168.1.2

Subnet Mask: 255.255.255.0

Default Gateway: 192.168.1.1

DNS Server: 0.0.0.0

IPv6 Configuration

☐ DHCP ☐ Auto Config ☒ Static

IPv6 Address: /

Link Local Address: FE80::5253:F706:D192:6E42

IPv6 Gateway:

IPv6 DNS Server:

802.1X

☐ Use 802.1X Security

☐ Top

2nd PC:

PC1

Physical Config Desktop Programming Attributes

IP Configuration

Interface: FastEthernet0

IP Configuration

☐ DHCP ☒ Static

IP Address: 192.168.1.3

Subnet Mask: 255.255.255.0

Default Gateway: 192.168.1.1

DNS Server: 0.0.0.0

IPv6 Configuration

☐ DHCP ☐ Auto Config ☒ Static

IPv6 Address: /

Link Local Address: FE80::201:42FF:FE8B:2377

IPv6 Gateway:

IPv6 DNS Server:

802.1X

☐ Use 802.1X Security

☐ Top

Output:

```
C:\>ping 10.0.0.3

Pinging 10.0.0.3 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 10.0.0.3:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\>ping
Packet Tracer PC Ping

Usage: ping [-n count | -v TOS | -t ] target

C:\>ping 192.168.1.3

Pinging 192.168.1.3 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.
```

Name: Kaustubh Rane
Roll No.: CS23037

Computer Networks