UC San Diego

# Safety Aware Speculative Decoding

Atharv Nair  Raghusrinivasan Venkatesan

ECE 285 | March 12 2025

# Agenda

Background

Methods

Results

# Background and Motivation

UC San Diego

## SPECULATIVE DECODING RISKS

Standard SD achieves 2-3x speedup but introduces a safety gap: draft models are often less aligned than target models.

- **Drift:** Draft models may generate harmful tokens that pass verification before rejection.
- **Challenge:** Strengthening the SD pipeline without retraining.

## THE ALIGNMENT PROBLEM

Pre-trained LLMs remain vulnerable to adversarial jailbreaks that elicit harmful content through sophisticated techniques.

- **DeepInception:** Role-play hypnotization to bypass filters.
- **Prefilling:** Adversarial prefixes forcing model compliance.

# Background & Motivation

UC San Diego

## Speculative Decoding

- **Idea**: Use a small, fast draft model to propose candidate tokens and a large target model to verify
- **Goal**: Speed up autoregressive decoding (which is sequential and expensive for big models)

## Speculative Safety Aware Decoding (SSD)

- To save up on instruction tuning, we use a training free drop in method
- Using Speculative Safety-Aware Decoding to add the safety aspect

*Leviathan et al., ICML 2023 — "Fast Inference from Transformers via Speculative Decoding"*
*Xuekang Wang, Shengyu Zhu, and Xueqi Cheng. 2025. Speculative Safety-Aware Decoding. In Proceedings of EMNLP 2025, pages 12838–12852.*

# Speculative Safety-Aware Decoding

- The authors suggest that the draft does come up with safety aligned in top-c.
- Over a window of length b (e.g. 7) tokens, **β** = fraction of steps where the sampled token was in the draft's top-c.
- **High β** → draft and target agree (likely benign) → Intersection mode
- **Low β** → draft and target disagree (possible jailbreak) → Union mode




- **Intersection mode**: sample from $\mathcal{S}_t = \text{top-}c(p_{\text{draft}}) \cap \text{top-}c(p_{\text{target}})$ — restricts to tokens both models agree on (safer)
- **Union mode**: sample from $\mathcal{U}_t = \text{top-}c(p_{\text{draft}}) \cup \text{top-}c(p_{\text{target}})$ — allows safety-expert tokens through even if target disagrees (more robust)

*Xuekang Wang, Shengyu Zhu, and Xueqi Cheng. 2025. Speculative Safety-Aware Decoding. In Proceedings of EMNLP 2025, pages 12838–12852.*

# Methods

Some improvements and novel extensions to the existing work on SSD

- Contrastive System Prompts for SSD and Perplexity-gated early Union (Improvements)
- Alignment Augmented Safety Aware Speculative Decoding (Novel Extension)
- Composite Risk Score over Match-Ratio SSD (Novel Extension)
- Steering (Novel Extension)

# Contrastive System Prompts for SSD and Perplexity-gated early Union

UC San Diego

## Contrastive system prompts

- Original work uses same system prompt, we did some intervention around keeping contrastive prompts for draft and Target model
- **Observation**: Union mode triggered earlier than the one with same system prompts
- Training free improvement on refusal for Jailbreak/Harmful Prompts

## Perplexity gated early Union

- Early refusal to high perplexity harmful queries, compared to match ratio
- Adversarial/jailbreak prompts (ex - GCG suffixes, DAN-style text) often have anomalously high perplexity
- If **perplexity > threshold** → force Union mode from token 1 for that prompt

# Alignment Augmented Safety Aware Speculative Decoding

- "**AASD** = KV-cached decoding + alignment sampling + conditional verification → speedup, safety-aligned."

**How we blend in the ideas of AASD with SSD?**

- Greedy decoding throws away the token distribution of the next token after prefill
  - AASD saves that distribution and uses it to blend with the draft's logits at each step
    - P_aligned_draft = (1 − λ) * P_draft + λ * P_target_prefill
  - **Effect**: the draft is biased toward tokens the target would likely accept → better alignment between draft and target → fewer rejections

- **SSD adds safety**: match ratio, Intersection/Union, composite distribution, Perplexity gate..

*Jikai Wang, Zhenxu Tian, Juntao Li, Qingrong Xia, Xinyu Duan, Zhefeng Wang, Baoxing Huai, and Min Zhang. 2025. Alignment-Augmented Speculative Decoding with Alignment Sampling and Conditional Verification. In Proceedings of EMNLP 2025, pages 6751–6763.*

# Alignment Augmented Safety Aware Speculative Decoding




**Algorithm 1** AASD

**Input:** Prompt $q$, LM $M$, $\alpha, \beta$, length of n-grams $n$, Maximum length of the key $l$.
**Output:** Prediction $A_q$

```
pool ← {}
for k = 1 to l do
    for i = 0 to len(q) − k do
        key ← q[i : i + k]
        pool[key].append(i + k)
    end for
end for                    ▷ Initialize the draft pool.
while ⟨eos⟩ not in q do
    T ← {q[−1]}
    for k = l to 1 do
        if q[−k :] ∈ pool then
            T ← T + Sample(q[pool[q[−k :]]])
            ▷ Conduct alignment sampling.
            break
        end if
    end for
    P ← M(T)
    y ← Verify(P, T, α, β)
    q ← q + y
    for k = 1 to l do
        for i = −k − len(y) to −k do
            key ← q[i : i + k]
            pool[key].append(i + k)
        end for
    end for                ▷ Update the draft pool.
end while
A_q ← q
```

*Jikai Wang, Zhenxu Tian, Juntao Li, Qingrong Xia, Xinyu Duan, Zhefeng Wang, Baoxing Huai, and Min Zhang. 2025. Alignment-Augmented Speculative Decoding with Alignment Sampling and Conditional Verification. In Proceedings of EMNLP 2025, pages 6751–6763.*

# Composite Risk Score

- Instead of using simple match ratio

$$r_t = w_1 (1 - \text{match}_t) + w_2 \widetilde{\text{KL}}_t + w_3 \widetilde{\Delta H}_t + w_4 \, \text{refusal_mass}_t$$

**Term definitions:**

| Weight | Term | Definition |
|---|---|---|
| $w_1$ | Match mismatch | $\text{match}_t = \mathbf{1}[\hat{x}_t = \arg\max_x p_{\text{draft}}(x)]$ |
| $w_2$ | KL divergence | $\widetilde{\text{KL}}_t = 1 - e^{-\max(0, \text{KL}(p_{\text{draft}} \,\|\, p_{\text{target}}))/\sigma}$ |
| $w_3$ | Entropy gap | $\widetilde{\Delta H}_t = \max\left(0, \dfrac{H(p_{\text{target}}) - H(p_{\text{draft}})}{\log V}\right)$ |
| $w_4$ | Refusal mass | $\text{refusal_mass}_t = \sum_{v \in \mathcal{R}} p_{\text{draft}}(v)$ |

Mode switching (per-step, no bin lag):

$$\text{mode}_t = \begin{cases} \text{Union} & \text{if } \bar{r}_t > \theta \\ \text{Intersection} & \text{if } \bar{r}_t \leq \theta \end{cases}$$

- **Intersection mode**: sample from $\mathcal{S}_t = \text{top-}c(p_{\text{draft}}) \cap \text{top-}c(p_{\text{target}})$ — restricts to tokens both models agree on (safer)
- **Union mode**: sample from $\mathcal{U}_t = \text{top-}c(p_{\text{draft}}) \cup \text{top-}c(p_{\text{target}})$ — allows safety-expert tokens through even if target disagrees (more robust)

# Steering Draft Model to be safer

- Use target features to steer the draft responses to be more safer
- **Key Intuition** : **Linear Representation Hypothesis**
- h_target encodes harmful information
  1. Extract target model hidden features : h_target
  2. Project to draft hidden dim: h_proj = W · h_target
  3. Inject into draft MLP (scaled by risk score)
     a. **h_draft ← h_draft - α · r̄_t · h_proj**
     b. **α is the crs score (last slide)**
- For harmful prompts -> **α** high-> steer away from harmful representations
- For benign prompts -> **α** low-> steer away from harmful representations




Berdoz, Rheinboldt, Wattenhofer (2025) 'Steering Pretrained Drafters during Speculative Decoding', AAAI 2026 • arXiv:2511.09844

# Setup

UC San Diego

- **Custom Eval Dataset:** (100 examples in total)
  - Harmful - DeepInception,JailbreakBench)
  - Benign : XSTest - 30
- Target Model : Qwen/Qwen2.5-7B-Instruct (acts as helpful assistant)
- Draft Model : Qwen/Qwen2.5-1.5B-Instruct - acts as safety expert (strong safety system prompt)
- Guard model to evaluate output response : Qwen/Qwen3Guard-Gen-0.6B
- max_new_tokens = 256

**Hardware** :

- 2× NVIDIA RTX 4000 Ada (20GB each), fp16
- W_proj training (steering): ~10 min on refusal sequences
- All other phases: inference only, no gradient computation
- Evaluation: Qwen3Guard-Gen-0.6B in 4-bit quantization

**SSD hyperparameters**

- Lookahead window T = 3 tokens
- Sample space C = 10 (top-k for intersection/union sets)
- Bin size b = 7 tokens (for match-ratio switching)
- Match-ratio threshold $\beta_0$ = 0.6, decay = 0.1
- PPL gate threshold = 150

**CRS hyperparameters:**

Weights:

- $w_1$=0.3 (match)
- $w_2$=0.3 (KL),
- $w_3$=0.1 ($\Delta$H),
- $w_4$=0.3 (refusal mass)

Smoothing window W = 3, threshold $\theta$ = 0.2

# Results




| Method | ASR | Refusal | Over Refusal |
|---|---|---|---|
| Vanilla | 34.3 | 64.3 | 0 |
| SSD | 28.6 | 70.0 | 0 |
| **SSD-CRS** | **24.3** | **74.3** | 3.3 |
| SSD-Steering-CRS | 25.7 | 72.9 | 3.3 |
| SSD-Steering | 30.0 | 68.6 | 0 |
| SSD-AASD | 30.7 | 67.3 | 0 |

| Method | ASR | Refusal | OverRefusal |
|---|---|---|---|
| Vanilla | 68.6 | 31.4 | 0 |
| SSD | 40.0 | 58.6 | 0 |
| SSD-CRS | 32.9 | 65.7 | 3.3 |
| SSD-Steering | 35.7 | 61.4 | 3.3 |
| SSD-Steering-CRS | 38.6 | 58.6 | 0 |
| SSD-AASD | 30.7 | 67.3 | 0 |

# Conclusion

- CRS per-step switching outperforms bin-level match ratio improving ASR by 8%
- Steering is not complementary to SSD injecting target hidden states into the draft (in either direction) degrades or does not improve safety. Further experiments required
- The draft model's role is critical - the 1.5B safety expert acts as a meaningful distributional signal and work across wide range of target models

# Future Works

- Integrate AASD with the best performing SSD + CRS model
- Test on base models without instruction tuning to highlight performance across
- Learned CRS weights. Replace fixed weights tuned on a small calibration set
- Latency analysis - CRS adds per-step KL and entropy computation; measure wall-clock overhead vs the vanilla SSD bin approach
- Cross-family models - draft and target from different model families (e.g. Llama draft, Qwen target) to test whether the projection-free setup still holds

UC San Diego

# Thank you!