

1060 | Machine Learning HW4
Hsueh Lin Huang
hsuehlinh

1. Support Vector Machines

1.1 Feature Maps

1. No, because we can't use one line to separate blue and red points.
Therefore, it's not linear separable.

2. Yes, $x_2 - 2.5 \geq 0$, the corresponding margin is 1.5.

3. $K(x, z) = xz + x^2z^2$

1.2 Constructing Kernels

1. $K(x, z) = c_1 k_1(x, z) + c_2 k_2(x, z)$ with $c_1, c_2 \geq 0$

$$\phi(x) = (\sqrt{c_1} \phi_1(x), \sqrt{c_2} \phi_2(x))$$

$$\phi(x) \cdot \phi(z) = c_1 \underbrace{\phi_1(x) \cdot \phi_1(z)}_{k_1(x, z)} + c_2 \underbrace{\phi_2(x) \cdot \phi_2(z)}_{k_2(x, z)}$$

2. $K(x, z) = k_1(x, z) \cdot k_2(x, z)$

$$\phi(x) = (\phi_{1,\bar{i}}(x) \phi_{2,\bar{j}}(x))_{\bar{i} \in \{1, \dots, n\}, \bar{j} \in \{1, \dots, m\}}$$

$$\phi(x) \cdot \phi(z) = \sum_{\bar{i}, \bar{j}} \phi_{1,\bar{i}}(x) \phi_{2,\bar{j}}(x) \phi_{1,\bar{i}}(z) \phi_{2,\bar{j}}(z)$$

$$= \sum_{\bar{i}} \phi_{1,\bar{i}}(x) \phi_{1,\bar{i}}(z) \left(\sum_{\bar{j}} \phi_{2,\bar{j}}(x) \phi_{2,\bar{j}}(z) \right)$$

$$= \sum_{\bar{i}} \phi_{1,\bar{i}}(x) \phi_{1,\bar{i}}(z) k_2(x, z) = k_1(x, z) k_2(x, z)$$

3. $q(t) = \sum_{\bar{\lambda}} C_{\bar{\lambda}} t^{\bar{\lambda}}$, prove $K(x, z) = q(k_1(x, z))$

$$\sum_{\bar{\lambda}} C_{\bar{\lambda}} k_1(x, z)^{\bar{\lambda}} = C_0 \underline{k_1(x, z)^0} + C_1 \underline{k_1(x, z)^1} + \dots + C_p \underline{k_1(x, z)^p}$$

Use $K(x, z) = k_1(x, z) k_2(x, z)$, we get =

$$\sum_{\bar{\lambda}} C_{\bar{\lambda}} k_1(x, z)^{\bar{\lambda}} = C_0 k^{(0)}(x, z) + C_1 k^{(1)}(x, z) + \dots + C_p k^{(p)}(x, z)$$

Then use $K(x, z) = C_1 k_1(x, z) + C_2 k_2(x, z)$, we get =

$$K(x, z) = q(k_1(x, z)) = \sum_{\bar{\lambda}} C_{\bar{\lambda}} k^{(\bar{\lambda})}(x, z) = \sum_{\bar{\lambda}} C_{\bar{\lambda}} k_1(x, z)^{\bar{\lambda}} \neq$$

4.

$$K(x, z) = \exp(k_1(x, z))$$

$$\text{Since: } \exp(x) = \lim_{\bar{\lambda} \rightarrow \infty} \left(1 + x + \dots + \frac{x^{\bar{\lambda}}}{\bar{\lambda}!} \right)$$

From the fact that $K(x, z) = f(k_1(x, z))$,

$$K(x, z) = \lim_{\bar{\lambda} \rightarrow \infty} k_{\bar{\lambda}}(x, z)$$

5.

$$K(x, z) = x^T A z$$

1.3 Support Vectors

$$1. \sum_i \ell(w, x, y) = \max(0, 1 - y(w \cdot x))$$

2.

C controls the relative weighting between the twin goals of making the $\|w\|^2$ small (margin is large) and ensuring that most examples have functional margin ≥ 1

If $C \rightarrow 0$, r will be very large

$C \rightarrow \infty$, r will be very small

3.

$$\text{Classifier} = f(x) = \sum_i \alpha_i y_i \phi(x_i) \phi(x) + b$$

$$\Rightarrow f(x) = \sum_i \alpha_i y_i K(x_i, x) + b$$


$$\text{Learning} \quad \max_{\alpha_i \geq 0} \sum \alpha_i - \frac{1}{2} \sum_{i,j} \alpha_i \alpha_j y_i y_j \phi(x_i)^T \phi(x_j)$$

$$\Rightarrow \max_{\alpha_i \geq 0} \sum \alpha_i - \frac{1}{2} \sum_{i,j} \alpha_i \alpha_j y_i y_j K(x_i, x_j)$$


2. Feed-forward Neural Networks

1. Yes

$$y = (w_1 w_5 + w_3 w_6) x_1 + (w_2 w_5 + w_4 w_6) x_2 + w_0$$



2.



for (1,1)

$$(w_1 + w_2)w_5 + (w_3 + w_4)w_6 + w_0 = 1 \quad (1)$$

for (-1,1)

$$(-w_1 + w_2)w_5 + (-w_3 + w_4)w_6 + w_0 = -1 \quad (2)$$

for (-1,-1)

$$(-w_1 - w_2)w_5 + (-w_3 - w_4)w_6 + w_0 = 1 \quad (3)$$


for (1,-1)

$$(w_1 - w_2)w_5 + (w_3 - w_4)w_6 + w_0 = -1 \quad (4)$$

From (1),(3), we conclude that $w_0 = 1$
 (2),(4) we conclude that $w_0 = -1$] conflicts!

3.

Using sigmoid function, we can solve XOR problem.




3. Ada Boost

1.

x	0
0	x

the minimum error rate is 0.5


2,



$$h_1(x) = \begin{cases} 1 & \text{if } x_1 \leq 1 \\ -1 & \text{otherwise} \end{cases}$$

$$\text{error rate} = \frac{2}{9}$$

3,



$$\textcircled{1} x_1 < 1, x_2 > 2 \Rightarrow h_1 = -1, h_2 = 1, h_3 = 1, h_4 = -1$$

$$\textcircled{2} x_1 > 1, x_2 > 2 \Rightarrow h_1 = 1, h_2 = 1, h_3 = 1, h_4 = -1$$

$$\textcircled{3} x_1 > 2, x_2 > 2 \Rightarrow h_1 = 1, h_2 = -1, h_3 = 1, h_4 = -1$$

$$\textcircled{4} x_1 < 1, 1 \leq x_2 \leq 2 \Rightarrow h_1 = -1, h_2 = 1, h_3 = 1, h_4 = 1$$

$$\textcircled{5} 1 \leq x_1 \leq 2, 1 \leq x_2 \leq 2 \Rightarrow h_1 = 1, h_2 = 1, h_3 = 1, h_4 = 1$$

$$\textcircled{6} x_1 > 2, 1 \leq x_2 \leq 2 \Rightarrow h_1 = 1, h_2 = -1, h_3 = 1, h_4 = 1$$

$$\textcircled{7} x_1 < 1, x_2 < 1 \Rightarrow h_1 = -1, h_2 = 1, h_3 = -1, h_4 = 1$$

$$\textcircled{8} 1 \leq x_1 \leq 2, x_2 < 1 \Rightarrow h_1 = 1, h_2 = 1, h_3 = -1, h_4 = 1$$

$$\textcircled{9} x_1 > 2, x_2 < 1 \Rightarrow h_1 = 1, h_2 = -1, h_3 = -1, h_4 = 1$$

$$\text{for } \textcircled{1} y_{\bar{a}} f(x_{\bar{a}}) = -1 \cdot \frac{1}{9} (0-3) = \frac{3}{9}$$

$$\textcircled{2} y_{\bar{a}} f(x_{\bar{a}}) = -1 \cdot \frac{1}{9} (2-3) = \frac{1}{9}$$

$$\textcircled{3} y_{\bar{a}} f(x_{\bar{a}}) = -1 \cdot \frac{1}{9} (0-3) = \frac{3}{9}$$

$$\textcircled{4} y_{\bar{a}} f(x_{\bar{a}}) = -1 \cdot \frac{1}{9} (2-3) = \frac{1}{9}$$

$$\textcircled{5} y_{\bar{a}} f(x_{\bar{a}}) = -1 \cdot \frac{1}{9} (4-3) = \frac{1}{9}$$

$$\textcircled{6} y_{\bar{a}} f(x_{\bar{a}}) = -1 \cdot \frac{1}{9} (2-3) = \frac{1}{9}$$

$$\textcircled{7} y_{\bar{a}} f(x_{\bar{a}}) = -1 \cdot \frac{1}{9} (0-3) = \frac{3}{9}$$

$$\textcircled{8} y_{\bar{a}} f(x_{\bar{a}}) = -1 \cdot \frac{1}{9} (2-3) = \frac{1}{9}$$

$$\textcircled{9} y_{\bar{a}} f(x_{\bar{a}}) = -1 \cdot \frac{1}{9} (0-3) = \frac{3}{9}$$

$$\Rightarrow y_{\bar{a}} f(x_{\bar{a}}) > \frac{1}{9}$$

3.2 Complexity and Overfitting

1. 4 params — dimension, threshold, direction, weight
2. $5 \times T$ params.
3. No. because the testing error doesn't increase.

3.3 Margin

$$1. \text{Margin}_k(x) = \sum_{t=y=h_t(x)} a_t - \sum_{t=y \neq h_t(x)} a_t = y \cdot \sum a_t h_t(x) = y \cdot f_k(x)$$


$$\text{if } y = h_t(x) \Rightarrow y \cdot h_t(x) = 1$$

$$y \neq h_t(x) \Rightarrow y \cdot h_t(x) = -1$$


2.

3.5.1 Report Questions





1. the highest weighted error rate: [h12, error rate = 0.0010]



2. & 3.
- T = 20



4.



5.

