

# **Running a CEPH-Cluster on a containerized infrastructure**

**Use case: distributed mySQL-database**

Julius Neudecker  
Bachelor of Science  
julius.neudecker@haw-hamburg.de

January 2020

## Contents

<b>1</b>	<b>Introduction</b>	<b>4</b>
1.1	CEPH Based storage cluster . . . . .	4
1.2	Provisioning . . . . .	4
1.3	Containerization . . . . .	4
1.4	Databases . . . . .	4
1.5	Scope of the problem . . . . .	4
<b>2</b>	<b>Setting up CEPH on Docker</b>	<b>4</b>
2.1	System Architecture . . . . .	4
2.2	Monitor Nodes . . . . .	4
2.3	Object Storage Devices - OSD . . . . .	4
<b>3</b>	<b>Setting up the database</b>	<b>4</b>
3.1	Structure of mySQL . . . . .	4
3.2	ACID . . . . .	4
3.3	Problems with clusters . . . . .	4
<b>4</b>	<b>Performance</b>	<b>4</b>
4.1	disclamer bc of my setup . . . . .	4
4.2	Integrity . . . . .	4
4.3	Penalty . . . . .	4
4.4	Administration . . . . .	4
<b>5</b>	<b>Conclusion</b>	<b>4</b>

Setting up and operate a storage cluster with high availability is a complex task. Modern paradigmas like containerization and orchestration are a way of abstracting away some complexity. However, running a cluster in a stateless and ephemeral containerized environment poses some problems. In the following paper these problems are identified and scrutinized. The use case will be a mySQL database, which will be stored on a CEPH cluster comprised of docker based daemons.

# **1 Introduction**

## **1.1 CEPH Based storage cluster**

## **1.2 Provisioning**

## **1.3 Containerization**

## **1.4 Databases**

## **1.5 Scope of the problem**

# **2 Setting up CEPH on Docker**

## **2.1 System Architecture**

## **2.2 Monitor Nodes**

## **2.3 Object Storage Devices - OSD**

# **3 Setting up the database**

## **3.1 Structure of mySQL**

## **3.2 ACID**

## **3.3 Problems with clusters**

# **4 Performance**

## **4.1 disclaimer bc of my setup**

## **4.2 Integrity**

## **4.3 Penalty**

## **4.4 Administration**

# **5 Conclusion**