

```
create database anudip_java;
```

```
use anudip_java;
```

```
create table dmart(  
    id int primary key,  
    name varchar(25),  
    code varchar(25) unique  
);
```

```
create table dmart_customer(  
    id int primary key,  
    c_name varchar(25),  
    purchases varchar(25)  
);
```

```
create table dmart_fruits(  
    id int primary key,  
    fruit_name varchar(25),  
    fruit_code varchar(25),  
    foreign key(fruit_code)  
    references dmart(code)  
);
```

```
create table dmart_dress(  
    id int primary key,  
    dress_name varchar(25),  
    dress_code varchar(25),  
    foreign key(dress_code)  
    references dmart(code)  
);
```

```
create table dmart_sports(  
    id int primary key,  
    sport_kit_name varchar(25),  
    sport_kit_code varchar(25),  
    foreign key (sport_kit_code)  
    references dmart(code)  
);
```

```
insert into dmart(id, name, code)  
values(1,'customer', 'C101'),  
(2,'fruits','F101'),  
(3,'dress','D101'),  
(4,'sports','S101');
```

```
INSERT INTO dmart(id, name, code)  
VALUES  
(5, 'fruits', 'F102'),  
(6, 'fruits', 'F103'),  
(7, 'dress', 'D102'),  
(8, 'dress', 'D103'),  
(9, 'sports', 'S102'),  
(10,'sport','S103');
```

```
insert into dmart_customer(id, c_name, purchases)  
values(1, 'vignesh','C101'),  
(2, 'Santhosh','C102'),  
(3, 'Pugal','C103'),  
(4, 'Sharvesh','D101'),  
(5, 'Virat','D102'),  
(6, 'Rohit','D103'),
```

```
(7, 'Kohli','F101'),  
(8, 'sharma','F102'),  
(9, 'Tilak','F103'),  
(10, 'Doni','S101');
```

```
select * from dmart_customer;  
select * from dmart_fruits;  
select * from dmart_dress;  
select * from dmart_sports;
```

```
desc dmart_fruits;  
desc dmart_dress;  
desc dmart_sports;
```

```
insert into dmart_fruits(id, fruit_name, fruit_code)  
values(1,'Apple','F101'),  
(2,'Orange','F102'),  
(3,'Grapes','F103');
```

```
insert into dmart_dress(id, dress_name, dress_code)  
values(2,'Pant','D102'),  
(3,'Belt','D103');  
insert into dmart_dress(id, dress_name, dress_code)  
values(1,'Shirt','D101');
```

```
insert into dmart_sports(id, sport_kit_name, sport_kit_code)  
values(1,'Cricket Bat','S101'),  
(2,'FootBall','S102'),  
(3,'Riding Kit','S103');
```

Select * from dmart;

SELECT

c.c_name,
c.purchases,
f.fruit_name,
d.dress_name,
s.sport_kit_name

FROM dmart_customer c

LEFT JOIN dmart_fruits f

ON c.purchases = f.fruit_code

LEFT JOIN dmart_dress d

ON c.purchases = d.dress_code

LEFT JOIN dmart_sports s

ON c.purchases = s.sport_kit_code;

The screenshot displays the MySQL Workbench interface. The SQL Editor window contains the following query:

```
92 (*, 'Riding Kit', '5093');  
93  
94 * Select * from dmart;  
95  
96 * SELECT  
97 c.c_name,  
98 c.purchases,  
99 f.fruit_name,  
100 d.dress_name,  
101 s.sport_kit_name  
102 FROM dmart_customer c  
103 LEFT JOIN dmart_fruits f  
104 ON c.purchases = f.fruit_code  
105 LEFT JOIN dmart_dress d  
106 ON c.purchases = d.dress_code  
107 LEFT JOIN dmart_sports s  
108 ON c.purchases = s.sport_kit_code;  
109
```

The Results window shows the output of the query, which includes columns: c_name, purchases, fruit_name, dress_name, and sport_kit_name. The data is as follows:

c_name	purchases	fruit_name	dress_name	sport_kit_name
vignesh	S102			Football
Sandesh	S103			Riding Kit
Papal	F103	Grapes		
Shanesh	D101		Shirt	
Wrat	D102		Pant	
Rahit	D103		Bel	
Kahil	F101	Apple		
ghana	F102	Orange		
Thak	D103	Grapes		
Dani	S101			Cricket Bat

The Output window shows the execution log:

```
1 11:53:17 use andup_java  
2 11:53:26 SELECT c.c_name, c.purchases, f.fruit_name, d.dress_name, s.sport_kit_name FROM dmart_customer c LEFT JOIN dmart_fruits f ... 10 row(s) returned  
0.016 sec / 0.000 sec
```