



## Main

|  |   |
|--|---|
| Range                                  | TeSys   |
| Product name                           | TeSys D   |
| Product or component type              | Contactor   |
| Device short name                      | LC1D  |
| Contactor application                  | Motor control<br>Resistive load   |
| Utilisation category                   | AC-1<br>AC-4<br>AC-3  |
| Poles description                      | 3P  |
| Power pole contact composition         | 3 NO  |
| [Ue] rated operational voltage         | Power circuit: $\leq 300$ V DC 25...400 Hz<br>Power circuit: $\leq 690$ V AC  |
| [Ie] rated operational current         | 125 A (at $\leq 60$ °C) at $\leq 440$ V AC AC-1 for power circuit<br>80 A (at $\leq 60$ °C) at $\leq 440$ V AC AC-3 for power circuit   |
| Motor power kW                         | 22 kW at 220...230 V AC 50/60 Hz (AC-3)<br>37 kW at 380...400 V AC 50/60 Hz (AC-3)<br>45 kW at 415...440 V AC 50/60 Hz (AC-3)<br>55 kW at 500 V AC 50/60 Hz (AC-3)<br>45 kW at 660...690 V AC 50/60 Hz (AC-3)<br>45 kW at 1000 V AC 50/60 Hz (AC-3)<br>15 kW at 400 V AC 50/60 Hz (AC-4)                                    |
| Motor power HP (UL / CSA)              | 20 hp at 200/208 V AC 50/60 Hz for 3 phases motors<br>7.5 hp at 115 V AC 50/60 Hz for 1 phase motors<br>15 hp at 230/240 V AC 50/60 Hz for 1 phase motors<br>25 hp at 230/240 V AC 50/60 Hz for 3 phases motors<br>60 hp at 460/480 V AC 50/60 Hz for 3 phases motors<br>60 hp at 575/600 V AC 50/60 Hz for 3 phases motors |
| Control circuit type                   | AC at 50 Hz   |
| [Uc] control circuit voltage           | 690 V AC 50 Hz  |
| Auxiliary contact composition          | 1 NO + 1 NC   |
| [Uimp] rated impulse withstand voltage | 8 kV conforming to IEC 60947  |

|   |  |
|---|--|
| Overvoltage category                        | III  |
| [Ith] conventional free air thermal current | 10 A (at 60 °C) for signalling circuit<br>125 A (at 60 °C) for power circuit   |
| Irms rated making capacity                  | 140 A AC for signalling circuit conforming to IEC 60947-5-1<br>250 A DC for signalling circuit conforming to IEC 60947-5-1<br>1100 A at 440 V for power circuit conforming to IEC 60947  |
| Rated breaking capacity                     | 1100 A at 440 V for power circuit conforming to IEC 60947  |
| [Icw] rated short-time withstand current    | 640 A 40 °C - 10 s for power circuit<br>990 A 40 °C - 1 s for power circuit<br>135 A 40 °C - 10 min for power circuit<br>320 A 40 °C - 1 min for power circuit<br>100 A - 1 s for signalling circuit<br>120 A - 500 ms for signalling circuit<br>140 A - 100 ms for signalling circuit   |
| Associated fuse rating                      | 10 A gG for signalling circuit conforming to IEC 60947-5-1<br>200 A gG at ≤ 690 V coordination type 1 for power circuit<br>160 A gG at ≤ 690 V coordination type 2 for power circuit   |
| Average impedance                           | 0.8 mOhm - Ith 125 A 50 Hz for power circuit   |
| [Ui] rated insulation voltage               | Power circuit: 600 V CSA certified<br>Power circuit: 600 V UL certified<br>Power circuit: 1000 V conforming to IEC 60947-4-1<br>Signalling circuit: 690 V conforming to IEC 60947-1<br>Signalling circuit: 600 V CSA certified<br>Signalling circuit: 600 V UL certified   |
| Electrical durability                       | 0.8 Mcycles 125 A AC-1 at Ue ≤ 440 V<br>1.5 Mcycles 80 A AC-3 at Ue ≤ 440 V  |
| Power dissipation per pole                  | 5.1 W AC-3<br>12.5 W AC-1  |
| Safety cover                                | With   |
| Mounting support                            | Rail<br>Plate  |
| Standards                                   | CSA C22.2 No 14<br>EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 508  |
| Product certifications                      | UL<br>LROS (Lloyds register of shipping)<br>DNV<br>GL<br>GOST<br>CSA<br>RINA<br>BV<br>CCC  |
| Connections - terminals                     | Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> flexible with cable end<br>Control circuit: screw clamp terminals 1 cable(s) 1...2.5 mm <sup>2</sup> flexible with cable end<br>Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> flexible without cable end<br>Control circuit: screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> flexible without cable end<br>Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> solid without cable end<br>Control circuit: screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> solid without cable end<br>Power circuit: connector 1 cable(s) 4...50 mm <sup>2</sup> flexible without cable end<br>Power circuit: connector 2 cable(s) 4...25 mm <sup>2</sup> flexible without cable end<br>Power circuit: connector 1 cable(s) 4...50 mm <sup>2</sup> flexible with cable end<br>Power circuit: connector 2 cable(s) 4...16 mm <sup>2</sup> flexible with cable end<br>Power circuit: connector 1 cable(s) 4...50 mm <sup>2</sup> solid without cable end<br>Power circuit: connector 2 cable(s) 4...25 mm <sup>2</sup> solid without cable end |
| Tightening torque                           | Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm<br>Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2<br>Power circuit: 9 N.m - on connector - with screwdriver flat Ø 6 to Ø 8 mm<br>Power circuit: 9 N.m - on connector hexagonal screw head 4 mm  |
| Operating time                              | 20...35 ms closing<br>6...20 ms opening  |
| Safety reliability level                    | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 2000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  |
| Mechanical durability                       | 10 Mcycles   |

|                        |                  |
|------------------------|------------------|
| Maximum operating rate | 3600 cyc/h 60 °C |
|------------------------|------------------|

## Complementary

|                                 |  |
|---------------------------------|--|
| Coil technology                 | Without built-in suppressor module   |
| Control circuit voltage limits  | Drop-out: 0.3...0.6 Uc AC 50 Hz (at 55 °C)<br>Operational: 0.85...1.1 Uc AC 50 Hz (at 55 °C)                             |
| Inrush power in VA              | 200 VA 50 Hz cos phi 0.75 (at 20 °C)   |
| Hold-in power consumption in VA | 20 VA 50 Hz cos phi 0.3 (at 20 °C)   |
| Heat dissipation                | 6...10 W at 50 Hz  |
| Auxiliary contacts type         | type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1<br>type mirror contact 1 NC conforming to IEC 60947-4-1 |
| Signalling circuit frequency    | 25...400 Hz  |
| Minimum switching current       | 5 mA for signalling circuit  |
| Minimum switching voltage       | 17 V for signalling circuit  |
| Non-overlap time                | 1.5 ms on de-energisation between NC and NO contact<br>1.5 ms on energisation between NC and NO contact                  |
| Insulation resistance           | > 10 MOhm for signalling circuit   |

## Environment

|   |   |
|---|---|
| IP degree of protection                               | IP20 front face conforming to IEC 60529   |
| Protective treatment                                  | TH conforming to IEC 60068-2-30   |
| Pollution degree                                      | 3   |
| Ambient air temperature for operation                 | -5...60 °C  |
| Ambient air temperature for storage                   | -60...80 °C   |
| Permissible ambient air temperature around the device | -40...70 °C at Uc   |
| Operating altitude                                    | 3000 m without  |
| Fire resistance                                       | 850 °C conforming to IEC 60695-2-1  |
| Flame retardance                                      | V1 conforming to UL 94  |
| Mechanical robustness                                 | Vibrations contactor open: 2 Gn, 5...300 Hz<br>Shocks contactor open: 8 Gn for 11 ms<br>Vibrations contactor closed: 3 Gn, 5...300 Hz<br>Shocks contactor closed: 10 Gn for 11 ms |
| Height  | 127 mm  |
| Width   | 85 mm   |
| Depth   | 130 mm  |
| Net weight  | 1.59 kg   |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|