**The first player's folder (read-only, 1.0 GB)**

Its memory, its 51-file library, 68 program files, git history, every program and event, its conversation, the server log, camera frames and the first paper. A generated INDEX.md lists it all.

searched 19 times during the run

**Two manifests (2,018 words)**

Infrastructure: a sealed base with four walls, floor, ceiling and torch; 10 mined obsidian and flint and steel before every Nether entry. Planning: when to plan, target times, what to avoid, budgets for each planning pass.

reread at all 7 compactions

**The objective and one request**

The first run's objective, plus: this is a speedrun, with both earlier times. Before your first program, measure where the previous player lost time and lives, and plan with targets. After a miss or a death, change the tool.

**The loop it kept**

After a death or a miss:
- find the cause, change the tool, one line in the lessons, commit.

After a finished step:
- actual against target, rescale later targets, rewrite the plan.

After a compaction:
- reread both manifests.

**One Claude Opus 5.5 agent, xhigh**

The same harness as the first run.
7 min 52 s of reading and measuring before its first program, while the world was already running.

**Its own workspace**

memory/: 00-plan (under 1,800 characters, rewritten as it went), 01-targets, 02-lessons (112 lines), 03-world.
lib/: 52 files, 81% of the lines identical to the first player's. 27 commits to the win.

writes

text back

**780 programs**

JavaScript, a median of 5.9 s each.

**A Mineflayer bot**

The same library, no helpers added.

**A Minecraft server**

Java 1.20.4, survival on Easy, a new random seed that the agent never saw.