


Multilayer Ceramic Chip Capacitors



GENERAL SPECIFICATIONS

NOTE: Electrical characteristics at + 25 °C unless otherwise specified

Capacitance Range: 1.0 pF to 0.056 μ F

Temperature Coefficient of Capacitance (TCC):

0 \pm 30 ppm/°C from - 55 °C to + 125 °C

Dissipation Factor (DF):

0.1 % maximum at 1.0 Vrms and 1 kHz for values > 1000 pF

0.1 % maximum at 1.0 Vrms and 1 MHz for values \leq 1000 pF

FEATURES

- C0G is an ultra-stable dielectric offering a Temperature Coefficient of Capacitance (TCC) of 0 \pm 30 ppm/°C
- Low Dissipation Factor (DF)
- Ideal for critical timing and tuning applications
- Ideal for snubber and surge suppression applications



RoHS
COMPLIANT

Insulation Resistance (IR):

At + 25 °C and rated voltage 100 000 M Ω minimum or 1000 Ω F, whichever is less

At + 125 °C and rated voltage 10 000 M Ω minimum or 100 Ω F, whichever is less

Dielectric Withstanding Voltage (DWV):

This is the maximum voltage the capacitors are tested for a 1 to 5 second period and the charge/discharge current does not exceed 50 mA

\leq 200 Vdc : DWV at 250 % of rated voltage

500 Vdc: DWV at 200 % of rated voltage

630/1000 Vdc: DWV at 150 % of rated voltage

3000 Vdc: DWV at 120 % of rated voltage

ORDERING INFORMATION

VJ0805 ³⁾	A	102	K	X	A	A	T	### ²⁾
CASE CODE	DIELECTRIC	CAPACITANCE NOMINAL CODE	CAPACITANCE TOLERANCE	TERMINATION	DC VOLTAGE RATING ¹⁾	MARKING	PACKAGING	PROCESS CODE
0402 0603 0805 1206 1210 1808 1812 1825 2220 2225	A = C0G (NP0)	Expressed in picofarads (pF). The first two digits are significant, the third is a multiplier. An "R" indicates a decimal point. Examples: 102 = 1000 pF 1R8 = 1.8 pF	B = \pm 0.10 pF C = \pm 0.25 pF D = \pm 0.5 pF F = \pm 1 % G = \pm 2 % J = \pm 5 % K = \pm 10 % NOTE: B, C, D < 10 pF F, G, J, K \geq 10 pF	X = Ni barrier 100 % tin plated F = AgPd	X = 25 V A = 50 V B = 100 V C = 200 V E = 500 V L = 630 V G = 1000 V H = 3000 V	A = Unmarked M = Marked NOTE: Marking is only available for 0805 and 1206	T = 7" reel/plastic tape C = 7" reel/paper tape R = 11 1/4" reel/plastic tape P = 11 1/4" reel/paper tape O = 7" reel/flamed paper tape I = 11 1/4"/13" reel/flamed paper tape NOTE: "I" and "O" is used for "F" termination paper taped	

Note

1. DC voltage rating should not be exceeded in application

2. Process Code may be added with up to three digits, used to control non-standard products and/or special requirements

3. Case size designator may be replaced by a four digit drawing number used to control non-standard products and/or requirements

C0G (NP0) DIELECTRIC																					
STYLE		VJ0402			VJ0603			VJ0805				VJ1206					VJ1210 ¹⁾				
EIA TYPE		0402			0603			0805				1206					1210				
VOLTAGE (Vdc)		25	50	100	50	100	200	50	100	200	500	50	100	200	500	630	50	100	200	500	630
CAP. CODE	CAP.																				
1R0	1.0 pF					
1R2	1.2 pF					
1R5	1.5 pF					
1R8	1.8 pF					
2R2	2.2 pF					
2R7	2.7 pF					
3R3	3.3 pF					
3R9	3.9 pF					
4R7	4.7 pF					
5R6	5.6 pF					
6R8	6.8 pF					
8R2	8.2 pF					
100	10 pF		
120	12 pF		
150	15 pF		
180	18 pF		
220	22 pF		
270	27 pF		
330	33 pF		
390	39 pF		
470	47 pF		
560	56 pF
680	68 pF
820	82 pF
101	100 pF
121	120 pF
151	150 pF
181	180 pF
221	220 pF
271	270 pF			
331	330 pF			
391	390 pF			
471	470 pF			
561	560 pF			
681	680 pF			
821	820 pF						
102	1000 pF						
122	1200 pF						
152	1500 pF						
182	1800 pF						
222	2200 pF						
272	2700 pF								
332	3300 pF								
392	3900 pF								
472	4700 pF												
562	5600 pF												
682	6800 pF											.					.	.			
822	8200 pF											.					.				
103	0.010 μF											.					.				
123	0.012 μF																.				
153	0.015 μF																				
183	0.018 μF																				
223	0.022 μF																				
273	0.027 μF																				
333	0.033 μF																				
393	0.039 μF																				
473	0.047 μF																				
563	0.056 μF																				

Note

1. See soldering recommendations within this data book, or visit www.vishay.com/doc?45034

.. Available only in paper tape










C0G (NP0) DIELECTRIC																									
STYLE		VJ1808 ¹⁾					VJ1812 ¹⁾						VJ1825 ¹⁾				VJ2220 ¹⁾					VJ2225 ¹⁾			
EIA TYPE		-					1812						1825				-					-			
VOLTAGE (VDC)		50	100	200	500	1000	50	100	200	500	1000	3000	50	100	200	500	50	100	200	500	1000	50	100	200	500
CAP. CODE	CAP.																								
1R0	1.0 pF																								
1R2	1.2 pF																								
1R5	1.5 pF																								
1R8	1.8 pF																								
2R2	2.2 pF																								
2R7	2.7 pF																								
3R3	3.3 pF																								
3R9	3.9 pF																								
4R7	4.7 pF																								
5R6	5.6 pF																								
6R8	6.8 pF																								
8R2	8.2 pF																								
100	10 pF																								
120	12 pF																								
150	15 pF																								
180	18 pF																								
220	22 pF																								
270	27 pF																								
330	33 pF																								
390	39 pF																								
470	47 pF																								
560	56 pF																								
680	68 pF																								
820	82 pF																								
101	100 pF																								
121	120 pF																								
151	150 pF																								
181	180 pF																								
221	220 pF																								
271	270 pF																								
331	330 pF																								
391	390 pF																								
471	470 pF																								
561	560 pF																								
681	680 pF																								
821	820 pF																								
102	1000 pF																								
122	1200 pF																								
152	1500 pF																								
182	1800 pF																								
222	2200 pF																								
272	2700 pF																								
332	3300 pF																								
392	3900 pF																								
472	4700 pF																								
562	5600 pF																								
682	6800 pF																								
822	8200 pF																								
103	0.010 μF																								
123	0.012 μF																								
153	0.015 μF																								
183	0.018 μF																								
223	0.022 μF																								

Note


1. See soldering recommendations within this data book, or visit www.vishay.com/doc?45034

C0G (NP0) DIELECTRIC - TYPICAL PARAMETERS



DIMENSIONS in inches [millimeters]


EIA STYLE	VISHAY VITRAMON STYLE DESIGNATION	LENGTH (L)	WIDTH (W)	MAXIMUM THICKNESS (T)	TERMINATION (P)	
					(Min.)	(Max.)
0402	VJ0402	0.040 ± 0.004 / - 0.002 [1.00 ± 0.10 / - 0.05]	0.020 ± 0.004 / - 0.002 [0.50 ± 0.10 / - 0.05]	0.024 [0.60]	0.004 [0.10]	0.016 [0.41]
0603	VJ0603	0.063 ± 0.005 [1.60 ± 0.12]	0.031 ± 0.005 [0.80 ± 0.12]	0.036 [0.92]	0.012 [0.30]	0.018 [0.46]
-	VJ0612	0.063 ± 0.008 [1.60 ± 0.20]	0.126 ± 0.008 [3.20 ± 0.20]	0.067 [1.68]	0.010 [0.25]	0.018 [0.46]
-	VJ0508	0.049 ± 0.008 [1.25 ± 0.20]	0.079 ± 0.008 [2.00 ± 0.20]	0.042 [1.07]	0.005 [0.13]	0.018 [0.46]
0805	VJ0805	0.079 ± 0.008 [2.00 ± 0.20]	0.049 ± 0.008 [1.25 ± 0.20]	0.057 [1.45]	0.010 [0.25]	0.028 [0.71]
1206	VJ1206	0.126 ± 0.008 [3.20 ± 0.20]	0.063 ± 0.008 [1.60 ± 0.20]	0.067 [1.68]	0.010 [0.25]	0.028 [0.71]
1210	VJ1210	0.126 ± 0.008 [3.20 ± 0.20]	0.098 ± 0.008 [2.50 ± 0.20]	0.067 [1.68]	0.010 [0.25]	0.028 [0.71]
-	VJ1808	0.177 ± 0.010 [4.50 ± 0.25]	0.080 ± 0.010 [2.03 ± 0.25]	0.067 [1.68]	0.010 [0.25]	0.030 [0.76]
1812	VJ1812	0.177 ± 0.010 [4.50 ± 0.25]	0.126 ± 0.008 [3.20 ± 0.20]	0.086 [2.18]	0.010 [0.25]	0.030 [0.76]
1825	VJ1825	0.177 ± 0.010 [4.50 ± 0.25]	0.252 ± 0.010 [6.40 ± 0.25]	0.086 [2.18]	0.010 [0.25]	0.030 [0.76]
-	VJ2220	0.220 ± 0.008 [5.59 ± 0.20]	0.200 ± 0.010 [5.08 ± 0.25]	0.086 [2.18]	0.010 [0.25]	0.030 [0.76]
-	VJ2225	0.220 ± 0.010 [5.59 ± 0.25]	0.250 ± 0.010 [6.35 ± 0.25]	0.086 [2.18]	0.010 [0.25]	0.030 [0.76]
-	VJ3640	0.360 ± 0.015 [9.14 ± 0.38]	0.400 ± 0.015 [10.20 ± 0.38]	0.086 [2.18]	0.010 [0.25]	0.030 [0.76]

**REEL DIMENSIONS** in inches (millimeters)

TAPE SIZE	A MAX.	B MIN.	C	D MIN.	N MIN.	W ₁	W ₂ MAX.	W ₃
8 mm	12.992 (330)	0.059 (1.5)	0.512 + 0.50 - 0.20 (13.0 + 0.50 - 0.20)	0.795 (20.2)	1.969 (50.0)	0.331 + 0.059/- 0.0 (8.4 + 1.5/- 0.0)	0.567 (14.4)	Shall accommodate tape width without interference
12 mm						0.488 + 0.079/- 0.0 (12.4 + 2.0/- 0.0)	0.724 (18.4)	
16 mm					2.401 (61.0)	0.646 + 0.0789/- 0.0 (16.4 + 2.0/- 0.0)	0.882 (22.4)	

Note

- For reels less than 360 mm diameter (A), the most widely used reel diameters are 178 mm ± 2 mm and 330 mm ± 2 mm. Reel diameters ranging from 254 mm to 292 mm also exist. Commonly used hub diameters are 80, 100, 150 and 178 mm.
- Tape with components must wrap around hub without damage.

STANDARD PACKAGING QUANTITIES ^{1/2)}

		7" REEL QUANTITIES		11 1/4" AND 13" REEL QUANTITIES	
BODY SIZE	TAPE SIZE	PAPER TAPE PACKAGING CODE "C"/"O" ⁴⁾	PLASTIC TAPE PACKAGING CODE "T"	PAPER TAPE PACKAGING CODE "P"/"I" ⁴⁾	PLASTIC TAPE PACKAGING CODE "R"
0402 ³⁾	8 mm	5000/10 000	N/A	10 000/30 000	N/A
0603	8 mm	4000	4000	10 000	N/A
0805 ⁴⁾	8 mm	3000	3000	10 000	10 000
1206 ⁵⁾	8 mm	N/A	3000	N/A	10 000
1210 ⁵⁾	8 mm	N/A	3000	N/A	10 000
1808	12 mm	N/A	3000	N/A	10 000
1812	12 mm	N/A	1000	N/A	5000
1825	12 mm	N/A	1000	N/A	4000
2220	12 mm	N/A	1000	N/A	4000
2225	12 mm	N/A	1000	N/A	4000
3640	16 mm	N/A	500	N/A	2000

Note

- REFERENCE: EIA Standard RS 481 – "Taping of Surface Mount Components for Automatic Placement"
- N/A = Not Available, not supported anymore
- Quantity can vary with customer request
- Flamed paper tape code "O" (7" reel) and "I" (11 1/4/13" reel) for AgPd terminated parts (termination code F)
- Packaging "C/P" or "T/R" and quantity can depend from product thickness

EMBOSSED 8, 12 AND 16 MM CARRIER TAPE





Figure 1

CONSTANT CARRIER TAPE METRIC DIMENSIONS in inches (millimeters)							
TAPE SIZE	D ₀	E ₁	P ₀	P ₂	S ₁ MIN.	T MAX.	T ₁
8 mm and 12 mm	0.059 + 0.004/- 0.0 (1.50 + 0.10/- 0.0)	0.069 + 0.004 (1.75 ± 0.10)	0.175 + 0.004 (4.0 ± 0.10)	0.079 + 0.002 (2.0 ± 0.05)	0.024 (0.60)	0.024 (0.60)	0.004 (0.10) Max.

VARIABLE CARRIER TAPE METRIC DIMENSIONS in inches (millimeters)									
TAPE SIZE	B ₁ MAX.	D ₁ MIN.	E ₂ MIN.	F	P ₁	R MIN.	T ₂	W MAX.	A ₀ , B ₀ AND K ₀
8 mm 2 mm Pitch	0.171 (4.35)	0.177 (0.450)	0.246 (6.25)	0.138 ± 0.002 (3.50 ± 0.05)	0.79 ± 0.004 (2.00 ± 0.10)	0.984 (25.0)	0.098 (2.50) Max.	0.327 (8.30)	see note 1
8 mm 4 mm Pitch	0.171 (4.35)	0.177 (0.450)	0.246 (6.25)	0.138 ± 0.002 (3.50 ± 0.05)	0.157 ± 0.004 (4.00 ± 0.10)	0.984 (25.0)	0.098 (2.50) Max.	0.327 (8.30)	see note 1
12 mm 2 mm Pitch	0.323 (8.20)	0.059 (0.150)	0.404 (10.25)	0.217 ± 0.002 (5.50 ± 0.05)	0.157 ± 0.004 (4.00 ± 0.10)	1.181 (30.0)	0.256 (6.50) Max.	0.484 (12.30)	see note 1
16 mm 4 mm Pitch	0.476 (12.1)	0.059 (0.150)	0.561 (14.25)	0.295 ± 0.004 (7.50 ± 0.1)	0.157 ± 0.004 (4.00 ± 0.10)	1.181 (30.0)	0.341 (8.0) Max.	0.641 (16.3)	see note 1

Note

- The cavity defined by A₀, B₀ and K₀ shall surround the component with sufficient clearance that:
 - The component does not protrude above the top surface of the carrier tape.
 - The component can be removed from the cavity in a vertical direction without mechanical restriction, after the cover tape has been removed.
 - Rotation of the component is limited to 20° maximum for 8 and 12 mm tapes and 10° maximum for 16 mm figure 3 & 4.
 - Lateral movement of the component is restricted to 0.5 mm maximum for 8 mm and 12mm wide tape and to 1.0 mm maximum for 16 mm wide tape figure 5.

PAPER 8 MM CARRIER TAPE**CONSTANT CARRIER TAPE METRIC DIMENSIONS** in inches (millimeters)

TAPE SIZE	D ₀	E ₁	P ₀	P ₂	T ₁ MAX.	G MIN.	R REF.
8 mm	0.059 + 0.004/- 0.0 (1.50 + 0.10/- 0.0)	0.069 + 0.004 (1.75 ± 0.10)	0.175 + 0.004 (4.0 ± 0.10)	0.079 + 0.002 (2.0 ± 0.05)	0.024 (0.60)	0.029 (0.75)	0.010 (0.25)

VARIABLE CARRIER TAPE METRIC DIMENSIONS in inches (millimeters)

TAPE SIZE	E ₂ MIN.	F	P ₁	W MAX.	A ₀ , B ₀ AND K ₀	T
8 mm 2 mm Pitch	0.246 (6.25)	0.138 ± 0.002 (3.50 ± 0.05)	0.79 ± 0.004 (2.00 ± 0.10)	0.327 (8.30)	see note 1	1.1 mm maximum for paper base tape
8 mm 4 mm Pitch	0.246 (6.25)	0.138 ± 0.002 (3.50 ± 0.05)	0.157 ± 0.004 (4.00 ± 0.10)	0.327 (8.30)	see note 1	1.1 mm maximum for paper base tape

Note

1. The cavity defined by A₀, B₀ and K₀ shall surround the component with sufficient clearance that:
 - a) The component does not protrude above the top surface of the carrier tape.
 - b) The component can be removed from the cavity in a vertical direction without mechanical restriction, after the cover tape has been removed.
 - c) Rotation of the component is limited to 20° maximum for 8 and 12 mm tapes and 10° maximum for 16 mm figure 3 & 4.
 - d) Lateral movement of the component is restricted to 0.5 mm maximum for 8 mm and 12 mm wide tape and to 1.0 mm maximum for 16 mm wide tape figure 5.

MAXIMUM COMPONENT ROTATION FOR PUNCHED AND EMBOSSED CARRIER

Figure 3 Maximum Lateral Movement Carrier Top View






Figure 4

Maximum Component Rotation Embossed Carrier Side View




Maximum Component Rotation Paper Carrier Side View



MAXIMUM LATERAL MOVEMENT FOR PUNCHED AND EMBOSSED CARRIER

Figure 5 Maximum Component Rotation Top View



BENDING RADIUS FOR PUNCHED EMBOSSED CARRIER




Figure 6

Note 1: The tape with or without components shall pass without damage round "R", see dimensions table



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.