

Gitops-runtime Version 0.27.1 - Published 30 January 2026			
Image	Tag	CVE	Mitigation
cap-app-proxy	93121a2	CVE-2025-25289	Vulnerability nested in package @octokit/rest. It won't affect the service because the package added long time ago and it usage was deleted without cleaning dependencies.
cap-app-proxy	93121a2	CVE-2024-29415	This package is not used inside our business logic to validate the loopback addresses thus we are not affected by this vulnerability.
cap-app-proxy	93121a2	CVE-2024-29409	CVE-2024-29409 describes a file upload vulnerability in NestJS Nest v10.3.2. This flaw allows a remote attacker to achieve remote code execution by manipulating the file upload endpoint. Our services are not impacted by this vulnerability because our applications do not use file upload functionalities. The vulnerability is specifically tied to the file upload endpoint.
cap-app-proxy	93121a2	CVE-2025-13151	CVE-2025-13151 is a high-severity vulnerability in OpenSSL related to the incorrect processing of X.509 certificate extensions, which can lead to a bypass in certificate validation. Our services are not affected by this vulnerability because we utilize a multi-layered security architecture where TLS termination is handled exclusively at the infrastructure level.
cap-app-proxy	93121a2	CVE-2025-14104	CVE-2025-14104 is a sensitive information exposure vulnerability identified within the Python Requests library during the handling of HTTP redirects. The flaw occurs when the library incorrectly handles redirects, potentially leaking sensitive information. Our services are not affected by this vulnerability because it is developed using a non-Python technology stack and does not execute Python code in production. While the vulnerability is present in the library, our application does not rely on the affected functionality.
cap-app-proxy-init	93121a2	CVE-2025-14104	CVE-2025-14104 is a sensitive information exposure vulnerability identified within the Python Requests library during the handling of HTTP redirects. The flaw occurs when the library incorrectly handles redirects, potentially leaking sensitive information. Our service is not affected by this vulnerability because it is developed using a non-Python technology stack and does not execute Python code in production. While the vulnerability is present in the library, our application does not rely on the affected functionality.
gitops-runtime-installer	0.27.1	CVE-2025-13151	CVE-2025-13151 is a high-severity vulnerability in OpenSSL related to the incorrect processing of X.509 certificate extensions, which can lead to a bypass in certificate validation. Our services are not affected by this vulnerability because we utilize a multi-layered security architecture where TLS termination is handled exclusively at the infrastructure level.
gitops-runtime-installer	0.27.1	CVE-2025-14104	CVE-2025-14104 is a sensitive information exposure vulnerability identified within the Python Requests library during the handling of HTTP redirects. The flaw occurs when the library incorrectly handles redirects, potentially leaking sensitive information. Our service is not affected by this vulnerability because it is developed using a non-Python technology stack and does not execute Python code in production. While the vulnerability is present in the library, our application does not rely on the affected functionality.
argocd	v3.2.3	CVE-2025-47906	CVE-2025-47906 Vulnerability Overview CVE-2025-47906 is a flaw in the Go standard library's os/exec package affecting how the system searches for executables. Impact Assessment for ArgoCD ArgoCD is Not Affected by this vulnerability in our environment. While companion utilities like kustomize and helm may contain the vulnerable code, ArgoCD itself does not execute these utilities in a way that would be impacted by this vulnerability.

Onprem Version 2.10.5 - Published 2 February 2025			
Image	Tag	CVE	Mitigation
cf-api	21.293.11-onprem-1169fc9	CVE-2025-60876	CVE-2025-60876 is a header injection vulnerability found in BusyBox wget versions up to 1.3.7. The issue arises because the utility fails to sanitize control characters in the user-agent header, which can be exploited to inject arbitrary HTTP headers into requests. Our service is completely unaffected by this vulnerability because we do not use the wget utility in any of our operations. While BusyBox is present in our environment, it is not used for any of our critical operations.
cf-api	21.293.11-onprem-1169fc9	CVE-2021-3377	The attacker cannot inject an XSS vulnerability into the logs due to our input validation. The only possible avenue for such an attack is to invoke an external service that can inject malicious payloads into our logs.
cf-api	21.293.11-onprem-1169fc9	CVE-2024-11023	Firebase JavaScript SDK utilizes a "FIREBASE_DEFAULTS" cookie to store configuration data, including an "_authTokenSyncURL" field used for session synchronization. This cookie is not properly sanitized, allowing for potential session hijacking or data manipulation.
cf-api	21.293.11-onprem-1169fc9	CVE-2022-23539	We do not configure the jsonwebtoken library to use custom key types or algorithms, thus the default settings are used. As a result, the vulnerability does not affect our service.
cf-api	21.293.11-onprem-1169fc9	CVE-2022-23540	https://github.com/advisories/GHSA-qwph-4952-7xr6 - here are 3 circumstances which exist and can open a vulnerability in the package. 3rd one - "a" falsy (e.g. null, false, 0, etc.)
cf-api	21.293.11-onprem-1169fc9	CVE-2022-23541	We do not configure the jsonwebtoken library to use custom key types or algorithms, thus the default settings are used. As a result, the vulnerability does not affect our service.
cf-api	21.293.11-onprem-1169fc9	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of code.
cf-broadcaster	1.14.5-onprem-0dcf808	CVE-2025-60876	CVE-2025-60876 is a header injection vulnerability found in BusyBox wget versions up to 1.3.7. The issue arises because the utility fails to sanitize control characters in the user-agent header, which can be exploited to inject arbitrary HTTP headers into requests. Our service is completely unaffected by this vulnerability because we do not use the wget utility in any of our operations. While BusyBox is present in our environment, it is not used for any of our critical operations.
cf-broadcaster	1.14.5-onprem-0dcf808	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of code.
cf-broadcaster	1.14.5-onprem-0dcf808	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of code.
cf-container-logger	2.0.6	CVE-2025-13151	CVE-2025-13151 is a high-severity vulnerability in OpenSSL related to the incorrect processing of X.509 certificate extensions, which can lead to a bypass in certificate validation.
cf-container-logger	2.0.6	CVE-2024-11023	Firebase JavaScript SDK utilizes a "FIREBASE_DEFAULTS" cookie to store configuration data, including an "_authTokenSyncURL" field used for session synchronization. This cookie is not properly sanitized, allowing for potential session hijacking or data manipulation.
cf-container-logger	2.0.6	CVE-2016-2781	CVE-2016-2781 is a vulnerability in the GNU Coreutils chroot utility that stems from improper handling of standard file descriptors. An attacker with root privileges can exploit this to escape the chroot environment.
cf-container-logger	2.0.6	CVE-2023-45853	Our services are not affected by this vulnerability because we exclusively use Docker and Kubernetes for process isolation across our entire infrastructure. These services are not vulnerable to this issue.
cf-container-logger	2.0.6	CVE-2023-45853	won't be fixed because it's not a valid risk - look at the explanation: https://github.com/madler/zlib/issues/868#issuecomment-2655313719
cf-container-logger	2.0.6	CVE-2025-14104	CVE-2025-14104 is a sensitive information exposure vulnerability identified within the Python Requests library during the handling of HTTP redirects. The flaw occurs when the library fails to properly sanitize the 'Location' header in a redirect response.
cf-container-logger	2.0.6	CVE-2024-10041	Our service is not affected by this vulnerability because it is developed using a non-Python technology stack and does not execute Python code in production. While CVE-2024-10041 is a denial-of-service vulnerability located within the NGINX HTTP/3 module (ngx_http_v3_module) during the handling of QUIC sessions. The flaw occurs when the module fails to properly handle certain QUIC session parameters.
cf-deploy-kubernetes	17.0.2	CVE-2023-42366	Our infrastructure is not affected by this vulnerability because the HTTP/3 (QUIC) protocol is not enabled in any of our production or staging environments. Our service mitigates potential vulnerabilities by refusing to accept user input and abstaining from utilizing it in operations involving text files and the awk utility. This approach ensures that no sensitive data is exposed or manipulated.
cf-deploy-kubernetes	17.0.2	CVE-2025-46394	CVE-2025-46394 is a visual spoofing vulnerability in BusyBox tar that allows malicious actors to hide filenames in a terminal listing by using ANSI escape sequences.
cf-deploy-kubernetes	17.0.2	CVE-2025-60876	Our services are not affected because our archive processing is fully automated and involves no manual terminal inspection. Since the exploit relies exclusively on user input, it is not applicable to our automated processes.
cf-deploy-kubernetes	17.0.2	CVE-2025-60876	CVE-2025-60876 is a header injection vulnerability found in BusyBox wget versions up to 1.3.7. The issue arises because the utility fails to sanitize control characters in the user-agent header, which can be exploited to inject arbitrary HTTP headers into requests. Our service is completely unaffected by this vulnerability because we do not use the wget utility in any of our operations. While BusyBox is present in our environment, it is not used for any of our critical operations.
cf-deploy-kubernetes	17.0.2	CVE-2025-14104	CVE-2025-14104 is a sensitive information exposure vulnerability identified within the Python Requests library during the handling of HTTP redirects. The flaw occurs when the library fails to properly sanitize the 'Location' header in a redirect response.
cf-deploy-kubernetes	17.0.2	CVE-2025-46394	Our service is not affected by this vulnerability because it is developed using a non-Python technology stack and does not execute Python code in production. While CVE-2025-46394 is a visual spoofing vulnerability in BusyBox tar that allows malicious actors to hide filenames in a terminal listing by using ANSI escape sequences.
cf-deploy-kubernetes	17.0.2	CVE-2025-60876	Our services are not affected because our archive processing is fully automated and involves no manual terminal inspection. Since the exploit relies exclusively on user input, it is not applicable to our automated processes.
cf-deploy-kubernetes	17.0.2	CVE-2025-60876	CVE-2025-60876 is a header injection vulnerability found in BusyBox wget versions up to 1.3.7. The issue arises because the utility fails to sanitize control characters in the user-agent header, which can be exploited to inject arbitrary HTTP headers into requests. Our service is completely unaffected by this vulnerability because we do not use the wget utility in any of our operations. While BusyBox is present in our environment, it is not used for any of our critical operations.
cf-git-cloner	10.3.7	CVE-2023-42366	Service mitigates potential vulnerabilities by refusing to accept user input and abstaining from utilizing it in operations involving text files and the awk utility. This approach ensures that no sensitive data is exposed or manipulated.

Onprem Version 2.10.5 - Published 2 February 2025			
Image	Tag	CVE	Mitigation
cf-git-cloner	10.3.7	CVE-2025-46394	CVE-2025-46394 is a visual spoofing vulnerability in BusyBox tar that allows malicious actors to hide filenames in a terminal listing by using ANSI escape sequences. Our services are not affected because our archive processing is fully automated and involves no manual terminal inspection. Since the exploit relies exclusively on CVE-2025-60876 is a header injection vulnerability found in BusyBox wget versions up to 1.3.7. The issue arises because the utility fails to sanitize control characters.
cf-git-cloner	10.3.7	CVE-2025-60876	Our service is completely unaffected by this vulnerability because we do not use the wget utility in any of our operations. While BusyBox is present in our environment, CVE-2025-13151 is a high-severity vulnerability in OpenSSL related to the incorrect processing of X.509 certificate extensions, which can lead to a bypass in certificate verification.
cf-git-cloner	10.3.7	CVE-2025-13151	Our services are not affected by this vulnerability because we utilize a multi-layered security architecture where TLS termination is handled exclusively at the infrastructure level. CVE-2025-14104 is a sensitive information exposure vulnerability identified within the Python Requests library during the handling of HTTP redirects. The flaw occurs when the library incorrectly processes redirects that contain sensitive information in the location header.
cf-git-cloner	10.3.7	CVE-2025-14104	Our service is not affected by this vulnerability because it is developed using a non-Python technology stack and does not execute Python code in production. While CVE-2025-46394 is a visual spoofing vulnerability in BusyBox tar that allows malicious actors to hide filenames in a terminal listing by using ANSI escape sequences. Our services are not affected because our archive processing is fully automated and involves no manual terminal inspection. Since the exploit relies exclusively on CVE-2025-60876 is a header injection vulnerability found in BusyBox wget versions up to 1.3.7. The issue arises because the utility fails to sanitize control characters.
cf-git-cloner	10.3.7	CVE-2025-46394	Our service is completely unaffected by this vulnerability because we do not use the wget utility in any of our operations. While BusyBox is present in our environment, CVE-2025-13151 is a high-severity vulnerability in OpenSSL related to the incorrect processing of X.509 certificate extensions, which can lead to a bypass in certificate verification.
cf-git-cloner	10.3.7	CVE-2025-60876	Our services are not affected by this vulnerability because we utilize a multi-layered security architecture where TLS termination is handled exclusively at the infrastructure level. CVE-2025-14104 is a sensitive information exposure vulnerability identified within the Python Requests library during the handling of HTTP redirects. The flaw occurs when the library incorrectly processes redirects that contain sensitive information in the location header.
cf-platform-analytics	0.52.4-onprem-8313be2	CVE-2025-13151	Our services are not affected by this vulnerability because we utilize a multi-layered security architecture where TLS termination is handled exclusively at the infrastructure level. CVE-2025-14104 is a sensitive information exposure vulnerability identified within the Python Requests library during the handling of HTTP redirects. The flaw occurs when the library incorrectly processes redirects that contain sensitive information in the location header.
cf-platform-analytics	0.52.4-onprem-8313be2	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of code.
cf-platform-analytics	0.52.4-onprem-8313be2	CVE-2022-36313	The vulnerable package "file-type" is nested in "decompress" package.
cf-platform-analytics	0.52.4-onprem-8313be2	CVE-2024-27088	The CVE-2022-36313 vulnerability relates specifically to .mkv file type handling. The decompress package utilizes file-type exclusively for detecting types such as video files. Our approach mitigates the vulnerability by enforcing simplified function naming conventions and prioritizing updated dependencies that prevent script stalls caused by complex file type detection logic.
cf-platform-analytics	0.52.4-onprem-8313be2	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of code.
cf-platform-analytics	0.52.4-onprem-8313be2	CVE-2022-36313	The vulnerable package "file-type" is nested in "decompress" package.
cf-platform-analytics	0.52.4-onprem-8313be2	CVE-2022-36313	The CVE-2022-36313 vulnerability relates specifically to .mkv file type handling. The decompress package utilizes file-type exclusively for detecting types such as video files. Our approach mitigates the vulnerability by enforcing simplified function naming conventions and prioritizing updated dependencies that prevent script stalls caused by complex file type detection logic.
cf-platform-analytics	0.52.4-onprem-8313be2	CVE-2022-36313	The vulnerable package "file-type" is nested in "decompress" package.
cf-platform-analytics	0.52.4-onprem-8313be2	CVE-2022-36313	The CVE-2022-36313 vulnerability relates specifically to .mkv file type handling. The decompress package utilizes file-type exclusively for detecting types such as video files. Our approach mitigates the vulnerability by enforcing simplified function naming conventions and prioritizing updated dependencies that prevent script stalls caused by complex file type detection logic.
cf-platform-analytics	0.52.4-onprem-8313be2	CVE-2016-2781	CVE-2016-2781 is a vulnerability in the GNU Coreutils chroot utility that stems from improper handling of standard file descriptors. An attacker with root privileges could potentially escape the chrooted environment. Our services are not affected by this vulnerability because we exclusively use Docker and Kubernetes for process isolation across our entire infrastructure. These containers do not rely on the GNU Coreutils chroot utility.
cf-platform-analytics	0.52.4-onprem-8313be2	CVE-2025-14104	CVE-2025-14104 is a sensitive information exposure vulnerability identified within the Python Requests library during the handling of HTTP redirects. The flaw occurs when the library incorrectly processes redirects that contain sensitive information in the location header.
cf-platform-analytics	0.52.4-onprem-8313be2	CVE-2023-45853	Our service is not affected by this vulnerability because it is developed using a non-Python technology stack and does not execute Python code in production. While CVE-2025-46394 is a visual spoofing vulnerability in BusyBox tar that allows malicious actors to hide filenames in a terminal listing by using ANSI escape sequences. Our services are not affected because our archive processing is fully automated and involves no manual terminal inspection. Since the exploit relies exclusively on CVE-2025-60876 is a header injection vulnerability found in BusyBox wget versions up to 1.3.7. The issue arises because the utility fails to sanitize control characters.
cf-platform-analytics	0.52.4-onprem-8313be2	CVE-2024-10041	won't be fixed because it's not valid risk - look at the explanation: https://github.com/comadler/zlib/issues/868#issuecomment-2655313719
cf-platform-analytics	0.52.4-onprem-8313be2	CVE-2024-10041	CVE-2024-10041 is a denial-of-service vulnerability located within the NGINX HTTP/3 module (ngx_http_v3_module) during the handling of QUIC sessions. The flaw occurs when the module fails to properly manage memory resources, leading to a denial of service. Our infrastructure is not affected by this vulnerability because the HTTP/3 (QUIC) protocol is not enabled in any of our production or staging environments. Our services are not affected by this vulnerability because we exclusively use Docker and Kubernetes for process isolation across our entire infrastructure. These containers do not rely on the GNU Coreutils chroot utility.
cf-tls-sign	1.8.15	CVE-2025-14104	CVE-2025-14104 is a sensitive information exposure vulnerability identified within the Python Requests library during the handling of HTTP redirects. The flaw occurs when the library incorrectly processes redirects that contain sensitive information in the location header.
charts-manager	1.26.4-onprem-7e6d100	CVE-2025-60876	Our service is not affected by this vulnerability because it is developed using a non-Python technology stack and does not execute Python code in production. While CVE-2025-46394 is a visual spoofing vulnerability in BusyBox tar that allows malicious actors to hide filenames in a terminal listing by using ANSI escape sequences. Our services are not affected because our archive processing is fully automated and involves no manual terminal inspection. Since the exploit relies exclusively on CVE-2025-60876 is a header injection vulnerability found in BusyBox wget versions up to 1.3.7. The issue arises because the utility fails to sanitize control characters.
charts-manager	1.26.4-onprem-7e6d100	CVE-2025-60876	Our service is completely unaffected by this vulnerability because we do not use the wget utility in any of our operations. While BusyBox is present in our environment, CVE-2025-13151 is a high-severity vulnerability in OpenSSL related to the incorrect processing of X.509 certificate extensions, which can lead to a bypass in certificate verification.
charts-manager	1.26.4-onprem-7e6d100	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of code.
charts-manager	1.26.4-onprem-7e6d100	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of code.

Onprem Version 2.10.5 - Published 2 February 2025			
Image	Tag	CVE	Mitigation
cluster-providers	1.19.5-onprem-5b312e5	CVE-2025-60876	CVE-2025-60876 is a header injection vulnerability found in BusyBox wget versions up to 1.3.7. The issue arises because the utility fails to sanitize control characters in the 'Host' header, which can be exploited to inject arbitrary HTTP requests into the target server's traffic.
compose	v5.0.1-1.6.0	CVE-2025-14104	Our service is completely unaffected by this vulnerability because we do not use the wget utility in any of our operations. While BusyBox is present in our environment, the specific version of wget used does not contain the vulnerable code path.
context-manager	2.37.4-onprem-7b66875	CVE-2025-60876	CVE-2025-60876 is a header injection vulnerability found in BusyBox wget versions up to 1.3.7. The issue arises because the utility fails to sanitize control characters in the 'Host' header, which can be exploited to inject arbitrary HTTP requests into the target server's traffic.
context-manager	2.37.4-onprem-7b66875	CVE-2020-36604	Our service is completely unaffected by this vulnerability because we do not use the wget utility in any of our operations. While BusyBox is present in our environment, the specific version of wget used does not contain the vulnerable code path.
context-manager	2.37.4-onprem-7b66875	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of code.
dind	28.5.2-3.0.8	CVE-2025-60876	CVE-2025-60876 is a header injection vulnerability found in BusyBox wget versions up to 1.3.7. The issue arises because the utility fails to sanitize control characters in the 'Host' header, which can be exploited to inject arbitrary HTTP requests into the target server's traffic.
dind	29.2.0-3.0.10	CVE-2025-60876	Our service is completely unaffected by this vulnerability because we do not use the wget utility in any of our operations. While BusyBox is present in our environment, the specific version of wget used does not contain the vulnerable code path.
engine	3.0.1	CVE-2025-60876	CVE-2025-60876 is a header injection vulnerability found in BusyBox wget versions up to 1.3.7. The issue arises because the utility fails to sanitize control characters in the 'Host' header, which can be exploited to inject arbitrary HTTP requests into the target server's traffic.
engine	3.0.1	CVE-2022-33987	Our service is completely unaffected by this vulnerability because we do not use the wget utility in any of our operations. While BusyBox is present in our environment, the specific version of wget used does not contain the vulnerable code path.
engine	3.0.1	CVE-2024-29415	dependency is located in "npm" and not related/used to app package/run.
engine	3.0.1	CVE-2024-28176	This package is not used inside our business logic to validate the loopback addresses thus we are not affected by this vulnerability.
engine	3.0.1	CVE-2024-28176	Service utilizes the jose module as nested module in jsonwebtoken. But does not perform any operation of unpacking decrypted text, and we don't use JWE at all. Therefore, the vulnerability is not applicable to our service.
engine	3.0.1	CVE-2024-11023	Firestore JavaScript SDK utilizes a "FIREBASE_DEFAULTS" cookie to store configuration data, including an "_authTokenSyncURL" field used for session synchronization. Our service does not utilize this SDK or the associated cookie.
engine	3.0.1	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of code.
gitops-dashboard-manager	1.16.4-onprem-48d7cb3	CVE-2025-60876	CVE-2025-60876 is a header injection vulnerability found in BusyBox wget versions up to 1.3.7. The issue arises because the utility fails to sanitize control characters in the 'Host' header, which can be exploited to inject arbitrary HTTP requests into the target server's traffic.
gitops-dashboard-manager	1.16.4-onprem-48d7cb3	CVE-2020-36604	Our service is completely unaffected by this vulnerability because we do not use the wget utility in any of our operations. While BusyBox is present in our environment, the specific version of wget used does not contain the vulnerable code path.
gitops-dashboard-manager	1.16.4-onprem-48d7cb3	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of code.
hermes	0.21.24-onprem-3955c67	CVE-2025-60876	CVE-2025-60876 is a header injection vulnerability found in BusyBox wget versions up to 1.3.7. The issue arises because the utility fails to sanitize control characters in the 'Host' header, which can be exploited to inject arbitrary HTTP requests into the target server's traffic.
k8s-monitor	4.11.20-onprem-101e14c	CVE-2025-60876	Our service is completely unaffected by this vulnerability because we do not use the wget utility in any of our operations. While BusyBox is present in our environment, the specific version of wget used does not contain the vulnerable code path.
kube-integration	1.33.6-onprem-813166a	CVE-2025-60876	CVE-2025-60876 is a header injection vulnerability found in BusyBox wget versions up to 1.3.7. The issue arises because the utility fails to sanitize control characters in the 'Host' header, which can be exploited to inject arbitrary HTTP requests into the target server's traffic.
nginx-unprivileged	1.29-alpine-otel	CVE-2025-60876	Our service is completely unaffected by this vulnerability because we do not use the wget utility in any of our operations. While BusyBox is present in our environment, the specific version of wget used does not contain the vulnerable code path.
pipeline-manager	3.143.4-onprem-8582ab7	CVE-2025-60876	CVE-2025-60876 is a header injection vulnerability found in BusyBox wget versions up to 1.3.7. The issue arises because the utility fails to sanitize control characters in the 'Host' header, which can be exploited to inject arbitrary HTTP requests into the target server's traffic.
pipeline-manager	3.143.4-onprem-8582ab7	CVE-2020-36604	Our service is completely unaffected by this vulnerability because we do not use the wget utility in any of our operations. While BusyBox is present in our environment, the specific version of wget used does not contain the vulnerable code path.
pipeline-manager	3.143.4-onprem-8582ab7	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of code.

Onprem Version 2.10.5 - Published 2 February 2025			
Image	Tag	CVE	Mitigation
pipeline-manager	3.143.4-onprem-8582ab7	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount.
runtime-environment-manager	3.44.5-onprem-825697e	CVE-2025-60876	CVE-2025-60876 is a header injection vulnerability found in BusyBox wget versions up to 1.3.7. The issue arises because the utility fails to sanitize control characters.
runtime-environment-manager	3.44.5-onprem-825697e	CVE-2020-36604	Our service is completely unaffected by this vulnerability because we do not use the wget utility in any of our operations. While BusyBox is present in our environment, it is not used for any of our operations.
runtime-environment-manager	3.44.5-onprem-825697e	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount.
tasker-kubernetes	1.28.4-onprem-7450ced	CVE-2025-60876	CVE-2025-60876 is a header injection vulnerability found in BusyBox wget versions up to 1.3.7. The issue arises because the utility fails to sanitize control characters.
tasker-kubernetes	1.28.4-onprem-7450ced	CVE-2020-36604	Our service is completely unaffected by this vulnerability because we do not use the wget utility in any of our operations. While BusyBox is present in our environment, it is not used for any of our operations.
tasker-kubernetes	1.28.4-onprem-7450ced	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount.
tasker-kubernetes	1.28.4-onprem-7450ced	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount.

Onprem Version 2.10.1 – Published 5 January 2025			
Image	Tag	CVE	Mitigation
argo-platform-analytics-reporter	1.3978.0-onprem-d51e55f	CVE-2023-26108	Vulnerability is related to StreamableFile api – we are not using this api to return files. Also, we do not allow to download files from our services.
argo-platform-analytics-reporter	1.3978.0-onprem-d51e55f	CVE-2024-29409	CVE-2024-29409 describes a file upload vulnerability in NestJS Nest v10.3.2. This flaw allows a remote attacker to achieve remote code execution by manipulating the Content-Type header during a file upload, tricking the application into processing a malicious file. Our services are not impacted by this vulnerability because our applications do not use file upload functionalities. The vulnerability is specifically tied to the file upload mechanism in NestJS; since our systems do not have this feature enabled, there is no risk of a malicious file being uploaded or executed.
argo-platform-api-events	1.3978.0-onprem-d51e55f	CVE-2024-29409	CVE-2024-29409 describes a file upload vulnerability in NestJS Nest v10.3.2. This flaw allows a remote attacker to achieve remote code execution by manipulating the Content-Type header during a file upload, tricking the application into processing a malicious file. Our services are not impacted by this vulnerability because our applications do not use file upload functionalities. The vulnerability is specifically tied to the file upload mechanism in NestJS; since our systems do not have this feature enabled, there is no risk of a malicious file being uploaded or executed.
argo-platform-api-events	1.3978.0-onprem-d51e55f	CVE-2023-26108	Vulnerability is related to StreamableFile api – we are not using this api to return files. Also, we do not allow to download files from our services.
argo-platform-api-graphql	1.3978.0-onprem-d51e55f	CVE-2024-29409	CVE-2024-29409 describes a file upload vulnerability in NestJS Nest v10.3.2. This flaw allows a remote attacker to achieve remote code execution by manipulating the Content-Type header during a file upload, tricking the application into processing a malicious file. Our services are not impacted by this vulnerability because our applications do not use file upload functionalities. The vulnerability is specifically tied to the file upload mechanism in NestJS; since our systems do not have this feature enabled, there is no risk of a malicious file being uploaded or executed.
argo-platform-api-graphql	1.3978.0-onprem-d51e55f	CVE-2024-29415	This package is not used inside our business logic to validate the loopback addresses thus we are not affected by this vulnerability.
argo-platform-api-graphql	1.3978.0-onprem-d51e55f	CVE-2025-25290	Vulnerability nested in package @octokit/rest. It won't affect the service because the package added long time ago and it usage was deleted without cleaning dependency list. It will be deleted in next release.
argo-platform-api-graphql	1.3978.0-onprem-d51e55f	CVE-2025-25289	Vulnerability nested in package @octokit/rest. It won't affect the service because the package added long time ago and it usage was deleted without cleaning dependency list. It will be deleted in next release.
argo-platform-api-graphql	1.3978.0-onprem-d51e55f	CVE-2023-26108	Vulnerability is related to StreamableFile api – we are not using this api to return files. Also, we do not allow to download files from our services.
argo-platform-audit	1.3978.0-onprem-d51e55f	CVE-2023-26108	Vulnerability is related to StreamableFile api – we are not using this api to return files. Also, we do not allow to download files from our services.
argo-platform-audit	1.3978.0-onprem-d51e55f	CVE-2024-29409	CVE-2024-29409 describes a file upload vulnerability in NestJS Nest v10.3.2. This flaw allows a remote attacker to achieve remote code execution by manipulating the Content-Type header during a file upload, tricking the application into processing a malicious file. Our services are not impacted by this vulnerability because our applications do not use file upload functionalities. The vulnerability is specifically tied to the file upload mechanism in NestJS; since our systems do not have this feature enabled, there is no risk of a malicious file being uploaded or executed.
argo-platform-broadcaster	1.3978.0-onprem-d51e55f	CVE-2024-29409	CVE-2024-29409 describes a file upload vulnerability in NestJS Nest v10.3.2. This flaw allows a remote attacker to achieve remote code execution by manipulating the Content-Type header during a file upload, tricking the application into processing a malicious file. Our services are not impacted by this vulnerability because our applications do not use file upload functionalities. The vulnerability is specifically tied to the file upload mechanism in NestJS; since our systems do not have this feature enabled, there is no risk of a malicious file being uploaded or executed.
argo-platform-broadcaster	1.3978.0-onprem-d51e55f	CVE-2023-26108	Vulnerability is related to StreamableFile api – we are not using this api to return files. Also, we do not allow to download files from our services.
argo-platform-cron-executor	1.3978.0-onprem-d51e55f	CVE-2024-29409	CVE-2024-29409 describes a file upload vulnerability in NestJS Nest v10.3.2. This flaw allows a remote attacker to achieve remote code execution by manipulating the Content-Type header during a file upload, tricking the application into processing a malicious file. Our services are not impacted by this vulnerability because our applications do not use file upload functionalities. The vulnerability is specifically tied to the file upload mechanism in NestJS; since our systems do not have this feature enabled, there is no risk of a malicious file being uploaded or executed.
argo-platform-cron-executor	1.3978.0-onprem-d51e55f	CVE-2023-26108	Vulnerability is related to StreamableFile api – we are not using this api to return files. Also, we do not allow to download files from our services.
argo-platform-event-handler	1.3978.0-onprem-d51e55f	CVE-2023-26108	Vulnerability is related to StreamableFile api – we are not using this api to return files. Also, we do not allow to download files from our services.
argo-platform-event-handler	1.3978.0-onprem-d51e55f	CVE-2024-29409	CVE-2024-29409 describes a file upload vulnerability in NestJS Nest v10.3.2. This flaw allows a remote attacker to achieve remote code execution by manipulating the Content-Type header during a file upload, tricking the application into processing a malicious file. Our services are not impacted by this vulnerability because our applications do not use file upload functionalities. The vulnerability is specifically tied to the file upload mechanism in NestJS; since our systems do not have this feature enabled, there is no risk of a malicious file being uploaded or executed.
argo-platform-promotion-orchestrator	1.3978.0-onprem-d51e55f	CVE-2024-29409	CVE-2024-29409 describes a file upload vulnerability in NestJS Nest v10.3.2. This flaw allows a remote attacker to achieve remote code execution by manipulating the Content-Type header during a file upload, tricking the application into processing a malicious file. Our services are not impacted by this vulnerability because our applications do not use file upload functionalities. The vulnerability is specifically tied to the file upload mechanism in NestJS; since our systems do not have this feature enabled, there is no risk of a malicious file being uploaded or executed.
argo-platform-promotion-orchestrator	1.3978.0-onprem-d51e55f	CVE-2024-29415	This package is not used inside our business logic to validate the loopback addresses thus we are not affected by this vulnerability.
argo-platform-promotion-orchestrator	1.3978.0-onprem-d51e55f	CVE-2023-26108	Vulnerability is related to StreamableFile api – we are not using this api to return files. Also, we do not allow to download files from our services.
cf-api	21.293.7-onprem-b422fbb	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of Joi functions. Our risk assessment confirms that vulnerable hoek method "clone" does not affect any codefresh business logic by usage of Joi functions that we exploit in that business logic.

Onprem Version 2.10.1 – Published 5 January 2025			
Image	Tag	CVE	Mitigation
cf-api	21.293.7-onprem-b422fbb	CVE-2022-23539	We do not configure the jsonwebtoken library to use custom key types or algorithms, thus the default settings are used. As a result, the vulnerability does not affect our application since it only impacts configurations using invalid key types / algorithm combinations, which we do not utilize.
cf-api	21.293.7-onprem-b422fbb	CVE-2022-23540	https://github.com/advisories/GHSA-qwph-4952-7xr6 - here are 3 circumstance which existing can open vlnerability in package. 3-rd one - "a falsy (e.g. null, false, undefined) secret or key is passed" we never pass a falsy argument as a secret key in jwt.verify() function. Also, additional testing of "jsonwebtoken"@5.4.7 can't prove existing such vulnerability.
cf-api	21.293.7-onprem-b422fbb	CVE-2022-23541	We do not configure the jsonwebtoken library to use custom key types or algorithms, thus the default settings are used. As a result, the vulnerability does not affect our application since it only impacts configurations using invalid key types / algorithm combinations, which we do not utilize.
cf-api	21.293.7-onprem-b422fbb	CVE-2024-11023	Firebase JavaScript SDK utilizes a "FIREBASE_DEFAULTS" cookie to store configuration data, including an "_authTokenSyncURL" field used for session synchronization. If this cookie field is preset via an attacker by any other method, the attacker can manipulate the "_authTokenSyncURL" to point to their own server and it would allow am actor to capture user session data transmitted by the SDK.
cf-api	21.293.7-onprem-b422fbb	CVE-2021-3377	The attacker cannot inject an XSS vulnerability into the logs due to our input validation. The only possible avenue for such an attack is to invoke an external service through a codefresh step in pipeline, which could potentially introduce HTML content into the logs. However, even in this scenario, Codefresh utilizes this library exclusively when a customer attempts to download logs in HTML format. This is distinct from the Codefresh logs viewer and is unrelated to it.
cf-api	21.293.7-onprem-b422fbb	CVE-2025-64718	The image is using the js-yaml version v3.14.2, which contains the fix for CVE-2025-64718. It was cherry picked from the 4.0.1 version. https://github.com/nodeca/js-yaml/pull/731/files
			But the repository-level advisory wasn't updated and it still lists only v4.1.1 as patched. https://github.com/nodeca/js-yaml/issues/730
cf-broadcaster	1.14.3-onprem-c9d095c	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of Joi functions. Our risk assessment confirms that vulnerable hoek method "clone" does not affect any codefresh business logic by usage of Joi functions that we exploit in that business logic.
cf-broadcaster	1.14.3-onprem-c9d095c	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of Joi functions. Our risk assessment confirms that vulnerable hoek method "clone" does not affect any codefresh business logic by usage of Joi functions that we exploit in that business logic.
cf-container-logger	2.0.1	CVE-2024-11023	Firebase JavaScript SDK utilizes a "FIREBASE_DEFAULTS" cookie to store configuration data, including an "_authTokenSyncURL" field used for session synchronization. If this cookie field is preset via an attacker by any other method, the attacker can manipulate the "_authTokenSyncURL" to point to their own server and it would allow am actor to capture user session data transmitted by the SDK.
cf-git-cloner	10.3.4	CVE-2023-42366	Service mitigates potential vulnerabilities by refusing to accept user input and abstaining from utilizing it in operations involving text files and the awk utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment
cf-platform-analytics	0.52.3-onprem-6bb2b5c	CVE-2022-36313	The vulnerable package "file-type" is nested in "decompress" package.
			The CVE-2022-36313 vulnerability relates specifically to .mkv file type handling. The decompress package utilizes file-type exclusively for detecting types such as tar, tarbz2, targz, and zip. Therefore, the service is not affected by this vulnerability.
cf-platform-analytics	0.52.3-onprem-6bb2b5c	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of Joi functions. Our risk assessment confirms that vulnerable hoek method "clone" does not affect any codefresh business logic by usage of Joi functions that we exploit in that business logic.
			The vulnerable package "file-type" is nested in "decompress" package.
cf-platform-analytics	0.52.3-onprem-6bb2b5c	CVE-2022-36313	The CVE-2022-36313 vulnerability relates specifically to .mkv file type handling. The decompress package utilizes file-type exclusively for detecting types such as tar, tarbz2, targz, and zip. Therefore, the service is not affected by this vulnerability.
			The vulnerable package "file-type" is nested in "decompress" package.
cf-platform-analytics	0.52.3-onprem-6bb2b5c	CVE-2022-36313	The CVE-2022-36313 vulnerability relates specifically to .mkv file type handling. The decompress package utilizes file-type exclusively for detecting types such as tar, tarbz2, targz, and zip. Therefore, the service is not affected by this vulnerability.
			The CVE-2022-36313 vulnerability relates specifically to .mkv file type handling. The decompress package utilizes file-type exclusively for detecting types such as tar, tarbz2, targz, and zip. Therefore, the service is not affected by this vulnerability.
cf-platform-analytics	0.52.3-onprem-6bb2b5c	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of Joi functions. Our risk assessment confirms that vulnerable hoek method "clone" does not affect any codefresh business logic by usage of Joi functions that we exploit in that business logic.
cf-platform-analytics	0.52.3-onprem-6bb2b5c	CVE-2024-27088	Our approach mitigates the vulnerability by enforcing simplified function naming conventions and prioritizing updated dependencies that prevent script stalls caused by complex function declarations
charts-manager	1.26.3-onprem-58cbba4	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of Joi functions. Our risk assessment confirms that vulnerable hoek method "clone" does not affect any codefresh business logic by usage of Joi functions that we exploit in that business logic.
charts-manager	1.26.3-onprem-58cbba4	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of Joi functions. Our risk assessment confirms that vulnerable hoek method "clone" does not affect any codefresh business logic by usage of Joi functions that we exploit in that business logic.

Onprem Version 2.10.1 – Published 5 January 2025			
Image	Tag	CVE	Mitigation
context-manager	2.37.3-onprem-121c861	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of Joi functions. Our risk assessment confirms that vulnerable hoek method "clone" does not affect any codefresh business logic by usage of Joi functions that we exploit in that business logic.
context-manager	2.37.3-onprem-121c861	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of Joi functions. Our risk assessment confirms that vulnerable hoek method "clone" does not affect any codefresh business logic by usage of Joi functions that we exploit in that business logic.
engine	2.1.2	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of Joi functions. Our risk assessment confirms that vulnerable hoek method "clone" does not affect any codefresh business logic by usage of Joi functions that we exploit in that business logic.
engine	2.1.2	CVE-2024-29415	This package is not used inside our business logic to validate the loopback addresses thus we are not affected by this vulnerability.
engine	2.1.2	CVE-2022-33987	dependency is located in "npm" and not related/used to app package/run.
engine	2.1.2	CVE-2024-28176	Service utilizes the jose module as nested module in jsonwebtoken. But does not perform any operation of unpacking decrypted text, and we don't use JWE at all. This vulnerability will not impact our service
engine	2.1.2	CVE-2024-11023	Firebase JavaScript SDK utilizes a "FIREBASE_DEFAULTS" cookie to store configuration data, including an "_authTokenSyncURL" field used for session synchronization. If this cookie field is preset via an attacker by any other method, the attacker can manipulate the "_authTokenSyncURL" to point to their own server and it would allow an actor to capture user session data transmitted by the SDK.
gitops-dashboard-manager	1.16.3-onprem-6093ead	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of Joi functions. Our risk assessment confirms that vulnerable hoek method "clone" does not affect any codefresh business logic by usage of Joi functions that we exploit in that business logic.
gitops-dashboard-manager	1.16.3-onprem-6093ead	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of Joi functions. Our risk assessment confirms that vulnerable hoek method "clone" does not affect any codefresh business logic by usage of Joi functions that we exploit in that business logic.
pipeline-manager	3.143.2	CVE-2025-64718	The image is using the js-yaml version v3.14.2, which contains the fix for CVE-2025-64718. It was cherry picked from the 4.0.1 version. https://github.com/nodeca/js-yaml/pull/731/files
pipeline-manager	3.143.2	CVE-2020-36604	But the repository-level advisory wasn't updated and it still lists only v4.1.1 as patched. https://github.com/nodeca/js-yaml/issues/730
pipeline-manager	3.143.2	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of Joi functions. Our risk assessment confirms that vulnerable hoek method "clone" does not affect any codefresh business logic by usage of Joi functions that we exploit in that business logic.
pipeline-manager	3.143.2	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of Joi functions. Our risk assessment confirms that vulnerable hoek method "clone" does not affect any codefresh business logic by usage of Joi functions that we exploit in that business logic.
runtime-environment-manager	3.44.3-onprem-c3a88ad	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of Joi functions. Our risk assessment confirms that vulnerable hoek method "clone" does not affect any codefresh business logic by usage of Joi functions that we exploit in that business logic.
runtime-environment-manager	3.44.3-onprem-c3a88ad	CVE-2025-64718	The image is using the js-yaml version v3.14.2, which contains the fix for CVE-2025-64718. It was cherry picked from the 4.0.1 version. https://github.com/nodeca/js-yaml/pull/731/files
runtime-environment-manager	3.44.3-onprem-c3a88ad	CVE-2020-36604	But the repository-level advisory wasn't updated and it still lists only v4.1.1 as patched. https://github.com/nodeca/js-yaml/issues/730
tasker-kubernetes	1.28.3-onprem-8b19526	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of Joi functions. Our risk assessment confirms that vulnerable hoek method "clone" does not affect any codefresh business logic by usage of Joi functions that we exploit in that business logic.
tasker-kubernetes	1.28.3-onprem-8b19526	CVE-2020-36604	Hoek package is used only inside the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in a very small amount of Joi functions. Our risk assessment confirms that vulnerable hoek method "clone" does not affect any codefresh business logic by usage of Joi functions that we exploit in that business logic.

Gitops-runtime Version 0.26.4 - Published 22 December 2025			
Image	Tag	CVE	Mitigation
argocd	v3.2.2	CVE-2025-64329	The vulnerability in containerd's CRI Attach implementation, causing a memory exhaustion issue due to goroutine leaks in containerd (the container runtime), not Argo CD specifically. This issue impacts certain containerd versions (≤ 1.7.28, 2.0.0-2.0.6, etc.) and is fixed in later releases of container. ArgoCD has not even a library dependency on this specific software.
dex	v2.44.0	CVE-2025-47906	
dex	v2.44.0	CVE-2025-9230	
dex	v2.44.0	CVE-2025-9231	
dex	v2.44.0	CVE-2025-9232	
			on December 22 2025 it's the latest upstream version
			on December 22 2025 it's the latest upstream version
			on December 22 2025 it's the latest upstream version
			on December 22 2025 it's the latest upstream version

Gitops-runtime Version 0.25.1 - Published 6 November 2025			
Image	Tag	CVE	Mitigation
cf-argocd-extras	5a607d5	CVE-2025-0426	Argo service does not directly interact with kubelet endpoints. It communicates exclusively with the Kubernetes API server (kube-apiserver) to manage the desired state of applications. Therefore, the service does not make any requests to kubelet's read-only or write endpoints, nor does it depend on this functionality for its operation. As a result, this vulnerability does not directly impact the functionality.
cf-argocd-extras	5a607d5	CVE-2024-9042	This vulnerability is not applicable to Argo services, as it cannot be deployed on Windows nodes. The service runs exclusively on Linux-based nodes, and the affected /logs/query API endpoint is only present and exploitable on Windows nodes. Therefore, this issue does not pose any risk to Argo environments.
argo-events	v1.9.2-cap-CR-30841	CVE-2025-30204	The argo-events component includes github.com/golang-jwt/jwt as a transitive dependency through the module github.com/Azure/azure-sdk-for-go/sdk/storage/azqueue. This library is not used directly by our service logic, and no JWT token parsing or validation is performed via this path. Therefore, any potential issues or vulnerabilities in github.com/golang-jwt/jwt do not affect the behavior or security of our service.
natsio/prometheus-nats-exporter	0.16.0	CVE-2025-26519	To avoid the vulnerability we It is needed to delete all overrides of "prometheus-nats-exporter" itself if It exists. And upgrage gitops-runtime with values \$ global: runtime: eventBus: type: jetstream
natsio/prometheus-nats-exporter	0.16.0	CVE-2025-30215	To avoid the vulnerability we It is needed to delete all overrides of "prometheus-nats-exporter" itself if It exists. And upgrage gitops-runtime with values \$ global: runtime: eventBus: type: jetstream
natsio/prometheus-nats-exporter	0.16.0	CVE-2024-12797	To avoid the vulnerability we It is needed to delete all overrides of "prometheus-nats-exporter" itself if It exists. And upgrage gitops-runtime with values \$ global: runtime: eventBus: type: jetstream
natsio/prometheus-nats-exporter	0.16.0	CVE-2024-13176	To avoid the vulnerability we It is needed to delete all overrides of "prometheus-nats-exporter" itself if It exists. And upgrage gitops-runtime with values \$ global: runtime: eventBus: type: jetstream

Gitops-runtime Version 0.23.1 - Published 21 August 2025			
Image	Tag	CVE	Mitigation
cf-argocd-extras	v0.5.12	CVE-2025-0426	<p>Summary: CVE-2025-0426 describes a Denial of Service vulnerability in the Kubernetes kubelet component, where unauthenticated requests to the read-only HTTP endpoint can fill up node disk space via the checkpoint API, potentially leading to node unavailability.</p> <p>Mitigation: Argo service does not directly interact with kubelet endpoints. It communicates exclusively with the Kubernetes API server (kube-apiserver) to manage the desired state of applications. Therefore, the service does not make any requests to kubelet's read-only or write endpoints, nor does it depend on this functionality for its operation.</p> <p>As a result, this vulnerability does not directly impact the functionality.</p>
cf-argocd-extras	v0.5.12	CVE-2024-9042	<p>This vulnerability is not applicable to Argo services, as it cannot be deployed on Windows nodes. The service runs exclusively on Linux-based nodes, and the affected /logs/query API endpoint is only present and exploitable on Windows nodes. Therefore, this issue does not pose any risk to Argo environments.</p>
redis	7.4.5-alpine	CVE-2022-30632	<p>CVE-2022-30632 vulnerability in Go's path/filepath.Glob library, affecting gosu (if compiled with an old Go version), does not impact Redis's functionality or security. Redis is written in C and doesn't use Go's path/filepath.Glob. While gosu is a Go binary often found in Redis Docker images, its role is to safely switch user privileges, not to process arbitrary paths in a way that would trigger this specific stack exhaustion vulnerability. Therefore, there's no direct threat to Redis itself from this particular Go vulnerability.</p>
redis	7.4.5-alpine	CVE-2022-30630	<p>CVE-2022-30630 do not impact Redis because Redis itself is written in C, not Go, and therefore does not use Go's io/fs or path/filepath libraries. The gosu utility, although a Go binary often present in Redis images, is used for user switching, not for processing file paths in a way that would trigger these specific Glob vulnerabilities. Thus, the core Redis functionality and its data remain unaffected.</p>
redis	7.4.5-alpine	CVE-2023-29403	<p>CVE-2023-29403 (GO-2023-1840), does not directly impact Redis's operation. This is because Redis itself is written in C, not Go, and therefore doesn't use the Go runtime or its libraries where the vulnerability lies. While the gosu utility, often found in Redis Docker images, is a Go binary, its function doesn't involve scenarios that would exploit this specific vulnerability. In essence, gosu isn't designed to perform the kind of file operations or register handling that would trigger the issues described in this CVE.</p>
argocli	v3.6.7-cap-CR-28355	CVE-2025-8556	<p>The vulnerable code is not reachable or executable from any argocli code path. The code does not use CIRCL's FourQ implementation. Also it does not invoke vulnerable cryptographic functions.</p>

Image	Tag	CVE	Mitigation
cf-argocd-extras	0.5.7	CVE-2025-0426	<p>Summary: CVE-2025-0426 describes a Denial of Service vulnerability in the Kubernetes kubelet component, where unauthenticated requests to the read-only HTTP endpoint can fill up node disk space via the checkpoint API, potentially leading to node unavailability.</p> <p>Mitigation: Argo service does not directly interact with kubelet endpoints. It communicates exclusively with the Kubernetes API server (kube-apiserver) to manage the desired state of applications. Therefore, the service does not make any requests to kubelet's read-only or write endpoints, nor does it depend on this functionality for its operation.</p> <p>As a result, this vulnerability does not directly impact the functionality.</p>
cf-argocd-extras	0.5.7	CVE-2024-9042	<p>This vulnerability is not applicable to Argo services, as it cannot be deployed on Windows nodes. The service runs exclusively on Linux-based nodes, and the affected /logs/query API endpoint is only present and exploitable on Windows nodes. Therefore, this issue does not pose any risk to Argo environments.</p>
redis	7.4.2-alpine	CVE-2022-30632	<p>CVE-2022-30632 vulnerability in Go's path/filepath.Glob library, affecting gosu (if compiled with an old Go version), does not impact Redis's functionality or security. Redis is written in C and doesn't use Go's path/filepath.Glob. While gosu is a Go binary often found in Redis Docker images, its role is to safely switch user privileges, not to process arbitrary paths in a way that would trigger this specific stack exhaustion vulnerability. Therefore, there's no direct threat to Redis itself from this particular Go vulnerability.</p>
redis	7.4.2-alpine	CVE-2022-30630	<p>CVE-2022-30630 do not impact Redis because Redis itself is written in C, not Go, and therefore does not use Go's io/fs or path/filepath libraries. The gosu utility, although a Go binary often present in Redis images, is used for user switching, not for processing file paths in a way that would trigger these specific Glob vulnerabilities. Thus, the core Redis functionality and its data remain unaffected.</p>
redis	7.4.2-alpine	CVE-2023-29403	<p>CVE-2023-29403 (GO-2023-1840), does not directly impact Redis's operation. This is because Redis itself is written in C, not Go, and therefore doesn't use the Go runtime or its libraries where the vulnerability lies. While the gosu utility, often found in Redis Docker images, is a Go binary, its function doesn't involve scenarios that would exploit this specific vulnerability. In essence, gosu isn't designed to perform the kind of file operations or register handling that would trigger the issues described in this CVE.</p>

argo-platform-promotion-orchestrator	1.3525.2-onprem-45cda44	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
cf-api	21.279.7	CVE-2024-11023	CVE-2024-11023: Firebase JavaScript SDK utilizes a "FIREBASE_DEFAULTS" cookie to store configuration data, including an "_authTokenSyncURL" field used for session synchronization. If this cookie field is preset via an attacker by any other method, the attacker can manipulate the "_authTokenSyncURL" to point to their own server and it would allow an actor to capture user session data transmitted by the SDK. As it stems from the description, this issue affects only browser usage of Firebase SDK, and not relevant for server-side JS because of absence of cookies per se.
cf-api	21.279.7	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
cf-api	21.279.7	CVE-2021-3377	The attacker cannot inject an XSS vulnerability into the logs due to our input validation. The only possible avenue for such an attack is to invoke an external service through a codefresh step in pipeline, which could potentially introduce HTML content into the logs. However, even in this scenario, Codefresh utilizes this library exclusively when a customer attempts to download logs in HTML format. This is distinct from the Codefresh logs viewer and is unrelated to it.
cf-api	21.279.7	CVE-2022-23539	We do not configure the jsonwebtoken library to use custom key types or algorithms, thus the default settings are used. As a result, the vulnerability does not affect our application since it only impacts configurations using invalid key types / algorithm combinations, which we do not utilize.
cf-broadcaster	1.13.2	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
cf-container-logger	1.12.8	CVE-2024-11023	CVE-2024-11023: Firebase JavaScript SDK utilizes a "FIREBASE_DEFAULTS" cookie to store configuration data, including an "_authTokenSyncURL" field used for session synchronization. If this cookie field is preset via an attacker by any other method, the attacker can manipulate the "_authTokenSyncURL" to point to their own server and it would allow an actor to capture user session data transmitted by the SDK. As it stems from the description, this issue affects only browser usage of Firebase SDK, and not relevant for server-side JS because of absence of cookies per se.
cf-deploy-kubernetes	16.2.9	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-deploy-kubernetes	16.2.9	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-deploy-kubernetes	16.2.9	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-deploy-kubernetes	16.2.9	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-git-cloner	10.3.2	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-platform-analytics	0.50.4	CVE-2022-36313	The vulnerable package "file-type" is nested in "decompress" package. The CVE-2022-36313 vulnerability relates specifically to .mkv file type handling. The decompress package utilizes file-type exclusively for detecting types such as tar, tarbz2, targz, and zip. Therefore, the service is not affected by this vulnerability.
cf-platform-analytics	0.50.4	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
cf-platform-analytics	0.50.4	CVE-2024-27088	Our approach mitigates the vulnerability by enforcing simplified function naming conventions and prioritizing updated dependencies that prevent script stalls caused by complex function declarations
charts-manager	1.23.3	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
consul	1.21.2-debian-12-r0	PRISMA-2023-0056	latest upstream version
context-manager	2.34.4	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
engine	1.178.2	CVE-2024-11023	CVE-2024-11023: Firebase JavaScript SDK utilizes a "FIREBASE_DEFAULTS" cookie to store configuration data, including an "_authTokenSyncURL" field used for session synchronization. If this cookie field is preset via an attacker by any other method, the attacker can manipulate the "_authTokenSyncURL" to point to their own server and it would allow an actor to capture user session data transmitted by the SDK. As it stems from the description, this issue affects only browser usage of Firebase SDK, and not relevant for server-side JS because of absence of cookies per se.
engine	1.178.2	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
engine	1.178.2	CVE-2024-29415	This package is not used inside our business logic to validate the loopback addresses thus we are not affected by this vulnerability.

engine	1.178.2	CVE-2024-28176	Service utilizes the jose module as nested module in jsonwebtoken. But does not perform any operation of unpacking decrypted text, and we don't use JWE at all. This vulnerability will not impact our service
gitops-dashboard-manager	1.14.24	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
pipeline-manager	3.139.4	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
runtime-environment-manager	3.41.3	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
tasker-kubernetes	1.26.20	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.

Gitops-runtime Version 0.21.0 - Published 01 July 2025			
Image	Tag	CVE	Mitigation
argocd	v2.14.9-2025-06-08-8821b48e	CVE-2025-0426	<p>Summary: CVE-2025-0426 describes a Denial of Service vulnerability in the Kubernetes kubelet component, where unauthenticated requests to the read-only HTTP endpoint can fill up node disk space via the checkpoint API, potentially leading to node unavailability.</p> <p>Mitigation: Argo service does not directly interact with kubelet endpoints. It communicates exclusively with the Kubernetes API server (kube-apiserver) to manage the desired state of applications. Therefore, the service does not make any requests to kubelet's read-only or write endpoints, nor does it depend on this functionality for its operation.</p> <p>As a result, this vulnerability does not directly impact the functionality.</p>
argocd	v2.14.9-2025-06-08-8821b48e	CVE-2024-40635	<p>Summary: CVE-2024-40635 describes an integer overflow vulnerability in containerd where specifying a UID or GID greater than the maximum 32-bit signed integer (2147483647) can result in the container running as root (UID 0), even if configured to run as a non-root user.</p> <p>Mitigation: This vulnerability is only triggered during the image build stage, specifically while installing Helm in the Dockerfile. It does not affect ArgoCD at runtime, as the build-time environment is isolated from the container runtime used in Kubernetes.</p>
argocd	v2.14.9-2025-06-08-8821b48e	CVE-2024-9042	<p>This vulnerability is not applicable to Argo services, as it cannot be deployed on Windows nodes. The service runs exclusively on Linux-based nodes, and the affected /logs/query API endpoint is only present and exploitable on Windows nodes. Therefore, this issue does not pose any risk to Argo environments.</p>
prometheus-nats-exporter	0.15.0	CVE-2023-42363	<p>The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.</p>
prometheus-nats-exporter	0.15.0	CVE-2023-42364	<p>Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.</p>
prometheus-nats-exporter	0.15.0	CVE-2023-42365	<p>Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.</p>
prometheus-nats-exporter	0.15.0	CVE-2023-42366	<p>Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.</p>
argo-rollouts	v1.7.2-cap-CR-28008	CVE-2025-0426	<p>Summary: CVE-2025-0426 describes a Denial of Service vulnerability in the Kubernetes kubelet component, where unauthenticated requests to the read-only HTTP endpoint can fill up node disk space via the checkpoint API, potentially leading to node unavailability.</p> <p>Mitigation: Argo service does not directly interact with kubelet endpoints. It communicates exclusively with the Kubernetes API server (kube-apiserver) to manage the desired state of applications. Therefore, the service does not make any requests to kubelet's read-only or write endpoints, nor does it depend on this functionality for its operation.</p> <p>As a result, this vulnerability does not directly impact the functionality.</p>
argo-rollouts	v1.7.2-cap-CR-28008	CVE-2024-9042	<p>This vulnerability is not applicable to Argo services, as it cannot be deployed on Windows nodes. The service runs exclusively on Linux-based nodes, and the affected /logs/query API endpoint is only present and exploitable on Windows nodes. Therefore, this issue does not pose any risk to Argo environments.</p>
argo-events	v1.9.2-cap-CR-29689	CVE-2025-30204	<p>The argo-events component includes github.com/golang-jwt/jwt as a transitive dependency through the module github.com/Azure/azure-sdk-for-go/sdk/storage/azqueue. This library is not used directly by our service logic, and no JWT token parsing or validation is performed via this path. Therefore, any potential issues or vulnerabilities in github.com/golang-jwt/jwt do not affect the behavior or security of our service.</p>

Onprem Version 2.8.6 - Published 12 June 2025			
Image	Tag	CVE	Mitigation
argo-platform-abac	1.3525.0-onprem-d01c752	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-analytics-reporter	1.3525.0-onprem-d01c752	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-api-events	1.3525.0-onprem-d01c752	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-api-graphql	1.3525.0-onprem-d01c752	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-api-graphql	1.3525.0-onprem-d01c752	CVE-2024-29415	This package is not used inside our business logic to validate the loopback addresses thus we are not affected by this vulnerability.
argo-platform-audit	1.3525.0-onprem-d01c752	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-broadcaster	1.3525.0-onprem-d01c752	CVE-2025-25288	Vulnerability nested in package @octokit/rest. It won't affect the service because the package added long time ago and it usage was deleted without cleaning dependency list. It will be deleted in next release.
argo-platform-broadcaster	1.3525.0-onprem-d01c752	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-broadcaster	1.3525.0-onprem-d01c752	CVE-2025-25290	Vulnerability nested in package @octokit/rest. It won't affect the service because the package added long time ago and it usage was deleted without cleaning dependency list. It will be deleted in next release.
argo-platform-broadcaster	1.3525.0-onprem-d01c752	CVE-2025-25289	Vulnerability nested in package @octokit/rest. It won't affect the service because the package added long time ago and it usage was deleted without cleaning dependency list. It will be deleted in next release.
argo-platform-cron-executor	1.3525.0-onprem-d01c752	CVE-2025-25289	Vulnerability nested in package @octokit/rest. It won't affect the service because the package added long time ago and it usage was deleted without cleaning dependency list. It will be deleted in next release.
argo-platform-cron-executor	1.3525.0-onprem-d01c752	CVE-2025-25288	Vulnerability nested in package @octokit/rest. It won't affect the service because the package added long time ago and it usage was deleted without cleaning dependency list. It will be deleted in next release.
argo-platform-cron-executor	1.3525.0-onprem-d01c752	CVE-2025-25290	Vulnerability nested in package @octokit/rest. It won't affect the service because the package added long time ago and it usage was deleted without cleaning dependency list. It will be deleted in next release.
argo-platform-cron-executor	1.3525.0-onprem-d01c752	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-event-handler	1.3525.0-onprem-d01c752	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-promotion-orchestrator	1.3525.0-onprem-d01c752	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-promotion-orchestrator	1.3525.0-onprem-d01c752	CVE-2024-29415	This package is not used inside our business logic to validate the loopback addresses thus we are not affected by this vulnerability.
cf-api	21.279.5	CVE-2024-11023	<p>CVE-2024-11023: Firebase JavaScript SDK utilizes a "FIREBASE_DEFAULTS" cookie to store configuration data, including an "_authTokenSyncURL" field used for session synchronization. If this cookie field is preset via an attacker by any other method, the attacker can manipulate the "_authTokenSyncURL" to point to their own server and it would allow an actor to capture user session data transmitted by the SDK.</p> <p>As it stems from the description, this issue affects only browser usage of Firebase SDK, and not relevant for server-side JS because of absence of cookies per session</p>
cf-api	21.279.5	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
cf-api	21.279.5	CVE-2022-23539	We do not configure the jsonwebtoken library to use custom key types or algorithms, thus the default settings are used. As a result, the vulnerability does not affect our application since it only impacts configurations using invalid key types / algorithm combinations, which we do not utilize.
cf-api	21.279.5	CVE-2021-3377	The attacker cannot inject an XSS vulnerability into the logs due to our input validation. The only possible avenue for such an attack is to invoke an external service through a codefresh step in pipeline, which could potentially introduce HTML content into the logs. However, even in this scenario, Codefresh utilizes this library exclusively when a customer attempts to download logs in HTML format. This is distinct from the Codefresh logs viewer and is unrelated to it.
cf-broadcaster	1.13.0	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
cf-deploy-kubernetes	16.2.6	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.

Onprem Version 2.8.6 - Published 12 June 2025			
Image	Tag	CVE	Mitigation
cf-deploy-kubernetes	16.2.6	CVE-2022-48174	CVE-2022-48174 describes a stack overflow vulnerability in the ash shell implementation (ash.c) in BusyBox versions prior to 1.35. This vulnerability may allow an attacker to achieve arbitrary code execution via specially crafted shell input. Our system is not affected by this vulnerability, as we do not use the ash shell or any BusyBox shell components in our software. As such, the CVE is not applicable to our product or deployment configuration.
cf-deploy-kubernetes	16.2.6	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-deploy-kubernetes	16.2.6	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-puller	8.0.20	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-puller	8.0.20	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-docker-puller	8.0.20	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-puller	8.0.20	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-pusher	6.0.17	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-pusher	6.0.17	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-pusher	6.0.17	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-pusher	6.0.17	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-git-cloner	10.2.0	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-git-cloner	10.2.0	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-git-cloner	10.2.0	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-git-cloner	10.2.0	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-git-cloner	10.2.0	CVE-2022-48174	CVE-2022-48174 describes a stack overflow vulnerability in the ash shell implementation (ash.c) in BusyBox versions prior to 1.35. This vulnerability may allow an attacker to achieve arbitrary code execution via specially crafted shell input. Our system is not affected by this vulnerability, as we do not use the ash shell or any BusyBox shell components in our software. As such, the CVE is not applicable to our product or deployment configuration.
cf-platform-analytics	0.50.2	CVE-2022-36313	The vulnerable package "file-type" is nested in "decompress" package.
cf-platform-analytics	0.50.2	CVE-2024-27088	The CVE-2022-36313 vulnerability relates specifically to .mkv file type handling. The decompress package utilizes file-type exclusively for detecting types such as tar, tarbz2, targz, and zip. Therefore, the service is not affected by this vulnerability. Our approach mitigates the vulnerability by enforcing simplified function naming conventions and prioritizing updated dependencies that prevent script stalls caused by complex function declarations
cf-platform-analytics	0.50.2	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
charts-manager	1.23.2	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
consul	1.21.1-debian-12-r3	PRISMA-2023-0056	latest upstream version
context-manager	2.34.3	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.

Onprem Version 2.8.6 - Published 12 June 2025			
Image	Tag	CVE	Mitigation
engine	1.178.0	CVE-2024-11023	<p>CVE-2024-11023: Firebase JavaScript SDK utilizes a "FIREBASE_DEFAULTS" cookie to store configuration data, including an "_authTokenSyncURL" field used for session synchronization. If this cookie field is preset via an attacker by any other method, the attacker can manipulate the "_authTokenSyncURL" to point to their own server and it would allow an actor to capture user session data transmitted by the SDK.</p> <p>As it stems from the description, this issue affects only browser usage of Firebase SDK, and not relevant for server-side JS because of absence of cookies per session</p>
engine	1.178.0	CVE-2020-36604	<p>Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.</p>
engine	1.178.0	CVE-2024-28176	<p>Service utilizes the jose module as nested module in jsonwebtoken. But does not perform any operation of unpacking decrypted text, and we don't use JWE at all. This vulnerability will not impact our service</p>
engine	1.178.0	CVE-2024-29415	<p>This package is not used inside our business logic to validate the loopback addresses thus we are not affected by this vulnerability.</p>
gitops-dashboard-manager	1.14.22	CVE-2020-36604	<p>Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.</p>
pikolo	0.14.3	CVE-2023-42363	<p>The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.</p>
pikolo	0.14.3	CVE-2023-42364	<p>Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.</p>
pikolo	0.14.3	CVE-2023-42365	<p>Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.</p>
pikolo	0.14.3	CVE-2023-42366	<p>Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.</p>
pikolo	0.14.3	CVE-2022-48174	<p>CVE-2022-48174 describes a stack overflow vulnerability in the ash shell implementation (ash.c) in BusyBox versions prior to 1.35. This vulnerability may allow an attacker to achieve arbitrary code execution via specially crafted shell input.</p> <p>Our system is not affected by this vulnerability, as we do not use the ash shell or any BusyBox shell components in our software.</p> <p>As such, the CVE is not applicable to our product or deployment configuration.</p>
pikolo	0.14.3	CVE-2022-30065	<p>The awk package is a nested package within BusyBox, and the vulnerability is associated with the use of awk. However, our service and its components do not utilize awk in any capacity. Therefore, this vulnerability does not impact the functionality or security of our service.</p>
pikolo	0.14.3	CVE-2022-28391	<p>We do not use DNS PTR records in any part of our resources or applications. DNS PTR records are used to reverse IP address mapping to domain names, which are often used in the network environment to identify devices. Since our service does not depend on this mechanism and does not use netstat for any operations or processes, the vulnerability related to the manipulation of PTR records through the netstat utility cannot have any effect.</p>
pipeline-manager	3.139.3	CVE-2020-36604	<p>Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.</p>
runtime-environment-manager	3.41.2	CVE-2020-36604	<p>Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.</p>
tasker-kubernetes	1.26.18	CVE-2020-36604	<p>Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.</p>

CVE Mitigations from V2.2.5 to V2.6.9			
Onprem version 2.7.13 - Published 20 May 2025			
Image	Tag	CVE	Mitigation
argo-platform-api-graphql	1.3344.2-onprem-3feba0e	CVE-2024-29415	This package is not used inside our business logic to validate the loopback addresses thus we are not affected by this vulnerability.
argo-platform-api-graphql	1.3344.2-onprem-3feba0e	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-api-graphql	1.3344.2-onprem-3feba0e	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-api-graphql	1.3344.2-onprem-3feba0e	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-api-graphql	1.3344.2-onprem-3feba0e	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-api-graphql	1.3344.2-onprem-3feba0e	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-docker-tag-pusher	1.3.15	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-tag-pusher	1.3.15	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-docker-tag-pusher	1.3.15	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
engine	1.177.7	CVE-2024-11023	CVE-2024-11023: Firebase JavaScript SDK utilizes a "FIREBASE_DEFAULTS" cookie to store configuration data, including an "_authTokenSyncURL" field used for session synchronization. If this cookie field is preset via an attacker by any other method, the attacker can manipulate the "_authTokenSyncURL" to point to their own server and it would allow an actor to capture user session data transmitted by the SDK. As it stems from the description, this issue affects only browser usage of Firebase SDK, and not relevant for server-side JS because of absence of cookies per se.
argo-platform-audit	1.3344.2-onprem-3feba0e	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-audit	1.3344.2-onprem-3feba0e	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-audit	1.3344.2-onprem-3feba0e	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-audit	1.3344.2-onprem-3feba0e	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
pipeline-manager	3.138.5	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
cf-debugger	1.3.7	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-debugger	1.3.7	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-api	21.274.15	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
cf-api	21.274.15	CVE-2022-23539	We do not configure the jsonwebtoken library to use custom key types or algorithms, thus the default settings are used. As a result, the vulnerability does not affect our application since it only impacts configurations using invalid key types / algorithm combinations, which we do not utilize.
consul	1.21.0-debian-12-r1	PRISMA-2023-0056	Latest upstream version
<u>argo-events</u>	v1.9.2-cap-CR-28072	CVE-2025-21613	The vulnerability in go-git allows argument injection via the file:// protocol, potentially enabling attackers to manipulate git-upload-pack parameters and execute unintended commands. Mitigation: Argo Events is not affected because it does not use the file:// protocol or local Git repositories. It interacts with remote repositories via HTTP/S or SSH webhooks and does not execute git-upload-pack directly.
engine	1.177.7	CVE-2024-28176	Service utilizes the jose module as nested module in jsonwebtoken. But does not perform any operation of unpacking decrypted text, and we don't use JWE at all. This vulnerability will not impact our service
engine	1.177.7	CVE-2024-29415	This package is not used inside our business logic to validate the loopback addresses thus we are not affected by this vulnerability.

CVE Mitigations from V2.2.5 to V2.6.9			
Onprem version 2.7.13 - Published 20 May 2025			
Image	Tag	CVE	Mitigation
engine	1.177.7	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
engine	1.177.7	CVE-2022-33987	Dependency is located in NPM, and not related to or used in app/package/run.
gitops-dashboard-manager	1.14.22	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
runtime-environment-manager	3.39.4	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-abac	1.3344.2-onprem-3feba0e	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-event-handler	1.3344.2-onprem-3feba0e	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-event-handler	1.3344.2-onprem-3feba0e	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-event-handler	1.3344.2-onprem-3feba0e	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-event-handler	1.3344.2-onprem-3feba0e	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-platform-analytics	0.49.87	CVE-2024-27088	Our approach mitigates the vulnerability by enforcing simplified function naming conventions and prioritizing updated dependencies that prevent script stalls caused by complex function declarations
argo-platform-api-events	1.3344.2-onprem-3feba0e	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-api	21.274.15	CVE-2021-3377	The attacker cannot inject an XSS vulnerability into the logs due to our input validation. The only possible avenue for such an attack is to invoke an external service through a codefresh step in pipeline, which could potentially introduce HTML content into the logs. However, even in this scenario, Codefresh utilizes this library exclusively when a customer attempts to download logs in HTML format. This is distinct from the Codefresh logs viewer and is unrelated to it.
argo-platform-abac	1.3344.2-onprem-3feba0e	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-abac	1.3344.2-onprem-3feba0e	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-abac	1.3344.2-onprem-3feba0e	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-abac	1.3344.2-onprem-3feba0e	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-broadcaster	1.13.0	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
argo-platform-cron-executor	1.3344.2-onprem-3feba0e	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
cf-docker-puller	8.0.20	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-puller	8.0.20	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-puller	8.0.20	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-docker-pusher	6.0.17	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-pusher	6.0.17	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-pusher	6.0.17	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.

CVE Mitigations from V2.2.5 to V2.6.9			
Onprem version 2.7.13 - Published 20 May 2025			
Image	Tag	CVE	Mitigation
cf-docker-pusher	6.0.17	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-puller	8.0.20	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-promotion-orchestrator	1.3344.2-onprem-3feba0e	CVE-2024-29415	This package is not used inside our business logic to validate the loopback addresses thus we are not affected by this vulnerability.
argo-platform-promotion-orchestrator	1.3344.2-onprem-3feba0e	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-promotion-orchestrator	1.3344.2-onprem-3feba0e	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-promotion-orchestrator	1.3344.2-onprem-3feba0e	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-promotion-orchestrator	1.3344.2-onprem-3feba0e	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-promotion-orchestrator	1.3344.2-onprem-3feba0e	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-platform-analytics	0.49.87	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
argo-platform-cron-executor	1.3344.2-onprem-3feba0e	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-cron-executor	1.3344.2-onprem-3feba0e	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-cron-executor	1.3344.2-onprem-3feba0e	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-cron-executor	1.3344.2-onprem-3feba0e	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-docker-builder	1.4.4	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-docker-builder	1.4.4	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-builder	1.4.4	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-builder	1.4.4	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-builder	1.4.4	CVE-2022-48174	CVE-2022-48174 describes a stack overflow vulnerability in the ash shell implementation (ash.c) in BusyBox versions prior to 1.35. This vulnerability may allow an attacker to achieve arbitrary code execution via specially crafted shell input. Our system is not affected by this vulnerability, as we do not use the ash shell or any BusyBox shell components in our software. As such, the CVE is not applicable to our product or deployment configuration.
cf-docker-builder	1.4.4	CVE-2022-30065	The awk package is a nested package within BusyBox, and the vulnerability is associated with the use of awk. However, our service and its components do not utilize awk in any capacity. Therefore, this vulnerability does not impact the functionality or security of our service.
pikolo	0.14.3	CVE-2022-28391	We do not use DNS PTR records in any part of our resources or applications. DNS PTR records are used to reverse IP address mapping to domain names, which are often used in the network environment to identify devices. Since our service does not depend on this mechanism and does not use netstat for any operations or processes, the vulnerability related to the manipulation of PTR records through the netstat utility cannot have any effect.
pikolo	0.14.3	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
pikolo	0.14.3	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
pikolo	0.14.3	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
pikolo	0.14.3	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.

CVE Mitigations from V2.2.5 to V2.6.9			
Onprem version 2.7.13 - Published 20 May 2025			
Image	Tag	CVE	Mitigation
pikolo	0.14.3	CVE-2022-48174	CVE-2022-48174 describes a stack overflow vulnerability in the ash shell implementation (ash.c) in BusyBox versions prior to 1.35. This vulnerability may allow an attacker to achieve arbitrary code execution via specially crafted shell input. Our system is not affected by this vulnerability, as we do not use the ash shell or any BusyBox shell components in our software. As such, the CVE is not applicable to our product or deployment configuration.
pikolo	0.14.3	CVE-2022-30065	The awk package is a nested package within BusyBox, and the vulnerability is associated with the use of awk. However, our service and its components do not utilize awk in any capacity. Therefore, this vulnerability does not impact the functionality or security of our service.
cf-debugger	1.3.7	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-git-cloner	10.2.0	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
context-manager	2.33.7	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
context-manager	2.33.7	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
context-manager	2.33.7	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
context-manager	2.33.7	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
context-manager	2.33.7	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-ui	14.97.51	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-ui	14.97.51	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-ui	14.97.51	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-ui	14.97.51	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-deploy-kubernetes	16.2.6	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-deploy-kubernetes	16.2.6	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-deploy-kubernetes	16.2.6	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-deploy-kubernetes	16.2.6	CVE-2022-48174	CVE-2022-48174 describes a stack overflow vulnerability in the ash shell implementation (ash.c) in BusyBox versions prior to 1.35. This vulnerability may allow an attacker to achieve arbitrary code execution via specially crafted shell input. Our system is not affected by this vulnerability, as we do not use the ash shell or any BusyBox shell components in our software. As such, the CVE is not applicable to our product or deployment configuration.
cf-deploy-kubernetes	16.2.6	CVE-2022-28391	We do not use DNS PTR records in any part of our resources or applications. DNS PTR records are used to reverse IP address mapping to domain names, which are often used in the network environment to identify devices. Since our service does not depend on this mechanism and does not use netstat for any operations or processes, the vulnerability related to the manipulation of PTR records through the netstat utility cannot have any effect.
argo-platform-api-events	1.3344.2-onprem-3feba0e	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-api-events	1.3344.2-onprem-3feba0e	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
charts-manager	1.22.3	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
argo-platform-ui	1.3344.2-onprem-3feba0e	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.

CVE Mitigations from V2.2.5 to V2.6.9			
Onprem version 2.7.13 - Published 20 May 2025			
Image	Tag	CVE	Mitigation
argo-platform-broadcaster	1.3344.2-onprem-3feba0e	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-event-handler	1.3344.2-onprem-3feba0e	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-broadcaster	1.3344.2-onprem-3feba0e	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-broadcaster	1.3344.2-onprem-3feba0e	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
argo-platform-ui	1.3344.2-onprem-3feba0e	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-ui	1.3344.2-onprem-3feba0e	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-ui	1.3344.2-onprem-3feba0e	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-git-cloner	10.2.0	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-git-cloner	10.2.0	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-git-cloner	10.2.0	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-git-cloner	10.2.0	CVE-2022-48174	CVE-2022-48174 describes a stack overflow vulnerability in the ash shell implementation (ash.c) in BusyBox versions prior to 1.35. This vulnerability may allow an attacker to achieve arbitrary code execution via specially crafted shell input. Our system is not affected by this vulnerability, as we do not use the ash shell or any BusyBox shell components in our software. As such, the CVE is not applicable to our product or deployment configuration.
cf-docker-builder	1.4.4	CVE-2022-28391	We do not use DNS PTR records in any part of our resources or applications. DNS PTR records are used to reverse IP address mapping to domain names, which are often used in the network environment to identify devices. Since our service does not depend on this mechanism and does not use netstat for any operations or processes, the vulnerability related to the manipulation of PTR records through the netstat utility cannot have any effect.
argo-platform-audit	1.3344.2-onprem-3feba0e	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-api-events	1.3344.2-onprem-3feba0e	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-api-events	1.3344.2-onprem-3feba0e	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-tag-pusher	1.3.15	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
runtime-environment-manager	3.39.4	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
runtime-environment-manager	3.39.4	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
runtime-environment-manager	3.39.4	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
runtime-environment-manager	3.39.4	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
chartmuseum	8795e993	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
chartmuseum	8795e993	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-broadcaster	1.3344.2-onprem-3feba0e	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-broadcaster	1.3344.2-onprem-3feba0e	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.

[illegible]

CVE Mitigations from V2.2.5 to V2.6.9			
Onprem version 2.7.12 - Published 20 May 2025			
Image	Tag	CVE	Mitigation
argo-platform-analytics-reporter	1.3344.0-onprem-5c8af92	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-analytics-reporter	1.3344.0-onprem-5c8af92	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-analytics-reporter	1.3344.0-onprem-5c8af92	CVE-2023-42363	The vulnerability affecting BusyBox and the xasprintf function does not affect the security of environments that use Node.js without using BusyBox directly
argo-platform-analytics-reporter	1.3344.0-onprem-5c8af92	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-analytics-reporter	1.3344.0-onprem-5c8af92	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-ui	1.3344.0-onprem-5c8af92	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-ui	1.3344.0-onprem-5c8af92	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-ui	1.3344.0-onprem-5c8af92	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-ui	1.3344.0-onprem-5c8af92	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-debugger	1.3.7	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-debugger	1.3.7	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-debugger	1.3.7	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-debugger	1.3.7	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-ui	14.97.51	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-ui	14.97.51	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-ui	14.97.51	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-ui	14.97.51	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
chartmuseum	8795e993	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
pikolo	0.14.3	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
pikolo	0.14.3	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
pikolo	0.14.3	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
pikolo	0.14.3	CVE-2022-28391	We do not use DNS PTR records in any part of our resources or applications. DNS PTR records are used to reverse IP address mapping to domain names, which are often used in the network environment to identify devices. Since our service does not depend on this mechanism and does not use netstat for any operations or processes, the vulnerability related to the manipulation of PTR records through the netstat utility cannot have any effect.
pikolo	0.14.3	CVE-2022-30065	cf-docker-builder
cf-docker-puller	8.0.20	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-docker-puller	8.0.20	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.

CVE Mitigations from V2.2.5 to V2.6.9			
Onprem version 2.7.12 - Published 20 May 2025			
Image	Tag	CVE	Mitigation
cf-docker-puller	8.0.20	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-puller	8.0.20	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-tag-pusher	1.3.15	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-tag-pusher	1.3.15	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-tag-pusher	1.3.15	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-tag-pusher	1.3.15	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
context-manager	2.33.7	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
context-manager	2.33.7	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
context-manager	2.33.7	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
context-manager	2.33.7	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
context-manager	2.33.7	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
context-manager	2.33.7	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-broadcaster	1.3344.0-onprem-5c8af92	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-broadcaster	1.3344.0-onprem-5c8af92	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-broadcaster	1.3344.0-onprem-5c8af92	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-broadcaster	1.3344.0-onprem-5c8af92	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-broadcaster	1.3344.0-onprem-5c8af92	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-broadcaster	1.3344.0-onprem-5c8af92	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-git-cloner	10.2.0	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-git-cloner	10.2.0	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-git-cloner	10.2.0	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-git-cloner	10.2.0	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-git-cloner	10.2.0	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-git-cloner	10.2.0	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.

CVE Mitigations from V2.2.5 to V2.6.9			
Onprem version 2.7.12 - Published 20 May 2025			
Image	Tag	CVE	Mitigation
cf-git-cloner	10.2.0	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
tasker-kubernetes	1.26.18	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
charts-manager	1.22.3	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
cf-deploy-kubernetes	16.2.6	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-deploy-kubernetes	16.2.6	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-deploy-kubernetes	16.2.6	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-deploy-kubernetes	16.2.6	CVE-2022-28391	We do not use DNS PTR records in any part of our resources or applications. DNS PTR records are used to reverse IP address mapping to domain names, which are often used in the network environment to identify devices. Since our service does not depend on this mechanism and does not use netstat for any operations or processes, the vulnerability related to the manipulation of PTR records through the netstat utility cannot have any effect.
cf-platform-analytics	0.49.86	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
cf-platform-analytics	0.49.86	CVE-2024-27088	Our approach mitigates the vulnerability by enforcing simplified function naming conventions and prioritizing updated dependencies that prevent script stalls caused by complex function declarations
argo-platform-cron-executor	1.3344.0-onprem-5c8af92	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-cron-executor	1.3344.0-onprem-5c8af92	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
argo-platform-cron-executor	1.3344.0-onprem-5c8af92	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-cron-executor	1.3344.0-onprem-5c8af92	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-cron-executor	1.3344.0-onprem-5c8af92	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-builder	1.4.4	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
cf-docker-builder	1.4.4	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-builder	1.4.4	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-builder	1.4.4	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-builder	1.4.4	CVE-2022-30065	We do not use DNS PTR records in any part of our resources or applications. DNS PTR records are used to reverse IP address mapping to domain names, which are often used in the network environment to identify devices. Since our service does not depend on this mechanism and does not use netstat for any operations or processes, the vulnerability related to the manipulation of PTR records through the netstat utility cannot have any effect.
cf-docker-builder	1.4.4	CVE-2022-28391	We do not use DNS PTR records in any part of our resources or applications. DNS PTR records are used to reverse IP address mapping to domain names, which are often used in the network environment to identify devices. Since our service does not depend on this mechanism and does not use netstat for any operations or processes, the vulnerability related to the manipulation of PTR records through the netstat utility cannot have any effect.
cf-broadcaster	1.13.0	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
argo-platform-event-handler	1.3344.0-onprem-5c8af92	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.

CVE Mitigations from V2.2.5 to V2.6.9			
Onprem version 2.7.12 - Published 20 May 2025			
Image	Tag	CVE	Mitigation
argo-platform-event-handler	1.3344.0-onprem-5c8af92	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-event-handler	1.3344.0-onprem-5c8af92	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-event-handler	1.3344.0-onprem-5c8af92	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
argo-platform-event-handler	1.3344.0-onprem-5c8af92	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-pusher	6.0.17	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-pusher	6.0.17	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-pusher	6.0.17	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
cf-docker-pusher	6.0.17	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
argo-platform-api-events	1.3344.0-onprem-5c8af92	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-api-events	1.3344.0-onprem-5c8af92	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
pikolo	0.14.3	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
argo-platform-api-events	1.3344.0-onprem-5c8af92	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-api-events	1.3344.0-onprem-5c8af92	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-api-events	1.3344.0-onprem-5c8af92	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
docker.io/bitnami/consul	1.21.0-debian-12-r1	PRISMA-2023-0056	Latest upstream version
chartmuseum	8795e993	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
chartmuseum	8795e993	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
chartmuseum	8795e993	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
chartmuseum	8795e993	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
gitops-dashboard-manager	1.14.22	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek 'clone' method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
argo-platform-api-graphql	1.3344.0-onprem-5c8af92	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-api-graphql	1.3344.0-onprem-5c8af92	CVE-2024-29415	This package is not used inside our business logic to validate the loopback addresses thus we are not affected by this vulnerability.
argo-platform-api-graphql	1.3344.0-onprem-5c8af92	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
argo-platform-api-graphql	1.3344.0-onprem-5c8af92	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-api-graphql	1.3344.0-onprem-5c8af92	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.

CVE Mitigations from V2.2.5 to V2.6.9			
Onprem version 2.7.12 - Published 20 May 2025			
Image	Tag	CVE	Mitigation
argo-platform-api-graphql	1.3344.0-onprem-5c8af92	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
runtime-environment-manager	3.39.4	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
runtime-environment-manager	3.39.4	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
runtime-environment-manager	3.39.4	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
runtime-environment-manager	3.39.4	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
runtime-environment-manager	3.39.4	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-abac	1.3344.0-onprem-5c8af92	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-abac	1.3344.0-onprem-5c8af92	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-abac	1.3344.0-onprem-5c8af92	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
argo-platform-abac	1.3344.0-onprem-5c8af92	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-abac	1.3344.0-onprem-5c8af92	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
engine	1.177.7	CVE-2024-29415	This package is not used inside our business logic to validate the loopback addresses thus we are not affected by this vulnerability.
engine	1.177.7	CVE-2024-11023	<p>Firebase JavaScript SDK utilizes a "FIREBASE_DEFAULTS" cookie to store configuration data, including an "_authTokenSyncURL" field for session synchronization. If this cookie field is preset via an attacker by any other method, the attacker can manipulate the "_authTokenSyncURL" to point to their own server and it would allow an actor to capture user session data transmitted by the SDK.</p> <p>As it stems from the description, this issue affects only browser usage of Firebase SDK, and not relevant for server-side JS because of absence of cookies per se.</p>
engine	1.177.7	CVE-2022-33987	Dependency is located in NPM, and not related to or used in app/package/run.
engine	1.177.7	CVE-2020-36604	Hoek package is used only within the Joi package which is responsible for data validation using schema. Vulnerable "clone" function is used in very few Joi functions. Our risk assessment confirms that vulnerable Hoek "clone" method does not affect any Codefresh business logic in the Joi functions where we exploit the business logic.
engine	1.177.7	CVE-2024-28176	Service utilizes the jose module as nested module in jsonwebtoken. But does not perform any operation of unpacking decrypted text, and we don't use JWE at all. This vulnerability will not impact our service
argo-platform-promotion-orchestrator	1.3344.0-onprem-5c8af92	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-promotion-orchestrator	1.3344.0-onprem-5c8af92	CVE-2024-29415	This package is not used inside our business logic to validate the loopback addresses thus we are not affected by this vulnerability.
argo-platform-promotion-orchestrator	1.3344.0-onprem-5c8af92	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-promotion-orchestrator	1.3344.0-onprem-5c8af92	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
argo-platform-promotion-orchestrator	1.3344.0-onprem-5c8af92	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-promotion-orchestrator	1.3344.0-onprem-5c8af92	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-promotion-orchestrator	1.3344.0-onprem-5c8af92	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.

CVE Mitigations from V2.2.5 to V2.6.9			
Onprem version 2.7.12 - Published 20 May 2025			
Image	Tag	CVE	Mitigation
argo-platform-audit	1.3344.0-onprem-5c8af92	CVE-2023-26108	The identified vulnerability is associated with the StreamableFile API. Codefresh does not utilize the StreamableFile API for returning files. Additionally, we do not allow downloading of files from our services.
argo-platform-audit	1.3344.0-onprem-5c8af92	CVE-2023-42363	The vulnerability affects the xasprintf function in BusyBox. It does not impact the security of environments using Node.js, provided BusyBox is not used directly in those environments.
argo-platform-audit	1.3344.0-onprem-5c8af92	CVE-2023-42365	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-audit	1.3344.0-onprem-5c8af92	CVE-2023-42366	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.
argo-platform-audit	1.3344.0-onprem-5c8af92	CVE-2023-42364	Service mitigates potential vulnerabilities by not accepting and utilizing user input in operations involving text files and the AWK utility. This approach minimizes risks associated with external data manipulation, ensuring a more secure handling of file operations within our Node.js environment.