

添加商品

PUT /ecommerce/product/1

```
{
  "name" : "gaolujie yagao",
  "desc" : "gaoxiao meibai",
  "price" : 30,
  "producer" : "gaolujie producer",
  "tags": [ "meibai", "fangzhu" ]
}
```

PUT /ecommerce/product/2

```
{
  "name" : "jiajieshi yagao",
  "desc" : "youxiao fangzhu",
  "price" : 25,
  "producer" : "jiajieshi producer",
  "tags": [ "fangzhu" ]
}
```

PUT /ecommerce/product/3

```
{
  "name" : "zhonghua yagao",
  "desc" : "caoben zhiwu",
  "price" : 40,
  "producer" : "zhonghua producer",
  "tags": [ "qingxin" ]
}
```

PUT /ecommerce/product/4

```
{
  "name" : "special yagao",
  "desc" : "special meibai",
  "price" : 44,
```

```
"producer" : "special producer",
"tags": [ "meibai", "fangzhu" ]
}
```

修改索引

PUT /ecommerce/product/1

```
{
  "name" : "jiaqiangban gaolujie yagao",
  "desc" : "gaoxiao meibai",
  "price" : 30,
  "producer" : "gaolujie producer",
  "tags": [ "meibai", "fangzhu" ]
}
```

返回响应:

```
{
  "_index": "ecommerce",
  "_type": "product",
  "_id": "1",
  "_version": 2,
  "result": "updated",
  "_shards": {
    "total": 2,
    "successful": 1,
    "failed": 0
  },
  "created": false
}
```

需要将所有的字段信息**field**填入去完成修改

单独修改无需所有字段:

将产品价格改为24,并添加新的字段

POST /ecommerce/product/1/_update

```
{
  "doc": {
```

```
"price": 24,  
  "flag": "true"  
}  
}
```

Updates can also be performed by using simple scripts. This example uses a script to increment the age by 5:

```
POST /customer/_doc/1/_update?pretty  
{  
  "script" : "ctx._source.age += 5"  
}
```

[COPY AS CURL](#) [VIEW IN CONSOLE](#) 

In the above example, `ctx._source` refers to the current source document that is about to be updated.

查询索引信息:

GET /ecommerce/product/1 //查询id为1的商品

1. 查询索引Query String Search

GET /ecommerce/product/_search 搜索全部

```
{
  "took": 10,
  "timed_out": false,
  "_shards": {
    "total": 5,
    "successful": 5,
    "skipped": 0,
    "failed": 0
  },
  "hits": {
    "total": 2,
    "max_score": 1,
    "hits": [
      {
        "_index": "ecommerce",
        "_type": "product",
        "_id": "2",
        "_score": 1,
        "_source": {
          "name": "jiajieshi yagao",
          "desc": "youxiao fangzhu",
          "price": 25,
          "producer": "jiajieshi producer",
          "tags": [
            "fangzhu"
          ]
        }
      },
      {
        "_index": "ecommerce",
        "_type": "product",
        "_id": "1",
        "_score": 1,
        "_source": {
          "name": "gaolujie yagao",
          "desc": "gaoxiao meibai",
          "price": 24,
          "producer": "gaolujie producer",
          "tags": [
            "meibai",
            "fangzhu"
          ]
        }
      }
    ]
  }
}
```

查询商品名包含牙膏且价格降序排序

GET /ecommerce/product/_search?q=name:yagao&sort=price:desc

2. Query Domain specified Language,特定领域语法

查询索引的产品信息:

GET /ecommerce/product/_search

```
{
  "query":{"match_all":{}}
}
```

查询商品名包含牙膏且价格降序排序

GET /ecommerce/product/_search

```
{
  "query": {
    "match": {
      "name": "yagao"
    }
  },
  "sort": [
    {
      "price": {
        "order": "desc"
      }
    }
  ]
}
```

分页显示数据

GET /ecommerce/product/_search

```
{
  "query": {
    "match": {
      "name": "yagao"
    }
  },
  "sort": [
```

```
{
  "price": {
    "order": "desc"
  }
},
"from": 0
, "size": 1
}
```

查询只有名字和价格的信息

GET /ecommerce/product/_search

```
{
  "query": {
    "match_all": {}
  },
  "_source": ["name", "price"]
}
```

搜索商品名称包含yagao且价格大于20小于30的商品:

GET /ecommerce/product/_search

```
{
  "query": {
    "bool": {
      "must": [
        {
          "match": {
            "name": "yagao"
          }
        }
      ]
    },
    "filter": {
      "range": {
        "price": {
          "gte": 20,
          "lte": 30
        }
      }
    }
  }
}
```

```
    }  
  }  
}  
}  
}  
}
```

全文检索

GET ecommerce/product/_search

```
{  
  "query": {  
    "match": {  
      "producer": "special producer"  
    }  
  }  
}
```

```
"took": 20,  
"timed_out": false,  
"_shards": {  
  "total": 5,  
  "successful": 5,  
  "skipped": 0,  
  "failed": 0  
},  
"hits": {  
  "total": 4,  
  "max_score": 0.8092568,  
  "hits": [  
    {  
      "_index": "ecommerce",  
      "_type": "product",  
      "_id": "4",  
      "_score": 0.8092568,  
      "_source": {  
        "name": "special yagao",  
        "desc": "special meibai",  
        "price": 44,  
        "producer": "special mingao producer",  
        "tags": [  
          "meibai",  
          "fangzhu"  
        ]  
      }  
    }  
  ]  
}
```



```
    ],
    },
    {
      "_index": "ecommerce",
      "_type": "product",
      "_id": "1",
      "score": 0.2876821,
      "_source": {
        "name": "gaolujie yagao",
        "desc": "gaoxiao meibai",
        "price": 30,
        "producer": "gaolujie producer",
        "tags": [
          "meibai",
          "fangzhu"
        ]
      }
    },
    {
      "_index": "ecommerce",
      "_type": "product",
      "_id": "3",
      "score": 0.2876821,
      "_source": {
        "name": "zhonghua yagao"
      }
    }
  ]
}
```

这里全文检索使用倒排索引机制:

首先会对producer字段进行拆解,拆解信息如下,数字为文档ID

special 4

mrgao 4

producer 1234

gaolujie 1

zhonghua 3

jiejieshi 2

当全文检索查询special,producer.会找到special 4 与producer 1234

短语搜索:与全文检索不同,不会将输入的字符串拆解,去倒排索引去查,只要匹配任意拆解后的单词成功即可返回结果,**phrase search** 要求必须按输入的字符串搜索,不能拆解查询

下面这个有查询结果

GET ecommerce/product/_search

```
{  
  "query": {  
    "match_phrase": {  
      "producer": "special mrgao producer"  
    }  
  }  
}
```

而这个查询无结果

GET ecommerce/product/_search

```
{  
  "query": {  
    "match_phrase": {  
      "producer": "special producer"  
    }  
  }  
}
```

查询高亮显示:

GET ecommerce/product/_search

```
{  
  "query": {  
    "match": {  
      "producer": "special"  
    }  
  }
```

```

},
"highlight": {
  "fields": {
    "producer": {}
  }
}
}
}

```

- 删除索引信息:

DELETE /ecommerce/product/3

返回信息:

```

{
  "_index": "ecommerce",
  "_type": "product",
  "_id": "3",
  "_version": 2,
  "result": "deleted",
  "_shards": {
    "total": 2,
    "successful": 1,
    "failed": 0
  },
  "_seq_no": 1,
  "_primary_term": 1
}

```

- 批处理添加, 修改以及删除

As a quick example, the following call indexes two documents (ID 1 - John Doe and ID 2 - Jane Doe) in one bulk operation:

POST /customer/_doc/_bulk?pretty

```

{"index":{"_id":"1"}}
{"name": "John Doe" }
{"index":{"_id":"2"}}
{"name": "Jane Doe" }

```

This example updates the first document (ID of 1) and then deletes the second document (ID of 2) in one bulk operation:

```
POST /customer/_doc/_bulk?pretty
```

```
{"update":{"_id":"1"}}
```

```
{"doc": { "name": "John Doe becomes Jane Doe" } }
```

```
{"delete":{"_id":"2"}}
```

批处理不会因为其中一个失败而造成整个处理过程失败，仍会处理其他文档操作。并会返回一个操作的状态。