TOOLS ~

TRENDING Analysing Storage Usage on a Raspberry Pi with Ncdu

BUY Y



BY MATT ON SEPTEMBER 21, 2017

CATEGORIES ~

HOME



TUTORIALS & HELP


20

YOU ARE AT: Home » Hardware » Sensors » DHT11 Temperature and Humidity Sensor and the Raspberry Pi

DHT11 Temperature and Humidity Sensor and the Raspberry Pi

BERRYCLIP ~


SENSORS, TUTORIALS & HELP



The DHT11 is a low-cost temperature and humidity sensor. It isn't the fastest sensor around but its cheap price makes it useful for experimenting or projects where you don't require new readings multiple times a second. The device only requires three connections to the Pi. +3.3v, ground and one GPIO pin.

DHT11 Specifications

The device itself has four pins but one of these is not used. You can buy the 4-pin device on its own or as part of a 3-pin module.



The modules have three pins and are easy to connect directly to the Pi's GPIO header.

- Humidity: 20-80% (5% accuracy)
- Temperature : 0-50°C (±2°C accuracy)



SITE MAP

Q

RECENT POPULAR NEWS

CONTACT US



JANUARY 14, 2018

Ultimate Alexa Skill for your
Raspberry Pi

2 2

Q 9

O n

20

Q 0



Building My Raspberry Pi IKEA Retro Arcade Table

DECEMBER 16, 2017

NOVEMBER 6 2017

OCTOBER 31, 2017

OCTOBER 28, 2017



How to Rotate the Raspberry Pi Display Output



Halloween Pumpkin with Servo Controlled Eyes



Analysing Storage Usage on a Raspberry Pi with Ncdu

Search Se	arc

CATEGORIES

3D Printing

Add-ons
BBC Micro:bit
BerryClip

Books

https://www.raspberrypi-spy.co.uk/2017/09/dht11-temperature-and-humidity-sensor-raspberry-pi/

The manufacturers do not recommended that you read data from this device more than once per 2 seconds. If you do you may get incorrect readings.

Hardware Setup

The 4-pin device will require a resistor (4.7K-10K) to be placed between Pin 1 (3.3V) and Pin 2 (Data).


The 3-pin modules will usually have this resistor included which makes the wiring a bit easier. For this reason I got hold of the module which I could then attach to the Pi with a piece of 3-way Dupont cable.

Different suppliers may wire the module pins differently so check the PCB markings to identify Vcc (+), data and Ground (-).

The 3 pins should be connected to the Pi as shown in the table below :

DHT Pin	Signal	Pi Pin
1	3.3V 1	
2	Data/Out	11 (GPIO17)
3	not used	-
4	Ground	6 or 9

Your data pin can be attached to any GPIO pin you prefer. In my example I am using physical pin 11 which is GPIO 17. Here is a 4-pin sensor connected to the Pi's GPIO header. It has a 10K resistor between pin 1 (3.3V) and 2 (Data/Out).




bolly I I	
Camera Module	
Cases	
Events	
General	
Hardware	
I2C	
Infographics	
Minecraft	
Model A+	
Model B+	
News	
Pi 2 Model B	
Pi Models	
Pi Zero	
Power	
Programming	
Python	
Raspbian	
RetroGaming	
Robotics	
Sensors	
Software	
SPI	
Tutorials & Help	



TAGS





Python Library

The DHT11 requires a specific protocol to be applied to the data pin. In order to save time trying to implement this yourself it's far easier to use the Adafruit DHT library.

The library deals with the data that needs to be exchanged with the sensor but it is sensitive to timing issues. The Pi's operating system may get in the way while performing other tasks so to compensate for this the library requests a number of readings from the device until it gets one that is valid.

Software Setup

To start with update your package lists and install a few Python libraries :


```
sudo apt-get update
sudo apt-get install build-essential python-dev
```

Then clone the Adafruit library from their repository :

git clone https://github.com/adafruit/Adafruit_Python_DHT.git
cd Adafruit_Python_DHT

Then install the library for Python 2 and Python 3 :

sudo python setup.py install
sudo python3 setup.py install



Archives Select Month

Hopefully at this point the library is installed and ready to be used within a Python script.

Adafruit Example Python Script

Adafruit provide an example script that you can use to check your sensor is operating correctly.

```
cd ~
cd Adafruit_Python_DHT
cd examples
```

Then:

```
python AdafruitDHT.py 11 17
```

The example script takes two parameters. The first is the sensor type so is set to "11" to represent the DHT11. The second is the GPIO number so for my example I am using "17" for GPIO17. You can change this if you are using a different GPIO pin for your data/out wire.

You should see an output similar to this:

```
Temp=22.0* Humidity=68.0%
```

Using the Library In Other Python Scripts

Once the Adafruit library is installed and you've got the example script to work you can use the sensor in your own scripts. Simply import the module, setup a few variables and call the "read_retry" function:

```
import Adafruit_DHT

# Set sensor type : Options are DHT11,DHT22 or AM2302
sensor=Adafruit_DHT.DHT11

# Set GPIO sensor is connected to
gpio=17

# Use read_retry method. This will retry up to 15 times to
# get a sensor reading (waiting 2 seconds between each retry).
humidity, temperature = Adafruit_DHT.read_retry(sensor, gpio)

# Reading the DHT11 is very sensitive to timings and occasionally
# the Pi might fail to get a valid reading. So check if readings are valid.
if humidity is not None and temperature is not None:
    print('Temp={0:0.1f}*C Humidity={1:0.1f}%'.format(temperature, humidity))
else:
    print('Failed to get reading. Try again!')
```

This script can be downloaded directly to your Pi using:

```
wget https://bitbucket.org/MattHawkinsUK/rpispy-misc/raw/master/python/dht11.py
```

and run using:

```
python dht11.py
```

Buying a DHT11

The DHT11 is available from many electrical component sellers. Here are a selection:


- Adafruit
- The Pi Hut
- eBay
- Amazon
- CPC

Some may only sell the device itself so you may need to shop around if you would prefer the 3-pin module.

Final Thoughts

The DHT11 is probably best suited for projects where rapid data readings are not required and the environment is not expected to see sudden changes in temperature or humidity. A weather station would be an idea project but a central heating controller may require something different.

For projects that need a faster temperature reading rate (<2 sec) I would probably use a DS18B20 as they respond much faster to changes in temperature. But with both these sensors costing <\$5 you can probably afford to buy both and experiment.



Your Name		
Your Email		
Your Website		
Your Website		
		POST COMMENT

POPULAR POSTS

Unofficial site devoted to the Raspberry Pi credit card sized computer offering tutorials, guides, resources, scripts and downloads. We hope to help everyone get the most out of their Pi by providing clear, simple articles on configuring, programming

ABOUT

and operating it.

JULY 27, 2012 Q 99 JANUARY 14, 2018 Q 2 16×2 LCD Module Control Using Ultimate Alexa Skill for your Python Raspberry Pi OCTOBER 20, 2013 DECEMBER 16, 2017 Q 9 **2** 96 Analogue Sensors On The Raspberry Building My Raspberry Pi IKEA Retro Pi Using An MCP3008 Arcade Table SEPTEMBER 19, 2014 NOVEMBER 6, 2017 **2** 83 Q 0 Top 5 Reasons The Raspberry Pi How to Rotate the Raspberry Pi Sucks Display Output

RECENT POSTS

Entries RSS | Comments RSS

This site is not associated with the official Raspberrypi.org site or the Raspberry Pi Foundation. Raspberry Pi is a trademark of the Raspberry Pi Foundation.

Copyright © 2017 - All Rights Reserved - Matt Hawkins