

Bit Manipulation

TABLE OF CONTENTS

1. Number System and Conversion
2. Addition of two binary numbers
3. Bitwise Operators
4. Negative Numbers
5. Ranges of Numbers
6. Importance of Constraints



Notes

arr[] = [5, 2, 8, 2, 7, 5, 3, 7, 5]

↓ Sorting

arr[] = [2, 2, 3, 5, 5, 5, 7, 7, 8]



Decimal Number System

→ digit can vary from 0 to 9. (base-10)

$$342 \rightarrow 3 \times 10^2 + 4 \times 10^1 + 2 \times 10^0$$

$$2563 \rightarrow 2000 + 500 + 60 + 3$$

$$= 2 \times 10^3 + 5 \times 10^2 + 6 \times 10^1 + 3 \times 10^0$$

Binary Number System

→ digit can either be 0 or 1. (base-2)

$$110 \rightarrow 1 \times 2^2 + 1 \times 2^1 + 0 \times 2^0 = 4 + 2 + 0 = \underline{6}$$

$$1011 \rightarrow 1 \times 2^3 + 0 \times 2^2 + 1 \times 2^1 + 1 \times 2^0$$

$$\rightarrow 8 + 0 + 2 + 1 \Rightarrow \underline{\underline{11}}$$



1. Binary to Decimal Conversion

• $(1101)_2 = (13)_{10}$

$$\begin{array}{r} 1101 \\ \begin{array}{l} \rightarrow 1 \times 2^0 \rightarrow 1 \\ \rightarrow 0 \times 2^1 \rightarrow 0 \\ \rightarrow 1 \times 2^2 \rightarrow 4 \\ \rightarrow 1 \times 2^3 \rightarrow 8 \end{array} \end{array}$$

• $(1011010)_2 = (90)_{10}$

$$\begin{array}{r} 1011010 \\ \begin{array}{l} \rightarrow 0 \times 2^0 \rightarrow 0 \\ \rightarrow 1 \times 2^1 \rightarrow 2 \\ \rightarrow 0 \times 2^2 \rightarrow 0 \\ \rightarrow 1 \times 2^3 \rightarrow 8 \\ \rightarrow 1 \times 2^4 \rightarrow 16 \\ \rightarrow 0 \times 2^5 \rightarrow 0 \\ \rightarrow 1 \times 2^6 \rightarrow 64 \end{array} \end{array}$$

$$N \rightarrow 1101$$

$$\downarrow_{10}$$

$$N \rightarrow 110, \quad r \rightarrow 1 \times 2^0$$

$$\downarrow_{10}$$

$$N \rightarrow 11, \quad r \rightarrow 0 \times 2^1$$

$$\downarrow_{10}$$

$$N \rightarrow 1, \quad r \rightarrow 1 \times 2^2$$

$$\downarrow_{10}$$

$$N \rightarrow 0, \quad r \rightarrow 1 \times 2^3$$

13

Code →

```
int ans = 0;
```

```
int power = 1 // initially, it is  $2^0$ .
```

```
while( N > 0 ) {
```

```
    int r = N % 10;
```

```
    N = N / 10;
```

```
    ans += (r * power);
```

```
    power *= 2;
```

```
}
```

```
return ans;
```

$N \rightarrow 101$

$= \sum$
 $ans = 0 + 1 + (0 \times 2) + 4$
 $power = 1 \ 2 \ 4 \ 8$

$r \rightarrow 1 \ 0 \ 1$

$\left[\begin{array}{l} \text{T.C} \rightarrow O(\log_{10} N) \\ \text{S.C} \rightarrow O(1) \end{array} \right]$



2. Decimal to Binary

• $(20)_{10} = (10100)_2$

2	20	
2	10	→ 0
2	5	→ 0
2	2	→ 1
2	1	→ 0
	0	→ 1

• $(45)_{10} = (101101)_2$

2	45	
2	22	→ 1 × 10 ⁰
2	11	→ 0 × 10 ¹
2	5	→ 1 × 10 ²
2	2	→ 1 × 10 ³
2	1	→ 0 × 10 ⁴
	0	→ 1 × 10 ⁵

#code ->

```
int ans = 0 ;
```

```
int power = 1 ;
```

```
while ( N > 0 ) {
```

```
    int r = N % 2 ;
```

```
    N = N / 2 ;
```

```
    ans += (r * power);
```

```
    power *= 10;
```

```
}
```

```
return ans;
```

$\left[\begin{array}{l} \text{T.C} \rightarrow O(\log_2 N) \\ \text{S.C} \rightarrow O(1) \end{array} \right]$



Addition of two decimal numbers -

	0	1	1	0
n1 →		3	6	8
n2 →		1	4	5
ans →		5 1 3		

- find the last digit of n1 & n2
- $\text{sum} = \text{carry} + l1 + l2$
- Remove last digit from n1 & n2
- update ans & carry.

Addition of two binary numbers -

	0	1	0	0	1	0
n1 →		1	1	0	1	
n2 → +		1	0	0	1	
		1 0 1 1 0				

$\text{sum} = 1 + 1 + 0 \rightarrow 2$
 $\begin{array}{c} 2 \\ \swarrow \searrow \\ 1 \quad 0 \end{array}$

$\text{sum} = 0 + 0 + 1 \Rightarrow 1$
 $\begin{array}{c} 0 \\ \swarrow \searrow \\ 1 \quad 0 \end{array}$

$\text{sum} = 1 + 0 + 0 \rightarrow 1$
 $\begin{array}{c} 0 \\ \swarrow \searrow \\ 1 \quad 0 \end{array}$

$\text{sum} = 1 + 1 + 0 \Rightarrow 2$
 $\begin{array}{c} 2 \\ \swarrow \searrow \\ 1 \quad 0 \end{array}$

$\text{sum} = 0 + 0 + 1 \Rightarrow 1$
 $\begin{array}{c} 0 \\ \swarrow \searrow \\ 1 \quad 0 \end{array}$



$$\begin{array}{r}
 010000 \\
 110101 \\
 + 100110 \\
 \hline
 101101 \\
 \hline
 \end{array}$$

$$\text{sum} = 1 \rightarrow 01$$

$$\text{sum} = 2 \rightarrow 10$$

$$\text{sum} = 3 \rightarrow 11$$

$$\text{sum} = 1 + 0 + 0 = 1 \quad \begin{array}{l} \xrightarrow{q} 0 \\ \xrightarrow{r} 1 \end{array}$$

$$\text{sum} = 0 + 1 + 0 = 1$$

$$\text{sum} = 1 + 1 + 0 = 2 \quad \begin{array}{l} \xrightarrow{q} 1 \\ \xrightarrow{r} 0 \end{array}$$

$$\text{sum} = 0 + 0 + 1 = 1 \quad \begin{array}{l} \xrightarrow{q} 0 \\ \xrightarrow{r} 1 \end{array}$$

$$\text{sum} = 1 + 0 + 0 = 1 \quad \begin{array}{l} \xrightarrow{q} 0 \\ \xrightarrow{r} 1 \end{array}$$

$$\text{sum} = 1 + 1 + 0 = 2 \quad \begin{array}{l} \xrightarrow{q} 1 \\ \xrightarrow{r} 0 \end{array}$$

$$\text{sum} = 0 + 0 + 1$$

$$\begin{array}{r}
 n1 \rightarrow 010100 \\
 n2 \rightarrow 00111 \\
 \hline
 ans \rightarrow 11101 \\
 \hline
 \end{array}$$

code →

//n1, n2 → given.

int ans = 0, power = 1;

int carry = 0;

while (n1 > 0 || n2 > 0 || carry > 0) {

l1 = n1 % 10; } last digit of n1 & n2

l2 = n2 % 10;

n1 = n1 / 10, n2 = n2 / 10; } reducing n1 & n2

sum = l1 + l2 + carry;

q = sum / 2;

r = sum % 2;

ans += (r * power);

carry = q;

power *= 10;

}

return ans;

T.C → $O(\log_{10} \max(n1, n2))$
S.C → $O(1)$



Bitwise Operators

!, &, |, ^, <<, >> - Advanced BM

same same puppy shame

a	b	a&b	a b	<u>a^b</u>	~a/!a
0	0	0	0	0	1
0	1	0	1	1	1
1	0	0	1	1	0
1	1	1	1	0	0

5 & 6 = ? 4

20 & 45 = ? 4

$$\begin{array}{r}
 5 \rightarrow 1 \ 0 \ 1 \\
 6 \rightarrow 1 \ 1 \ 0 \\
 \hline
 1 \ 0 \ 0 \\
 \hline
 \end{array}$$

$$\begin{array}{r}
 20 \rightarrow 0 \ 1 \ 0 \ 1 \ 0 \ 0 \\
 45 \rightarrow 1 \ 0 \ 1 \ 1 \ 0 \ 1 \\
 \hline
 0 \ 0 \ 0 \ 1 \ 0 \ 0 \\
 \hline
 \end{array}$$



$$20 \mid 45 = ? \quad (61)$$

$$\begin{array}{rcccccc} 20 \rightarrow & 0 & 1 & 0 & 1 & 0 & 0 \\ 45 \rightarrow & 1 & 0 & 1 & 1 & 0 & 1 \\ \hline & 1 & 1 & 1 & 1 & 0 & 1 \\ \hline \end{array}$$

$$20 \wedge 45 = ? \quad (57)$$

$$\begin{array}{rcccccc} 20 \rightarrow & 0 & 1 & 0 & 1 & 0 & 0 \\ 45 \rightarrow & 1 & 0 & 1 & 1 & 0 & 1 \\ \hline & 1 & 1 & 1 & 0 & 0 & 1 \\ \hline \end{array}$$



Negative Numbers

int \rightarrow 4B \rightarrow 32 bits.

Assumption 1 int \rightarrow 8 bits

 ↑
sign bit

-13

0 0 0 0 1 1 0 1 (13)

1's complement

1 1 1 1 0 0 1 0

2's complement

+ 1

1 1 1 1 0 0 1 1
 ↑ ↑ ↑ ↑ ↑ ↑ ↑
 2^7 2^6 2^5 2^4 2^3 2^2 2^1 2^0

$$(-2^7) + (2^6 + 2^5 + 2^4 + 2^1 + 2^0) \Rightarrow -128 + 64 + 32 + 16 + 2 + 1$$

$$\Rightarrow -128 + 115$$


$$\Rightarrow \underline{\underline{-13}}$$



0



No. is positive



No. is negative

$$2^0 + 2^1 + 2^2 + 2^3 + \dots + 2^{30}$$

$$= \frac{1[2^{31}-1]}{(2-1)} \Rightarrow \underline{\underline{2^{31}-1}}$$

Binary representation of -3 (in 8 bits)

0 0 0 0 0 0 1 1



1 1 1 1 1 1 0 0
+ 1

1 1 1 1 1 0 1

↓ ↓ ↓ ↓ ↓ ↓ ↓

$-2^7 + 2^6 + 2^5 + 2^4 + 2^3 + 2^2 + 2^0$

1 0 0 0 0 0 0 0
1 0 0 0 0 0 0 1

$\leftarrow -128$

0 0 0 0 0 0 0 0
1
1 0
1 1
⋮
0 1 1 1 1 1 1 1

$[127]$

8 bits $\rightarrow [-128, 127] \rightarrow [-2^7, 2^7-1]$

32 bits $\rightarrow [-2^{31}, 2^{31}-1]$

$\rightarrow [-2147483648, 2147483647]$

$\rightarrow [-2 \times 10^9, 2 \times 10^9]$

integer range $\rightarrow [-2^{31}, 2^{31}-1]$

approx $\rightarrow [-2 \times 10^9, 2 \times 10^9]$

long range $\rightarrow [-2^{63}, 2^{63}-1]$

approx $\rightarrow [-9 \times 10^{18}, 9 \times 10^{18}]$

Importance of Constraints →

int $a \rightarrow 10^5$, $b \rightarrow 10^6$

int $c = a * b$;

print(c); } ⇒ Wrong ans because of overflow.

int $a \rightarrow 10^5$, $b \rightarrow 10^6$

long $c = \underline{a * b}$;

↪ overflow happens here

print(c);

int $a \rightarrow 10^5$, $b \rightarrow 10^6$

long $c = (\text{long})(a) \times b$;

print(c);

$1 \leq N \leq 10^5$

$1 \leq A[i] \leq 10^6$

$1 \leq N \leq 10^5$

$1 \leq A[i] \leq \underline{10^6}$

Is the following code correct?

`int sum = 0;`

`for (int i = 0; i < N; i++) {`

`sum = sum + A[i];`

`}`

`print(sum)`

long ✓

$[10^6, 10^6, 10^6, 10^6, 10^6, \dots, 10^6]$
10⁵ such elements.

⇓

Sum of all $\rightarrow \underline{10^{11}}$

integer can't hold this.

Revise assignment problems \rightarrow Notes.

From every 5-7 problem - pick 1 & try to code it.

+ve.

0 0 1 0 1 1 0 1

↓

1 1 0 1 0 0 1 0
+ 1

1 1 0 1 0 0 1 1

-ve.