



Data Analysis with Python

Cheat Sheet: Data Wrangling

Package/Method	Description	Code Example
Replace missing data with frequency	Replace the missing values of the data set attribute with the mode common occurring entry in the column.	<pre> 1 MostFrequentEntry = df['attribute_name'].value_counts().idxmax() 2 df['attribute_name'].replace(np.nan,MostFrequentEntry,>df['attribute_name'].replace(np.nan,MostFrequentEntry, inplace=True) </pre>
Replace missing data with mean	Replace the missing values of the data set attribute with the mean of all the entries in the column.	<pre> 1 AverageValue=df['attribute_name'].astype(<data_type>).mean(axis=0) 2 df['attribute_name'].replace(np.nan, AverageValue, inplace=True) </pre>
Fix the data types	Fix the data types of the columns in the dataframe.	<pre> 1 df[['attribute1_name', 'attribute2_name', ...]] = 2 df[['attribute1_name', 'attribute2_name', ...]].astype('data_type') 3 #data_type is int, float, char, etc. </pre>
Data Normalization	Normalize the data in a column such that the values are restricted between 0 and 1.	<pre> 1 df['attribute_name'] = df['attribute_name']/df['attribute_name'].max() </pre>
Binning	Create bins of data for better analysis and visualization.	<pre> 1 bins = np.linspace(min(df['attribute_name']), 2 max(df['attribute_name'],n) 3 # n is the number of bins needed 4 GroupNames = ['Group1','Group2','Group3,...] 5 df['binned_attribute_name'] = 6 pd.cut(df['attribute_name'], bins, labels=GroupNames, include_lowest=True) </pre>
Change column name	Change the label name of a dataframe column.	<pre> 1 df.rename(columns={'old_name':'new_name'}, inplace=True) </pre>
Indicator Variables	Create indicator variables for categorical data.	<pre> 1 dummy_variable = pd.get_dummies(df['attribute_name']) 2 df = pd.concat([df, dummy_variable],axis = 1) </pre>