



Oracle OpenWorld 2019

SAN FRANCISCO





Using the Go Language for Efficient Oracle Database Applications [DEV6708]

Anthony Tuininga

anthony.tuininga@oracle.com


Data Access Development
Oracle Database

Safe Harbor

The following is intended to outline our general product direction. It is intended for information purposes only, and may not be incorporated into any contract. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, timing, and pricing of any features or functionality described for Oracle's products may change and remains at the sole discretion of Oracle Corporation.

Statements in this presentation relating to Oracle's future plans, expectations, beliefs, intentions and prospects are "forward-looking statements" and are subject to material risks and uncertainties. A detailed discussion of these factors and other risks that affect our business is contained in Oracle's Securities and Exchange Commission (SEC) filings, including our most recent reports on Form 10-K and Form 10-Q under the heading "Risk Factors." These filings are available on the SEC's website or on Oracle's website at <http://www.oracle.com/investor>. All information in this presentation is current as of September 2019 and Oracle undertakes no duty to update any statement in light of new information or future events.

Oracle Database for the Developer



- ☒ Oracle Open Source Drivers
- ☒ Third Party Open Source Drivers

- ☐ Oracle Proprietary Drivers
Oracle Call Interface, Oracle C++ Call Interface, ODBC, JDBC, ODP.NET, Pro*C, Pro*COBOL, SQLJ, OLE DB, OLE DB for OLAP




Introduction

What is Go?



- General purpose, cross platform, open source programming language
- In the tradition of C but with many changes to make code shorter, simpler and safer
- Started at Google in 2007
 - Goal: “Fast, statically typed, compiled language that feels like a dynamically typed, interpreted language”
 - Open source in 2009
 - Version 1.0 released 2012, now at version 1.12
 - Consideration of version 2 features underway



Popularity



- Increasing in popularity
 - Stack Overflow put Go in #13 earlier this year
 - TIOBE index for September 2019 puts Go in #14
 - IEEE puts Go at #10 in 2019
 - GitHub in 2019 puts Go as 4th for pull requests
- Docker container system and Kubernetes container management system written in Go

What Go Has



- Fast compilation
- Simple cross compilation
- Binaries are standalone and have no dependencies
- Built-in concurrency primitives
- Automatic memory management
- Easily extensible via packages
- Type inference
- Can integrate with C code

What Go Does Not Have



- No forward declarations or header files
- No exception handling (explicit error checking)
- No type hierarchy/inheritance (interfaces inferred by compiler)
- No overloading of methods/operators
- No implicit conversions
- No declaration of public/private (uses case of first letter of identifiers)

Simple Example



```
package main

import (
    "fmt"
)

func main() {
    fmt.Println("Hello, world!")
}
```

```
go run hello.go
```

```
go build hello.go
./hello
```

```
GOOS=windows go build hello.go
```



Types in Go

Primitive Types



- Integer types (int, int8, int16, int32, int64, uint, etc.)
- Floating point types (float32, float64)
- Complex types (complex64, complex128)
- String
- Bool

Derived Types



- Pointers
- Functions
- Arrays, slices, maps
- Structures, interfaces
- Channels

Arrays/Slices

```
var arr [5]int
fmt.Println("1 array:", arr)
for i := range arr {
    arr[i] = i * i
}
fmt.Println("2 array:", arr)
```

```
slice := arr[1:3]
fmt.Println("3 slice:", slice)
slice[1] = 15
fmt.Println("4 array:", arr)
fmt.Println("5 slice:", slice)
```

```
1 array: [0 0 0 0 0]
2 array: [0 1 4 9 16]
3 slice: [1 4]
4 array: [0 1 15 9 16]
5 slice: [1 15]
```


Structures/Interfaces

```
type TwoDShape interface {  
    Area() float64  
    Description() string  
}
```

Structures/Interfaces (continued)

```
type Circle struct {  
    Radius float64  
}
```

```
func (circle *Circle) Area() float64 {  
    return math.Pi * circle.Radius * circle.Radius  
}
```

```
func (circle *Circle) Description() string {  
    return fmt.Sprintf("Circle of radius %v", circle.Radius)  
}
```

Structures/Interfaces (continued)

```
type Triangle struct {  
    Base, Height float64  
}
```

```
func (triangle *Triangle) Area() float64 {  
    return 0.5 * triangle.Base * triangle.Height  
}
```

```
func (triangle *Triangle) Description() string {  
    return fmt.Sprintf("Triangle of base %v and height %v", triangle.Base,  
        triangle.Height)  
}
```

Structures/Interfaces (continued)

```
func ShowAreas(shapes ...TwoDShape) {  
    for _, s := range shapes {  
        fmt.Printf("%s has area %.2f\n", s.Description(), s.Area())  
    }  
}
```

```
Circle of radius 5 has area 78.54  
Triangle of base 4 and height 6 has area 12.00  
Circle of radius 3 has area 28.27  
Circle of radius 2.5 has area 19.63  
Triangle of base 2 and height 7.5 has area 7.50
```

```
func main() {  
    ShowAreas(&Circle{5}, &Triangle{4, 6}, &Circle{3},  
             &Circle{2.5}, &Triangle{Base: 2, Height: 7.5})  
}
```

Channels

```
func calc_sum(c chan int, arr []int) {  
    sum := 0  
    for _, v := range arr {  
        sum += v  
    }  
    c <- sum  
}
```

Channels (continued)

```
func main() {  
    c := make(chan int)  
    go calc_sum(c, []int{1, 2, 3, 4, 5})  
    go calc_sum(c, []int{8, -1, 0, 15, -25, 6, 2})  
    go calc_sum(c, []int{1})  
    for i := 0; i < 3; i++ {  
        sum := <- c  
        fmt.Printf("Calculated sum is %v\n", sum)  
    }  
}
```

```
Calculated sum is 15  
Calculated sum is 5  
Calculated sum is 1
```




General Database Support

Database Support Overview



- Package name is “database/sql”
- Intended to be generic database API for accessing any type of database
- Covers common cases but excludes database specific extensions
- Drivers implement the interfaces defined in package “database/sql/driver”
- Supports concurrent access by goroutines, context management (timeout, cancellation, etc.), connection pooling, statement caching, etc.

Database Type Support



- Only handles booleans, strings, numbers, dates
- Also has `sql.NullInt64`, `sql.NullFloat64`, `sql.NullBool`, `sql.NullString`
- Type conversion is permitted, but only if it can be done without data loss

Connecting to a Database



```
import (  
    "database/sql"  
    _ "gopkg.in/goracle.v2"  
)  
  
func main() {  
    db, _ := sql.Open("goracle", "godb/welcome@localhost/orclpdb1")  
    defer db.Close()  
    db.Ping()  
}
```

Database Setup



```
create table TestQuery (  
    IntCol          number(9) not null,  
    StringCol       varchar2(30) not null  
);
```

```
create table TestInsert (  
    IntCol          number(9) not null,  
    StringCol       varchar2(30) not null,  
    DateCol         date not null  
);
```

Database Setup (continued)



```
begin
  for i in 1..10 loop
    insert into TestQuery values (power(3, i),
                                   '3 ^ ' || to_char(i));
  end loop;
  commit;
end;
/
```


Multiple row query



```
sql := "select IntCol, StringCol from TestQuery where IntCol < 100"
rows, _ := db.Query(sql)
defer rows.Close()

var intCol, strCol string
for rows.Next() {
    rows.Scan(&intCol, &strCol)
    fmt.Printf("IntCol=%s, StrCol=%s\n", intCol, strCol)
}

err = rows.Err()
```

```
IntCol=3, StrCol=3 ^ 1
IntCol=9, StrCol=3 ^ 2
IntCol=27, StrCol=3 ^ 3
IntCol=81, StrCol=3 ^ 4
```

Single row query



```
var intCol, strCol string
sql := "select IntCol, StringCol from TestQuery where IntCol = :1"
row := db.QueryRow(sql, 27)
row.Scan(&intCol, &strCol)
fmt.Printf("IntCol=%s, StrCol=%s\n", intCol, strCol)
```

```
IntCol=27, StrCol=3 ^ 3
```

DML Execution



```
var timeInserted time.Time
sqlText := "insert into TestInsert values " +
    "(:IntCol, :StrCol, sysdate) " +
    "returning DateCol into :TimeInserted"
db.Exec(sqlText, sql.Named("IntCol", 1),
    sql.Named("StrCol", "Test String 1"),
    sql.Named("TimeInserted", sql.Out{Dest: &timeInserted}))
fmt.Printf("Time inserted was %v\n", timeInserted)
```

```
Time inserted was 2019-09-03 12:00:09 +0000 UTC
```



Transactions



```
tx, _ := db.Begin()

for i := 0; i < 5; i++ {
    tx.Exec("insert into TestInsert values (:1, :2, :3)",
        i + 1, "Test String " + strconv.Itoa(i + 1), time.Now())
}

tx.Commit()
```

Concurrent DML



```
func Insert100(db *sql.DB, startingNum int, c chan int) {  
    tx, _ := db.Begin()  
    for i := 0; i < 100; i++ {  
        val := startingNum + i  
        tx.Exec("insert into TestInsert values (:1, :2, :3)",  
                val, "Test String " + strconv.Itoa(val),  
                time.Now())  
    }  
    tx.Commit()  
    c <- 1  
}
```

Concurrent DML (continued)



```
const numBatches = 5
c := make(chan int)
for i := 0; i < numBatches; i++ {
    go Insert100(db, i * 100 + 1, c)
}

for i := 0; i < numBatches; i++ {
    <- c
}
```




Oracle Database Support

Oracle Database Drivers



- <https://github.com/go-goracle/goracle>
 - Youngest driver (about two years old)
 - Most active development
 - based on ODPI-C
- <https://github.com/rana/ora>
 - Oldest driver (about five years old)
 - Development has mostly ceased
- <https://github.com/mattn/go-oci8>
 - Next oldest driver (about four years old)

Bulk DML



```
const numRows = 500
intVals := make([]int, numRows)
strVals := make([]string, numRows)
dateVals := make([]time.Time, numRows)
for i := range intVals {
    intVals[i] = i + 1
    strVals[i] = "Test String " + strconv.Itoa(i + 1)
    dateVals[i] = time.Now()
}
db.Exec("insert into TestInsert values (:1, :2, :3)", intVals,
        strVals, dateVals)
```

PL/SQL Arrays (Package Header)



```
create or replace package pkg_TestArrays as
```

```
    type udt_NumberList is table of number index by binary_integer;
```

```
    type udt_StringList is table of varchar2(100) index by binary_integer;
```

```
    procedure TestArrays (
```

```
        a_NumElems          number,
```

```
        a_OutNums           out udt_NumberList,
```

```
        a_OutStrings        out udt_StringList
```

```
    );
```

```
end;
```

```
/
```

PL/SQL Arrays (Package Body)



```
create or replace package body pkg_TestArrays as
  procedure TestArrays (
    a_NumElems          number,
    a_OutNums           out udt_NumberList,
    a_OutStrings        out udt_StringList
  ) is
  begin
    for i in 1..a_NumElems loop
      a_OutNums(i) := i * i;
      a_OutStrings(i) := 'The square of ' || to_char(i);
    end loop;
  end;
end;
/
```

PL/SQL Arrays



```
import (  
    "database/sql"  
    goracle "gopkg.in/goracle.v2"  
)  
  
...  
const numElems = 5  
numArr := make([]int, numElems)  
strArr := make([]string, numElems)  
db.Exec("begin pkg_TestArrays.TestArrays(:1, :2, :3); end;",  
        goracle.PlSQLArrays, numElems, sql.Out{Dest: &numArr},  
        sql.Out{Dest: &strArr})  
for i := range numArr {  
    fmt.Printf("%v is %v\n", strArr[i], numArr[i])  
}
```

```
The square of 1 is 1  
The square of 2 is 4  
The square of 3 is 9  
The square of 4 is 16  
The square of 5 is 25
```



LOBs – As String/Bytes

```
rows, _ := db.Query("select IntCol, CLOBCol from TestCLOBs")  
defer rows.Close()
```

```
var intCol int  
var clobCol string  
for rows.Next() {  
    rows.Scan(&intCol, &clobCol)  
    fmt.Printf("IntCol=%v, CLOBCol=%v bytes\n", intCol,  
               len(clobCol))  
}
```

LOBs – As Reader

```
rows, _ := db.Query("select IntCol, CLOBCol from TestCLOBs",
                    goracle.LobAsReader())
defer rows.Close()

var intCol int
var clobCol interface{}
for rows.Next() {
    rows.Scan(&intCol, &clobCol)
    clob, _ := clobCol.(*goracle.Lob)
    data, _ := ioutil.ReadAll(clob)
    fmt.Printf("IntCol=%v, CLOBCol=%v bytes\n", intCol, len(data))
}
```


Nested Cursors



```
sql := "select cursor(select * from TestQuery) from dual"
rows, _ := db.Query(sql)
defer rows.Close()
for rows.Next() {
    var nestedRows sql.Rows
    rows.Scan(&nestedRows)
    defer nestedRows.Close()
    for nestedRows.Next() {
        ...
    }
}
```

AQ – Enqueue



```
ctx, _ := context.WithTimeout(context.Background(),  
    10 * time.Second)
```

```
q, _ := goracle.NewQueue(ctx, db, "RAW_QUEUE", "")  
defer q.Close()
```

```
tx, _ := db.Begin()  
message := goracle.Message{Raw: []byte("Message 1")}  
q.Enqueue([]goracle.Message{message})  
tx.Commit()
```

AQ – Dequeue



```
ctx, _ := context.WithTimeout(context.Background(),
    10 * time.Second)
q, _ := goracle.NewQueue(ctx, db, "RAW_QUEUE", "")
defer q.Close()
tx, _ := db.Begin()
messages := make([]goracle.Message, 5)
n, _ := q.Dequeue(messages)
for i := 0; i < n; i++ {
    fmt.Printf("Received message: %s\n", string(messages[i].Raw))
}
tx.Commit()
```

Named Object Types – Setup

```
create or replace type udt_Book as object (  
    Title          varchar2(100) ,  
    Authors        varchar2(100) ,  
    Price          number(5,2)  
);  
/
```

```
create table Books (  
    Id              number(9) not null,  
    Book            udt_book not null  
);
```

Named Object Types – Insert

```
tx, _ := db.Begin()
ctx, _ := context.WithTimeout(context.Background(),
    30 * time.Second)
objType, _ := goracle.GetObjectType(ctx, tx, "UDT_BOOK")
obj, _ := objType.NewObject()
defer obj.Close()
obj.Set("TITLE", "The Fellowship of the Ring")
obj.Set("AUTHORS", "J.R.R. Tolkien")
obj.Set("PRICE", 12.50)
tx.Exec("insert into Books values (:1, :2)", 1, obj)
tx.Commit()
```

Named Object Types – Fetch

```
var idVal int
var obj *goracle.Object
row := db.QueryRow("select Id, Book from Books")
row.Scan(&idVal, &obj)
defer obj.Close()
authors, _ := obj.Get("AUTHORS")
title, _ := obj.Get("TITLE")
price, _ := obj.Get("PRICE")
fmt.Printf("Authors: %s\nTitle: %s\nPrice: %.2f\n", authors, title,
           price)
```

Resources



Mail:

anthony.tuininga@oracle.com

Twitter:

[@AnthonyTuininga](https://twitter.com/AnthonyTuininga)

Facebook:

<https://tinyurl.com/FBOracle>

goracle:

<https://github.com/go-goracle/goracle>

Thank You

Anthony Tuininga

anthony.tuininga@oracle.com

Data Access Development
Oracle Database

