

How to document your research software

In this lesson we will discuss different solutions for implementing and deploying code documentation.

This demonstration will be mostly **independent of programming languages** (you will be able to follow and do all the exercises using the [CodeRefinery conda environment](#)).

We will start by discussing the form of documentation which is the most immediate to write: **in-code** comments, and docstrings.

To step up our game we will discuss **what makes a good README**. For many projects, a curated README is enough.

We will then learn how to build documentation with the **documentation generator Sphinx** and how to deploy it to [GitHub Pages](#). The approach that we will learn will be transferable to [GitLab Pages](#) and [Bitbucket Pages](#).

After we have seen Sphinx as an example, we will see a brief taxonomy of the other popular tools and solutions, and finally, once we know what tooling can do and how to use it, we will take a step back and look at best practices: what makes documentation important and useful and how to best maintain it.

⚙️ Prerequisites

1. Basic understanding of Git.
2. For the Sphinx part, You need to have [sphinx](#) and [sphinx_rtd_theme](#) installed (they are part of the [coderefinery environment](#)).
3. For the [GitHub Pages](#) part you need a [GitHub](#) account.

If you wish to follow in the terminal and are new to the command line, we recorded a [short shell crash course](#).

An optional episode is about deploying a **project website or personal homepage** to [GitHub Pages](#).

5 min	Intro
5 min	In-code documentation

10 min	Writing good README files
35 min	Sphinx and Markdown (with exercise)
10 min	Break
30 min	Deploying Sphinx documentation to GitHub Pages (with exercise)
10 min	Popular tools and solutions
10 min	Motivation and wishlist
5 min	Summary

In-code documentation

? Questions

- What can I do to make my code more easily understandable?
- What information should go into comments?
- What are docstrings and what information should go into docstrings?

In this episode we will learn how to write good documentation inside your code.

Demonstration - Writing good comments

🔧 In-code-1: Comments

Let's take a look at two example comments (comments in Python start with `#`):

Comment A

```
# now we check if temperature is below -50
if temperature < -50:
    print("ERROR: temperature is too low")
```

Comment B

```
# we regard temperatures below -50 degrees as measurement errors
if temperature < -50:
    print("ERROR: temperature is too low")
```

Which of these comments is more useful? Can you explain why?

✓ Solution

- Comment A describes **what** happens in this piece of code. This can be useful for somebody who has never seen Python or a program, but for somebody who has, it can feel like a redundant commentary.
- Comment B is probably more useful as it describes **why** this piece of code is there, i.e. its **purpose**.

Sometimes version control is better than a comment

! Examples for code comments where Git is a better solution

Keeping zombie code “just in case” (rather use version control):

```
# do not run this code!  
# if temperature > 0:  
#     print("It is warm")
```

Instead: Remove the code, you can always find it back in a previous version of your code in Git.

Emulating version control:

```
# John Doe: threshold changed from 0 to 15 on August 5, 2013  
if temperature > 15:  
    print("It is warm")
```

Instead: You can get this information from `git log` or `git show` or `git annotate` or similar.

What are “docstrings” and how can they be useful?

Here is function `fahrenheit_to_celsius` which converts temperature in Fahrenheit to Celsius, implemented in a couple of different languages. Your language is missing? Please contribute an example.

The first set of examples uses **regular comments**:

Python

```
# This function converts a temperature in Fahrenheit to Celsius.  
def fahrenheit_to_celsius(temp_f: float) -> float:  
    temp_c = (temp_f - 32.0) * (5.0/9.0)  
    return temp_c
```

R

```
# Convert Fahrenheit to Celsius
fahrenheit_to_celsius <- function(temp_f)
{
  temp_c <- (temp_f - 32.0) * (5.0/9.0)
  temp_c
}
```

Julia

```
# This function converts a temperature in Fahrenheit to Celsius.
function fahrenheit_to_celsius(temp_f)
  temp_c = (temp_f - 32.0) * (5.0/9.0)
  return temp_c
end
```

Fortran

```
! Convert Fahrenheit to Celsius
function fahrenheit_to_celsius(temp_f) result(temp_c)
  implicit none
  real temp_f
  real temp_c
  temp_c = (temp_f - 32.0) * (5.0/9.0)
end function
```

C++

```
// Converts a temperature in Fahrenheit to Celsius
double fahrenheit_to_celsius(double temp_f) {
  auto temp_c = (temp_f - 32.0) * (5.0 / 9.0);
  return temp_c;
}
```

Rust

```
// Convert Fahrenheit to Celsius
fn fahrenheit_to_celsius(temp_f: f64) -> f64 {
  let temp_c = (temp_f - 32.0) * 5.0 / 9.0
  temp_c
}
```

The second set uses **docstrings or similar concepts**. Please compare the two (above and below):

Python

```
def fahrenheit_to_celsius(temp_f: float) -> float:
    """
    Converts a temperature in Fahrenheit to Celsius.

    Parameters
    -----
    temp_f : float
        The temperature in Fahrenheit.

    Returns
    -----
    float
        The temperature in Celsius.
    """

    temp_c = (temp_f - 32.0) * (5.0/9.0)
    return temp_c
```

Read more: <https://peps.python.org/pep-0257/> 

R

```
## Convert Fahrenheit to Celsius
#'
#' @param temp_f A numeric vector of temperatures in Fahrenheit.
#' @return A numeric vector of temperatures in Celsius.
fahrenheit_to_celsius <- function(temp_f)
{
  temp_c <- (temp_f - 32.0) * (5.0/9.0)
  temp_c
}
```

Read more: <https://cran.r-project.org/web/packages/roxygen2/vignettes/roxygen2.html> 

Julia

```

"""
    fahrenheit_to_celsius(temp_f::Float)

Converts temperature in Fahrenheit to Celsius.

# Arguments
- `temp_f::Float`: Temperature in Fahrenheit.

# Returns
- `temp_c::Float`: Temperature in Celsius.
"""
function fahrenheit_to_celsius(temp_f)
    temp_c = (temp_f - 32.0) * (5.0/9.0)
    return temp_c
end

```

Read more: <https://docs.julialang.org/en/v1/manual/documentation/>

Fortran

```

!> @brief Convert Fahrenheit to Celsius
!! @param temp_f Temperature in Fahrenheit
!! @return Temperature in Celsius
function fahrenheit_to_celsius(temp_f) result(temp_c)
    implicit none
    real temp_f
    real temp_c
    temp_c = (temp_f - 32.0) * (5.0/9.0)
end function

```

Read more: https://en.wikibooks.org/wiki/Fortran/Documenting_Fortran

C++

```

// @brief: Converts a temperature in Fahrenheit to Celsius
//
// @param: temp_f: Temperature in Fahrenheit
//
// @return: Temperature in Celsius
double fahrenheit_to_celsius(double temp_f) {
    auto temp_c = (temp_f - 32.0) * (5.0 / 9.0);
    return temp_c;
}

```

Read more: <https://www.doxygen.nl>

Rust

```

/// Convert Fahrenheit to Celsius
/// # Arguments
/// * `temp_f` - Temperature in Fahrenheit
///
/// # Returns
/// * `temp_c` - Temperature in Celsius
fn fahrenheit_to_celsius(temp_f: f64) -> f64 {
    let temp_c = (temp_f - 32.0) * 5.0 / 9.0
    temp_c
}

```

Read more: <https://doc.rust-lang.org/rust-by-example/meta/doc.html> 

Docstrings can do a bit more than just comments:

- Tools can generate help text automatically from the docstrings.
- Tools can generate documentation pages automatically from code.

It is common to write docstrings for functions, classes, and modules.

Good docstrings describe:

- What the function does
- What goes in (including the type of the input variables)
- What goes out (including the return type)

Naming is documentation: Giving explicit, descriptive names to your code segments (functions, classes, variables) already provides very useful and important documentation. In practice you will find that for simple functions it is unnecessary to add a docstring when the function name and variable names already give enough information.

Keypoints

- Comments should describe the why for your code not the what.
- Writing docstrings can be a good way to write documentation while you type code since it also makes it possible to query that information from outside the code or to auto-generate documentation pages.

Writing good README files

The README file (often `README.md` or `README.rst`) is usually the first thing users/collaborators see when visiting your GitHub repository.

Use it to communicate important information about your project! For many smaller or mid-size projects, this is enough documentation. It's not that hard to make a basic one, and it's easy to expand as needed.

Demonstration: Have fun testing some README features

Exercise README-1: Have fun testing some README features you may not have heard about

- Test the effect of adding the following to your GitHub README ([read more](#)):

```
> [!NOTE]
> Highlights information that users should take into account, even when
skimming.

> [!IMPORTANT]
> Crucial information necessary for users to succeed.

> [!WARNING]
> Critical content demanding immediate user attention due to potential risks.
```

- For more detailed descriptions which you don't want to show by default you might find this useful (please try it out):

```
<details>
<summary>
Short summary
</summary>

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod
tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam,
quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo
consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse
cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non
proident, sunt in culpa qui officia deserunt mollit anim id est laborum.
</details>
```

- Would you like to add a badge like this one: ?

Badge that links to a website (see also <https://shields.io/>):

```
[!please replace with alt text](https://img.shields.io/badge/anytext-youlike-blue)(https://example.org)
```

Badge without link:

```
![please replace with alt text](https://img.shields.io/badge/anytext-youlike-blue)
```

- Know about other tips and tricks? Please share them (send a pull request to this lesson).

Optional Exercise: Improve the README for your own project

Exercise README-2: Draft or improve a README for one of your recent projects

Try to draft a brief README or review a README which you have written for one of your projects.

- You can do that either by screensharing and discussing or working individually.
- Use the [checklist](#) which we have discussed earlier.
- Think about the user (**which can be a future you**) of your project, what does this user need to know to use or contribute to the project? And how do you make your project attractive to use or contribute to?
- (Optional): Try the <https://hemingwayapp.com/>  to analyse your README file and make your writing bold and clear.
- Please note observations and recommendations in the collaborative notes.

Optional Exercise: Discuss the README of a project that you use

Exercise README-3: Review and discuss a README of a project that you have used

In this exercise we will review and discuss a README of a project which you have used. You can also review a library which is popular in your domain of research and discuss their README.

- You can do that either by screensharing and discussing or working individually.
- When discussing other people's projects please remember to be respectful and constructive. The goal of this exercise is not to criticize other projects but to learn from other projects and to collect the aspects that you enjoyed finding in a README and to also collect aspects which you have searched for but which are sometimes missing.
- Please note observations and recommendations in the collaborative notes.

Table of contents in README files

- GitHub automatically generates a [table of contents for README.md files](#) .
- On GitLab you can generate a TOC in Markdown with:

```
[[_TOC_]]
```

- With RST you can generate a table of contents (TOC) automatically by adding:

```
.. contents:: Table of Contents
```

Sphinx and Markdown

📌 Objectives

- Understand how static site generators build websites out of plain text files.
- Create example Sphinx documentation and learn some Markdown along the way.

We will take the first steps in creating documentation using Sphinx, and learn some MyST flavored Markdown syntax along the way.

💬 This lesson is built with Sphinx

Try to compare the [source code](#) and the result side by side.

Our goal in this episode is to build HTML pages locally on our computers.

⚙️ Before we start, let us verify whether we have the software we need

You may need to activate your CodeRefinery conda environment we set up in the installation instructions. This was covered as part of the installation instructions, but the most usual command to do this is:

```
$ conda activate coderefinery
```

Check whether Python is available (you should see a version; precise version is not so important):

```
$ python --version
```

```
Python 3.11.5
```

Check whether Sphinx is available (you should see a version; precise version is not so important):

```
$ sphinx-build --version
```

```
sphinx-build 5.3.0
```

Check whether the quickstart tool is available (you should see a version; precise version is not so important):

```
$ sphinx-quickstart --version  
  
sphinx-quickstart 5.3.0
```

Check whether MyST parser is available (you should see no output):

```
$ python -c "import myst_parser"
```

If the above commands produce an error (**command not found** or **module not found** or **ModuleNotFoundError**), please follow our [installation instructions](#)[↗]. But please don't give up if you don't have these - the episodes after this one will work even without these tools.

Exercise: Setting up a Sphinx project

Sphinx-1: Generate the basic documentation template

Create a directory for the example documentation, step into it, and inside generate the basic documentation template:

```
$ mkdir doc-example  
$ cd doc-example
```

We create the basic structure of the project manually.

File/directory	Contents
conf.py	Documentation configuration file
index.md	Main file in Sphinx

Let's create the `index.md` with this content:

Documentation example with Sphinx

A small example of how to use Sphinx and MyST to create easily readable and aesthetically pleasing documentation.

```
``{toctree}
:maxdepth: 2
:caption: Contents:
some-feature.md
``
```

Note that indentation and spaces play a role here.

We also create a `conf.py` configuration file, with this content:

```
project = 'Test sphinx project'
author = 'Alice, Bob'
release = '0.1'

extensions = ['myst_parser']

exclude_patterns = ['_build']
```

For more information about the configuration, see the [Sphinx documentation](#) .

Let's create the file `some-feature.md` (in Markdown format) which we have just listed in `index.md`:

Some feature

Subsection

Exciting documentation in here.

Let's make a list (empty surrounding lines required):

- item 1
 - nested item 1
 - nested item 2
- item 2
- item 3

We now build the site:

```
$ ls -l

conf.py
index.md
some-feature.md

$ sphinx-build . _build

... lots of output ...
build succeeded.

The HTML pages are in _build.

$ ls -l _build

_sources
_static
genindex.html
index.html
objects.inv
search.html
searchindex.js
some-feature.html
```

Now open the file `_build/index.html` in your browser.

- Linux users, type:

```
$ xdg-open _build/index.html
```

- macOS users, type:

```
$ open _build/index.html
```

- Windows users, type:

```
$ start _build/index.html
```

- If the above does not work: Enter `file:///home/user/doc-example/_build/index.html` in your browser (adapting the path to your case).

Hopefully you can now see a website. If so, then you are able to build Sphinx pages locally. This is useful to check how things look before pushing changes to GitHub or elsewhere.

Note that you can change the styling by adding the line

```
html_theme = "<my favorite theme>"
```

in `conf.py`. For instance you can use `sphinx_rtd_theme` to have the Read the Docs look (make sure the `sphinx_rtd_theme` python package is available first)

→ See also

Sphinx also provides a tool called `sphinx-quickstart` that guides you in the creation of the project. The reason why we do not use it here is that it does not use Markdown by default, but a more complex format called ReStructured Text (ReST).

Exercise: Adding more Sphinx content

Sphinx-2: Add more content to your example documentation

1. Add a entry below `some-feature.md` labeled `another-feature.md` (or a better name) to the `index.md` file.
2. Create a file `another-feature.md` in the same directory as the `index.md` file.
3. Add some content to `another-feature.md`, rebuild with `sphinx-build . _build`, and refresh the browser to look at the results.
4. Use the [MyST Typography](#) page as help.

Experiment with the following Markdown syntax:

- **Emphasized text** and ****bold text****
- Headings:

```
# Level 1
```

```
## Level 2
```

```
### Level 3
```

```
#### Level 4
```

- An image: `![alt text](image.png)`
- `[A link](https://www.example.org)`
- Numbered lists (numbers adjusted automatically):

1. item 1
2. item 2
3. item 3
1. item 4
1. item 5

- Simple tables:

No.	Prime
1	No
2	Yes
3	Yes
4	No

- Code blocks:

The following is a Python code block:

```
```python
def hello():
 print("Hello world")
```
```

And this is a C code block:

```
```c
#include <stdio.h>
int main()
{
 printf("Hello, World!");
 return 0;
}
```
```

- You could include an external file (here we assume a file called “example.py” exists; at the same time we highlight lines 2 and 3):

```
```{literalinclude} example.py
:language: python
:emphasize-lines: 2-3
```
```

- Math equations with LaTeX should work out of the box. Try this (result below):

This creates an equation:

```
```{math}
a^2 + b^2 = c^2
```
```

This is an in-line equation, `{math}`a^2 + b^2 = c^2``, embedded in text.

This creates an equation:

$$a^2 + b^2 = c^2$$

This is an in-line equation, `a^2 + b^2 = c^2`, embedded in text.

❗ Older versions of Sphinx

In some older versions, you might need to edit `conf.py` and add `sphinx.ext.mathjax`:

```
extensions = ['myst_parser', 'sphinx.ext.mathjax']
```

Exercise: Sphinx autodoc

🔧 Sphinx-3: Auto-generating documentation from Python docstrings

1. Write some docstrings in functions and/or class definitions to a python module

`multiply.py`:

```
def multiply(a: float, b: float) -> float:
    """
    Multiply two numbers.

    :param a: First number.
    :param b: Second number.
    :return: The product of a and b.
    """
    return a * b
```

2. In the file `conf.py` add `autodoc2` to the “extensions”, and add the list

`autodoc2_packages` which will mention `"multiply.py"`:

```
extensions = ['myst_parser', "autodoc2"]

autodoc2_packages = [
    "multiply.py"
]
```

If you already have extensions from another exercise, just add `"autodoc2"` to the existing list.

4. Add `apidocs/index` to the toctree in `index.md`.

```
``{toctree}
:maxdepth: 2
:caption: Contents:

...
apidocs/index
```

5. Re-build the documentation and check the “API reference” section.

Exercise: Using Jupyter with Sphinx

Sphinx-4: Writing Sphinx content with Jupyter

1. For simplicity, create a text-based notebook files `flower.md` in the same directory as the `index.md` file. This file will be converted to a Jupyter notebook by the `myst_nb` Sphinx extension and then executed by Jupyter. Fill the file with the following content:

```
---
file_format: mystnb
kernelspec:
  name: python3
---
# Flower plot

``{code-cell} ipython3
import matplotlib.pyplot as plt
import numpy as np

fig, ax = plt.subplots(1, 1, figsize=(5, 8), subplot_kw={"projection": "polar"})
theta = np.arange(0, 2 * np.pi, 0.01)
r = np.sin(5 * theta)
ax.set_rticks([])
ax.set_thetagrids([])
ax.plot(theta, r);
ax.plot(theta, np.full(len(theta), -1));
``
```

Note that there needs to be a title in the notebook (a heading starting with a single `#`), that will be used as an entry and link in the table of content. 2. In the file `conf.py` modify `extensions` to remove `"myst_parser"` and add `"myst_nb"` (you will get an error if you include both [🔗](#)):

```
extensions = ["myst_nb"]
```

Note that MyST parser functionality is included in MyST NB, so everything else will continue to work as before.

3. List `flower` in the toctree in `index.md`.

```
``{toctree}
:maxdepth: 2
:caption: Contents:
...
flower.md
``
```

4. Re-build the documentation and check the “Flower” section.

5. Alternatively, you can directly add `.ipynb` files saved from Jupyter notebook or Jupyter lab. Just make sure to list it in the toctree in `index.md` with the correct path.

If you have problems, consider cleaning manually the `jupyter_execute` directory.

Good to know

- The `_build` directory is a generated directory and should not be part of the Git repository. We recommend to add `_build` to `.gitignore` to prevent you from accidentally adding files below `_build` to the Git repository.
- [sphinx-autobuild](#) provides a local web server that will automatically refresh your view every time you save a file - which makes writing and testing much easier.
- This is useful if you want to check the integrity of all internal and external links:

```
$ sphinx-build . -W -b linkcheck _build
```

References

- [Sphinx documentation](#)
- [Sphinx + ReadTheDocs guide](#)
- For more Markdown functionality, see the [Markdown guide](#).
- For Sphinx additions, see [Sphinx Markup Constructs](#).
- <https://docs.python-guide.org/writing/documentation/>

- Sphinx and Markdown is a powerful duo for writing documentation.
- In the next episode we will learn how to deploy the documentation to a cloud service and update it upon every `git push`.

Deploying Sphinx documentation to GitHub Pages

📌 Objectives

- Create a basic workflow which you can take home and adapt for your project.

GitHub Pages

- Serve websites from a GitHub repository.
- It is no problem to serve using your own URL `https://myproject.org` instead of `https://myuser.github.io/myproject`.

GitHub Actions

- Automatically runs code when your repository changes.
- We will let it run `sphinx-build` and make the result available to GitHub Pages.

Our goal: putting it all together

- Host source code with documentation sources on a public Git repository.
- Each time we `git push` to the repository, a GitHub action triggers to rebuild the documentation.
- The documentation is pushed to a separate branch called 'gh-pages'.

Demonstration - Deploy Sphinx documentation to GitHub Pages

GH-Pages-1: Deploy Sphinx documentation to GitHub Pages

In this exercise we will create an example repository on GitHub and deploy it to GitHub Pages.

Step 1: Go to the [documentation-example](#)  project template on GitHub and create a copy to your namespace.

- Give it a name, for instance “documentation-example”.
- You don’t need to “Include all branches”
- Click on “Create a repository”.

Step 2: Browse the new repository.

- It will look very familiar to the previous episode.
- However, we have moved the documentation part under `doc/` (many projects do it this way). But it is still a Sphinx documentation project.
- The source code for your project could then go under `src/`.

Step 3: Add the GitHub Action to your new Git repository.

- Add a new file at `.github/workflows/documentation.yml` (either through terminal or web interface), containing:

```

1  name: documentation
2
3  on: [push, pull_request, workflow_dispatch]
4
5  permissions:
6    contents: write
7
8  jobs:
9    docs:
10     runs-on: ubuntu-latest
11     steps:
12       - uses: actions/checkout@v4
13       - uses: actions/setup-python@v5
14       - name: Install dependencies
15         run: |
16           pip install sphinx sphinx_rtd_theme myst_parser
17       - name: Sphinx build
18         run: |
19           sphinx-build doc _build
20       - name: Deploy to GitHub Pages
21         uses: peaceiris/actions-gh-pages@v3
22         if: ${ github.event_name == 'push' && github.ref == 'refs/heads/main'
23       }
24       with:
25         publish_branch: gh-pages
26         github_token: ${ secrets.GITHUB_TOKEN }
27         publish_dir: _build/
28         force_orphan: true

```

- You don't need to understand all of the above – you should mainly pay attention the highlighted lines which are shell commands (we know this because they are part of a `run: |` section). The first uses `pip` to install the dependencies and the second runs `sphinx-build` to actually build the documentation (as we saw in the previous episode).
- After the file has been committed (and pushed), check the action at <https://github.com/USER/documentation-example/actions> (replace `USER` with your GitHub username).

Step 4: Enable GitHub Pages

- On GitHub go to “Settings” -> “Pages”.

- Under “Build and deployment”
 - In the **Source** section: choose “Deploy from a branch” in the dropdown menu
 - In the **Branch** section: choose “gh-pages” and “/ (root)” in the dropdown menus and click the **Save** button.
- You should now be able to verify the pages deployment in the “Actions” list ([this is how it looks like](#)  for this lesson material).

Step 5: Verify the result

- Your site should now be live on `https://USER.github.io/documentation-example/` (replace USER).

Step 6 (optional): Verify refreshing the documentation

- Commit some changes to your documentation
- Verify that the documentation website refreshes after your changes (can take few seconds or a minute)

Exercise - Sphinx documentation on GitHub Pages

GH-Pages-2: Putting it all together

1. Follow the above instructions to create a new repository with a Sphinx documentation project;
2. Try adding one or more of the following to your Sphinx project:
 1. API documentation (see [previous exercise](#) on API references) which requires the `sphinx-autodoc2` package.
 2. a Jupyter notebook (see [previous exercise](#) on Jupyter notebooks) which requires the `myst-nb` package.
 3. change the theme (see the end of [the quickstart](#)). You can browse themes and find their package names on the [Sphinx themes gallery](#) .

Important

The computer on which the GitHub actions run is *not* your local machine, and might not have the libraries you need to build the project. Make sure you update the dependencies (installed with `pip` in the demonstration) appropriately.

Important

Make sure the correct file paths are used. This will require adjusting paths from the example from the previous episode to the new layout. Note many paths, including e.g. the `autodoc2_packages` preference are now relative to the `doc/` directory.

What do you need to change in the workflow file?

✓ Solution

1. API documentation

1. Change line 16 of `.github/workflows/documentation.yml` from `pip install sphinx sphinx_rtd_theme myst_parser` to `pip install sphinx sphinx_rtd_theme myst_parser sphinx-autodoc2`.
2. Follow the instructions in [Sphinx-3](#) changing paths so that:
 1. `multiply.py` is `src/multiply.py` and is specified as `../src/multiply.py` in the `autodoc2_packages` preference in `conf.py`
 2. `conf.py` is `doc/conf.py`
 3. `index.md` is `doc/index.md`.
3. Commit and push your changes, verify the action has run successfully, and view the built site in your browser.

2. a Jupyter notebook

1. Change line 16 of `.github/workflows/documentation.yml` from `pip install sphinx sphinx_rtd_theme myst_parser` to `pip install sphinx sphinx_rtd_theme myst_parser myst-nb`.
2. Follow the instructions in [Sphinx-4](#) changing paths so that:
 1. `flower.md` is `doc/flower.md`
 2. `conf.py` is `doc/conf.py`
 3. `index.md` is `doc/index.md`.
3. Commit and push your changes, verify the action has run successfully, and view the built site in your browser.

3. change the theme

1. Change line 16 of `.github/workflows/documentation.yml` and add the theme package if necessary.
2. In `doc/conf.py` change `html_theme = 'sphinx_rtd_theme'` to the name of your chosen theme.
3. Commit and push your changes, verify the action has run successfully, and view the built site in your browser.

Alternatives to GitHub Pages

- [GitLab Pages](#) and [GitLab CI](#) can create a very similar workflow.
- [Read the Docs](#) is the most common alternative to hosting in GitHub Pages.
- Sphinx builds HTML files (this is what static site generators do), and you can host them anywhere, for example your university's web space or own web server.

Migrating your own documentation to Sphinx

- First convert your documentation to Markdown using [Pandoc](#) [↗].
- Create a file `index.rst` which lists all other Markdown files and provides the table of contents.
- Add a `conf.py` file. You can generate a starting point for `conf.py` and `index.rst` with `sphinx-quickstart`, or you can take the examples in this lesson as inspiration.
- Test building the documentation locally with `sphinx-build`.
- Once this works, follow the above steps to build and deploy to GitHub Pages or some other web space.

Keypoints

- Sphinx makes simple HTML (and more) files, so it is easy to find a place to host them.
- Github Pages + Github Actions provides a convenient way to make sites and host them on the web.

Popular tools and solutions

? Questions

- What tools are out there?
- What are their pros and cons?

Objectives

- Choose the right tool for the right reason.

In-code documentation

- Comments, function docstrings, ...
- Advantages
 - Good for programmers
 - Version controlled alongside code
 - Can be used to auto-generate documentation for functions/classes
- Disadvantage
 - Probably not enough for users of the code

For a closer look at this see the [In-code documentation](#) episode.

README files

- Advantages
 - Versioned (goes with the code development)
 - It is often good enough to have a `README.md` or `README.rst` along with your code/script
- If you use README files, use either [RST](#) or [Markdown](#)
- A great guide to README files: [MakeaREADME](#)

For a closer look at this see the [Writing good README files](#) episode.

Plain Text formats: reStructuredText and Markdown

| | |
|--|--|
| <code># This is a section in Markdown</code> | <code>This is a section in RST</code>
===== |
| <code>## This is a subsection</code> | <code>This is a subsection</code>
----- |
| Nothing special needed for
a normal paragraph. | Nothing special needed for
a normal paragraph. |
| | :: |
| This is a code block | This is a code block |
| <code>**Bold**</code> and <i><code>*emphasized*</code></i> . | <code>**Bold**</code> and <i><code>*emphasized*</code></i> . |
| A list: <ul style="list-style-type: none">- this is an item- another item | A list: <ul style="list-style-type: none">- this is an item- another item |
| There is more: images,
tables, links, ... | There is more: images,
tables, links, ... |

- Two of the most popular lightweight markup languages.
- reStructuredText (RST) has more features than Markdown but the choice is a matter of taste.
- There are (unfortunately) [many flavors of Markdown](#).
- Motivation to stick to a standard text-based format: **They make it easier to move the documentation to other tools which also expect a standard format, as the project/organization grows.**
- We use [MyST](#) flavored Markdown in the [Sphinx and Markdown](#) episode and the [Hosting websites/homepages on GitHub Pages](#) example.
- Nice resource to learn Markdown: [Learn Markdown in 60 seconds](#)
- [Pandoc](#) can convert between MD and RST (and many other formats).

HTML static site generators

There are many tools generate documentation that can be viewed locally, or hosted on the web.

Here are some HTML static site generators, relevant in our communities. These tools offer some or all of these features:

- **API Reference generation:** source code is read, scan for docstrings and render them
- **Search:** they offer a “whole site” search feature (non trivial, when viewing only one page). (if you can download)
- **Validation:** check that the code snipped in the documentation match the real behaviour of the code.
- **Continuous checks:** regenerate automatically every time you save, so that you can catch errors early

Python

- [Sphinx](#)  ← this is how this lesson material is built
 - Generate HTML/PDF/LaTeX from RST and Markdown (MyST)
 - Basically all Python projects use Sphinx but **Sphinx is not limited to Python**.
 - [Read the docs](#)  hosts public Sphinx documentation for free!
 - **API Reference generation:** via [autodoc](#)  or [autoapi](#) 
 - **Search:**
 - limited, keyword-based client-side (Javascript that runs in browser)
 - Full-text server-side on [Read the docs](#) 
 - **Validation:** via [doctest](#) 
- [MkDocs](#) : A Markdown-first static site generator.
 - **API Reference generation:** via [mkdocstrings](#) 
 - **Search:** search plugin for client-side (Javascript that runs in the browser - lunr.js)
- [Doxygen](#) :
 - **API Reference generation:** has also support for Python

R

- [pkgdown](#) 
 - **API Reference generation:** via [roxygen2](#)  and Rdconv
 - Uses RMarkdown and a LaTeX-like syntax
 - **Search:**
 - client-side (Javascript that runs in browser - fuse.js)
 - also typically available in RStudio

Long-Form Documentation for R is typically contained in [vignettes](#) .
C/C++

- [Doxygen](#)
 - **API Reference generation** out of the box, generates static call graph
 - Focus on Documentation directly in the source code
 - Markdown-like syntax, with its own flavour and [special commands](#)
 - **Search:**
 - limited keyword-based client-side
 - full text search server-side
- [Sphinx](#) can be also used to generate documentation for C++ projects, using the XML output from Doxygen via [Breathe](#)

Fortran

- [Doxygen](#):
 - **API Reference generation** out of the box, generates static call graph (but has limited Fortran parsing capabilities)
 - Focus on Documentation directly in the source code
 - Markdown-like syntax, with its own flavour and [special commands](#)
 - **Search:**
 - limited keyword-based client-side
 - full text search server-side
- [FORD](#)
 - Python-based
 - **Search:** client-side (Javascript that runs in the browser - lunr.js)

Julia

- [Documenter.jl](#)
 - Using Markdown (JuliaMarkdown flavour)
 - Parses Julia code and in-code documentation/docstrings
 - **Search:** client-side (but typically the whole site is loaded for search on every page)
 - **Validation:** runs the code and checks

Rust

[RustDoc](#)

- Uses Markdown (CommonMark flavour)
- **Search:** client-side (Javascript that runs in the browser - elasticlunr.js)
- **Validation:** validates code examples when run with `--test`

Any

These are general-purpose static website generators that match the philosophy of the other tools presented so far, but might be better suited for blogging, reports or other kinds of publications:

- [Hugo](#) 
- [Hexo](#) 
- [Zola](#)  ← this is what we use for our project website and workshop websites
- [Jekyll](#) , default for GitHub pages
- [Franklin.jl](#) : focuses on technical blogging for the Julia community
- [Quarto](#)  converts markdown to websites, pdfs, ebooks and many other things (dynamic notebook-based documents)

Discussion

Do you know an awesome tool or feature that should be in this list? Let us know! (Open a PR)

Hosting Documentation on the Web

GitHub, GitLab, and Bitbucket make it possible to serve HTML pages:

- [GitHub Pages](#) 
- [Bitbucket Pages](#) 
- [GitLab Pages](#) 

[Read The Docs](#)  is also free to use for open source code, and can be [connected](#)  to common software forges.

Wikis

- Popular solutions (but many others exist):
 - [MediaWiki](#) 
 - [Dokuwiki](#) 
 - Advantage
 - Barrier to write and edit is low
 - Disadvantages
 - Typically disconnected from source code repository (**reproducibility**)
 - Difficult to serve multiple versions
 - Difficult to check out a specific old version
 - Typically needs to be hosted and maintained
-

- Advantage
 - Popular and familiar in the physics and mathematics community
- Disadvantages
 - PDF format is not ideal for copy-pasting of examples
 - Possible, but not trivial to automate rebuilding documentation after every Git push

! Keypoints

- Some popular solutions make reproducibility and maintenance of multiple code versions difficult.

Motivation and wishlist

Motivation

💬 Motivation-1: Why documenting code?

Use the collaborative document:

- Is project documentation important? Why?
- How would you describe a useful documentation?
- How can you motivate your colleagues to contribute to the documentation?

✓ Our motivation (but let us brainstorm first)

- You will probably use your code in the future and may forget details.
- You may want others to use your code (almost impossible without documentation).
- You may want others to contribute to the code.
- Shield your limited time and let the documentation answer FAQs.

What do we expect from a suitably good documentation?

! Note

Documentation comes in different forms - what *is* documentation?

- **Tutorials:** learning-oriented, allows the newcomer to get started
- **How-to guides:** goal-oriented, shows how to solve a specific problem
- **Explanation:** understanding-oriented, explains a concept
- **Reference:** information-oriented, describes the machinery

Read more:

- <https://www.divio.com/blog/documentation/>
- <https://diataxis.fr/>
- <https://www.writethedocs.org/guide/writing/beginners-guide-to-docs/>

There is no one size fits all: often for small projects a `README.md` or `README.rst` can be enough (more about these formats later).

Creating a checklist

💬 Motivation-2: Create a wishlist

Use the collaborative document:

- Let us create a wishlist for how we would like documentation to be.
- Below are some of our ideas but please do not look at them yet.
- We are sure you will come up with ideas we did not think about.

✓ Our wishlist (but let us brainstorm first)

Versions

- Your code project should be versioned (version control).
- Enable reproducibility and avoid confusion: **documentation should be versioned** as well.
- Have you ever seen: *"We will soon release a new version and are updating the documentation. Some features may not be available in the version you have downloaded."*?

Documentation should be placed and tracked close to the source code

- Documenting **close to the source code** (e.g. subdirectory `doc/`) minimizes barrier to contribute.
- I should not need to log in to another machine or service and jump through hoops to contribute.
- It is often good enough to have a `README.md` or `README.rst` along with your code/script.

Use a standard markup language

Markup

Markup is a set of human readable instructions that is used to tell the computer how a document shall be styled and structured. By using a markup language we can for example write a `*` or `-` where we want a bullet point to appear in the rendered document.

- offers formatting flexibility, enforces a basic document structure and the rendered documents can be exported to other formats (e.g. for printing). Also, the source can be read by humans without knowledge of the language in case the rendered document is unavailable.
- We suggest to use either [reStructuredText \(RST\)](#) or [Markdown](#) markup.
- GitHub and GitLab automatically render `README.md` or `README.rst` files.

Copy-paste-able

- PDF alone is not enough since **copy-pasting out of a PDF document can be difficult**.
- It is OK to provide a generated PDF in addition to a copy-paste-able format.

Written by humans

- Automatically generated documentation (e.g. API documentation) is useful as complementary documentation but it does not replace tutorials written by humans.

Installation instructions

- Give **step by step instructions for the basic case**. Additional information and caveats can be linked from there.
- List requirements and dependencies (libraries, compilers, environment).
- Include instructions for how to test for correctness after installation.

Make the license explicit

- **Include a LICENSE file** with your source code.
- Without a license, your work is under exclusive copyright by default: others are not allowed to re-use or modify anything.
- GitHub and GitLab allows to choose a license from common license templates.

Information for contributors

- Make it easy for others to contribute: **document how you prefer others to contribute**.
- Users of your code may be shy to contribute code. Your **documentation provides a platform for your first contributions**.

📌 Documentation checklist

Which items to include depends on the number of users apart from yourself.

- Purpose
- Authors
- License

- Recommended citation
- Copy-paste-able example to get started
- Dependencies and their versions or version ranges
- Installation instructions
- Tutorials covering key functionality
- Reference documentation (e.g. API) covering all functionality
- How do you want to be asked questions (mailing list or forum or chat or issue tracker)
- Possibly a FAQ section
- Contribution guide

! Keypoints

- Documentation is part of the code and should be versionable.
- Documentation (sources) should be tracked with the corresponding code in the same repository.
- Use standard markup languages such as reStructuredText or Markdown.

Summary

? Questions

- What recommendations can we take home?

There is not the one right way: it is always a balance

Jupyter notebooks can be good documentation for scripts

- For simple scripts and post-processing, Jupyter notebooks can form a nice self-documenting pipeline.
- They can be a nice way to accompany a paper that analyzed some data.

READMEs or Sphinx?

- For smaller projects READMEs can be absolutely enough.
- If the code is closed-source (and hence nobody can see the README), you probably prefer Sphinx (or similar).
- If you need math equations, Sphinx might be a good fit.

How to make sure that code changes come together with documentation changes?

- Make documentation part of your code review.

Read the Docs or GitHub pages or both?

- GitHub pages typically serves one version (one branch). However, it is possible to build several or all branches as part of a workflow.
- Read the Docs can serve several versions (several branches/tags) at the same time.
- Some projects use both.

Consider making your development tutorial-driven

- Writing documentation is as important as writing software.
- Focus on how you use the software.
- If there is no tutorial on it, the feature “doesn't exist”.
- Don't keep tutorial in sync with code, keep code in sync with tutorial - change the tutorial first.
- Read more in this [fantastic slide-deck](#) about tutorial-driven development.

Hosting websites/homepages on GitHub Pages

Often we don't need more than a static website

You can host your personal homepage or group webpage or project website on GitHub using [GitHub Pages](#). [GitLab](#) and [Bitbucket](#) also offer a very similar solution.

Unless you need user authentication or a sophisticated database behind your website, [GitHub Pages](#) can be a very nice alternative to running your own web servers. This is how all <https://coderefinery.org> material is hosted.

How to find the website URL

Here below, NAMESPACE can either be a username or an organizational account.

Personal homepage or organizational homepage

- Generated URL: `https://NAMESPACE.github.io`
- Generated from: `https://github.com/NAMESPACE/NAMESPACE.github.io` (main branch)

Project website

- Generated URL: `https://NAMESPACE.github.io/REPOSITORY`
- Generated from: `https://github.com/NAMESPACE/REPOSITORY` (gh-pages branch)

Exercise - Your own website on GitHub Pages

GH-Pages-2: Host your own github page

- Deploy own website reusing a template:

- Follow the steps from GitHub Pages <https://pages.github.com/>. The documentation there is very good so there is no need for us to duplicate the screenshots.
- Select “Project site”.
- Select “Choose a theme”.
- Follow the instructions on <https://pages.github.com/>.
- Browse your page on <https://USERNAME.github.io/REPOSITORY> (adjust “USERNAME” and “REPOSITORY”).
- Make a change to the repository after the webpage has been deployed for the first time.
- Please wait few minutes and then verify that the change shows up on the website.

! Real-life examples

- CodeRefinery website (built using [Zola](#))
 - [Source](#)
 - Result: <https://coderefinery.org/lessons/>
- This lesson (built using [Sphinx](#) and [MyST](#) and [sphinx-lesson](#))
 - [Source](#)
 - Result: this page

! Note

- You can use HTML directly or another static site generator if you prefer to not use the default [Jekyll](#).
- It is no problem to use a custom domain instead of `*.github.io`.

List of exercises

Full list

This is a list of all exercises and solutions in this lesson, mainly as a reference for helpers and instructors. This list is automatically generated from all of the other pages in the lesson. Any single teaching event will probably cover only a subset of these, depending on their interests.

Instructor guide

Why we teach this lesson

Everyone should document their code, even if they’re working alone.

These are the main points:

- Code documentation has to be versionnable and branchable
- Code documentation should be tracked together with the source code
- README is often enough

Please do not skim over the two above points. Please take few minutes to explain why documentation (sources) should be tracked together with the source code. Please discuss this aspect with workshop participants and connect it to **reproducibility**. This is for me (Radovan) the most important take-home message.

Specific motivations:

- Code documentation becomes quickly unmanageable if not part of the source code.
- It helps people to quickly use your code thus reducing the time spent to explain over and again to new users.
- It helps people to collaborate.
- It improves the design of your code.

Intended learning outcomes

By the end of this lesson, learners should:

- Understand the importance of writing code documentation together with the source code
- Know what makes a good documentation
- Learn what tools can be used for writing documentation
- Be able to motivate a balanced decision: sometimes READMEs are absolutely enough

Timing

As an instructor you should prepare all bullet points but do not go through each bullet point in detail. Only highlight the main points and rather give time for a discussion. Leave details for a later lecture for those who want to find out more. If you go through each bullet point in detail, the motivation can easily take up 30 minutes and you will run out of time.

The lesson does not fit into 1.5 hours if you go through everything. Optimize for discussions and prepare well to be able to jump over bullet points which can be left for a later lecture. Some sections can be skipped if needed (see below). However, we recommend to have a discussion with your learners to make them aware of what the training material contains.

- Do not insist on practicing Markdown or RST syntax.
- The section *Rendering (LaTeX) math equations* may be optional if your attendees do not have to deal with equations.
- In the GitHub Pages episode, the goal is not anymore to write code documentation but to show how to build project website with GitHub. If time is tight, the GitHub pages episode can be skipped or can be done as demonstration instead of exercise.

Detailed schedule

- 09:00 - 09:10 Motivation and tools
 - create a wishlist in collaborative notes
- 09:10 - 09:20 Writing good README files
 - brief discussion
- 09:20 - 09:40 **Exercises:** README-1, README-2, README-3 (choose one or multiple)
- 09:40 - 10:00 Sphinx and Markdown: Sphinx-1 as type along
- 10:00 - 10:10 Break
- 10:10 - 10:40 **Exercises,** Sphinx-2, Sphinx-3, GH-Pages-1
- 10:40 - 11:00 Discussion, GH Pages, Summary

Place this lesson towards the end of the workshop

Reason is that with collaborative Git we can create more interesting documentation exercises. Currently there are some elements of forking and pushing and this is only really introduced on day two. We have tried this lesson on day one and it felt too early and disconnected/abrupt. It works best after the reproducibility lesson since we then reuse the example and it feels familiar.

Troubleshooting

Character encoding issues

Can arise when using non-utf8 characters in `conf.py`. Diagnose this with `file -i conf.py` and `locale`.

Live better than reading the website material

It is better to demonstrate the commands live and type-along. Ideally connecting to examples discussed earlier.

In online workshops most of the type-along becomes group exercise work where groups can share screen and discuss.

Field reports

2022 September

We were pressed for time (we started 5-10 minutes late, relative to the schedule below), so we made most of the first lessons fast. In the schedule below, note that we had the first 10 minutes for “Motivation” *and* “Popular tools”, which we didn’t fully realize so that put us even further behind. Doing these introduction parts quickly was hard but was probably worth it

since we had plenty of time in the end. For the “tools”, one person summarized the point of each section on the page quickly. The README episode was done quickly, we basically skipped the exercises to get to Sphinx, and this put us back on schedule.

For Sphinx, we did it a lot like you see in the schedule: first exercise (the basic setup) was type-along, but it was a bit too much to do in the 10 minutes we had allotted (we typed too fast). But, people then had a nice long time to make it up and do everything. It seemed to work well. The GitHub pages deployment could then be done as a nice, slow demo, and we had plenty of time to ask questions.

Overall, I think this was the right track, but we could have practiced doing the first parts even faster, and warned people that we focus on the Sphinx exercises.

Reusing

This lesson material is free to reuse, adapt, and cite. This page collects everything you need to do so.

How to cite this lesson

If you use this lesson material, please cite it using this DOI:

<https://doi.org/10.5281/zenodo.8280234>

The machine-readable citation record is kept in `CITATION.cff` at the root of this lesson’s repository, which lists the full set of contributing authors and stays up to date as the lesson evolves.

Structured metadata

This lesson also publishes its metadata as machine-readable [Bioschemas](#) / [schema.org](#) structured data, embedded as JSON-LD on every page of this site. You can inspect the source directly in `bioschemas.yml`.

License

Website template

The website template is maintained by [CodeRefinery](#) and rendered with [sphinx-lesson: structured lessons with Sphinx](#).

Instructional material

All CodeRefinery instructional material is made available under the [Creative Commons Attribution license \(CC-BY-4.0\)](#)[↗]. The following is a human-readable summary of (and not a substitute for) the [full legal text of the CC-BY-4.0 license](#)[↗].

You are free:

- to **Share** - copy and redistribute the material in any medium or format
- to **Adapt** - remix, transform, and build upon the material

for any purpose, even commercially. The licensor cannot revoke these freedoms as long as you follow these license terms:

- **Attribution** - You must give appropriate credit (mentioning that your work is derived from work that is Copyright (c) CodeRefinery and, where practical, linking to <https://coderefinery.org>[↗], provide a [link to the license](#)[↗], and indicate if changes were made. You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use.

No additional restrictions - You may not apply legal terms or technological measures that legally restrict others from doing anything the license permits. With the understanding that:

- You do not have to comply with the license for elements of the material in the public domain or where your use is permitted by an applicable exception or limitation.
- No warranties are given. The license may not give you all of the permissions necessary for your intended use. For example, other rights such as publicity, privacy, or moral rights may limit how you use the material.