

# C++ vs Haskell vs BQN



Conor Hoekstra





code\_report




codereport





# About Me

Conor Hoekstra / @code\_report





319 Videos



32 (20) Talks

## Algorithms + Data Structures = Programs

136 Episodes  
@adspthepodcast



## Array Cast

56 Episodes  
@arraycast



**RUN**   
**FOR THE**  
**FUN**   
**OF IT!**

10 Episodes  
@conorhoekstra



<https://github.com/codereport/Content>

[1, 2, 3, 4, 5]

[1, 3, 5]



C++14 Function Deduced  
Return Type

```
auto filter_odds(std::vector<int> nums) {  
    auto odds = std::vector<int>{};  
    for (auto const num : nums)  
        if (num % 2 == 1)  
            odds.push_back(num);  
    return odds;  
}
```

C++11 auto

C++11 range-  
based for



```
auto filter_odds(std::vector<int> nums) {  
    auto odds = std::vector<int>{};  
    std::copy_if(  
        nums.begin(), nums.end(),  
        std::back_inserter(odds),  
        [](auto e) { return e % 2 == 1; });  
    return odds;  
}
```

C++11 lambda





```
auto filter_odds(std::vector<int> nums) {  
    auto odds = std::vector<int>{};  
    std::copy_if(  
        nums.begin(), nums.end(),  
        std::back_inserter(odds),  
        [](auto e) { return e % 2 == 1; });  
    return odds;  
}
```

C++14 generic lambda



```
auto filter_odds(std::vector<int> nums) {  
    auto odds = std::vector<int>{};  
    std::ranges::copy_if(  
        nums, std::back_inserter(odds),  
        [](auto e) { return e % 2 == 1; });  
    return odds;  
}
```

C++20 range overload



```
auto filter_odds(std::vector<int> nums) {  
    return nums  
        | std::views::filter(  
            [](auto e) { return e % 2 == 1; });  
}
```

C++20 Ranges



```
filterOdd xs = filter (\e -> mod e 2 == 1) xs
```



```
filterOdd xs = filter odd xs
```



`filterOdd = filter odd`



`filter odd`

NEV





$$\{(2 \mid x) / x\}$$




$$\underbrace{2 \rightarrow 1 / \vdash}_{\emptyset} \quad \text{I}$$



W



$\{ \mathbf{x} / \sim 2 | \mathbf{x} \}$






$$\underbrace{2 \rightarrow 1 / \vdash}_{\emptyset} \quad \text{I}$$



$$2 \rightarrow \bullet \mid \rightarrow \bullet /$$

$\Sigma$  


**combinatorylogic.com**  
**bqnpad.mechanize.systems**  
**tryapl.org**




# Thank You

<https://github.com/codereport/Content/Talks>

Conor Hoekstra

 code\_report

 codereport