

































## EXTREME PLUS LED HEADLIGHT CONVERSION KITS

Product Picture	Product Dimension (mm)	Product Specification	Model No.	LED chip brand	Input (A)	Lumens (lm)	Color
		1.LED Quantity: 8PCS-G-XP 2.Voltage: DC9V-32V 3.Beam Angle: 360° 4. Temperature: -45±85℃ 5.Usage:Head Light/Fog light	LHK-EXT-P-H4	G-XP	H:3.8A±0.3A L:3.8A±0.3A	10000 10000	Pure White
		1.LED Quantity: 8PCS-G-XP 2.Voltage: DC9V-32V 3.Beam Angle: 360° 4. Temperature: -45±85℃ 5.Usage:Head Light/Fog light	LHK-EXT-P-H13	G-XP	H:3.8A±0.3A L:3.8A±0.3A	10000 10000	Pure White
		1.LED Quantity: 8PCS-G-XP 2.Voltage: DC9V-32V 3.Beam Angle: 360° 4. Temperature: -45±85℃ 5.Usage:Head Light/Fog light	LHK-EXT-P-9004	G-XP	H:3.8A±0.3A L:3.8A±0.3A	10000 10000	Pure White
		1.LED Quantity: 8PCS-G-XP 2.Voltage: DC9V-32V 3.Beam Angle: 360° 4. Temperature: -45±85℃ 5.Usage:Head Light/Fog light	LHK-EXT-P-9007	G-XP	H:3.8A±0.3A L:3.8A±0.3A	10000 10000	Pure White
		1.LED Quantity: 4PCS-G-XP 2.Voltage: DC9V-32V 3.Beam Angle: 360° 4. Temperature: -45±85℃ 5.Usage:Head Light/Fog light	LHK-EXT-P-H7	G-XP	3.8A±0.3A	10000	Pure White
		1.LED Quantity: 4PCS-G-XP 2.Voltage: DC9V-32V 3.Beam Angle: 360° 4. Temperature: -45±85℃ 5.Usage:Head Light/Fog light	LHK-EXT-P-HB3 9005	G-XP	3.8A±0.3A	10000	Pure White
		1.LED Quantity: 4PCS-G-XP 2.Voltage: DC9V-32V 3.Beam Angle: 360° 4. Temperature: -45±85℃ 5.Usage:Head Light/Fog light	LHK-EXT-P-HB4 9006	G-XP	3.8A±0.3A	10000	Pure White
		1.LED Quantity: 4PCS-G-XP 2.Voltage: DC9V-32V 3.Beam Angle: 360° 4. Temperature: -45±85℃ 5.Usage:Head Light/Fog light	LHK-EXT-P-H10	G-XP	3.8A±0.3A	10000	Pure White

Product Picture	Product Dimension (mm)	Product Specification	Model No.	LED chip brand	Input (A)	Lumens (lm)	Color
		1.LED Quantity: 4PCS-G-XP 2.Voltage: DC9V-32V 3.Beam Angle: 360° 4. Temperature: -45±85℃ 5.Usage:Head Light/Fog light	LHK-EXT-P-HIR2-9012	G-XP	3.8A±0.3A	10000	Pure White
		1.LED Quantity: 4PCS-G-XP 2.Voltage: DC9V-32V 3.Beam Angle: 360° 4. Temperature: -45±85℃ 5.Usage:Head Light/Fog light	LHK-EXT-P-H8/H9	G-XP	3.8A±0.3A	10000	Pure White
		1.LED Quantity: 4PCS-G-XP 2.Voltage: DC9V-32V 3.Beam Angle: 360° 4. Temperature: -45±85℃ 5.Usage:Head Light/Fog light	LHK-EXT-P-H11	G-XP	3.8A±0.3A	10000	Pure White
		1.LED Quantity: 4PCS-G-XP 2.Voltage: DC9V-32V 3.Beam Angle: 360° 4. Temperature: -45±85℃ 5.Usage:Head Light/Fog light	LHK-EXT-P-H16 (JP)	G-XP	3.8A±0.3A	10000	Pure White
		1.LED Quantity: 4PCS-G-XP 2.Voltage: DC9V-32V 3.Beam Angle: 360° 4. Temperature: -45±85℃ 5.Usage:Head Light/Fog light	LHK-EXT-P-PSX24W	G-XP	3.8A±0.3A	10000	Pure White
		1.LED Quantity: 4PCS-G-XP 2.Voltage: DC9V-32V 3.Beam Angle: 360° 4. Temperature: -45±85℃ 5.Usage:Head Light/Fog light	LHK-EXT-P-H16W (EU)	G-XP	3.8A±0.3A	10000	Pure White
		1.LED Quantity: 4PCS-G-XP 2.Voltage: DC9V-32V 3.Beam Angle: 360° 4. Temperature: -45±85℃ 5.Usage:Head Light/Fog light	LHK-EXT-P-PSX26W	G-XP	3.8A±0.3A	10000	Pure White
		1.LED Quantity: 4PCS-G-XP 2.Voltage: DC9V-32V 3.Beam Angle: 360° 4. Temperature: -45±85℃ 5.Usage:Head Light/Fog light	LHK-EXT-P-P13W	G-XP	3.8A±0.3A	10000	Pure White