# Introduction to Machine Learning, Fall 2015 -Exercise session VI

Rodion "rodde" Efremov, student ID 013593012 December 9, 2015

### Intro

The only material I used are the slides. Did not discuss in a group, except mailed Amin about possible "typo" which wasn't one. I omitted the pen and paper exercises.

# 1 Problem 4 (Programming task)

#### 1.1 k-means

#### 1.1.1 Uset first 10 images as the initial cluster means

So when I run the k-means algorithm using **10 first images** as the initial means, I get the following means: And the classified digits follow:




Figure 1: First iteration cluster means




Figure 2: Digits 0




Figure 3: Digits 1




Figure 4: Digits 2




Figure 5: Digits 3




Figure 6: Digits 4




Figure 7: Digits 5




Figure 8: Digits 6




Figure 9: Digits 7




Figure 10: Digits 8




Figure 11: Digits 9

## 1.1.2 Use the first images with distinct digits

Here, we used the first 10 **unique** digits as the initial cluster means.




Figure 12: Second iteration cluster means

The classified digits follow:

Obvously, the first iteration with non-unique digits as the initial cluster means perform rather poorly. The second iteration that uses distinct digit clusters improves on the latter, yet it is far from perfect.




Figure 13: Digits 0




Figure 14: Digits 1




Figure 15: Digits 2




Figure 16: Digits 3




Figure 17: Digits 4




Figure 18: Digits 5




Figure 19: Digits 6




Figure 20: Digits 7




Figure 21: Digits 8




Figure 22: Digits 9