

**Title will be here**

Rodion Efremov

Master thesis  
UNIVERSITY OF HELSINKI  
Department of Computer Science

Helsinki, May 5, 2016

Tiedekunta — Fakultet — Faculty		Laitos — Institution — Department	
Faculty of Science		Department of Computer Science	
Tekijä — Författare — Author			
Rodion Efremov			
Työn nimi — Arbetets titel — Title			
Title will be here			
Oppiaine — Läroämne — Subject			
Computer Science			
Työn laji — Arbetets art — Level	Aika — Datum — Month and year	Sivumäärä — Sidoantal — Number of pages	
Master thesis	May 5, 2016	1	
Tiivistelmä — Referat — Abstract			
Abstract goes here			
Avainsanat — Nyckelord — Keywords			
Säilytyspaikka — Förvaringsställe — Where deposited			
Muita tietoja — Övriga uppgifter — Additional information			

## Contents

0.1	Strongly connected components . . . . .	1
0.1.1	Kosaraju's algorithm . . . . .	1

## Dummy section

### 0.1 Strongly connected components

Since our methods require the input graph to be strongly connected, we review here briefly how to algorithmically validate that the input graph exhibits the requirement. A directed graph is called *strongly connected* if and only if for every pair of nodes  $u, v$  of the graph  $u$  is reachable from  $v$ , and  $v$  is reachable from  $u$ . Let  $u \stackrel{r}{\sim} v$  denote the aforementioned reachability relation. Now, it is easy to see that

**(Reflexivity)**  $u \stackrel{r}{\sim} u$ , for all  $u \in V(G)$ .

**(Symmetry)** if  $u \stackrel{r}{\sim} v$ , then  $v \stackrel{r}{\sim} u$ .

**(Transitivity)** If  $u \stackrel{r}{\sim} v$  and  $v \stackrel{r}{\sim} v'$ , then  $u \stackrel{r}{\sim} v'$ .

The above three properties imply that  $\stackrel{r}{\sim}$  is an equivalence relation, and as such, implies that the graph has a unique partition into strongly connected components.

Algorithms for finding all strongly connected components of a graph in linear time are known. We review three of them below.

#### 0.1.1 Kosaraju's algorithm

---

**Algorithm 1:** KOSARAJUVISIT( $G, S, L, v$ )

---

```

1 if  $v \notin S$  then
2    $S \leftarrow S \cup \{v\}$ 
3   for  $(v, w) \in G(A)$  do
4      $\text{KOSARAJUVISIT}(G, S, L, w)$ 
5    $L \leftarrow \langle v \rangle \circ L$ 

```

---



---

**Algorithm 2:** KOSARAJUASSIGN( $G, \mu, u, r$ )

---

```

1 if  $(u \mapsto r) \notin \mu$  then
2    $\mu(u) \leftarrow r$ 
   For all parents of  $u$ 
3   for  $(v, u) \in G(A)$  do
4      $\text{KOSARAJUASSIGN}(G\mu, v, r)$ 

```

---

---

**Algorithm 3:** KOSARAJUSCC( $G$ )

---

```
1  $S \leftarrow \emptyset$ 
2  $L \leftarrow \langle \rangle$ 
3  $\mu \leftarrow \emptyset$ 
4 for  $v \in V(G)$  do
5    $\lfloor$  KOSARAJUVISIT( $G, S, L, v$ )
   Iterate the list  $L$  in its natural order
6 for  $v \in L$  do
7    $\lfloor$  KOSARAJUASSIGN()
```

---