

PDF Combiner

A simple Windows Forms app to combine multiple PDF files in a single PDF file

Table of Contents

Symbol Reference	1
PdfCombiner Namespace	1
PdfCombiner.Properties Namespace	1
Classes	1
Resources Class	1
Settings Class	3
Classes	4
BaseException Class	5
BaseException Constructor	5
ExceptionExtensions Class	6
ExceptionExtensions Methods	6
FrmMain Class	7
FrmMain.FrmMain Constructor	8
FrmMain Fields	8
FrmMain Methods	10
Program Class	19
Program Methods	19
Files	20
AssemblyInfo.cs	20
Exceptions.cs	21
FrmMain.cs	22
FrmMain.Designer.cs	27
PdfCombiner.csproj	30
PdfCombiner.sln	30
Program.cs	30
Resources.Designer.cs	31
Settings.Designer.cs	32
Index	а

1 Symbol Reference

1.1 PdfCombiner Namespace

This is namespace PdfCombiner.

Namespaces

Name	Description
Properties (see page 1)	This is namespace PdfCombiner.Properties.

Classes

	Name	Description
♣ 🏔	BaseException (see page 5)	This function is used to take exceptions which can be thrown in PDF Combiner App
4 ; 🗟	ExceptionExtensions (see page 6)	This is class PdfCombiner.ExceptionExtensions.
4\$	FrmMain (☑ see page 7)	This is class PdfCombiner.FrmMain.
₹ ; 😽	Program (a see page 19)	This is class PdfCombiner.Program.

1.1.1 PdfCombiner.Properties Namespace

This is namespace PdfCombiner.Properties.

Classes

	Name	Description
4	\$ Resources (see page 1)	A strongly-typed resource class, for looking up localized strings, etc.
4	\$ Settings (≥ see page 3)	This is class PdfCombiner.Properties.Settings.

1.1.1.1 Classes

The following table lists classes in this documentation.

Classes

1		Name	Description
	^ 1\$	Resources (see page 1)	A strongly-typed resource class, for looking up localized strings, etc.
	^ 3	Settings (Is see page 3)	This is class PdfCombiner.Properties.Settings.

1.1.1.1.1 Resources Class

A strongly-typed resource class, for looking up localized strings, etc.

Class Hierarchy

PdfCombiner.Properties.Resources

C#

```
[global::System.CodeDom.Compiler.GeneratedCodeAttribute("System.Resources.Tools.StronglyType
dResourceBuilder",
"15.0.0.0")]
[global::System.Diagnostics.DebuggerNonUserCodeAttribute()]
[global::System.Runtime.CompilerServices.CompilerGeneratedAttribute()]
internal class Resources;
```

File

Resources.Designer.cs (see page 31)

Description

This class was auto-generated by the StronglyTypedResourceBuilder class via a tool like ResGen or Visual Studio. To add or remove a member, edit your .ResX file then rerun ResGen with the /str option, or rebuild your VS project.

Methods

	Name	Description
= ♠ _?	Resources (see page 2)	This is Resources, a member of class Resources.

Resources Fields

	Name	Description
4 3 😽	resourceCulture (☑ see page 2)	This is resourceCulture, a member of class Resources.
∳ ≘ <mark>S</mark> S	resourceMan (≥ see page 3)	This is resourceMan, a member of class Resources.

Resources Properties

	Name	Description
≅ • 8	Culture (see page 3)	Overrides the current thread's CurrentUICulture property for all resource lookups using this strongly typed resource class.
** 8	Deletelcon (see page 3)	Looks up a localized resource of type System.Drawing.Bitmap.
* S	Deletelcon1 (≥ see page 3)	Looks up a localized resource of type System.Drawing.Bitmap.
** 8	ResourceManager (see page 3)	Returns the cached ResourceManager instance used by this class.

1.1.1.1.1.1 Resources.Resources Constructor

C#

```
[global::System.Diagnostics.CodeAnalysis.SuppressMessageAttribute("Microsoft.Performance",
"CA1811:AvoidUncalledPrivateCode")]
internal Resources();
```

Description

This is Resources, a member of class Resources.

Body Source

```
1:
[global::System.Diagnostics.CodeAnalysis.SuppressMessageAttribute("Microsoft.Performance",
"CA1811:AvoidUncalledPrivateCode")]
2: internal Resources() {
3: }
```

1.1.1.1.1.2 Resources Fields

1.1.1.1.2.1 Resources.resourceCulture Field

C#

```
private static global::System.Globalization.CultureInfo resourceCulture;
```

PdfCombiner.Properties Namespace

This is resourceCulture, a member of class Resources.

1.1.1.1.1.2.2 Resources.resourceMan Field

C#

private static global::System.Resources.ResourceManager resourceMan;

Description

This is resourceMan, a member of class Resources.

1.1.1.1.3 Resources Properties

1.1.1.1.3.1 Resources.Culture Property

Overrides the current thread's CurrentUICulture property for all resource lookups using this strongly typed resource class.

C#

```
[global::System.ComponentModel.EditorBrowsableAttribute(global::System.ComponentModel.Editor
BrowsableState.Advanced)]
internal static global::System.Globalization.CultureInfo Culture;
```

1.1.1.1.3.2 Resources.Deletelcon Property

Looks up a localized resource of type System.Drawing.Bitmap.

C#

internal static System.Drawing.Bitmap DeleteIcon;

1.1.1.1.3.3 Resources.Deletelcon1 Property

Looks up a localized resource of type System.Drawing.Bitmap.

C#

```
internal static System.Drawing.Bitmap DeleteIcon1;
```

1.1.1.1.3.4 Resources.ResourceManager Property

Returns the cached ResourceManager instance used by this class.

C#

```
[global::System.ComponentModel.EditorBrowsableAttribute(global::System.ComponentModel.Editor
BrowsableState.Advanced)]
internal static global::System.Resources.ResourceManager ResourceManager;
```

1.1.1.1.2 Settings Class

Class Hierarchy

```
global::System.Configuration.ApplicationSettingsBase PdfCombiner.Properties.Settings
```

C#

```
[global::System.Runtime.CompilerServices.CompilerGeneratedAttribute()]
[global::System.CodeDom.Compiler.GeneratedCodeAttribute("Microsoft.VisualStudio.Editors.SettingsDesigner.SettingsSingleFileGenerator",
"11.0.0.0")]
internal sealed class Settings : global::System.Configuration.ApplicationSettingsBase;
```

Settings.Designer.cs (see page 32)

Description

This is class PdfCombiner.Properties.Settings.

Settings Fields

		Name	Description
₽ ₽	8	defaultInstance (see page 4)	This is defaultInstance, a member of class Settings.

Settings Properties

	Name	Description
8	Default (see page 4)	This is Default, a member of class Settings.

1.1.1.1.2.1 Settings Fields

1.1.1.1.2.1.1 Settings.defaultInstance Field

C#

```
private static Settings defaultInstance =
((Settings)(global::System.Configuration.ApplicationSettingsBase.Synchronized(new
Settings())));
```

Description

This is defaultInstance, a member of class Settings.

1.1.1.1.2.2 Settings Properties

1.1.1.1.2.2.1 Settings.Default Property

C#

```
public static Settings Default;
```

Description

This is Default, a member of class Settings.

1.1.2 Classes

The following table lists classes in this documentation.

Classes

	Name	Description
♣ 🏔	BaseException (☐ see page 5)	This function is used to take exceptions which can be thrown in PDF Combiner App
♣ ; 🕏	ExceptionExtensions (see page 6)	This is class PdfCombiner.ExceptionExtensions.
4\$	FrmMain (see page 7)	This is class PdfCombiner.FrmMain.
4 ; S	Program (see page 19)	This is class PdfCombiner.Program.

1.1.2.1 BaseException Class

This function is used to take exceptions which can be thrown in PDF Combiner App

Class Hierarchy

```
#

[Serializable]

public abstract class BaseException : Exception;
```

File

Exceptions.cs (see page 21)

Methods

	Name	Description
≡∳ ?	BaseException (see page 5)	This is BaseException, a member of class BaseException.

1.1.2.1.1 BaseException Constructor

1.1.2.1.1.1 BaseException.BaseException Constructor ()

C#

```
protected BaseException();
```

Description

This is BaseException, a member of class BaseException.

Body Source

```
1: protected BaseException()
2: {
3: }
```

1.1.2.1.1.2 BaseException.BaseException Constructor (string)

C#

```
protected BaseException(string message);
```

Description

This is BaseException, a member of class BaseException.

Body Source

```
1: protected BaseException(string message) : base(message)
2: {
3: }
```

1.1.2.1.1.3 BaseException.BaseException Constructor (string, Exception)

C#

```
protected BaseException(string message, Exception innerException);
```

Description

This is BaseException, a member of class BaseException.

Body Source

```
1: protected BaseException(string message, Exception innerException) : base(message, innerException)
2: {
3: }
```

1.1.2.2 ExceptionExtensions Class

Class Hierarchy

PdfCombiner.ExceptionExtensions

C#

public static class ExceptionExtensions;

File

Exceptions.cs (see page 21)

Description

This is class PdfCombiner.ExceptionExtensions.

ExceptionExtensions Methods

	Name	Description
=♦ \	GetAllMessages (see page 6)	This method is used to take all messages with stack trace info in
		exception

1.1.2.2.1 ExceptionExtensions Methods

1.1.2.2.1.1 ExceptionExtensions.GetAllMessages Method

This method is used to take all messages with stack trace info in exception

C#

public static string GetAllMessages(this Exception exception);

Parameters

Parameters	Description
this Exception exception	Exception

Returns

Detailed Error Message

Body Source

```
1: public static string GetAllMessages(this Exception exception)
 2: {
 3:
        var messages = exception. Message;
 4:
        if (exception.InnerException != null)
 5:
            messages += " " + exception.InnerException.GetAllMessages();
        if (!string.IsNullOrEmpty(exception.StackTrace))
 6:
 7:
            messages += " " + exception.StackTrace;
        if (!string.IsNullOrEmpty(exception.Source))
 8:
                          " + exception.Source;
 9:
            messages += "
10:
        return messages;
11: }
```

1.1.2.3 FrmMain Class

Class Hierarchy



C#

public class FrmMain : Form;

File

FrmMain.Designer.cs (see page 27)

Description

This is class PdfCombiner.FrmMain.

Methods

	Name	Description
≡♦	FrmMain (⊿ see page 8)	This is FrmMain, a member of class FrmMain.

FrmMain Fields

	Name	Description
•	AppTitle (see page 8)	This is AppTitle, a member of class FrmMain.
₽ ⊇	btnAddFile (☐ see page 8)	This is btnAddFile, a member of class FrmMain.
₽ ⊇	btnAddFolder (≥ see page 8)	This is btnAddFolder, a member of class FrmMain.
₽ ⊇	btnClearList (☑ see page 9)	This is btnClearList, a member of class FrmMain.
₽ ®	btnCombinelTextSharp (⋑ see page 9)	This is btnCombinelTextSharp, a member of class FrmMain.
₽ ®	btnCombinePdfSharp (☐ see page 9)	This is btnCombinePdfSharp, a member of class FrmMain.
₽ @	components (see page 9)	Required designer variable.
4 0	lbFiles (≥ see page 9)	This is lbFiles, a member of class FrmMain.
₽ ⊗	lblDetails (≥ see page 9)	This is lblDetails, a member of class FrmMain.
₽ ⊗	menultemDelete (see page 9)	This is menultemDelete, a member of class FrmMain.
₽ B	menuStrip (see page 10)	This is menuStrip, a member of class FrmMain.
₽ ⊗	pbFiles (≥ see page 10)	This is pbFiles, a member of class FrmMain.

FrmMain Methods

	Name	Description
= Q	btnAddFile_Click (see page 10)	It is used to add single or multiple PDF files to combine When you choose file or files The listbox in the form will be filled with the name of the files Which you choose to combine
=Q ₀	btnAddFolder_Click (2 see page 10)	This function is used to add PDF files in a folder which you choose in Folder Dialog recursively When you use it the added files will be seen in listbox
=00	btnClearList_Click (☑ see page 11)	This function is used to clear the file list in listbox
=Q ₂	btnCombinelTextSharp_Click (☑ see page 11)	This function is used to take list of PDF files in listbox, Combine them with a single file in location which you choose in folder dialog And you can see the progress in progress bar It uses iTextSharp Nuget Package
=00	btnCombinePdfSharp_Click (≥ see page 13)	This function is used to take list of PDF files in listbox, Combine them with a single file in location which you choose in folder dialog And you can see the progress in progress bar It uses PdfSharp Nuget Package

≡♠©	DeleteFilesFromListBox (☐ see page 14)	This method is used to Delete selected files from ListBox This is used different ways in this app So we created this as a method
=\$ _{?}	Dispose (a see page 15)	Clean up any resources being used.
= ♠₽	FrmMain_FormClosed (I see page 15)	This function is used to terminate application
=Q ₂	FrmMain_Shown (⊿ see page 15)	This function is used to assign menu to listbox When form is shown
= ♦₽	InitializeComponent (☐ see page 16)	Required method for Designer support - do not modify the contents of this method with the code editor.
= ♦₽ S	InitializeFileDialog (☑ see page 18)	This function is used to set options of file dialog like Filter, start path etc.
=0	lbFiles_KeyDown (⊿ see page 18)	This function is used to delete files in listbox which are chosen If you press the Delete button in your keyboard The selected files will be deleted from the list
=Q _{Q}	menultemDelete_Click (■ see page 18)	This is used to delete selected items in listbox When menu item Delete is clicked and opened dialog

1.1.2.3.1 FrmMain.FrmMain Constructor

C#

```
public FrmMain();
```

Description

This is FrmMain, a member of class FrmMain.

Body Source

1.1.2.3.2 FrmMain Fields

1.1.2.3.2.1 FrmMain.AppTitle Field

C#

```
public const string AppTitle = "PDF Combiner";
```

Description

This is AppTitle, a member of class FrmMain.

1.1.2.3.2.2 FrmMain.btnAddFile Field

C#

```
private System.Windows.Forms.Button btnAddFile;
```

Description

This is btnAddFile, a member of class FrmMain.

1.1.2.3.2.3 FrmMain.btnAddFolder Field

C#

```
private System.Windows.Forms.Button btnAddFolder;
```

Description

This is btnAddFolder, a member of class FrmMain.

1.1.2.3.2.4 FrmMain.btnClearList Field

C#

private System.Windows.Forms.Button btnClearList;

Description

This is btnClearList, a member of class FrmMain.

1.1.2.3.2.5 FrmMain.btnCombinelTextSharp Field

C#

private System.Windows.Forms.Button btnCombineITextSharp;

Description

This is btnCombinelTextSharp, a member of class FrmMain.

1.1.2.3.2.6 FrmMain.btnCombinePdfSharp Field

C#

private System.Windows.Forms.Button btnCombinePdfSharp;

Description

This is btnCombinePdfSharp, a member of class FrmMain.

1.1.2.3.2.7 FrmMain.components Field

Required designer variable.

C#

private System.ComponentModel.IContainer components = null;

1.1.2.3.2.8 FrmMain.lbFiles Field

C#

private System.Windows.Forms.ListBox lbFiles;

Description

This is lbFiles, a member of class FrmMain.

1.1.2.3.2.9 FrmMain.lblDetails Field

C#

```
private System.Windows.Forms.Label lblDetails;
```

Description

This is lblDetails, a member of class FrmMain.

1.1.2.3.2.10 FrmMain.menultemDelete Field

C#

```
private System.Windows.Forms.ToolStripMenuItem menuItemDelete;
```

Description

This is menultemDelete, a member of class FrmMain.

1.1.2.3.2.11 FrmMain.menuStrip Field

C#

private System.Windows.Forms.ContextMenuStrip;

Description

This is menuStrip, a member of class FrmMain.

1.1.2.3.2.12 FrmMain.pbFiles Field

C#

private System.Windows.Forms.ProgressBar pbFiles;

Description

This is pbFiles, a member of class FrmMain.

1.1.2.3.3 FrmMain Methods

1.1.2.3.3.1 FrmMain.btnAddFile Click Method

It is used to add single or multiple PDF files to combine When you choose file or files The listbox in the form will be filled with the name of the files Which you choose to combine

C#

private void btnAddFile_Click(object sender, EventArgs e);

Parameters

Parameters	Description
object sender	The sender info (For example Main Form)
EventArgs e	Event Arguments

Body Source

```
1: private void btnAddFile_Click(object sender, EventArgs e)
 3:
        using (var dialogAddFile = new OpenFileDialog())
 4:
 5:
            InitializeFileDialog(dialogAddFile);
            var result = dialogAddFile.ShowDialog();
 6:
 7:
            var addedFileCount = 0;
 8:
            if (result == DialogResult.OK && dialogAddFile.FileNames != null)
 9:
10:
                 foreach (var file in dialogAddFile.FileNames)
11:
12:
                     if (!lbFiles.Items.Contains(file))
13:
                     {
14:
                         lbFiles.Items.Add(file);
15:
                         addedFileCount++;
                     }
16:
17:
                MessageBox.Show(addedFileCount + " file/s successfully added to the list",
18:
AppTitle, MessageBoxButtons.OK, MessageBoxIcon.Information);
19:
20:
21: }
```

1.1.2.3.3.2 FrmMain.btnAddFolder_Click Method

This function is used to add PDF files in a folder which you choose in Folder Dialog recursively When you use it the added

files will be seen in listbox

C#

```
private void btnAddFolder_Click(object sender, EventArgs e);
```

Parameters

Parameters	Description
object sender	The sender info (For example Main Form)
EventArgs e	Event Arguments

Body Source

```
1: private void btnAddFolder_Click(object sender, EventArgs e)
 2:
        using (var dialogAddFolder = new FolderBrowserDialog())
 3:
 4:
            var result = dialogAddFolder.ShowDialog();
 5:
 6:
            if (result == DialogResult.OK &&
!string.IsNullOrEmpty(dialogAddFolder.SelectedPath))
 7:
 8:
                var fileNames = Directory.GetFiles(dialogAddFolder.SelectedPath, "*.pdf",
SearchOption.AllDirectories);
9:
                var addedFileCount = 0;
10:
                foreach (var file in fileNames)
11:
12:
                    if (!lbFiles.Items.Contains(file))
13:
                        lbFiles.Items.Add(file);
14:
15:
                        addedFileCount++;
                    }
16:
17:
                MessageBox.Show(addedFileCount + " file/s successfully added to the list",
AppTitle, MessageBoxButtons.OK, MessageBoxIcon.Information);
            }
20:
21: }
```

1.1.2.3.3.3 FrmMain.btnClearList_Click Method

This function is used to clear the file list in listbox

C#

```
private void btnClearList_Click(object sender, EventArgs e);
```

Parameters

Parameters	Description
object sender	The sender info (For example Main Form)
EventArgs e	Event Arguments

Body Source

```
1: private void btnClearList_Click(object sender, EventArgs e)
2: {
3:    var fileCount = lbFiles.Items.Count;
4:    lbFiles.Items.Clear();
5:    MessageBox.Show(fileCount + " file/s successfully deleted from the list", AppTitle, MessageBoxButtons.OK, MessageBoxIcon.Information);
6: }
```

1.1.2.3.3.4 FrmMain.btnCombinelTextSharp_Click Method

This function is used to take list of PDF files in listbox, Combine them with a single file in location which you choose in folder dialog And you can see the progress in progress bar It uses iTextSharp Nuget Package

C#

private void btnCombineITextSharp_Click(object sender, EventArgs e);

Parameters

Parameters	Description
object sender	The sender info (For example Main Form)
EventArgs e	Event Arguments

Body Source

```
1: private void btnCombineITextSharp_Click(object sender, EventArgs e)
 2:
    {
 3:
        try
 4:
 5:
            if (lbFiles.Items.Count < 2)</pre>
 6:
 7:
                MessageBox.Show("There must be at least 2 PDF files to combine", AppTitle,
MessageBoxButtons.OK, MessageBoxIcon.Error);
8:
9:
            else
10:
11:
                using (var dialogExport = new FolderBrowserDialog())
12:
13:
                     var result = dialogExport.ShowDialog();
14:
                     if (result == DialogResult.OK &&
!string.IsNullOrEmpty(dialogExport.SelectedPath))
15:
16:
                         var outputFileName = dialogExport.SelectedPath + "/" +
Guid.NewGuid().ToString() + ".pdf";
17:
                         var fileCount = lbFiles.Items.Count;
18:
                         var combinedFiles = 0;
19:
20:
                         var outputFile = new Document();
                         using (FileStream outputFileStream = new FileStream(outputFileName,
21:
FileMode.Create))
22:
                         {
                             var pdfWriter = new iTextSharp.text.pdf.PdfCopy(outputFile,
23:
outputFileStream);
24:
                             if (pdfWriter == null)
25:
26:
                                 return;
27:
28:
                             pdfWriter.SetFullCompression();
29:
                             outputFile.Open();
                             for (int i = 0; i < lbFiles.Items.Count; i++)</pre>
30:
31:
32:
                                  trv
33:
34:
                                      var pdfReader = new
iTextSharp.text.pdf.PdfReader(lbFiles.Items[i].ToString());
35:
                                      pdfReader.ConsolidateNamedDestinations();
36:
                                      for (int j = 1; j <= pdfReader.NumberOfPages; j++)</pre>
37:
38:
                                          var page = pdfWriter.GetImportedPage(pdfReader, j);
39:
                                          pdfWriter.AddPage(page);
40:
41:
                                      pdfReader.Close();
                                      combinedFiles++;
42:
43:
44:
                                 catch (Exception)
45:
                                  {
46:
                                      fileCount --;
47:
48:
49:
                                 pbFiles.Value = (combinedFiles * 100 / fileCount);
50:
                                  if (pbFiles.Value > pbFiles.Maximum)
```

```
pbFiles.Value = pbFiles.Maximum;
51:
52:
53:
                             pdfWriter.Close();
54:
                             outputFile.Close();
                         }
55:
56:
                         MessageBox.Show(fileCount + " PDF files successfully combined in "
57:
+ outputFileName, AppTitle, MessageBoxButtons.OK, MessageBoxIcon.Information);
58:
59:
                         pbFiles.Value = pbFiles.Minimum;
                     }
60:
61:
                }
62:
            }
63:
64:
        catch (Exception ex)
65:
66:
            MessageBox.Show("There is an error while combining PDF files in list. Details:
" + ex.GetAllMessages(), AppTitle, MessageBoxButtons.OK, MessageBoxIcon.Error);
67:
            pbFiles.Value = pbFiles.Minimum;
68:
69: }
```

1.1.2.3.3.5 FrmMain.btnCombinePdfSharp_Click Method

This function is used to take list of PDF files in listbox, Combine them with a single file in location which you choose in folder dialog And you can see the progress in progress bar It uses PdfSharp Nuget Package

C#

```
private void btnCombinePdfSharp_Click(object sender, EventArgs e);
```

Parameters

Parameters	Description
object sender	The sender info (For example Main Form)
EventArgs e	Event Arguments

Body Source

```
1: private void btnCombinePdfSharp_Click(object sender, EventArgs e)
 2: {
 3:
 4:
 5:
            if (lbFiles.Items.Count < 2)</pre>
 6:
 7:
                MessageBox.Show("There must be at least 2 PDF files to combine", AppTitle,
MessageBoxButtons.OK, MessageBoxIcon.Error);
 8:
 9:
            else
10:
11:
                using (var dialogExport = new FolderBrowserDialog())
12:
13:
                     var result = dialogExport.ShowDialog();
14:
                    if (result == DialogResult.OK &&
!string.IsNullOrEmpty(dialogExport.SelectedPath))
15:
16:
                         var outputFileName = dialogExport.SelectedPath + "/" +
Guid.NewGuid().ToString() + ".pdf";
                         var outputFile = new PdfDocument();
17:
18:
                         outputFile.Options.CompressContentStreams = true;
                         outputFile.Options.EnableCcittCompressionForBilevelImages = true;
19:
20:
                         outputFile.Options.FlateEncodeMode =
PdfFlateEncodeMode.BestCompression;
21:
                         var fileCount = lbFiles.Items.Count;
22:
                         var combinedFiles = 0;
23:
24:
                         for (int i = 0; i < lbFiles.Items.Count; i++)</pre>
25:
```

```
26:
                             try
27:
28:
                                 var inputDocument =
PdfReader.Open(lbFiles.Items[i].ToString(), PdfDocumentOpenMode.Import);
29:
                                 var count = inputDocument.PageCount;
30:
                                 for (int idx = 0; idx < count; idx++)</pre>
31:
32:
                                      var page = inputDocument.Pages[idx];
33:
                                      outputFile.AddPage(page);
34:
35:
                                 inputDocument.Close();
36:
                                 combinedFiles++;
37:
                             }
38:
                             catch (Exception)
39:
                             {
40:
                                 fileCount --;
41:
42:
                             pbFiles.Value = (combinedFiles * 100 / fileCount);
43:
44:
                             if (pbFiles.Value > pbFiles.Maximum)
                                 pbFiles.Value = pbFiles.Maximum;
45:
46:
47:
                         outputFile.Save(outputFileName);
48:
                         outputFile.Close();
49:
                         MessageBox.Show(fileCount + " PDF files successfully combined in "
50:
+ outputFileName, AppTitle, MessageBoxButtons.OK, MessageBoxIcon.Information);
52:
                         pbFiles.Value = pbFiles.Minimum;
53:
                     }
54:
                 }
            }
55:
56:
57:
        catch (Exception ex)
58:
59:
            MessageBox.Show("There is an error while combining PDF files in list. Details:
" + ex.GetAllMessages(), AppTitle, MessageBoxButtons.OK, MessageBoxIcon.Error);
60:
            pbFiles.Value = pbFiles.Minimum;
61:
62: }
```

1.1.2.3.3.6 FrmMain.DeleteFilesFromListBox Method

This method is used to Delete selected files from ListBox This is used different ways in this app So we created this as a method

C#

private void DeleteFilesFromListBox();

Body Source

```
1: private void DeleteFilesFromListBox()
 2: {
 3:
        var allItems = new List<string>();
 4:
        var removedItems = new List<string>();
 5:
        var fileCount = lbFiles.SelectedItems.Count;
        for (int i = 0; i < lbFiles.SelectedItems.Count; i++)</pre>
 6:
 7:
        {
 8:
            removedItems.Add(lbFiles.SelectedItems[i].ToString());
 9:
10:
        foreach (var item in lbFiles.Items)
11:
12:
            if (!removedItems.Any(j => j == item.ToString()))
13:
                allItems.Add(item.ToString());
14:
15:
        lbFiles.Items.Clear();
        foreach (var item in allItems)
16:
17:
```

1.1.2.3.3.7 FrmMain.Dispose Method

Clean up any resources being used.

C#

protected override void Dispose(bool disposing);

Parameters

Parameters	Description
bool disposing	true if managed resources should be disposed; otherwise,
	false.

Body Source

```
1: protected override void Dispose(bool disposing)
2: {
3:     if (disposing && (components != null))
4:     {
5:         components.Dispose();
6:     }
7:     base.Dispose(disposing);
8: }
```

1.1.2.3.3.8 FrmMain.FrmMain_FormClosed Method

This function is used to terminate application

C#

```
private void FrmMain_FormClosed(object sender, FormClosedEventArgs e);
```

Parameters

Parameters	Description
object sender	The sender info (For example Main Form)
FormClosedEventArgs e	Event Arguments

Body Source

```
1: private void FrmMain_FormClosed(object sender, FormClosedEventArgs e)
2: {
3:     MessageBox.Show("Thanks for using this app", AppTitle, MessageBoxButtons.OK,
MessageBoxIcon.Information);
4:     Application.Exit();
5: }
```

1.1.2.3.3.9 FrmMain.FrmMain_Shown Method

This function is used to assign menu to listbox When form is shown

C#

```
private void FrmMain_Shown(object sender, EventArgs e);
```

Parameters

Parameters	Description
object sender	The sender info (For example Main Form)
EventArgs e	Event Arguments

Body Source

```
1: private void FrmMain_Shown(object sender, EventArgs e)
2: {
3:    lbFiles.ContextMenuStrip = menuStrip;
4: }
```

1.1.2.3.3.10 FrmMain.InitializeComponent Method

Required method for Designer support - do not modify the contents of this method with the code editor.

C#

```
private void InitializeComponent();
```

Body Source

```
1: private void InitializeComponent()
  2:
  3:
         this.components = new System.ComponentModel.Container();
  4:
         this.btnCombinePdfSharp = new System.Windows.Forms.Button();
  5:
         this.btnAddFolder = new System.Windows.Forms.Button();
  6:
         this.btnAddFile = new System.Windows.Forms.Button();
  7:
         this.btnClearList = new System.Windows.Forms.Button();
  8:
         this.lbFiles = new System.Windows.Forms.ListBox();
  9:
         this.lblDetails = new System.Windows.Forms.Label();
 10:
         this.pbFiles = new System.Windows.Forms.ProgressBar();
 11:
         this.btnCombineITextSharp = new System.Windows.Forms.Button();
 12:
         this.menuStrip = new System.Windows.Forms.ContextMenuStrip(this.components);
 13:
         this.menuItemDelete = new System.Windows.Forms.ToolStripMenuItem();
 14:
         this.menuStrip.SuspendLayout();
 15:
         this.SuspendLayout();
 16:
         // btnCombinePdfSharp
 17:
 18:
 19:
         this.btnCombinePdfSharp.Location = new System.Drawing.Point(487, 12);
 20:
         this.btnCombinePdfSharp.Name = "btnCombinePdfSharp";
         this.btnCombinePdfSharp.Size = new System.Drawing.Size(169, 23);
 21:
         this.btnCombinePdfSharp.TabIndex = 0;
 22:
 23:
         this.btnCombinePdfSharp.Text = "Combine Files (PdfSharp)";
 24:
         this.btnCombinePdfSharp.UseVisualStyleBackColor = true;
 25:
         this.btnCombinePdfSharp.Click += new
System.EventHandler(this.btnCombinePdfSharp_Click);
 26:
 27:
         // btnAddFolder
 28:
 29:
         this.btnAddFolder.Location = new System.Drawing.Point(12, 38);
 30:
         this.btnAddFolder.Name = "btnAddFolder";
         this.btnAddFolder.Size = new System.Drawing.Size(156, 23);
 31:
         this.btnAddFolder.TabIndex = 2;
 32:
 33:
         this.btnAddFolder.Text = "Add Folder";
 34:
         this.btnAddFolder.UseVisualStyleBackColor = true;
 35:
         this.btnAddFolder.Click += new System.EventHandler(this.btnAddFolder_Click);
 36:
         // btnAddFile
 37:
 38:
 39:
         this.btnAddFile.Location = new System.Drawing.Point(12, 12);
         this.btnAddFile.Name = "btnAddFile";
 40:
         this.btnAddFile.Size = new System.Drawing.Size(156, 23);
 41:
 42:
         this.btnAddFile.TabIndex = 3;
 43:
         this.btnAddFile.Text = "Add Files";
 44:
         this.btnAddFile.UseVisualStyleBackColor = true;
         this.btnAddFile.Click += new System.EventHandler(this.btnAddFile_Click);
 45:
 46:
 47:
         // btnClearList
 48:
 49:
         this.btnClearList.Location = new System.Drawing.Point(174, 12);
         this.btnClearList.Name = "btnClearList";
 50:
 51:
         this.btnClearList.Size = new System.Drawing.Size(90, 49);
```

```
52:
         this.btnClearList.TabIndex = 4;
 53:
         this.btnClearList.Text = "Clear File List";
 54:
         this.btnClearList.UseVisualStyleBackColor = true;
 55:
         this.btnClearList.Click += new System.EventHandler(this.btnClearList_Click);
 56:
         // lbFiles
 57:
 58:
 59:
         this.lbFiles.FormattingEnabled = true;
 60:
         this.lbFiles.Location = new System.Drawing.Point(12, 88);
         this.lbFiles.Name = "lbFiles";
 61:
 62:
         this.lbFiles.SelectionMode = System.Windows.Forms.SelectionMode.MultiExtended;
 63:
         this.lbFiles.Size = new System.Drawing.Size(644, 186);
 64:
         this.lbFiles.TabIndex = 5;
 65:
         this.lbFiles.KeyDown += new
System.Windows.Forms.KeyEventHandler(this.lbFiles_KeyDown);
 66:
         // lblDetails
 67:
 68:
 69:
         this.lblDetails.AutoSize = true;
 70:
         this.lblDetails.Location = new System.Drawing.Point(12, 65);
         this.lblDetails.Name = "lblDetails";
 71:
 72:
         this.lblDetails.Size = new System.Drawing.Size(0, 13);
 73:
         this.lblDetails.TabIndex = 6;
 74:
         // pbFiles
 75:
 76:
 77:
         this.pbFiles.Location = new System.Drawing.Point(270, 12);
 78:
         this.pbFiles.Name = "pbFiles";
         this.pbFiles.Size = new System.Drawing.Size(211, 49);
 79:
 :08
         this.pbFiles.TabIndex = 7;
 81:
         // btnCombineITextSharp
 82:
 83:
 84:
         this.btnCombineITextSharp.Location = new System.Drawing.Point(487, 38);
 85:
         this.btnCombineITextSharp.Name = "btnCombineITextSharp";
         this.btnCombineITextSharp.Size = new System.Drawing.Size(169, 23);
 86:
         this.btnCombineITextSharp.TabIndex = 9;
 87:
 88:
         this.btnCombineITextSharp.Text = "Combine Files (iTextSharp)";
 89:
         this.btnCombineITextSharp.UseVisualStyleBackColor = true;
 90:
         this.btnCombineITextSharp.Click += new
System.EventHandler(this.btnCombineITextSharp_Click);
 91:
         //
         // menuStrip
 92:
 93:
 94:
         this.menuStrip.Items.AddRange(new System.Windows.Forms.ToolStripItem[] {
 95:
         this.menuItemDelete});
         this.menuStrip.Name = "menuStrip";
 96:
 97:
         this.menuStrip.Size = new System.Drawing.Size(181, 48);
 98:
         // menuItemDelete
 99:
100:
101:
         this.menuItemDelete.Image = global::PdfCombiner.Properties.Resources.DeleteIcon1;
         this.menuItemDelete.Name = "menuItemDelete";
102:
103:
         this.menuItemDelete.Size = new System.Drawing.Size(180, 22);
         this.menuItemDelete.Text = "Delete";
104:
105:
         this.menuItemDelete.Click += new System.EventHandler(this.menuItemDelete_Click);
106:
         // FrmMain
107:
108:
109:
         this.AutoScaleDimensions = new System.Drawing.SizeF(6F, 13F);
110:
         this.AutoScaleMode = System.Windows.Forms.AutoScaleMode.Font;
111:
         this.ClientSize = new System.Drawing.Size(668, 287);
         this.Controls.Add(this.btnCombineITextSharp);
112:
113:
         this.Controls.Add(this.pbFiles);
114:
         this.Controls.Add(this.lblDetails);
115:
         this.Controls.Add(this.lbFiles);
         this.Controls.Add(this.btnClearList);
116:
117:
         this.Controls.Add(this.btnAddFile);
118:
         this.Controls.Add(this.btnAddFolder);
```

```
119:
         this.Controls.Add(this.btnCombinePdfSharp);
120:
         this.Name = "FrmMain";
121:
         this.StartPosition = System.Windows.Forms.FormStartPosition.CenterScreen;
122:
         this.Text = "PDF Combiner";
123:
         this.FormClosed += new
System.Windows.Forms.FormClosedEventHandler(this.FrmMain_FormClosed);
         this.Shown += new System.EventHandler(this.FrmMain_Shown);
124:
125:
         this.menuStrip.ResumeLayout(false);
126:
         this.ResumeLayout(false);
127:
         this.PerformLayout();
128:
129: }
```

1.1.2.3.3.11 FrmMain.InitializeFileDialog Method

This function is used to set options of file dialog like Filter, start path etc.

C#

```
private static void InitializeFileDialog(OpenFileDialog dialogAddFile);
```

Parameters

Parameters	Description
OpenFileDialog dialogAddFile	File Dialog

Body Source

```
1: private static void InitializeFileDialog(OpenFileDialog dialogAddFile)
2: {
3:          dialogAddFile.Multiselect = true;
4:          dialogAddFile.Filter = "pdf files (*.pdf)|*.pdf";
5:          dialogAddFile.InitialDirectory = Application.StartupPath;
6:          dialogAddFile.Title = "Select PDF File/s";
7:          dialogAddFile.DefaultExt = "pdf";
8: }
```

1.1.2.3.3.12 FrmMain.lbFiles_KeyDown Method

This function is used to delete files in listbox which are chosen If you press the Delete button in your keyboard The selected files will be deleted from the list

C#

```
private void lbFiles_KeyDown(object sender, KeyEventArgs e);
```

Parameters

Parameters	Description
object sender	The sender info (For example Main Form)
KeyEventArgs e	Event Arguments

Body Source

```
1: private void lbFiles_KeyDown(object sender, KeyEventArgs e)
2: {
3:    if (e.KeyValue == Keys.Delete.GetHashCode())
4:         DeleteFilesFromListBox();
5: }
```

1.1.2.3.3.13 FrmMain.menultemDelete Click Method

This is used to delete selected items in listbox When menu item Delete is clicked and opened dialog

C#

```
private void menuItemDelete_Click(object sender, EventArgs e);
```

Parameters

Parameters	Description
object sender	The sender info (For example Main Form)
EventArgs e	Event Arguments

Body Source

```
1: private void menuItemDelete_Click(object sender, EventArgs e)
2: {
3:    var deleteDialog = new DialogResult();
4:    deleteDialog = MessageBox.Show("You are about to delete " +
lbFiles.SelectedItems.Count + " files in listbox. Are you sure?", AppTitle,
MessageBoxButtons.YesNo, MessageBoxIcon.Warning);
5:    if (deleteDialog == DialogResult.Yes)
6:         DeleteFilesFromListBox();
7: }
```

1.1.2.4 Program Class

Class Hierarchy

PdfCombiner.Program

C#

public static class Program;

File

Program.cs (see page 30)

Description

This is class PdfCombiner.Program.

Program Methods

	Name	Description
= ♦₽	Main (⊿ see page 19)	The main entry point for the application.

1.1.2.4.1 Program Methods

1.1.2.4.1.1 Program.Main Method

The main entry point for the application.

C#

```
[STAThread]
private static void Main();
```

Body Source

```
1: [STAThread]
2: static void Main()
3: {
4:     Application.EnableVisualStyles();
5:     Application.SetCompatibleTextRenderingDefault(false);
6:     Application.Run(new FrmMain());
7: }
```

1.2 Files

The following table lists files in this documentation.

Files

Name	Description
AssemblyInfo.cs (≥ see page 20)	This is file AssemblyInfo.cs.
Exceptions.cs (see page 21)	This is file Exceptions.cs.
FrmMain.cs (see page 22)	This is file FrmMain.cs.
FrmMain.Designer.cs (see page 27)	This is file FrmMain.Designer.cs.
PdfCombiner.csproj (see page 30)	This is file PdfCombiner.csproj.
PdfCombiner.sln (a see page 30)	This is file PdfCombiner.sln.
Program.cs (see page 30)	This is file Program.cs.
Resources.Designer.cs (2 see page 31)	This code was generated by a tool. Runtime Version:4.0.30319.42000 Changes to this file may cause incorrect behavior and will be lost if the code is regenerated.
Settings.Designer.cs (see page 32)	This code was generated by a tool. Runtime Version:4.0.30319.42000 Changes to this file may cause incorrect behavior and will be lost if the code is regenerated.

1.2.1 AssemblyInfo.cs

This is file AssemblyInfo.cs.

Body Source

```
1: ?using System.Reflection;
 2: using System.Runtime.CompilerServices;
 3: using System.Runtime.InteropServices;
 5: // General Information about an assembly is controlled through the following
 6: // set of attributes. Change these attribute values to modify the information
 7: // associated with an assembly.
 8: [assembly: AssemblyTitle("PdfCombiner")]
 9: [assembly: AssemblyDescription("")]
10: [assembly: AssemblyConfiguration("")]
11: [assembly: AssemblyCompany("")]
12: [assembly: AssemblyProduct("PdfCombiner")]
13: [assembly: AssemblyCopyright("Copyright © 2022")]
14: [assembly: AssemblyTrademark("")]
15: [assembly: AssemblyCulture("")]
16:
17: // Setting ComVisible to false makes the types in this assembly not visible
18: // to COM components. If you need to access a type in this assembly from
19: // COM, set the ComVisible attribute to true on that type.
20: [assembly: ComVisible(false)]
21:
22: // The following GUID is for the ID of the typelib if this project is exposed to COM
23: [assembly: Guid("48e34ee8-dfaa-48db-acfd-70573cee9c00")]
24:
25: // Version information for an assembly consists of the following four values: 26: //
27: //
            Major Version
28: //
            Minor Version
```

```
29: // Build Number
30: // Revision
31: //
32: // You can specify all the values or you can default the Build and Revision Numbers
33: // by using the '*' as shown below:
34: // [assembly: AssemblyVersion("1.0.*")]
35: [assembly: AssemblyVersion("1.0.0.0")]
36: [assembly: AssemblyFileVersion("1.0.0.0")]
```

1.2.2 Exceptions.cs

This is file Exceptions.cs.

Body Source

```
1: ?using System;
 2:
 3: namespace PdfCombiner
 4: {
 5:
        /// <summarv>
 6:
        /// This function is used to take exceptions which can be thrown in
 7:
        /// PDF Combiner App
 8:
        /// </summary>
 9:
        [Serializable]
        public abstract class BaseException : Exception
10:
11:
12:
            protected BaseException()
13:
14:
15:
16:
            protected BaseException(string message) : base(message)
17:
18:
19:
            protected BaseException(string message, Exception innerException) :
base(message, innerException)
21:
22:
23:
24:
25:
        public static class ExceptionExtensions
26:
27:
            /// <summary>
            /// This method is used to take all messages with stack trace info in exception
28:
29:
            /// </summary>
            /// <param name="exception">Exception</param>
30:
            /// <returns>Detailed Error Message</returns>
31:
32:
            public static string GetAllMessages(this Exception exception)
33:
34:
                var messages = exception.Message;
35:
                if (exception.InnerException != null)
                    messages += " " + exception.InnerException.GetAllMessages();
36:
37:
                if (!string.IsNullOrEmpty(exception.StackTrace))
                    messages += " " + exception.StackTrace;
38:
39:
                if (!string.IsNullOrEmpty(exception.Source))
                    messages += " " + exception.Source;
40:
41:
                return messages;
42:
            }
43:
44: }
```

Namespaces

Name	Description
PdfCombiner (☑ see page 1)	This is namespace PdfCombiner.

1.2.3 FrmMain.cs

This is file FrmMain.cs.

Body Source

```
1: ?using iTextSharp.text;
  2: using PdfSharp.Pdf;
  3: using PdfSharp.Pdf.IO;
  4: using System;
  5: using System.Collections.Generic;
  6: using System.IO;
  7: using System.Linq;
  8: using System.Windows.Forms;
  9:
 10: namespace PdfCombiner
 11: {
 12:
         public partial class FrmMain : Form
 13:
 14:
             public const string AppTitle = "PDF Combiner";
 15:
 16:
             public FrmMain()
 17:
 18:
                 InitializeComponent();
 19:
 20:
             /// <summary>
/// This function is used to terminate application
 21:
 22:
 23:
             /// </summary>
 24:
             /// <param name="sender">The sender info (For example Main Form)</param>
             /// <param name="e">Event Arguments</param>
 25:
 26:
             private void FrmMain_FormClosed(object sender, FormClosedEventArgs e)
 27:
 28:
                 MessageBox.Show("Thanks for using this app", AppTitle,
MessageBoxButtons.OK, MessageBoxIcon.Information);
 29:
                 Application.Exit();
 30:
 31:
 32:
             /// <summary>
 33:
             /// This function is used to assign menu to listbox
             /// When form is shown
 34:
             /// </summary>
 35:
 36:
             /// <param name="sender">The sender info (For example Main Form)</param>
 37:
             /// <param name="e">Event Arguments</param>
 38:
             private void FrmMain_Shown(object sender, EventArgs e)
 39:
 40:
                 lbFiles.ContextMenuStrip = menuStrip;
             }
 41:
 42:
 43:
             /// <summary>
             /// It is used to add single or multiple PDF files to combine
 44:
 45:
             /// When you choose file or files
             /// The listbox in the form will be filled with the name of the files
 46:
 47:
             /// Which you choose to combine
 48:
             /// </summary>
 49:
             /// <param name="sender">The sender info (For example Main Form)</param>
 50:
             /// <param name="e">Event Arguments</param>
 51:
             private void btnAddFile_Click(object sender, EventArgs e)
 52:
 53:
                 using (var dialogAddFile = new OpenFileDialog())
 54:
 55:
                     InitializeFileDialog(dialogAddFile);
 56:
                     var result = dialogAddFile.ShowDialog();
 57:
                     var addedFileCount = 0;
 58:
                     if (result == DialogResult.OK && dialogAddFile.FileNames != null)
```

```
59:
                     {
 60:
                          foreach (var file in dialogAddFile.FileNames)
 61:
 62:
                              if (!lbFiles.Items.Contains(file))
 63:
 64:
                                  lbFiles.Items.Add(file);
 65:
                                  addedFileCount++;
 66:
 67:
                         MessageBox. Show (addedFileCount + " file/s successfully added to
the list", AppTitle, MessageBoxButtons.OK, MessageBoxIcon.Information);
 69:
                     }
 70:
 71:
             }
 72:
 73:
             /// <summary>
 74:
             /// This function is used to set options of file dialog like
 75:
             /// Filter, start path etc.
 76:
             /// </summary>
             /// <param name="dialogAddFile">File Dialog</param>
 77:
 78:
             private static void InitializeFileDialog(OpenFileDialog dialogAddFile)
 79:
                 dialogAddFile.Multiselect = true;
 :08
                 dialogAddFile.Filter = "pdf files (*.pdf)|*.pdf";
 81:
 82:
                 dialogAddFile.InitialDirectory = Application.StartupPath;
                 dialogAddFile.Title = "Select PDF File/s";
 83:
 84:
                 dialogAddFile.DefaultExt = "pdf";
 85:
             }
 86:
 87:
             /// <summary>
 88:
             /// This function is used to clear the file list in listbox
             /// </summary>
 89:
 90:
             /// <param name="sender">The sender info (For example Main Form)</param>
             /// <param name="e">Event Arguments</param>
 91:
 92:
             private void btnClearList_Click(object sender, EventArgs e)
 93:
 94:
                 var fileCount = lbFiles.Items.Count;
 95:
                 lbFiles.Items.Clear();
 96:
                 MessageBox.Show(fileCount + " file/s successfully deleted from the list",
AppTitle, MessageBoxButtons.OK, MessageBoxIcon.Information);
 97:
             }
98:
99:
             /// <summary>
100:
             /// This function is used to add PDF files in a folder which you choose in
             /// Folder Dialog recursively
101:
102:
             /// When you use it the added files will be seen in listbox
103:
             /// </summary>
             /// <param name="sender">The sender info (For example Main Form)</param>
104:
             /// <param name="e">Event Arguments</param>
105:
106:
             private void btnAddFolder_Click(object sender, EventArgs e)
107:
108:
                 using (var dialogAddFolder = new FolderBrowserDialog())
109:
110:
                     var result = dialogAddFolder.ShowDialog();
                     if (result == DialogResult.OK &&
111:
!string.IsNullOrEmpty(dialogAddFolder.SelectedPath))
112:
113:
                         var fileNames = Directory.GetFiles(dialogAddFolder.SelectedPath,
"*.pdf", SearchOption.AllDirectories);
114:
                         var addedFileCount = 0;
115:
                         foreach (var file in fileNames)
116:
117:
                              if (!lbFiles.Items.Contains(file))
118:
119:
                                  lbFiles.Items.Add(file);
                                  addedFileCount++;
120:
121:
122:
123:
                         MessageBox.Show(addedFileCount + " file/s successfully added to
```

```
the list", AppTitle, MessageBoxButtons.OK, MessageBoxIcon.Information);
124:
125:
126:
             }
127:
128:
             /// <summary>
129:
             /// This function is used to delete files in listbox which are chosen
130:
             /// If you press the Delete button in your keyboard
131:
             /// The selected files will be deleted from the list
             /// </summary>
132:
             /// <param name="sender">The sender info (For example Main Form)</param>
133:
134:
             /// <param name="e">Event Arguments</param>
135:
             private void lbFiles_KeyDown(object sender, KeyEventArgs e)
136:
137:
                 if (e.KeyValue == Keys.Delete.GetHashCode())
138:
                     DeleteFilesFromListBox();
139:
140:
             /// <summary>
141:
142:
             /// This function is used to take list of PDF files in listbox,
143:
             /// Combine them with a single file in location which you choose in folder
dialog
144:
             /// And you can see the progress in progress bar
145:
             /// It uses PdfSharp Nuget Package
             /// </summary>
146:
             /// <param name="sender">The sender info (For example Main Form)</param>
147:
             /// <param name="e">Event Arguments</param>
148:
             private void btnCombinePdfSharp_Click(object sender, EventArgs e)
149:
150:
151:
                 try
152:
                  {
                     if (lbFiles.Items.Count < 2)</pre>
153:
154:
                      {
                          MessageBox.Show("There must be at least 2 PDF files to combine",
155:
AppTitle, MessageBoxButtons.OK, MessageBoxIcon.Error);
156:
157:
                     else
158:
159:
                          using (var dialogExport = new FolderBrowserDialog())
160:
161:
                              var result = dialogExport.ShowDialog();
                              if (result == DialogResult.OK &&
162:
!string.IsNullOrEmpty(dialogExport.SelectedPath))
163:
                                  var outputFileName = dialogExport.SelectedPath + "/" +
164:
Guid.NewGuid().ToString() + ".pdf";
165:
                                  var outputFile = new PdfDocument();
166:
                                  outputFile.Options.CompressContentStreams = true;
167:
                                  outputFile.Options.EnableCcittCompressionForBilevelImages
= true;
168:
                                  outputFile.Options.FlateEncodeMode =
PdfFlateEncodeMode.BestCompression;
169:
                                  var fileCount = lbFiles.Items.Count;
170:
                                  var combinedFiles = 0;
171:
172:
                                  for (int i = 0; i < lbFiles.Items.Count; i++)</pre>
173:
                                  {
174:
                                      try
175:
                                           var inputDocument =
176:
PdfReader.Open(lbFiles.Items[i].ToString(), PdfDocumentOpenMode.Import);
177:
                                          var count = inputDocument.PageCount;
178:
                                          for (int idx = 0; idx < count; idx++)</pre>
179:
                                           {
180:
                                               var page = inputDocument.Pages[idx];
181:
                                               outputFile.AddPage(page);
182:
183:
                                           inputDocument.Close();
184:
                                           combinedFiles++;
```

```
185:
                                       catch (Exception)
186:
187:
188:
                                           fileCount--;
189:
190:
191:
                                       pbFiles.Value = (combinedFiles * 100 / fileCount);
192:
                                       if (pbFiles.Value > pbFiles.Maximum)
193:
                                           pbFiles.Value = pbFiles.Maximum;
194:
195:
                                   outputFile.Save(outputFileName);
196:
                                   outputFile.Close();
197:
                                   MessageBox.Show(fileCount + " PDF files successfully
198:
combined in " + outputFileName, AppTitle, MessageBoxButtons.OK, MessageBoxIcon.Information);
199:
200:
                                   pbFiles.Value = pbFiles.Minimum;
201:
                              }
                          }
202:
203:
                      }
204:
205:
                  catch (Exception ex)
206:
                      MessageBox.Show("There is an error while combining PDF files in list.
207:
Details: " + ex.GetAllMessages(), AppTitle, MessageBoxButtons.OK, MessageBoxIcon.Error);
                      pbFiles.Value = pbFiles.Minimum;
208:
209:
210:
             }
211:
212:
             /// <summary>
213:
             /// This function is used to take list of PDF files in listbox,
             /// Combine them with a single file in location which you choose in folder
214:
dialog
             /// And you can see the progress in progress bar /// It uses iTextSharp Nuget Package
215:
216:
217:
             /// </summary>
             /// <param name="sender">The sender info (For example Main Form)</param>
218:
             /// <param name="e">Event Arguments</param>
219:
220:
             private void btnCombineITextSharp_Click(object sender, EventArgs e)
221:
222:
                  try
223:
                  {
224:
                      if (lbFiles.Items.Count < 2)</pre>
225:
                      {
                          MessageBox.Show("There must be at least 2 PDF files to combine",
226:
AppTitle, MessageBoxButtons.OK, MessageBoxIcon.Error);
227:
                      }
228:
                      else
229:
230:
                          using (var dialogExport = new FolderBrowserDialog())
231:
232:
                              var result = dialogExport.ShowDialog();
                              if (result == DialogResult.OK &&
233:
!string.IsNullOrEmpty(dialogExport.SelectedPath))
234:
235:
                                   var outputFileName = dialogExport.SelectedPath + "/" +
Guid.NewGuid().ToString() + ".pdf";
                                   var fileCount = lbFiles.Items.Count;
236:
237:
                                   var combinedFiles = 0;
238:
239:
                                   var outputFile = new Document();
                                   using (FileStream outputFileStream = new
FileStream(outputFileName, FileMode.Create))
241:
242:
                                       var pdfWriter = new
iTextSharp.text.pdf.PdfCopy(outputFile, outputFileStream);
243:
                                       if (pdfWriter == null)
244:
                                       {
245:
                                           return;
```

```
246:
247:
                                      pdfWriter.SetFullCompression();
248:
                                       outputFile.Open();
249:
                                       for (int i = 0; i < lbFiles.Items.Count; i++)</pre>
250:
                                       {
251:
252:
253:
                                               var pdfReader = new
iTextSharp.text.pdf.PdfReader(lbFiles.Items[i].ToString());
                                               pdfReader.ConsolidateNamedDestinations();
                                               for (int j = 1; j <= pdfReader.NumberOfPages;</pre>
255:
j++)
256:
257:
                                                   var page =
pdfWriter.GetImportedPage(pdfReader, j);
                                                   pdfWriter.AddPage(page);
258:
259:
260:
                                               pdfReader.Close();
261:
                                               combinedFiles++;
262:
263:
                                           catch (Exception)
264:
265:
                                               fileCount --;
266:
267:
268:
                                           pbFiles.Value = (combinedFiles * 100 / fileCount);
269:
                                           if (pbFiles.Value > pbFiles.Maximum)
270:
                                               pbFiles.Value = pbFiles.Maximum;
271:
272:
                                      pdfWriter.Close();
273:
                                       outputFile.Close();
                                  }
274:
275:
                                  MessageBox.Show(fileCount + " PDF files successfully
276:
combined in " + outputFileName, AppTitle, MessageBoxButtons.OK, MessageBoxIcon.Information);
277:
278:
                                  pbFiles.Value = pbFiles.Minimum;
                              }
279:
280:
                          }
281:
                      }
282:
283:
                 catch (Exception ex)
284:
285:
                      MessageBox. Show("There is an error while combining PDF files in list.
Details: " + ex.GetAllMessages(), AppTitle, MessageBoxButtons.OK, MessageBoxIcon.Error);
                     pbFiles.Value = pbFiles.Minimum;
286:
287:
                 }
             }
288:
289:
290:
             /// <summary>
291:
             /// This is used to delete selected items in listbox
             /// When menu item Delete is clicked and opened dialog
292:
293:
             /// </summary>
294:
             /// <param name="sender">The sender info (For example Main Form)</param>
             /// <param name="e">Event Arguments</param>
295:
296:
             private void menuItemDelete_Click(object sender, EventArgs e)
297:
                 var deleteDialog = new DialogResult();
298:
299:
                 deleteDialog = MessageBox.Show("You are about to delete " +
lbFiles.SelectedItems.Count + " files in listbox. Are you sure?", AppTitle,
MessageBoxButtons.YesNo, MessageBoxIcon.Warning);
                 if (deleteDialog == DialogResult.Yes)
301:
                     DeleteFilesFromListBox();
             }
302:
303:
304:
             /// <summary>
             /// This method is used to Delete selected files from ListBox
305:
             /// This is used different ways in this app
306:
307:
             /// So we created this as a method
```

```
308:
             /// </summary>
309:
             private void DeleteFilesFromListBox()
310:
311:
                 var allItems = new List<string>();
312:
                 var removedItems = new List<string>();
313:
                 var fileCount = lbFiles.SelectedItems.Count;
314:
                 for (int i = 0; i < lbFiles.SelectedItems.Count; i++)</pre>
315:
316:
                      removedItems.Add(lbFiles.SelectedItems[i].ToString());
317:
318:
                 foreach (var item in lbFiles.Items)
319:
                 {
320:
                      if (!removedItems.Any(j => j == item.ToString()))
321:
                          allItems.Add(item.ToString());
322:
323:
                 lbFiles.Items.Clear();
324:
                 foreach (var item in allItems)
325:
                      lbFiles.Items.Add(item);
326:
327:
                 MessageBox.Show(fileCount + " file/s are deleted from the list.",
328:
AppTitle, MessageBoxButtons.OK, MessageBoxIcon.Information);
329:
330:
331: }
```

Name	Description
PdfCombiner (see page 1)	This is namespace PdfCombiner.

1.2.4 FrmMain.Designer.cs

This is file FrmMain.Designer.cs.

Body Source

```
1: ?namespace PdfCombiner
  2:
  3:
         partial class FrmMain
  4:
  5:
              /// <summary>
             /// Required designer variable.
  7:
             /// </summary>
  8:
             private System.ComponentModel.IContainer components = null;
  9:
 10:
             /// <summary>
             /// Clean up any resources being used.
/// </summary>
12:
             /// <param name="disposing">true if managed resources should be disposed;
13:
otherwise, false.</param>
             protected override void Dispose(bool disposing)
14:
 15:
 16:
                  if (disposing && (components != null))
 17:
 18:
                      components.Dispose();
 19:
 20:
                  base.Dispose(disposing);
 21:
             }
 22:
 23:
             #region Windows Form Designer generated code
 24:
             /// <summary>
 25:
             /// Required method for Designer support - do not modify
 26:
             /// the contents of this method with the code editor.
 27:
```

```
28:
             /// </summary>
 29:
             private void InitializeComponent()
 30:
 31:
                 this.components = new System.ComponentModel.Container();
 32:
                 this.btnCombinePdfSharp = new System.Windows.Forms.Button();
                 this.btnAddFolder = new System.Windows.Forms.Button();
 33:
                 this.btnAddFile = new System.Windows.Forms.Button();
 34:
 35:
                 this.btnClearList = new System.Windows.Forms.Button();
 36:
                 this.lbFiles = new System.Windows.Forms.ListBox();
 37:
                 this.lblDetails = new System.Windows.Forms.Label();
 38:
                 this.pbFiles = new System.Windows.Forms.ProgressBar();
 39:
                 this.btnCombineITextSharp = new System.Windows.Forms.Button();
 40:
                 this.menuStrip = new
System.Windows.Forms.ContextMenuStrip(this.components);
 41:
                 this.menuItemDelete = new System.Windows.Forms.ToolStripMenuItem();
                 this.menuStrip.SuspendLayout();
 42:
 43:
                 this.SuspendLayout();
 44:
                 // btnCombinePdfSharp
 45:
 46:
                 11
 47:
                 this.btnCombinePdfSharp.Location = new System.Drawing.Point(487, 12);
 48:
                 this.btnCombinePdfSharp.Name = "btnCombinePdfSharp";
                 this.btnCombinePdfSharp.Size = new System.Drawing.Size(169, 23);
 49:
 50:
                 this.btnCombinePdfSharp.TabIndex = 0;
 51:
                 this.btnCombinePdfSharp.Text = "Combine Files (PdfSharp)";
 52:
                 this.btnCombinePdfSharp.UseVisualStyleBackColor = true;
 53:
                 this.btnCombinePdfSharp.Click += new
System.EventHandler(this.btnCombinePdfSharp_Click);
 54:
                 //
                 // btnAddFolder
 55:
 56:
                 this.btnAddFolder.Location = new System.Drawing.Point(12, 38);
 57:
 58:
                 this.btnAddFolder.Name = "btnAddFolder";
 59:
                 this.btnAddFolder.Size = new System.Drawing.Size(156, 23);
 60:
                 this.btnAddFolder.TabIndex = 2;
                 this.btnAddFolder.Text = "Add Folder";
 61:
                 this.btnAddFolder.UseVisualStyleBackColor = true;
 62:
 63:
                 this.btnAddFolder.Click += new
System.EventHandler(this.btnAddFolder_Click);
 64:
                 // btnAddFile
 65:
 66:
 67:
                 this.btnAddFile.Location = new System.Drawing.Point(12, 12);
 68:
                 this.btnAddFile.Name = "btnAddFile";
 69:
                 this.btnAddFile.Size = new System.Drawing.Size(156, 23);
 70:
                 this.btnAddFile.TabIndex = 3;
 71:
                 this.btnAddFile.Text = "Add Files";
 72:
                 this.btnAddFile.UseVisualStyleBackColor = true;
 73:
                 this.btnAddFile.Click += new System.EventHandler(this.btnAddFile_Click);
 74:
                 //
 75:
 76:
 77:
                 this.btnClearList.Location = new System.Drawing.Point(174, 12);
 78:
                 this.btnClearList.Name = "btnClearList";
 79:
                 this.btnClearList.Size = new System.Drawing.Size(90, 49);
 :08
                 this.btnClearList.TabIndex = 4;
 81:
                 this.btnClearList.Text = "Clear File List";
 82:
                 this.btnClearList.UseVisualStyleBackColor = true;
                 this.btnClearList.Click += new
 83:
System.EventHandler(this.btnClearList_Click);
 84:
                 // lbFiles
 85:
 86:
 87:
                 this.lbFiles.FormattingEnabled = true;
 88:
                 this.lbFiles.Location = new System.Drawing.Point(12, 88);
                 this.lbFiles.Name = "lbFiles";
 89:
                 this.lbFiles.SelectionMode =
System.Windows.Forms.SelectionMode.MultiExtended;
 91:
                 this.lbFiles.Size = new System.Drawing.Size(644, 186);
```

```
92:
                 this.lbFiles.TabIndex = 5;
 93:
                 this.lbFiles.KeyDown += new
System.Windows.Forms.KeyEventHandler(this.lbFiles_KeyDown);
                 // lblDetails
 95:
 96:
 97:
                 this.lblDetails.AutoSize = true;
                 this.lblDetails.Location = new System.Drawing.Point(12, 65);
 98:
 99:
                 this.lblDetails.Name = "lblDetails";
                 this.lblDetails.Size = new System.Drawing.Size(0, 13);
100:
101:
                 this.lblDetails.TabIndex = 6;
102:
103:
                 // pbFiles
104:
                 //
105:
                 this.pbFiles.Location = new System.Drawing.Point(270, 12);
106:
                 this.pbFiles.Name = "pbFiles";
                 this.pbFiles.Size = new System.Drawing.Size(211, 49);
107:
108:
                 this.pbFiles.TabIndex = 7;
109:
110:
                 // btnCombineITextSharp
111:
                 11
112:
                 this.btnCombineITextSharp.Location = new System.Drawing.Point(487, 38);
                 this.btnCombineITextSharp.Name = "btnCombineITextSharp";
113:
                 this.btnCombineITextSharp.Size = new System.Drawing.Size(169, 23);
114:
115:
                 this.btnCombineITextSharp.TabIndex = 9;
116:
                 this.btnCombineITextSharp.Text = "Combine Files (iTextSharp)";
117:
                 this.btnCombineITextSharp.UseVisualStyleBackColor = true;
118:
                 this.btnCombineITextSharp.Click += new
System.EventHandler(this.btnCombineITextSharp_Click);
119:
120:
                 // menuStrip
                 11
121:
122:
                 this.menuStrip.Items.AddRange(new System.Windows.Forms.ToolStripItem[] {
123:
                 this.menuItemDelete});
                 this.menuStrip.Name = "menuStrip";
124:
125:
                 this.menuStrip.Size = new System.Drawing.Size(181, 48);
126:
                 // menuItemDelete
127:
128:
129:
                 this.menuItemDelete.Image =
global::PdfCombiner.Properties.Resources.DeleteIcon1;
                 this.menuItemDelete.Name = "menuItemDelete";
130:
131:
                 this.menuItemDelete.Size = new System.Drawing.Size(180, 22);
132:
                 this.menuItemDelete.Text = "Delete";
                 this.menuItemDelete.Click += new
133:
System.EventHandler(this.menuItemDelete_Click);
134:
                 // FrmMain
135:
136:
137:
                 this.AutoScaleDimensions = new System.Drawing.SizeF(6F, 13F);
138:
                 this.AutoScaleMode = System.Windows.Forms.AutoScaleMode.Font;
139:
                 this.ClientSize = new System.Drawing.Size(668, 287);
140:
                 this.Controls.Add(this.btnCombineITextSharp);
141:
                 this.Controls.Add(this.pbFiles);
142:
                 this.Controls.Add(this.lblDetails);
143:
                 this.Controls.Add(this.lbFiles);
144:
                 this.Controls.Add(this.btnClearList);
                 this.Controls.Add(this.btnAddFile);
145:
                 this.Controls.Add(this.btnAddFolder);
146:
147:
                 this.Controls.Add(this.btnCombinePdfSharp);
148:
                 this.Name = "FrmMain";
149:
                 this.StartPosition = System.Windows.Forms.FormStartPosition.CenterScreen;
                 this.Text = "PDF Combiner";
150:
                 this.FormClosed += new
System.Windows.Forms.FormClosedEventHandler(this.FrmMain_FormClosed);
152:
                 this.Shown += new System.EventHandler(this.FrmMain_Shown);
153:
                 this.menuStrip.ResumeLayout(false);
154:
                 this.ResumeLayout(false);
155:
                 this.PerformLayout();
```

```
156:
157:
158:
159:
             #endregion
160:
161:
             private System.Windows.Forms.Button btnCombinePdfSharp;
162:
             private System.Windows.Forms.Button btnAddFolder;
163:
             private System.Windows.Forms.Button btnAddFile;
164:
             private System.Windows.Forms.Button btnClearList;
165:
             private System.Windows.Forms.ListBox lbFiles;
166:
             private System.Windows.Forms.Label lblDetails;
167:
             private System.Windows.Forms.ProgressBar pbFiles;
168:
             private System.Windows.Forms.Button btnCombineITextSharp;
169:
             private System.Windows.Forms.ContextMenuStrip menuStrip;
170:
             private System.Windows.Forms.ToolStripMenuItem menuItemDelete;
171:
172: }
173:
```

Name	Description
PdfCombiner (see page 1)	This is namespace PdfCombiner.

1.2.5 PdfCombiner.csproj

This is file PdfCombiner.csproj.

1.2.6 PdfCombiner.sIn

This is file PdfCombiner.sln.

1.2.7 Program.cs

This is file Program.cs.

Body Source

```
1: ?using System;
 2: using System.Collections.Generic;
 3: using System.Linq;
 4: using System.Windows.Forms;
 5:
 6: namespace PdfCombiner
 7: {
 8:
        static class Program
 9:
            /// <summary>
10:
11:
            /// The main entry point for the application.
            /// </summary>
12:
13:
            [STAThread]
14:
            static void Main()
15:
16:
                Application.EnableVisualStyles();
17:
                Application.SetCompatibleTextRenderingDefault(false);
18:
                Application.Run(new FrmMain());
```

```
19: }
20: }
21: }
```

Name	Description
PdfCombiner (see page 1)	This is namespace PdfCombiner.

1.2.8 Resources.Designer.cs

This code was generated by a tool. Runtime Version: 4.0.30319.42000

Changes to this file may cause incorrect behavior and will be lost if the code is regenerated.

Body Source

```
1: ?//----
 2: // <auto-generated>
 3: //
          This code was generated by a tool.
 4: //
5: //
           Runtime Version: 4.0.30319.42000
 6: //
           Changes to this file may cause incorrect behavior and will be lost if
 7: //
          the code is regenerated.
 8: // </auto-generated>
 9: //-
10:
11: namespace PdfCombiner.Properties {
12:
        using System;
13:
14:
15:
        /// <summary>
16:
             A strongly-typed resource class, for looking up localized strings, etc.
        /// </summary>
17:
        //\ {\tt This\ class\ was\ auto-generated\ by\ the\ Strongly Typed Resource Builder}
18:
        // class via a tool like ResGen or Visual Studio.
19:
        // To add or remove a member, edit your .ResX file then rerun ResGen \,
20:
21:
        // with the /str option, or rebuild your VS project.
22:
[global::System.CodeDom.Compiler.GeneratedCodeAttribute("System.Resources.Tools.StronglyType
dResourceBuilder",
"15.0.0.0")]
23:
        [global::System.Diagnostics.DebuggerNonUserCodeAttribute()]
24:
        [global::System.Runtime.CompilerServices.CompilerGeneratedAttribute()]
25:
        internal class Resources {
26:
27:
            private static global::System.Resources.ResourceManager resourceMan;
28:
29:
            private static global::System.Globalization.CultureInfo resourceCulture;
30:
[global::System.Diagnostics.CodeAnalysis.SuppressMessageAttribute("Microsoft.Performance",
"CA1811:AvoidUncalledPrivateCode")]
32:
            internal Resources() {
33:
34:
35:
            /// <summary>
                Returns the cached ResourceManager instance used by this class.
36:
37:
38:
[global::System.ComponentModel.EditorBrowsableAttribute(global::System.ComponentModel.Editor
BrowsableState.Advanced)]
39:
            internal static global::System.Resources.ResourceManager ResourceManager {
40:
41:
                    if (object.ReferenceEquals(resourceMan, null)) {
```

```
42:
                        global::System.Resources.ResourceManager temp = new
global::System.Resources.ResourceManager("PdfCombiner.Properties.Resources",
typeof(Resources).Assembly);
43:
                        resourceMan = temp;
44:
45:
                    return resourceMan;
46:
                }
47:
            }
48:
            /// <summary>
                  Overrides the current thread's CurrentUICulture property for all
50:
51:
                  resource lookups using this strongly typed resource class.
52:
            /// </summary>
53:
[global::System.ComponentModel.EditorBrowsableAttribute(global::System.ComponentModel.Editor
BrowsableState.Advanced)]
54:
            internal static global::System.Globalization.CultureInfo Culture {
55:
56:
                    return resourceCulture;
57:
58:
                set {
59:
                    resourceCulture = value;
60:
                }
            }
61:
62:
63:
            /// <summary>
64:
                  Looks up a localized resource of type System. Drawing. Bitmap.
            /// </summary>
65:
66:
            internal static System.Drawing.Bitmap DeleteIcon {
67:
68:
                    object obj = ResourceManager.GetObject("DeleteIcon", resourceCulture);
69:
                    return ((System.Drawing.Bitmap)(obj));
70:
71:
            }
72:
73:
            /// <summary>
                  Looks up a localized resource of type System.Drawing.Bitmap.
74:
            /// </summary>
75:
76:
            internal static System.Drawing.Bitmap DeleteIcon1 {
77:
                get {
78:
                    object obj = ResourceManager.GetObject("DeleteIcon1", resourceCulture);
79:
                    return ((System.Drawing.Bitmap)(obj));
80:
81:
            }
82:
83: }
```

Name	Description
PdfCombiner (☑ see page 1)	This is namespace PdfCombiner.

1.2.9 Settings.Designer.cs

This code was generated by a tool. Runtime Version: 4.0.30319.42000

Changes to this file may cause incorrect behavior and will be lost if the code is regenerated.

Body Source

```
6: //
           Changes to this file may cause incorrect behavior and will be lost if
 7: //
           the code is regenerated.
8: // </auto-generated>
9: //----
10:
11: namespace PdfCombiner.Properties
12: {
13:
14:
15:
        [global::System.Runtime.CompilerServices.CompilerGeneratedAttribute()]
16:
[global::System.CodeDom.Compiler.GeneratedCodeAttribute("Microsoft.VisualStudio.Editors.Sett
ingsDesigner.SettingsSingleFileGenerator",
"11.0.0.0")]
       internal sealed partial class Settings :
global::System.Configuration.ApplicationSettingsBase
18:
19:
           private static Settings defaultInstance =
20:
((Settings)(global::System.Configuration.ApplicationSettingsBase.Synchronized(new
Settings()));
21:
22:
            public static Settings Default
23:
24:
                get
25:
26:
                    return defaultInstance;
27:
28:
            }
        }
29:
30: }
```

Name	Description
PdfCombiner (see page 1)	This is namespace PdfCombiner.

2 PDF Combiner

Index	lbFiles 9
	lbFiles_KeyDown 18
	IbIDetails 9
A	menultemDelete 9
AssemblyInfo.cs 20	menultemDelete_Click 18
	menuStrip 10
В	pbFiles 10
	FrmMain.cs 22
BaseException class 5	FrmMain.Designer.cs 27
about BaseException class 5	
BaseException 5	P
E	PdfCombiner 1
ExceptionExtensions class 6	PdfCombiner namespace 1
about ExceptionExtensions class 6	Classes 4
GetAllMessages 6	PdfCombiner.BaseException 5
Exceptions.cs 21	PdfCombiner.BaseException.BaseException 5
2.000pii0110.00 21	PdfCombiner.csproj 30
F	PdfCombiner.ExceptionExtensions 6
	PdfCombiner.ExceptionExtensions.GetAllMessages 6
Files 20	PdfCombiner.FrmMain 7
FrmMain class 7	PdfCombiner.FrmMain.AppTitle 8
about FrmMain class 7	PdfCombiner.FrmMain.btnAddFile 8
AppTitle 8	PdfCombiner.FrmMain.btnAddFile_Click 10
btnAddFile 8	PdfCombiner.FrmMain.btnAddFolder 8
btnAddFile_Click 10	PdfCombiner.FrmMain.btnAddFolder_Click 10
btnAddFolder 8	PdfCombiner.FrmMain.btnClearList 9
btnAddFolder_Click 10	PdfCombiner.FrmMain.btnClearList_Click 11
btnClearList 9	PdfCombiner.FrmMain.btnCombinelTextSharp 9
btnClearList_Click 11	PdfCombiner.FrmMain.btnCombinelTextSharp_Click 11
btnCombinelTextSharp 9	PdfCombiner.FrmMain.btnCombinePdfSharp 9
btnCombinelTextSharp_Click 11	PdfCombiner.FrmMain.btnCombinePdfSharp_Click 13
btnCombinePdfSharp 9	PdfCombiner.FrmMain.components 9
btnCombinePdfSharp_Click 13	PdfCombiner.FrmMain.DeleteFilesFromListBox 14
components 9	PdfCombiner.FrmMain.Dispose 15
DeleteFilesFromListBox 14	PdfCombiner.FrmMain.FrmMain 8
Dispose 15	PdfCombiner.FrmMain.FrmMain_FormClosed 15
FrmMain 8	PdfCombiner.FrmMain.FrmMain_Shown 15
FrmMain_FormClosed 15	PdfCombiner.FrmMain.InitializeComponent 16
FrmMain_Shown 15	PdfCombiner.FrmMain.InitializeFileDialog 18
InitializeComponent 16	PdfCombiner.FrmMain.lbFiles 9

Created with a commercial version of Doc-O-Matic. In order to make this message disappear you need to register this software. If you have problems registering this software please contact us at support@toolsfactory.com.

InitializeFileDialog 18

2 PDF Combiner

PdfCombiner.FrmMain.lbFiles_KeyDown 18 PdfCombiner.FrmMain.lblDetails 9 PdfCombiner.FrmMain.menuItemDelete 9 PdfCombiner.FrmMain.menuItemDelete_Click 18 PdfCombiner.FrmMain.menuStrip 10 PdfCombiner.FrmMain.pbFiles 10 PdfCombiner.Program 19 PdfCombiner.Program.Main 19 PdfCombiner.Properties 1 PdfCombiner.Properties namespace 1 Classes 1 PdfCombiner.Properties.Resources 1 PdfCombiner.Properties.Resources.Culture 3 PdfCombiner.Properties.Resources.DeleteIcon 3 PdfCombiner.Properties.Resources.DeleteIcon1 3 PdfCombiner.Properties.Resources.resourceCulture 2 PdfCombiner.Properties.Resources.resourceMan 3 PdfCombiner.Properties.Resources.ResourceManager 3 PdfCombiner.Properties.Resources.Resources 2 PdfCombiner.Properties.Settings 3 PdfCombiner.Properties.Settings.Default 4 PdfCombiner.Properties.Settings.defaultInstance 4 PdfCombiner.sln 30 Program class 19 about Program class 19 Main 19

Settings class 3
about Settings class 3
Default 4

defaultInstance 4

Settings.Designer.cs 32

R

Program.cs 30

Resources class 1
about Resources class 1
Culture 3
Deletelcon 3
Deletelcon1 3
resourceCulture 2
resourceMan 3
ResourceManager 3
Resources 2

Resources.Designer.cs 31