

Linux Standard Base Desktop Specification for PPC64 3.1

Linux Standard Base Desktop Specification for PPC64 3.1

Copyright © 2005, 2006 Free Standards Group

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1; with no Invariant Sections, with no Front-Cover Texts, and with no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

Portions of the text are copyrighted by the following parties:

- The Regents of the University of California
- Free Software Foundation
- Ian F. Darwin
- Paul Vixie
- BSDI (now Wind River)
- Andrew G Morgan
- Jean-loup Gailly and Mark Adler
- Massachusetts Institute of Technology

These excerpts are being used in accordance with their respective licenses.

Linux is the registered trademark of Linus Torvalds in the U.S. and other countries.

UNIX is a registered trademark of The Open Group.

LSB is a trademark of the Free Standards Group in the United States and other countries.

AMD is a trademark of Advanced Micro Devices, Inc.

Intel and Itanium are registered trademarks and Intel386 is a trademark of Intel Corporation.

PowerPC is a registered trademark and PowerPC Architecture is a trademark of the IBM Corporation.

S/390 is a registered trademark of the IBM Corporation.

OpenGL is a registered trademark of Silicon Graphics, Inc.

Contents

I Introductory Elements	1
1 Scope.....	1
2 References.....	2
2.1 Normative References	2
2.2 Informative References/Bibliography	4
3 Requirements	5
3.1 Relevant Libraries	5
4 Definitions	6
5 Terminology	7
II GTK+ Stack Libraries.....	8
6 Libraries	9
6.1 Introduction	9
6.2 Interfaces for libglib-2.0.....	10
6.3 Data Definitions for libglib-2.0.....	10
6.4 Interfaces for libgobject-2.0	11
6.5 Data Definitions for libgobject-2.0	12
6.6 Interfaces for libgmodule-2.0.....	12
6.7 Data Definitions for libgmodule-2.0.....	13
6.8 Interfaces for libatk-1.0	13
6.9 Data Definitions for libatk-1.0	13
6.10 Interfaces for libpango-1.0	14
6.11 Data Definitions for libpango-1.0.....	14
6.12 Interfaces for libpangoft2-1.0.....	15
6.13 Data Definitions for libpangoft2-1.0.....	15
6.14 Interfaces for libpangoft2-1.0.....	16
6.15 Data Definitions for libpangoft2-1.0	16
6.16 Interfaces for libgdk_pixbuf-2.0	17
6.17 Data Definitions for libgdk_pixbuf-2.0	17
6.18 Interfaces for libgdk_pixbuf_xlib-2.0.....	18
6.19 Data Definitions for libgdk_pixbuf_xlib-2.0.....	18
6.20 Interfaces for libgdk-x11-2.0	19
6.21 Data Definitions for libgdk-x11-2.0.....	19
6.22 Interfaces for libgtk-x11-2.0	20
6.23 Data Definitions for libgtk-x11-2.0.....	20
III Qt3 Library.....	21
7 Library	22
7.1 Introduction	22
7.2 Interfaces for libqt-mt	22
IV Package Information.....	712
8 Package Dependencies.....	713
8.1 Package Dependencies	713
A GNU Free Documentation License (Informative).....	714
A.1 PREAMBLE	714
A.2 APPLICABILITY AND DEFINITIONS	714
A.3 VERBATIM COPYING	715
A.4 COPYING IN QUANTITY	715
A.5 MODIFICATIONS.....	716
A.6 COMBINING DOCUMENTS	717
A.7 COLLECTIONS OF DOCUMENTS.....	718
A.8 AGGREGATION WITH INDEPENDENT WORKS	718

A.9 TRANSLATION.....	718
A.10 TERMINATION.....	718
A.11 FUTURE REVISIONS OF THIS LICENSE	719
A.12 How to use this License for your documents	719

List of Tables

2-1 Normative References	2
2-2 Other References	4
3-1 Standard Library Names	5
6-1 libglib-2.0 Definition	10
6-2 libgobject-2.0 Definition	11
6-3 libgmodule-2.0 Definition	12
6-4 libatk-1.0 Definition	13
6-5 libpango-1.0 Definition	14
6-6 libpangoxft-1.0 Definition	15
6-7 libpangoft2-1.0 Definition	16
6-8 libgdk_pixbuf-2.0 Definition	17
6-9 libgdk_pixbuf_xlib-2.0 Definition	18
6-10 libgdk-x11-2.0 Definition	19
6-11 libgtk-x11-2.0 Definition	20
7-1 libqt-mt Definition	22
7-2 Primary vtable for QTextCodec	23
7-3 typeinfo for QTextCodec	23
7-4 Primary vtable for QTimer	24
7-5 typeinfo for QTimer	24
7-6 Primary vtable for QXmlEntityResolver	25
7-7 typeinfo for QXmlEntityResolver	25
7-8 Primary vtable for QObjectCleanupHandler	25
7-9 typeinfo for QObjectCleanupHandler	26
7-10 Primary vtable for QPtrCollection	26
7-11 typeinfo for QPtrCollection	27
7-12 Primary vtable for QHBox	27
7-13 Secondary vtable for QHBox	31
7-14 typeinfo for QHBox	32
7-15 Primary vtable for QGVector	32
7-16 typeinfo for QGVector	33
7-17 Primary vtable for QToolBar	33
7-18 Secondary vtable for QToolBar	38
7-19 typeinfo for QToolBar	39
7-20 Primary vtable for QDataSource	39
7-21 typeinfo for QDataSource	39
7-22 Primary vtable for QCanvasItem	39
7-23 typeinfo for QCanvasItem	40
7-24 Primary vtable for QWaitCondition	40
7-25 typeinfo for QWaitCondition	41
7-26 Primary vtable for QFrame	41
7-27 Secondary vtable for QFrame	45
7-28 typeinfo for QFrame	46
7-29 Primary vtable for QScrollView	46
7-30 Secondary vtable for QScrollView	52
7-31 typeinfo for QScrollView	53
7-32 Primary vtable for QTextBrowser	53
7-33 Secondary vtable for QTextBrowser	62
7-34 typeinfo for QTextBrowser	63
7-35 Primary vtable for QCanvasSprite	63
7-36 typeinfo for QCanvasSprite	64
7-37 Primary vtable for QSplitter	64

7-38 Secondary vtable for QSplitter	69
7-39 typeinfo for QSplitter	69
7-40 Primary vtable for QLineEdit.....	70
7-41 Secondary vtable for QLineEdit.....	75
7-42 typeinfo for QLineEdit	75
7-43 Primary vtable for QVBox	76
7-44 Secondary vtable for QVBox	80
7-45 typeinfo for QVBox.....	80
7-46 Primary vtable for QContextMenuEvent	81
7-47 typeinfo for QContextMenuEvent.....	81
7-48 Primary vtable for QProcess.....	81
7-49 typeinfo for QProcess	83
7-50 Primary vtable for QImageFormat	83
7-51 typeinfo for QImageFormat.....	83
7-52 Primary vtable for QTranslator.....	83
7-53 typeinfo for QTranslator	84
7-54 Primary vtable for QXmlLocator	84
7-55 typeinfo for QXmlLocator.....	85
7-56 Primary vtable for QPopupMenu.....	85
7-57 Secondary vtable for QPopupMenu.....	90
7-58 Secondary vtable for QPopupMenu.....	90
7-59 typeinfo for QPopupMenu	91
7-60 Primary vtable for QImageDrag	91
7-61 Secondary vtable for QImageDrag	92
7-62 typeinfo for QImageDrag	93
7-63 Primary vtable for QMimeSourceFactory	93
7-64 typeinfo for QMimeSourceFactory	94
7-65 Primary vtable for QListBoxText.....	94
7-66 typeinfo for QListBoxText	95
7-67 Primary vtable for QGroupBox.....	95
7-68 Secondary vtable for QGroupBox.....	99
7-69 typeinfo for QGroupBox	100
7-70 Primary vtable for QMenuBar	100
7-71 Secondary vtable for QMenuBar	105
7-72 Secondary vtable for QMenuBar	105
7-73 typeinfo for QMenuBar	106
7-74 Primary vtable for QProgressDialog.....	106
7-75 Secondary vtable for QProgressDialog.....	111
7-76 typeinfo for QProgressDialog	111
7-77 Primary vtable for QDateTimeEdit	112
7-78 Secondary vtable for QDateTimeEdit	116
7-79 typeinfo for QDateTimeEdit.....	116
7-80 Primary vtable for QSqlResult	117
7-81 typeinfo for QSqlResult.....	117
7-82 Primary vtable for QRegExpValidator.....	118
7-83 typeinfo for QRegExpValidator	119
7-84 Primary vtable for QDockAreaLayout.....	119
7-85 Secondary vtable for QDockAreaLayout.....	120
7-86 typeinfo for QDockAreaLayout	122
7-87 Primary vtable for QDragLeaveEvent	122
7-88 typeinfo for QDragLeaveEvent.....	122
7-89 Primary vtable for QLCDNumber.....	122
7-90 Secondary vtable for QLCDNumber.....	127
7-91 typeinfo for QLCDNumber	128

7-92 Primary vtable for QUrlOperator	128
7-93 Secondary vtable for QUrlOperator	129
7-94 typeinfo for QUrlOperator	130
7-95 Primary vtable for QSocket	130
7-96 Secondary vtable for QSocket	132
7-97 typeinfo for QSocket.....	133
7-98 Primary vtable for QGridView	133
7-99 Secondary vtable for QGridView	140
7-100 typeinfo for QGridView.....	140
7-101 Primary vtable for QBoxLayout.....	140
7-102 Secondary vtable for QBoxLayout.....	142
7-103 typeinfo for QBoxLayout	143
7-104 Primary vtable for QIMEvent.....	143
7-105 typeinfo for QIMEvent.....	143
7-106 Primary vtable for QLayout	144
7-107 Secondary vtable for QLayout	145
7-108 typeinfo for QLayout.....	146
7-109 Primary vtable for QSocketNotifier.....	146
7-110 typeinfo for QSocketNotifier	147
7-111 Primary vtable for QPushButton.....	147
7-112 Secondary vtable for QPushButton.....	152
7-113 typeinfo for QPushButton	152
7-114 Primary vtable for QIntValidator	153
7-115 typeinfo for QIntValidator.....	154
7-116 Primary vtable for QWizard.....	154
7-117 Secondary vtable for QWizard.....	159
7-118 typeinfo for QWizard	159
7-119 Primary vtable for QCanvasPolygonalItem.....	159
7-120 typeinfo for QCanvasPolygonalItem	161
7-121 Primary vtable for QSqlSelectCursor	161
7-122 Secondary vtable for QSqlSelectCursor	163
7-123 typeinfo for QSqlSelectCursor	164
7-124 Primary vtable for QTabWidget	164
7-125 Secondary vtable for QTabWidget	168
7-126 typeinfo for QTabWidget.....	169
7-127 Primary vtable for QDomElement.....	169
7-128 typeinfo for QDomElement.....	171
7-129 Primary vtable for QSqlDriver	171
7-130 typeinfo for QSqlDriver	173
7-131 Primary vtable for QTableWidgetItem.....	173
7-132 typeinfo for QTableWidgetItem.....	174
7-133 Primary vtable for QDomImplementation.....	174
7-134 typeinfo for QDomImplementation	174
7-135 Primary vtable for QGPlugin	175
7-136 typeinfo for QGPlugin.....	176
7-137 Primary vtable for QGb18030Codec.....	176
7-138 typeinfo for QGb18030Codec	177
7-139 Primary vtable for QGLList	177
7-140 typeinfo for QGLList.....	177
7-141 Primary vtable for QDataPump.....	177
7-142 typeinfo for QDataPump	178
7-143 Primary vtable for QPaintDevice.....	179
7-144 typeinfo for QPaintDevice	179
7-145 Primary vtable for QCheckTableItem	179

7-146 typeinfo for QCheckTableWidgetItem.....	180
7-147 Primary vtable for QCommonStyle.....	180
7-148 typeinfo for QCommonStyle	183
7-149 Primary vtable for QTextView	183
7-150 Secondary vtable for QTextView	192
7-151 typeinfo for QTextView	192
7-152 Primary vtable for QSyntaxHighlighter	193
7-153 typeinfo for QSyntaxHighlighter	193
7-154 Primary vtable for QSemimodal.....	193
7-155 Secondary vtable for QSemimodal.....	197
7-156 typeinfo for QSemimodal	198
7-157 Primary vtable for QTab	198
7-158 typeinfo for QTab.....	198
7-159 Primary vtable for QPolygonScanner	199
7-160 typeinfo for QPolygonScanner.....	199
7-161 Primary vtable for QNetworkProtocol	199
7-162 typeinfo for QNetworkProtocol.....	201
7-163 Primary vtable for QObjectUserData	201
7-164 typeinfo for QObjectUserData	201
7-165 Primary vtable for QRangeControl	201
7-166 typeinfo for QRangeControl.....	202
7-167 Primary vtable for QHGroupBox	202
7-168 Secondary vtable for QHGroupBox	206
7-169 typeinfo for QHGroupBox.....	207
7-170 Primary vtable for QTimerEvent	207
7-171 typeinfo for QTimerEvent	208
7-172 Primary vtable for QHeader.....	208
7-173 Secondary vtable for QHeader.....	212
7-174 typeinfo for QHeader	213
7-175 Primary vtable for QGbkCodec	213
7-176 typeinfo for QGbkCodec.....	214
7-177 Primary vtable for QSplashScreen.....	214
7-178 Secondary vtable for QSplashScreen.....	218
7-179 typeinfo for QSplashScreen	219
7-180 Primary vtable for QMutex	219
7-181 typeinfo for QMutex.....	219
7-182 Primary vtable for QSqlPropertyMap.....	220
7-183 typeinfo for QSqlPropertyMap	220
7-184 Primary vtable for QKeyEvent.....	220
7-185 typeinfo for QKeyEvent.....	220
7-186 Primary vtable for QGCache	221
7-187 typeinfo for QGCache	221
7-188 Primary vtable for QDial	221
7-189 Secondary vtable for QDial	225
7-190 Secondary vtable for QDial	226
7-191 typeinfo for QDial.....	226
7-192 Primary vtable for QUrl.....	227
7-193 typeinfo for QUrl	227
7-194 Primary vtable for QListView	227
7-195 Secondary vtable for QListView	235
7-196 typeinfo for QListView	235
7-197 Primary vtable for QStylePlugin.....	236
7-198 typeinfo for QStylePlugin.....	237
7-199 Primary vtable for QFileDialog.....	237

7-200 Secondary vtable for QFileDialog.....	241
7-201 typeinfo for QFileDialog.....	242
7-202 Primary vtable for QHButtonGroup.....	242
7-203 Secondary vtable for QHButtonGroup.....	247
7-204 typeinfo for QHButtonGroup.....	247
7-205 Primary vtable for QColorDrag.....	248
7-206 Secondary vtable for QColorDrag.....	249
7-207 typeinfo for QColorDrag.....	249
7-208 Primary vtable for QDesktopWidget.....	249
7-209 Secondary vtable for QDesktopWidget.....	254
7-210 typeinfo for QDesktopWidget.....	254
7-211 Primary vtable for QSqlQuery.....	254
7-212 typeinfo for QSqlQuery.....	255
7-213 Primary vtable for QUtf16Codec.....	255
7-214 typeinfo for QUtf16Codec.....	256
7-215 Primary vtable for QObject.....	256
7-216 typeinfo for QObject.....	257
7-217 Primary vtable for QFile.....	257
7-218 typeinfo for QFile.....	258
7-219 Primary vtable for QDomDocumentType.....	258
7-220 typeinfo for QDomDocumentType.....	260
7-221 Primary vtable for QListBoxItem.....	260
7-222 typeinfo for QListBoxItem.....	261
7-223 Primary vtable for QDragResponseEvent.....	261
7-224 typeinfo for QDragResponseEvent.....	261
7-225 Primary vtable for QDomDocument.....	261
7-226 typeinfo for QDomDocument.....	263
7-227 Primary vtable for QTextCodecPlugin.....	263
7-228 typeinfo for QTextCodecPlugin.....	265
7-229 Primary vtable for QWidgetPlugin.....	265
7-230 typeinfo for QWidgetPlugin.....	266
7-231 Primary vtable for QScrollBar.....	266
7-232 Secondary vtable for QScrollBar.....	271
7-233 Secondary vtable for QScrollBar.....	271
7-234 typeinfo for QScrollBar.....	272
7-235 Primary vtable for QPixmap.....	272
7-236 typeinfo for QPixmap.....	272
7-237 Primary vtable for QIconFactory.....	273
7-238 typeinfo for QIconFactory.....	273
7-239 Primary vtable for QSpinBox.....	273
7-240 Secondary vtable for QSpinBox.....	278
7-241 Secondary vtable for QSpinBox.....	279
7-242 typeinfo for QSpinBox.....	279
7-243 Primary vtable for QLibrary.....	279
7-244 typeinfo for QLibrary.....	280
7-245 Primary vtable for QEucKrCodec.....	280
7-246 typeinfo for QEucKrCodec.....	281
7-247 Primary vtable for QWidgetStack.....	281
7-248 Secondary vtable for QWidgetStack.....	285
7-249 typeinfo for QWidgetStack.....	286
7-250 Primary vtable for QLabel.....	286
7-251 Secondary vtable for QLabel.....	291
7-252 typeinfo for QLabel.....	291
7-253 Primary vtable for QStyleSheet.....	291

7-254 typeinfo for QStyleSheet	293
7-255 Primary vtable for QCustomEvent	293
7-256 typeinfo for QCustomEvent	293
7-257 Primary vtable for QListBoxPixmap	293
7-258 typeinfo for QListBoxPixmap	294
7-259 Primary vtable for QDragManager	294
7-260 typeinfo for QDragManager	295
7-261 Primary vtable for QDomAttr	295
7-262 typeinfo for QDomAttr	297
7-263 Primary vtable for QWhatsThis	297
7-264 typeinfo for QWhatsThis	297
7-265 Primary vtable for QDomNodeList	298
7-266 typeinfo for QDomNodeList	298
7-267 Primary vtable for QJisCodec	298
7-268 typeinfo for QJisCodec	299
7-269 Primary vtable for QPointArray	299
7-270 typeinfo for QPointArray	299
7-271 Primary vtable for QMultiLineEdit	300
7-272 Secondary vtable for QMultiLineEdit	309
7-273 typeinfo for QMultiLineEdit	310
7-274 Primary vtable for QNetworkProtocolFactoryBase	310
7-275 typeinfo for QNetworkProtocolFactoryBase	310
7-276 Primary vtable for QHBoxLayout	310
7-277 Secondary vtable for QHBoxLayout	312
7-278 typeinfo for QHBoxLayout	313
7-279 Primary vtable for QSocketDevice	313
7-280 typeinfo for QSocketDevice	314
7-281 Primary vtable for QXmlReader	314
7-282 typeinfo for QXmlReader	315
7-283 Primary vtable for QDomEntity	315
7-284 typeinfo for QDomEntity	317
7-285 Primary vtable for QMetaObject	317
7-286 typeinfo for QMetaObject	318
7-287 Primary vtable for QErrorMessage	318
7-288 Secondary vtable for QErrorMessage	322
7-289 typeinfo for QErrorMessage	323
7-290 Primary vtable for QListBox	323
7-291 Secondary vtable for QListBox	329
7-292 typeinfo for QListBox	330
7-293 Primary vtable for QCustomMenuItem	330
7-294 typeinfo for QCustomMenuItem	331
7-295 Primary vtable for QIconDrag	331
7-296 Secondary vtable for QIconDrag	332
7-297 typeinfo for QIconDrag	332
7-298 Primary vtable for QUriDrag	333
7-299 Secondary vtable for QUriDrag	334
7-300 typeinfo for QUriDrag	334
7-301 Primary vtable for QXmlDeclHandler	334
7-302 typeinfo for QXmlDeclHandler	335
7-303 Primary vtable for QVBoxLayout	335
7-304 Secondary vtable for QVBoxLayout	336
7-305 typeinfo for QVBoxLayout	337
7-306 Primary vtable for QDomNode	338
7-307 typeinfo for QDomNode	339

7-308 Primary vtable for QBuffer.....	339
7-309 typeinfo for QBuffer	340
7-310 Primary vtable for QCanvasRectangle.....	340
7-311 typeinfo for QCanvasRectangle	342
7-312 Primary vtable for QIconSet.....	342
7-313 typeinfo for QIconSet	342
7-314 Primary vtable for QDropSite	342
7-315 typeinfo for QDropSite.....	343
7-316 Primary vtable for QThread	343
7-317 typeinfo for QThread.....	343
7-318 Primary vtable for QStoredDrag.....	343
7-319 Secondary vtable for QStoredDrag.....	344
7-320 typeinfo for QStoredDrag	345
7-321 Primary vtable for QTextDrag	345
7-322 Secondary vtable for QTextDrag	346
7-323 typeinfo for QTextDrag.....	347
7-324 Primary vtable for QFilePreview	347
7-325 typeinfo for QFilePreview	347
7-326 Primary vtable for QButtonGroup	347
7-327 Secondary vtable for QButtonGroup	352
7-328 typeinfo for QButtonGroup.....	353
7-329 Primary vtable for QSqlRecord	353
7-330 typeinfo for QSqlRecord	354
7-331 Primary vtable for QPicture	354
7-332 typeinfo for QPicture.....	354
7-333 Primary vtable for QSemaphore.....	355
7-334 typeinfo for QSemaphore	355
7-335 Primary vtable for QComboBox	355
7-336 Secondary vtable for QComboBox	360
7-337 typeinfo for QComboBox.....	360
7-338 Primary vtable for QDomText	360
7-339 typeinfo for QDomText.....	362
7-340 Primary vtable for QVButtonGroup.....	363
7-341 Secondary vtable for QVButtonGroup	367
7-342 typeinfo for QVButtonGroup.....	368
7-343 Primary vtable for QClipboard.....	368
7-344 typeinfo for QClipboard	369
7-345 Primary vtable for QTextEncoder.....	369
7-346 typeinfo for QTextEncoder.....	370
7-347 Primary vtable for QCanvasView.....	370
7-348 Secondary vtable for QCanvasView.....	376
7-349 typeinfo for QCanvasView	377
7-350 Primary vtable for QPixmap	377
7-351 typeinfo for QPixmap.....	377
7-352 Primary vtable for QGrid.....	378
7-353 Secondary vtable for QGrid.....	382
7-354 typeinfo for QGrid	383
7-355 Primary vtable for QRadioButton.....	383
7-356 Secondary vtable for QRadioButton.....	388
7-357 typeinfo for QRadioButton.....	388
7-358 Primary vtable for QAsyncIO	388
7-359 typeinfo for QAsyncIO	389
7-360 Primary vtable for QSlider.....	389
7-361 Secondary vtable for QSlider	393

7-362 Secondary vtable for QSlider	394
7-363 typeinfo for QSlider.....	394
7-364 Primary vtable for QHttpResponseHeader.....	394
7-365 typeinfo for QHttpResponseHeader	395
7-366 Primary vtable for QDomCharacterData.....	395
7-367 typeinfo for QDomCharacterData	397
7-368 Primary vtable for QDragEnterEvent	397
7-369 Secondary vtable for QDragEnterEvent	398
7-370 typeinfo for QDragEnterEvent.....	398
7-371 Primary vtable for QActionGroup.....	398
7-372 typeinfo for QActionGroup	400
7-373 Primary vtable for QDataTable.....	400
7-374 Secondary vtable for QDataTable.....	411
7-375 typeinfo for QDataTable	411
7-376 Primary vtable for QDragMoveEvent.....	411
7-377 Secondary vtable for QDragMoveEvent.....	412
7-378 typeinfo for QDragMoveEvent	412
7-379 Primary vtable for QCanvasEllipse.....	412
7-380 typeinfo for QCanvasEllipse	414
7-381 Primary vtable for QDropEvent	414
7-382 Secondary vtable for QDropEvent	414
7-383 typeinfo for QDropEvent.....	415
7-384 Primary vtable for QMainWindow	415
7-385 Secondary vtable for QMainWindow	420
7-386 typeinfo for QMainWindow.....	421
7-387 Primary vtable for QStatusBar	421
7-388 Secondary vtable for QStatusBar	425
7-389 typeinfo for QStatusBar.....	426
7-390 Primary vtable for QList	426
7-391 typeinfo for QList.....	427
7-392 Primary vtable for QTsciiCodec.....	427
7-393 typeinfo for QTsciiCodec	428
7-394 Primary vtable for QSqlDatabase	428
7-395 typeinfo for QSqlDatabase.....	429
7-396 Primary vtable for QCanvasPixmap	429
7-397 typeinfo for QCanvasPixmap.....	430
7-398 Primary vtable for QPrinter.....	430
7-399 typeinfo for QPrinter	431
7-400 Primary vtable for QSjisCodec.....	432
7-401 typeinfo for QSjisCodec	432
7-402 Primary vtable for QMessageBox	433
7-403 Secondary vtable for QMessageBox	437
7-404 typeinfo for QMessageBox	438
7-405 Primary vtable for QSound	438
7-406 typeinfo for QSound.....	439
7-407 Primary vtable for QEditorFactory.....	439
7-408 typeinfo for QEditorFactory	440
7-409 Primary vtable for QEventLoop.....	440
7-410 typeinfo for QEventLoop.....	441
7-411 Primary vtable for QSignal.....	442
7-412 typeinfo for QSignal	443
7-413 Primary vtable for QSizeGrip.....	443
7-414 Secondary vtable for QSizeGrip.....	447
7-415 typeinfo for QSizeGrip.....	447

7-416 Primary vtable for QObjectList	448
7-417 typeinfo for QObjectList	448
7-418 Primary vtable for QDomComment	448
7-419 typeinfo for QDomComment	450
7-420 Primary vtable for QXmlDefaultHandler	451
7-421 Secondary vtable for QXmlDefaultHandler	452
7-422 Secondary vtable for QXmlDefaultHandler	453
7-423 Secondary vtable for QXmlDefaultHandler	453
7-424 Secondary vtable for QXmlDefaultHandler	453
7-425 Secondary vtable for QXmlDefaultHandler	454
7-426 typeinfo for QXmlDefaultHandler	454
7-427 Primary vtable for QDataSink	455
7-428 typeinfo for QDataSink	455
7-429 Primary vtable for QSqlDriverPlugin	456
7-430 typeinfo for QSqlDriverPlugin	457
7-431 Primary vtable for QToolButton	457
7-432 Secondary vtable for QToolButton	462
7-433 typeinfo for QToolButton	462
7-434 Primary vtable for QWidgetIntDict	462
7-435 typeinfo for QWidgetIntDict	463
7-436 Primary vtable for QTabBar	463
7-437 Secondary vtable for QTabBar	468
7-438 typeinfo for QTabBar	468
7-439 Primary vtable for QDomNotation	469
7-440 typeinfo for QDomNotation	470
7-441 Primary vtable for QXmlSimpleReader	470
7-442 typeinfo for QXmlSimpleReader	472
7-443 Primary vtable for QHideEvent	472
7-444 typeinfo for QHideEvent	472
7-445 Primary vtable for QToolTip	472
7-446 typeinfo for QToolTip	473
7-447 Primary vtable for QResizeEvent	473
7-448 typeinfo for QResizeEvent	473
7-449 Primary vtable for QXmlLexicalHandler	473
7-450 typeinfo for QXmlLexicalHandler	474
7-451 Primary vtable for QCanvasLine	474
7-452 typeinfo for QCanvasLine	475
7-453 Primary vtable for QXmlAttributes	475
7-454 typeinfo for QXmlAttributes	475
7-455 Primary vtable for QDialog	476
7-456 Secondary vtable for QDialog	480
7-457 typeinfo for QDialog	480
7-458 Primary vtable for QGLLayoutIterator	481
7-459 typeinfo for QGLLayoutIterator	481
7-460 Primary vtable for QTabletEvent	481
7-461 typeinfo for QTabletEvent	482
7-462 Primary vtable for QWidgetItem	482
7-463 typeinfo for QWidgetItem	482
7-464 Primary vtable for QDir	483
7-465 typeinfo for QDir	484
7-466 Primary vtable for QDomProcessingInstruction	484
7-467 typeinfo for QDomProcessingInstruction	486
7-468 Primary vtable for QCanvasSpline	486
7-469 typeinfo for QCanvasSpline	488

7-470 Primary vtable for QFontDialog	488
7-471 Secondary vtable for QFontDialog	492
7-472 typeinfo for QFontDialog	493
7-473 Primary vtable for QGArray	493
7-474 typeinfo for QGArray	493
7-475 Primary vtable for QBitArray	493
7-476 typeinfo for QBitArray	494
7-477 Primary vtable for QCheckBox	494
7-478 Secondary vtable for QCheckBox	498
7-479 typeinfo for QCheckBox	499
7-480 Primary vtable for QDockWindow	499
7-481 Secondary vtable for QDockWindow	504
7-482 typeinfo for QDockWindow	505
7-483 Primary vtable for QImageFormatPlugin	505
7-484 typeinfo for QImageFormatPlugin	506
7-485 Primary vtable for QEuclJpCodec	507
7-486 typeinfo for QEuclJpCodec	507
7-487 Primary vtable for QSqlResultShared	508
7-488 typeinfo for QSqlResultShared	509
7-489 Primary vtable for QSqlError	509
7-490 typeinfo for QSqlError	509
7-491 Primary vtable for QServerSocket	509
7-492 typeinfo for QServerSocket	510
7-493 Primary vtable for QXmlContentHandler	511
7-494 typeinfo for QXmlContentHandler	511
7-495 Primary vtable for QGbz312Codec	511
7-496 typeinfo for QGbz312Codec	512
7-497 Primary vtable for QFocusEvent	512
7-498 typeinfo for QFocusEvent	513
7-499 Primary vtable for QMouseEvent	513
7-500 typeinfo for QMouseEvent	513
7-501 Primary vtable for QUrlInfo	513
7-502 typeinfo for QUrlInfo	514
7-503 Primary vtable for QImageConsumer	514
7-504 typeinfo for QImageConsumer	514
7-505 Primary vtable for QDomEntityReference	515
7-506 typeinfo for QDomEntityReference	516
7-507 Primary vtable for QSpinWidget	517
7-508 Secondary vtable for QSpinWidget	521
7-509 typeinfo for QSpinWidget	521
7-510 Primary vtable for QChildEvent	522
7-511 typeinfo for QChildEvent	522
7-512 Primary vtable for QTextOStream	522
7-513 typeinfo for QTextOStream	522
7-514 Primary vtable for QSignalVec	522
7-515 typeinfo for QSignalVec	523
7-516 Primary vtable for QValidator	523
7-517 typeinfo for QValidator	524
7-518 Primary vtable for QGridLayout	524
7-519 Secondary vtable for QGridLayout	526
7-520 typeinfo for QGridLayout	527
7-521 Primary vtable for QHebrewCodec	527
7-522 typeinfo for QHebrewCodec	528
7-523 Primary vtable for QToolBox	528

7-524 Secondary vtable for QToolBox	533
7-525 typeinfo for QToolBox.....	533
7-526 Primary vtable for QNetworkOperation	533
7-527 typeinfo for QNetworkOperation.....	534
7-528 Primary vtable for QHttp.....	535
7-529 typeinfo for QHttp	536
7-530 Primary vtable for QSqlForm.....	536
7-531 typeinfo for QSqlForm	538
7-532 Primary vtable for QEvent.....	538
7-533 typeinfo for QEvent.....	538
7-534 Primary vtable for QMimeSource.....	538
7-535 typeinfo for QMimeSource	539
7-536 Primary vtable for QIMComposeEvent.....	539
7-537 typeinfo for QIMComposeEvent	539
7-538 Primary vtable for QTextDecoder	539
7-539 typeinfo for QTextDecoder.....	540
7-540 Primary vtable for QSessionManager	540
7-541 typeinfo for QSessionManager.....	541
7-542 Primary vtable for QImageFormatType	541
7-543 typeinfo for QImageFormatType.....	541
7-544 Primary vtable for QTextCodec	542
7-545 typeinfo for QTextCodec	542
7-546 Primary vtable for QSpacerItem.....	543
7-547 typeinfo for QSpacerItem.....	543
7-548 Primary vtable for QPrintDialog	543
7-549 Secondary vtable for QPrintDialog	548
7-550 typeinfo for QPrintDialog.....	548
7-551 Primary vtable for QProgressBar.....	549
7-552 Secondary vtable for QProgressBar.....	553
7-553 typeinfo for QProgressBar	554
7-554 Primary vtable for QIconViewItem.....	554
7-555 typeinfo for QIconViewItem	555
7-556 Primary vtable for QDomCDATASection.....	556
7-557 typeinfo for QDomCDATASection	558
7-558 Primary vtable for QTextStream.....	558
7-559 typeinfo for QTextStream	558
7-560 Primary vtable for QCheckListItem	558
7-561 typeinfo for QCheckListItem.....	560
7-562 Primary vtable for QSignalMapper.....	560
7-563 typeinfo for QSignalMapper	561
7-564 Primary vtable for QDockArea	562
7-565 Secondary vtable for QDockArea	566
7-566 typeinfo for QDockArea	566
7-567 Primary vtable for QCString	567
7-568 typeinfo for QCString.....	567
7-569 Primary vtable for QStyle	567
7-570 typeinfo for QStyle.....	569
7-571 Primary vtable for QXmlDTDHandler	569
7-572 typeinfo for QXmlDTDHandler.....	569
7-573 Primary vtable for QColorDialog	569
7-574 Secondary vtable for QColorDialog	574
7-575 typeinfo for QColorDialog.....	574
7-576 Primary vtable for QGuardedPtrPrivate	574
7-577 typeinfo for QGuardedPtrPrivate.....	575

7-578 Primary vtable for QApplication	576
7-579 typeinfo for QApplication	577
7-580 Primary vtable for QListViewItem	577
7-581 typeinfo for QListViewItem	579
7-582 Primary vtable for QIconView	579
7-583 Secondary vtable for QIconView	587
7-584 typeinfo for QIconView	587
7-585 Primary vtable for QComboBoxItem	588
7-586 typeinfo for QComboBoxItem	589
7-587 Primary vtable for QWidget	589
7-588 Secondary vtable for QWidget	593
7-589 typeinfo for QWidget	594
7-590 Primary vtable for QDns	594
7-591 typeinfo for QDns	595
7-592 Primary vtable for QIODeviceSource	595
7-593 typeinfo for QIODeviceSource	596
7-594 Primary vtable for QCanvasText	596
7-595 typeinfo for QCanvasText	597
7-596 Primary vtable for QXmlInputSource	597
7-597 typeinfo for QXmlInputSource	597
7-598 Primary vtable for QDoubleValidator	598
7-599 typeinfo for QDoubleValidator	599
7-600 Primary vtable for QIODevice	599
7-601 typeinfo for QIODevice	600
7-602 Primary vtable for QInputDialog	600
7-603 Secondary vtable for QInputDialog	604
7-604 typeinfo for QInputDialog	605
7-605 Primary vtable for QGDICT	605
7-606 typeinfo for QGDICT	605
7-607 Primary vtable for QXmlErrorHandler	606
7-608 typeinfo for QXmlErrorHandler	606
7-609 Primary vtable for QWorkspace	606
7-610 Secondary vtable for QWorkspace	610
7-611 typeinfo for QWorkspace	611
7-612 Primary vtable for QTabDialog	611
7-613 Secondary vtable for QTabDialog	615
7-614 typeinfo for QTabDialog	616
7-615 Primary vtable for QHttpRequestHeader	616
7-616 typeinfo for QHttpRequestHeader	617
7-617 Primary vtable for QDragObject	617
7-618 Secondary vtable for QDragObject	618
7-619 typeinfo for QDragObject	618
7-620 Primary vtable for QToolTipGroup	619
7-621 typeinfo for QToolTipGroup	619
7-622 Primary vtable for QDateTimeEditBase	620
7-623 Secondary vtable for QDateTimeEditBase	624
7-624 typeinfo for QDateTimeEditBase	625
7-625 Primary vtable for QHTTPHeader	625
7-626 typeinfo for QHTTPHeader	625
7-627 Primary vtable for QShowEvent	626
7-628 typeinfo for QShowEvent	626
7-629 Primary vtable for QTable	626
7-630 Secondary vtable for QTable	635
7-631 typeinfo for QTable	635

7-632 Primary vtable for QLocalFs	636
7-633 typeinfo for QLocalFs.....	637
7-634 Primary vtable for QCanvasPolygon	637
7-635 typeinfo for QCanvasPolygon.....	639
7-636 Primary vtable for QDateEdit	639
7-637 Secondary vtable for QDateEdit	644
7-638 typeinfo for QDateEdit.....	644
7-639 Primary vtable for QPaintEvent.....	645
7-640 typeinfo for QPaintEvent.....	645
7-641 Primary vtable for QAccel	645
7-642 typeinfo for QAccel.....	646
7-643 Primary vtable for QCanvas.....	646
7-644 typeinfo for QCanvas	648
7-645 Primary vtable for QDomDocumentFragment.....	648
7-646 typeinfo for QDomDocumentFragment	650
7-647 Primary vtable for QDataStream	650
7-648 typeinfo for QDataStream.....	650
7-649 Primary vtable for QJpUnicodeConv	651
7-650 typeinfo for QJpUnicodeConv	651
7-651 Primary vtable for QPushButton	651
7-652 Secondary vtable for QPushButton	656
7-653 typeinfo for QPushButton.....	657
7-654 Primary vtable for QWidgetList	657
7-655 typeinfo for QWidgetList.....	657
7-656 Primary vtable for QMenuData	658
7-657 typeinfo for QMenuData.....	658
7-658 Primary vtable for QDataView	658
7-659 Secondary vtable for QDataView	663
7-660 typeinfo for QDataView.....	663
7-661 Primary vtable for QSqlEditorFactory	663
7-662 typeinfo for QSqlEditorFactory.....	664
7-663 Primary vtable for QConnectionList.....	665
7-664 typeinfo for QConnectionList	665
7-665 Primary vtable for QSqlCursor	665
7-666 Secondary vtable for QSqlCursor	667
7-667 typeinfo for QSqlCursor.....	668
7-668 Primary vtable for QAction.....	668
7-669 typeinfo for QAction	670
7-670 Primary vtable for QHostAddress.....	670
7-671 typeinfo for QHostAddress	670
7-672 Primary vtable for QWheelEvent	670
7-673 typeinfo for QWheelEvent.....	671
7-674 Primary vtable for QDataBrowser.....	671
7-675 Secondary vtable for QDataBrowser.....	676
7-676 typeinfo for QDataBrowser	677
7-677 Primary vtable for QTimeEdit.....	677
7-678 Secondary vtable for QTimeEdit	682
7-679 typeinfo for QTimeEdit	682
7-680 Primary vtable for QIconDragItem	682
7-681 typeinfo for QIconDragItem.....	683
7-682 Primary vtable for QSqlFieldInfo	683
7-683 typeinfo for QSqlFieldInfo.....	683
7-684 Primary vtable for QFtp	683
7-685 typeinfo for QFtp	685

7-686 Primary vtable for QLayoutItem	685
7-687 typeinfo for QLayoutItem.....	686
7-688 Primary vtable for QMoveEvent.....	686
7-689 typeinfo for QMoveEvent	686
7-690 Primary vtable for QTextEdit.....	687
7-691 Secondary vtable for QTextEdit.....	695
7-692 typeinfo for QTextEdit	696
7-693 Primary vtable for QFileIconProvider	696
7-694 typeinfo for QFileIconProvider.....	697
7-695 Primary vtable for QSqlIndex	698
7-696 typeinfo for QSqlIndex.....	699
7-697 Primary vtable for QSqlField.....	699
7-698 typeinfo for QSqlField	699
7-699 Primary vtable for QVGroupBox.....	699
7-700 Secondary vtable for QVGroupBox.....	704
7-701 typeinfo for QVGroupBox	705
7-702 Primary vtable for QCloseEvent.....	705
7-703 typeinfo for QCloseEvent	705
7-704 libqt-mt - Qt Function Interfaces.....	705

Foreword

This is version 3.1 of the LSB-Desktop Module Specification. This specification is part of a family of specifications under the general title "Linux Standard Base". Developers of applications or implementations interested in using the LSB trademark should see the Free Standards Group Certification Policy for details.

Introduction

The LSB-Desktop Module defines components that are required to be present on an LSB conforming system.

This document should be used in conjunction with the documents it references. Information referenced in this way is as much a part of this document as is the information explicitly included here.

I Introductory Elements

1 Scope

The LSB Desktop module defines components found on an LSB conforming system.

2 References

2.1 Normative References

The specifications listed below are referenced in whole or in part by the LSB-Desktop Module Standard. Such references may be normative or informative; a reference to specification shall only be considered normative if it is explicitly cited as such. The LSB-Desktop Module may make normative references to a portion of these specifications (that is, to define a specific function or group of functions); in such cases, only the explicitly referenced portion of the specification is to be considered normative.

Table 2-1 Normative References

Name	Title	URL
ATK 1.9.0 Reference Manual	ATK 1.9.0 Reference Manual	http://www.gtk.org/api/2.6/atk/index.html
Double Buffer Extension Library	Double Buffer Extension Library - Protocol Version 1.0	http://refspecs.freestdards.org/X11/dbelib.pdf
Fontconfig Developers Reference	Fontconfig Developers Reference, Version 2.3.0	http://fontconfig.org/fontconfig-devel/
Gdk 2.6.2 Reference Manual	Gdk 2.6.2 Reference Manual	http://www.gtk.org/api/2.6/gdk/index.html
Gdk-pixbuf 2.6.2 Reference Manual	Gdk-pixbuf 2.6.2 Reference Manual	http://www.gtk.org/api/2.6/gdk-pixbuf/index.html
Glib 2.6.2 Reference Manual	Glib 2.6.2 Reference Manual	http://www.gtk.org/api/2.6/glib/index.html
Gobject 2.6.2 Reference Manual	Gobject 2.6.2 Reference Manual	http://www.gtk.org/api/2.6/gobject/index.html
Gtk 2.6.2 Reference Manual	Gtk 2.6.2 Reference Manual	http://www.gtk.org/api/2.6/gtk/index.html
ISO C (1999)	ISO/IEC 9899: 1999, Programming Languages --C	
OpenGL	OpenGL Application Binary Interface for Linux	http://oss.sgi.com/projects/ogl-sample/ABI/
Pango 1.8.0 Reference Manual	Pango 1.8.0 Reference Manual	http://www.gtk.org/api/2.6/pango/index.html
Qt 3.3.6	Qt 3.3.6 Reference Manual	http://doc.trolltech.com/3.3/index.html
Reference Manual for	Reference Manual for	http://xmlsoft.org/ht

Name	Title	URL
libxml2	libxml2	ml/index.html
The MIT Shared Memory Extension	MIT-SHM - The MIT Shared Memory Extension - X version 11, Release 5	http://refspecs.freestdards.org/X11/mit-shm.pdf
X Display Power Management Signaling	X Display Power Management Signaling (DPMS) Extension - Library Specification - Version 1.0	http://refspecs.freestdards.org/X11/DPMSlib.pdf
X Extended Visual Interface Extension	Extended Visual Information Extension - Version 1.0	http://refspecs.freestdards.org/X11/evi.pdf
X Nonrectangular Window Shape Extension Library	X Nonrectangular Window Shape Extension Library - Version 1.0	http://refspecs.freestdards.org/X11/shapelib.pdf
X Record Extension Library	X Record Extension Library - Version 1.13	http://refspecs.freestdards.org/X11/recordlib.pdf
X Security Extension Specification	Security Extension Specification - Version 7.1	http://refspecs.freestdards.org/X11/security.pdf
X Synchronization Extension Library	X Synchronization Extension Library - Version 3.0	http://refspecs.freestdards.org/X11/synclib.pdf
X11 C Library	Xlib - C Language X Interface - X Version 11 Release 6.4	http://refspecs.freestdards.org/X11/xlib.pdf
X11 Input Library	X Input Device Extension Library - X Version 11, Release 6.4	http://refspecs.freestdards.org/X11/Xinput.pdf
X11 Inter-Client Exchange	Inter-Client Exchange Library - Version 1.0	http://refspecs.freestdards.org/X11/ICELib.pdf
X11 Session Management	X Session Management Library - Version 1.0	http://refspecs.freestdards.org/X11/SMlib.pdf
X11 Toolkit Intrinsic	X Toolkit Intrinsic - C Language Interface - X Version 11, Release 6.4	http://refspecs.freestdards.org/X11/intrinsics.pdf

2.2 Informative References/Bibliography

In addition, the specifications listed below provide essential background information to implementors of this specification. These references are included for information only.

Table 2-2 Other References

Name	Title	URL
A description on how to use and modify libpng	A description on how to use and modify libpng	http://www.libpng.org/pub/png/libpng-1.2.5-manual.html
Independent JPEG Group	Independent JPEG Group	http://www.iwg.org/

3 Requirements

3.1 Relevant Libraries

The libraries listed in Table 3-1 shall be available on a Linux Standard Base - Desktop system, with the specified runtime names. This list may be supplemented or amended by the architecture-specific specification.

Table 3-1 Standard Library Names

Library	Runtime Name
libX11	libX11.so.6
libXt	libXt.so.6
libGL	libGL.so.1
libXext	libXext.so.6
libICE	libICE.so.6
libSM	libSM.so.6
libXi	libXi.so.6
libfontconfig	libfontconfig.so.1
libpng12	libpng12.so.0
libjpeg	libjpeg.so.62
libglib-2.0	libglib-2.0.so.0
libgobject-2.0	libgobject-2.0.so.0
libgmodule-2.0	libgmodule-2.0.so.0
libgthread-2.0	libgthread-2.0.so.0
libatk-1.0	libatk-1.0.so.0
libpango-1.0	libpango-1.0.so.0
libpangoft2-1.0	libpangoft2-1.0.so.0
libpangoxft-1.0	libpangoxft-1.0.so.0
libgdk_pixbuf-2.0	libgdk_pixbuf-2.0.so.0
libgdk_pixbuf_xlib-2.0	libgdk_pixbuf_xlib-2.0.so.0
libgdk-x11-2.0	libgdk-x11-2.0.so.0
libgtk-x11-2.0	libgtk-x11-2.0.so.0
libqt-mt	libqt-mt.so.3
libxml2	libxml2.so.2

These libraries will be in an implementation-defined directory which the dynamic linker shall search by default.

4 Definitions

For the purposes of this document, the following definitions, as specified in the *ISO/IEC Directives, Part 2, 2001, 4th Edition*, apply:

can

be able to; there is a possibility of; it is possible to

cannot

be unable to; there is no possibility of; it is not possible to

may

is permitted; is allowed; is permissible

need not

it is not required that; no...is required

shall

is to; is required to; it is required that; has to; only...is permitted; it is necessary

shall not

is not allowed [permitted] [acceptable] [permissible]; is required to be not; is required that...be not; is not to be

should

it is recommended that; ought to

should not

it is not recommended that; ought not to

5 Terminology

For the purposes of this document, the following terms apply:

implementation-defined

Describes a value or behavior that is not defined by this document but is selected by an implementor. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence of the value or behavior. An application that relies on such a value or behavior cannot be assured to be portable across conforming implementations. The implementor shall document such a value or behavior so that it can be used correctly by an application.

Shell Script

A file that is read by an interpreter (e.g., awk). The first line of the shell script includes a reference to its interpreter binary.

undefined

Describes the nature of a value or behavior not defined by this document which results from use of an invalid program construct or invalid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

unspecified

Describes the nature of a value or behavior not specified by this document which results from use of a valid program construct or valid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

II GTK+ Stack Libraries

6 Libraries

6.1 Introduction

A conforming implementation shall support the following GTK+ stack libraries which provide interfaces for creating rich graphical user interface applications.

GLib

A general-purpose utility library, not specific to graphical user interfaces. GLib provides many useful data types, macros, type conversions, string utilities, file utilities, a main loop abstraction, and so on.

libglib-2.0

libgmodule-2.0

libgobject-2.0

libgthread-2.0

ATK

ATK is the Accessibility Toolkit. It provides a set of generic interfaces allowing accessibility technologies to interact with a graphical user interface. For example, a screen reader uses ATK to discover the text in an interface and read it to blind users. GTK+ widgets have built-in support for accessibility using the ATK framework.

libatk-1.0

Pango

Pango is a library for internationalized text handling. It centers around the PangoLayout object, representing a paragraph of text. Pango provides the engine for GtkTextView, GtkLabel, GtkEntry, and other widgets that display text.

libpango-1.0

libpangoxft-1.0

libpangoft2-1.0

GdkPixbuf

This is a small library which allows you to create GdkPixbuf ("pixel buffer") objects from image data or image files. Use a GdkPixbuf in combination with GtkImage to display images.

libgdk_pixbuf-2.0

libgdk_pixbuf_xlib-2.0

GDK

GDK is the abstraction layer that allows GTK+ to support multiple windowing systems. GDK provides drawing and window system facilities on X11, Windows, and the Linux framebuffer device.

libgdk-x11-2.0

GTK+

The GTK+ library contains widgets, that is, GUI components such as GtkButton or GtkTextView.

libgtk-x11-2.0

There are three main parts to the definition of each of these libraries.

The "Interfaces" section defines the required library name and version, and the required public symbols (interfaces and global data), as well as symbol versions, if any.

The "Interface Definitions" section provides complete or partial definitions of certain interfaces where either this specification is the source specification, or where there are variations from the source specification. If an interface definition requires one or more header files, one of those headers shall include the function prototype for the interface.

For source definitions of interfaces which include a reference to a header file, the contents of such header files form a part of the specification. The "Data Definitions" section provides the binary-level details for the header files from the source specifications, such as values for macros and enumerated types, as well as structure layouts, sizes and padding, etc. These data definitions, although presented in the form of header files for convenience, should not be taken as representing complete header files, as they are a supplement to the source specifications. Application developers should follow the guidelines of the source specifications when determining which header files need to be included to completely resolve all references.

Note: While the Data Definitions supplement the source specifications, this specification itself does not require conforming implementations to supply any header files.

6.2 Interfaces for libglib-2.0

Table 6-1 defines the library name and shared object name for the libglib-2.0 library

Table 6-1 libglib-2.0 Definition

Library:	libglib-2.0
SONAME:	libglib-2.0.so.0

6.2.1 GTK General purpose utility library

6.2.1.1 Interfaces for GTK General purpose utility library

No external functions are defined for libglib-2.0 - GTK General purpose utility library in this part of the specification. See also the generic specification, ISO/IEC 23360 Part 1.

6.3 Data Definitions for libglib-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libglib-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.3.1 glib-2.0/glib.h

[illegible]

6.3.2 glib-2.0/glib/gstdio.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.4 Interfaces for libgobject-2.0

Table 6-2 defines the library name and shared object name for the libgobject-2.0 library

Table 6-2 libgobject-2.0 Definition

Library:	libgobject-2.0
----------	----------------

SONAME:	libgobject-2.0.so.0
---------	---------------------

6.4.1 Glib Object System

6.4.1.1 Interfaces for Glib Object System

No external functions are defined for libgobject-2.0 - Glib Object System in this part of the specification. See also the generic specification, ISO/IEC 23360 Part 1.

6.5 Data Definitions for libgobject-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libgobject-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.5.1 glib-2.0/glib-object.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.5.2 glib-2.0/gobject/gvaluecollector.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.6 Interfaces for libgmodule-2.0

Table 6-3 defines the library name and shared object name for the libgmodule-2.0 library

Table 6-3 libgmodule-2.0 Definition

Library:	libgmodule-2.0
SONAME:	libgmodule-2.0.so.0

6.6.1 Glib-Dynamic loading of Modules

6.6.1.1 Interfaces for Glib-Dynamic loading of Modules

No external functions are defined for libgmodule-2.0 - Glib-Dynamic loading of Modules in this part of the specification. See also the generic specification, ISO/IEC 23360 Part 1.

6.7 Data Definitions for libgmodule-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libgmodule-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.7.1 glib-2.0/gmodule.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.8 Interfaces for libatk-1.0

Table 6-4 defines the library name and shared object name for the libatk-1.0 library

Table 6-4 libatk-1.0 Definition

Library:	libatk-1.0
SONAME:	libatk-1.0.so.0

6.8.1 GTK Accessibility Toolkit

6.8.1.1 Interfaces for GTK Accessibility Toolkit

No external functions are defined for libatk-1.0 - GTK Accessibility Toolkit in this part of the specification. See also the generic specification, ISO/IEC 23360 Part 1.

6.9 Data Definitions for libatk-1.0

This section defines global identifiers and their values that are associated with interfaces contained in libatk-1.0. These definitions are organized into groups

that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.9.1 atk-1.0/atk/atk-enum-types.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.9.2 atk-1.0/atk/atk.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.10 Interfaces for libpango-1.0

Table 6-5 defines the library name and shared object name for the libpango-1.0 library

Table 6-5 libpango-1.0 Definition

Library:	libpango-1.0
SONAME:	libpango-1.0.so.0

6.10.1 GTK Internationalized Text Layout and Rendering library

6.10.1.1 Interfaces for GTK Internationalized Text Layout and Rendering library

No external functions are defined for libpango-1.0 - GTK Internationalized Text Layout and Rendering library in this part of the specification. See also the generic specification, ISO/IEC 23360 Part 1.

6.11 Data Definitions for libpango-1.0

This section defines global identifiers and their values that are associated with interfaces contained in libpango-1.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system

header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.11.1 pango-1.0/pango/pango.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.12 Interfaces for libpangoxft-1.0

Table 6-6 defines the library name and shared object name for the libpangoxft-1.0 library

Table 6-6 libpangoxft-1.0 Definition

Library:	libpangoxft-1.0
SONAME:	libpangoxft-1.0.so.0

6.12.1 Pango Xft Fonts and Rendering library

6.12.1.1 Interfaces for Pango Xft Fonts and Rendering library

No external functions are defined for libpangoxft-1.0 - Pango Xft Fonts and Rendering library in this part of the specification. See also the generic specification, ISO/IEC 23360 Part 1.

6.13 Data Definitions for libpangoxft-1.0

This section defines global identifiers and their values that are associated with interfaces contained in libpangoxft-1.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language

description of these data objects does not preclude their use by other programming languages.

6.13.1 pango-1.0/pango/pangoxft.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.14 Interfaces for libpangoft2-1.0

Table 6-7 defines the library name and shared object name for the libpangoft2-1.0 library

Table 6-7 libpangoft2-1.0 Definition

Library:	libpangoft2-1.0
SONAME:	libpangoft2-1.0.so.0

6.14.1 Pango Freetype Fonts and Rendering library

6.14.1.1 Interfaces for Pango Freetype Fonts and Rendering library

No external functions are defined for libpangoft2-1.0 - Pango Freetype Fonts and Rendering library in this part of the specification. See also the generic specification, ISO/IEC 23360 Part 1.

6.15 Data Definitions for libpangoft2-1.0

This section defines global identifiers and their values that are associated with interfaces contained in libpangoft2-1.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.15.1 pango-1.0/pango/pangofc-decoder.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.15.2 pango-1.0/pango/pangofc-fontmap.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.15.3 pango-1.0/pango/pangoft2.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.16 Interfaces for libgdk_pixbuf-2.0

Table 6-8 defines the library name and shared object name for the libgdk_pixbuf-2.0 library

Table 6-8 libgdk_pixbuf-2.0 Definition

Library:	libgdk_pixbuf-2.0
SONAME:	libgdk_pixbuf-2.0.so.0

6.16.1 GDK pixbuf rendering on drawables library

6.16.1.1 Interfaces for GDK pixbuf rendering on drawables library

No external functions are defined for libgdk_pixbuf-2.0 - GDK pixbuf rendering on drawables library in this part of the specification. See also the generic specification, ISO/IEC 23360 Part 1.

6.17 Data Definitions for libgdk_pixbuf-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libgdk_pixbuf-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.17.1 gtk-2.0/gdk-pixbuf/gdk-pixbuf.h

```
/*
 * This header is architecture neutral
```

```

* Please refer to the generic specification for details
*/

```

6.17.2 gtk-2.0/gdk-pixbuf/gdk-pixdata.h

```

/*
* This header is architecture neutral
* Please refer to the generic specification for details
*/

```

6.18 Interfaces for libgdk_pixbuf_xlib-2.0

Table 6-9 defines the library name and shared object name for the libgdk_pixbuf_xlib-2.0 library

Table 6-9 libgdk_pixbuf_xlib-2.0 Definition

Library:	libgdk_pixbuf_xlib-2.0
SONAME:	libgdk_pixbuf_xlib-2.0.so.0

6.18.1 GDK pixbuf rendering to an X drawable library

6.18.1.1 Interfaces for GDK pixbuf rendering to an X drawable library

No external functions are defined for libgdk_pixbuf_xlib-2.0 - GDK pixbuf rendering to an X drawable library in this part of the specification. See also the generic specification, ISO/IEC 23360 Part 1.

6.19 Data Definitions for libgdk_pixbuf_xlib-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libgdk_pixbuf_xlib-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.19.1 gtk-2.0/gdk-pixbuf-xlib/gdk-pixbuf-xlib.h

```

/*
* This header is architecture neutral
* Please refer to the generic specification for details
*/

```


6.20 Interfaces for libgdk-x11-2.0

Table 6-10 defines the library name and shared object name for the libgdk-x11-2.0 library

Table 6-10 libgdk-x11-2.0 Definition

Library:	libgdk-x11-2.0
SONAME:	libgdk-x11-2.0.so.0

6.20.1 GTK Drawing toolkit

6.20.1.1 Interfaces for GTK Drawing toolkit

No external functions are defined for libgdk-x11-2.0 - GTK Drawing toolkit in this part of the specification. See also the generic specification, ISO/IEC 23360 Part 1.

6.21 Data Definitions for libgdk-x11-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libgdk-x11-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.21.1 gtk-2.0/gdk/gdk.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.21.2 gtk-2.0/gdk/gdkkeysyms.h

```
/*
 * This header is architecture neutral
 * Please refer to the generic specification for details
 */
```

6.21.3 gtk-2.0/gdk/gdkx.h

```
/*
 * This header is architecture neutral
```

```

* Please refer to the generic specification for details
*/

```

6.22 Interfaces for libgtk-x11-2.0

Table 6-11 defines the library name and shared object name for the libgtk-x11-2.0 library

Table 6-11 libgtk-x11-2.0 Definition

Library:	libgtk-x11-2.0
SONAME:	libgtk-x11-2.0.so.0

6.22.1 GTK main Widgets library

6.22.1.1 Interfaces for GTK main Widgets library

No external functions are defined for libgtk-x11-2.0 - GTK main Widgets library in this part of the specification. See also the generic specification, ISO/IEC 23360 Part 1.

6.23 Data Definitions for libgtk-x11-2.0

This section defines global identifiers and their values that are associated with interfaces contained in libgtk-x11-2.0. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

6.23.1 gtk-2.0/gtk/gtk.h

```

/*
* This header is architecture neutral
* Please refer to the generic specification for details
*/

```

III Qt3 Library

7 Library

7.1 Introduction

An conforming implementation shall support the following Qt library which provide interfaces for creating rich user applications, either graphical or console.

qt-mt

A general-purpose application development library. Provides a GUI-independent layer of tool classes, network support, SQL database support, XML handling and a GUI layer featuring a device-independent drawing API for printing, screen output and OpenGL support.

There are three main parts to the definition of each of this library.

The "Interfaces" section defines the required library name and version, and the required public symbols (interfaces and global data), as well as symbol versions, if any.

The "Interface Definitions" section provides complete or partial definitions of certain interfaces where either this specification is the source specification, or where there are variations from the source specification. If an interface definition requires one or more header files, one of those headers shall include the function prototype for the interface.

For source definitions of interfaces which include a reference to a header file, the contents of such header files form a part of the specification. The "Data Definitions" section provides the binary-level details for the header files from the source specifications, such as values for macros and enumerated types, as well as structure layouts, sizes and padding, etc. These data definitions, although presented in the form of header files for convenience, should not be taken a representing complete header files, as they are a supplement to the source specifications. Application developers should follow the guidelines of the source specifications when determining which header files need to be included to completely resolve all references.

Note: While the Data Definitions supplement the source specifications, this specification itself does not require conforming implementations to supply any header files.

7.2 Interfaces for libqt-mt

Table 7-1 defines the library name and shared object name for the libqt-mt library

Table 7-1 libqt-mt Definition

Library:	libqt-mt
SONAME:	libqt-mt.so.3

The behavior of the interfaces in this library is specified by the following specifications:

[qt-mt] Qt 3.3.6

7.2.1 Qt

7.2.1.1 Class data for QTextCodec

The virtual table for the QTextCodec class is described by Table 7-2

Table 7-2 Primary vtable for QTextCodec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextCodec
vfunc[0]:	QTextCodec::~~QTextCodec()
vfunc[1]:	QTextCodec::~~QTextCodec()
vfunc[2]:	QTextCodec::name() const
vfunc[3]:	QTextCodec::mimeTypeName() const
vfunc[4]:	QTextCodec::mibEnum() const
vfunc[5]:	QTextCodec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QTextCodec::toUnicode(char const*, int) const
vfunc[8]:	QTextCodec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QTextCodec::heuristicContentMatch(char const*, int) const
vfunc[12]:	QTextCodec::heuristicNameMatch(char const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode(QString const&, int) const

The Run Time Type Information for the QTextCodec class is described by Table 7-3

Table 7-3 typeinfo for QTextCodec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextCodec
basetype:	typeinfo for QTextCodec

7.2.1.2 Class data for QTimer

The virtual table for the QTimer class is described by Table 7-4

Table 7-4 Primary vtable for QTimer

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTimer
vfunc[0]:	QTimer::metaObject() const
vfunc[1]:	QTimer::className() const
vfunc[2]:	QTimer::qt_cast(char const*)
vfunc[3]:	QTimer::qt_invoke(int, QUObject*)
vfunc[4]:	QTimer::qt_emit(int, QUObject*)
vfunc[5]:	QTimer::qt_property(int, int, QVariant*)
vfunc[6]:	QTimer::~~QTimer()
vfunc[7]:	QTimer::~~QTimer()
vfunc[8]:	QTimer::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QTimer class is described by Table 7-5

Table 7-5 typeinfo for QTimer

Base Vtable	vtable for
-------------	------------

	__cxxabiv1::__si_class_type_info
Name	typeinfo name for QTimer
basetype:	typeinfo for QObject

7.2.1.3 Class data for QXmlEntityResolver

The virtual table for the QXmlEntityResolver class is described by Table 7-6

Table 7-6 Primary vtable for QXmlEntityResolver

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlEntityResolver
vfunc[0]:	__cxa_pure_virtual
vfunc[1]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlEntityResolver class is described by Table 7-7

Table 7-7 typeinfo for QXmlEntityResolver

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlEntityResolver

7.2.1.4 Class data for QObjectCleanupHandler

The virtual table for the QObjectCleanupHandler class is described by Table 7-8

Table 7-8 Primary vtable for QObjectCleanupHandler

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QObjectCleanupHandler
vfunc[0]:	QObjectCleanupHandler::metaObject () const
vfunc[1]:	QObjectCleanupHandler::className () const
vfunc[2]:	QObjectCleanupHandler::qt_cast(char const*)
vfunc[3]:	QObjectCleanupHandler::qt_invoke(int, QUObject*)
vfunc[4]:	QObjectCleanupHandler::qt_emit(int, QUObject*)
vfunc[5]:	QObjectCleanupHandler::qt_property(int, int, QVariant*)

vfunc[6]:	QObjectCleanupHandler::~~QObjectCleanupHandler()
vfunc[7]:	QObjectCleanupHandler::~~QObjectCleanupHandler()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QObjectCleanupHandler class is described by Table 7-9

Table 7-9 typeinfo for QObjectCleanupHandler

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QObjectCleanupHandler
basetype:	typeinfo for QObject

7.2.1.5 Class data for QPtrCollection

The virtual table for the QPtrCollection class is described by Table 7-10

Table 7-10 Primary vtable for QPtrCollection

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPtrCollection
vfunc[0]:	__cxa_pure_virtual

vfunc[1]:	__cxa_pure_virtual
vfunc[2]:	QPtrCollection::~~QPtrCollection()
vfunc[3]:	QPtrCollection::~~QPtrCollection()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	__cxa_pure_virtual

The Run Time Type Information for the QPtrCollection class is described by Table 7-11

Table 7-11 typeinfo for QPtrCollection

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QPtrCollection

7.2.1.6 Class data for QHBox

The virtual table for the QHBox class is described by Table 7-12

Table 7-12 Primary vtable for QHBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHBox
vfunc[0]:	QHBox::metaObject() const
vfunc[1]:	QHBox::className() const
vfunc[2]:	QHBox::qt_cast(char const*)
vfunc[3]:	QHBox::qt_invoke(int, QUObject*)
vfunc[4]:	QHBox::qt_emit(int, QUObject*)
vfunc[5]:	QHBox::qt_property(int, int, QVariant*)
vfunc[6]:	QHBox::~~QHBox()
vfunc[7]:	QHBox::~~QHBox()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const

vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)

vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QHBoxLayout::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)

vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QFrame::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()

vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QHBox::frameChanged()

Table 7-13 Secondary vtable for QHBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QHBox
vfunc[0]:	non-virtual thunk to QHBox::~~QHBox()
vfunc[1]:	non-virtual thunk to QHBox::~~QHBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const

vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QHBox class is described by Table 7-14

Table 7-14 typeinfo for QHBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHBox
basetype:	typeinfo for QFrame

7.2.1.7 Class data for QGVector

The virtual table for the QGVector class is described by Table 7-15

Table 7-15 Primary vtable for QGVector

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGVector
vfunc[0]:	QGVector::count() const
vfunc[1]:	QGVector::clear()
vfunc[2]:	QGVector::~~QGVector()
vfunc[3]:	QGVector::~~QGVector()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	QGVector::compareItems(void*, void*)
vfunc[7]:	QGVector::read(QDataStream&, void*&)
vfunc[8]:	QGVector::write(QDataStream&, void*) const

The Run Time Type Information for the QGVector class is described by Table 7-16

Table 7-16 typeinfo for QGVector

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGVector
basetype:	typeinfo for QPtrCollection

7.2.1.8 Class data for QToolBar

The virtual table for the QToolBar class is described by Table 7-17

Table 7-17 Primary vtable for QToolBar

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QToolBar
vfunc[0]:	QToolBar::metaObject() const
vfunc[1]:	QToolBar::className() const
vfunc[2]:	QToolBar::qt_cast(char const*)
vfunc[3]:	QToolBar::qt_invoke(int, QUObject*)
vfunc[4]:	QToolBar::qt_emit(int, QUObject*)
vfunc[5]:	QToolBar::qt_property(int, int, QVariant*)
vfunc[6]:	QToolBar::~QToolBar()
vfunc[7]:	QToolBar::~QToolBar()
vfunc[8]:	QToolBar::event(QEvent*)
vfunc[9]:	QDockWindow::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)

vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QToolBar::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QDockWindow::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)

vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QToolBar::show()
vfunc[48]:	QToolBar::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDockWindow::sizeHint() const
vfunc[59]:	QToolBar::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)

vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QToolBar::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QDockWindow::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QDockWindow::showEvent(QShowEvent*)
vfunc[94]:	QDockWindow::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QToolBar::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette)

	const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QDockWindow::drawFrame(QPainter*)
vfunc[116]:	QDockWindow::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QDockWindow::setWidget(QWidget*)
vfunc[119]:	QDockWindow::setCloseMode(int)
vfunc[120]:	QDockWindow::setResizeEnabled(bool)
vfunc[121]:	QDockWindow::setMovingEnabled(bool)
vfunc[122]:	QDockWindow::setHorizontallyStretchable(bool)
vfunc[123]:	QDockWindow::setVerticallyStretchable(bool)
vfunc[124]:	QDockWindow::setOffset(int)
vfunc[125]:	QDockWindow::setFixedExtentWidth(int)

vfunc[126]:	QDockWindow::setFixedExtentHeight(int)
vfunc[127]:	QDockWindow::setNewLine(bool)
vfunc[128]:	QDockWindow::setOpaqueMoving(bool)
vfunc[129]:	QDockWindow::undock(QWidget*)
vfunc[130]:	QDockWindow::undock()
vfunc[131]:	QDockWindow::dock()
vfunc[132]:	QToolBar::setOrientation(Qt::Orientation)
vfunc[133]:	QToolBar::setStretchableWidget(QWidget*)
vfunc[134]:	QToolBar::setLabel(QString const&)
vfunc[135]:	QToolBar::clear()

Table 7-18 Secondary vtable for QToolBar

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QToolBar
vfunc[0]:	non-virtual thunk to QToolBar::~QToolBar()
vfunc[1]:	non-virtual thunk to QToolBar::~QToolBar()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QToolBar class is described by Table 7-19

Table 7-19 typeinfo for QToolBar

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QToolBar
basetype:	typeinfo for QDockWindow

7.2.1.9 Class data for QDataSource

The virtual table for the QDataSource class is described by Table 7-20

Table 7-20 Primary vtable for QDataSource

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDataSource
vfunc[0]:	QDataSource::~~QDataSource()
vfunc[1]:	QDataSource::~~QDataSource()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	QDataSource::rewindable() const
vfunc[5]:	QDataSource::enableRewind(bool)
vfunc[6]:	QDataSource::rewind()

The Run Time Type Information for the QDataSource class is described by Table 7-21

Table 7-21 typeinfo for QDataSource

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDataSource
basetype:	typeinfo for QAsyncIO

7.2.1.10 Class data for QCanvasItem

The virtual table for the QCanvasItem class is described by Table 7-22

Table 7-22 Primary vtable for QCanvasItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvasItem
vfunc[0]:	QCanvasItem::~~QCanvasItem()
vfunc[1]:	QCanvasItem::~~QCanvasItem()
vfunc[2]:	QCanvasItem::moveBy(double,

	double)
vfunc[3]:	QCanvasItem::setAnimated(bool)
vfunc[4]:	QCanvasItem::setVelocity(double, double)
vfunc[5]:	QCanvasItem::advance(int)
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	QCanvasItem::setCanvas(QCanvas*)
vfunc[8]:	__cxa_pure_virtual
vfunc[9]:	QCanvasItem::setVisible(bool)
vfunc[10]:	QCanvasItem::setSelected(bool)
vfunc[11]:	QCanvasItem::setEnabled(bool)
vfunc[12]:	QCanvasItem::setActive(bool)
vfunc[13]:	QCanvasItem::rtti() const
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	QCanvasItem::boundingRectAdvanced() const
vfunc[16]:	QCanvasItem::chunks() const
vfunc[17]:	QCanvasItem::addToChunks()
vfunc[18]:	QCanvasItem::removeFromChunks()
vfunc[19]:	QCanvasItem::changeChunks()
vfunc[20]:	__cxa_pure_virtual

The Run Time Type Information for the QCanvasItem class is described by Table 7-23

Table 7-23 typeinfo for QCanvasItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasItem
basetype:	typeinfo for Qt

7.2.1.11 Class data for QWaitCondition

The virtual table for the QWaitCondition class is described by Table 7-24

Table 7-24 Primary vtable for QWaitCondition

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWaitCondition
vfunc[0]:	QWaitCondition::~~QWaitCondition()

vfunc[1]:	QWaitCondition::~~QWaitCondition()
-----------	------------------------------------

The Run Time Type Information for the QWaitCondition class is described by Table 7-25

Table 7-25 typeinfo for QWaitCondition

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QWaitCondition

7.2.1.12 Class data for QFrame

The virtual table for the QFrame class is described by Table 7-26

Table 7-26 Primary vtable for QFrame

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFrame
vfunc[0]:	QFrame::metaObject() const
vfunc[1]:	QFrame::className() const
vfunc[2]:	QFrame::qt_cast(char const*)
vfunc[3]:	QFrame::qt_invoke(int, QUObject*)
vfunc[4]:	QFrame::qt_emit(int, QUObject*)
vfunc[5]:	QFrame::qt_property(int, int, QVariant*)
vfunc[6]:	QFrame::~~QFrame()
vfunc[7]:	QFrame::~~QFrame()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)

vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::F

	ocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QFrame::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)

vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QFrame::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)

vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()

Table 7-27 Secondary vtable for QFrame

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QFrame
vfunc[0]:	non-virtual thunk to QFrame::~~QFrame()
vfunc[1]:	non-virtual thunk to QFrame::~~QFrame()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)

vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QFrame class is described by Table 7-28

Table 7-28 typeinfo for QFrame

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFrame
basetype:	typeinfo for QWidget

7.2.1.13 Class data for QScrollView

The virtual table for the QScrollView class is described by Table 7-29

Table 7-29 Primary vtable for QScrollView

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QScrollView
vfunc[0]:	QScrollView::metaObject() const
vfunc[1]:	QScrollView::className() const
vfunc[2]:	QScrollView::qt_cast(char const*)
vfunc[3]:	QScrollView::qt_invoke(int, QUObject*)
vfunc[4]:	QScrollView::qt_emit(int, QUObject*)
vfunc[5]:	QScrollView::qt_property(int, int, QVariant*)
vfunc[6]:	QScrollView::~~QScrollView()
vfunc[7]:	QScrollView::~~QScrollView()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QScrollView::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)

vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QScrollView::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)

vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QScrollView::sizeHint() const
vfunc[59]:	QScrollView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const

vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QScrollView::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)

vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QScrollView::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QScrollView::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*,

	int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QS crollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QS crollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWi dget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QScrollView::drawContents(QPainte r*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(Q Painter*, int, int, int, int, int)
vfunc[129]:	QScrollView::contentsMousePressEv ent(QMouseEvent*)
vfunc[130]:	QScrollView::contentsMouseRelease Event(QMouseEvent*)
vfunc[131]:	QScrollView::contentsMouseDouble ClickEvent(QMouseEvent*)
vfunc[132]:	QScrollView::contentsMouseMoveEv ent(QMouseEvent*)
vfunc[133]:	QScrollView::contentsDragEnterEve nt(QDragEnterEvent*)
vfunc[134]:	QScrollView::contentsDragMoveEve nt(QDragMoveEvent*)
vfunc[135]:	QScrollView::contentsDragLeaveEve nt(QDragLeaveEvent*)
vfunc[136]:	QScrollView::contentsDropEvent(QD ropEvent*)
vfunc[137]:	QScrollView::contentsWheelEvent(Q WheelEvent*)
vfunc[138]:	QScrollView::contentsContextMenuE vent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(Q PaintEvent*)
vfunc[140]:	QScrollView::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEv ent(QMouseEvent*)

vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)

Table 7-30 Secondary vtable for QScrollView

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QScrollView
vfunc[0]:	non-virtual thunk to QScrollView::~~QScrollView()
vfunc[1]:	non-virtual thunk to QScrollView::~~QScrollView()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*,

	QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QScrollView class is described by Table 7-31

Table 7-31 typeinfo for QScrollView

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QScrollView
basetype:	typeinfo for QFrame

7.2.1.14 Class data for QTextBrowser

The virtual table for the QTextBrowser class is described by Table 7-32

Table 7-32 Primary vtable for QTextBrowser

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextBrowser
vfunc[0]:	QTextBrowser::metaObject() const
vfunc[1]:	QTextBrowser::className() const
vfunc[2]:	QTextBrowser::qt_cast(char const*)
vfunc[3]:	QTextBrowser::qt_invoke(int, QObject*)
vfunc[4]:	QTextBrowser::qt_emit(int, QObject*)
vfunc[5]:	QTextBrowser::qt_property(int, int, QVariant*)
vfunc[6]:	QTextBrowser::~~QTextBrowser()
vfunc[7]:	QTextBrowser::~~QTextBrowser()
vfunc[8]:	QTextEdit::event(QEvent*)
vfunc[9]:	QTextEdit::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)

vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QTextEdit::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QTextEdit::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QTextEdit::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString

	const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QTextEdit::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QTextEdit::sizeHint() const
vfunc[59]:	QScrollView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QTextEdit::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)

vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QTextBrowser::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QTextEdit::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QTextEdit::imStartEvent(QIMEvent*)
vfunc[86]:	QTextEdit::imComposeEvent(QIMEvent*)
vfunc[87]:	QTextEdit::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)

vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QTextEdit::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QTextEdit::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QTextEdit::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*,

	int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QS crollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QS crollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWi dget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QTextEdit::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(Q Painter*, int, int, int, int, int, int)
vfunc[129]:	QTextEdit::contentsMousePressEvent (QMouseEvent*)
vfunc[130]:	QTextEdit::contentsMouseReleaseEv ent(QMouseEvent*)
vfunc[131]:	QTextEdit::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QTextEdit::contentsMouseMoveEven t(QMouseEvent*)
vfunc[133]:	QTextEdit::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QTextEdit::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QTextEdit::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QTextEdit::contentsDropEvent(QDro pEvent*)
vfunc[137]:	QTextEdit::contentsWheelEvent(QW heelEvent*)
vfunc[138]:	QTextEdit::contentsContextMenuEve nt(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(Q PaintEvent*)
vfunc[140]:	QTextEdit::viewportResizeEvent(QR esizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)

vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)
vfunc[154]:	QTextEdit::find(QString const&, bool, bool, bool, int*, int*)
vfunc[155]:	QTextEdit::getFormat(int, int, QFont*, QColor*, QTextEdit::VerticalAlignment*)
vfunc[156]:	QTextEdit::getParagraphFormat(int, QFont*, QColor*, QTextEdit::VerticalAlignment*, int*, QStyleSheetItem::DisplayMode*, QStyleSheetItem::ListStyle*, int*)
vfunc[157]:	QTextEdit::setMimeSourceFactory(QMimeSourceFactory*)
vfunc[158]:	QTextEdit::setStyleSheet(QStyleSheet*)
vfunc[159]:	QTextEdit::scrollToAnchor(QString const&)
vfunc[160]:	QTextEdit::setPaper(QBrush const&)
vfunc[161]:	QTextEdit::setLinkUnderline(bool)

vfunc[162]:	QTextEdit::setWordWrap(QTextEdit::WordWrap)
vfunc[163]:	QTextEdit::setWrapColumnOrWidth(int)
vfunc[164]:	QTextEdit::setWrapPolicy(QTextEdit::WrapPolicy)
vfunc[165]:	QTextEdit::copy()
vfunc[166]:	QTextEdit::append(QString const&)
vfunc[167]:	QTextBrowser::setText(QString const&, QString const&)
vfunc[168]:	QTextEdit::setTextFormat(Qt::TextFormat)
vfunc[169]:	QTextEdit::selectAll(bool)
vfunc[170]:	QTextEdit::setTabStopWidth(int)
vfunc[171]:	QTextEdit::zoomIn(int)
vfunc[172]:	QTextEdit::zoomIn()
vfunc[173]:	QTextEdit::zoomOut(int)
vfunc[174]:	QTextEdit::zoomOut()
vfunc[175]:	QTextEdit::zoomTo(int)
vfunc[176]:	QTextEdit::sync()
vfunc[177]:	QTextEdit::setReadOnly(bool)
vfunc[178]:	QTextEdit::undo()
vfunc[179]:	QTextEdit::redo()
vfunc[180]:	QTextEdit::cut()
vfunc[181]:	QTextEdit::paste()
vfunc[182]:	QTextEdit::pasteSubType(QCString const&)
vfunc[183]:	QTextEdit::clear()
vfunc[184]:	QTextEdit::del()
vfunc[185]:	QTextEdit::indent()
vfunc[186]:	QTextEdit::setItalic(bool)
vfunc[187]:	QTextEdit::setBold(bool)
vfunc[188]:	QTextEdit::setUnderline(bool)
vfunc[189]:	QTextEdit::setFamily(QString const&)
vfunc[190]:	QTextEdit::setPointSize(int)
vfunc[191]:	QTextEdit::setColor(QColor const&)

vfunc[192]:	QTextEdit::setVerticalAlignment(QTextEdit::VerticalAlignment)
vfunc[193]:	QTextEdit::setAlignment(int)
vfunc[194]:	QTextEdit::setParagType(QStyleSheetItem::DisplayMode, QStyleSheetItem::ListStyle)
vfunc[195]:	QTextEdit::setCursorPosition(int, int)
vfunc[196]:	QTextEdit::setSelection(int, int, int, int, int)
vfunc[197]:	QTextEdit::setSelectionAttributes(int, QColor const&, bool)
vfunc[198]:	QTextEdit::setModified(bool)
vfunc[199]:	QTextEdit::resetFormat()
vfunc[200]:	QTextEdit::setUndoDepth(int)
vfunc[201]:	QTextEdit::setFormat(QTextFormat*, int)
vfunc[202]:	QTextEdit::ensureCursorVisible()
vfunc[203]:	QTextEdit::placeCursor(QPoint const&, QTextCursor*)
vfunc[204]:	QTextEdit::moveCursor(QTextEdit::CursorAction, bool)
vfunc[205]:	QTextEdit::doKeyboardAction(QTextEdit::KeyboardAction)
vfunc[206]:	QTextEdit::removeSelectedText(int)
vfunc[207]:	QTextEdit::removeSelection(int)
vfunc[208]:	QTextEdit::setCurrentFont(QFont const&)
vfunc[209]:	QTextEdit::setOverwriteMode(bool)
vfunc[210]:	QTextEdit::scrollToBottom()
vfunc[211]:	QTextEdit::insert(QString const&, bool, bool, bool)
vfunc[212]:	QTextEdit::insertAt(QString const&, int, int)
vfunc[213]:	QTextEdit::removeParagraph(int)
vfunc[214]:	QTextEdit::insertParagraph(QString const&, int)
vfunc[215]:	QTextEdit::setParagraphBackgroundColor(int, QColor const&)
vfunc[216]:	QTextEdit::clearParagraphBackground(int)

vfunc[217]:	QTextEdit::setUndoRedoEnabled(bool)
vfunc[218]:	QTextEdit::createPopupMenu(QPoint const&)
vfunc[219]:	QTextEdit::createPopupMenu()
vfunc[220]:	QTextEdit::doChangeInterval()
vfunc[221]:	QTextBrowser::linksEnabled() const
vfunc[222]:	QTextBrowser::emitHighlighted(QString const&)
vfunc[223]:	QTextBrowser::emitLinkClicked(QString const&)
vfunc[224]:	QTextBrowser::setSource(QString const&)
vfunc[225]:	QTextBrowser::backward()
vfunc[226]:	QTextBrowser::forward()
vfunc[227]:	QTextBrowser::home()
vfunc[228]:	QTextBrowser::reload()

Table 7-33 Secondary vtable for QTextBrowser

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QTextBrowser
vfunc[0]:	non-virtual thunk to QTextBrowser::~~QTextBrowser()
vfunc[1]:	non-virtual thunk to QTextBrowser::~~QTextBrowser()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const

vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const
------------	---

The Run Time Type Information for the QTextBrowser class is described by Table 7-34

Table 7-34 typeinfo for QTextBrowser

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextBrowser
basetype:	typeinfo for QTextEdit

7.2.1.15 Class data for QCanvasSprite

The virtual table for the QCanvasSprite class is described by Table 7-35

Table 7-35 Primary vtable for QCanvasSprite

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvasSprite
vfunc[0]:	QCanvasSprite::~~QCanvasSprite()
vfunc[1]:	QCanvasSprite::~~QCanvasSprite()
vfunc[2]:	QCanvasItem::moveBy(double, double)
vfunc[3]:	QCanvasItem::setAnimated(bool)
vfunc[4]:	QCanvasItem::setVelocity(double, double)
vfunc[5]:	QCanvasSprite::advance(int)
vfunc[6]:	QCanvasSprite::collidesWith(QCanv asItem const*) const
vfunc[7]:	QCanvasItem::setCanvas(QCanvas*)
vfunc[8]:	QCanvasSprite::draw(QPainter&)
vfunc[9]:	QCanvasItem::setVisible(bool)
vfunc[10]:	QCanvasItem::setSelected(bool)
vfunc[11]:	QCanvasItem::setEnabled(bool)
vfunc[12]:	QCanvasItem::setActive(bool)
vfunc[13]:	QCanvasSprite::rtti() const
vfunc[14]:	QCanvasSprite::boundingRect() const
vfunc[15]:	QCanvasItem::boundingRectAdvanc ed() const

vfunc[16]:	QCanvasItem::chunks() const
vfunc[17]:	QCanvasSprite::addToChunks()
vfunc[18]:	QCanvasSprite::removeFromChunks()
vfunc[19]:	QCanvasSprite::changeChunks()
vfunc[20]:	QCanvasSprite::collidesWith(QCanvasSprite const*, QCanvasPolygonalItem const*, QCanvasRectangle const*, QCanvasEllipse const*, QCanvasText const*) const
vfunc[21]:	QCanvasSprite::move(double, double, int)
vfunc[22]:	QCanvasSprite::setFrameAnimation(QCanvasSprite::FrameAnimationType, int, int)
vfunc[23]:	QCanvasSprite::imageAdvanced() const

The Run Time Type Information for the QCanvasSprite class is described by Table 7-36

Table 7-36 typeinfo for QCanvasSprite

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasSprite
basetype:	typeinfo for QCanvasItem

7.2.1.16 Class data for QSplitter

The virtual table for the QSplitter class is described by Table 7-37

Table 7-37 Primary vtable for QSplitter

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSplitter
vfunc[0]:	QSplitter::metaObject() const
vfunc[1]:	QSplitter::className() const
vfunc[2]:	QSplitter::qt_cast(char const*)
vfunc[3]:	QSplitter::qt_invoke(int, QUObject*)
vfunc[4]:	QSplitter::qt_emit(int, QUObject*)
vfunc[5]:	QSplitter::qt_property(int, int, QVariant*)

vfunc[6]:	QSplitter::~~QSplitter()
vfunc[7]:	QSplitter::~~QSplitter()
vfunc[8]:	QSplitter::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QSplitter::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)

vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QSplitter::sizeHint() const
vfunc[59]:	QSplitter::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const

vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QSplitter::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)

vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QSplitter::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)

vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QSplitter::setOrientation(Qt::Orientat ion)
vfunc[119]:	QSplitter::setResizeMode(QWidget*, QSplitter::ResizeMode)
vfunc[120]:	QSplitter::setOpaqueResize(bool)
vfunc[121]:	QSplitter::drawSplitter(QPainter*, int, int, int, int)
vfunc[122]:	QSplitter::setRubberband(int)

Table 7-38 Secondary vtable for QSplitter

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QSplitter
vfunc[0]:	non-virtual thunk to QSplitter::~~QSplitter()
vfunc[1]:	non-virtual thunk to QSplitter::~~QSplitter()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPaintDeviceCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QSplitter class is described by Table 7-39

Table 7-39 typeinfo for QSplitter

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSplitter

basetype:	typeinfo for QFrame
-----------	---------------------

7.2.1.17 Class data for QLineEdit

The virtual table for the QLineEdit class is described by Table 7-40

Table 7-40 Primary vtable for QLineEdit

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLineEdit
vfunc[0]:	QLineEdit::metaObject() const
vfunc[1]:	QLineEdit::className() const
vfunc[2]:	QLineEdit::qt_cast(char const*)
vfunc[3]:	QLineEdit::qt_invoke(int, QUObject*)
vfunc[4]:	QLineEdit::qt_emit(int, QUObject*)
vfunc[5]:	QLineEdit::qt_property(int, int, QVariant*)
vfunc[6]:	QLineEdit::~~QLineEdit()
vfunc[7]:	QLineEdit::~~QLineEdit()
vfunc[8]:	QLineEdit::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)

vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QLineEdit::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QLineEdit::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()

vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QLineEdit::sizeHint() const
vfunc[59]:	QLineEdit::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QLineEdit::mousePressEvent(QMouseEvent*)
vfunc[70]:	QLineEdit::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QLineEdit::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QLineEdit::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QLineEdit::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QLineEdit::focusInEvent(QFocusEvent*)

vfunc[77]:	QLineEdit::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QLineEdit::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QLineEdit::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QLineEdit::imStartEvent(QIMEvent*)
vfunc[86]:	QLineEdit::imComposeEvent(QIMEvent*)
vfunc[87]:	QLineEdit::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QLineEdit::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QLineEdit::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QLineEdit::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QLineEdit::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QLineEdit::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)

vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QLineEdit::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QLineEdit::setText(QString const&)
vfunc[119]:	QLineEdit::selectAll()
vfunc[120]:	QLineEdit::deselect()
vfunc[121]:	QLineEdit::clearValidator()
vfunc[122]:	QLineEdit::insert(QString const&)
vfunc[123]:	QLineEdit::clear()
vfunc[124]:	QLineEdit::undo()
vfunc[125]:	QLineEdit::redo()
vfunc[126]:	QLineEdit::setMaxLength(int)
vfunc[127]:	QLineEdit::setFrame(bool)
vfunc[128]:	QLineEdit::setEchoMode(QLineEdit::EchoMode)
vfunc[129]:	QLineEdit::setReadOnly(bool)
vfunc[130]:	QLineEdit::setValidator(QValidator const*)
vfunc[131]:	QLineEdit::setSelection(int, int)
vfunc[132]:	QLineEdit::setCursorPosition(int)
vfunc[133]:	QLineEdit::setAlignment(int)
vfunc[134]:	QLineEdit::cut()
vfunc[135]:	QLineEdit::copy() const

vfunc[136]:	QLineEdit::paste()
vfunc[137]:	QLineEdit::setDragEnabled(bool)
vfunc[138]:	QLineEdit::createPopupMenu()

Table 7-41 Secondary vtable for QLineEdit

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QLineEdit
vfunc[0]:	non-virtual thunk to QLineEdit::~~QLineEdit()
vfunc[1]:	non-virtual thunk to QLineEdit::~~QLineEdit()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPaintDeviceCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QLineEdit class is described by Table 7-42

Table 7-42 typeinfo for QLineEdit

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QLineEdit
basetype:	typeinfo for QFrame

7.2.1.18 Class data for QVBox

The virtual table for the QVBox class is described by Table 7-43

Table 7-43 Primary vtable for QVBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QVBox
vfunc[0]:	QVBox::metaObject() const
vfunc[1]:	QVBox::className() const
vfunc[2]:	QVBox::qt_cast(char const*)
vfunc[3]:	QVBox::qt_invoke(int, QUObject*)
vfunc[4]:	QVBox::qt_emit(int, QUObject*)
vfunc[5]:	QVBox::qt_property(int, int, QVariant*)
vfunc[6]:	QVBox::~~QVBox()
vfunc[7]:	QVBox::~~QVBox()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)

vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)

vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QHBoxLayout::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)

vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QFrame::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)

vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QHBoxLayout::frameChanged()

Table 7-44 Secondary vtable for QVBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QVBox
vfunc[0]:	non-virtual thunk to QVBox::~~QVBox()
vfunc[1]:	non-virtual thunk to QVBox::~~QVBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QVBox class is described by Table 7-45

Table 7-45 typeinfo for QVBox

Base Vtable	vtable for
-------------	------------

	__cxxabiv1::__si_class_type_info
Name	typeinfo name for QVBox
basetype:	typeinfo for QHBox

7.2.1.19 Class data for QContextMenuEvent

The virtual table for the QContextMenuEvent class is described by Table 7-46

Table 7-46 Primary vtable for QContextMenuEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QContextMenuEvent
vfunc[0]:	QContextMenuEvent::~~QContextMenuEvent()
vfunc[1]:	QContextMenuEvent::~~QContextMenuEvent()

The Run Time Type Information for the QContextMenuEvent class is described by Table 7-47

Table 7-47 typeinfo for QContextMenuEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QContextMenuEvent
basetype:	typeinfo for QEvent

7.2.1.20 Class data for QProcess

The virtual table for the QProcess class is described by Table 7-48

Table 7-48 Primary vtable for QProcess

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QProcess
vfunc[0]:	QProcess::metaObject() const
vfunc[1]:	QProcess::className() const
vfunc[2]:	QProcess::qt_cast(char const*)
vfunc[3]:	QProcess::qt_invoke(int, QUObject*)
vfunc[4]:	QProcess::qt_emit(int, QUObject*)
vfunc[5]:	QProcess::qt_property(int, int, QVariant*)
vfunc[6]:	QProcess::~~QProcess()

vfunc[7]:	QProcess::~~QProcess()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QProcess::connectNotify(char const*)
vfunc[19]:	QProcess::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QProcess::setArguments(QStringList const&)
vfunc[22]:	QProcess::addArgument(QString const&)
vfunc[23]:	QProcess::setWorkingDirectory(QDir const&)
vfunc[24]:	QProcess::start(QStringList*)
vfunc[25]:	QProcess::launch(QString const&, QStringList*)
vfunc[26]:	QProcess::launch(QMemArray<char> const&, QStringList*)
vfunc[27]:	QProcess::readStdout()
vfunc[28]:	QProcess::readStderr()
vfunc[29]:	QProcess::readLineStdout()
vfunc[30]:	QProcess::readLineStderr()
vfunc[31]:	QProcess::writeToStdin(QMemArray<char> const&)
vfunc[32]:	QProcess::writeToStdin(QString const&)
vfunc[33]:	QProcess::closeStdin()

The Run Time Type Information for the QProcess class is described by Table 7-49

Table 7-49 typeinfo for QProcess

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QProcess
basetype:	typeinfo for QObject

7.2.1.21 Class data for QImageFormat

The virtual table for the QImageFormat class is described by Table 7-50

Table 7-50 Primary vtable for QImageFormat

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QImageFormat
vfunc[0]:	QImageFormat::~~QImageFormat()
vfunc[1]:	QImageFormat::~~QImageFormat()
vfunc[2]:	__cxa_pure_virtual

The Run Time Type Information for the QImageFormat class is described by Table 7-51

Table 7-51 typeinfo for QImageFormat

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QImageFormat

7.2.1.22 Class data for QTranslator

The virtual table for the QTranslator class is described by Table 7-52

Table 7-52 Primary vtable for QTranslator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTranslator
vfunc[0]:	QTranslator::metaObject() const
vfunc[1]:	QTranslator::className() const
vfunc[2]:	QTranslator::qt_cast(char const*)
vfunc[3]:	QTranslator::qt_invoke(int, QUObject*)
vfunc[4]:	QTranslator::qt_emit(int, QUObject*)
vfunc[5]:	QTranslator::qt_property(int, int,

	QVariant*)
vfunc[6]:	QTranslator::~~QTranslator()
vfunc[7]:	QTranslator::~~QTranslator()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QTranslator::findMessage(char const*, char const*, char const*) const

The Run Time Type Information for the QTranslator class is described by Table 7-53

Table 7-53 typeinfo for QTranslator

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTranslator
basetype:	typeinfo for QObject

7.2.1.23 Class data for QXmlLocator

The virtual table for the QXmlLocator class is described by Table 7-54

Table 7-54 Primary vtable for QXmlLocator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlLocator

vfunc[0]:	QXmlLocator::~~QXmlLocator()
vfunc[1]:	QXmlLocator::~~QXmlLocator()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlLocator class is described by Table 7-55

Table 7-55 typeinfo for QXmlLocator

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlLocator

7.2.1.24 Class data for QPopupMenu

The virtual table for the QPopupMenu class is described by Table 7-56

Table 7-56 Primary vtable for QPopupMenu

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPopupMenu
vfunc[0]:	QPopupMenu::metaObject() const
vfunc[1]:	QPopupMenu::className() const
vfunc[2]:	QPopupMenu::qt_cast(char const*)
vfunc[3]:	QPopupMenu::qt_invoke(int, QUObject*)
vfunc[4]:	QPopupMenu::qt_emit(int, QUObject*)
vfunc[5]:	QPopupMenu::qt_property(int, int, QVariant*)
vfunc[6]:	QPopupMenu::~~QPopupMenu()
vfunc[7]:	QPopupMenu::~~QPopupMenu()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const

vfunc[15]:	QPopupMenu::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QPopupMenu::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)

vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QPopupMenu::show()
vfunc[48]:	QPopupMenu::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QPopupMenu::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QPopupMenu::customWhatsThis() const
vfunc[69]:	QPopupMenu::mousePressEvent(Q

	MouseEvent*)
vfunc[70]:	QPopupMenu::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QPopupMenu::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QPopupMenu::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QPopupMenu::focusInEvent(QFocusEvent*)
vfunc[77]:	QPopupMenu::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QPopupMenu::leaveEvent(QEvent*)
vfunc[80]:	QPopupMenu::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QFrame::resizeEvent(QResizeEvent*)
vfunc[83]:	QPopupMenu::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)

vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QPopupMenu::styleChange(QStyle&)
vfunc[98]:	QPopupMenu::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QPopupMenu::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QPopupMenu::drawContents(QPainter*)
vfunc[117]:	QPopupMenu::frameChanged()
vfunc[118]:	QPopupMenu::updateItem(int)
vfunc[119]:	QPopupMenu::setCheckable(bool)
vfunc[120]:	QPopupMenu::setActiveItem(int)
vfunc[121]:	QPopupMenu::activateItemAt(int)

vfunc[122]:	QPopupMenu::menuContentsChanged()
vfunc[123]:	QPopupMenu::menuStateChanged()
vfunc[124]:	QPopupMenu::menuInsPopup(QPopupMenu*)
vfunc[125]:	QPopupMenu::menuDelPopup(QPopupMenu*)
vfunc[126]:	QPopupMenu::setFirstItemActive()

Table 7-57 Secondary vtable for QPopupMenu

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QPopupMenu
vfunc[0]:	non-virtual thunk to QPopupMenu::~~QPopupMenu()
vfunc[1]:	non-virtual thunk to QPopupMenu::~~QPopupMenu()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

Table 7-58 Secondary vtable for QPopupMenu

Base Offset	-240
Virtual Base Offset	0
RTTI	typeinfo for QPopupMenu
vfunc[0]:	non-virtual thunk to QPopupMenu::~~QPopupMenu()
vfunc[1]:	non-virtual thunk to

	QPopupMenu::~~QPopupMenu()
vfunc[2]:	non-virtual thunk to QPopupMenu::updateItem(int)
vfunc[3]:	QMenuData::setId(int, int)
vfunc[4]:	non-virtual thunk to QPopupMenu::activateItemAt(int)
vfunc[5]:	non-virtual thunk to QPopupMenu::menuContentsChanged()
vfunc[6]:	non-virtual thunk to QPopupMenu::menuStateChanged()
vfunc[7]:	non-virtual thunk to QPopupMenu::menuInsPopup(QPopupMenu*)
vfunc[8]:	non-virtual thunk to QPopupMenu::menuDelPopup(QPopupMenu*)

The Run Time Type Information for the QPopupMenu class is described by Table 7-59

Table 7-59 typeinfo for QPopupMenu

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	2
Name	typeinfo name for QPopupMenu	
flags:	0	
basetype:	typeinfo for QFrame	
basetype:	typeinfo for QMenuData	37890

7.2.1.25 Class data for QImageDrag

The virtual table for the QImageDrag class is described by Table 7-60

Table 7-60 Primary vtable for QImageDrag

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QImageDrag
vfunc[0]:	QImageDrag::metaObject() const
vfunc[1]:	QImageDrag::className() const
vfunc[2]:	QImageDrag::qt_cast(char const*)

vfunc[3]:	QImageDrag::qt_invoke(int, QUObject*)
vfunc[4]:	QImageDrag::qt_emit(int, QUObject*)
vfunc[5]:	QImageDrag::qt_property(int, int, QVariant*)
vfunc[6]:	QImageDrag::~~QImageDrag()
vfunc[7]:	QImageDrag::~~QImageDrag()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QDragObject::setPixmap(QPixmap)
vfunc[22]:	QDragObject::setPixmap(QPixmap, QPoint const&)
vfunc[23]:	QDragObject::drag(QDragObject::DragMode)
vfunc[24]:	QImageDrag::setImage(QImage)
vfunc[25]:	QImageDrag::format(int) const
vfunc[26]:	QImageDrag::encodedData(char const*) const

Table 7-61 Secondary vtable for QImageDrag

Base Offset	-80
Virtual Base Offset	0

RTTI	typeinfo for QImageDrag
vfunc[0]:	non-virtual thunk to QImageDrag::~~QImageDrag()
vfunc[1]:	non-virtual thunk to QImageDrag::~~QImageDrag()
vfunc[2]:	non-virtual thunk to QImageDrag::format(int) const
vfunc[3]:	QMimeSource::provides(char const*) const
vfunc[4]:	non-virtual thunk to QImageDrag::encodedData(char const*) const

The Run Time Type Information for the QImageDrag class is described by Table 7-62

Table 7-62 typeinfo for QImageDrag

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QImageDrag
basetype:	typeinfo for QDragObject

7.2.1.26 Class data for QMimeSourceFactory

The virtual table for the QMimeSourceFactory class is described by Table 7-63

Table 7-63 Primary vtable for QMimeSourceFactory

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMimeSourceFactory
vfunc[0]:	QMimeSourceFactory::~~QMimeSourceFactory()
vfunc[1]:	QMimeSourceFactory::~~QMimeSourceFactory()
vfunc[2]:	QMimeSourceFactory::data(QString const&) const
vfunc[3]:	QMimeSourceFactory::makeAbsolute(QString const&, QString const&) const
vfunc[4]:	QMimeSourceFactory::setText(QString const&, QString const&)
vfunc[5]:	QMimeSourceFactory::setImage(QString const&, QImage const&)
vfunc[6]:	QMimeSourceFactory::setPixmap(QS

	tring const&, QPixmap const&)
vfunc[7]:	QMimeSourceFactory::setData(QString const&, QMimeSource*)
vfunc[8]:	QMimeSourceFactory::setFilePath(QStringList const&)
vfunc[9]:	QMimeSourceFactory::filePath() const
vfunc[10]:	QMimeSourceFactory::setExtensionType(QString const&, char const*)

The Run Time Type Information for the QMimeSourceFactory class is described by Table 7-64

Table 7-64 typeinfo for QMimeSourceFactory

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QMimeSourceFactory

7.2.1.27 Class data for QListBoxText

The virtual table for the QListBoxText class is described by Table 7-65

Table 7-65 Primary vtable for QListBoxText

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QListBoxText
vfunc[0]:	QListBoxText::~~QListBoxText()
vfunc[1]:	QListBoxText::~~QListBoxText()
vfunc[2]:	QListBoxItem::text() const
vfunc[3]:	QListBoxItem::pixmap() const
vfunc[4]:	QListBoxText::height(QListBox const*) const
vfunc[5]:	QListBoxText::width(QListBox const*) const
vfunc[6]:	QListBoxText::rtti() const
vfunc[7]:	QListBoxText::paint(QPainter*)
vfunc[8]:	QListBoxItem::setText(QString const&)

The Run Time Type Information for the QListBoxText class is described by Table 7-66

Table 7-66 typeinfo for QListBoxText

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QListBoxText
basetype:	typeinfo for QListBoxItem

7.2.1.28 Class data for QGroupBox

The virtual table for the QGroupBox class is described by Table 7-67

Table 7-67 Primary vtable for QGroupBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGroupBox
vfunc[0]:	QGroupBox::metaObject() const
vfunc[1]:	QGroupBox::className() const
vfunc[2]:	QGroupBox::qt_cast(char const*)
vfunc[3]:	QGroupBox::qt_invoke(int, QUObject*)
vfunc[4]:	QGroupBox::qt_emit(int, QUObject*)
vfunc[5]:	QGroupBox::qt_property(int, int, QVariant*)
vfunc[6]:	QGroupBox::~~QGroupBox()
vfunc[7]:	QGroupBox::~~QGroupBox()
vfunc[8]:	QGroupBox::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QGroupBox::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char

	const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QGroupBox::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)

vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QGroupBox::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent)

	*)
vfunc[75]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[76]:	QGroupBox::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QGroupBox::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QGroupBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QGroupBox::fontChange(QFont)

	const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QGroupBox::setColumnLayout(int, Qt::Orientation)
vfunc[119]:	QGroupBox::setTitle(QString const&)
vfunc[120]:	QGroupBox::setAlignment(int)

Table 7-68 Secondary vtable for QGroupBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QGroupBox
vfunc[0]:	non-virtual thunk to QGroupBox::~~QGroupBox()
vfunc[1]:	non-virtual thunk to QGroupBox::~~QGroupBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const

vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QGroupBox class is described by Table 7-69

Table 7-69 typeinfo for QGroupBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGroupBox
basetype:	typeinfo for QFrame

7.2.1.29 Class data for QMenuBar

The virtual table for the QMenuBar class is described by Table 7-70

Table 7-70 Primary vtable for QMenuBar

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMenuBar
vfunc[0]:	QMenuBar::metaObject() const
vfunc[1]:	QMenuBar::className() const
vfunc[2]:	QMenuBar::qt_cast(char const*)
vfunc[3]:	QMenuBar::qt_invoke(int, QUObject*)
vfunc[4]:	QMenuBar::qt_emit(int, QUObject*)
vfunc[5]:	QMenuBar::qt_property(int, int, QVariant*)
vfunc[6]:	QMenuBar::~~QMenuBar()
vfunc[7]:	QMenuBar::~~QMenuBar()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QMenuBar::eventFilter(QObject*,

	QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)

vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QMenuBar::show()
vfunc[48]:	QMenuBar::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QMenuBar::sizeHint() const
vfunc[59]:	QMenuBar::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QMenuBar::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)

vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QMenuBar::customWhatsThis() const
vfunc[69]:	QMenuBar::mousePressEvent(QMouseEvent*)
vfunc[70]:	QMenuBar::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QMenuBar::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QMenuBar::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QMenuBar::focusInEvent(QFocusEvent*)
vfunc[77]:	QMenuBar::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QMenuBar::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QMenuBar::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)

	veEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QMenuBar::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QMenuBar::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QMenuBar::drawContents(QPainter*)
vfunc[117]:	QMenuBar::frameChanged()
vfunc[118]:	QMenuBar::updateItem(int)

vfunc[119]:	QMenuBar::setSeparator(QMenuBar::Separator)
vfunc[120]:	QMenuBar::activateItemAt(int)
vfunc[121]:	QMenuBar::menuContentsChanged()
vfunc[122]:	QMenuBar::menuStateChanged()
vfunc[123]:	QMenuBar::menuInsPopup(QPopup Menu*)
vfunc[124]:	QMenuBar::menuDelPopup(QPopup Menu*)

Table 7-71 Secondary vtable for QMenuBar

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QMenuBar
vfunc[0]:	non-virtual thunk to QMenuBar::~~QMenuBar()
vfunc[1]:	non-virtual thunk to QMenuBar::~~QMenuBar()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

Table 7-72 Secondary vtable for QMenuBar

Base Offset	-240
Virtual Base Offset	0
RTTI	typeinfo for QMenuBar
vfunc[0]:	non-virtual thunk to QMenuBar::~~QMenuBar()

vfunc[1]:	non-virtual thunk to QMenuBar::~~QMenuBar()
vfunc[2]:	non-virtual thunk to QMenuBar::updateItem(int)
vfunc[3]:	QMenuData::setId(int, int)
vfunc[4]:	non-virtual thunk to QMenuBar::activateItemAt(int)
vfunc[5]:	non-virtual thunk to QMenuBar::menuContentsChanged()
vfunc[6]:	non-virtual thunk to QMenuBar::menuStateChanged()
vfunc[7]:	non-virtual thunk to QMenuBar::menuInsPopup(QPopup Menu*)
vfunc[8]:	non-virtual thunk to QMenuBar::menuDelPopup(QPopup Menu*)

The Run Time Type Information for the QMenuBar class is described by Table 7-73

Table 7-73 typeinfo for QMenuBar

Base Vtable	vtable for __cxxabiv1::__vmi_class _type_info	2
Name	typeinfo name for QMenuBar	
flags:	0	
basetype:	typeinfo for QFrame	
basetype:	typeinfo for QMenuData	37890

7.2.1.30 Class data for QProgressDialog

The virtual table for the QProgressDialog class is described by Table 7-74

Table 7-74 Primary vtable for QProgressDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QProgressDialog
vfunc[0]:	QProgressDialog::metaObject() const
vfunc[1]:	QProgressDialog::className() const
vfunc[2]:	QProgressDialog::qt_cast(char const*)

vfunc[3]:	QProgressDialog::qt_invoke(int, QUObject*)
vfunc[4]:	QProgressDialog::qt_emit(int, QUObject*)
vfunc[5]:	QProgressDialog::qt_property(int, int, QVariant*)
vfunc[6]:	QProgressDialog::~~QProgressDialog()
vfunc[7]:	QProgressDialog::~~QProgressDialog()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)

vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)

vfunc[58]:	QProgressDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QProgressDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QProgressDialog::closeEvent(QCloseEvent*)

vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QProgressDialog::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QProgressDialog::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDialog::done(int)

vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 7-75 Secondary vtable for QProgressDialog

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QProgressDialog
vfunc[0]:	non-virtual thunk to QProgressDialog::~~QProgressDialog()
vfunc[1]:	non-virtual thunk to QProgressDialog::~~QProgressDialog()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPaintDevice::CmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QProgressDialog class is described by Table 7-76

Table 7-76 typeinfo for QProgressDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QProgressDialog
basetype:	typeinfo for QDialog

7.2.1.31 Class data for QDateTimeEdit

The virtual table for the QDateTimeEdit class is described by Table 7-77

Table 7-77 Primary vtable for QDateTimeEdit

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDateTimeEdit
vfunc[0]:	QDateTimeEdit::metaObject() const
vfunc[1]:	QDateTimeEdit::className() const
vfunc[2]:	QDateTimeEdit::qt_cast(char const*)
vfunc[3]:	QDateTimeEdit::qt_invoke(int, QUObject*)
vfunc[4]:	QDateTimeEdit::qt_emit(int, QUObject*)
vfunc[5]:	QDateTimeEdit::qt_property(int, int, QVariant*)
vfunc[6]:	QDateTimeEdit::~~QDateTimeEdit()
vfunc[7]:	QDateTimeEdit::~~QDateTimeEdit()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)

vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPi xmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::F ocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()

vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDateTimeEdit::sizeHint() const
vfunc[59]:	QDateTimeEdit::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)

	nt*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDateTimeEdit::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)

vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDateTimeEdit::setDateTime(QDateTime const&)
vfunc[111]:	QDateTimeEdit::setAutoAdvance(bool)

Table 7-78 Secondary vtable for QDateTimeEdit

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDateTimeEdit
vfunc[0]:	non-virtual thunk to QDateTimeEdit::~~QDateTimeEdit()
vfunc[1]:	non-virtual thunk to QDateTimeEdit::~~QDateTimeEdit()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QDateTimeEdit class is described by Table 7-79

Table 7-79 typeinfo for QDateTimeEdit

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
-------------	--

Name	typeinfo name for QDateTimeEdit
basetype:	typeinfo for QWidget

7.2.1.32 Class data for QSqlResult

The virtual table for the QSqlResult class is described by Table 7-80

Table 7-80 Primary vtable for QSqlResult

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlResult
vfunc[0]:	QSqlResult::~~QSqlResult()
vfunc[1]:	QSqlResult::~~QSqlResult()
vfunc[2]:	QSqlResult::setAt(int)
vfunc[3]:	QSqlResult::setActive(bool)
vfunc[4]:	QSqlResult::setLastError(QSqlError const&)
vfunc[5]:	QSqlResult::setQuery(QString const&)
vfunc[6]:	QSqlResult::setSelect(bool)
vfunc[7]:	QSqlResult::setForwardOnly(bool)
vfunc[8]:	__cxa_pure_virtual
vfunc[9]:	__cxa_pure_virtual
vfunc[10]:	__cxa_pure_virtual
vfunc[11]:	__cxa_pure_virtual
vfunc[12]:	QSqlResult::fetchNext()
vfunc[13]:	QSqlResult::fetchPrev()
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	__cxa_pure_virtual
vfunc[16]:	__cxa_pure_virtual
vfunc[17]:	__cxa_pure_virtual

The Run Time Type Information for the QSqlResult class is described by Table 7-81

Table 7-81 typeinfo for QSqlResult

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QSqlResult

7.2.1.33 Class data for QRegExpValidator

The virtual table for the QRegExpValidator class is described by Table 7-82

Table 7-82 Primary vtable for QRegExpValidator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QRegExpValidator
vfunc[0]:	QRegExpValidator::metaObject() const
vfunc[1]:	QRegExpValidator::className() const
vfunc[2]:	QRegExpValidator::qt_cast(char const*)
vfunc[3]:	QRegExpValidator::qt_invoke(int, QObject*)
vfunc[4]:	QRegExpValidator::qt_emit(int, QObject*)
vfunc[5]:	QRegExpValidator::qt_property(int, int, QVariant*)
vfunc[6]:	QRegExpValidator::~QRegExpValida tor()
vfunc[7]:	QRegExpValidator::~QRegExpValida tor()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char

	const*, QObject const*, char const*)
vfunc[21]:	QRegExpValidator::validate(QString &, int&) const
vfunc[22]:	QValidator::fixup(QString&) const

The Run Time Type Information for the QRegExpValidator class is described by Table 7-83

Table 7-83 typeinfo for QRegExpValidator

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QRegExpValidator
basetype:	typeinfo for QValidator

7.2.1.34 Class data for QDockAreaLayout

The virtual table for the QDockAreaLayout class is described by Table 7-84

Table 7-84 Primary vtable for QDockAreaLayout

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDockAreaLayout
vfunc[0]:	QDockAreaLayout::metaObject() const
vfunc[1]:	QDockAreaLayout::className() const
vfunc[2]:	QDockAreaLayout::qt_cast(char const*)
vfunc[3]:	QDockAreaLayout::qt_invoke(int, QObject*)
vfunc[4]:	QDockAreaLayout::qt_emit(int, QObject*)
vfunc[5]:	QDockAreaLayout::qt_property(int, int, QVariant*)
vfunc[6]:	QDockAreaLayout::~~QDockAreaLayout() out()
vfunc[7]:	QDockAreaLayout::~~QDockAreaLayout() out()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QLayout::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)

vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QLayout::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QLayout::setMargin(int)
vfunc[22]:	QLayout::setSpacing(int)
vfunc[23]:	QLayout::setMenuBar(QMenuBar*)
vfunc[24]:	QLayout::setAutoAdd(bool)
vfunc[25]:	QDockAreaLayout::invalidate()
vfunc[26]:	QLayout::geometry() const
vfunc[27]:	QDockAreaLayout::addItem(QLayoutItem*)
vfunc[28]:	QDockAreaLayout::expanding() const
vfunc[29]:	QDockAreaLayout::minimumSize() const
vfunc[30]:	QLayout::maximumSize() const
vfunc[31]:	QDockAreaLayout::setGeometry(QRect const&)
vfunc[32]:	QDockAreaLayout::iterator()
vfunc[33]:	QLayout::isEmpty() const
vfunc[34]:	QLayout::layout()
vfunc[35]:	QDockAreaLayout::hasHeightForWidth() const
vfunc[36]:	QDockAreaLayout::heightForWidth(int) const
vfunc[37]:	QDockAreaLayout::sizeHint() const

Table 7-85 Secondary vtable for QDockAreaLayout

Base Offset	-80
-------------	-----

Virtual Base Offset	0
RTTI	typeinfo for QDockAreaLayout
vfunc[0]:	non-virtual thunk to QDockAreaLayout::~~QDockAreaLayout()
vfunc[1]:	non-virtual thunk to QDockAreaLayout::~~QDockAreaLayout()
vfunc[2]:	non-virtual thunk to QDockAreaLayout::sizeHint() const
vfunc[3]:	non-virtual thunk to QDockAreaLayout::minimumSize() const
vfunc[4]:	non-virtual thunk to QLayout::maximumSize() const
vfunc[5]:	non-virtual thunk to QDockAreaLayout::expanding() const
vfunc[6]:	non-virtual thunk to QDockAreaLayout::setGeometry(QRect const&)
vfunc[7]:	non-virtual thunk to QLayout::geometry() const
vfunc[8]:	non-virtual thunk to QLayout::isEmpty() const
vfunc[9]:	non-virtual thunk to QDockAreaLayout::hasHeightForWidth() const
vfunc[10]:	non-virtual thunk to QDockAreaLayout::heightForWidth(int) const
vfunc[11]:	non-virtual thunk to QDockAreaLayout::invalidate()
vfunc[12]:	QLayoutItem::widget()
vfunc[13]:	non-virtual thunk to QDockAreaLayout::iterator()
vfunc[14]:	non-virtual thunk to QLayout::layout()
vfunc[15]:	QLayoutItem::spacerItem()
vfunc[16]:	QLayoutItem::setAlignment(int)

The Run Time Type Information for the QDockAreaLayout class is described by Table 7-86

Table 7-86 typeinfo for QDockAreaLayout

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDockAreaLayout
basetype:	typeinfo for QLayout

7.2.1.35 Class data for QDragLeaveEvent

The virtual table for the QDragLeaveEvent class is described by Table 7-87

Table 7-87 Primary vtable for QDragLeaveEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDragLeaveEvent
vfunc[0]:	QDragLeaveEvent::~~QDragLeaveEvent()
vfunc[1]:	QDragLeaveEvent::~~QDragLeaveEvent()

The Run Time Type Information for the QDragLeaveEvent class is described by Table 7-88

Table 7-88 typeinfo for QDragLeaveEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDragLeaveEvent
basetype:	typeinfo for QEvent

7.2.1.36 Class data for QLCDNumber

The virtual table for the QLCDNumber class is described by Table 7-89

Table 7-89 Primary vtable for QLCDNumber

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLCDNumber
vfunc[0]:	QLCDNumber::metaObject() const
vfunc[1]:	QLCDNumber::className() const
vfunc[2]:	QLCDNumber::qt_cast(char const*)
vfunc[3]:	QLCDNumber::qt_invoke(int, QUObject*)
vfunc[4]:	QLCDNumber::qt_emit(int, QUObject*)

vfunc[5]:	QLCDNumber::qt_property(int, int, QVariant*)
vfunc[6]:	QLCDNumber::~~QLCDNumber()
vfunc[7]:	QLCDNumber::~~QLCDNumber()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)

vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QLCDNumber::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const

vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QFrame::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)

vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)

vfunc[116]:	QLCDNumber::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QLCDNumber::setNumDigits(int)
vfunc[119]:	QLCDNumber::setMode(QLCDNumber::Mode)
vfunc[120]:	QLCDNumber::setSegmentStyle(QLCDNumber::SegmentStyle)
vfunc[121]:	QLCDNumber::setHexMode()
vfunc[122]:	QLCDNumber::setDecMode()
vfunc[123]:	QLCDNumber::setOctMode()
vfunc[124]:	QLCDNumber::setBinMode()
vfunc[125]:	QLCDNumber::setSmallDecimalPoint(bool)

Table 7-90 Secondary vtable for QLCDNumber

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QLCDNumber
vfunc[0]:	non-virtual thunk to QLCDNumber::~~QLCDNumber()
vfunc[1]:	non-virtual thunk to QLCDNumber::~~QLCDNumber()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QLCDNumber class is described by Table 7-91

Table 7-91 typeinfo for QLCDNumber

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QLCDNumber
basetype:	typeinfo for QFrame

7.2.1.37 Class data for QUrlOperator

The virtual table for the QUrlOperator class is described by Table 7-92

Table 7-92 Primary vtable for QUrlOperator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QUrlOperator
vfunc[0]:	QUrlOperator::metaObject() const
vfunc[1]:	QUrlOperator::className() const
vfunc[2]:	QUrlOperator::qt_cast(char const*)
vfunc[3]:	QUrlOperator::qt_invoke(int, QUObject*)
vfunc[4]:	QUrlOperator::qt_emit(int, QUObject*)
vfunc[5]:	QUrlOperator::qt_property(int, int, QVariant*)
vfunc[6]:	QUrlOperator::~~QUrlOperator()
vfunc[7]:	QUrlOperator::~~QUrlOperator()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char

	const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QUrlOperator::setPath(QString const&)
vfunc[22]:	QUrlOperator::cdUp()
vfunc[23]:	QUrlOperator::listChildren()
vfunc[24]:	QUrlOperator::mkdir(QString const&)
vfunc[25]:	QUrlOperator::remove(QString const&)
vfunc[26]:	QUrlOperator::rename(QString const&, QString const&)
vfunc[27]:	QUrlOperator::get(QString const&)
vfunc[28]:	QUrlOperator::put(QMemArray<char> const&, QString const&)
vfunc[29]:	QUrlOperator::copy(QString const&, QString const&, bool, bool)
vfunc[30]:	QUrlOperator::copy(QStringList const&, QString const&, bool)
vfunc[31]:	QUrlOperator::isDir(bool*)
vfunc[32]:	QUrlOperator::setNameFilter(QString const&)
vfunc[33]:	QUrlOperator::info(QString const&) const
vfunc[34]:	QUrlOperator::stop()
vfunc[35]:	QUrlOperator::reset()
vfunc[36]:	QUrlOperator::parse(QString const&)
vfunc[37]:	QUrlOperator::checkValid()
vfunc[38]:	QUrlOperator::clearEntries()

Table 7-93 Secondary vtable for QUrlOperator

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QUrlOperator
vfunc[0]:	non-virtual thunk to QUrlOperator::~~QUrlOperator()
vfunc[1]:	non-virtual thunk to QUrlOperator::~~QUrlOperator()

vfunc[2]:	QUrl::setProtocol(QString const&)
vfunc[3]:	QUrl::setUser(QString const&)
vfunc[4]:	QUrl::setPassword(QString const&)
vfunc[5]:	QUrl::setHost(QString const&)
vfunc[6]:	QUrl::setPort(int)
vfunc[7]:	non-virtual thunk to QUrlOperator::setPath(QString const&)
vfunc[8]:	QUrl::setEncodedPathAndQuery(QSt ring const&)
vfunc[9]:	QUrl::setQuery(QString const&)
vfunc[10]:	QUrl::setRef(QString const&)
vfunc[11]:	QUrl::addPath(QString const&)
vfunc[12]:	QUrl::setFileName(QString const&)
vfunc[13]:	QUrl::toString(bool, bool) const
vfunc[14]:	non-virtual thunk to QUrlOperator::cdUp()
vfunc[15]:	non-virtual thunk to QUrlOperator::reset()
vfunc[16]:	non-virtual thunk to QUrlOperator::parse(QString const&)

The Run Time Type Information for the QUrlOperator class is described by Table 7-94

Table 7-94 typeinfo for QUrlOperator

Base Vtable	vtable for __cxxabiv1::__vmi_class _type_info	2 10242
Name	typeinfo name for QUrlOperator	
flags:	0	
basetype:	typeinfo for QObject	
basetype:	typeinfo for QUrl	

7.2.1.38 Class data for QSocket

The virtual table for the QSocket class is described by Table 7-95

Table 7-95 Primary vtable for QSocket

Base Offset	0
Virtual Base Offset	0

RTTI	typeid for QSocket
vfunc[0]:	QSocket::metaObject() const
vfunc[1]:	QSocket::className() const
vfunc[2]:	QSocket::qt_cast(char const*)
vfunc[3]:	QSocket::qt_invoke(int, QUObject*)
vfunc[4]:	QSocket::qt_emit(int, QUObject*)
vfunc[5]:	QSocket::qt_property(int, int, QVariant*)
vfunc[6]:	QSocket::~~QSocket()
vfunc[7]:	QSocket::~~QSocket()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QSocket::setSocket(int)
vfunc[22]:	QSocket::setSocketDevice(QSocketDevice*)
vfunc[23]:	QSocket::connectToHost(QString const&, unsigned short)
vfunc[24]:	QSocket::open(int)
vfunc[25]:	QSocket::close()
vfunc[26]:	QSocket::flush()
vfunc[27]:	QSocket::size() const

vfunc[28]:	QSocket::at() const
vfunc[29]:	QSocket::at(unsigned long)
vfunc[30]:	QSocket::atEnd() const
vfunc[31]:	QSocket::readBlock(char*, unsigned long)
vfunc[32]:	QSocket::writeBlock(char const*, unsigned long)
vfunc[33]:	QSocket::readLine(char*, unsigned long)
vfunc[34]:	QSocket::getch()
vfunc[35]:	QSocket::putch(int)
vfunc[36]:	QSocket::ungetch(int)
vfunc[37]:	QSocket::readLine()
vfunc[38]:	QSocket::sn_read(bool)
vfunc[39]:	QSocket::sn_write()

Table 7-96 Secondary vtable for QSocket

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QSocket
vfunc[0]:	non-virtual thunk to QSocket::~~QSocket()
vfunc[1]:	non-virtual thunk to QSocket::~~QSocket()
vfunc[2]:	non-virtual thunk to QSocket::open(int)
vfunc[3]:	non-virtual thunk to QSocket::close()
vfunc[4]:	non-virtual thunk to QSocket::flush()
vfunc[5]:	non-virtual thunk to QSocket::size() const
vfunc[6]:	non-virtual thunk to QSocket::at() const
vfunc[7]:	non-virtual thunk to QSocket::at(unsigned long)
vfunc[8]:	non-virtual thunk to QSocket::atEnd() const
vfunc[9]:	non-virtual thunk to QSocket::readBlock(char*, unsigned long)

vfunc[10]:	non-virtual thunk to QSocket::writeBlock(char const*, unsigned long)
vfunc[11]:	non-virtual thunk to QSocket::readLine(char*, unsigned long)
vfunc[12]:	QIODevice::readAll()
vfunc[13]:	non-virtual thunk to QSocket::getch()
vfunc[14]:	non-virtual thunk to QSocket::putch(int)
vfunc[15]:	non-virtual thunk to QSocket::ungetch(int)

The Run Time Type Information for the QSocket class is described by Table 7-97

Table 7-97 typeinfo for QSocket

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	2 10242
Name	typeinfo name for QSocket	
flags:	0	
basetype:	typeinfo for QObject	
basetype:	typeinfo for QIODevice	

7.2.1.39 Class data for QGridView

The virtual table for the QGridView class is described by Table 7-98

Table 7-98 Primary vtable for QGridView

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGridView
vfunc[0]:	QGridView::metaObject() const
vfunc[1]:	QGridView::className() const
vfunc[2]:	QGridView::qt_cast(char const*)
vfunc[3]:	QGridView::qt_invoke(int, QUObject*)
vfunc[4]:	QGridView::qt_emit(int, QUObject*)
vfunc[5]:	QGridView::qt_property(int, int, QVariant*)
vfunc[6]:	QGridView::~~QGridView()

vfunc[7]:	QGridView::~~QGridView()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QScrollView::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QScrollView::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()

vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QScrollView::sizeHint() const
vfunc[59]:	QScrollView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const

vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QScrollView::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)

vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QScrollView::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)

vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QGridView::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QGridView::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QScrollView::contentsMouseEvent(QMouseEvent*)
vfunc[130]:	QScrollView::contentsMouseReleaseEvent(QMouseEvent*)
vfunc[131]:	QScrollView::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QScrollView::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QScrollView::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QScrollView::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QScrollView::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QScrollView::contentsDropEvent(QDropEvent*)
vfunc[137]:	QScrollView::contentsWheelEvent(Q

	WheelEvent*)
vfunc[138]:	QScrollView::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QScrollView::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)
vfunc[154]:	QGridView::setNumRows(int)
vfunc[155]:	QGridView::setNumCols(int)
vfunc[156]:	QGridView::setCellWidth(int)
vfunc[157]:	QGridView::setCellHeight(int)
vfunc[158]:	__cxa_pure_virtual
vfunc[159]:	QGridView::paintEmptyArea(QPainter*, int, int, int, int)
vfunc[160]:	QGridView::dimensionChange(int,

	int)
--	------

Table 7-99 Secondary vtable for QGraphicsView

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QGraphicsView
vfunc[0]:	non-virtual thunk to QGraphicsView::~~QGraphicsView()
vfunc[1]:	non-virtual thunk to QGraphicsView::~~QGraphicsView()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QGraphicsView class is described by Table 7-100

Table 7-100 typeinfo for QGraphicsView

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGraphicsView
basetype:	typeinfo for QGraphicsView

7.2.1.40 Class data for QVBoxLayout

The virtual table for the QVBoxLayout class is described by Table 7-101

Table 7-101 Primary vtable for QVBoxLayout

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QVBoxLayout

vfunc[0]:	QBoxLayout::metaObject() const
vfunc[1]:	QBoxLayout::className() const
vfunc[2]:	QBoxLayout::qt_cast(char const*)
vfunc[3]:	QBoxLayout::qt_invoke(int, QUObject*)
vfunc[4]:	QBoxLayout::qt_emit(int, QUObject*)
vfunc[5]:	QBoxLayout::qt_property(int, int, QVariant*)
vfunc[6]:	QBoxLayout::~~QBoxLayout()
vfunc[7]:	QBoxLayout::~~QBoxLayout()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QLayout::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QLayout::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QLayout::setMargin(int)
vfunc[22]:	QLayout::setSpacing(int)
vfunc[23]:	QLayout::setMenuBar(QMenuBar*)
vfunc[24]:	QLayout::setAutoAdd(bool)
vfunc[25]:	QBoxLayout::invalidate()
vfunc[26]:	QLayout::geometry() const
vfunc[27]:	QBoxLayout::addItem(QLayoutItem*)
vfunc[28]:	QBoxLayout::expanding() const

vfunc[29]:	QBoxLayout::minimumSize() const
vfunc[30]:	QBoxLayout::maximumSize() const
vfunc[31]:	QBoxLayout::setGeometry(QRect const&)
vfunc[32]:	QBoxLayout::iterator()
vfunc[33]:	QLayout::isEmpty() const
vfunc[34]:	QLayout::layout()
vfunc[35]:	QBoxLayout::sizeHint() const
vfunc[36]:	QBoxLayout::hasHeightForWidth() const
vfunc[37]:	QBoxLayout::heightForWidth(int) const

Table 7-102 Secondary vtable for QBoxLayout

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QBoxLayout
vfunc[0]:	non-virtual thunk to QBoxLayout::~~QBoxLayout()
vfunc[1]:	non-virtual thunk to QBoxLayout::~~QBoxLayout()
vfunc[2]:	non-virtual thunk to QBoxLayout::sizeHint() const
vfunc[3]:	non-virtual thunk to QBoxLayout::minimumSize() const
vfunc[4]:	non-virtual thunk to QBoxLayout::maximumSize() const
vfunc[5]:	non-virtual thunk to QBoxLayout::expanding() const
vfunc[6]:	non-virtual thunk to QBoxLayout::setGeometry(QRect const&)
vfunc[7]:	non-virtual thunk to QLayout::geometry() const
vfunc[8]:	non-virtual thunk to QLayout::isEmpty() const
vfunc[9]:	non-virtual thunk to QBoxLayout::hasHeightForWidth() const
vfunc[10]:	non-virtual thunk to QBoxLayout::heightForWidth(int)

	const
vfunc[11]:	non-virtual thunk to QBoxLayout::invalidate()
vfunc[12]:	QLayoutItem::widget()
vfunc[13]:	non-virtual thunk to QBoxLayout::iterator()
vfunc[14]:	non-virtual thunk to QLayout::layout()
vfunc[15]:	QLayoutItem::spacerItem()
vfunc[16]:	QLayoutItem::setAlignment(int)

The Run Time Type Information for the QBoxLayout class is described by Table 7-103

Table 7-103 typeinfo for QBoxLayout

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QBoxLayout
basetype:	typeinfo for QLayout

7.2.1.41 Class data for QIMEvent

The virtual table for the QIMEvent class is described by Table 7-104

Table 7-104 Primary vtable for QIMEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIMEvent
vfunc[0]:	QIMEvent::~~QIMEvent()
vfunc[1]:	QIMEvent::~~QIMEvent()

The Run Time Type Information for the QIMEvent class is described by Table 7-105

Table 7-105 typeinfo for QIMEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QIMEvent
basetype:	typeinfo for QEvent

7.2.1.42 Class data for QLayout

The virtual table for the QLayout class is described by Table 7-106

Table 7-106 Primary vtable for QLayout

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLayout
vfunc[0]:	QLayout::metaObject() const
vfunc[1]:	QLayout::className() const
vfunc[2]:	QLayout::qt_cast(char const*)
vfunc[3]:	QLayout::qt_invoke(int, QUObject*)
vfunc[4]:	QLayout::qt_emit(int, QUObject*)
vfunc[5]:	QLayout::qt_property(int, int, QVariant*)
vfunc[6]:	QLayout::~~QLayout()
vfunc[7]:	QLayout::~~QLayout()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QLayout::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QLayout::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QLayout::setMargin(int)
vfunc[22]:	QLayout::setSpacing(int)
vfunc[23]:	QLayout::setMenuBar(QMenuBar*)
vfunc[24]:	QLayout::setAutoAdd(bool)
vfunc[25]:	QLayout::invalidate()
vfunc[26]:	QLayout::geometry() const

vfunc[27]:	__cxa_pure_virtual
vfunc[28]:	QLayout::expanding() const
vfunc[29]:	QLayout::minimumSize() const
vfunc[30]:	QLayout::maximumSize() const
vfunc[31]:	__cxa_pure_virtual
vfunc[32]:	__cxa_pure_virtual
vfunc[33]:	QLayout::isEmpty() const
vfunc[34]:	QLayout::layout()

Table 7-107 Secondary vtable for QLayout

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QLayout
vfunc[0]:	non-virtual thunk to QLayout::~~QLayout()
vfunc[1]:	non-virtual thunk to QLayout::~~QLayout()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	non-virtual thunk to QLayout::minimumSize() const
vfunc[4]:	non-virtual thunk to QLayout::maximumSize() const
vfunc[5]:	non-virtual thunk to QLayout::expanding() const
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	non-virtual thunk to QLayout::geometry() const
vfunc[8]:	non-virtual thunk to QLayout::isEmpty() const
vfunc[9]:	QLayoutItem::hasHeightForWidth() const
vfunc[10]:	QLayoutItem::heightForWidth(int) const
vfunc[11]:	non-virtual thunk to QLayout::invalidate()
vfunc[12]:	QLayoutItem::widget()
vfunc[13]:	__cxa_pure_virtual
vfunc[14]:	non-virtual thunk to QLayout::layout()

vfunc[15]:	QLayoutItem::spacerItem()
vfunc[16]:	QLayoutItem::setAlignment(int)

The Run Time Type Information for the QLayout class is described by Table 7-108

Table 7-108 typeinfo for QLayout

Base Vtable	vtable for __cxxabiv1::__vmi_class _type_info	2
Name	typeinfo name for QLayout	
flags:	0	
basetype:	typeinfo for QObject	
basetype:	typeinfo for QLayoutItem	10242

7.2.1.43 Class data for QSocketNotifier

The virtual table for the QSocketNotifier class is described by Table 7-109

Table 7-109 Primary vtable for QSocketNotifier

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSocketNotifier
vfunc[0]:	QSocketNotifier::metaObject() const
vfunc[1]:	QSocketNotifier::className() const
vfunc[2]:	QSocketNotifier::qt_cast(char const*)
vfunc[3]:	QSocketNotifier::qt_invoke(int, QUObject*)
vfunc[4]:	QSocketNotifier::qt_emit(int, QUObject*)
vfunc[5]:	QSocketNotifier::qt_property(int, int, QVariant*)
vfunc[6]:	QSocketNotifier::~~QSocketNotifier()
vfunc[7]:	QSocketNotifier::~~QSocketNotifier()
vfunc[8]:	QSocketNotifier::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)

vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QSocketNotifier::setEnabled(bool)

The Run Time Type Information for the QSocketNotifier class is described by Table 7-110

Table 7-110 typeinfo for QSocketNotifier

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSocketNotifier
basetype:	typeinfo for QObject

7.2.1.44 Class data for QPushButton

The virtual table for the QPushButton class is described by Table 7-111

Table 7-111 Primary vtable for QPushButton

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPushButton
vfunc[0]:	QPushButton::metaObject() const
vfunc[1]:	QPushButton::className() const
vfunc[2]:	QPushButton::qt_cast(char const*)
vfunc[3]:	QPushButton::qt_invoke(int, QUObject*)
vfunc[4]:	QPushButton::qt_emit(int, QUObject*)
vfunc[5]:	QPushButton::qt_property(int, int, QVariant*)
vfunc[6]:	QPushButton::~~QPushButton()
vfunc[7]:	QPushButton::~~QPushButton()

vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)

vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*,

	unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QPushButton::mousePressEvent(QMouseEvent*)
vfunc[70]:	QPushButton::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QPushButton::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QPushButton::keyPressEvent(QKeyEvent*)
vfunc[75]:	QPushButton::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QPushButton::focusInEvent(QFocusEvent*)
vfunc[77]:	QPushButton::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QPushButton::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnt

	erEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QPushButton::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QPushButton::setText(QString const&)
vfunc[111]:	QPushButton::setPixmap(QPixmap const&)
vfunc[112]:	QPushButton::setAccel(QKeySequence const&)
vfunc[113]:	QPushButton::setDown(bool)
vfunc[114]:	QPushButton::setAutoRepeat(bool)
vfunc[115]:	QPushButton::setToggleType(QButton::ToggleType)
vfunc[116]:	QPushButton::setState(QButton::ToggleState)

vfunc[117]:	QPushButton::hitButton(QPoint const&) const
vfunc[118]:	QPushButton::drawButton(QPainter*)
vfunc[119]:	QPushButton::drawButtonLabel(QPainter*)
vfunc[120]:	QPushButton::setGroup(QButtonGroup*)

Table 7-112 Secondary vtable for QPushButton

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QPushButton
vfunc[0]:	non-virtual thunk to QPushButton::~~QPushButton()
vfunc[1]:	non-virtual thunk to QPushButton::~~QPushButton()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPaintDeviceCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QPushButton class is described by Table 7-113

Table 7-113 typeinfo for QPushButton

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPushButton
basetype:	typeinfo for QWidget

7.2.1.45 Class data for QIntValidator

The virtual table for the QIntValidator class is described by Table 7-114

Table 7-114 Primary vtable for QIntValidator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIntValidator
vfunc[0]:	QIntValidator::metaObject() const
vfunc[1]:	QIntValidator::className() const
vfunc[2]:	QIntValidator::qt_cast(char const*)
vfunc[3]:	QIntValidator::qt_invoke(int, QUObject*)
vfunc[4]:	QIntValidator::qt_emit(int, QUObject*)
vfunc[5]:	QIntValidator::qt_property(int, int, QVariant*)
vfunc[6]:	QIntValidator::~~QIntValidator()
vfunc[7]:	QIntValidator::~~QIntValidator()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QIntValidator::validate(QString&, int&) const
vfunc[22]:	QValidator::fixup(QString&) const
vfunc[23]:	QIntValidator::setRange(int, int)

The Run Time Type Information for the `QIntValidator` class is described by Table 7-115

Table 7-115 typeinfo for `QIntValidator`

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>QIntValidator</code>
basetype:	typeinfo for <code>QValidator</code>

7.2.1.46 Class data for `QWizard`

The virtual table for the `QWizard` class is described by Table 7-116

Table 7-116 Primary vtable for `QWizard`

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>QWizard</code>
<code>vfunc[0]:</code>	<code>QWizard::metaObject() const</code>
<code>vfunc[1]:</code>	<code>QWizard::className() const</code>
<code>vfunc[2]:</code>	<code>QWizard::qt_cast(char const*)</code>
<code>vfunc[3]:</code>	<code>QWizard::qt_invoke(int, QObject*)</code>
<code>vfunc[4]:</code>	<code>QWizard::qt_emit(int, QObject*)</code>
<code>vfunc[5]:</code>	<code>QWizard::qt_property(int, int, QVariant*)</code>
<code>vfunc[6]:</code>	<code>QWizard::~~QWizard()</code>
<code>vfunc[7]:</code>	<code>QWizard::~~QWizard()</code>
<code>vfunc[8]:</code>	<code>QWidget::event(QEvent*)</code>
<code>vfunc[9]:</code>	<code>QWizard::eventFilter(QObject*, QEvent*)</code>
<code>vfunc[10]:</code>	<code>QWidget::setName(char const*)</code>
<code>vfunc[11]:</code>	<code>QObject::insertChild(QObject*)</code>
<code>vfunc[12]:</code>	<code>QObject::removeChild(QObject*)</code>
<code>vfunc[13]:</code>	<code>QObject::setProperty(char const*, QVariant const&)</code>
<code>vfunc[14]:</code>	<code>QObject::property(char const*) const</code>
<code>vfunc[15]:</code>	<code>QObject::timerEvent(QTimerEvent*)</code>
<code>vfunc[16]:</code>	<code>QObject::childEvent(QChildEvent*)</code>
<code>vfunc[17]:</code>	<code>QObject::customEvent(QCustomEvent*)</code>
<code>vfunc[18]:</code>	<code>QObject::connectNotify(char const*)</code>

vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWizard::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)

vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWizard::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)

vfunc[74]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)

vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()
vfunc[113]:	QWizard::addPage(QWidget*, QString const&)
vfunc[114]:	QWizard::insertPage(QWidget*, QString const&, int)
vfunc[115]:	QWizard::removePage(QWidget*)
vfunc[116]:	QWizard::showPage(QWidget*)
vfunc[117]:	QWizard::appropriate(QWidget*) const
vfunc[118]:	QWizard::setAppropriate(QWidget*, bool)
vfunc[119]:	QWizard::setBackEnabled(QWidget*, bool)
vfunc[120]:	QWizard::setNextEnabled(QWidget*, bool)
vfunc[121]:	QWizard::setFinishEnabled(QWidget *, bool)
vfunc[122]:	QWizard::setHelpEnabled(QWidget* , bool)
vfunc[123]:	QWizard::setFinish(QWidget*, bool)
vfunc[124]:	QWizard::back()
vfunc[125]:	QWizard::next()
vfunc[126]:	QWizard::help()
vfunc[127]:	QWizard::layOutButtonRow(QHBox Layout*)

vfunc[128]:	QWizard::layOutTitleRow(QHBoxLayout*, QString const&)
-------------	---

Table 7-117 Secondary vtable for QWizard

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QWizard
vfunc[0]:	non-virtual thunk to QWizard::~~QWizard()
vfunc[1]:	non-virtual thunk to QWizard::~~QWizard()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QWizard class is described by Table 7-118

Table 7-118 typeinfo for QWizard

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWizard
basetype:	typeinfo for QDialog

7.2.1.47 Class data for QCanvasPolygonalItem

The virtual table for the QCanvasPolygonalItem class is described by Table 7-119

Table 7-119 Primary vtable for QCanvasPolygonalItem

Base Offset	0
-------------	---

Virtual Base Offset	0
RTTI	typeinfo for QCanvasPolygonalItem
vfunc[0]:	QCanvasPolygonalItem::~~QCanvasPolygonalItem()
vfunc[1]:	QCanvasPolygonalItem::~~QCanvasPolygonalItem()
vfunc[2]:	QCanvasItem::moveBy(double, double)
vfunc[3]:	QCanvasItem::setAnimated(bool)
vfunc[4]:	QCanvasItem::setVelocity(double, double)
vfunc[5]:	QCanvasItem::advance(int)
vfunc[6]:	QCanvasPolygonalItem::collidesWith(QCanvasItem const*) const
vfunc[7]:	QCanvasItem::setCanvas(QCanvas*)
vfunc[8]:	QCanvasPolygonalItem::draw(QPainter&)
vfunc[9]:	QCanvasItem::setVisible(bool)
vfunc[10]:	QCanvasItem::setSelected(bool)
vfunc[11]:	QCanvasItem::setEnabled(bool)
vfunc[12]:	QCanvasItem::setActive(bool)
vfunc[13]:	QCanvasPolygonalItem::rtti() const
vfunc[14]:	QCanvasPolygonalItem::boundingRect() const
vfunc[15]:	QCanvasItem::boundingRectAdvanced() const
vfunc[16]:	QCanvasPolygonalItem::chunks() const
vfunc[17]:	QCanvasItem::addToChunks()
vfunc[18]:	QCanvasItem::removeFromChunks()
vfunc[19]:	QCanvasItem::changeChunks()
vfunc[20]:	QCanvasPolygonalItem::collidesWith(QCanvasSprite const*, QCanvasPolygonalItem const*, QCanvasRectangle const*, QCanvasEllipse const*, QCanvasText const*) const
vfunc[21]:	QCanvasPolygonalItem::setPen(QPen)
vfunc[22]:	QCanvasPolygonalItem::setBrush(QBrush)

	rush)
vfunc[23]:	__cxa_pure_virtual
vfunc[24]:	QCanvasPolygonalItem::areaPointsAdvanced() const
vfunc[25]:	__cxa_pure_virtual

The Run Time Type Information for the QCanvasPolygonalItem class is described by Table 7-120

Table 7-120 typeinfo for QCanvasPolygonalItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasPolygonalItem
basetype:	typeinfo for QCanvasItem

7.2.1.48 Class data for QSqlSelectCursor

The virtual table for the QSqlSelectCursor class is described by Table 7-121

Table 7-121 Primary vtable for QSqlSelectCursor

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlSelectCursor
vfunc[0]:	QSqlSelectCursor::~~QSqlSelectCursor()
vfunc[1]:	QSqlSelectCursor::~~QSqlSelectCursor()
vfunc[2]:	QSqlCursor::value(int) const
vfunc[3]:	QSqlCursor::value(QString const&) const
vfunc[4]:	QSqlCursor::setValue(int, QVariant const&)
vfunc[5]:	QSqlCursor::setValue(QString const&, QVariant const&)
vfunc[6]:	QSqlSelectCursor::setGenerated(QString const&, bool)
vfunc[7]:	QSqlSelectCursor::setGenerated(int, bool)
vfunc[8]:	QSqlRecord::setNull(int)
vfunc[9]:	QSqlRecord::setNull(QString const&)
vfunc[10]:	QSqlCursor::append(QSqlField const&)

vfunc[11]:	QSqlCursor::insert(int, QSqlField const&)
vfunc[12]:	QSqlSelectCursor::remove(int)
vfunc[13]:	QSqlSelectCursor::clear()
vfunc[14]:	QSqlRecord::clearValues(bool)
vfunc[15]:	QSqlSelectCursor::toString(QString const&, QString const&) const
vfunc[16]:	QSqlRecord::toStringList(QString const&) const
vfunc[17]:	QSqlSelectCursor::primaryIndex(bool) const
vfunc[18]:	QSqlSelectCursor::index(QStringList const&) const
vfunc[19]:	QSqlSelectCursor::setPrimaryIndex(QSqlIndex const&)
vfunc[20]:	QSqlSelectCursor::append(QSqlFieldInfo const&)
vfunc[21]:	QSqlSelectCursor::insert(int, QSqlFieldInfo const&)
vfunc[22]:	QSqlSelectCursor::editBuffer(bool)
vfunc[23]:	QSqlSelectCursor::primeInsert()
vfunc[24]:	QSqlSelectCursor::primeUpdate()
vfunc[25]:	QSqlSelectCursor::primeDelete()
vfunc[26]:	QSqlSelectCursor::insert(bool)
vfunc[27]:	QSqlSelectCursor::update(bool)
vfunc[28]:	QSqlSelectCursor::del(bool)
vfunc[29]:	QSqlSelectCursor::setMode(int)
vfunc[30]:	QSqlCursor::setCalculated(QString const&, bool)
vfunc[31]:	QSqlCursor::setTrimmed(QString const&, bool)
vfunc[32]:	QSqlSelectCursor::select(QString const&, QSqlIndex const&)
vfunc[33]:	QSqlSelectCursor::setSort(QSqlIndex const&)
vfunc[34]:	QSqlSelectCursor::setFilter(QString const&)
vfunc[35]:	QSqlSelectCursor::setName(QString const&, bool)

vfunc[36]:	QSqlCursor::afterSeek()
vfunc[37]:	QSqlSelectCursor::exec(QString const&)
vfunc[38]:	QSqlCursor::calculateField(QString const&)
vfunc[39]:	QSqlCursor::update(QString const&, bool)
vfunc[40]:	QSqlCursor::del(QString const&, bool)
vfunc[41]:	QSqlCursor::toString(QString const&, QSqlField*, QString const&) const
vfunc[42]:	QSqlCursor::toString(QSqlRecord*, QString const&, QString const&, QString const&) const
vfunc[43]:	QSqlCursor::toString(QSqlIndex const&, QSqlRecord*, QString const&, QString const&, QString const&) const

Table 7-122 Secondary vtable for QSqlSelectCursor

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QSqlSelectCursor
vfunc[0]:	non-virtual thunk to QSqlSelectCursor::~~QSqlSelectCursor()
vfunc[1]:	non-virtual thunk to QSqlSelectCursor::~~QSqlSelectCursor()
vfunc[2]:	non-virtual thunk to QSqlSelectCursor::exec(QString const&)
vfunc[3]:	non-virtual thunk to QSqlCursor::value(int) const
vfunc[4]:	QSqlQuery::seek(int, bool)
vfunc[5]:	QSqlQuery::next()
vfunc[6]:	QSqlQuery::prev()
vfunc[7]:	QSqlQuery::first()
vfunc[8]:	QSqlQuery::last()
vfunc[9]:	QSqlQuery::beforeSeek()

vfunc[10]:	non-virtual thunk to QSqlCursor::afterSeek()
------------	---

The Run Time Type Information for the QSqlSelectCursor class is described by Table 7-123

Table 7-123 typeinfo for QSqlSelectCursor

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSqlSelectCursor
basetype:	typeinfo for QSqlCursor

7.2.1.49 Class data for QTabWidget

The virtual table for the QTabWidget class is described by Table 7-124

Table 7-124 Primary vtable for QTabWidget

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTabWidget
vfunc[0]:	QTabWidget::metaObject() const
vfunc[1]:	QTabWidget::className() const
vfunc[2]:	QTabWidget::qt_cast(char const*)
vfunc[3]:	QTabWidget::qt_invoke(int, QObject*)
vfunc[4]:	QTabWidget::qt_emit(int, QObject*)
vfunc[5]:	QTabWidget::qt_property(int, int, QVariant*)
vfunc[6]:	QTabWidget::~~QTabWidget()
vfunc[7]:	QTabWidget::~~QTabWidget()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QTabWidget::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)

vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)

vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QTabWidget::sizeHint() const
vfunc[59]:	QTabWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)

vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QTabWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QTabWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)

vfunc[96]:	QTabWidget::updateMask()
vfunc[97]:	QTabWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QTabWidget::addTab(QWidget*, QString const&)
vfunc[111]:	QTabWidget::addTab(QWidget*, QIconSet const&, QString const&)
vfunc[112]:	QTabWidget::addTab(QWidget*, QTab*)
vfunc[113]:	QTabWidget::insertTab(QWidget*, QString const&, int)
vfunc[114]:	QTabWidget::insertTab(QWidget*, QIconSet const&, QString const&, int)
vfunc[115]:	QTabWidget::insertTab(QWidget*, QTab*, int)
vfunc[116]:	QTabWidget::showPage(QWidget*)
vfunc[117]:	QTabWidget::removePage(QWidget*)

Table 7-125 Secondary vtable for QTabWidget

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QTabWidget

vfunc[0]:	non-virtual thunk to QTabWidget::~~QTabWidget()
vfunc[1]:	non-virtual thunk to QTabWidget::~~QTabWidget()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QTabWidget class is described by Table 7-126

Table 7-126 typeinfo for QTabWidget

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTabWidget
basetype:	typeinfo for QWidget

7.2.1.50 Class data for QDomElement

The virtual table for the QDomElement class is described by Table 7-127

Table 7-127 Primary vtable for QDomElement

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomElement
vfunc[0]:	QDomElement::~~QDomElement()
vfunc[1]:	QDomElement::~~QDomElement()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)

vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomElement::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomElement::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType()

	const
vfunc[33]:	QDomElement::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction() const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const
vfunc[41]:	QDomElement::elementsByTagName (QString const&) const
vfunc[42]:	QDomElement::elementsByTagName NS(QString const&, QString const&) const

The Run Time Type Information for the QDomElement class is described by Table 7-128

Table 7-128 typeinfo for QDomElement

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomElement
basetype:	typeinfo for QDomNode

7.2.1.51 Class data for QSqlDriver

The virtual table for the QSqlDriver class is described by Table 7-129

Table 7-129 Primary vtable for QSqlDriver

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlDriver
vfunc[0]:	QSqlDriver::metaObject() const
vfunc[1]:	QSqlDriver::className() const
vfunc[2]:	QSqlDriver::qt_cast(char const*)
vfunc[3]:	QSqlDriver::qt_invoke(int, QUObject*)
vfunc[4]:	QSqlDriver::qt_emit(int, QUObject*)
vfunc[5]:	QSqlDriver::qt_property(int, int, QVariant*)

vfunc[6]:	QSqlDriver::~~QSqlDriver()
vfunc[7]:	QSqlDriver::~~QSqlDriver()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QSqlDriver::beginTransaction()
vfunc[22]:	QSqlDriver::commitTransaction()
vfunc[23]:	QSqlDriver::rollbackTransaction()
vfunc[24]:	QSqlDriver::tables(QString const&) const
vfunc[25]:	QSqlDriver::primaryIndex(QString const&) const
vfunc[26]:	QSqlDriver::record(QString const&) const
vfunc[27]:	QSqlDriver::record(QSqlQuery const&) const
vfunc[28]:	QSqlDriver::recordInfo(QString const&) const
vfunc[29]:	QSqlDriver::recordInfo(QSqlQuery const&) const
vfunc[30]:	QSqlDriver::nullText() const
vfunc[31]:	QSqlDriver::formatValue(QSqlField const*, bool) const
vfunc[32]:	__cxa_pure_virtual

vfunc[33]:	__cxa_pure_virtual
vfunc[34]:	__cxa_pure_virtual
vfunc[35]:	__cxa_pure_virtual
vfunc[36]:	QSqlDriver::setOpen(bool)
vfunc[37]:	QSqlDriver::setOpenError(bool)
vfunc[38]:	QSqlDriver::setLastError(QSqlError const&)

The Run Time Type Information for the QSqlDriver class is described by Table 7-130

Table 7-130 typeinfo for QSqlDriver

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSqlDriver
basetype:	typeinfo for QObject

7.2.1.52 Class data for QTableWidgetItem

The virtual table for the QTableWidgetItem class is described by Table 7-131

Table 7-131 Primary vtable for QTableWidgetItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTableWidgetItem
vfunc[0]:	QTableWidgetItem::~~QTableWidgetItem()
vfunc[1]:	QTableWidgetItem::~~QTableWidgetItem()
vfunc[2]:	QTableWidgetItem::pixmap() const
vfunc[3]:	QTableWidgetItem::text() const
vfunc[4]:	QTableWidgetItem::setPixmap(QPixmap const&)
vfunc[5]:	QTableWidgetItem::setText(QString const&)
vfunc[6]:	QTableWidgetItem::alignment() const
vfunc[7]:	QTableWidgetItem::setWordWrap(bool)
vfunc[8]:	QTableWidgetItem::createEditor() const
vfunc[9]:	QTableWidgetItem::setContentFromEditor(QWidget*)
vfunc[10]:	QTableWidgetItem::setReplaceable(bool)
vfunc[11]:	QTableWidgetItem::key() const
vfunc[12]:	QTableWidgetItem::sizeHint() const

vfunc[13]:	QTableWidgetItem::setSpan(int, int)
vfunc[14]:	QTableWidgetItem::setRow(int)
vfunc[15]:	QTableWidgetItem::setCol(int)
vfunc[16]:	QTableWidgetItem::paint(QPainter*, QColorGroup const&, QRect const&, bool)
vfunc[17]:	QTableWidgetItem::setEnabled(bool)
vfunc[18]:	QTableWidgetItem::rtti() const

The Run Time Type Information for the QTableWidgetItem class is described by Table 7-132

Table 7-132 typeinfo for QTableWidgetItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTableWidgetItem
basetype:	typeinfo for Qt

7.2.1.53 Class data for QDomImplementation

The virtual table for the QDomImplementation class is described by Table 7-133

Table 7-133 Primary vtable for QDomImplementation

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomImplementation
vfunc[0]:	QDomImplementation::~~QDomImplementation()
vfunc[1]:	QDomImplementation::~~QDomImplementation()
vfunc[2]:	QDomImplementation::hasFeature(QString const&, QString const&)
vfunc[3]:	QDomImplementation::createDocumentType(QString const&, QString const&, QString const&)
vfunc[4]:	QDomImplementation::createDocument(QString const&, QString const&, QDomDocumentType const&)

The Run Time Type Information for the QDomImplementation class is described by Table 7-134

Table 7-134 typeinfo for QDomImplementation

Base Vtable	vtable for
-------------	------------

	__cxxabiv1::__class_type_info
Name	typeinfo name for QDomImplementation

7.2.1.54 Class data for QGPlugin

The virtual table for the QGPlugin class is described by Table 7-135

Table 7-135 Primary vtable for QGPlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGPlugin
vfunc[0]:	QGPlugin::metaObject() const
vfunc[1]:	QGPlugin::className() const
vfunc[2]:	QGPlugin::qt_cast(char const*)
vfunc[3]:	QGPlugin::qt_invoke(int, QUObject*)
vfunc[4]:	QGPlugin::qt_emit(int, QUObject*)
vfunc[5]:	QGPlugin::qt_property(int, int, QVariant*)
vfunc[6]:	QGPlugin::~~QGPlugin()
vfunc[7]:	QGPlugin::~~QGPlugin()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QGPlugin class is described by Table 7-136

Table 7-136 typeinfo for QGPlugin

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGPlugin
basetype:	typeinfo for QObject

7.2.1.55 Class data for QGb18030Codec

The virtual table for the QGb18030Codec class is described by Table 7-137

Table 7-137 Primary vtable for QGb18030Codec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGb18030Codec
vfunc[0]:	QGb18030Codec::~~QGb18030Codec()
vfunc[1]:	QGb18030Codec::~~QGb18030Codec()
vfunc[2]:	QGb18030Codec::name() const
vfunc[3]:	QTextCodec::mimeTypeName() const
vfunc[4]:	QGb18030Codec::mibEnum() const
vfunc[5]:	QGb18030Codec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QGb18030Codec::toUnicode(char const*, int) const
vfunc[8]:	QGb18030Codec::fromUnicode(QStri ng const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QGb18030Codec::heuristicContentM atch(char const*, int) const
vfunc[12]:	QGb18030Codec::heuristicNameMatc h(char const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode(QString const&, int) const

The Run Time Type Information for the QGb18030Codec class is described by Table 7-138

Table 7-138 typeinfo for QGb18030Codec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGb18030Codec
basetype:	typeinfo for QTextCodec

7.2.1.56 Class data for QGList

The virtual table for the QGList class is described by Table 7-139

Table 7-139 Primary vtable for QGList

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGList
vfunc[0]:	QGList::count() const
vfunc[1]:	QGList::clear()
vfunc[2]:	QGList::~~QGList()
vfunc[3]:	QGList::~~QGList()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	QGList::compareItems(void*, void*)
vfunc[7]:	QGList::read(QDataStream&, void*&)
vfunc[8]:	QGList::write(QDataStream&, void*) const

The Run Time Type Information for the QGList class is described by Table 7-140

Table 7-140 typeinfo for QGList

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGList
basetype:	typeinfo for QPtrCollection

7.2.1.57 Class data for QDataPump

The virtual table for the QDataPump class is described by Table 7-141

Table 7-141 Primary vtable for QDataPump

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QDataPump
vfunc[0]:	QDataPump::metaObject() const
vfunc[1]:	QDataPump::className() const
vfunc[2]:	QDataPump::qt_cast(char const*)
vfunc[3]:	QDataPump::qt_invoke(int, QUObject*)
vfunc[4]:	QDataPump::qt_emit(int, QUObject*)
vfunc[5]:	QDataPump::qt_property(int, int, QVariant*)
vfunc[6]:	QDataPump::~~QDataPump()
vfunc[7]:	QDataPump::~~QDataPump()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QDataPump class is described by Table 7-142

Table 7-142 typeinfo for QDataPump

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDataPump
basetype:	typeinfo for QObject

7.2.1.58 Class data for QPaintDevice

The virtual table for the QPaintDevice class is described by Table 7-143

Table 7-143 Primary vtable for QPaintDevice

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPaintDevice
vfunc[0]:	QPaintDevice::~~QPaintDevice()
vfunc[1]:	QPaintDevice::~~QPaintDevice()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDvCmdParam*)
vfunc[8]:	QPaintDevice::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QPaintDevice class is described by Table 7-144

Table 7-144 typeinfo for QPaintDevice

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QPaintDevice

7.2.1.59 Class data for QCheckTableItem

The virtual table for the QCheckTableItem class is described by Table 7-145

Table 7-145 Primary vtable for QCheckTableItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCheckTableItem
vfunc[0]:	QCheckTableItem::~~QCheckTableIte m()

vfunc[1]:	QCheckTableWidgetItem::~~QCheckTableWidgetItem()
vfunc[2]:	QTableWidgetItem::pixmap() const
vfunc[3]:	QTableWidgetItem::text() const
vfunc[4]:	QTableWidgetItem::setPixmap(QPixmap const&)
vfunc[5]:	QCheckTableWidgetItem::setText(QString const&)
vfunc[6]:	QTableWidgetItem::alignment() const
vfunc[7]:	QTableWidgetItem::setWordWrap(bool)
vfunc[8]:	QCheckTableWidgetItem::createEditor() const
vfunc[9]:	QCheckTableWidgetItem::setContentFromEditor(QWidget*)
vfunc[10]:	QTableWidgetItem::setReplaceable(bool)
vfunc[11]:	QTableWidgetItem::key() const
vfunc[12]:	QCheckTableWidgetItem::sizeHint() const
vfunc[13]:	QTableWidgetItem::setSpan(int, int)
vfunc[14]:	QTableWidgetItem::setRow(int)
vfunc[15]:	QTableWidgetItem::setCol(int)
vfunc[16]:	QCheckTableWidgetItem::paint(QPainter*, QColorGroup const&, QRect const&, bool)
vfunc[17]:	QTableWidgetItem::setEnabled(bool)
vfunc[18]:	QCheckTableWidgetItem::rtti() const
vfunc[19]:	QCheckTableWidgetItem::setChecked(bool)

The Run Time Type Information for the QCheckTableWidgetItem class is described by Table 7-146

Table 7-146 typeinfo for QCheckTableWidgetItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCheckTableWidgetItem
basetype:	typeinfo for QTableWidgetItem

7.2.1.60 Class data for QCommonStyle

The virtual table for the QCommonStyle class is described by Table 7-147

Table 7-147 Primary vtable for QCommonStyle

Base Offset	0
-------------	---

Virtual Base Offset	0
RTTI	typeinfo for QCommonStyle
vfunc[0]:	QCommonStyle::metaObject() const
vfunc[1]:	QCommonStyle::className() const
vfunc[2]:	QCommonStyle::qt_cast(char const*)
vfunc[3]:	QCommonStyle::qt_invoke(int, QUObject*)
vfunc[4]:	QCommonStyle::qt_emit(int, QUObject*)
vfunc[5]:	QCommonStyle::qt_property(int, int, QVariant*)
vfunc[6]:	QCommonStyle::~~QCommonStyle()
vfunc[7]:	QCommonStyle::~~QCommonStyle()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QStyle::polish(QWidget*)
vfunc[22]:	QStyle::unPolish(QWidget*)
vfunc[23]:	QStyle::polish(QApplication*)
vfunc[24]:	QStyle::unPolish(QApplication*)
vfunc[25]:	QStyle::polish(QPalette&)
vfunc[26]:	__cxa_pure_virtual

vfunc[27]:	QStyle::itemRect(QPainter*, QRect const&, int, bool, QPixmap const*, QString const&, int) const
vfunc[28]:	QStyle::drawItem(QPainter*, QRect const&, int, QColorGroup const&, bool, QPixmap const*, QString const&, int, QColor const*) const
vfunc[29]:	QCommonStyle::drawPrimitive(QStyle::PrimitiveElement, QPainter*, QRect const&, QColorGroup const&, unsigned int, QStyleOption const&) const
vfunc[30]:	QCommonStyle::drawControl(QStyle::ControlElement, QPainter*, QWidget const*, QRect const&, QColorGroup const&, unsigned int, QStyleOption const&) const
vfunc[31]:	QCommonStyle::drawControlMask(QStyle::ControlElement, QPainter*, QWidget const*, QRect const&, QStyleOption const&) const
vfunc[32]:	QCommonStyle::subRect(QStyle::SubRect, QWidget const*) const
vfunc[33]:	QCommonStyle::drawComplexControl(QStyle::ComplexControl, QPainter*, QWidget const*, QRect const&, QColorGroup const&, unsigned int, unsigned int, unsigned int, QStyleOption const&) const
vfunc[34]:	QCommonStyle::drawComplexControlMask(QStyle::ComplexControl, QPainter*, QWidget const*, QRect const&, QStyleOption const&) const
vfunc[35]:	QCommonStyle::querySubControlMetrics(QStyle::ComplexControl, QWidget const*, QStyle::SubControl, QStyleOption const&) const
vfunc[36]:	QCommonStyle::querySubControl(QStyle::ComplexControl, QWidget const*, QPoint const&, QStyleOption const&) const
vfunc[37]:	QCommonStyle::pixelMetric(QStyle::PixelMetric, QWidget const*) const
vfunc[38]:	QCommonStyle::sizeFromContents(QStyle::ContentsType, QWidget const*, QSize const&, QStyleOption const&) const

vfunc[39]:	QCommonStyle::styleHint(QStyle::StyleHint, QWidget const*, QStyleOption const&, QStyleHintReturn*) const
vfunc[40]:	QCommonStyle::stylePixmap(QStyle::StylePixmap, QWidget const*, QStyleOption const&) const

The Run Time Type Information for the QCommonStyle class is described by Table 7-148

Table 7-148 typeinfo for QCommonStyle

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCommonStyle
basetype:	typeinfo for QStyle

7.2.1.61 Class data for QTextView

The virtual table for the QTextView class is described by Table 7-149

Table 7-149 Primary vtable for QTextView

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextView
vfunc[0]:	QTextView::metaObject() const
vfunc[1]:	QTextView::className() const
vfunc[2]:	QTextView::qt_cast(char const*)
vfunc[3]:	QTextView::qt_invoke(int, QUObject*)
vfunc[4]:	QTextView::qt_emit(int, QUObject*)
vfunc[5]:	QTextView::qt_property(int, int, QVariant*)
vfunc[6]:	QTextView::~~QTextView()
vfunc[7]:	QTextView::~~QTextView()
vfunc[8]:	QTextEdit::event(QEvent*)
vfunc[9]:	QTextEdit::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*,

	QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QTextEdit::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QTextEdit::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QTextEdit::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)

vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QTextEdit::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QTextEdit::sizeHint() const
vfunc[59]:	QScrollView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QTextEdit::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const

vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QTextEdit::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QTextEdit::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QTextEdit::imStartEvent(QIMEvent*)
vfunc[86]:	QTextEdit::imComposeEvent(QIMEvent*)
vfunc[87]:	QTextEdit::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)

vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QTextEdit::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QTextEdit::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QTextEdit::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)

vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QTextEdit::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QTextEdit::contentsMouseEvent(QMouseEvent*)
vfunc[130]:	QTextEdit::contentsMouseReleaseEvent(QMouseEvent*)
vfunc[131]:	QTextEdit::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QTextEdit::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QTextEdit::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QTextEdit::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QTextEdit::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QTextEdit::contentsDropEvent(QDropEvent*)
vfunc[137]:	QTextEdit::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QTextEdit::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QTextEdit::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)

vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)
vfunc[154]:	QTextEdit::find(QString const&, bool, bool, bool, int*, int*)
vfunc[155]:	QTextEdit::getFormat(int, int, QFont*, QColor*, QTextEdit::VerticalAlignment*)
vfunc[156]:	QTextEdit::getParagraphFormat(int, QFont*, QColor*, QTextEdit::VerticalAlignment*, int*, QStyleSheetItem::DisplayMode*, QStyleSheetItem::ListStyle*, int*)
vfunc[157]:	QTextEdit::setMimeSourceFactory(QMimeSourceFactory*)
vfunc[158]:	QTextEdit::setStyleSheet(QStyleSheet*)
vfunc[159]:	QTextEdit::scrollToAnchor(QString const&)
vfunc[160]:	QTextEdit::setPaper(QBrush const&)
vfunc[161]:	QTextEdit::setLinkUnderline(bool)
vfunc[162]:	QTextEdit::setWordWrap(QTextEdit::WordWrap)

vfunc[163]:	QTextEdit::setWrapColumnOrWidth(int)
vfunc[164]:	QTextEdit::setWrapPolicy(QTextEdit::WrapPolicy)
vfunc[165]:	QTextEdit::copy()
vfunc[166]:	QTextEdit::append(QString const&)
vfunc[167]:	QTextEdit::setText(QString const&, QString const&)
vfunc[168]:	QTextEdit::setTextFormat(Qt::TextFormat)
vfunc[169]:	QTextEdit::selectAll(bool)
vfunc[170]:	QTextEdit::setTabStopWidth(int)
vfunc[171]:	QTextEdit::zoomIn(int)
vfunc[172]:	QTextEdit::zoomIn()
vfunc[173]:	QTextEdit::zoomOut(int)
vfunc[174]:	QTextEdit::zoomOut()
vfunc[175]:	QTextEdit::zoomTo(int)
vfunc[176]:	QTextEdit::sync()
vfunc[177]:	QTextEdit::setReadOnly(bool)
vfunc[178]:	QTextEdit::undo()
vfunc[179]:	QTextEdit::redo()
vfunc[180]:	QTextEdit::cut()
vfunc[181]:	QTextEdit::paste()
vfunc[182]:	QTextEdit::pasteSubType(QCString const&)
vfunc[183]:	QTextEdit::clear()
vfunc[184]:	QTextEdit::del()
vfunc[185]:	QTextEdit::indent()
vfunc[186]:	QTextEdit::setItalic(bool)
vfunc[187]:	QTextEdit::setBold(bool)
vfunc[188]:	QTextEdit::setUnderline(bool)
vfunc[189]:	QTextEdit::setFamily(QString const&)
vfunc[190]:	QTextEdit::setPointSize(int)
vfunc[191]:	QTextEdit::setColor(QColor const&)
vfunc[192]:	QTextEdit::setVerticalAlignment(QTextEdit::VerticalAlignment)

vfunc[193]:	QTextEdit::setAlignment(int)
vfunc[194]:	QTextEdit::setParagType(QStyleShee tItem::DisplayMode, QStyleSheetItem::ListStyle)
vfunc[195]:	QTextEdit::setCursorPosition(int, int)
vfunc[196]:	QTextEdit::setSelection(int, int, int, int, int)
vfunc[197]:	QTextEdit::setSelectionAttributes(int, QColor const&, bool)
vfunc[198]:	QTextEdit::setModified(bool)
vfunc[199]:	QTextEdit::resetFormat()
vfunc[200]:	QTextEdit::setUndoDepth(int)
vfunc[201]:	QTextEdit::setFormat(QTextFormat*, int)
vfunc[202]:	QTextEdit::ensureCursorVisible()
vfunc[203]:	QTextEdit::placeCursor(QPoint const&, QTextCursor*)
vfunc[204]:	QTextEdit::moveCursor(QTextEdit:: CursorAction, bool)
vfunc[205]:	QTextEdit::doKeyboardAction(QText Edit::KeyboardAction)
vfunc[206]:	QTextEdit::removeSelectedText(int)
vfunc[207]:	QTextEdit::removeSelection(int)
vfunc[208]:	QTextEdit::setCurrentFont(QFont const&)
vfunc[209]:	QTextEdit::setOverwriteMode(bool)
vfunc[210]:	QTextEdit::scrollToBottom()
vfunc[211]:	QTextEdit::insert(QString const&, bool, bool, bool)
vfunc[212]:	QTextEdit::insertAt(QString const&, int, int)
vfunc[213]:	QTextEdit::removeParagraph(int)
vfunc[214]:	QTextEdit::insertParagraph(QString const&, int)
vfunc[215]:	QTextEdit::setParagraphBackground Color(int, QColor const&)
vfunc[216]:	QTextEdit::clearParagraphBackgroun d(int)
vfunc[217]:	QTextEdit::setUndoRedoEnabled(bo ol)

vfunc[218]:	QTextEdit::createPopupMenu(QPoint const&)
vfunc[219]:	QTextEdit::createPopupMenu()
vfunc[220]:	QTextEdit::doChangeInterval()
vfunc[221]:	QTextEdit::linksEnabled() const
vfunc[222]:	QTextEdit::emitHighlighted(QString const&)
vfunc[223]:	QTextEdit::emitLinkClicked(QString const&)

Table 7-150 Secondary vtable for QTextView

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QTextView
vfunc[0]:	non-virtual thunk to QTextView::~~QTextView()
vfunc[1]:	non-virtual thunk to QTextView::~~QTextView()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QTextView class is described by Table 7-151

Table 7-151 typeinfo for QTextView

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextView

basetype:	typeinfo for QTextEdit
-----------	------------------------

7.2.1.62 Class data for QSyntaxHighlighter

The virtual table for the QSyntaxHighlighter class is described by Table 7-152

Table 7-152 Primary vtable for QSyntaxHighlighter

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSyntaxHighlighter
vfunc[0]:	QSyntaxHighlighter::~~QSyntaxHighlighter()
vfunc[1]:	QSyntaxHighlighter::~~QSyntaxHighlighter()
vfunc[2]:	__cxa_pure_virtual

The Run Time Type Information for the QSyntaxHighlighter class is described by Table 7-153

Table 7-153 typeinfo for QSyntaxHighlighter

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSyntaxHighlighter
basetype:	typeinfo for Qt

7.2.1.63 Class data for QSemimodal

The virtual table for the QSemimodal class is described by Table 7-154

Table 7-154 Primary vtable for QSemimodal

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSemimodal
vfunc[0]:	QSemimodal::metaObject() const
vfunc[1]:	QSemimodal::className() const
vfunc[2]:	QSemimodal::qt_cast(char const*)
vfunc[3]:	QSemimodal::qt_invoke(int, QUObject*)
vfunc[4]:	QSemimodal::qt_emit(int, QUObject*)
vfunc[5]:	QSemimodal::qt_property(int, int, QVariant*)
vfunc[6]:	QSemimodal::~~QSemimodal()

vfunc[7]:	QSemimodal::~QSemimodal()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()

vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*,

	unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)

vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, bool, QFont*)
vfunc[110]:	QDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 7-155 Secondary vtable for QSEmiModal

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QSEmiModal
vfunc[0]:	non-virtual thunk to QSEmiModal::~~QSEmiModal()
vfunc[1]:	non-virtual thunk to QSEmiModal::~~QSEmiModal()

vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QSEmiModal class is described by Table 7-156

Table 7-156 typeinfo for QSEmiModal

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSEmiModal
basetype:	typeinfo for QDialog

7.2.1.64 Class data for QTab

The virtual table for the QTab class is described by Table 7-157

Table 7-157 Primary vtable for QTab

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTab
vfunc[0]:	QTab::~~QTab()
vfunc[1]:	QTab::~~QTab()

The Run Time Type Information for the QTab class is described by Table 7-158

Table 7-158 typeinfo for QTab

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTab
basetype:	typeinfo for Qt

7.2.1.65 Class data for QPolygonScanner

The virtual table for the QPolygonScanner class is described by Table 7-159

Table 7-159 Primary vtable for QPolygonScanner

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPolygonScanner
vfunc[0]:	__cxa_pure_virtual

The Run Time Type Information for the QPolygonScanner class is described by Table 7-160

Table 7-160 typeinfo for QPolygonScanner

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QPolygonScanner

7.2.1.66 Class data for QNetworkProtocol

The virtual table for the QNetworkProtocol class is described by Table 7-161

Table 7-161 Primary vtable for QNetworkProtocol

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QNetworkProtocol
vfunc[0]:	QNetworkProtocol::metaObject() const
vfunc[1]:	QNetworkProtocol::className() const
vfunc[2]:	QNetworkProtocol::qt_cast(char const*)
vfunc[3]:	QNetworkProtocol::qt_invoke(int, QIODevice*)
vfunc[4]:	QNetworkProtocol::qt_emit(int, QIODevice*)
vfunc[5]:	QNetworkProtocol::qt_property(int, int, QVariant*)
vfunc[6]:	QNetworkProtocol::~~QNetworkProt ocol()
vfunc[7]:	QNetworkProtocol::~~QNetworkProt ocol()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*,

	QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QNetworkProtocol::setUrl(QUrlOperator*)
vfunc[22]:	QNetworkProtocol::setAutoDelete(bool, int)
vfunc[23]:	QNetworkProtocol::supportedOperations() const
vfunc[24]:	QNetworkProtocol::addOperation(QNetworkOperation*)
vfunc[25]:	QNetworkProtocol::clearOperationQueue()
vfunc[26]:	QNetworkProtocol::stop()
vfunc[27]:	QNetworkProtocol::processOperation(QNetworkOperation*)
vfunc[28]:	QNetworkProtocol::operationListChildren(QNetworkOperation*)
vfunc[29]:	QNetworkProtocol::operationMkDir(QNetworkOperation*)
vfunc[30]:	QNetworkProtocol::operationRemove(QNetworkOperation*)
vfunc[31]:	QNetworkProtocol::operationRename(QNetworkOperation*)
vfunc[32]:	QNetworkProtocol::operationGet(QNetworkOperation*)
vfunc[33]:	QNetworkProtocol::operationPut(Q

	NetworkOperation*)
vfunc[34]:	QNetworkProtocol::operationPutChunk(QNetworkOperation*)
vfunc[35]:	QNetworkProtocol::checkConnection(QNetworkOperation*)

The Run Time Type Information for the QNetworkProtocol class is described by Table 7-162

Table 7-162 typeinfo for QNetworkProtocol

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QNetworkProtocol
basetype:	typeinfo for QObject

7.2.1.67 Class data for QObjectUserData

The virtual table for the QObjectUserData class is described by Table 7-163

Table 7-163 Primary vtable for QObjectUserData

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QObjectUserData
vfunc[0]:	QObjectUserData::~~QObjectUserData()
vfunc[1]:	QObjectUserData::~~QObjectUserData()

The Run Time Type Information for the QObjectUserData class is described by Table 7-164

Table 7-164 typeinfo for QObjectUserData

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QObjectUserData

7.2.1.68 Class data for QRangeControl

The virtual table for the QRangeControl class is described by Table 7-165

Table 7-165 Primary vtable for QRangeControl

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QRangeControl
vfunc[0]:	QRangeControl::~~QRangeControl()

vfunc[1]:	QRangeControl::~~QRangeControl()
vfunc[2]:	QRangeControl::valueChange()
vfunc[3]:	QRangeControl::rangeChange()
vfunc[4]:	QRangeControl::stepChange()

The Run Time Type Information for the QRangeControl class is described by Table 7-166

Table 7-166 typeinfo for QRangeControl

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QRangeControl

7.2.1.69 Class data for QHGroupBox

The virtual table for the QHGroupBox class is described by Table 7-167

Table 7-167 Primary vtable for QHGroupBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHGroupBox
vfunc[0]:	QHGroupBox::metaObject() const
vfunc[1]:	QHGroupBox::className() const
vfunc[2]:	QHGroupBox::qt_cast(char const*)
vfunc[3]:	QHGroupBox::qt_invoke(int, QUObject*)
vfunc[4]:	QHGroupBox::qt_emit(int, QUObject*)
vfunc[5]:	QHGroupBox::qt_property(int, int, QVariant*)
vfunc[6]:	QHGroupBox::~~QHGroupBox()
vfunc[7]:	QHGroupBox::~~QHGroupBox()
vfunc[8]:	QGroupBox::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const

vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QGroupBox::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QGroupBox::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString

	const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QGroupBox::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)

	seEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QGroupBox::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QGroupBox::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QGroupBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)

vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QGroupBox::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QGroupBox::setColumnLayout(int, Qt::Orientation)
vfunc[119]:	QGroupBox::setTitle(QString const&)
vfunc[120]:	QGroupBox::setAlignment(int)

Table 7-168 Secondary vtable for QHGroupBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QHGroupBox

vfunc[0]:	non-virtual thunk to QHGroupBox::~QHGroupBox()
vfunc[1]:	non-virtual thunk to QHGroupBox::~QHGroupBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QHGroupBox class is described by Table 7-169

Table 7-169 typeinfo for QHGroupBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHGroupBox
basetype:	typeinfo for QGroupBox

7.2.1.70 Class data for QTimerEvent

The virtual table for the QTimerEvent class is described by Table 7-170

Table 7-170 Primary vtable for QTimerEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTimerEvent
vfunc[0]:	QTimerEvent::~QTimerEvent()
vfunc[1]:	QTimerEvent::~QTimerEvent()

The Run Time Type Information for the QTimerEvent class is described by Table 7-171

Table 7-171 typeinfo for QTimerEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTimerEvent
basetype:	typeinfo for QEvent

7.2.1.71 Class data for QHeader

The virtual table for the QHeader class is described by Table 7-172

Table 7-172 Primary vtable for QHeader

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHeader
vfunc[0]:	QHeader::metaObject() const
vfunc[1]:	QHeader::className() const
vfunc[2]:	QHeader::qt_cast(char const*)
vfunc[3]:	QHeader::qt_invoke(int, QUObject*)
vfunc[4]:	QHeader::qt_emit(int, QUObject*)
vfunc[5]:	QHeader::qt_property(int, int, QVariant*)
vfunc[6]:	QHeader::~~QHeader()
vfunc[7]:	QHeader::~~QHeader()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)

vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QHeader::setUpdatesEnabled(bool)

vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QHeader::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QHeader::mousePressEvent(QMouseEvent*)
vfunc[70]:	QHeader::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QHeader::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QHeader::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QHeader::keyPressEvent(QKeyEvent*)

vfunc[75]:	QHeader::keyPressEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QHeader::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QHeader::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QHeader::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QHeader::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)

vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QHeader::setLabel(int, QString const&, int)
vfunc[111]:	QHeader::setLabel(int, QIconSet const&, QString const&, int)
vfunc[112]:	QHeader::setOrientation(Qt::Orientat ion)
vfunc[113]:	QHeader::setTracking(bool)
vfunc[114]:	QHeader::setClickEnabled(bool, int)
vfunc[115]:	QHeader::setResizeEnabled(bool, int)
vfunc[116]:	QHeader::setMovingEnabled(bool)
vfunc[117]:	QHeader::setStretchEnabled(bool, int)
vfunc[118]:	QHeader::setCellSize(int, int)
vfunc[119]:	QHeader::moveCell(int, int)
vfunc[120]:	QHeader::setOffset(int)
vfunc[121]:	QHeader::paintSection(QPainter*, int, QRect const&)
vfunc[122]:	QHeader::paintSectionLabel(QPainte r*, int, QRect const&)

Table 7-173 Secondary vtable for QHeader

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QHeader
vfunc[0]:	non-virtual thunk to QHeader::~~QHeader()
vfunc[1]:	non-virtual thunk to QHeader::~~QHeader()
vfunc[2]:	QPaintDevice::setResolution(int)

vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QHeader class is described by Table 7-174

Table 7-174 typeinfo for QHeader

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHeader
basetype:	typeinfo for QWidget

7.2.1.72 Class data for QGbkCodec

The virtual table for the QGbkCodec class is described by Table 7-175

Table 7-175 Primary vtable for QGbkCodec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGbkCodec
vfunc[0]:	QGbkCodec::~~QGbkCodec()
vfunc[1]:	QGbkCodec::~~QGbkCodec()
vfunc[2]:	QGbkCodec::name() const
vfunc[3]:	QTextCodec::mimeTypeName() const
vfunc[4]:	QGbkCodec::mibEnum() const
vfunc[5]:	QGbkCodec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QGbkCodec::toUnicode(char const*, int) const
vfunc[8]:	QGbkCodec::fromUnicode(QString

	const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QGbkCodec::heuristicContentMatch(char const*, int) const
vfunc[12]:	QGbkCodec::heuristicNameMatch(ch ar const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode(QString const&, int) const

The Run Time Type Information for the QGbkCodec class is described by Table 7-176

Table 7-176 typeinfo for QGbkCodec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGbkCodec
basetype:	typeinfo for QGb18030Codec

7.2.1.73 Class data for QSplashScreen

The virtual table for the QSplashScreen class is described by Table 7-177

Table 7-177 Primary vtable for QSplashScreen

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSplashScreen
vfunc[0]:	QSplashScreen::metaObject() const
vfunc[1]:	QSplashScreen::className() const
vfunc[2]:	QSplashScreen::qt_cast(char const*)
vfunc[3]:	QSplashScreen::qt_invoke(int, QUObject*)
vfunc[4]:	QSplashScreen::qt_emit(int, QUObject*)
vfunc[5]:	QSplashScreen::qt_property(int, int, QVariant*)
vfunc[6]:	QSplashScreen::~~QSplashScreen()
vfunc[7]:	QSplashScreen::~~QSplashScreen()

vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)

vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*,

	unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QSplashScreen::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnt

	erEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QSplashScreen::drawContents(QPainter*)

Table 7-178 Secondary vtable for QSplashScreen

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QSplashScreen
vfunc[0]:	non-virtual thunk to QSplashScreen::~~QSplashScreen()
vfunc[1]:	non-virtual thunk to QSplashScreen::~~QSplashScreen()

vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QSplashScreen class is described by Table 7-179

Table 7-179 typeinfo for QSplashScreen

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSplashScreen
basetype:	typeinfo for QWidget

7.2.1.74 Class data for QMutex

The virtual table for the QMutex class is described by Table 7-180

Table 7-180 Primary vtable for QMutex

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMutex
vfunc[0]:	QMutex::~~QMutex()
vfunc[1]:	QMutex::~~QMutex()

The Run Time Type Information for the QMutex class is described by Table 7-181

Table 7-181 typeinfo for QMutex

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QMutex

7.2.1.75 Class data for QSqlPropertyMap

The virtual table for the QSqlPropertyMap class is described by Table 7-182

Table 7-182 Primary vtable for QSqlPropertyMap

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlPropertyMap
vfunc[0]:	QSqlPropertyMap::~~QSqlPropertyMap()
vfunc[1]:	QSqlPropertyMap::~~QSqlPropertyMap()
vfunc[2]:	QSqlPropertyMap::setProperty(QWidget*, QVariant const&)

The Run Time Type Information for the QSqlPropertyMap class is described by Table 7-183

Table 7-183 typeinfo for QSqlPropertyMap

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QSqlPropertyMap

7.2.1.76 Class data for QKeyEvent

The virtual table for the QKeyEvent class is described by Table 7-184

Table 7-184 Primary vtable for QKeyEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QKeyEvent
vfunc[0]:	QKeyEvent::~~QKeyEvent()
vfunc[1]:	QKeyEvent::~~QKeyEvent()

The Run Time Type Information for the QKeyEvent class is described by Table 7-185

Table 7-185 typeinfo for QKeyEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QKeyEvent
basetype:	typeinfo for QEvent

7.2.1.77 Class data for QGCache

The virtual table for the QGCache class is described by Table 7-186

Table 7-186 Primary vtable for QGCache

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGCache
vfunc[0]:	QGCache::count() const
vfunc[1]:	QGCache::clear()
vfunc[2]:	QGCache::~~QGCache()
vfunc[3]:	QGCache::~~QGCache()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	__cxa_pure_virtual

The Run Time Type Information for the QGCache class is described by Table 7-187

Table 7-187 typeinfo for QGCache

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGCache
basetype:	typeinfo for QPtrCollection

7.2.1.78 Class data for QDial

The virtual table for the QDial class is described by Table 7-188

Table 7-188 Primary vtable for QDial

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDial
vfunc[0]:	QDial::metaObject() const
vfunc[1]:	QDial::className() const
vfunc[2]:	QDial::qt_cast(char const*)
vfunc[3]:	QDial::qt_invoke(int, QUObject*)
vfunc[4]:	QDial::qt_emit(int, QUObject*)
vfunc[5]:	QDial::qt_property(int, int, QVariant*)
vfunc[6]:	QDial::~~QDial()
vfunc[7]:	QDial::~~QDial()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)

vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)

vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDial::sizeHint() const
vfunc[59]:	QDial::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)

vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QDial::mousePressEvent(QMouseEvent*)
vfunc[70]:	QDial::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QDial::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QDial::wheelEvent(QWheelEvent*)
vfunc[74]:	QDial::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QDial::focusInEvent(QFocusEvent*)
vfunc[77]:	QDial::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QDial::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDial::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)

vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDial::setNotchTarget(double)
vfunc[111]:	QDial::setValue(int)
vfunc[112]:	QDial::setNotchesVisible(bool)
vfunc[113]:	QDial::setWrapping(bool)
vfunc[114]:	QDial::setTracking(bool)
vfunc[115]:	QDial::valueChange()
vfunc[116]:	QDial::rangeChange()
vfunc[117]:	QDial::repaintScreen(QRect const*)

Table 7-189 Secondary vtable for QDial

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDial
vfunc[0]:	non-virtual thunk to QDial::~~QDial()
vfunc[1]:	non-virtual thunk to QDial::~~QDial()

vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDvCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

Table 7-190 Secondary vtable for QDial

Base Offset	-200
Virtual Base Offset	0
RTTI	typeinfo for QDial
vfunc[0]:	non-virtual thunk to QDial::~~QDial()
vfunc[1]:	non-virtual thunk to QDial::~~QDial()
vfunc[2]:	non-virtual thunk to QDial::valueChange()
vfunc[3]:	non-virtual thunk to QDial::rangeChange()
vfunc[4]:	QRangeControl::stepChange()

The Run Time Type Information for the QDial class is described by Table 7-191

Table 7-191 typeinfo for QDial

Base Vtable	vtable for __cxxabiv1::__vmi_class _type_info	2 29698
Name	typeinfo name for QDial	
flags:	0	
basetype:	typeinfo for QWidget	
basetype:	typeinfo for QRangeControl	

7.2.1.79 Class data for QUrl

The virtual table for the QUrl class is described by Table 7-192

Table 7-192 Primary vtable for QUrl

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QUrl
vfunc[0]:	QUrl::~~QUrl()
vfunc[1]:	QUrl::~~QUrl()
vfunc[2]:	QUrl::setProtocol(QString const&)
vfunc[3]:	QUrl::setUser(QString const&)
vfunc[4]:	QUrl::setPassword(QString const&)
vfunc[5]:	QUrl::setHost(QString const&)
vfunc[6]:	QUrl::setPort(int)
vfunc[7]:	QUrl::setPath(QString const&)
vfunc[8]:	QUrl::setEncodedPathAndQuery(QString const&)
vfunc[9]:	QUrl::setQuery(QString const&)
vfunc[10]:	QUrl::setRef(QString const&)
vfunc[11]:	QUrl::addPath(QString const&)
vfunc[12]:	QUrl::setFileName(QString const&)
vfunc[13]:	QUrl::toString(bool, bool) const
vfunc[14]:	QUrl::cdUp()
vfunc[15]:	QUrl::reset()
vfunc[16]:	QUrl::parse(QString const&)

The Run Time Type Information for the QUrl class is described by Table 7-193

Table 7-193 typeinfo for QUrl

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QUrl

7.2.1.80 Class data for QListView

The virtual table for the QListView class is described by Table 7-194

Table 7-194 Primary vtable for QListView

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QListView
vfunc[0]:	QListView::metaObject() const
vfunc[1]:	QListView::className() const
vfunc[2]:	QListView::qt_cast(char const*)
vfunc[3]:	QListView::qt_invoke(int, QUObject*)
vfunc[4]:	QListView::qt_emit(int, QUObject*)
vfunc[5]:	QListView::qt_property(int, int, QVariant*)
vfunc[6]:	QListView::~~QListView()
vfunc[7]:	QListView::~~QListView()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QListView::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QScrollView::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap)

	const&)
vfunc[28]:	QListView::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QListView::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QListView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int,

	int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QListView::sizeHint() const
vfunc[59]:	QListView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QListView::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QListView::focusInEvent(QFocusEvent*)
vfunc[77]:	QListView::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)

vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QListView::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QListView::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QListView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QListView::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QScrollView::focusNextPrevChild(bool)

	ol)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QScrollView::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QListView::setContentsPos(int, int)
vfunc[127]:	QScrollView::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QListView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QListView::contentsMouseEvent(QMouseEvent*)
vfunc[130]:	QListView::contentsMouseReleaseEvent(QMouseEvent*)
vfunc[131]:	QListView::contentsMouseDoubleClickEvent(QMouseEvent*)

vfunc[132]:	QListView::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QListView::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QListView::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QListView::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QListView::contentsDropEvent(QDropEvent*)
vfunc[137]:	QScrollView::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QListView::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QListView::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)

vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)
vfunc[154]:	QListView::setTreeStepSize(int)
vfunc[155]:	QListView::insertItem(QListViewItem*)
vfunc[156]:	QListView::takeItem(QListViewItem*)
vfunc[157]:	QListView::removeItem(QListViewItem*)
vfunc[158]:	QListView::addColumn(QString const&, int)
vfunc[159]:	QListView::addColumn(QIconSet const&, QString const&, int)
vfunc[160]:	QListView::removeColumn(int)
vfunc[161]:	QListView::setColumnText(int, QString const&)
vfunc[162]:	QListView::setColumnText(int, QIconSet const&, QString const&)
vfunc[163]:	QListView::setColumnWidth(int, int)
vfunc[164]:	QListView::setColumnWidthMode(int, QListView::WidthMode)
vfunc[165]:	QListView::setColumnAlignment(int, int)
vfunc[166]:	QListView::setMultiSelection(bool)
vfunc[167]:	QListView::clearSelection()
vfunc[168]:	QListView::setSelected(QListViewItem*, bool)
vfunc[169]:	QListView::setOpen(QListViewItem*, bool)
vfunc[170]:	QListView::setCurrentItem(QListViewItem*)
vfunc[171]:	QListView::setAllColumnsShowFocus(bool)
vfunc[172]:	QListView::setItemMargin(int)
vfunc[173]:	QListView::setRootIsDecorated(bool)
vfunc[174]:	QListView::setSorting(int, bool)
vfunc[175]:	QListView::sort()
vfunc[176]:	QListView::setShowSortIndicator(bool)
vfunc[177]:	QListView::setShowToolTips(bool)

vfunc[178]:	QListView::setResizeMode(QListView::ResizeMode)
vfunc[179]:	QListView::setDefaultRenameAction(QListView::RenameAction)
vfunc[180]:	QListView::clear()
vfunc[181]:	QListView::invertSelection()
vfunc[182]:	QListView::selectAll(bool)
vfunc[183]:	QListView::dragObject()
vfunc[184]:	QListView::startDrag()
vfunc[185]:	QListView::paintEmptyArea(QPainter*, QRect const&)

Table 7-195 Secondary vtable for QListView

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QListView
vfunc[0]:	non-virtual thunk to QListView::~~QListView()
vfunc[1]:	non-virtual thunk to QListView::~~QListView()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QListView class is described by Table 7-196

Table 7-196 typeinfo for QListView

Base Vtable	vtable for
-------------	------------

	__cxxabiv1::__si_class_type_info
Name	typeinfo name for QListView
basetype:	typeinfo for QScrollView

7.2.1.81 Class data for QStylePlugin

The virtual table for the QStylePlugin class is described by Table 7-197

Table 7-197 Primary vtable for QStylePlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QStylePlugin
vfunc[0]:	QStylePlugin::metaObject() const
vfunc[1]:	QStylePlugin::className() const
vfunc[2]:	QStylePlugin::qt_cast(char const*)
vfunc[3]:	QStylePlugin::qt_invoke(int, QUObject*)
vfunc[4]:	QStylePlugin::qt_emit(int, QUObject*)
vfunc[5]:	QStylePlugin::qt_property(int, int, QVariant*)
vfunc[6]:	QStylePlugin::~~QStylePlugin()
vfunc[7]:	QStylePlugin::~~QStylePlugin()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char

	const*, QObject const*, char const*)
vfunc[21]:	__cxa_pure_virtual
vfunc[22]:	__cxa_pure_virtual

The Run Time Type Information for the QStylePlugin class is described by Table 7-198

Table 7-198 typeinfo for QStylePlugin

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStylePlugin
basetype:	typeinfo for QGPlugin

7.2.1.82 Class data for QFileDialog

The virtual table for the QFileDialog class is described by Table 7-199

Table 7-199 Primary vtable for QFileDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFileDialog
vfunc[0]:	QFileDialog::metaObject() const
vfunc[1]:	QFileDialog::className() const
vfunc[2]:	QFileDialog::qt_cast(char const*)
vfunc[3]:	QFileDialog::qt_invoke(int, QUObject*)
vfunc[4]:	QFileDialog::qt_emit(int, QUObject*)
vfunc[5]:	QFileDialog::qt_property(int, int, QVariant*)
vfunc[6]:	QFileDialog::~~QFileDialog()
vfunc[7]:	QFileDialog::~~QFileDialog()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QFileDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)

vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)

vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)

vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QFileDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QFileDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)

vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFileDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()
vfunc[113]:	QFileDialog::setSelectedFilter(QString const&)
vfunc[114]:	QFileDialog::setSelectedFilter(int)

Table 7-200 Secondary vtable for QFileDialog

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QFileDialog
vfunc[0]:	non-virtual thunk to QFileDialog::~~QFileDialog()
vfunc[1]:	non-virtual thunk to QFileDialog::~~QFileDialog()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)

vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QFileDialog class is described by Table 7-201

Table 7-201 typeinfo for QFileDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFileDialog
basetype:	typeinfo for QDialog

7.2.1.83 Class data for QHButtonGroup

The virtual table for the QHButtonGroup class is described by Table 7-202

Table 7-202 Primary vtable for QHButtonGroup

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHButtonGroup
vfunc[0]:	QHButtonGroup::metaObject() const
vfunc[1]:	QHButtonGroup::className() const
vfunc[2]:	QHButtonGroup::qt_cast(char const*)
vfunc[3]:	QHButtonGroup::qt_invoke(int, QUObject*)
vfunc[4]:	QHButtonGroup::qt_emit(int, QUObject*)
vfunc[5]:	QHButtonGroup::qt_property(int, int, QVariant*)
vfunc[6]:	QHButtonGroup::~~QHButtonGroup()
vfunc[7]:	QHButtonGroup::~~QHButtonGroup()
vfunc[8]:	QButtonGroup::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)

vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QGroupBox::childEvent(QChildEven t*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QGroupBox::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPi

	xmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QGroupBox::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWi

	dget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QGroupBox::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QGroupBox::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QGroupBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)

vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QGroupBox::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QGroupBox::setColumnLayout(int, Qt::Orientation)
vfunc[119]:	QGroupBox::setTitle(QString const&)

vfunc[120]:	QGroupBox::setAlignment(int)
vfunc[121]:	QButtonGroup::setExclusive(bool)
vfunc[122]:	QButtonGroup::setRadioButtonExclusive(bool)
vfunc[123]:	QButtonGroup::setButton(int)
vfunc[124]:	QButtonGroup::moveFocus(int)

Table 7-203 Secondary vtable for QHButtonGroup

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QHButtonGroup
vfunc[0]:	non-virtual thunk to QHButtonGroup::~~QHButtonGroup()
vfunc[1]:	non-virtual thunk to QHButtonGroup::~~QHButtonGroup()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QHButtonGroup class is described by Table 7-204

Table 7-204 typeinfo for QHButtonGroup

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHButtonGroup
basetype:	typeinfo for QButtonGroup

7.2.1.84 Class data for QColorDrag

The virtual table for the QColorDrag class is described by Table 7-205

Table 7-205 Primary vtable for QColorDrag

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QColorDrag
vfunc[0]:	QColorDrag::metaObject() const
vfunc[1]:	QColorDrag::className() const
vfunc[2]:	QColorDrag::qt_cast(char const*)
vfunc[3]:	QColorDrag::qt_invoke(int, QUObject*)
vfunc[4]:	QColorDrag::qt_emit(int, QUObject*)
vfunc[5]:	QColorDrag::qt_property(int, int, QVariant*)
vfunc[6]:	QColorDrag::~~QColorDrag()
vfunc[7]:	QColorDrag::~~QColorDrag()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QDragObject::setPixmap(QPixmap)
vfunc[22]:	QDragObject::setPixmap(QPixmap, QPoint const&)

vfunc[23]:	QDragObject::drag(QDragObject::DragMode)
vfunc[24]:	QStoredDrag::setEncodedData(QMemArray<char> const&)
vfunc[25]:	QStoredDrag::format(int) const
vfunc[26]:	QStoredDrag::encodedData(char const*) const

Table 7-206 Secondary vtable for QColorDrag

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QColorDrag
vfunc[0]:	non-virtual thunk to QColorDrag::~QColorDrag()
vfunc[1]:	non-virtual thunk to QColorDrag::~QColorDrag()
vfunc[2]:	non-virtual thunk to QStoredDrag::format(int) const
vfunc[3]:	QMimeSource::provides(char const*) const
vfunc[4]:	non-virtual thunk to QStoredDrag::encodedData(char const*) const

The Run Time Type Information for the QColorDrag class is described by Table 7-207

Table 7-207 typeinfo for QColorDrag

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QColorDrag
basetype:	typeinfo for QStoredDrag

7.2.1.85 Class data for QDesktopWidget

The virtual table for the QDesktopWidget class is described by Table 7-208

Table 7-208 Primary vtable for QDesktopWidget

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDesktopWidget
vfunc[0]:	QDesktopWidget::metaObject() const
vfunc[1]:	QDesktopWidget::className() const

vfunc[2]:	QDesktopWidget::qt_cast(char const*)
vfunc[3]:	QDesktopWidget::qt_invoke(int, QUObject*)
vfunc[4]:	QDesktopWidget::qt_emit(int, QUObject*)
vfunc[5]:	QDesktopWidget::qt_property(int, int, QVariant*)
vfunc[6]:	QDesktopWidget::~~QDesktopWidget()
vfunc[7]:	QDesktopWidget::~~QDesktopWidget()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QDesktopWidget::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)

vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int,

	int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)

vfunc[82]:	QDesktopWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int,

	int, int, bool, QFont*)
--	-------------------------

Table 7-209 Secondary vtable for QDesktopWidget

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDesktopWidget
vfunc[0]:	non-virtual thunk to QDesktopWidget::~~QDesktopWidget()
vfunc[1]:	non-virtual thunk to QDesktopWidget::~~QDesktopWidget()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QDesktopWidget class is described by Table 7-210

Table 7-210 typeinfo for QDesktopWidget

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDesktopWidget
basetype:	typeinfo for QWidget

7.2.1.86 Class data for QSqlQuery

The virtual table for the QSqlQuery class is described by Table 7-211

Table 7-211 Primary vtable for QSqlQuery

Base Offset	0
-------------	---

Virtual Base Offset	0
RTTI	typeinfo for QSqlQuery
vfunc[0]:	QSqlQuery::~~QSqlQuery()
vfunc[1]:	QSqlQuery::~~QSqlQuery()
vfunc[2]:	QSqlQuery::exec(QString const&)
vfunc[3]:	QSqlQuery::value(int) const
vfunc[4]:	QSqlQuery::seek(int, bool)
vfunc[5]:	QSqlQuery::next()
vfunc[6]:	QSqlQuery::prev()
vfunc[7]:	QSqlQuery::first()
vfunc[8]:	QSqlQuery::last()
vfunc[9]:	QSqlQuery::beforeSeek()
vfunc[10]:	QSqlQuery::afterSeek()

The Run Time Type Information for the QSqlQuery class is described by Table 7-212

Table 7-212 typeinfo for QSqlQuery

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QSqlQuery

7.2.1.87 Class data for QUtf16Codec

The virtual table for the QUtf16Codec class is described by Table 7-213

Table 7-213 Primary vtable for QUtf16Codec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QUtf16Codec
vfunc[0]:	QUtf16Codec::~~QUtf16Codec()
vfunc[1]:	QUtf16Codec::~~QUtf16Codec()
vfunc[2]:	QUtf16Codec::name() const
vfunc[3]:	QTextCodec::mimeTypeName() const
vfunc[4]:	QUtf16Codec::mibEnum() const
vfunc[5]:	QUtf16Codec::makeDecoder() const
vfunc[6]:	QUtf16Codec::makeEncoder() const
vfunc[7]:	QTextCodec::toUnicode(char const*, int) const

vfunc[8]:	QTextCodec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QUtf16Codec::heuristicContentMatch(char const*, int) const
vfunc[12]:	QTextCodec::heuristicNameMatch(char const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode(QString const&, int) const

The Run Time Type Information for the QUtf16Codec class is described by Table 7-214

Table 7-214 typeinfo for QUtf16Codec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QUtf16Codec
basetype:	typeinfo for QTextCodec

7.2.1.88 Class data for QObject

The virtual table for the QObject class is described by Table 7-215

Table 7-215 Primary vtable for QObject

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QObject
vfunc[0]:	QObject::metaObject() const
vfunc[1]:	QObject::className() const
vfunc[2]:	QObject::qt_cast(char const*)
vfunc[3]:	QObject::qt_invoke(int, QUObject*)
vfunc[4]:	QObject::qt_emit(int, QUObject*)
vfunc[5]:	QObject::qt_property(int, int, QVariant*)
vfunc[6]:	QObject::~~QObject()
vfunc[7]:	QObject::~~QObject()
vfunc[8]:	QObject::event(QEvent*)

vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QObject class is described by Table 7-216

Table 7-216 typeinfo for QObject

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QObject
basetype:	typeinfo for Qt

7.2.1.89 Class data for QFile

The virtual table for the QFile class is described by Table 7-217

Table 7-217 Primary vtable for QFile

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFile
vfunc[0]:	QFile::~~QFile()
vfunc[1]:	QFile::~~QFile()
vfunc[2]:	QFile::open(int)
vfunc[3]:	QFile::close()
vfunc[4]:	QFile::flush()
vfunc[5]:	QFile::size() const

vfunc[6]:	QFile::at() const
vfunc[7]:	QFile::at(unsigned long)
vfunc[8]:	QFile::atEnd() const
vfunc[9]:	QFile::readBlock(char*, unsigned long)
vfunc[10]:	QFile::writeBlock(char const*, unsigned long)
vfunc[11]:	QFile::readLine(char*, unsigned long)
vfunc[12]:	QIODevice::readAll()
vfunc[13]:	QFile::getch()
vfunc[14]:	QFile::putch(int)
vfunc[15]:	QFile::ungetch(int)

The Run Time Type Information for the QFile class is described by Table 7-218

Table 7-218 typeinfo for QFile

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFile
basetype:	typeinfo for QIODevice

7.2.1.90 Class data for QDomDocumentType

The virtual table for the QDomDocumentType class is described by Table 7-219

Table 7-219 Primary vtable for QDomDocumentType

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomDocumentType
vfunc[0]:	QDomDocumentType::~~QDomDocumentType()
vfunc[1]:	QDomDocumentType::~~QDomDocumentType()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)

vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomDocumentType::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomDocumentType::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference()

	const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction() const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const
vfunc[41]:	QDomDocumentType::name() const
vfunc[42]:	QDomDocumentType::entities() const
vfunc[43]:	QDomDocumentType::notations() const
vfunc[44]:	QDomDocumentType::publicId() const
vfunc[45]:	QDomDocumentType::systemId() const
vfunc[46]:	QDomDocumentType::internalSubse t() const

The Run Time Type Information for the QDomDocumentType class is described by Table 7-220

Table 7-220 typeinfo for QDomDocumentType

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomDocumentType
basetype:	typeinfo for QDomNode

7.2.1.91 Class data for QListBoxItem

The virtual table for the QListBoxItem class is described by Table 7-221

Table 7-221 Primary vtable for QListBoxItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QListBoxItem
vfunc[0]:	QListBoxItem::~~QListBoxItem()
vfunc[1]:	QListBoxItem::~~QListBoxItem()
vfunc[2]:	QListBoxItem::text() const
vfunc[3]:	QListBoxItem::pixmap() const

vfunc[4]:	QListBoxItem::height(QListBox const*) const
vfunc[5]:	QListBoxItem::width(QListBox const*) const
vfunc[6]:	QListBoxItem::rtti() const
vfunc[7]:	__cxa_pure_virtual
vfunc[8]:	QListBoxItem::setText(QString const&)

The Run Time Type Information for the QListBoxItem class is described by Table 7-222

Table 7-222 typeinfo for QListBoxItem

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QListBoxItem

7.2.1.92 Class data for QDragResponseEvent

The virtual table for the QDragResponseEvent class is described by Table 7-223

Table 7-223 Primary vtable for QDragResponseEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDragResponseEvent
vfunc[0]:	QDragResponseEvent::~~QDragResponseEvent()
vfunc[1]:	QDragResponseEvent::~~QDragResponseEvent()

The Run Time Type Information for the QDragResponseEvent class is described by Table 7-224

Table 7-224 typeinfo for QDragResponseEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDragResponseEvent
basetype:	typeinfo for QEvent

7.2.1.93 Class data for QDomDocument

The virtual table for the QDomDocument class is described by Table 7-225

Table 7-225 Primary vtable for QDomDocument

Base Offset	0
-------------	---

Virtual Base Offset	0
RTTI	typeinfo for QDomDocument
vfunc[0]:	QDomDocument::~~QDomDocument()
vfunc[1]:	QDomDocument::~~QDomDocument()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomDocument::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)

vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomDocument::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction()) const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const

The Run Time Type Information for the QDomDocument class is described by Table 7-226

Table 7-226 typeinfo for QDomDocument

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomDocument
basetype:	typeinfo for QDomNode

7.2.1.94 Class data for QTextCodecPlugin

The virtual table for the QTextCodecPlugin class is described by Table 7-227

Table 7-227 Primary vtable for QTextCodecPlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextCodecPlugin
vfunc[0]:	QTextCodecPlugin::metaObject() const

vfunc[1]:	QTextCodecPlugin::className() const
vfunc[2]:	QTextCodecPlugin::qt_cast(char const*)
vfunc[3]:	QTextCodecPlugin::qt_invoke(int, QObject*)
vfunc[4]:	QTextCodecPlugin::qt_emit(int, QObject*)
vfunc[5]:	QTextCodecPlugin::qt_property(int, int, QVariant*)
vfunc[6]:	QTextCodecPlugin::~~QTextCodecPlu gin()
vfunc[7]:	QTextCodecPlugin::~~QTextCodecPlu gin()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	__cxa_pure_virtual
vfunc[22]:	__cxa_pure_virtual
vfunc[23]:	__cxa_pure_virtual
vfunc[24]:	__cxa_pure_virtual

The Run Time Type Information for the QTextCodecPlugin class is described by Table 7-228

Table 7-228 typeinfo for QTextCodecPlugin

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextCodecPlugin
basetype:	typeinfo for QGPlugin

7.2.1.95 Class data for QWidgetPlugin

The virtual table for the QWidgetPlugin class is described by Table 7-229

Table 7-229 Primary vtable for QWidgetPlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWidgetPlugin
vfunc[0]:	QWidgetPlugin::metaObject() const
vfunc[1]:	QWidgetPlugin::className() const
vfunc[2]:	QWidgetPlugin::qt_cast(char const*)
vfunc[3]:	QWidgetPlugin::qt_invoke(int, QUObject*)
vfunc[4]:	QWidgetPlugin::qt_emit(int, QUObject*)
vfunc[5]:	QWidgetPlugin::qt_property(int, int, QVariant*)
vfunc[6]:	QWidgetPlugin::~~QWidgetPlugin()
vfunc[7]:	QWidgetPlugin::~~QWidgetPlugin()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char

	const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	__cxa_pure_virtual
vfunc[22]:	__cxa_pure_virtual
vfunc[23]:	QWidgetPlugin::group(QString const&) const
vfunc[24]:	QWidgetPlugin::iconSet(QString const&) const
vfunc[25]:	QWidgetPlugin::includeFile(QString const&) const
vfunc[26]:	QWidgetPlugin::toolTip(QString const&) const
vfunc[27]:	QWidgetPlugin::whatsThis(QString const&) const
vfunc[28]:	QWidgetPlugin::isContainer(QString const&) const

The Run Time Type Information for the QWidgetPlugin class is described by Table 7-230

Table 7-230 typeinfo for QWidgetPlugin

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWidgetPlugin
basetype:	typeinfo for QGPlugin

7.2.1.96 Class data for QScrollBar

The virtual table for the QScrollBar class is described by Table 7-231

Table 7-231 Primary vtable for QScrollBar

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QScrollBar
vfunc[0]:	QScrollBar::metaObject() const
vfunc[1]:	QScrollBar::className() const
vfunc[2]:	QScrollBar::qt_cast(char const*)
vfunc[3]:	QScrollBar::qt_invoke(int, QUObject*)
vfunc[4]:	QScrollBar::qt_emit(int, QUObject*)
vfunc[5]:	QScrollBar::qt_property(int, int,

	QVariant*)
vfunc[6]:	QScrollBar::~~QScrollBar()
vfunc[7]:	QScrollBar::~~QScrollBar()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QScrollBar::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor

	const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QScrollBar::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QScrollBar::setSizePolicy(QSizePolicy)

	y)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollBar::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollBar::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollBar::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollBar::wheelEvent(QWheelEvent*)
vfunc[74]:	QScrollBar::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QScrollBar::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QScrollBar::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollBar::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEve

	nt*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QScrollBar::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollBar::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QScrollBar::setOrientation(Qt::Orientation)
vfunc[111]:	QScrollBar::setTracking(bool)
vfunc[112]:	QScrollBar::valueChange()
vfunc[113]:	QScrollBar::stepChange()
vfunc[114]:	QScrollBar::rangeChange()

Table 7-232 Secondary vtable for QScrollBar

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QScrollBar
vfunc[0]:	non-virtual thunk to QScrollBar::~~QScrollBar()
vfunc[1]:	non-virtual thunk to QScrollBar::~~QScrollBar()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

Table 7-233 Secondary vtable for QScrollBar

Base Offset	-200
Virtual Base Offset	0
RTTI	typeinfo for QScrollBar
vfunc[0]:	non-virtual thunk to QScrollBar::~~QScrollBar()
vfunc[1]:	non-virtual thunk to QScrollBar::~~QScrollBar()
vfunc[2]:	non-virtual thunk to QScrollBar::valueChange()
vfunc[3]:	non-virtual thunk to QScrollBar::rangeChange()
vfunc[4]:	non-virtual thunk to QScrollBar::stepChange()

The Run Time Type Information for the QScrollBar class is described by Table 7-234

Table 7-234 typeinfo for QScrollBar

Base Vtable	vtable for __cxxabiv1::__vmi_class _type_info	2
Name	typeinfo name for QScrollBar	
flags:	0	
basetype:	typeinfo for QWidget	
basetype:	typeinfo for QRangeControl	29698

7.2.1.97 Class data for QBitmap

The virtual table for the QBitmap class is described by Table 7-235

Table 7-235 Primary vtable for QBitmap

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QBitmap
vfunc[0]:	QBitmap::~~QBitmap()
vfunc[1]:	QBitmap::~~QBitmap()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPaintDeviceCmdParam*)
vfunc[8]:	QPixmap::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const
vfunc[11]:	QPixmap::detach()

The Run Time Type Information for the QBitmap class is described by Table 7-236

Table 7-236 typeinfo for QBitmap

Base Vtable	vtable for
-------------	------------

	__cxxabiv1::__si_class_type_info
Name	typeinfo name for QPixmap
basetype:	typeinfo for QPixmap

7.2.1.98 Class data for QIconFactory

The virtual table for the QIconFactory class is described by Table 7-237

Table 7-237 Primary vtable for QIconFactory

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIconFactory
vfunc[0]:	QIconFactory::~~QIconFactory()
vfunc[1]:	QIconFactory::~~QIconFactory()
vfunc[2]:	QIconFactory::createPixmap(QIconSet const&, QIconSet::Size, QIconSet::Mode, QIconSet::State)

The Run Time Type Information for the QIconFactory class is described by Table 7-238

Table 7-238 typeinfo for QIconFactory

Base Vtable	vtable for __cxxabiv1::__vmi_class_type_info	1024
Name	typeinfo name for QIconFactory	
flags:	0	
basetype:	typeinfo for QShared	

7.2.1.99 Class data for QSpinBox

The virtual table for the QSpinBox class is described by Table 7-239

Table 7-239 Primary vtable for QSpinBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSpinBox
vfunc[0]:	QSpinBox::metaObject() const
vfunc[1]:	QSpinBox::className() const
vfunc[2]:	QSpinBox::qt_cast(char const*)
vfunc[3]:	QSpinBox::qt_invoke(int, QUObject*)
vfunc[4]:	QSpinBox::qt_emit(int, QUObject*)

vfunc[5]:	QSpinBox::qt_property(int, int, QVariant*)
vfunc[6]:	QSpinBox::~~QSpinBox()
vfunc[7]:	QSpinBox::~~QSpinBox()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QSpinBox::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QSpinBox::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)

vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QSpinBox::sizeHint() const
vfunc[59]:	QSpinBox::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const

vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QSpinBox::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QSpinBox::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QSpinBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)

	nt*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QSpinBox::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QSpinBox::prefix() const
vfunc[111]:	QSpinBox::suffix() const
vfunc[112]:	QSpinBox::cleanText() const
vfunc[113]:	QSpinBox::setSpecialValueText(QString const&)
vfunc[114]:	QSpinBox::setWrapping(bool)

vfunc[115]:	QSpinBox::setButtonSymbols(QSpinBox::ButtonSymbols)
vfunc[116]:	QSpinBox::setValidator(QValidator const*)
vfunc[117]:	QSpinBox::setValue(int)
vfunc[118]:	QSpinBox::setPrefix(QString const&)
vfunc[119]:	QSpinBox::setSuffix(QString const&)
vfunc[120]:	QSpinBox::stepUp()
vfunc[121]:	QSpinBox::stepDown()
vfunc[122]:	QSpinBox::selectAll()
vfunc[123]:	QSpinBox::mapValueToText(int)
vfunc[124]:	QSpinBox::mapTextToValue(bool*)
vfunc[125]:	QSpinBox::updateDisplay()
vfunc[126]:	QSpinBox::interpretText()
vfunc[127]:	QSpinBox::valueChange()
vfunc[128]:	QSpinBox::rangeChange()

Table 7-240 Secondary vtable for QSpinBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QSpinBox
vfunc[0]:	non-virtual thunk to QSpinBox::~~QSpinBox()
vfunc[1]:	non-virtual thunk to QSpinBox::~~QSpinBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const

vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const
------------	---

Table 7-241 Secondary vtable for QSpinBox

Base Offset	-200
Virtual Base Offset	0
RTTI	typeinfo for QSpinBox
vfunc[0]:	non-virtual thunk to QSpinBox::~~QSpinBox()
vfunc[1]:	non-virtual thunk to QSpinBox::~~QSpinBox()
vfunc[2]:	non-virtual thunk to QSpinBox::valueChange()
vfunc[3]:	non-virtual thunk to QSpinBox::rangeChange()
vfunc[4]:	QRangeControl::stepChange()

The Run Time Type Information for the QSpinBox class is described by Table 7-242

Table 7-242 typeinfo for QSpinBox

Base Vtable	vtable for __cxxabiv1::__vmi_class _type_info	2
Name	typeinfo name for QSpinBox	
flags:	0	
basetype:	typeinfo for QWidget	
basetype:	typeinfo for QRangeControl	29698

7.2.1.100 Class data for QLibrary

The virtual table for the QLibrary class is described by Table 7-243

Table 7-243 Primary vtable for QLibrary

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLibrary
vfunc[0]:	QLibrary::~~QLibrary()
vfunc[1]:	QLibrary::~~QLibrary()
vfunc[2]:	QLibrary::unload()

The Run Time Type Information for the QLibrary class is described by Table 7-244

Table 7-244 typeinfo for QLibrary

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QLibrary

7.2.1.101 Class data for QEucKrCodec

The virtual table for the QEucKrCodec class is described by Table 7-245

Table 7-245 Primary vtable for QEucKrCodec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QEucKrCodec
vfunc[0]:	QEucKrCodec::~~QEucKrCodec()
vfunc[1]:	QEucKrCodec::~~QEucKrCodec()
vfunc[2]:	QEucKrCodec::name() const
vfunc[3]:	QEucKrCodec::mimeType() const
vfunc[4]:	QEucKrCodec::mibEnum() const
vfunc[5]:	QEucKrCodec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QEucKrCodec::toUnicode(char const*, int) const
vfunc[8]:	QEucKrCodec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QEucKrCodec::heuristicContentMatc h(char const*, int) const
vfunc[12]:	QEucKrCodec::heuristicNameMatch(char const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode(QString const&, int) const

The Run Time Type Information for the QEucKrCodec class is described by Table 7-246

Table 7-246 typeinfo for QEucKrCodec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QEucKrCodec
basetype:	typeinfo for QTextCodec

7.2.1.102 Class data for QWidgetStack

The virtual table for the QWidgetStack class is described by Table 7-247

Table 7-247 Primary vtable for QWidgetStack

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWidgetStack
vfunc[0]:	QWidgetStack::metaObject() const
vfunc[1]:	QWidgetStack::className() const
vfunc[2]:	QWidgetStack::qt_cast(char const*)
vfunc[3]:	QWidgetStack::qt_invoke(int, QUObject*)
vfunc[4]:	QWidgetStack::qt_emit(int, QUObject*)
vfunc[5]:	QWidgetStack::qt_property(int, int, QVariant*)
vfunc[6]:	QWidgetStack::~~QWidgetStack()
vfunc[7]:	QWidgetStack::~~QWidgetStack()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QWidgetStack::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)

vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)

vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidgetStack::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidgetStack::sizeHint() const
vfunc[59]:	QWidgetStack::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent)

	*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidgetStack::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)

vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QWidgetStack::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QWidgetStack::frameChanged()
vfunc[118]:	QWidgetStack::setChildGeometries()

Table 7-248 Secondary vtable for QWidgetStack

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QWidgetStack
vfunc[0]:	non-virtual thunk to QWidgetStack::~~QWidgetStack()
vfunc[1]:	non-virtual thunk to QWidgetStack::~~QWidgetStack()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe

	viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QWidgetStack class is described by Table 7-249

Table 7-249 typeinfo for QWidgetStack

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWidgetStack
basetype:	typeinfo for QFrame

7.2.1.103 Class data for QLabel

The virtual table for the QLabel class is described by Table 7-250

Table 7-250 Primary vtable for QLabel

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLabel
vfunc[0]:	QLabel::metaObject() const
vfunc[1]:	QLabel::className() const
vfunc[2]:	QLabel::qt_cast(char const*)
vfunc[3]:	QLabel::qt_invoke(int, QUObject*)
vfunc[4]:	QLabel::qt_emit(int, QUObject*)
vfunc[5]:	QLabel::qt_property(int, int, QVariant*)
vfunc[6]:	QLabel::~QLabel()
vfunc[7]:	QLabel::~QLabel()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)

vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QLabel::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPi xmap const&)
vfunc[38]:	QWidget::setCaption(QString

	const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QLabel::sizeHint() const
vfunc[59]:	QLabel::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QLabel::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const

vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QLabel::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)

vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QLabel::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QLabel::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QLabel::setAlignment(int)
vfunc[119]:	QLabel::setAutoResize(bool)
vfunc[120]:	QLabel::setBuddy(QWidget*)
vfunc[121]:	QLabel::setText(QString const&)
vfunc[122]:	QLabel::setPixmap(QPixmap const&)
vfunc[123]:	QLabel::setPicture(QPicture const&)
vfunc[124]:	QLabel::setMovie(QMovie const&)

vfunc[125]:	QLabel::setNum(int)
vfunc[126]:	QLabel::setNum(double)

Table 7-251 Secondary vtable for QLabel

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QLabel
vfunc[0]:	non-virtual thunk to QLabel::~~QLabel()
vfunc[1]:	non-virtual thunk to QLabel::~~QLabel()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QLabel class is described by Table 7-252

Table 7-252 typeinfo for QLabel

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QLabel
basetype:	typeinfo for QFrame

7.2.1.104 Class data for QStyleSheet

The virtual table for the QStyleSheet class is described by Table 7-253

Table 7-253 Primary vtable for QStyleSheet

Base Offset	0
Virtual Base Offset	0

RTTI	typeid for QStyleSheet
vfunc[0]:	QStyleSheet::metaObject() const
vfunc[1]:	QStyleSheet::className() const
vfunc[2]:	QStyleSheet::qt_cast(char const*)
vfunc[3]:	QStyleSheet::qt_invoke(int, QUObject*)
vfunc[4]:	QStyleSheet::qt_emit(int, QUObject*)
vfunc[5]:	QStyleSheet::qt_property(int, int, QVariant*)
vfunc[6]:	QStyleSheet::~~QStyleSheet()
vfunc[7]:	QStyleSheet::~~QStyleSheet()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QStyleSheet::tag(QString const&, QMap<QString, QString> const&, QString const&, QMimeSourceFactory const&, bool, QTextDocument*) const
vfunc[22]:	QStyleSheet::scaleFont(QFont&, int) const
vfunc[23]:	QStyleSheet::error(QString const&) const

The Run Time Type Information for the QStyleSheet class is described by Table 7-254

Table 7-254 typeinfo for QStyleSheet

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStyleSheet
basetype:	typeinfo for QObject

7.2.1.105 Class data for QCustomEvent

The virtual table for the QCustomEvent class is described by Table 7-255

Table 7-255 Primary vtable for QCustomEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCustomEvent
vfunc[0]:	QCustomEvent::~~QCustomEvent()
vfunc[1]:	QCustomEvent::~~QCustomEvent()

The Run Time Type Information for the QCustomEvent class is described by Table 7-256

Table 7-256 typeinfo for QCustomEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCustomEvent
basetype:	typeinfo for QEvent

7.2.1.106 Class data for QListBoxPixmap

The virtual table for the QListBoxPixmap class is described by Table 7-257

Table 7-257 Primary vtable for QListBoxPixmap

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QListBoxPixmap
vfunc[0]:	QListBoxPixmap::~~QListBoxPixmap()
vfunc[1]:	QListBoxPixmap::~~QListBoxPixmap()
vfunc[2]:	QListBoxItem::text() const
vfunc[3]:	QListBoxPixmap::pixmap() const
vfunc[4]:	QListBoxPixmap::height(QListBox

	const*) const
vfunc[5]:	QListBoxPixmap::width(QListBox const*) const
vfunc[6]:	QListBoxPixmap::rtti() const
vfunc[7]:	QListBoxPixmap::paint(QPainter*)
vfunc[8]:	QListBoxItem::setText(QString const&)

The Run Time Type Information for the QListBoxPixmap class is described by Table 7-258

Table 7-258 typeinfo for QListBoxPixmap

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QListBoxPixmap
basetype:	typeinfo for QListBoxItem

7.2.1.107 Class data for QDragManager

The virtual table for the QDragManager class is described by Table 7-259

Table 7-259 Primary vtable for QDragManager

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDragManager
vfunc[0]:	QDragManager::metaObject() const
vfunc[1]:	QDragManager::className() const
vfunc[2]:	QDragManager::qt_cast(char const*)
vfunc[3]:	QDragManager::qt_invoke(int, QUObject*)
vfunc[4]:	QDragManager::qt_emit(int, QUObject*)
vfunc[5]:	QDragManager::qt_property(int, int, QVariant*)
vfunc[6]:	QDragManager::~~QDragManager()
vfunc[7]:	QDragManager::~~QDragManager()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QDragManager::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)

vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QDragManager::timerEvent(QTimer Event*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QDragManager class is described by Table 7-260

Table 7-260 typeinfo for QDragManager

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDragManager
basetype:	typeinfo for QObject

7.2.1.108 Class data for QDomAttr

The virtual table for the QDomAttr class is described by Table 7-261

Table 7-261 Primary vtable for QDomAttr

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomAttr
vfunc[0]:	QDomAttr::~~QDomAttr()
vfunc[1]:	QDomAttr::~~QDomAttr()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)

vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomAttr::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomAttr::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const

vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction()) const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const
vfunc[41]:	QDomAttr::name() const
vfunc[42]:	QDomAttr::specified() const
vfunc[43]:	QDomAttr::ownerElement() const
vfunc[44]:	QDomAttr::value() const
vfunc[45]:	QDomAttr::setValue(QString const&)

The Run Time Type Information for the QDomAttr class is described by Table 7-262

Table 7-262 typeinfo for QDomAttr

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomAttr
basetype:	typeinfo for QDomNode

7.2.1.109 Class data for QWhatsThis

The virtual table for the QWhatsThis class is described by Table 7-263

Table 7-263 Primary vtable for QWhatsThis

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWhatsThis
vfunc[0]:	QWhatsThis::~~QWhatsThis()
vfunc[1]:	QWhatsThis::~~QWhatsThis()
vfunc[2]:	QWhatsThis::text(QPoint const&)
vfunc[3]:	QWhatsThis::clicked(QString const&)

The Run Time Type Information for the QWhatsThis class is described by Table 7-264

Table 7-264 typeinfo for QWhatsThis

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWhatsThis

basetype:	typeinfo for Qt
-----------	-----------------

7.2.1.110 Class data for QDomNodeList

The virtual table for the QDomNodeList class is described by Table 7-265

Table 7-265 Primary vtable for QDomNodeList

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomNodeList
vfunc[0]:	QDomNodeList::~~QDomNodeList()
vfunc[1]:	QDomNodeList::~~QDomNodeList()
vfunc[2]:	QDomNodeList::item(int) const
vfunc[3]:	QDomNodeList::length() const

The Run Time Type Information for the QDomNodeList class is described by Table 7-266

Table 7-266 typeinfo for QDomNodeList

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QDomNodeList

7.2.1.111 Class data for QJisCodec

The virtual table for the QJisCodec class is described by Table 7-267

Table 7-267 Primary vtable for QJisCodec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QJisCodec
vfunc[0]:	QJisCodec::~~QJisCodec()
vfunc[1]:	QJisCodec::~~QJisCodec()
vfunc[2]:	QJisCodec::name() const
vfunc[3]:	QJisCodec::mimeType() const
vfunc[4]:	QJisCodec::mibEnum() const
vfunc[5]:	QJisCodec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QJisCodec::toUnicode(char const*, int) const
vfunc[8]:	QJisCodec::fromUnicode(QString const&, int&) const

vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QJisCodec::heuristicContentMatch(c har const*, int) const
vfunc[12]:	QJisCodec::heuristicNameMatch(cha r const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode(QString const&, int) const

The Run Time Type Information for the QJisCodec class is described by Table 7-268

Table 7-268 typeinfo for QJisCodec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QJisCodec
basetype:	typeinfo for QTextCodec

7.2.1.112 Class data for QPointArray

The virtual table for the QPointArray class is described by Table 7-269

Table 7-269 Primary vtable for QPointArray

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPointArray
vfunc[0]:	QPointArray::~~QPointArray()
vfunc[1]:	QPointArray::~~QPointArray()
vfunc[2]:	QMemArray<QPoint>::detach()
vfunc[3]:	QGArray::newData()
vfunc[4]:	QGArray::deleteData(QGArray::arra y_data*)

The Run Time Type Information for the QPointArray class is described by Table 7-270

Table 7-270 typeinfo for QPointArray

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPointArray

basetype:	typeinfo for QMemArray<QPoint>
-----------	--------------------------------

7.2.1.113 Class data for QMultiLineEdit

The virtual table for the QMultiLineEdit class is described by Table 7-271

Table 7-271 Primary vtable for QMultiLineEdit

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMultiLineEdit
vfunc[0]:	QMultiLineEdit::metaObject() const
vfunc[1]:	QMultiLineEdit::className() const
vfunc[2]:	QMultiLineEdit::qt_cast(char const*)
vfunc[3]:	QMultiLineEdit::qt_invoke(int, QUObject*)
vfunc[4]:	QMultiLineEdit::qt_emit(int, QUObject*)
vfunc[5]:	QMultiLineEdit::qt_property(int, int, QVariant*)
vfunc[6]:	QMultiLineEdit::~~QMultiLineEdit()
vfunc[7]:	QMultiLineEdit::~~QMultiLineEdit()
vfunc[8]:	QTextEdit::event(QEvent*)
vfunc[9]:	QTextEdit::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QTextEdit::setEnabled(bool)

vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QTextEdit::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QTextEdit::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPi xmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::F ocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()

vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QTextEdit::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QTextEdit::sizeHint() const
vfunc[59]:	QScrollView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QTextEdit::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QTextEdit::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)

vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QTextEdit::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QTextEdit::imStartEvent(QIMEvent*)
vfunc[86]:	QTextEdit::imComposeEvent(QIMEvent*)
vfunc[87]:	QTextEdit::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QTextEdit::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const

vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QTextEdit::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QTextEdit::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QTextEdit::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)

vfunc[129]:	QTextEdit::contentsMouseEvent(QMouseEvent*)
vfunc[130]:	QTextEdit::contentsMouseReleaseEvent(QMouseEvent*)
vfunc[131]:	QTextEdit::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QTextEdit::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QTextEdit::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QTextEdit::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QTextEdit::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QTextEdit::contentsDropEvent(QDropEvent*)
vfunc[137]:	QTextEdit::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QTextEdit::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QTextEdit::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMouseEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)

vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)
vfunc[154]:	QTextEdit::find(QString const&, bool, bool, bool, int*, int*)
vfunc[155]:	QTextEdit::getFormat(int, int, QFont*, QColor*, QTextEdit::VerticalAlignment*)
vfunc[156]:	QTextEdit::getParagraphFormat(int, QFont*, QColor*, QTextEdit::VerticalAlignment*, int*, QStyleSheetItem::DisplayMode*, QStyleSheetItem::ListStyle*, int*)
vfunc[157]:	QTextEdit::setMimeSourceFactory(QMimeSourceFactory*)
vfunc[158]:	QTextEdit::setStyleSheet(QStyleSheet*)
vfunc[159]:	QTextEdit::scrollToAnchor(QString const&)
vfunc[160]:	QTextEdit::setPaper(QBrush const&)
vfunc[161]:	QTextEdit::setLinkUnderline(bool)
vfunc[162]:	QTextEdit::setWordWrap(QTextEdit::WordWrap)
vfunc[163]:	QTextEdit::setWrapColumnOrWidth(int)
vfunc[164]:	QTextEdit::setWrapPolicy(QTextEdit::WrapPolicy)
vfunc[165]:	QTextEdit::copy()
vfunc[166]:	QTextEdit::append(QString const&)
vfunc[167]:	QTextEdit::setText(QString const&, QString const&)
vfunc[168]:	QTextEdit::setTextFormat(Qt::TextFormat)
vfunc[169]:	QTextEdit::selectAll(bool)
vfunc[170]:	QTextEdit::setTabStopWidth(int)
vfunc[171]:	QTextEdit::zoomIn(int)

vfunc[172]:	QTextEdit::zoomIn()
vfunc[173]:	QTextEdit::zoomOut(int)
vfunc[174]:	QTextEdit::zoomOut()
vfunc[175]:	QTextEdit::zoomTo(int)
vfunc[176]:	QTextEdit::sync()
vfunc[177]:	QTextEdit::setReadOnly(bool)
vfunc[178]:	QTextEdit::undo()
vfunc[179]:	QTextEdit::redo()
vfunc[180]:	QTextEdit::cut()
vfunc[181]:	QTextEdit::paste()
vfunc[182]:	QTextEdit::pasteSubType(QCString const&)
vfunc[183]:	QTextEdit::clear()
vfunc[184]:	QTextEdit::del()
vfunc[185]:	QTextEdit::indent()
vfunc[186]:	QTextEdit::setItalic(bool)
vfunc[187]:	QTextEdit::setBold(bool)
vfunc[188]:	QTextEdit::setUnderline(bool)
vfunc[189]:	QTextEdit::setFamily(QString const&)
vfunc[190]:	QTextEdit::setPointSize(int)
vfunc[191]:	QTextEdit::setColor(QColor const&)
vfunc[192]:	QTextEdit::setVerticalAlignment(QTextEdit::VerticalAlignment)
vfunc[193]:	QMultiLineEdit::setAlignment(int)
vfunc[194]:	QTextEdit::setParagType(QStyleSheetItem::DisplayMode, QStyleSheetItem::ListStyle)
vfunc[195]:	QMultiLineEdit::setCursorPosition(int, int)
vfunc[196]:	QTextEdit::setSelection(int, int, int, int, int)
vfunc[197]:	QTextEdit::setSelectionAttributes(int, QColor const&, bool)
vfunc[198]:	QTextEdit::setModified(bool)
vfunc[199]:	QTextEdit::resetFormat()
vfunc[200]:	QTextEdit::setUndoDepth(int)

vfunc[201]:	QTextEdit::setFormat(QTextFormat*, int)
vfunc[202]:	QTextEdit::ensureCursorVisible()
vfunc[203]:	QTextEdit::placeCursor(QPoint const&, QTextCursor*)
vfunc[204]:	QTextEdit::moveCursor(QTextEdit::CursorAction, bool)
vfunc[205]:	QTextEdit::doKeyboardAction(QTextEdit::KeyboardAction)
vfunc[206]:	QTextEdit::removeSelectedText(int)
vfunc[207]:	QTextEdit::removeSelection(int)
vfunc[208]:	QTextEdit::setCurrentFont(QFont const&)
vfunc[209]:	QTextEdit::setOverwriteMode(bool)
vfunc[210]:	QTextEdit::scrollToBottom()
vfunc[211]:	QTextEdit::insert(QString const&, bool, bool, bool)
vfunc[212]:	QMultiLineEdit::insertAt(QString const&, int, int)
vfunc[213]:	QTextEdit::removeParagraph(int)
vfunc[214]:	QTextEdit::insertParagraph(QString const&, int)
vfunc[215]:	QTextEdit::setParagraphBackgroundColor(int, QColor const&)
vfunc[216]:	QTextEdit::clearParagraphBackground(int)
vfunc[217]:	QTextEdit::setUndoRedoEnabled(bool)
vfunc[218]:	QTextEdit::createPopupMenu(QPoint const&)
vfunc[219]:	QTextEdit::createPopupMenu()
vfunc[220]:	QTextEdit::doChangeInterval()
vfunc[221]:	QTextEdit::linksEnabled() const
vfunc[222]:	QTextEdit::emitHighlighted(QString const&)
vfunc[223]:	QTextEdit::emitLinkClicked(QString const&)
vfunc[224]:	QMultiLineEdit::insertLine(QString const&, int)
vfunc[225]:	QMultiLineEdit::insertAt(QString

	const&, int, int, bool)
vfunc[226]:	QMultiLineEdit::removeLine(int)
vfunc[227]:	QMultiLineEdit::setCursorPosition(int, int, bool)
vfunc[228]:	QMultiLineEdit::setAutoUpdate(bool)
vfunc[229]:	QMultiLineEdit::insertAndMark(QString const&, bool)
vfunc[230]:	QMultiLineEdit::newLine()
vfunc[231]:	QMultiLineEdit::killLine()
vfunc[232]:	QMultiLineEdit::pageUp(bool)
vfunc[233]:	QMultiLineEdit::pageDown(bool)
vfunc[234]:	QMultiLineEdit::cursorLeft(bool, bool)
vfunc[235]:	QMultiLineEdit::cursorRight(bool, bool)
vfunc[236]:	QMultiLineEdit::cursorUp(bool)
vfunc[237]:	QMultiLineEdit::cursorDown(bool)
vfunc[238]:	QMultiLineEdit::backspace()
vfunc[239]:	QMultiLineEdit::home(bool)
vfunc[240]:	QMultiLineEdit::end(bool)

Table 7-272 Secondary vtable for QMultiLineEdit

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QMultiLineEdit
vfunc[0]:	non-virtual thunk to QMultiLineEdit::~~QMultiLineEdit()
vfunc[1]:	non-virtual thunk to QMultiLineEdit::~~QMultiLineEdit()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)

vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QMultiLineEdit class is described by Table 7-273

Table 7-273 typeinfo for QMultiLineEdit

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMultiLineEdit
basetype:	typeinfo for QTextEdit

7.2.1.114 Class data for QNetworkProtocolFactoryBase

The virtual table for the QNetworkProtocolFactoryBase class is described by Table 7-274

Table 7-274 Primary vtable for QNetworkProtocolFactoryBase

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QNetworkProtocolFactoryBase
vfunc[0]:	__cxa_pure_virtual

The Run Time Type Information for the QNetworkProtocolFactoryBase class is described by Table 7-275

Table 7-275 typeinfo for QNetworkProtocolFactoryBase

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QNetworkProtocolFactoryBase

7.2.1.115 Class data for QHBoxLayout

The virtual table for the QHBoxLayout class is described by Table 7-276

Table 7-276 Primary vtable for QHBoxLayout

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHBoxLayout
vfunc[0]:	QHBoxLayout::metaObject() const

vfunc[1]:	QHBoxLayout::className() const
vfunc[2]:	QHBoxLayout::qt_cast(char const*)
vfunc[3]:	QHBoxLayout::qt_invoke(int, QUObject*)
vfunc[4]:	QHBoxLayout::qt_emit(int, QUObject*)
vfunc[5]:	QHBoxLayout::qt_property(int, int, QVariant*)
vfunc[6]:	QHBoxLayout::~~QHBoxLayout()
vfunc[7]:	QHBoxLayout::~~QHBoxLayout()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QLayout::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QLayout::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QLayout::setMargin(int)
vfunc[22]:	QLayout::setSpacing(int)
vfunc[23]:	QLayout::setMenuBar(QMenuBar*)
vfunc[24]:	QLayout::setAutoAdd(bool)
vfunc[25]:	QBoxLayout::invalidate()
vfunc[26]:	QLayout::geometry() const
vfunc[27]:	QBoxLayout::addItem(QLayoutItem*)
vfunc[28]:	QBoxLayout::expanding() const
vfunc[29]:	QBoxLayout::minimumSize() const

vfunc[30]:	QBoxLayout::maximumSize() const
vfunc[31]:	QBoxLayout::setGeometry(QRect const&)
vfunc[32]:	QBoxLayout::iterator()
vfunc[33]:	QLayout::isEmpty() const
vfunc[34]:	QLayout::layout()
vfunc[35]:	QBoxLayout::sizeHint() const
vfunc[36]:	QBoxLayout::hasHeightForWidth() const
vfunc[37]:	QBoxLayout::heightForWidth(int) const

Table 7-277 Secondary vtable for QHBoxLayout

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QHBoxLayout
vfunc[0]:	non-virtual thunk to QHBoxLayout::~~QHBoxLayout()
vfunc[1]:	non-virtual thunk to QHBoxLayout::~~QHBoxLayout()
vfunc[2]:	non-virtual thunk to QBoxLayout::sizeHint() const
vfunc[3]:	non-virtual thunk to QBoxLayout::minimumSize() const
vfunc[4]:	non-virtual thunk to QBoxLayout::maximumSize() const
vfunc[5]:	non-virtual thunk to QBoxLayout::expanding() const
vfunc[6]:	non-virtual thunk to QBoxLayout::setGeometry(QRect const&)
vfunc[7]:	non-virtual thunk to QLayout::geometry() const
vfunc[8]:	non-virtual thunk to QLayout::isEmpty() const
vfunc[9]:	non-virtual thunk to QBoxLayout::hasHeightForWidth() const
vfunc[10]:	non-virtual thunk to QBoxLayout::heightForWidth(int) const

vfunc[11]:	non-virtual thunk to QBoxLayout::invalidate()
vfunc[12]:	QLayoutItem::widget()
vfunc[13]:	non-virtual thunk to QBoxLayout::iterator()
vfunc[14]:	non-virtual thunk to QLayout::layout()
vfunc[15]:	QLayoutItem::spacerItem()
vfunc[16]:	QLayoutItem::setAlignment(int)

The Run Time Type Information for the QHBoxLayout class is described by Table 7-278

Table 7-278 typeinfo for QHBoxLayout

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHBoxLayout
basetype:	typeinfo for QBoxLayout

7.2.1.116 Class data for QSocketDevice

The virtual table for the QSocketDevice class is described by Table 7-279

Table 7-279 Primary vtable for QSocketDevice

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSocketDevice
vfunc[0]:	QSocketDevice::~~QSocketDevice()
vfunc[1]:	QSocketDevice::~~QSocketDevice()
vfunc[2]:	QSocketDevice::open(int)
vfunc[3]:	QSocketDevice::close()
vfunc[4]:	QSocketDevice::flush()
vfunc[5]:	QSocketDevice::size() const
vfunc[6]:	QSocketDevice::at() const
vfunc[7]:	QSocketDevice::at(unsigned long)
vfunc[8]:	QSocketDevice::atEnd() const
vfunc[9]:	QSocketDevice::readBlock(char*, unsigned long)
vfunc[10]:	QSocketDevice::writeBlock(char const*, unsigned long)
vfunc[11]:	QIODevice::readLine(char*, unsigned

	long)
vfunc[12]:	QIODevice::readAll()
vfunc[13]:	QSocketDevice::getch()
vfunc[14]:	QSocketDevice::putch(int)
vfunc[15]:	QSocketDevice::ungetch(int)
vfunc[16]:	QSocketDevice::setSocket(int, QSocketDevice::Type)
vfunc[17]:	QSocketDevice::setBlocking(bool)
vfunc[18]:	QSocketDevice::setAddressReusable(bool)
vfunc[19]:	QSocketDevice::setReceiveBufferSize (unsigned int)
vfunc[20]:	QSocketDevice::setSendBufferSize(u nsigned int)
vfunc[21]:	QSocketDevice::connect(QHostAddr ess const&, unsigned short)
vfunc[22]:	QSocketDevice::bind(QHostAddress const&, unsigned short)
vfunc[23]:	QSocketDevice::listen(int)
vfunc[24]:	QSocketDevice::accept()
vfunc[25]:	QSocketDevice::writeBlock(char const*, unsigned long, QHostAddress const&, unsigned short)
vfunc[26]:	QSocketDevice::setOption(QSocketD evice::Option, int)

The Run Time Type Information for the QSocketDevice class is described by Table 7-280

Table 7-280 typeinfo for QSocketDevice

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSocketDevice
basetype:	typeinfo for QIODevice

7.2.1.117 Class data for QXmlReader

The virtual table for the QXmlReader class is described by Table 7-281

Table 7-281 Primary vtable for QXmlReader

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QXmlReader
vfunc[0]:	__cxa_pure_virtual
vfunc[1]:	__cxa_pure_virtual
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	__cxa_pure_virtual
vfunc[8]:	__cxa_pure_virtual
vfunc[9]:	__cxa_pure_virtual
vfunc[10]:	__cxa_pure_virtual
vfunc[11]:	__cxa_pure_virtual
vfunc[12]:	__cxa_pure_virtual
vfunc[13]:	__cxa_pure_virtual
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	__cxa_pure_virtual
vfunc[16]:	__cxa_pure_virtual
vfunc[17]:	__cxa_pure_virtual
vfunc[18]:	__cxa_pure_virtual
vfunc[19]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlReader class is described by Table 7-282

Table 7-282 typeinfo for QXmlReader

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlReader

7.2.1.118 Class data for QDomEntity

The virtual table for the QDomEntity class is described by Table 7-283

Table 7-283 Primary vtable for QDomEntity

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomEntity
vfunc[0]:	QDomEntity::~~QDomEntity()

vfunc[1]:	QDomEntity::~~QDomEntity()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomEntity::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection()

	const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomEntity::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction() const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const
vfunc[41]:	QDomEntity::publicId() const
vfunc[42]:	QDomEntity::systemId() const
vfunc[43]:	QDomEntity::notationName() const

The Run Time Type Information for the QDomEntity class is described by Table 7-284

Table 7-284 typeinfo for QDomEntity

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomEntity
basetype:	typeinfo for QDomNode

7.2.1.119 Class data for QMetaObject

The virtual table for the QMetaObject class is described by Table 7-285

Table 7-285 Primary vtable for QMetaObject

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMetaObject
vfunc[0]:	QMetaObject::~~QMetaObject()
vfunc[1]:	QMetaObject::~~QMetaObject()

The Run Time Type Information for the QMetaObject class is described by Table 7-286

Table 7-286 typeinfo for QMetaObject

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QMetaObject

7.2.1.120 Class data for QErrorMessage

The virtual table for the QErrorMessage class is described by Table 7-287

Table 7-287 Primary vtable for QErrorMessage

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QErrorMessage
vfunc[0]:	QErrorMessage::metaObject() const
vfunc[1]:	QErrorMessage::className() const
vfunc[2]:	QErrorMessage::qt_cast(char const*)
vfunc[3]:	QErrorMessage::qt_invoke(int, QUObject*)
vfunc[4]:	QErrorMessage::qt_emit(int, QUObject*)
vfunc[5]:	QErrorMessage::qt_property(int, int, QVariant*)
vfunc[6]:	QErrorMessage::~~QErrorMessage()
vfunc[7]:	QErrorMessage::~~QErrorMessage()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)

vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)

vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)

	nt*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const

vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QErrorMessage::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 7-288 Secondary vtable for QErrorMessage

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QErrorMessage
vfunc[0]:	non-virtual thunk to QErrorMessage::~~QErrorMessage()
vfunc[1]:	non-virtual thunk to QErrorMessage::~~QErrorMessage()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QErrorMessage class is described by Table 7-289

Table 7-289 typeinfo for QErrorMessage

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QErrorMessage
basetype:	typeinfo for QDialog

7.2.1.121 Class data for QListBox

The virtual table for the QListBox class is described by Table 7-290

Table 7-290 Primary vtable for QListBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QListBox
vfunc[0]:	QListBox::metaObject() const
vfunc[1]:	QListBox::className() const
vfunc[2]:	QListBox::qt_cast(char const*)
vfunc[3]:	QListBox::qt_invoke(int, QUObject*)
vfunc[4]:	QListBox::qt_emit(int, QUObject*)
vfunc[5]:	QListBox::qt_property(int, int, QVariant*)
vfunc[6]:	QListBox::~~QListBox()
vfunc[7]:	QListBox::~~QListBox()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QListBox::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)

vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QScrollView::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QListBox::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)

vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QListBox::sizeHint() const
vfunc[59]:	QListBox::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QListBox::mousePressEvent(QMouseEvent*)
vfunc[70]:	QListBox::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QListBox::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QListBox::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QListBox::keyPressEvent(QKeyEvent*)

vfunc[75]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[76]:	QListBox::focusInEvent(QFocusEvent*)
vfunc[77]:	QListBox::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QListBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QListBox::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QListBox::windowActivationChange

	(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QScrollView::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QScrollView::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QScrollView::drawContents(QPainter*)

	r*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QScrollView::contentsMousePressEvent(QMouseEvent*)
vfunc[130]:	QScrollView::contentsMouseReleaseEvent(QMouseEvent*)
vfunc[131]:	QScrollView::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QScrollView::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QScrollView::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QScrollView::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QScrollView::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QScrollView::contentsDropEvent(QDropEvent*)
vfunc[137]:	QScrollView::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QListBox::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QListBox::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QScrollView::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(Q

	DropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)
vfunc[154]:	QListBox::setCurrentItem(int)
vfunc[155]:	QListBox::setCurrentItem(QListBoxItem*)
vfunc[156]:	QListBox::setTopItem(int)
vfunc[157]:	QListBox::setBottomItem(int)
vfunc[158]:	QListBox::setSelectionMode(QListBox::SelectionMode)
vfunc[159]:	QListBox::setSelected(QListBoxItem*, bool)
vfunc[160]:	QListBox::setColumnMode(QListBox::LayoutMode)
vfunc[161]:	QListBox::setColumnMode(int)
vfunc[162]:	QListBox::setRowMode(QListBox::LayoutMode)
vfunc[163]:	QListBox::setRowMode(int)
vfunc[164]:	QListBox::setVariableWidth(bool)
vfunc[165]:	QListBox::setVariableHeight(bool)
vfunc[166]:	QListBox::ensureCurrentVisible()
vfunc[167]:	QListBox::clearSelection()
vfunc[168]:	QListBox::selectAll(bool)
vfunc[169]:	QListBox::invertSelection()
vfunc[170]:	QListBox::paintCell(QPainter*, int, int)

Table 7-291 Secondary vtable for QListBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QListBox

vfunc[0]:	non-virtual thunk to QListBox::~~QListBox()
vfunc[1]:	non-virtual thunk to QListBox::~~QListBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QListBox class is described by Table 7-292

Table 7-292 typeinfo for QListBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QListBox
basetype:	typeinfo for QScrollView

7.2.1.122 Class data for QCustomMenuItem

The virtual table for the QCustomMenuItem class is described by Table 7-293

Table 7-293 Primary vtable for QCustomMenuItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCustomMenuItem
vfunc[0]:	QCustomMenuItem::~~QCustomMenuItem()
vfunc[1]:	QCustomMenuItem::~~QCustomMenuItem()
vfunc[2]:	QCustomMenuItem::fullSpan() const
vfunc[3]:	QCustomMenuItem::isSeparator()

	const
vfunc[4]:	QCustomMenuItem::setFont(QFont const&)
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual

The Run Time Type Information for the QCustomMenuItem class is described by Table 7-294

Table 7-294 typeinfo for QCustomMenuItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCustomMenuItem
basetype:	typeinfo for Qt

7.2.1.123 Class data for QIconDrag

The virtual table for the QIconDrag class is described by Table 7-295

Table 7-295 Primary vtable for QIconDrag

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIconDrag
vfunc[0]:	QIconDrag::metaObject() const
vfunc[1]:	QIconDrag::className() const
vfunc[2]:	QIconDrag::qt_cast(char const*)
vfunc[3]:	QIconDrag::qt_invoke(int, QUObject*)
vfunc[4]:	QIconDrag::qt_emit(int, QUObject*)
vfunc[5]:	QIconDrag::qt_property(int, int, QVariant*)
vfunc[6]:	QIconDrag::~~QIconDrag()
vfunc[7]:	QIconDrag::~~QIconDrag()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*,

	QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QDragObject::setPixmap(QPixmap)
vfunc[22]:	QDragObject::setPixmap(QPixmap, QPoint const&)
vfunc[23]:	QDragObject::drag(QDragObject::DragMode)
vfunc[24]:	QIconDrag::format(int) const
vfunc[25]:	QIconDrag::encodedData(char const*) const

Table 7-296 Secondary vtable for QIconDrag

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QIconDrag
vfunc[0]:	non-virtual thunk to QIconDrag::~~QIconDrag()
vfunc[1]:	non-virtual thunk to QIconDrag::~~QIconDrag()
vfunc[2]:	non-virtual thunk to QIconDrag::format(int) const
vfunc[3]:	QMimeSource::provides(char const*) const
vfunc[4]:	non-virtual thunk to QIconDrag::encodedData(char const*) const

The Run Time Type Information for the QIconDrag class is described by Table 7-297

Table 7-297 typeinfo for QIconDrag

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
-------------	---

Name	typeinfo name for QIconDrag
basetype:	typeinfo for QDragObject

7.2.1.124 Class data for QUriDrag

The virtual table for the QUriDrag class is described by Table 7-298

Table 7-298 Primary vtable for QUriDrag

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QUriDrag
vfunc[0]:	QUriDrag::metaObject() const
vfunc[1]:	QUriDrag::className() const
vfunc[2]:	QUriDrag::qt_cast(char const*)
vfunc[3]:	QUriDrag::qt_invoke(int, QUObject*)
vfunc[4]:	QUriDrag::qt_emit(int, QUObject*)
vfunc[5]:	QUriDrag::qt_property(int, int, QVariant*)
vfunc[6]:	QUriDrag::~QUriDrag()
vfunc[7]:	QUriDrag::~~QUriDrag()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QDragObject::setPixmap(QPixmap)

vfunc[22]:	QDragObject::setPixmap(QPixmap, QPoint const&)
vfunc[23]:	QDragObject::drag(QDragObject::DragMode)
vfunc[24]:	QStoredDrag::setEncodedData(QMemArray<char> const&)
vfunc[25]:	QStoredDrag::format(int) const
vfunc[26]:	QStoredDrag::encodedData(char const*) const
vfunc[27]:	QUriDrag::setUris(QStrList)

Table 7-299 Secondary vtable for QUriDrag

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QUriDrag
vfunc[0]:	non-virtual thunk to QUriDrag::~~QUriDrag()
vfunc[1]:	non-virtual thunk to QUriDrag::~~QUriDrag()
vfunc[2]:	non-virtual thunk to QStoredDrag::format(int) const
vfunc[3]:	QMimeSource::provides(char const*) const
vfunc[4]:	non-virtual thunk to QStoredDrag::encodedData(char const*) const

The Run Time Type Information for the QUriDrag class is described by Table 7-300

Table 7-300 typeinfo for QUriDrag

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QUriDrag
basetype:	typeinfo for QStoredDrag

7.2.1.125 Class data for QXmlDeclHandler

The virtual table for the QXmlDeclHandler class is described by Table 7-301

Table 7-301 Primary vtable for QXmlDeclHandler

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QXmlDeclHandler
vfunc[0]:	__cxa_pure_virtual
vfunc[1]:	__cxa_pure_virtual
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlDeclHandler class is described by Table 7-302

Table 7-302 typeinfo for QXmlDeclHandler

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlDeclHandler

7.2.1.126 Class data for QVBoxLayout

The virtual table for the QVBoxLayout class is described by Table 7-303

Table 7-303 Primary vtable for QVBoxLayout

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QVBoxLayout
vfunc[0]:	QVBoxLayout::metaObject() const
vfunc[1]:	QVBoxLayout::className() const
vfunc[2]:	QVBoxLayout::qt_cast(char const*)
vfunc[3]:	QVBoxLayout::qt_invoke(int, QUObject*)
vfunc[4]:	QVBoxLayout::qt_emit(int, QUObject*)
vfunc[5]:	QVBoxLayout::qt_property(int, int, QVariant*)
vfunc[6]:	QVBoxLayout::~~QVBoxLayout()
vfunc[7]:	QVBoxLayout::~~QVBoxLayout()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QLayout::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)

vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QLayout::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QLayout::setMargin(int)
vfunc[22]:	QLayout::setSpacing(int)
vfunc[23]:	QLayout::setMenuBar(QMenuBar*)
vfunc[24]:	QLayout::setAutoAdd(bool)
vfunc[25]:	QBoxLayout::invalidate()
vfunc[26]:	QLayout::geometry() const
vfunc[27]:	QBoxLayout::addItem(QLayoutItem*)
vfunc[28]:	QBoxLayout::expanding() const
vfunc[29]:	QBoxLayout::minimumSize() const
vfunc[30]:	QBoxLayout::maximumSize() const
vfunc[31]:	QBoxLayout::setGeometry(QRect const&)
vfunc[32]:	QBoxLayout::iterator()
vfunc[33]:	QLayout::isEmpty() const
vfunc[34]:	QLayout::layout()
vfunc[35]:	QBoxLayout::sizeHint() const
vfunc[36]:	QBoxLayout::hasHeightForWidth() const
vfunc[37]:	QBoxLayout::heightForWidth(int) const

Table 7-304 Secondary vtable for QVBoxLayout

Base Offset	-80
Virtual Base Offset	0
RTTI	typeid for QVBoxLayout
vfunc[0]:	non-virtual thunk to QVBoxLayout::~~QVBoxLayout()

vfunc[1]:	non-virtual thunk to QVBoxLayout::~~QVBoxLayout()
vfunc[2]:	non-virtual thunk to QBoxLayout::sizeHint() const
vfunc[3]:	non-virtual thunk to QBoxLayout::minimumSize() const
vfunc[4]:	non-virtual thunk to QBoxLayout::maximumSize() const
vfunc[5]:	non-virtual thunk to QBoxLayout::expanding() const
vfunc[6]:	non-virtual thunk to QBoxLayout::setGeometry(QRect const&)
vfunc[7]:	non-virtual thunk to QLayout::geometry() const
vfunc[8]:	non-virtual thunk to QLayout::isEmpty() const
vfunc[9]:	non-virtual thunk to QBoxLayout::hasHeightForWidth() const
vfunc[10]:	non-virtual thunk to QBoxLayout::heightForWidth(int) const
vfunc[11]:	non-virtual thunk to QBoxLayout::invalidate()
vfunc[12]:	QLayoutItem::widget()
vfunc[13]:	non-virtual thunk to QBoxLayout::iterator()
vfunc[14]:	non-virtual thunk to QLayout::layout()
vfunc[15]:	QLayoutItem::spacerItem()
vfunc[16]:	QLayoutItem::setAlignment(int)

The Run Time Type Information for the QVBoxLayout class is described by Table 7-305

Table 7-305 typeinfo for QVBoxLayout

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QVBoxLayout
basetype:	typeinfo for QBoxLayout

7.2.1.127 Class data for QDomNode

The virtual table for the QDomNode class is described by Table 7-306

Table 7-306 Primary vtable for QDomNode

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomNode
vfunc[0]:	QDomNode::~~QDomNode()
vfunc[1]:	QDomNode::~~QDomNode()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomNode::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const

vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction() const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const

The Run Time Type Information for the QDomNode class is described by Table 7-307

Table 7-307 typeinfo for QDomNode

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QDomNode

7.2.1.128 Class data for QBuffer

The virtual table for the QBuffer class is described by Table 7-308

Table 7-308 Primary vtable for QBuffer

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QBuffer
vfunc[0]:	QBuffer::~QBuffer()

vfunc[1]:	QBuffer::~~QBuffer()
vfunc[2]:	QBuffer::open(int)
vfunc[3]:	QBuffer::close()
vfunc[4]:	QBuffer::flush()
vfunc[5]:	QBuffer::size() const
vfunc[6]:	QBuffer::at() const
vfunc[7]:	QBuffer::at(unsigned long)
vfunc[8]:	QIODevice::atEnd() const
vfunc[9]:	QBuffer::readBlock(char*, unsigned long)
vfunc[10]:	QBuffer::writeBlock(char const*, unsigned long)
vfunc[11]:	QBuffer::readLine(char*, unsigned long)
vfunc[12]:	QIODevice::readAll()
vfunc[13]:	QBuffer::getch()
vfunc[14]:	QBuffer::putch(int)
vfunc[15]:	QBuffer::ungetch(int)

The Run Time Type Information for the QBuffer class is described by Table 7-309

Table 7-309 typeinfo for QBuffer

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QBuffer
basetype:	typeinfo for QIODevice

7.2.1.129 Class data for QCanvasRectangle

The virtual table for the QCanvasRectangle class is described by Table 7-310

Table 7-310 Primary vtable for QCanvasRectangle

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvasRectangle
vfunc[0]:	QCanvasRectangle::~~QCanvasRectangle()
vfunc[1]:	QCanvasRectangle::~~QCanvasRectangle()
vfunc[2]:	QCanvasItem::moveBy(double,

	double)
vfunc[3]:	QCanvasItem::setAnimated(bool)
vfunc[4]:	QCanvasItem::setVelocity(double, double)
vfunc[5]:	QCanvasItem::advance(int)
vfunc[6]:	QCanvasRectangle::collidesWith(QCanvasItem const*) const
vfunc[7]:	QCanvasItem::setCanvas(QCanvas*)
vfunc[8]:	QCanvasPolygonalItem::draw(QPainter&)
vfunc[9]:	QCanvasItem::setVisible(bool)
vfunc[10]:	QCanvasItem::setSelected(bool)
vfunc[11]:	QCanvasItem::setEnabled(bool)
vfunc[12]:	QCanvasItem::setActive(bool)
vfunc[13]:	QCanvasRectangle::rtti() const
vfunc[14]:	QCanvasPolygonalItem::boundingRect() const
vfunc[15]:	QCanvasItem::boundingRectAdvanced() const
vfunc[16]:	QCanvasRectangle::chunks() const
vfunc[17]:	QCanvasItem::addToChunks()
vfunc[18]:	QCanvasItem::removeFromChunks()
vfunc[19]:	QCanvasItem::changeChunks()
vfunc[20]:	QCanvasRectangle::collidesWith(QCanvasSprite const*, QCanvasPolygonalItem const*, QCanvasRectangle const*, QCanvasEllipse const*, QCanvasText const*) const
vfunc[21]:	QCanvasPolygonalItem::setPen(QPen)
vfunc[22]:	QCanvasPolygonalItem::setBrush(QBrush)
vfunc[23]:	QCanvasRectangle::areaPoints() const
vfunc[24]:	QCanvasPolygonalItem::areaPointsAdvanced() const
vfunc[25]:	QCanvasRectangle::drawShape(QPainter&)

The Run Time Type Information for the QCanvasRectangle class is described by Table 7-311

Table 7-311 typeinfo for QCanvasRectangle

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasRectangle
basetype:	typeinfo for QCanvasPolygonalItem

7.2.1.130 Class data for QIconSet

The virtual table for the QIconSet class is described by Table 7-312

Table 7-312 Primary vtable for QIconSet

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIconSet
vfunc[0]:	QIconSet::~~QIconSet()
vfunc[1]:	QIconSet::~~QIconSet()
vfunc[2]:	QIconSet::setPixmap(QPixmap const&, QIconSet::Size, QIconSet::Mode, QIconSet::State)
vfunc[3]:	QIconSet::setPixmap(QString const&, QIconSet::Size, QIconSet::Mode, QIconSet::State)

The Run Time Type Information for the QIconSet class is described by Table 7-313

Table 7-313 typeinfo for QIconSet

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QIconSet

7.2.1.131 Class data for QDropSite

The virtual table for the QDropSite class is described by Table 7-314

Table 7-314 Primary vtable for QDropSite

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDropSite
vfunc[0]:	QDropSite::~~QDropSite()
vfunc[1]:	QDropSite::~~QDropSite()

The Run Time Type Information for the QDropSite class is described by Table 7-315

Table 7-315 typeinfo for QDropSite

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QDropSite

7.2.1.132 Class data for QThread

The virtual table for the QThread class is described by Table 7-316

Table 7-316 Primary vtable for QThread

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QThread
vfunc[0]:	QThread::~~QThread()
vfunc[1]:	QThread::~~QThread()
vfunc[2]:	__cxa_pure_virtual

The Run Time Type Information for the QThread class is described by Table 7-317

Table 7-317 typeinfo for QThread

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QThread
basetype:	typeinfo for Qt

7.2.1.133 Class data for QStoredDrag

The virtual table for the QStoredDrag class is described by Table 7-318

Table 7-318 Primary vtable for QStoredDrag

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QStoredDrag
vfunc[0]:	QStoredDrag::metaObject() const
vfunc[1]:	QStoredDrag::className() const
vfunc[2]:	QStoredDrag::qt_cast(char const*)
vfunc[3]:	QStoredDrag::qt_invoke(int, QUObject*)
vfunc[4]:	QStoredDrag::qt_emit(int, QUObject*)

vfunc[5]:	QStoredDrag::qt_property(int, int, QVariant*)
vfunc[6]:	QStoredDrag::~~QStoredDrag()
vfunc[7]:	QStoredDrag::~~QStoredDrag()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QDragObject::setPixmap(QPixmap)
vfunc[22]:	QDragObject::setPixmap(QPixmap, QPoint const&)
vfunc[23]:	QDragObject::drag(QDragObject::DragMode)
vfunc[24]:	QStoredDrag::setEncodedData(QMemArray<char> const&)
vfunc[25]:	QStoredDrag::format(int) const
vfunc[26]:	QStoredDrag::encodedData(char const*) const

Table 7-319 Secondary vtable for QStoredDrag

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QStoredDrag
vfunc[0]:	non-virtual thunk to QStoredDrag::~~QStoredDrag()

vfunc[1]:	non-virtual thunk to QStoredDrag::~~QStoredDrag()
vfunc[2]:	non-virtual thunk to QStoredDrag::format(int) const
vfunc[3]:	QMimeSource::provides(char const*) const
vfunc[4]:	non-virtual thunk to QStoredDrag::encodedData(char const*) const

The Run Time Type Information for the QStoredDrag class is described by Table 7-320

Table 7-320 typeinfo for QStoredDrag

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStoredDrag
basetype:	typeinfo for QDragObject

7.2.1.134 Class data for QTextDrag

The virtual table for the QTextDrag class is described by Table 7-321

Table 7-321 Primary vtable for QTextDrag

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextDrag
vfunc[0]:	QTextDrag::metaObject() const
vfunc[1]:	QTextDrag::className() const
vfunc[2]:	QTextDrag::qt_cast(char const*)
vfunc[3]:	QTextDrag::qt_invoke(int, QUObject*)
vfunc[4]:	QTextDrag::qt_emit(int, QUObject*)
vfunc[5]:	QTextDrag::qt_property(int, int, QVariant*)
vfunc[6]:	QTextDrag::~~QTextDrag()
vfunc[7]:	QTextDrag::~~QTextDrag()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)

vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QDragObject::setPixmap(QPixmap)
vfunc[22]:	QDragObject::setPixmap(QPixmap, QPoint const&)
vfunc[23]:	QDragObject::drag(QDragObject::DragMode)
vfunc[24]:	QTextDrag::setText(QString const&)
vfunc[25]:	QTextDrag::setSubtype(QCString const&)
vfunc[26]:	QTextDrag::format(int) const
vfunc[27]:	QTextDrag::encodedData(char const*) const

Table 7-322 Secondary vtable for QTextDrag

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QTextDrag
vfunc[0]:	non-virtual thunk to QTextDrag::~~QTextDrag()
vfunc[1]:	non-virtual thunk to QTextDrag::~~QTextDrag()
vfunc[2]:	non-virtual thunk to QTextDrag::format(int) const
vfunc[3]:	QMimeSource::provides(char const*) const
vfunc[4]:	non-virtual thunk to QTextDrag::encodedData(char const*) const

The Run Time Type Information for the QTextDrag class is described by Table 7-323

Table 7-323 typeinfo for QTextDrag

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextDrag
basetype:	typeinfo for QDragObject

7.2.1.135 Class data for QFilePreview

The virtual table for the QFilePreview class is described by Table 7-324

Table 7-324 Primary vtable for QFilePreview

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFilePreview
vfunc[0]:	__cxa_pure_virtual

The Run Time Type Information for the QFilePreview class is described by Table 7-325

Table 7-325 typeinfo for QFilePreview

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QFilePreview

7.2.1.136 Class data for QButtonGroup

The virtual table for the QButtonGroup class is described by Table 7-326

Table 7-326 Primary vtable for QButtonGroup

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QButtonGroup
vfunc[0]:	QButtonGroup::metaObject() const
vfunc[1]:	QButtonGroup::className() const
vfunc[2]:	QButtonGroup::qt_cast(char const*)
vfunc[3]:	QButtonGroup::qt_invoke(int, QUObject*)
vfunc[4]:	QButtonGroup::qt_emit(int, QUObject*)
vfunc[5]:	QButtonGroup::qt_property(int, int, QVariant*)

vfunc[6]:	QButtonGroup::~~QButtonGroup()
vfunc[7]:	QButtonGroup::~~QButtonGroup()
vfunc[8]:	QButtonGroup::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QGroupBox::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QGroupBox::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)

vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QGroupBox::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const

vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QGroupBox::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QGroupBox::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QGroupBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)

vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QGroupBox::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)

vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QGroupBox::setColumnLayout(int, Qt::Orientation)
vfunc[119]:	QGroupBox::setTitle(QString const&)
vfunc[120]:	QGroupBox::setAlignment(int)
vfunc[121]:	QButtonGroup::setExclusive(bool)
vfunc[122]:	QButtonGroup::setRadioButtonExclusive(bool)
vfunc[123]:	QButtonGroup::setButton(int)
vfunc[124]:	QButtonGroup::moveFocus(int)

Table 7-327 Secondary vtable for QButtonGroup

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QButtonGroup
vfunc[0]:	non-virtual thunk to QButtonGroup::~QButtonGroup()
vfunc[1]:	non-virtual thunk to QButtonGroup::~QButtonGroup()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QButtonGroup class is described by Table 7-328

Table 7-328 typeinfo for QButtonGroup

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QButtonGroup
basetype:	typeinfo for QGroupBox

7.2.1.137 Class data for QSqlRecord

The virtual table for the QSqlRecord class is described by Table 7-329

Table 7-329 Primary vtable for QSqlRecord

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlRecord
vfunc[0]:	QSqlRecord::~~QSqlRecord()
vfunc[1]:	QSqlRecord::~~QSqlRecord()
vfunc[2]:	QSqlRecord::value(int) const
vfunc[3]:	QSqlRecord::value(QString const&) const
vfunc[4]:	QSqlRecord::setValue(int, QVariant const&)
vfunc[5]:	QSqlRecord::setValue(QString const&, QVariant const&)
vfunc[6]:	QSqlRecord::setGenerated(QString const&, bool)
vfunc[7]:	QSqlRecord::setGenerated(int, bool)
vfunc[8]:	QSqlRecord::setNull(int)
vfunc[9]:	QSqlRecord::setNull(QString const&)
vfunc[10]:	QSqlRecord::append(QSqlField const&)
vfunc[11]:	QSqlRecord::insert(int, QSqlField const&)
vfunc[12]:	QSqlRecord::remove(int)
vfunc[13]:	QSqlRecord::clear()
vfunc[14]:	QSqlRecord::clearValues(bool)
vfunc[15]:	QSqlRecord::toString(QString const&, QString const&) const
vfunc[16]:	QSqlRecord::toStringList(QString const&) const

The Run Time Type Information for the QSqlRecord class is described by Table 7-330

Table 7-330 typeinfo for QSqlRecord

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QSqlRecord

7.2.1.138 Class data for QPicture

The virtual table for the QPicture class is described by Table 7-331

Table 7-331 Primary vtable for QPicture

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPicture
vfunc[0]:	QPicture::~~QPicture()
vfunc[1]:	QPicture::~~QPicture()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPicture::cmd(int, QPainter*, QPaintDevice::CmdParam*)
vfunc[8]:	QPicture::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const
vfunc[11]:	QPicture::setData(char const*, unsigned int)

The Run Time Type Information for the QPicture class is described by Table 7-332

Table 7-332 typeinfo for QPicture

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPicture
basetype:	typeinfo for QPaintDevice

7.2.1.139 Class data for QSemaphore

The virtual table for the QSemaphore class is described by Table 7-333

Table 7-333 Primary vtable for QSemaphore

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSemaphore
vfunc[0]:	QSemaphore::~~QSemaphore()
vfunc[1]:	QSemaphore::~~QSemaphore()

The Run Time Type Information for the QSemaphore class is described by Table 7-334

Table 7-334 typeinfo for QSemaphore

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QSemaphore

7.2.1.140 Class data for QComboBox

The virtual table for the QComboBox class is described by Table 7-335

Table 7-335 Primary vtable for QComboBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QComboBox
vfunc[0]:	QComboBox::metaObject() const
vfunc[1]:	QComboBox::className() const
vfunc[2]:	QComboBox::qt_cast(char const*)
vfunc[3]:	QComboBox::qt_invoke(int, QUObject*)
vfunc[4]:	QComboBox::qt_emit(int, QUObject*)
vfunc[5]:	QComboBox::qt_property(int, int, QVariant*)
vfunc[6]:	QComboBox::~~QComboBox()
vfunc[7]:	QComboBox::~~QComboBox()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QComboBox::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)

vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QComboBox::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QComboBox::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QComboBox::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)

vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QComboBox::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QComboBox::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)

vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QComboBox::mousePressEvent(QMouseEvent*)
vfunc[70]:	QComboBox::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QComboBox::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QComboBox::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QComboBox::wheelEvent(QWheelEvent*)
vfunc[74]:	QComboBox::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QComboBox::focusInEvent(QFocusEvent*)
vfunc[77]:	QComboBox::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QComboBox::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QComboBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)

vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QComboBox::updateMask()
vfunc[97]:	QComboBox::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QComboBox::setCurrentItem(int)
vfunc[111]:	QComboBox::setCurrentText(QString const&)
vfunc[112]:	QComboBox::setAutoResize(bool)
vfunc[113]:	QComboBox::setSizeLimit(int)
vfunc[114]:	QComboBox::setMaxCount(int)
vfunc[115]:	QComboBox::setInsertionPolicy(QComboBox::Policy)
vfunc[116]:	QComboBox::setValidator(QValidator const*)
vfunc[117]:	QComboBox::setListBox(QListBox*)
vfunc[118]:	QComboBox::setLineEdit(QLineEdit*)
vfunc[119]:	QComboBox::setAutoCompletion(bool)
vfunc[120]:	QComboBox::popup()

vfunc[121]:	QComboBox::setEditText(QString const&)
-------------	--

Table 7-336 Secondary vtable for QComboBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QComboBox
vfunc[0]:	non-virtual thunk to QComboBox::~~QComboBox()
vfunc[1]:	non-virtual thunk to QComboBox::~~QComboBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QComboBox class is described by Table 7-337

Table 7-337 typeinfo for QComboBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QComboBox
basetype:	typeinfo for QWidget

7.2.1.141 Class data for QDomText

The virtual table for the QDomText class is described by Table 7-338

Table 7-338 Primary vtable for QDomText

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QDomText
vfunc[0]:	QDomText::~~QDomText()
vfunc[1]:	QDomText::~~QDomText()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomText::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)

vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomText::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction()) const
vfunc[39]:	QDomCharacterData::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const
vfunc[41]:	QDomCharacterData::substringData(unsigned long, unsigned long)
vfunc[42]:	QDomCharacterData::appendData(QString const&)
vfunc[43]:	QDomCharacterData::insertData(unsigned long, QString const&)
vfunc[44]:	QDomCharacterData::deleteData(unsigned long, unsigned long)
vfunc[45]:	QDomCharacterData::replaceData(unsigned long, unsigned long, QString const&)
vfunc[46]:	QDomCharacterData::length() const
vfunc[47]:	QDomCharacterData::data() const
vfunc[48]:	QDomCharacterData::setData(QString const&)

The Run Time Type Information for the QDomText class is described by Table 7-339

Table 7-339 typeinfo for QDomText

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
-------------	--

Name	typeinfo name for QDomText
basetype:	typeinfo for QDomCharacterData

7.2.1.142 Class data for QVButtonGroup

The virtual table for the QVButtonGroup class is described by Table 7-340

Table 7-340 Primary vtable for QVButtonGroup

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QVButtonGroup
vfunc[0]:	QVButtonGroup::metaObject() const
vfunc[1]:	QVButtonGroup::className() const
vfunc[2]:	QVButtonGroup::qt_cast(char const*)
vfunc[3]:	QVButtonGroup::qt_invoke(int, QUObject*)
vfunc[4]:	QVButtonGroup::qt_emit(int, QUObject*)
vfunc[5]:	QVButtonGroup::qt_property(int, int, QVariant*)
vfunc[6]:	QVButtonGroup::~~QVButtonGroup()
vfunc[7]:	QVButtonGroup::~~QVButtonGroup()
vfunc[8]:	QButtonGroup::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QGroupBox::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char

	const*, QObject const*, char const*)
vfunc[21]:	QGroupBox::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPi xmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::F ocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()

vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QGroupBox::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)

	nt*)
vfunc[76]:	QGroupBox::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QGroupBox::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QGroupBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QGroupBox::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(

	bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QGroupBox::setColumnLayout(int, Qt::Orientation)
vfunc[119]:	QGroupBox::setTitle(QString const&)
vfunc[120]:	QGroupBox::setAlignment(int)
vfunc[121]:	QButtonGroup::setExclusive(bool)
vfunc[122]:	QButtonGroup::setRadioButtonExclusive(bool)
vfunc[123]:	QButtonGroup::setButton(int)
vfunc[124]:	QButtonGroup::moveFocus(int)

Table 7-341 Secondary vtable for QVButtonGroup

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QVButtonGroup
vfunc[0]:	non-virtual thunk to QVButtonGroup::~~QVButtonGroup()
vfunc[1]:	non-virtual thunk to QVButtonGroup::~~QVButtonGroup()

vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QVButtonGroup class is described by Table 7-342

Table 7-342 typeinfo for QVButtonGroup

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QVButtonGroup
basetype:	typeinfo for QButtonGroup

7.2.1.143 Class data for QClipboard

The virtual table for the QClipboard class is described by Table 7-343

Table 7-343 Primary vtable for QClipboard

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QClipboard
vfunc[0]:	QClipboard::metaObject() const
vfunc[1]:	QClipboard::className() const
vfunc[2]:	QClipboard::qt_cast(char const*)
vfunc[3]:	QClipboard::qt_invoke(int, QUObject*)
vfunc[4]:	QClipboard::qt_emit(int, QUObject*)
vfunc[5]:	QClipboard::qt_property(int, int, QVariant*)
vfunc[6]:	QClipboard::~~QClipboard()

vfunc[7]:	QClipboard::~~QClipboard()
vfunc[8]:	QClipboard::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QClipboard::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QClipboard class is described by Table 7-344

Table 7-344 typeinfo for QClipboard

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QClipboard
basetype:	typeinfo for QObject

7.2.1.144 Class data for QTextEncoder

The virtual table for the QTextEncoder class is described by Table 7-345

Table 7-345 Primary vtable for QTextEncoder

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextEncoder
vfunc[0]:	QTextEncoder::~~QTextEncoder()
vfunc[1]:	QTextEncoder::~~QTextEncoder()
vfunc[2]:	__cxa_pure_virtual

The Run Time Type Information for the QTextEncoder class is described by Table 7-346

Table 7-346 typeinfo for QTextEncoder

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QTextEncoder

7.2.1.145 Class data for QCanvasView

The virtual table for the QCanvasView class is described by Table 7-347

Table 7-347 Primary vtable for QCanvasView

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvasView
vfunc[0]:	QCanvasView::metaObject() const
vfunc[1]:	QCanvasView::className() const
vfunc[2]:	QCanvasView::qt_cast(char const*)
vfunc[3]:	QCanvasView::qt_invoke(int, QUObject*)
vfunc[4]:	QCanvasView::qt_emit(int, QUObject*)
vfunc[5]:	QCanvasView::qt_property(int, int, QVariant*)
vfunc[6]:	QCanvasView::~~QCanvasView()
vfunc[7]:	QCanvasView::~~QCanvasView()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QScrollView::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)

vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QScrollView::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)

vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QCanvasView::sizeHint() const
vfunc[59]:	QScrollView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEv

	ent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QScrollView::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)

vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QScrollView::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QCanvasView::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)

vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QCanvasView::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QScrollView::contentsMousePressEvent(QMouseEvent*)
vfunc[130]:	QScrollView::contentsMouseReleaseEvent(QMouseEvent*)
vfunc[131]:	QScrollView::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QScrollView::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QScrollView::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QScrollView::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QScrollView::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QScrollView::contentsDropEvent(QDropEvent*)
vfunc[137]:	QScrollView::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QScrollView::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QScrollView::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)

vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)

Table 7-348 Secondary vtable for QCanvasView

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QCanvasView
vfunc[0]:	non-virtual thunk to QCanvasView::~~QCanvasView()
vfunc[1]:	non-virtual thunk to QCanvasView::~~QCanvasView()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QCanvasView class is described by Table 7-349

Table 7-349 typeinfo for QCanvasView

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasView
basetype:	typeinfo for QScrollView

7.2.1.146 Class data for QPixmap

The virtual table for the QPixmap class is described by Table 7-350

Table 7-350 Primary vtable for QPixmap

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPixmap
vfunc[0]:	QPixmap::~~QPixmap()
vfunc[1]:	QPixmap::~~QPixmap()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDvCmdParam*)
vfunc[8]:	QPixmap::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const
vfunc[11]:	QPixmap::detach()

The Run Time Type Information for the QPixmap class is described by Table 7-351

Table 7-351 typeinfo for QPixmap

Base Vtable	vtable for __cxxabiv1::__vmi_class _type_info	
Name	typeinfo name for QPixmap	
flags:	0	

basetype:	typeinfo for QPaintDevice	2
basetype:	typeinfo for Qt	2

7.2.1.147 Class data for QGrid

The virtual table for the QGrid class is described by Table 7-352

Table 7-352 Primary vtable for QGrid

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGrid
vfunc[0]:	QGrid::metaObject() const
vfunc[1]:	QGrid::className() const
vfunc[2]:	QGrid::qt_cast(char const*)
vfunc[3]:	QGrid::qt_invoke(int, QUObject*)
vfunc[4]:	QGrid::qt_emit(int, QUObject*)
vfunc[5]:	QGrid::qt_property(int, int, QVariant*)
vfunc[6]:	QGrid::~~QGrid()
vfunc[7]:	QGrid::~~QGrid()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()

vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QGrid::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)

	nt*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QFrame::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const

vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QGrid::frameChanged()

Table 7-353 Secondary vtable for QGrid

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QGrid
vfunc[0]:	non-virtual thunk to QGrid::~~QGrid()
vfunc[1]:	non-virtual thunk to QGrid::~~QGrid()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const

vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QGrid class is described by Table 7-354

Table 7-354 typeinfo for QGrid

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGrid
basetype:	typeinfo for QFrame

7.2.1.148 Class data for QRadioButton

The virtual table for the QRadioButton class is described by Table 7-355

Table 7-355 Primary vtable for QRadioButton

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QRadioButton
vfunc[0]:	QRadioButton::metaObject() const
vfunc[1]:	QRadioButton::className() const
vfunc[2]:	QRadioButton::qt_cast(char const*)
vfunc[3]:	QRadioButton::qt_invoke(int, QUObject*)
vfunc[4]:	QRadioButton::qt_emit(int, QUObject*)
vfunc[5]:	QRadioButton::qt_property(int, int, QVariant*)
vfunc[6]:	QRadioButton::~~QRadioButton()
vfunc[7]:	QRadioButton::~~QRadioButton()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const

vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)

vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QRadioButton::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QPushButton::mousePressEvent(QMouseEvent*)
vfunc[70]:	QPushButton::mouseReleaseEvent(QMouseEvent*)

vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QPushButton::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QPushButton::keyPressEvent(QKeyEvent*)
vfunc[75]:	QPushButton::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QPushButton::focusInEvent(QFocusEvent*)
vfunc[77]:	QPushButton::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QPushButton::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QRadioButton::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)

vfunc[96]:	QRadioButton::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QPushButton::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QPushButton::setText(QString const&)
vfunc[111]:	QPushButton::setPixmap(QPixmap const&)
vfunc[112]:	QPushButton::setAccel(QKeySequence const&)
vfunc[113]:	QPushButton::setDown(bool)
vfunc[114]:	QPushButton::setAutoRepeat(bool)
vfunc[115]:	QPushButton::setToggleType(QPushButton::ToggleType)
vfunc[116]:	QPushButton::setState(QPushButton::ToggleState)
vfunc[117]:	QRadioButton::hitButton(QPoint const&) const
vfunc[118]:	QRadioButton::drawButton(QPainter*)
vfunc[119]:	QRadioButton::drawButtonLabel(QPainter*)
vfunc[120]:	QPushButton::setGroup(QButtonGroup*)
vfunc[121]:	QRadioButton::setChecked(bool)

Table 7-356 Secondary vtable for QRadioButton

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QRadioButton
vfunc[0]:	non-virtual thunk to QRadioButton::~~QRadioButton()
vfunc[1]:	non-virtual thunk to QRadioButton::~~QRadioButton()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QRadioButton class is described by Table 7-357

Table 7-357 typeinfo for QRadioButton

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QRadioButton
basetype:	typeinfo for QButton

7.2.1.149 Class data for QAsyncIO

The virtual table for the QAsyncIO class is described by Table 7-358

Table 7-358 Primary vtable for QAsyncIO

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAsyncIO
vfunc[0]:	QAsyncIO::~~QAsyncIO()

vfunc[1]:	QAsyncIO::~QAsyncIO()
-----------	-----------------------

The Run Time Type Information for the QAsyncIO class is described by Table 7-359

Table 7-359 typeinfo for QAsyncIO

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QAsyncIO

7.2.1.150 Class data for QSlider

The virtual table for the QSlider class is described by Table 7-360

Table 7-360 Primary vtable for QSlider

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSlider
vfunc[0]:	QSlider::metaObject() const
vfunc[1]:	QSlider::className() const
vfunc[2]:	QSlider::qt_cast(char const*)
vfunc[3]:	QSlider::qt_invoke(int, QUObject*)
vfunc[4]:	QSlider::qt_emit(int, QUObject*)
vfunc[5]:	QSlider::qt_property(int, int, QVariant*)
vfunc[6]:	QSlider::~QSlider()
vfunc[7]:	QSlider::~QSlider()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)

vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QSlider::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::F

	ocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QSlider::sizeHint() const
vfunc[59]:	QSlider::minimumSizeHint() const
vfunc[60]:	QSlider::sizePolicy() const
vfunc[61]:	QSlider::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QSlider::mousePressEvent(QMouseEvent*)
vfunc[70]:	QSlider::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QSlider::mouseMoveEvent(QMouseEvent*)

vfunc[73]:	QSlider::wheelEvent(QWheelEvent*)
vfunc[74]:	QSlider::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QSlider::focusInEvent(QFocusEvent*)
vfunc[77]:	QSlider::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QSlider::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QSlider::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QSlider::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)

vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QSlider::setOrientation(Qt::Orientati on)
vfunc[111]:	QSlider::setTracking(bool)
vfunc[112]:	QSlider::setTickmarks(QSlider::TickS etting)
vfunc[113]:	QSlider::setTickInterval(int)
vfunc[114]:	QSlider::setValue(int)
vfunc[115]:	QSlider::valueChange()
vfunc[116]:	QSlider::rangeChange()

Table 7-361 Secondary vtable for QSlider

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QSlider
vfunc[0]:	non-virtual thunk to QSlider::~~QSlider()
vfunc[1]:	non-virtual thunk to QSlider::~~QSlider()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPaintDeviceCmdParam*)

vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

Table 7-362 Secondary vtable for QSlider

Base Offset	-200
Virtual Base Offset	0
RTTI	typeinfo for QSlider
vfunc[0]:	non-virtual thunk to QSlider::~~QSlider()
vfunc[1]:	non-virtual thunk to QSlider::~~QSlider()
vfunc[2]:	non-virtual thunk to QSlider::valueChange()
vfunc[3]:	non-virtual thunk to QSlider::rangeChange()
vfunc[4]:	QRangeControl::stepChange()

The Run Time Type Information for the QSlider class is described by Table 7-363

Table 7-363 typeinfo for QSlider

Base Vtable	vtable for __cxxabiv1::__vmi_class _type_info	2
Name	typeinfo name for QSlider	
flags:	0	
basetype:	typeinfo for QWidget	
basetype:	typeinfo for QRangeControl	29698

7.2.1.151 Class data for QHttpResponseHeader

The virtual table for the QHttpResponseHeader class is described by Table 7-364

Table 7-364 Primary vtable for QHttpResponseHeader

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QHttpResponseHeader
vfunc[0]:	QHttpResponseHeader::~~QHttpResponseHeader()
vfunc[1]:	QHttpResponseHeader::~~QHttpResponseHeader()
vfunc[2]:	QHttpResponseHeader::toString() const
vfunc[3]:	QHttpResponseHeader::majorVersion() const
vfunc[4]:	QHttpResponseHeader::minorVersion() const
vfunc[5]:	QHttpResponseHeader::parseLine(QString const&, int)

The Run Time Type Information for the QHttpResponseHeader class is described by Table 7-365

Table 7-365 typeinfo for QHttpResponseHeader

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHttpResponseHeader
basetype:	typeinfo for QHttpHeader

7.2.1.152 Class data for QDomCharacterData

The virtual table for the QDomCharacterData class is described by Table 7-366

Table 7-366 Primary vtable for QDomCharacterData

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomCharacterData
vfunc[0]:	QDomCharacterData::~~QDomCharacterData()
vfunc[1]:	QDomCharacterData::~~QDomCharacterData()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)

vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomCharacterData::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference()

	const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction() const
vfunc[39]:	QDomCharacterData::isCharacterDat a() const
vfunc[40]:	QDomNode::isComment() const
vfunc[41]:	QDomCharacterData::substringData(unsigned long, unsigned long)
vfunc[42]:	QDomCharacterData::appendData(Q String const&)
vfunc[43]:	QDomCharacterData::insertData(uns igned long, QString const&)
vfunc[44]:	QDomCharacterData::deleteData(uns igned long, unsigned long)
vfunc[45]:	QDomCharacterData::replaceData(u nsigned long, unsigned long, QString const&)
vfunc[46]:	QDomCharacterData::length() const
vfunc[47]:	QDomCharacterData::data() const
vfunc[48]:	QDomCharacterData::setData(QStrin g const&)

The Run Time Type Information for the QDomCharacterData class is described by Table 7-367

Table 7-367 typeinfo for QDomCharacterData

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomCharacterData
basetype:	typeinfo for QDomNode

7.2.1.153 Class data for QDragEnterEvent

The virtual table for the QDragEnterEvent class is described by Table 7-368

Table 7-368 Primary vtable for QDragEnterEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDragEnterEvent

vfunc[0]:	QDragEnterEvent::~~QDragEnterEvent()
vfunc[1]:	QDragEnterEvent::~~QDragEnterEvent()
vfunc[2]:	QDropEvent::format(int) const
vfunc[3]:	QDropEvent::encodedData(char const*) const
vfunc[4]:	QDropEvent::provides(char const*) const

Table 7-369 Secondary vtable for QDragEnterEvent

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QDragEnterEvent
vfunc[0]:	non-virtual thunk to QDragEnterEvent::~~QDragEnterEvent()
vfunc[1]:	non-virtual thunk to QDragEnterEvent::~~QDragEnterEvent()
vfunc[2]:	non-virtual thunk to QDropEvent::format(int) const
vfunc[3]:	non-virtual thunk to QDropEvent::provides(char const*) const
vfunc[4]:	non-virtual thunk to QDropEvent::encodedData(char const*) const

The Run Time Type Information for the QDragEnterEvent class is described by Table 7-370

Table 7-370 typeinfo for QDragEnterEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDragEnterEvent
basetype:	typeinfo for QDragMoveEvent

7.2.1.154 Class data for QActionGroup

The virtual table for the QActionGroup class is described by Table 7-371

Table 7-371 Primary vtable for QActionGroup

Base Offset	0
-------------	---

Virtual Base Offset	0
RTTI	typeinfo for QActionGroup
vfunc[0]:	QActionGroup::metaObject() const
vfunc[1]:	QActionGroup::className() const
vfunc[2]:	QActionGroup::qt_cast(char const*)
vfunc[3]:	QActionGroup::qt_invoke(int, QObject*)
vfunc[4]:	QActionGroup::qt_emit(int, QObject*)
vfunc[5]:	QActionGroup::qt_property(int, int, QVariant*)
vfunc[6]:	QActionGroup::~~QActionGroup()
vfunc[7]:	QActionGroup::~~QActionGroup()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QActionGroup::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QActionGroup::setIconSet(QIconSet const&)
vfunc[22]:	QActionGroup::setText(QString const&)
vfunc[23]:	QActionGroup::setMenuText(QString const&)
vfunc[24]:	QActionGroup::setToolTip(QString

	const&)
vfunc[25]:	QAction::setStatusTip(QString const&)
vfunc[26]:	QActionGroup::setWhatsThis(QString const&)
vfunc[27]:	QAction::setAccel(QKeySequence const&)
vfunc[28]:	QActionGroup::setToggleAction(bool)
vfunc[29]:	QActionGroup::addTo(QWidget*)
vfunc[30]:	QActionGroup::removeFrom(QWidget*)
vfunc[31]:	QActionGroup::addedTo(QWidget*, QWidget*)
vfunc[32]:	QActionGroup::addedTo(int, QPopupMenu*)
vfunc[33]:	QActionGroup::setOn(bool)
vfunc[34]:	QActionGroup::setEnabled(bool)
vfunc[35]:	QActionGroup::addedTo(QWidget*, QWidget*, QAction*)
vfunc[36]:	QActionGroup::addedTo(int, QPopupMenu*, QAction*)

The Run Time Type Information for the QActionGroup class is described by Table 7-372

Table 7-372 typeinfo for QActionGroup

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QActionGroup
basetype:	typeinfo for QAction

7.2.1.155 Class data for QDataTable

The virtual table for the QDataTable class is described by Table 7-373

Table 7-373 Primary vtable for QDataTable

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDataTable
vfunc[0]:	QDataTable::metaObject() const
vfunc[1]:	QDataTable::className() const

vfunc[2]:	QDataTable::qt_cast(char const*)
vfunc[3]:	QDataTable::qt_invoke(int, QUObject*)
vfunc[4]:	QDataTable::qt_emit(int, QUObject*)
vfunc[5]:	QDataTable::qt_property(int, int, QVariant*)
vfunc[6]:	QDataTable::~~QDataTable()
vfunc[7]:	QDataTable::~~QDataTable()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDataTable::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QTable::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor

	r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)

vfunc[58]:	QTable::sizeHint() const
vfunc[59]:	QScrollView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QDataTable::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QTable::focusInEvent(QFocusEvent*)
vfunc[77]:	QTable::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QTable::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDataTable::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QC

	onContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QTable::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QTable::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QScrollView::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)

vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QTable::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QDataTable::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QDataTable::contentsMouseEvent(QMouseEvent*)
vfunc[130]:	QTable::contentsMouseEvent(QMouseEvent*)
vfunc[131]:	QTable::contentsMouseEvent(QMouseEvent*)
vfunc[132]:	QTable::contentsMouseEvent(QMouseEvent*)
vfunc[133]:	QTable::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QTable::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QTable::contentsDragLeaveEvent(QDragLeaveEvent*)

vfunc[136]:	QTable::contentsDropEvent(QDropEvent*)
vfunc[137]:	QScrollView::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QDataTable::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QTable::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)
vfunc[154]:	QTable::setSelectionMode(QTable::SelectionMode)
vfunc[155]:	QDataTable::setItem(int, int, QTableWidgetItem*)
vfunc[156]:	QTable::setText(int, int, QString const&)

vfunc[157]:	QDataTable::setPixmap(int, int, QPixmap const&)
vfunc[158]:	QDataTable::item(int, int) const
vfunc[159]:	QDataTable::text(int, int) const
vfunc[160]:	QTable::pixmap(int, int) const
vfunc[161]:	QDataTable::clearCell(int, int)
vfunc[162]:	QTable::cellGeometry(int, int) const
vfunc[163]:	QTable::columnWidth(int) const
vfunc[164]:	QTable::rowHeight(int) const
vfunc[165]:	QTable::columnPos(int) const
vfunc[166]:	QTable::rowPos(int) const
vfunc[167]:	QTable::columnAt(int) const
vfunc[168]:	QTable::rowAt(int) const
vfunc[169]:	QDataTable::numRows() const
vfunc[170]:	QDataTable::numCols() const
vfunc[171]:	QTable::addSelection(QTableSelection const&)
vfunc[172]:	QTable::removeSelection(QTableSelection const&)
vfunc[173]:	QTable::removeSelection(int)
vfunc[174]:	QTable::currentSelection() const
vfunc[175]:	QDataTable::sortColumn(int, bool, bool)
vfunc[176]:	QDataTable::takeItem(QTableWidgetItem*)
vfunc[177]:	QTable::setCellWidget(int, int, QWidget*)
vfunc[178]:	QTable::cellWidget(int, int) const
vfunc[179]:	QTable::clearCellWidget(int, int)
vfunc[180]:	QTable::cellRect(int, int) const
vfunc[181]:	QTable::paintCell(QPainter*, int, int, QRect const&, bool)
vfunc[182]:	QDataTable::paintCell(QPainter*, int, int, QRect const&, bool, QColorGroup const&)
vfunc[183]:	QTable::paintFocus(QPainter*, QRect const&)
vfunc[184]:	QTable::setFocusStyle(QTable::FocusStyle)

vfunc[185]:	QDataTable::setNumRows(int)
vfunc[186]:	QDataTable::setNumCols(int)
vfunc[187]:	QTable::setShowGrid(bool)
vfunc[188]:	QTable::hideRow(int)
vfunc[189]:	QDataTable::hideColumn(int)
vfunc[190]:	QTable::showRow(int)
vfunc[191]:	QDataTable::showColumn(int)
vfunc[192]:	QDataTable::setColumnWidth(int, int)
vfunc[193]:	QTable::setRowHeight(int, int)
vfunc[194]:	QDataTable::adjustColumn(int)
vfunc[195]:	QTable::adjustRow(int)
vfunc[196]:	QDataTable::setColumnStretchable(int, bool)
vfunc[197]:	QTable::setRowStretchable(int, bool)
vfunc[198]:	QTable::setSorting(bool)
vfunc[199]:	QTable::swapRows(int, int, bool)
vfunc[200]:	QDataTable::swapColumns(int, int, bool)
vfunc[201]:	QTable::swapCells(int, int, int, int)
vfunc[202]:	QTable::setLeftMargin(int)
vfunc[203]:	QTable::setTopMargin(int)
vfunc[204]:	QTable::setCurrentCell(int, int)
vfunc[205]:	QTable::setColumnMovingEnabled(bool)
vfunc[206]:	QTable::setRowMovingEnabled(bool)
vfunc[207]:	QTable::setReadOnly(bool)
vfunc[208]:	QTable::setRowReadOnly(int, bool)
vfunc[209]:	QTable::setColumnReadOnly(int, bool)
vfunc[210]:	QTable::setDragEnabled(bool)
vfunc[211]:	QTable::insertRows(int, int)
vfunc[212]:	QTable::insertColumns(int, int)
vfunc[213]:	QTable::removeRow(int)
vfunc[214]:	QTable::removeRows(QMemArray<int> const&)

vfunc[215]:	QTable::removeColumn(int)
vfunc[216]:	QTable::removeColumns(QMemArray<int> const&)
vfunc[217]:	QTable::editCell(int, int, bool)
vfunc[218]:	QTable::dragObject()
vfunc[219]:	QTable::startDrag()
vfunc[220]:	QTable::paintEmptyArea(QPainter*, int, int, int, int)
vfunc[221]:	QDataTable::activateNextCell()
vfunc[222]:	QDataTable::createEditor(int, int, bool) const
vfunc[223]:	QTable::setCellContentFromEditor(int, int)
vfunc[224]:	QDataTable::beginEdit(int, int, bool)
vfunc[225]:	QDataTable::endEdit(int, int, bool, bool)
vfunc[226]:	QDataTable::resizeData(int)
vfunc[227]:	QTable::insertWidget(int, int, QWidget*)
vfunc[228]:	QTable::columnWidthChanged(int)
vfunc[229]:	QTable::rowHeightChanged(int)
vfunc[230]:	QTable::columnIndexChanged(int, int, int)
vfunc[231]:	QTable::rowIndexChanged(int, int, int)
vfunc[232]:	QDataTable::columnClicked(int)
vfunc[233]:	QDataTable::addColumn(QString const&, QString const&, int, QIconSet const&)
vfunc[234]:	QDataTable::removeColumn(unsigned int)
vfunc[235]:	QDataTable::setColumn(unsigned int, QString const&, QString const&, int, QIconSet const&)
vfunc[236]:	QDataTable::setSqlCursor(QSqlCursor*, bool, bool)
vfunc[237]:	QDataTable::setNullText(QString const&)
vfunc[238]:	QDataTable::setTrueText(QString const&)

vfunc[239]:	QDataTable::setFalseText(QString const&)
vfunc[240]:	QDataTable::setDateFormat(Qt::DateFormat)
vfunc[241]:	QDataTable::setConfirmEdits(bool)
vfunc[242]:	QDataTable::setConfirmInsert(bool)
vfunc[243]:	QDataTable::setConfirmUpdate(bool)
vfunc[244]:	QDataTable::setConfirmDelete(bool)
vfunc[245]:	QDataTable::setConfirmCancels(bool)
vfunc[246]:	QDataTable::setAutoDelete(bool)
vfunc[247]:	QDataTable::setAutoEdit(bool)
vfunc[248]:	QDataTable::setFilter(QString const&)
vfunc[249]:	QDataTable::setSort(QStringList const&)
vfunc[250]:	QDataTable::setSort(QSqlIndex const&)
vfunc[251]:	QDataTable::find(QString const&, bool, bool)
vfunc[252]:	QDataTable::sortAscending(int)
vfunc[253]:	QDataTable::sortDescending(int)
vfunc[254]:	QDataTable::refresh()
vfunc[255]:	QDataTable::insertCurrent()
vfunc[256]:	QDataTable::updateCurrent()
vfunc[257]:	QDataTable::deleteCurrent()
vfunc[258]:	QDataTable::confirmEdit(QSql::Op)
vfunc[259]:	QDataTable::confirmCancel(QSql::Op)
vfunc[260]:	QDataTable::handleError(QSqlError const&)
vfunc[261]:	QDataTable::beginInsert()
vfunc[262]:	QDataTable::beginUpdate(int, int, bool)
vfunc[263]:	QDataTable::paintField(QPainter*, QSqlField const*, QRect const&, bool)
vfunc[264]:	QDataTable::fieldAlignment(QSqlFie

	ld const*)
--	------------

Table 7-374 Secondary vtable for QDataTable

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDataTable
vfunc[0]:	non-virtual thunk to QDataTable::~~QDataTable()
vfunc[1]:	non-virtual thunk to QDataTable::~~QDataTable()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QDataTable class is described by Table 7-375

Table 7-375 typeinfo for QDataTable

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDataTable
basetype:	typeinfo for QTable

7.2.1.156 Class data for QDragMoveEvent

The virtual table for the QDragMoveEvent class is described by Table 7-376

Table 7-376 Primary vtable for QDragMoveEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDragMoveEvent

vfunc[0]:	QDragMoveEvent::~~QDragMoveEvent()
vfunc[1]:	QDragMoveEvent::~~QDragMoveEvent()
vfunc[2]:	QDropEvent::format(int) const
vfunc[3]:	QDropEvent::encodedData(char const*) const
vfunc[4]:	QDropEvent::provides(char const*) const

Table 7-377 Secondary vtable for QDragMoveEvent

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QDragMoveEvent
vfunc[0]:	non-virtual thunk to QDragMoveEvent::~~QDragMoveEvent()
vfunc[1]:	non-virtual thunk to QDragMoveEvent::~~QDragMoveEvent()
vfunc[2]:	non-virtual thunk to QDropEvent::format(int) const
vfunc[3]:	non-virtual thunk to QDropEvent::provides(char const*) const
vfunc[4]:	non-virtual thunk to QDropEvent::encodedData(char const*) const

The Run Time Type Information for the QDragMoveEvent class is described by Table 7-378

Table 7-378 typeinfo for QDragMoveEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDragMoveEvent
basetype:	typeinfo for QDropEvent

7.2.1.157 Class data for QCanvasEllipse

The virtual table for the QCanvasEllipse class is described by Table 7-379

Table 7-379 Primary vtable for QCanvasEllipse

Base Offset	0
-------------	---

Virtual Base Offset	0
RTTI	typeinfo for QCanvasEllipse
vfunc[0]:	QCanvasEllipse::~~QCanvasEllipse()
vfunc[1]:	QCanvasEllipse::~~QCanvasEllipse()
vfunc[2]:	QCanvasItem::moveBy(double, double)
vfunc[3]:	QCanvasItem::setAnimated(bool)
vfunc[4]:	QCanvasItem::setVelocity(double, double)
vfunc[5]:	QCanvasItem::advance(int)
vfunc[6]:	QCanvasEllipse::collidesWith(QCanvasItem const*) const
vfunc[7]:	QCanvasItem::setCanvas(QCanvas*)
vfunc[8]:	QCanvasPolygonalItem::draw(QPainter&)
vfunc[9]:	QCanvasItem::setVisible(bool)
vfunc[10]:	QCanvasItem::setSelected(bool)
vfunc[11]:	QCanvasItem::setEnabled(bool)
vfunc[12]:	QCanvasItem::setActive(bool)
vfunc[13]:	QCanvasEllipse::rtti() const
vfunc[14]:	QCanvasPolygonalItem::boundingRect() const
vfunc[15]:	QCanvasItem::boundingRectAdvanced() const
vfunc[16]:	QCanvasPolygonalItem::chunks() const
vfunc[17]:	QCanvasItem::addToChunks()
vfunc[18]:	QCanvasItem::removeFromChunks()
vfunc[19]:	QCanvasItem::changeChunks()
vfunc[20]:	QCanvasEllipse::collidesWith(QCanvasSprite const*, QCanvasPolygonalItem const*, QCanvasRectangle const*, QCanvasEllipse const*, QCanvasText const*) const
vfunc[21]:	QCanvasPolygonalItem::setPen(QPen)
vfunc[22]:	QCanvasPolygonalItem::setBrush(QBrush)

vfunc[23]:	QCanvasEllipse::areaPoints() const
vfunc[24]:	QCanvasPolygonalItem::areaPointsAdvanced() const
vfunc[25]:	QCanvasEllipse::drawShape(QPainter&)

The Run Time Type Information for the QCanvasEllipse class is described by Table 7-380

Table 7-380 typeinfo for QCanvasEllipse

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasEllipse
basetype:	typeinfo for QCanvasPolygonalItem

7.2.1.158 Class data for QDropEvent

The virtual table for the QDropEvent class is described by Table 7-381

Table 7-381 Primary vtable for QDropEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDropEvent
vfunc[0]:	QDropEvent::~~QDropEvent()
vfunc[1]:	QDropEvent::~~QDropEvent()
vfunc[2]:	QDropEvent::format(int) const
vfunc[3]:	QDropEvent::encodedData(char const*) const
vfunc[4]:	QDropEvent::provides(char const*) const

Table 7-382 Secondary vtable for QDropEvent

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QDropEvent
vfunc[0]:	non-virtual thunk to QDropEvent::~~QDropEvent()
vfunc[1]:	non-virtual thunk to QDropEvent::~~QDropEvent()
vfunc[2]:	non-virtual thunk to QDropEvent::format(int) const
vfunc[3]:	non-virtual thunk to QDropEvent::provides(char const*)

	const
vfunc[4]:	non-virtual thunk to QDropEvent::encodedData(char const*) const

The Run Time Type Information for the QDropEvent class is described by Table 7-383

Table 7-383 typeinfo for QDropEvent

Base Vtable	vtable for __cxxabiv1::__vmi_class _type_info	2
Name	typeinfo name for QDropEvent	
flags:	0	
basetype:	typeinfo for QEvent	
basetype:	typeinfo for QMimeSource	3074

7.2.1.159 Class data for QMainWindow

The virtual table for the QMainWindow class is described by Table 7-384

Table 7-384 Primary vtable for QMainWindow

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMainWindow
vfunc[0]:	QMainWindow::metaObject() const
vfunc[1]:	QMainWindow::className() const
vfunc[2]:	QMainWindow::qt_cast(char const*)
vfunc[3]:	QMainWindow::qt_invoke(int, QUObject*)
vfunc[4]:	QMainWindow::qt_emit(int, QUObject*)
vfunc[5]:	QMainWindow::qt_property(int, int, QVariant*)
vfunc[6]:	QMainWindow::~~QMainWindow()
vfunc[7]:	QMainWindow::~~QMainWindow()
vfunc[8]:	QMainWindow::event(QEvent*)
vfunc[9]:	QMainWindow::eventFilter(QObject* , QEvent*)
vfunc[10]:	QWidget::setName(char const*)

vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QMainWindow::childEvent(QChildE vent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPi

	xmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QMainWindow::show()
vfunc[48]:	QMainWindow::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QMainWindow::sizeHint() const
vfunc[59]:	QMainWindow::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)

vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QMainWindow::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)

vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QMainWindow::styleChange(QStyle &)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QMainWindow::setCentralWidget(QWidget*)
vfunc[111]:	QMainWindow::setDockEnabled(Qt::Dock, bool)
vfunc[112]:	QMainWindow::setDockEnabled(QDockWindow*, Qt::Dock, bool)
vfunc[113]:	QMainWindow::addDockWindow(QDockWindow*, Qt::Dock, bool)
vfunc[114]:	QMainWindow::addDockWindow(QDockWindow*, QString const&, Qt::Dock, bool)
vfunc[115]:	QMainWindow::moveDockWindow(QDockWindow*, Qt::Dock)
vfunc[116]:	QMainWindow::moveDockWindow(QDockWindow*, Qt::Dock, bool, int,

	int)
vfunc[117]:	QMainWindow::removeDockWindow(QDockWindow*)
vfunc[118]:	QMainWindow::dockingArea(QPoint const&)
vfunc[119]:	QMainWindow::isCustomizable() const
vfunc[120]:	QMainWindow::setRightJustification(bool)
vfunc[121]:	QMainWindow::setUsesBigPixmaps(bool)
vfunc[122]:	QMainWindow::setUsesTextLabel(bool)
vfunc[123]:	QMainWindow::setDockWindowsMovable(bool)
vfunc[124]:	QMainWindow::setOpaqueMoving(bool)
vfunc[125]:	QMainWindow::setDockMenuEnabled(bool)
vfunc[126]:	QMainWindow::whatsThis()
vfunc[127]:	QMainWindow::setAppropriate(QDockWindow*, bool)
vfunc[128]:	QMainWindow::customize()
vfunc[129]:	QMainWindow::setUpLayout()
vfunc[130]:	QMainWindow::showDockMenu(QPoint const&)
vfunc[131]:	QMainWindow::setMenuBar(QMenuBar*)
vfunc[132]:	QMainWindow::setStatusbar(QStatusBar*)
vfunc[133]:	QMainWindow::setToolTipGroup(QToolTipGroup*)

Table 7-385 Secondary vtable for QMainWindow

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QMainWindow
vfunc[0]:	non-virtual thunk to QMainWindow::~~QMainWindow()
vfunc[1]:	non-virtual thunk to QMainWindow::~~QMainWindow()

vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QMainWindow class is described by Table 7-386

Table 7-386 typeinfo for QMainWindow

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMainWindow
basetype:	typeinfo for QWidget

7.2.1.160 Class data for QStatusBar

The virtual table for the QStatusBar class is described by Table 7-387

Table 7-387 Primary vtable for QStatusBar

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QStatusBar
vfunc[0]:	QStatusBar::metaObject() const
vfunc[1]:	QStatusBar::className() const
vfunc[2]:	QStatusBar::qt_cast(char const*)
vfunc[3]:	QStatusBar::qt_invoke(int, QUObject*)
vfunc[4]:	QStatusBar::qt_emit(int, QUObject*)
vfunc[5]:	QStatusBar::qt_property(int, int, QVariant*)
vfunc[6]:	QStatusBar::~~QStatusBar()

vfunc[7]:	QStatusBar::~~QStatusBar()
vfunc[8]:	QStatusBar::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()

vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()

vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QStatusBar::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QStatusBar::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)

)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QStatusBar::addWidget(QWidget*, int, bool)
vfunc[111]:	QStatusBar::removeWidget(QWidget*)

Table 7-388 Secondary vtable for QStatusBar

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QStatusBar

vfunc[0]:	non-virtual thunk to QStatusBar::~~QStatusBar()
vfunc[1]:	non-virtual thunk to QStatusBar::~~QStatusBar()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QStatusBar class is described by Table 7-389

Table 7-389 typeinfo for QStatusBar

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStatusBar
basetype:	typeinfo for QWidget

7.2.1.161 Class data for QList

The virtual table for the QList class is described by Table 7-390

Table 7-390 Primary vtable for QList

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QList
vfunc[0]:	QPtrList<char>::count() const
vfunc[1]:	QPtrList<char>::clear()
vfunc[2]:	QList::~QList()
vfunc[3]:	QList::~QList()
vfunc[4]:	QList::newItem(void*)

vfunc[5]:	QStrList::deleteItem(void*)
vfunc[6]:	QStrList::compareItems(void*, void*)
vfunc[7]:	QStrList::read(QDataStream&, void*&)
vfunc[8]:	QStrList::write(QDataStream&, void*) const

The Run Time Type Information for the QStrList class is described by Table 7-391

Table 7-391 typeinfo for QStrList

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStrList
basetype:	typeinfo for QPtrList<char>

7.2.1.162 Class data for QTsciiCodec

The virtual table for the QTsciiCodec class is described by Table 7-392

Table 7-392 Primary vtable for QTsciiCodec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTsciiCodec
vfunc[0]:	QTsciiCodec::~~QTsciiCodec()
vfunc[1]:	QTsciiCodec::~~QTsciiCodec()
vfunc[2]:	QTsciiCodec::name() const
vfunc[3]:	QTextCodec::mimeTypeName() const
vfunc[4]:	QTsciiCodec::mibEnum() const
vfunc[5]:	QTextCodec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QTsciiCodec::toUnicode(char const*, int) const
vfunc[8]:	QTsciiCodec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QTsciiCodec::heuristicContentMatch(char const*, int) const
vfunc[12]:	QTsciiCodec::heuristicNameMatch(c

	har const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode(QString const&, int) const

The Run Time Type Information for the QTsciiCodec class is described by Table 7-393

Table 7-393 typeinfo for QTsciiCodec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTsciiCodec
basetype:	typeinfo for QTextCodec

7.2.1.163 Class data for QSqlDatabase

The virtual table for the QSqlDatabase class is described by Table 7-394

Table 7-394 Primary vtable for QSqlDatabase

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlDatabase
vfunc[0]:	QSqlDatabase::metaObject() const
vfunc[1]:	QSqlDatabase::className() const
vfunc[2]:	QSqlDatabase::qt_cast(char const*)
vfunc[3]:	QSqlDatabase::qt_invoke(int, QUObject*)
vfunc[4]:	QSqlDatabase::qt_emit(int, QUObject*)
vfunc[5]:	QSqlDatabase::qt_property(int, int, QVariant*)
vfunc[6]:	QSqlDatabase::~~QSqlDatabase()
vfunc[7]:	QSqlDatabase::~~QSqlDatabase()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)

vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QSqlDatabase::setDatabaseName(QString const&)
vfunc[22]:	QSqlDatabase::setUserName(QString const&)
vfunc[23]:	QSqlDatabase::setPassword(QString const&)
vfunc[24]:	QSqlDatabase::setHostName(QString const&)
vfunc[25]:	QSqlDatabase::setPort(int)

The Run Time Type Information for the QSqlDatabase class is described by Table 7-395

Table 7-395 typeinfo for QSqlDatabase

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSqlDatabase
basetype:	typeinfo for QObject

7.2.1.164 Class data for QCanvasPixmap

The virtual table for the QCanvasPixmap class is described by Table 7-396

Table 7-396 Primary vtable for QCanvasPixmap

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvasPixmap
vfunc[0]:	QCanvasPixmap::~~QCanvasPixmap()
vfunc[1]:	QCanvasPixmap::~~QCanvasPixmap()
vfunc[2]:	QPaintDevice::setResolution(int)

vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QDevCmdParam*)
vfunc[8]:	QPixmap::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const
vfunc[11]:	QPixmap::detach()

The Run Time Type Information for the QCanvasPixmap class is described by Table 7-397

Table 7-397 typeinfo for QCanvasPixmap

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasPixmap
basetype:	typeinfo for QPixmap

7.2.1.165 Class data for QPainter

The virtual table for the QPainter class is described by Table 7-398

Table 7-398 Primary vtable for QPainter

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPainter
vfunc[0]:	QPainter::~~QPainter()
vfunc[1]:	QPainter::~~QPainter()
vfunc[2]:	QPainter::setResolution(int)
vfunc[3]:	QPainter::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPainter::cmd(int, QPainter*,

	QPDevCmdParam*)
vfunc[8]:	QPrinter::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const
vfunc[11]:	QPrinter::setPrinterName(QString const&)
vfunc[12]:	QPrinter::setOutputToFile(bool)
vfunc[13]:	QPrinter::setOutputFileName(QString const&)
vfunc[14]:	QPrinter::setPrintProgram(QString const&)
vfunc[15]:	QPrinter::setPrinterSelectionOption(QString const&)
vfunc[16]:	QPrinter::setDocName(QString const&)
vfunc[17]:	QPrinter::setCreator(QString const&)
vfunc[18]:	QPrinter::setOrientation(QPrinter::Orientation)
vfunc[19]:	QPrinter::setPageSize(QPrinter::PageSize)
vfunc[20]:	QPrinter::setPageOrder(QPrinter::PageOrder)
vfunc[21]:	QPrinter::setColorMode(QPrinter::ColorMode)
vfunc[22]:	QPrinter::setFullPage(bool)
vfunc[23]:	QPrinter::setFromTo(int, int)
vfunc[24]:	QPrinter::setMinMax(int, int)
vfunc[25]:	QPrinter::setNumCopies(int)
vfunc[26]:	QPrinter::setPaperSource(QPrinter::PaperSource)

The Run Time Type Information for the QPrinter class is described by Table 7-399

Table 7-399 typeinfo for QPrinter

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPrinter
basetype:	typeinfo for QPaintDevice

7.2.1.166 Class data for QSjisCodec

The virtual table for the QSjisCodec class is described by Table 7-400

Table 7-400 Primary vtable for QSjisCodec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSjisCodec
vfunc[0]:	QSjisCodec::~~QSjisCodec()
vfunc[1]:	QSjisCodec::~~QSjisCodec()
vfunc[2]:	QSjisCodec::name() const
vfunc[3]:	QSjisCodec::mimeType() const
vfunc[4]:	QSjisCodec::mibEnum() const
vfunc[5]:	QSjisCodec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QSjisCodec::toUnicode(char const*, int) const
vfunc[8]:	QSjisCodec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QSjisCodec::heuristicContentMatch(char const*, int) const
vfunc[12]:	QSjisCodec::heuristicNameMatch(char const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode(QString const&, int) const

The Run Time Type Information for the QSjisCodec class is described by Table 7-401

Table 7-401 typeinfo for QSjisCodec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSjisCodec
basetype:	typeinfo for QTextCodec

7.2.1.167 Class data for QMessageBox

The virtual table for the QMessageBox class is described by Table 7-402

Table 7-402 Primary vtable for QMessageBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMessageBox
vfunc[0]:	QMessageBox::metaObject() const
vfunc[1]:	QMessageBox::className() const
vfunc[2]:	QMessageBox::qt_cast(char const*)
vfunc[3]:	QMessageBox::qt_invoke(int, QUObject*)
vfunc[4]:	QMessageBox::qt_emit(int, QUObject*)
vfunc[5]:	QMessageBox::qt_property(int, int, QVariant*)
vfunc[6]:	QMessageBox::~~QMessageBox()
vfunc[7]:	QMessageBox::~~QMessageBox()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)

vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QMessageBox::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()

vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QMessageBox::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QMessageBox::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)

vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QMessageBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QMessageBox::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QMessageBox::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool,

	bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 7-403 Secondary vtable for QMessageBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QMessageBox
vfunc[0]:	non-virtual thunk to QMessageBox::~~QMessageBox()
vfunc[1]:	non-virtual thunk to QMessageBox::~~QMessageBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QMessageBox class is described by Table 7-404

Table 7-404 typeinfo for QMessageBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMessageBox
basetype:	typeinfo for QDialog

7.2.1.168 Class data for QSound

The virtual table for the QSound class is described by Table 7-405

Table 7-405 Primary vtable for QSound

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSound
vfunc[0]:	QSound::metaObject() const
vfunc[1]:	QSound::className() const
vfunc[2]:	QSound::qt_cast(char const*)
vfunc[3]:	QSound::qt_invoke(int, QUObject*)
vfunc[4]:	QSound::qt_emit(int, QUObject*)
vfunc[5]:	QSound::qt_property(int, int, QVariant*)
vfunc[6]:	QSound::~~QSound()
vfunc[7]:	QSound::~~QSound()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)

vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
------------	---

The Run Time Type Information for the QSound class is described by Table 7-406

Table 7-406 typeinfo for QSound

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSound
basetype:	typeinfo for QObject

7.2.1.169 Class data for QEditorFactory

The virtual table for the QEditorFactory class is described by Table 7-407

Table 7-407 Primary vtable for QEditorFactory

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QEditorFactory
vfunc[0]:	QObject::metaObject() const
vfunc[1]:	QObject::className() const
vfunc[2]:	QObject::qt_cast(char const*)
vfunc[3]:	QObject::qt_invoke(int, QUObject*)
vfunc[4]:	QObject::qt_emit(int, QUObject*)
vfunc[5]:	QObject::qt_property(int, int, QVariant*)
vfunc[6]:	QEditorFactory::~~QEditorFactory()
vfunc[7]:	QEditorFactory::~~QEditorFactory()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)

vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QEditorFactory::createEditor(QWidget*, QVariant const&)

The Run Time Type Information for the QEditorFactory class is described by Table 7-408

Table 7-408 typeinfo for QEditorFactory

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QEditorFactory
basetype:	typeinfo for QObject

7.2.1.170 Class data for QEventLoop

The virtual table for the QEventLoop class is described by Table 7-409

Table 7-409 Primary vtable for QEventLoop

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QEventLoop
vfunc[0]:	QEventLoop::metaObject() const
vfunc[1]:	QEventLoop::className() const
vfunc[2]:	QEventLoop::qt_cast(char const*)
vfunc[3]:	QEventLoop::qt_invoke(int, QUObject*)
vfunc[4]:	QEventLoop::qt_emit(int, QUObject*)
vfunc[5]:	QEventLoop::qt_property(int, int, QVariant*)
vfunc[6]:	QEventLoop::~~QEventLoop()
vfunc[7]:	QEventLoop::~~QEventLoop()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)

vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QEventLoop::processEvents(unsigned int)
vfunc[22]:	QEventLoop::hasPendingEvents() const
vfunc[23]:	QEventLoop::registerSocketNotifier(QSocketNotifier*)
vfunc[24]:	QEventLoop::unregisterSocketNotifie r(QSocketNotifier*)
vfunc[25]:	QEventLoop::exec()
vfunc[26]:	QEventLoop::exit(int)
vfunc[27]:	QEventLoop::enterLoop()
vfunc[28]:	QEventLoop::exitLoop()
vfunc[29]:	QEventLoop::loopLevel() const
vfunc[30]:	QEventLoop::wakeUp()
vfunc[31]:	QEventLoop::appStartingUp()
vfunc[32]:	QEventLoop::appClosingDown()

The Run Time Type Information for the QEventLoop class is described by Table 7-410

Table 7-410 typeinfo for QEventLoop

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QEventLoop
basetype:	typeinfo for QObject

7.2.1.171 Class data for QSignal

The virtual table for the QSignal class is described by Table 7-411

Table 7-411 Primary vtable for QSignal

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSignal
vfunc[0]:	QSignal::metaObject() const
vfunc[1]:	QSignal::className() const
vfunc[2]:	QSignal::qt_cast(char const*)
vfunc[3]:	QSignal::qt_invoke(int, QUObject*)
vfunc[4]:	QSignal::qt_emit(int, QUObject*)
vfunc[5]:	QSignal::qt_property(int, int, QVariant*)
vfunc[6]:	QSignal::~~QSignal()
vfunc[7]:	QSignal::~~QSignal()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QSignal class is described by Table 7-412

Table 7-412 typeinfo for QSignal

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSignal
basetype:	typeinfo for QObject

7.2.1.172 Class data for QSizeGrip

The virtual table for the QSizeGrip class is described by Table 7-413

Table 7-413 Primary vtable for QSizeGrip

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSizeGrip
vfunc[0]:	QSizeGrip::metaObject() const
vfunc[1]:	QSizeGrip::className() const
vfunc[2]:	QSizeGrip::qt_cast(char const*)
vfunc[3]:	QSizeGrip::qt_invoke(int, QUObject*)
vfunc[4]:	QSizeGrip::qt_emit(int, QUObject*)
vfunc[5]:	QSizeGrip::qt_property(int, int, QVariant*)
vfunc[6]:	QSizeGrip::~QSizeGrip()
vfunc[7]:	QSizeGrip::~QSizeGrip()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QSizeGrip::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)

vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)

vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QSizeGrip::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QSizeGrip::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QSizeGrip::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)

vfunc[75]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QSizeGrip::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(

	bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, bool, QFont*)

Table 7-414 Secondary vtable for QSizeGrip

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QSizeGrip
vfunc[0]:	non-virtual thunk to QSizeGrip::~~QSizeGrip()
vfunc[1]:	non-virtual thunk to QSizeGrip::~~QSizeGrip()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QSizeGrip class is described by Table 7-415

Table 7-415 typeinfo for QSizeGrip

Base Vtable	vtable for
-------------	------------

	__cxxabiv1::__si_class_type_info
Name	typeinfo name for QSizeGrip
basetype:	typeinfo for QWidget

7.2.1.173 Class data for QList

The virtual table for the QList class is described by Table 7-416

Table 7-416 Primary vtable for QList

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QList
vfunc[0]:	QPtrList<QObject>::count() const
vfunc[1]:	QPtrList<QObject>::clear()
vfunc[2]:	QList::~QList()
vfunc[3]:	QList::~QList()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	QPtrList<QObject>::deleteItem(void*)
vfunc[6]:	QList::compareItems(void*, void*)
vfunc[7]:	QList::read(QDataStream&, void*&)
vfunc[8]:	QList::write(QDataStream&, void*) const

The Run Time Type Information for the QList class is described by Table 7-417

Table 7-417 typeinfo for QList

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QList
basetype:	typeinfo for QPtrList<QObject>

7.2.1.174 Class data for QDomComment

The virtual table for the QDomComment class is described by Table 7-418

Table 7-418 Primary vtable for QDomComment

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomComment
vfunc[0]:	QDomComment::~QDomComment()

vfunc[1]:	QDomComment::~~QDomComment()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomComment::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection()

	const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction() const
vfunc[39]:	QDomCharacterData::isCharacterDat a() const
vfunc[40]:	QDomComment::isComment() const
vfunc[41]:	QDomCharacterData::substringData(unsigned long, unsigned long)
vfunc[42]:	QDomCharacterData::appendData(Q String const&)
vfunc[43]:	QDomCharacterData::insertData(uns igned long, QString const&)
vfunc[44]:	QDomCharacterData::deleteData(uns igned long, unsigned long)
vfunc[45]:	QDomCharacterData::replaceData(u nsigned long, unsigned long, QString const&)
vfunc[46]:	QDomCharacterData::length() const
vfunc[47]:	QDomCharacterData::data() const
vfunc[48]:	QDomCharacterData::setData(QStrin g const&)

The Run Time Type Information for the QDomComment class is described by Table 7-419

Table 7-419 typeinfo for QDomComment

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomComment
basetype:	typeinfo for QDomCharacterData

7.2.1.175 Class data for QXmlDefaultHandler

The virtual table for the QXmlDefaultHandler class is described by Table 7-420

Table 7-420 Primary vtable for QXmlDefaultHandler

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlDefaultHandler
vfunc[0]:	QXmlDefaultHandler::setDocumentLocator(QXmlLocator*)
vfunc[1]:	QXmlDefaultHandler::startDocument()
vfunc[2]:	QXmlDefaultHandler::endDocument()
vfunc[3]:	QXmlDefaultHandler::startPrefixMapping(QString const&, QString const&)
vfunc[4]:	QXmlDefaultHandler::endPrefixMapping(QString const&)
vfunc[5]:	QXmlDefaultHandler::startElement(QString const&, QString const&, QString const&, QXmlAttributes const&)
vfunc[6]:	QXmlDefaultHandler::endElement(QString const&, QString const&, QString const&)
vfunc[7]:	QXmlDefaultHandler::characters(QString const&)
vfunc[8]:	QXmlDefaultHandler::ignorableWhitespace(QString const&)
vfunc[9]:	QXmlDefaultHandler::processingInstruction(QString const&, QString const&)
vfunc[10]:	QXmlDefaultHandler::skippedEntity(QString const&)
vfunc[11]:	QXmlDefaultHandler::errorString()
vfunc[12]:	QXmlDefaultHandler::~QXmlDefaultHandler()
vfunc[13]:	QXmlDefaultHandler::~QXmlDefaultHandler()
vfunc[14]:	QXmlDefaultHandler::warning(QXmlParseException const&)
vfunc[15]:	QXmlDefaultHandler::error(QXmlParseException const&)

vfunc[16]:	QXmlDefaultHandler::fatalError(QXmlParseException const&)
vfunc[17]:	QXmlDefaultHandler::notationDecl(QString const&, QString const&, QString const&)
vfunc[18]:	QXmlDefaultHandler::unparsedEntityDecl(QString const&, QString const&, QString const&, QString const&)
vfunc[19]:	QXmlDefaultHandler::resolveEntity(QString const&, QString const&, QXmlInputSource*&)
vfunc[20]:	QXmlDefaultHandler::startDTD(QString const&, QString const&, QString const&)
vfunc[21]:	QXmlDefaultHandler::endDTD()
vfunc[22]:	QXmlDefaultHandler::startEntity(QString const&)
vfunc[23]:	QXmlDefaultHandler::endEntity(QString const&)
vfunc[24]:	QXmlDefaultHandler::startCDATA()
vfunc[25]:	QXmlDefaultHandler::endCDATA()
vfunc[26]:	QXmlDefaultHandler::comment(QString const&)
vfunc[27]:	QXmlDefaultHandler::attributeDecl(QString const&, QString const&, QString const&, QString const&, QString const&)
vfunc[28]:	QXmlDefaultHandler::internalEntityDecl(QString const&, QString const&)
vfunc[29]:	QXmlDefaultHandler::externalEntityDecl(QString const&, QString const&, QString const&)

Table 7-421 Secondary vtable for QXmlDefaultHandler

Base Offset	-8
Virtual Base Offset	0
RTTI	typeinfo for QXmlDefaultHandler
vfunc[0]:	non-virtual thunk to QXmlDefaultHandler::warning(QXmlParseException const&)
vfunc[1]:	non-virtual thunk to

	QXmlDefaultHandler::error(QXmlParseException const&)
vfunc[2]:	non-virtual thunk to QXmlDefaultHandler::fatalError(QXmlParseException const&)
vfunc[3]:	non-virtual thunk to QXmlDefaultHandler::errorString()

Table 7-422 Secondary vtable for QXmlDefaultHandler

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QXmlDefaultHandler
vfunc[0]:	non-virtual thunk to QXmlDefaultHandler::notationDecl(QString const&, QString const&, QString const&)
vfunc[1]:	non-virtual thunk to QXmlDefaultHandler::unparsedEntityDecl(QString const&, QString const&, QString const&)
vfunc[2]:	non-virtual thunk to QXmlDefaultHandler::errorString()

Table 7-423 Secondary vtable for QXmlDefaultHandler

Base Offset	-24
Virtual Base Offset	0
RTTI	typeinfo for QXmlDefaultHandler
vfunc[0]:	non-virtual thunk to QXmlDefaultHandler::resolveEntity(QString const&, QString const&, QXmlInputSource*&)
vfunc[1]:	non-virtual thunk to QXmlDefaultHandler::errorString()

Table 7-424 Secondary vtable for QXmlDefaultHandler

Base Offset	-32
Virtual Base Offset	0
RTTI	typeinfo for QXmlDefaultHandler
vfunc[0]:	non-virtual thunk to QXmlDefaultHandler::startDTD(QString const&, QString const&, QString const&)

vfunc[1]:	non-virtual thunk to QXmlDefaultHandler::endDTD()
vfunc[2]:	non-virtual thunk to QXmlDefaultHandler::startEntity(QS tring const&)
vfunc[3]:	non-virtual thunk to QXmlDefaultHandler::endEntity(QSt ring const&)
vfunc[4]:	non-virtual thunk to QXmlDefaultHandler::startCDATA()
vfunc[5]:	non-virtual thunk to QXmlDefaultHandler::endCDATA()
vfunc[6]:	non-virtual thunk to QXmlDefaultHandler::comment(QStr ing const&)
vfunc[7]:	non-virtual thunk to QXmlDefaultHandler::errorString()

Table 7-425 Secondary vtable for QXmlDefaultHandler

Base Offset	-40
Virtual Base Offset	0
RTTI	typeinfo for QXmlDefaultHandler
vfunc[0]:	non-virtual thunk to QXmlDefaultHandler::attributeDecl(QString const&, QString const&, QString const&, QString const&, QString const&)
vfunc[1]:	non-virtual thunk to QXmlDefaultHandler::internalEntity Decl(QString const&, QString const&)
vfunc[2]:	non-virtual thunk to QXmlDefaultHandler::externalEntity Decl(QString const&, QString const&, QString const&)
vfunc[3]:	non-virtual thunk to QXmlDefaultHandler::errorString()

The Run Time Type Information for the QXmlDefaultHandler class is described by Table 7-426

Table 7-426 typeinfo for QXmlDefaultHandler

Base Vtable	vtable for __cxxabiv1::__vmi_class _type_info	
-------------	---	--

Name	typeinfo name for QXmlDefaultHandler	2
flags:	0	
basetype:	typeinfo for QXmlContentHandler	
basetype:	typeinfo for QXmlErrorHandler	1026
basetype:	typeinfo for QXmlErrorHandler	2050
basetype:	typeinfo for QXmlErrorHandler	1026
basetype:	typeinfo for QXmlErrorHandler	2050
basetype:	typeinfo for QXmlErrorHandler	1026

7.2.1.176 Class data for QDataSink

The virtual table for the QDataSink class is described by Table 7-427

Table 7-427 Primary vtable for QDataSink

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDataSink
vfunc[0]:	QDataSink::~~QDataSink()
vfunc[1]:	QDataSink::~~QDataSink()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual

The Run Time Type Information for the QDataSink class is described by Table 7-428

Table 7-428 typeinfo for QDataSink

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDataSink
basetype:	typeinfo for QAsyncIO

7.2.1.177 Class data for QSqlDriverPlugin

The virtual table for the QSqlDriverPlugin class is described by Table 7-429

Table 7-429 Primary vtable for QSqlDriverPlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlDriverPlugin
vfunc[0]:	QSqlDriverPlugin::metaObject() const
vfunc[1]:	QSqlDriverPlugin::className() const
vfunc[2]:	QSqlDriverPlugin::qt_cast(char const*)
vfunc[3]:	QSqlDriverPlugin::qt_invoke(int, QIODevice*)
vfunc[4]:	QSqlDriverPlugin::qt_emit(int, QIODevice*)
vfunc[5]:	QSqlDriverPlugin::qt_property(int, int, QVariant*)
vfunc[6]:	QSqlDriverPlugin::~~QSqlDriverPlugi n()
vfunc[7]:	QSqlDriverPlugin::~~QSqlDriverPlugi n()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	__cxa_pure_virtual
vfunc[22]:	__cxa_pure_virtual

The Run Time Type Information for the QSqlDriverPlugin class is described by Table 7-430

Table 7-430 typeinfo for QSqlDriverPlugin

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSqlDriverPlugin
basetype:	typeinfo for QGPlugin

7.2.1.178 Class data for QToolButton

The virtual table for the QToolButton class is described by Table 7-431

Table 7-431 Primary vtable for QToolButton

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QToolButton
vfunc[0]:	QToolButton::metaObject() const
vfunc[1]:	QToolButton::className() const
vfunc[2]:	QToolButton::qt_cast(char const*)
vfunc[3]:	QToolButton::qt_invoke(int, QUObject*)
vfunc[4]:	QToolButton::qt_emit(int, QUObject*)
vfunc[5]:	QToolButton::qt_property(int, int, QVariant*)
vfunc[6]:	QToolButton::~~QToolButton()
vfunc[7]:	QToolButton::~~QToolButton()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QToolButton::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)

vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::F

	ocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QToolButton::sizeHint() const
vfunc[59]:	QToolButton::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QToolButton::mousePressEvent(QMouseEvent*)
vfunc[70]:	QButton::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QButton::mouseMoveEvent(QMouseEvent*)

vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QPushButton::keyPressEvent(QKeyEvent*)
vfunc[75]:	QPushButton::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QPushButton::focusInEvent(QFocusEvent*)
vfunc[77]:	QPushButton::focusOutEvent(QFocusEvent*)
vfunc[78]:	QToolButton::enterEvent(QEvent*)
vfunc[79]:	QToolButton::leaveEvent(QEvent*)
vfunc[80]:	QPushButton::paintEvent(QPaintEvent*)
vfunc[81]:	QToolButton::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QPushButton::enabledChange(bool)

vfunc[99]:	QToolButton::paletteChange(QPalett e const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QToolButton::setText(QString const&)
vfunc[111]:	QButton::setPixmap(QPixmap const&)
vfunc[112]:	QButton::setAccel(QKeySequence const&)
vfunc[113]:	QButton::setDown(bool)
vfunc[114]:	QButton::setAutoRepeat(bool)
vfunc[115]:	QButton::setToggleType(QButton::To ggleType)
vfunc[116]:	QButton::setState(QButton::ToggleSt ate)
vfunc[117]:	QButton::hitButton(QPoint const&) const
vfunc[118]:	QToolButton::drawButton(QPainter*)
vfunc[119]:	QToolButton::drawButtonLabel(QPai nter*)
vfunc[120]:	QButton::setGroup(QButtonGroup*)
vfunc[121]:	QToolButton::setIconSet(QIconSet const&)
vfunc[122]:	QToolButton::setUsesBigPixmap(boo l)
vfunc[123]:	QToolButton::setUsesTextLabel(bool)
vfunc[124]:	QToolButton::setTextLabel(QString

	const&, bool)
vfunc[125]:	QToolButton::setToggleButton(bool)
vfunc[126]:	QToolButton::setOn(bool)

Table 7-432 Secondary vtable for QToolButton

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QToolButton
vfunc[0]:	non-virtual thunk to QToolButton::~~QToolButton()
vfunc[1]:	non-virtual thunk to QToolButton::~~QToolButton()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPaintDevice::CmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QToolButton class is described by Table 7-433

Table 7-433 typeinfo for QToolButton

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QToolButton
basetype:	typeinfo for QButton

7.2.1.179 Class data for QWidgetIntDict

The virtual table for the QWidgetIntDict class is described by Table 7-434

Table 7-434 Primary vtable for QWidgetIntDict

Base Offset	0
-------------	---

Virtual Base Offset	0
RTTI	typeinfo for QWidgetIntDict
vfunc[0]:	QIntDict<QWidget>::count() const
vfunc[1]:	QIntDict<QWidget>::clear()
vfunc[2]:	QWidgetIntDict::~~QWidgetIntDict()
vfunc[3]:	QWidgetIntDict::~~QWidgetIntDict()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	QIntDict<QWidget>::deleteItem(void*)
vfunc[6]:	QGDICT::read(QDataStream&, void*&)
vfunc[7]:	QGDICT::write(QDataStream&, void*) const

The Run Time Type Information for the QWidgetIntDict class is described by Table 7-435

Table 7-435 typeinfo for QWidgetIntDict

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWidgetIntDict
basetype:	typeinfo for QIntDict<QWidget>

7.2.1.180 Class data for QTabBar

The virtual table for the QTabBar class is described by Table 7-436

Table 7-436 Primary vtable for QTabBar

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTabBar
vfunc[0]:	QTabBar::metaObject() const
vfunc[1]:	QTabBar::className() const
vfunc[2]:	QTabBar::qt_cast(char const*)
vfunc[3]:	QTabBar::qt_invoke(int, QUObject*)
vfunc[4]:	QTabBar::qt_emit(int, QUObject*)
vfunc[5]:	QTabBar::qt_property(int, int, QVariant*)
vfunc[6]:	QTabBar::~~QTabBar()
vfunc[7]:	QTabBar::~~QTabBar()

vfunc[8]:	QTabBar::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)

vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QTabBar::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QTabBar::sizeHint() const
vfunc[59]:	QTabBar::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*,

	unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QTabBar::mousePressEvent(QMouseEvent*)
vfunc[70]:	QTabBar::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QTabBar::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QTabBar::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QTabBar::focusInEvent(QFocusEvent*)
vfunc[77]:	QTabBar::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QTabBar::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QTabBar::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnt

	erEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QTabBar::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QTabBar::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QTabBar::setShape(QTabBar::Shape)
vfunc[111]:	QTabBar::addTab(QTab*)
vfunc[112]:	QTabBar::insertTab(QTab*, int)
vfunc[113]:	QTabBar::removeTab(QTab*)
vfunc[114]:	QTabBar::setTabEnabled(int, bool)
vfunc[115]:	QTabBar::layoutTabs()
vfunc[116]:	QTabBar::selectTab(QPoint const& const)
vfunc[117]:	QTabBar::setCurrentTab(int)
vfunc[118]:	QTabBar::setCurrentTab(QTab*)

vfunc[119]:	QTabBar::paint(QPainter*, QTab*, bool) const
vfunc[120]:	QTabBar::paintLabel(QPainter*, QRect const&, QTab*, bool) const

Table 7-437 Secondary vtable for QTabBar

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QTabBar
vfunc[0]:	non-virtual thunk to QTabBar::~~QTabBar()
vfunc[1]:	non-virtual thunk to QTabBar::~~QTabBar()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QTabBar class is described by Table 7-438

Table 7-438 typeinfo for QTabBar

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTabBar
basetype:	typeinfo for QWidget

7.2.1.181 Class data for QDomNotation

The virtual table for the QDomNotation class is described by Table 7-439

Table 7-439 Primary vtable for QDomNotation

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomNotation
vfunc[0]:	QDomNotation::~~QDomNotation()
vfunc[1]:	QDomNotation::~~QDomNotation()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomNotation::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString)

	const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNotation::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction() const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const

The Run Time Type Information for the QDomNotation class is described by Table 7-440

Table 7-440 typeinfo for QDomNotation

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomNotation
basetype:	typeinfo for QDomNode

7.2.1.182 Class data for QXmlSimpleReader

The virtual table for the QXmlSimpleReader class is described by Table 7-441

Table 7-441 Primary vtable for QXmlSimpleReader

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlSimpleReader
vfunc[0]:	QXmlSimpleReader::feature(QString const&, bool*) const

vfunc[1]:	QXmlSimpleReader::setFeature(QString const&, bool)
vfunc[2]:	QXmlSimpleReader::hasFeature(QString const&) const
vfunc[3]:	QXmlSimpleReader::property(QString const&, bool*) const
vfunc[4]:	QXmlSimpleReader::setProperty(QString const&, void*)
vfunc[5]:	QXmlSimpleReader::hasProperty(QString const&) const
vfunc[6]:	QXmlSimpleReader::setEntityResolver(QXmlEntityResolver*)
vfunc[7]:	QXmlSimpleReader::entityResolver() const
vfunc[8]:	QXmlSimpleReader::setDTDHandler(QXmlDTDHandler*)
vfunc[9]:	QXmlSimpleReader::DTDHandler() const
vfunc[10]:	QXmlSimpleReader::setContentHandler(QXmlContentHandler*)
vfunc[11]:	QXmlSimpleReader::contentHandler() const
vfunc[12]:	QXmlSimpleReader::setErrorHandler(QXmlErrorHandler*)
vfunc[13]:	QXmlSimpleReader::errorHandler() const
vfunc[14]:	QXmlSimpleReader::setLexicalHandler(QXmlLexicalHandler*)
vfunc[15]:	QXmlSimpleReader::lexicalHandler() const
vfunc[16]:	QXmlSimpleReader::setDeclHandler(QXmlDeclHandler*)
vfunc[17]:	QXmlSimpleReader::declHandler() const
vfunc[18]:	QXmlSimpleReader::parse(QXmlInputSource const&)
vfunc[19]:	QXmlSimpleReader::parse(QXmlInputSource const*)
vfunc[20]:	QXmlSimpleReader::~QXmlSimpleReader()
vfunc[21]:	QXmlSimpleReader::~~QXmlSimpleReader()

vfunc[22]:	QXmlSimpleReader::parse(QXmlInputSource const*, bool)
vfunc[23]:	QXmlSimpleReader::parseContinue()

The Run Time Type Information for the QXmlSimpleReader class is described by Table 7-442

Table 7-442 typeinfo for QXmlSimpleReader

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QXmlSimpleReader
basetype:	typeinfo for QXmlReader

7.2.1.183 Class data for QHideEvent

The virtual table for the QHideEvent class is described by Table 7-443

Table 7-443 Primary vtable for QHideEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHideEvent
vfunc[0]:	QHideEvent::~~QHideEvent()
vfunc[1]:	QHideEvent::~~QHideEvent()

The Run Time Type Information for the QHideEvent class is described by Table 7-444

Table 7-444 typeinfo for QHideEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHideEvent
basetype:	typeinfo for QEvent

7.2.1.184 Class data for QToolTip

The virtual table for the QToolTip class is described by Table 7-445

Table 7-445 Primary vtable for QToolTip

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QToolTip
vfunc[0]:	__cxa_pure_virtual

The Run Time Type Information for the QToolTip class is described by Table 7-446

Table 7-446 typeinfo for QToolTip

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QToolTip
basetype:	typeinfo for Qt

7.2.1.185 Class data for QResizeEvent

The virtual table for the QResizeEvent class is described by Table 7-447

Table 7-447 Primary vtable for QResizeEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QResizeEvent
vfunc[0]:	QResizeEvent::~~QResizeEvent()
vfunc[1]:	QResizeEvent::~~QResizeEvent()

The Run Time Type Information for the QResizeEvent class is described by Table 7-448

Table 7-448 typeinfo for QResizeEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QResizeEvent
basetype:	typeinfo for QEvent

7.2.1.186 Class data for QXmlLexicalHandler

The virtual table for the QXmlLexicalHandler class is described by Table 7-449

Table 7-449 Primary vtable for QXmlLexicalHandler

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlLexicalHandler
vfunc[0]:	__cxa_pure_virtual
vfunc[1]:	__cxa_pure_virtual
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlLexicalHandler class is described by Table 7-450

Table 7-450 typeinfo for QXmlLexicalHandler

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlLexicalHandler

7.2.1.187 Class data for QCanvasLine

The virtual table for the QCanvasLine class is described by Table 7-451

Table 7-451 Primary vtable for QCanvasLine

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvasLine
vfunc[0]:	QCanvasLine::~~QCanvasLine()
vfunc[1]:	QCanvasLine::~~QCanvasLine()
vfunc[2]:	QCanvasLine::moveBy(double, double)
vfunc[3]:	QCanvasItem::setAnimated(bool)
vfunc[4]:	QCanvasItem::setVelocity(double, double)
vfunc[5]:	QCanvasItem::advance(int)
vfunc[6]:	QCanvasPolygonalItem::collidesWith (QCanvasItem const*) const
vfunc[7]:	QCanvasItem::setCanvas(QCanvas*)
vfunc[8]:	QCanvasPolygonalItem::draw(QPainter&)
vfunc[9]:	QCanvasItem::setVisible(bool)
vfunc[10]:	QCanvasItem::setSelected(bool)
vfunc[11]:	QCanvasItem::setEnabled(bool)
vfunc[12]:	QCanvasItem::setActive(bool)
vfunc[13]:	QCanvasLine::rtti() const
vfunc[14]:	QCanvasPolygonalItem::boundingRect() const
vfunc[15]:	QCanvasItem::boundingRectAdvanced() const
vfunc[16]:	QCanvasPolygonalItem::chunks() const

vfunc[17]:	QCanvasItem::addToChunks()
vfunc[18]:	QCanvasItem::removeFromChunks()
vfunc[19]:	QCanvasItem::changeChunks()
vfunc[20]:	QCanvasPolygonalItem::collidesWith (QCanvasSprite const*, QCanvasPolygonalItem const*, QCanvasRectangle const*, QCanvasEllipse const*, QCanvasText const*) const
vfunc[21]:	QCanvasLine::setPen(QPen)
vfunc[22]:	QCanvasPolygonalItem::setBrush(QBrush)
vfunc[23]:	QCanvasLine::areaPoints() const
vfunc[24]:	QCanvasPolygonalItem::areaPointsAdvanced() const
vfunc[25]:	QCanvasLine::drawShape(QPainter&)

The Run Time Type Information for the QCanvasLine class is described by Table 7-452

Table 7-452 typeinfo for QCanvasLine

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasLine
basetype:	typeinfo for QCanvasPolygonalItem

7.2.1.188 Class data for QXmlAttributes

The virtual table for the QXmlAttributes class is described by Table 7-453

Table 7-453 Primary vtable for QXmlAttributes

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlAttributes
vfunc[0]:	QXmlAttributes::~~QXmlAttributes()
vfunc[1]:	QXmlAttributes::~~QXmlAttributes()

The Run Time Type Information for the QXmlAttributes class is described by Table 7-454

Table 7-454 typeinfo for QXmlAttributes

Base Vtable	vtable for __cxxabiv1::__class_type_info
-------------	---

Name	typeinfo name for QXmlAttributes
------	----------------------------------

7.2.1.189 Class data for QDialog

The virtual table for the QDialog class is described by Table 7-455

Table 7-455 Primary vtable for QDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDialog
vfunc[0]:	QDialog::metaObject() const
vfunc[1]:	QDialog::className() const
vfunc[2]:	QDialog::qt_cast(char const*)
vfunc[3]:	QDialog::qt_invoke(int, QUObject*)
vfunc[4]:	QDialog::qt_emit(int, QUObject*)
vfunc[5]:	QDialog::qt_property(int, int, QVariant*)
vfunc[6]:	QDialog::~~QDialog()
vfunc[7]:	QDialog::~~QDialog()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)

vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPi xmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::F ocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()

vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)

vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)

vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 7-456 Secondary vtable for QDialog

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDialog
vfunc[0]:	non-virtual thunk to QDialog::~~QDialog()
vfunc[1]:	non-virtual thunk to QDialog::~~QDialog()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QDialog class is described by Table 7-457

Table 7-457 typeinfo for QDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
-------------	--

Name	typeinfo name for QDialog
basetype:	typeinfo for QWidget

7.2.1.190 Class data for QGLayoutIterator

The virtual table for the QGLayoutIterator class is described by Table 7-458

Table 7-458 Primary vtable for QGLayoutIterator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGLayoutIterator
vfunc[0]:	QGLayoutIterator::~~QGLayoutIterator()
vfunc[1]:	QGLayoutIterator::~~QGLayoutIterator()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual

The Run Time Type Information for the QGLayoutIterator class is described by Table 7-459

Table 7-459 typeinfo for QGLayoutIterator

Base Vtable	vtable for __cxxabiv1::__vmi_class _type_info	1026
Name	typeinfo name for QGLayoutIterator	
flags:	0	
basetype:	typeinfo for QShared	

7.2.1.191 Class data for QTabletEvent

The virtual table for the QTabletEvent class is described by Table 7-460

Table 7-460 Primary vtable for QTabletEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTabletEvent
vfunc[0]:	QTabletEvent::~~QTabletEvent()
vfunc[1]:	QTabletEvent::~~QTabletEvent()

The Run Time Type Information for the QTabletEvent class is described by Table 7-461

Table 7-461 typeinfo for QTabletEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTabletEvent
basetype:	typeinfo for QEvent

7.2.1.192 Class data for QWidgetItem

The virtual table for the QWidgetItem class is described by Table 7-462

Table 7-462 Primary vtable for QWidgetItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWidgetItem
vfunc[0]:	QWidgetItem::~~QWidgetItem()
vfunc[1]:	QWidgetItem::~~QWidgetItem()
vfunc[2]:	QWidgetItem::sizeHint() const
vfunc[3]:	QWidgetItem::minimumSize() const
vfunc[4]:	QWidgetItem::maximumSize() const
vfunc[5]:	QWidgetItem::expanding() const
vfunc[6]:	QWidgetItem::setGeometry(QRect const&)
vfunc[7]:	QWidgetItem::geometry() const
vfunc[8]:	QWidgetItem::isEmpty() const
vfunc[9]:	QWidgetItem::hasHeightForWidth() const
vfunc[10]:	QWidgetItem::heightForWidth(int) const
vfunc[11]:	QLayoutItem::invalidate()
vfunc[12]:	QWidgetItem::widget()
vfunc[13]:	QLayoutItem::iterator()
vfunc[14]:	QLayoutItem::layout()
vfunc[15]:	QLayoutItem::spacerItem()
vfunc[16]:	QLayoutItem::setAlignment(int)

The Run Time Type Information for the QWidgetItem class is described by Table 7-463

Table 7-463 typeinfo for QWidgetItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
-------------	--

Name	typeinfo name for QWidgetItem
basetype:	typeinfo for QLayoutItem

7.2.1.193 Class data for QDir

The virtual table for the QDir class is described by Table 7-464

Table 7-464 Primary vtable for QDir

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDir
vfunc[0]:	QDir::~~QDir()
vfunc[1]:	QDir::~~QDir()
vfunc[2]:	QDir::setPath(QString const&)
vfunc[3]:	QDir::path() const
vfunc[4]:	QDir::absPath() const
vfunc[5]:	QDir::canonicalPath() const
vfunc[6]:	QDir::dirName() const
vfunc[7]:	QDir::filePath(QString const&, bool) const
vfunc[8]:	QDir::absFilePath(QString const&, bool) const
vfunc[9]:	QDir::cd(QString const&, bool)
vfunc[10]:	QDir::cdUp()
vfunc[11]:	QDir::setNameFilter(QString const&)
vfunc[12]:	QDir::setFilter(int)
vfunc[13]:	QDir::setSorting(int)
vfunc[14]:	QDir::setMatchAllDirs(bool)
vfunc[15]:	QDir::encodedEntryList(int, int) const
vfunc[16]:	QDir::encodedEntryList(QString const&, int, int) const
vfunc[17]:	QDir::entryList(int, int) const
vfunc[18]:	QDir::entryList(QString const&, int, int) const
vfunc[19]:	QDir::entryInfoList(int, int) const
vfunc[20]:	QDir::entryInfoList(QString const&, int, int) const
vfunc[21]:	QDir::mkdir(QString const&, bool)

	const
vfunc[22]:	QDir::rmdir(QString const&, bool) const
vfunc[23]:	QDir::isReadable() const
vfunc[24]:	QDir::exists() const
vfunc[25]:	QDir::isRoot() const
vfunc[26]:	QDir::isRelative() const
vfunc[27]:	QDir::convertToAbs()
vfunc[28]:	QDir::operator==(QDir const&) const
vfunc[29]:	QDir::operator!=(QDir const&) const
vfunc[30]:	QDir::remove(QString const&, bool)
vfunc[31]:	QDir::rename(QString const&, QString const&, bool)
vfunc[32]:	QDir::exists(QString const&, bool)
vfunc[33]:	QDir::readDirEntries(QString const&, int, int)

The Run Time Type Information for the QDir class is described by Table 7-465

Table 7-465 typeinfo for QDir

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QDir

7.2.1.194 Class data for QDomProcessingInstruction

The virtual table for the QDomProcessingInstruction class is described by Table 7-466

Table 7-466 Primary vtable for QDomProcessingInstruction

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomProcessingInstruction
vfunc[0]:	QDomProcessingInstruction::~~QDomProcessingInstruction()
vfunc[1]:	QDomProcessingInstruction::~~QDomProcessingInstruction()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)

vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomProcessingInstruction::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const

vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomProcessingInstruction::isProcessingInstruction() const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const
vfunc[41]:	QDomProcessingInstruction::target() const
vfunc[42]:	QDomProcessingInstruction::data() const
vfunc[43]:	QDomProcessingInstruction::setData(QString const&)

The Run Time Type Information for the QDomProcessingInstruction class is described by Table 7-467

Table 7-467 typeinfo for QDomProcessingInstruction

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomProcessingInstruction
basetype:	typeinfo for QDomNode

7.2.1.195 Class data for QCanvasSpline

The virtual table for the QCanvasSpline class is described by Table 7-468

Table 7-468 Primary vtable for QCanvasSpline

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvasSpline
vfunc[0]:	QCanvasSpline::~~QCanvasSpline()
vfunc[1]:	QCanvasSpline::~~QCanvasSpline()
vfunc[2]:	QCanvasPolygon::moveBy(double, double)
vfunc[3]:	QCanvasItem::setAnimated(bool)

vfunc[4]:	QCanvasItem::setVelocity(double, double)
vfunc[5]:	QCanvasItem::advance(int)
vfunc[6]:	QCanvasPolygonalItem::collidesWith(QCanvasItem const*) const
vfunc[7]:	QCanvasItem::setCanvas(QCanvas*)
vfunc[8]:	QCanvasPolygonalItem::draw(QPainter&)
vfunc[9]:	QCanvasItem::setVisible(bool)
vfunc[10]:	QCanvasItem::setSelected(bool)
vfunc[11]:	QCanvasItem::setEnabled(bool)
vfunc[12]:	QCanvasItem::setActive(bool)
vfunc[13]:	QCanvasSpline::rtti() const
vfunc[14]:	QCanvasPolygonalItem::boundingRect() const
vfunc[15]:	QCanvasItem::boundingRectAdvanced() const
vfunc[16]:	QCanvasPolygonalItem::chunks() const
vfunc[17]:	QCanvasItem::addToChunks()
vfunc[18]:	QCanvasItem::removeFromChunks()
vfunc[19]:	QCanvasItem::changeChunks()
vfunc[20]:	QCanvasPolygonalItem::collidesWith(QCanvasSprite const*, QCanvasPolygonalItem const*, QCanvasRectangle const*, QCanvasEllipse const*, QCanvasText const*) const
vfunc[21]:	QCanvasPolygonalItem::setPen(QPen)
vfunc[22]:	QCanvasPolygonalItem::setBrush(QBrush)
vfunc[23]:	QCanvasPolygon::areaPoints() const
vfunc[24]:	QCanvasPolygonalItem::areaPointsAdvanced() const
vfunc[25]:	QCanvasPolygon::drawShape(QPainter&)

The Run Time Type Information for the QCanvasSpline class is described by Table 7-469

Table 7-469 typeinfo for QCanvasSpline

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasSpline
basetype:	typeinfo for QCanvasPolygon

7.2.1.196 Class data for QFontDialog

The virtual table for the QFontDialog class is described by Table 7-470

Table 7-470 Primary vtable for QFontDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFontDialog
vfunc[0]:	QFontDialog::metaObject() const
vfunc[1]:	QFontDialog::className() const
vfunc[2]:	QFontDialog::qt_cast(char const*)
vfunc[3]:	QFontDialog::qt_invoke(int, QUObject*)
vfunc[4]:	QFontDialog::qt_emit(int, QUObject*)
vfunc[5]:	QFontDialog::qt_property(int, int, QVariant*)
vfunc[6]:	QFontDialog::~~QFontDialog()
vfunc[7]:	QFontDialog::~~QFontDialog()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QFontDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char

	const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QFontDialog::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)

vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QDialog::keyPressEvent(QKeyEvent*)

vfunc[75]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)

vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 7-471 Secondary vtable for QFontDialog

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QFontDialog
vfunc[0]:	non-virtual thunk to QFontDialog::~~QFontDialog()
vfunc[1]:	non-virtual thunk to QFontDialog::~~QFontDialog()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QFontDialog class is described by Table 7-472

Table 7-472 typeinfo for QFontDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFontDialog
basetype:	typeinfo for QDialog

7.2.1.197 Class data for QGArray

The virtual table for the QGArray class is described by Table 7-473

Table 7-473 Primary vtable for QGArray

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGArray
vfunc[0]:	QGArray::~~QGArray()
vfunc[1]:	QGArray::~~QGArray()
vfunc[2]:	QGArray::detach()
vfunc[3]:	QGArray::newData()
vfunc[4]:	QGArray::deleteData(QGArray::array_data*)

The Run Time Type Information for the QGArray class is described by Table 7-474

Table 7-474 typeinfo for QGArray

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QGArray

7.2.1.198 Class data for QBitArray

The virtual table for the QBitArray class is described by Table 7-475

Table 7-475 Primary vtable for QBitArray

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QBitArray
vfunc[0]:	QBitArray::~~QBitArray()
vfunc[1]:	QBitArray::~~QBitArray()
vfunc[2]:	QBitArray::detach()
vfunc[3]:	QBitArray::newData()
vfunc[4]:	QBitArray::deleteData(QGArray::array_data*)

The Run Time Type Information for the QBitArray class is described by Table 7-476

Table 7-476 typeinfo for QBitArray

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QBitArray
basetype:	typeinfo for QMemArray<char>

7.2.1.199 Class data for QCheckBox

The virtual table for the QCheckBox class is described by Table 7-477

Table 7-477 Primary vtable for QCheckBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCheckBox
vfunc[0]:	QCheckBox::metaObject() const
vfunc[1]:	QCheckBox::className() const
vfunc[2]:	QCheckBox::qt_cast(char const*)
vfunc[3]:	QCheckBox::qt_invoke(int, QUObject*)
vfunc[4]:	QCheckBox::qt_emit(int, QUObject*)
vfunc[5]:	QCheckBox::qt_property(int, int, QVariant*)
vfunc[6]:	QCheckBox::~~QCheckBox()
vfunc[7]:	QCheckBox::~~QCheckBox()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)

vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::F

	ocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QCheckBox::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QPushButton::mousePressEvent(QMouseEvent*)
vfunc[70]:	QPushButton::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QPushButton::mouseMoveEvent(QMouseEvent*)

vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QPushButton::keyPressEvent(QKeyEvent*)
vfunc[75]:	QPushButton::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QPushButton::focusInEvent(QFocusEvent*)
vfunc[77]:	QPushButton::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QPushButton::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QCheckBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QCheckBox::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QPushButton::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette)

	const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QPushButton::setText(QString const&)
vfunc[111]:	QPushButton::setPixmap(QPixmap const&)
vfunc[112]:	QPushButton::setAccel(QKeySequence const&)
vfunc[113]:	QPushButton::setDown(bool)
vfunc[114]:	QPushButton::setAutoRepeat(bool)
vfunc[115]:	QPushButton::setToggleType(QPushButton::ToggleType)
vfunc[116]:	QPushButton::setState(QPushButton::ToggleState)
vfunc[117]:	QCheckBox::hitButton(QPoint const&) const
vfunc[118]:	QCheckBox::drawButton(QPainter*)
vfunc[119]:	QCheckBox::drawButtonLabel(QPainter*)
vfunc[120]:	QPushButton::setGroup(QButtonGroup*)

Table 7-478 Secondary vtable for QCheckBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QCheckBox
vfunc[0]:	non-virtual thunk to QCheckBox::~~QCheckBox()
vfunc[1]:	non-virtual thunk to

	QCheckBox::~~QCheckBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QCheckBox class is described by Table 7-479

Table 7-479 typeinfo for QCheckBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCheckBox
basetype:	typeinfo for QPushButton

7.2.1.200 Class data for QDockWindow

The virtual table for the QDockWindow class is described by Table 7-480

Table 7-480 Primary vtable for QDockWindow

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDockWindow
vfunc[0]:	QDockWindow::metaObject() const
vfunc[1]:	QDockWindow::className() const
vfunc[2]:	QDockWindow::qt_cast(char const*)
vfunc[3]:	QDockWindow::qt_invoke(int, QUObject*)
vfunc[4]:	QDockWindow::qt_emit(int, QUObject*)
vfunc[5]:	QDockWindow::qt_property(int, int,

	QVariant*)
vfunc[6]:	QDockWindow::~~QDockWindow()
vfunc[7]:	QDockWindow::~~QDockWindow()
vfunc[8]:	QDockWindow::event(QEvent*)
vfunc[9]:	QDockWindow::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)

vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QDockWindow::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDockWindow::sizeHint() const
vfunc[59]:	QDockWindow::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)

vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDockWindow::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QDockWindow::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)

vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QDockWindow::showEvent(QShowEvent*)
vfunc[94]:	QDockWindow::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect

	const&)
vfunc[115]:	QDockWindow::drawFrame(QPainter*)
vfunc[116]:	QDockWindow::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QDockWindow::setWidget(QWidget*)
vfunc[119]:	QDockWindow::setCloseMode(int)
vfunc[120]:	QDockWindow::setResizeEnabled(bool)
vfunc[121]:	QDockWindow::setMovingEnabled(bool)
vfunc[122]:	QDockWindow::setHorizontallyStretchable(bool)
vfunc[123]:	QDockWindow::setVerticallyStretchable(bool)
vfunc[124]:	QDockWindow::setOffset(int)
vfunc[125]:	QDockWindow::setFixedExtentWidth(int)
vfunc[126]:	QDockWindow::setFixedExtentHeight(int)
vfunc[127]:	QDockWindow::setNewLine(bool)
vfunc[128]:	QDockWindow::setOpaqueMoving(bool)
vfunc[129]:	QDockWindow::undock(QWidget*)
vfunc[130]:	QDockWindow::undock()
vfunc[131]:	QDockWindow::dock()
vfunc[132]:	QDockWindow::setOrientation(Qt::Orientation)

Table 7-481 Secondary vtable for QDockWindow

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDockWindow
vfunc[0]:	non-virtual thunk to QDockWindow::~~QDockWindow()
vfunc[1]:	non-virtual thunk to QDockWindow::~~QDockWindow()
vfunc[2]:	QPaintDevice::setResolution(int)

vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QDockWindow class is described by Table 7-482

Table 7-482 typeinfo for QDockWindow

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDockWindow
basetype:	typeinfo for QFrame

7.2.1.201 Class data for QImageFormatPlugin

The virtual table for the QImageFormatPlugin class is described by Table 7-483

Table 7-483 Primary vtable for QImageFormatPlugin

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QImageFormatPlugin
vfunc[0]:	QImageFormatPlugin::metaObject() const
vfunc[1]:	QImageFormatPlugin::className() const
vfunc[2]:	QImageFormatPlugin::qt_cast(char const*)
vfunc[3]:	QImageFormatPlugin::qt_invoke(int, QUObject*)
vfunc[4]:	QImageFormatPlugin::qt_emit(int, QUObject*)
vfunc[5]:	QImageFormatPlugin::qt_property(i

	nt, int, QVariant*)
vfunc[6]:	QImageFormatPlugin::~~QImageFormatPlugin()
vfunc[7]:	QImageFormatPlugin::~~QImageFormatPlugin()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	__cxa_pure_virtual
vfunc[22]:	QImageFormatPlugin::loadImage(QString const&, QString const&, QImage*)
vfunc[23]:	QImageFormatPlugin::saveImage(QString const&, QString const&, QImage const&)
vfunc[24]:	__cxa_pure_virtual

The Run Time Type Information for the QImageFormatPlugin class is described by Table 7-484

Table 7-484 typeinfo for QImageFormatPlugin

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QImageFormatPlugin
basetype:	typeinfo for QGPlugin

7.2.1.202 Class data for QEucJpCodec

The virtual table for the QEucJpCodec class is described by Table 7-485

Table 7-485 Primary vtable for QEucJpCodec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QEucJpCodec
vfunc[0]:	QEucJpCodec::~~QEucJpCodec()
vfunc[1]:	QEucJpCodec::~~QEucJpCodec()
vfunc[2]:	QEucJpCodec::name() const
vfunc[3]:	QEucJpCodec::mimeType() const
vfunc[4]:	QEucJpCodec::mibEnum() const
vfunc[5]:	QEucJpCodec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QEucJpCodec::toUnicode(char const*, int) const
vfunc[8]:	QEucJpCodec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QEucJpCodec::heuristicContentMatch(char const*, int) const
vfunc[12]:	QEucJpCodec::heuristicNameMatch(char const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode(QString const&, int) const

The Run Time Type Information for the QEucJpCodec class is described by Table 7-486

Table 7-486 typeinfo for QEucJpCodec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QEucJpCodec
basetype:	typeinfo for QTextCodec

7.2.1.203 Class data for QSqlResultShared

The virtual table for the QSqlResultShared class is described by Table 7-487

Table 7-487 Primary vtable for QSqlResultShared

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlResultShared
vfunc[0]:	QSqlResultShared::metaObject() const
vfunc[1]:	QSqlResultShared::className() const
vfunc[2]:	QSqlResultShared::qt_cast(char const*)
vfunc[3]:	QSqlResultShared::qt_invoke(int, QIODevice*)
vfunc[4]:	QSqlResultShared::qt_emit(int, QIODevice*)
vfunc[5]:	QSqlResultShared::qt_property(int, int, QVariant*)
vfunc[6]:	QSqlResultShared::~~QSqlResultShare d()
vfunc[7]:	QSqlResultShared::~~QSqlResultShare d()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QSqlResultShared class is described by Table 7-488

Table 7-488 typeinfo for QSqlResultShared

Base Vtable	vtable for __cxxabiv1::__vmi_class _type_info	2
Name	typeinfo name for QSqlResultShared	
flags:	0	
basetype:	typeinfo for QObject	
basetype:	typeinfo for QShared	

7.2.1.204 Class data for QSqlError

The virtual table for the QSqlError class is described by Table 7-489

Table 7-489 Primary vtable for QSqlError

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlError
vfunc[0]:	QSqlError::~~QSqlError()
vfunc[1]:	QSqlError::~~QSqlError()
vfunc[2]:	QSqlError::setDriverText(QString const&)
vfunc[3]:	QSqlError::setDatabaseText(QString const&)
vfunc[4]:	QSqlError::setType(int)
vfunc[5]:	QSqlError::setNumber(int)

The Run Time Type Information for the QSqlError class is described by Table 7-490

Table 7-490 typeinfo for QSqlError

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QSqlError

7.2.1.205 Class data for QServerSocket

The virtual table for the QServerSocket class is described by Table 7-491

Table 7-491 Primary vtable for QServerSocket

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QServerSocket
vfunc[0]:	QServerSocket::metaObject() const
vfunc[1]:	QServerSocket::className() const
vfunc[2]:	QServerSocket::qt_cast(char const*)
vfunc[3]:	QServerSocket::qt_invoke(int, QUObject*)
vfunc[4]:	QServerSocket::qt_emit(int, QUObject*)
vfunc[5]:	QServerSocket::qt_property(int, int, QVariant*)
vfunc[6]:	QServerSocket::~QServerSocket()
vfunc[7]:	QServerSocket::~QServerSocket()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QServerSocket::setSocket(int)
vfunc[22]:	__cxa_pure_virtual

The Run Time Type Information for the QServerSocket class is described by Table 7-492

Table 7-492 typeinfo for QServerSocket

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
-------------	--

Name	typeinfo name for QServerSocket
basetype:	typeinfo for QObject

7.2.1.206 Class data for QXmlContentHandler

The virtual table for the QXmlContentHandler class is described by Table 7-493

Table 7-493 Primary vtable for QXmlContentHandler

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlContentHandler
vfunc[0]:	__cxa_pure_virtual
vfunc[1]:	__cxa_pure_virtual
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	__cxa_pure_virtual
vfunc[8]:	__cxa_pure_virtual
vfunc[9]:	__cxa_pure_virtual
vfunc[10]:	__cxa_pure_virtual
vfunc[11]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlContentHandler class is described by Table 7-494

Table 7-494 typeinfo for QXmlContentHandler

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlContentHandler

7.2.1.207 Class data for QGb2312Codec

The virtual table for the QGb2312Codec class is described by Table 7-495

Table 7-495 Primary vtable for QGb2312Codec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGb2312Codec
vfunc[0]:	QGb2312Codec::~~QGb2312Codec()

vfunc[1]:	QGb2312Codec::~~QGb2312Codec()
vfunc[2]:	QGb2312Codec::name() const
vfunc[3]:	QTextCodec::mimeTypeName() const
vfunc[4]:	QGb2312Codec::mibEnum() const
vfunc[5]:	QGb2312Codec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QGb2312Codec::toUnicode(char const*, int) const
vfunc[8]:	QGb2312Codec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QGb2312Codec::heuristicContentMatch(char const*, int) const
vfunc[12]:	QGb2312Codec::heuristicNameMatch(char const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode(QString const&, int) const

The Run Time Type Information for the QGb2312Codec class is described by Table 7-496

Table 7-496 typeinfo for QGb2312Codec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGb2312Codec
basetype:	typeinfo for QGb18030Codec

7.2.1.208 Class data for QFocusEvent

The virtual table for the QFocusEvent class is described by Table 7-497

Table 7-497 Primary vtable for QFocusEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFocusEvent
vfunc[0]:	QFocusEvent::~~QFocusEvent()

vfunc[1]:	QFocusEvent::~QFocusEvent()
-----------	-----------------------------

The Run Time Type Information for the QFocusEvent class is described by Table 7-498

Table 7-498 typeinfo for QFocusEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFocusEvent
basetype:	typeinfo for QEvent

7.2.1.209 Class data for QMouseEvent

The virtual table for the QMouseEvent class is described by Table 7-499

Table 7-499 Primary vtable for QMouseEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMouseEvent
vfunc[0]:	QMouseEvent::~~QMouseEvent()
vfunc[1]:	QMouseEvent::~~QMouseEvent()

The Run Time Type Information for the QMouseEvent class is described by Table 7-500

Table 7-500 typeinfo for QMouseEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMouseEvent
basetype:	typeinfo for QEvent

7.2.1.210 Class data for QUrlInfo

The virtual table for the QUrlInfo class is described by Table 7-501

Table 7-501 Primary vtable for QUrlInfo

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QUrlInfo
vfunc[0]:	QUrlInfo::~~QUrlInfo()
vfunc[1]:	QUrlInfo::~~QUrlInfo()
vfunc[2]:	QUrlInfo::setName(QString const&)
vfunc[3]:	QUrlInfo::setDir(bool)
vfunc[4]:	QUrlInfo::setFile(bool)

vfunc[5]:	QUrlInfo::setSymLink(bool)
vfunc[6]:	QUrlInfo::setOwner(QString const&)
vfunc[7]:	QUrlInfo::setGroup(QString const&)
vfunc[8]:	QUrlInfo::setSize(unsigned int)
vfunc[9]:	QUrlInfo::setWritable(bool)
vfunc[10]:	QUrlInfo::setReadable(bool)
vfunc[11]:	QUrlInfo::setPermissions(int)
vfunc[12]:	QUrlInfo::setLastModified(QDateTi me const&)

The Run Time Type Information for the QUrlInfo class is described by Table 7-502

Table 7-502 typeinfo for QUrlInfo

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QUrlInfo

7.2.1.211 Class data for QImageConsumer

The virtual table for the QImageConsumer class is described by Table 7-503

Table 7-503 Primary vtable for QImageConsumer

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QImageConsumer
vfunc[0]:	__cxa_pure_virtual
vfunc[1]:	__cxa_pure_virtual
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual

The Run Time Type Information for the QImageConsumer class is described by Table 7-504

Table 7-504 typeinfo for QImageConsumer

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QImageConsumer

7.2.1.212 Class data for QDomEntityReference

The virtual table for the QDomEntityReference class is described by Table 7-505

Table 7-505 Primary vtable for QDomEntityReference

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomEntityReference
vfunc[0]:	QDomEntityReference::~~QDomEntityReference()
vfunc[1]:	QDomEntityReference::~~QDomEntityReference()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomEntityReference::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const

vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomEntityReference::isEntityReference() const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction() const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const

The Run Time Type Information for the QDomEntityReference class is described by Table 7-506

Table 7-506 typeinfo for QDomEntityReference

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomEntityReference
basetype:	typeinfo for QDomNode

7.2.1.213 Class data for QSpinWidget

The virtual table for the QSpinWidget class is described by Table 7-507

Table 7-507 Primary vtable for QSpinWidget

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSpinWidget
vfunc[0]:	QSpinWidget::metaObject() const
vfunc[1]:	QSpinWidget::className() const
vfunc[2]:	QSpinWidget::qt_cast(char const*)
vfunc[3]:	QSpinWidget::qt_invoke(int, QUObject*)
vfunc[4]:	QSpinWidget::qt_emit(int, QUObject*)
vfunc[5]:	QSpinWidget::qt_property(int, int, QVariant*)
vfunc[6]:	QSpinWidget::~~QSpinWidget()
vfunc[7]:	QSpinWidget::~~QSpinWidget()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)

vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPi xmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::F ocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()

vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QSpinWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QSpinWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QSpinWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QSpinWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)

vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QSpinWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QSpinWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QSpinWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QSpinWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)

vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QSpinWidget::setButtonSymbols(QSpinWidget::ButtonSymbols)

Table 7-508 Secondary vtable for QSpinWidget

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QSpinWidget
vfunc[0]:	non-virtual thunk to QSpinWidget::~~QSpinWidget()
vfunc[1]:	non-virtual thunk to QSpinWidget::~~QSpinWidget()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QSpinWidget class is described by Table 7-509

Table 7-509 typeinfo for QSpinWidget

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSpinWidget
basetype:	typeinfo for QWidget

7.2.1.214 Class data for QChildEvent

The virtual table for the QChildEvent class is described by Table 7-510

Table 7-510 Primary vtable for QChildEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QChildEvent
vfunc[0]:	QChildEvent::~~QChildEvent()
vfunc[1]:	QChildEvent::~~QChildEvent()

The Run Time Type Information for the QChildEvent class is described by Table 7-511

Table 7-511 typeinfo for QChildEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QChildEvent
basetype:	typeinfo for QEvent

7.2.1.215 Class data for QTextOStream

The virtual table for the QTextOStream class is described by Table 7-512

Table 7-512 Primary vtable for QTextOStream

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextOStream
vfunc[0]:	QTextOStream::~~QTextOStream()
vfunc[1]:	QTextOStream::~~QTextOStream()

The Run Time Type Information for the QTextOStream class is described by Table 7-513

Table 7-513 typeinfo for QTextOStream

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextOStream
basetype:	typeinfo for QTextStream

7.2.1.216 Class data for QSignalVec

The virtual table for the QSignalVec class is described by Table 7-514

Table 7-514 Primary vtable for QSignalVec

Base Offset	0
-------------	---

Virtual Base Offset	0
RTTI	typeinfo for QSignalVec
vfunc[0]:	QPtrVector<QConnectionList>::count() const
vfunc[1]:	QPtrVector<QConnectionList>::clear()
vfunc[2]:	QSignalVec::~~QSignalVec()
vfunc[3]:	QSignalVec::~~QSignalVec()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	QPtrVector<QConnectionList>::deleteItem(void*)
vfunc[6]:	QGVector::compareItems(void*, void*)
vfunc[7]:	QGVector::read(QDataStream&, void*&)
vfunc[8]:	QGVector::write(QDataStream&, void*) const

The Run Time Type Information for the QSignalVec class is described by Table 7-515

Table 7-515 typeinfo for QSignalVec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSignalVec
basetype:	typeinfo for QPtrVector<QConnectionList>

7.2.1.217 Class data for QValidator

The virtual table for the QValidator class is described by Table 7-516

Table 7-516 Primary vtable for QValidator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QValidator
vfunc[0]:	QValidator::metaObject() const
vfunc[1]:	QValidator::className() const
vfunc[2]:	QValidator::qt_cast(char const*)
vfunc[3]:	QValidator::qt_invoke(int, QUObject*)
vfunc[4]:	QValidator::qt_emit(int, QUObject*)

vfunc[5]:	QValidator::qt_property(int, int, QVariant*)
vfunc[6]:	QValidator::~~QValidator()
vfunc[7]:	QValidator::~~QValidator()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	__cxa_pure_virtual
vfunc[22]:	QValidator::fixup(QString&) const

The Run Time Type Information for the QValidator class is described by Table 7-517

Table 7-517 typeinfo for QValidator

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QValidator
basetype:	typeinfo for QObject

7.2.1.218 Class data for QGridLayout

The virtual table for the QGridLayout class is described by Table 7-518

Table 7-518 Primary vtable for QGridLayout

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QGridLayout
vfunc[0]:	QGridLayout::metaObject() const
vfunc[1]:	QGridLayout::className() const
vfunc[2]:	QGridLayout::qt_cast(char const*)
vfunc[3]:	QGridLayout::qt_invoke(int, QUObject*)
vfunc[4]:	QGridLayout::qt_emit(int, QUObject*)
vfunc[5]:	QGridLayout::qt_property(int, int, QVariant*)
vfunc[6]:	QGridLayout::~QGridLayout()
vfunc[7]:	QGridLayout::~QGridLayout()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QLayout::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QLayout::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QLayout::setMargin(int)
vfunc[22]:	QLayout::setSpacing(int)
vfunc[23]:	QLayout::setMenuBar(QMenuBar*)
vfunc[24]:	QLayout::setAutoAdd(bool)
vfunc[25]:	QGridLayout::invalidate()
vfunc[26]:	QLayout::geometry() const
vfunc[27]:	QGridLayout::addItem(QLayoutItem*)

vfunc[28]:	QGridLayout::expanding() const
vfunc[29]:	QGridLayout::minimumSize() const
vfunc[30]:	QGridLayout::maximumSize() const
vfunc[31]:	QGridLayout::setGeometry(QRect const&)
vfunc[32]:	QGridLayout::iterator()
vfunc[33]:	QLayout::isEmpty() const
vfunc[34]:	QLayout::layout()
vfunc[35]:	QGridLayout::sizeHint() const
vfunc[36]:	QGridLayout::setRowStretch(int, int)
vfunc[37]:	QGridLayout::setColStretch(int, int)
vfunc[38]:	QGridLayout::hasHeightForWidth() const
vfunc[39]:	QGridLayout::heightForWidth(int) const

Table 7-519 Secondary vtable for QGridLayout

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QGridLayout
vfunc[0]:	non-virtual thunk to QGridLayout::~~QGridLayout()
vfunc[1]:	non-virtual thunk to QGridLayout::~~QGridLayout()
vfunc[2]:	non-virtual thunk to QGridLayout::sizeHint() const
vfunc[3]:	non-virtual thunk to QGridLayout::minimumSize() const
vfunc[4]:	non-virtual thunk to QGridLayout::maximumSize() const
vfunc[5]:	non-virtual thunk to QGridLayout::expanding() const
vfunc[6]:	non-virtual thunk to QGridLayout::setGeometry(QRect const&)
vfunc[7]:	non-virtual thunk to QLayout::geometry() const
vfunc[8]:	non-virtual thunk to QLayout::isEmpty() const
vfunc[9]:	non-virtual thunk to

	QGridLayout::hasHeightForWidth() const
vfunc[10]:	non-virtual thunk to QGridLayout::heightForWidth(int) const
vfunc[11]:	non-virtual thunk to QGridLayout::invalidate()
vfunc[12]:	QLayoutItem::widget()
vfunc[13]:	non-virtual thunk to QGridLayout::iterator()
vfunc[14]:	non-virtual thunk to QLayout::layout()
vfunc[15]:	QLayoutItem::spacerItem()
vfunc[16]:	QLayoutItem::setAlignment(int)

The Run Time Type Information for the QGridLayout class is described by Table 7-520

Table 7-520 typeinfo for QGridLayout

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGridLayout
basetype:	typeinfo for QLayout

7.2.1.219 Class data for QHebrewCodec

The virtual table for the QHebrewCodec class is described by Table 7-521

Table 7-521 Primary vtable for QHebrewCodec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHebrewCodec
vfunc[0]:	QHebrewCodec::~~QHebrewCodec()
vfunc[1]:	QHebrewCodec::~~QHebrewCodec()
vfunc[2]:	QHebrewCodec::name() const
vfunc[3]:	QHebrewCodec::mimeTypeName() const
vfunc[4]:	QHebrewCodec::mibEnum() const
vfunc[5]:	QTextCodec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QHebrewCodec::toUnicode(char const*, int) const
vfunc[8]:	QHebrewCodec::fromUnicode(QStri

	ng const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	QHebrewCodec::heuristicContentMatch(char const*, int) const
vfunc[12]:	QTextCodec::heuristicNameMatch(char const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode(QString const&, int) const

The Run Time Type Information for the QHebrewCodec class is described by Table 7-522

Table 7-522 typeinfo for QHebrewCodec

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHebrewCodec
basetype:	typeinfo for QTextCodec

7.2.1.220 Class data for QToolBox

The virtual table for the QToolBox class is described by Table 7-523

Table 7-523 Primary vtable for QToolBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QToolBox
vfunc[0]:	QToolBox::metaObject() const
vfunc[1]:	QToolBox::className() const
vfunc[2]:	QToolBox::qt_cast(char const*)
vfunc[3]:	QToolBox::qt_invoke(int, QUObject*)
vfunc[4]:	QToolBox::qt_emit(int, QUObject*)
vfunc[5]:	QToolBox::qt_property(int, int, QVariant*)
vfunc[6]:	QToolBox::~QToolBox()
vfunc[7]:	QToolBox::~QToolBox()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*,

	QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)

vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QFrame::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)

vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QFrame::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLe

	aveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QToolBox::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QToolBox::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QToolBox::frameChanged()
vfunc[118]:	QToolBox::itemInserted(int)
vfunc[119]:	QToolBox::itemRemoved(int)

Table 7-524 Secondary vtable for QToolBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QToolBox
vfunc[0]:	non-virtual thunk to QToolBox::~~QToolBox()
vfunc[1]:	non-virtual thunk to QToolBox::~~QToolBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QToolBox class is described by Table 7-525

Table 7-525 typeinfo for QToolBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QToolBox
basetype:	typeinfo for QFrame

7.2.1.221 Class data for QNetworkOperation

The virtual table for the QNetworkOperation class is described by Table 7-526

Table 7-526 Primary vtable for QNetworkOperation

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QNetworkOperation
vfunc[0]:	QNetworkOperation::metaObject()

	const
vfunc[1]:	QNetworkOperation::className() const
vfunc[2]:	QNetworkOperation::qt_cast(char const*)
vfunc[3]:	QNetworkOperation::qt_invoke(int, QUObject*)
vfunc[4]:	QNetworkOperation::qt_emit(int, QUObject*)
vfunc[5]:	QNetworkOperation::qt_property(int , int, QVariant*)
vfunc[6]:	QNetworkOperation::~~QNetworkOp eration()
vfunc[7]:	QNetworkOperation::~~QNetworkOp eration()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QNetworkOperation class is described by Table 7-527

Table 7-527 typeinfo for QNetworkOperation

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for

	QNetworkOperation
basetype:	typeinfo for QObject

7.2.1.222 Class data for QHttp

The virtual table for the QHttp class is described by Table 7-528

Table 7-528 Primary vtable for QHttp

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHttp
vfunc[0]:	QHttp::metaObject() const
vfunc[1]:	QHttp::className() const
vfunc[2]:	QHttp::qt_cast(char const*)
vfunc[3]:	QHttp::qt_invoke(int, QUObject*)
vfunc[4]:	QHttp::qt_emit(int, QUObject*)
vfunc[5]:	QHttp::qt_property(int, int, QVariant*)
vfunc[6]:	QHttp::~QHttp()
vfunc[7]:	QHttp::~QHttp()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QHttp::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QNetworkProtocol::setUrl(QUrlOperator*)

vfunc[22]:	QNetworkProtocol::setAutoDelete(bool, int)
vfunc[23]:	QHttp::supportedOperations() const
vfunc[24]:	QNetworkProtocol::addOperation(QNetworkOperation*)
vfunc[25]:	QNetworkProtocol::clearOperationQueue()
vfunc[26]:	QNetworkProtocol::stop()
vfunc[27]:	QNetworkProtocol::processOperation(QNetworkOperation*)
vfunc[28]:	QNetworkProtocol::operationListChildren(QNetworkOperation*)
vfunc[29]:	QNetworkProtocol::operationMkdir(QNetworkOperation*)
vfunc[30]:	QNetworkProtocol::operationRemove(QNetworkOperation*)
vfunc[31]:	QNetworkProtocol::operationRename(QNetworkOperation*)
vfunc[32]:	QHttp::operationGet(QNetworkOperation*)
vfunc[33]:	QHttp::operationPut(QNetworkOperation*)
vfunc[34]:	QNetworkProtocol::operationPutChunk(QNetworkOperation*)
vfunc[35]:	QNetworkProtocol::checkConnection(QNetworkOperation*)

The Run Time Type Information for the QHttp class is described by Table 7-529

Table 7-529 typeinfo for QHttp

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QHttp
basetype:	typeinfo for QNetworkProtocol

7.2.1.223 Class data for QSqlForm

The virtual table for the QSqlForm class is described by Table 7-530

Table 7-530 Primary vtable for QSqlForm

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlForm

vfunc[0]:	QSqlForm::metaObject() const
vfunc[1]:	QSqlForm::className() const
vfunc[2]:	QSqlForm::qt_cast(char const*)
vfunc[3]:	QSqlForm::qt_invoke(int, QUObject*)
vfunc[4]:	QSqlForm::qt_emit(int, QUObject*)
vfunc[5]:	QSqlForm::qt_property(int, int, QVariant*)
vfunc[6]:	QSqlForm::~~QSqlForm()
vfunc[7]:	QSqlForm::~~QSqlForm()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QSqlForm::insert(QWidget*, QString const&)
vfunc[22]:	QSqlForm::remove(QString const&)
vfunc[23]:	QSqlForm::setRecord(QSqlRecord*)
vfunc[24]:	QSqlForm::readField(QWidget*)
vfunc[25]:	QSqlForm::writeField(QWidget*)
vfunc[26]:	QSqlForm::readFields()
vfunc[27]:	QSqlForm::writeFields()
vfunc[28]:	QSqlForm::clear()
vfunc[29]:	QSqlForm::clearValues(bool)

vfunc[30]:	QSqlForm::insert(QWidget*, QSqlField*)
vfunc[31]:	QSqlForm::remove(QWidget*)
vfunc[32]:	QSqlForm::sync()

The Run Time Type Information for the QSqlForm class is described by Table 7-531

Table 7-531 typeinfo for QSqlForm

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSqlForm
basetype:	typeinfo for QObject

7.2.1.224 Class data for QEvent

The virtual table for the QEvent class is described by Table 7-532

Table 7-532 Primary vtable for QEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QEvent
vfunc[0]:	QEvent::~~QEvent()
vfunc[1]:	QEvent::~~QEvent()

The Run Time Type Information for the QEvent class is described by Table 7-533

Table 7-533 typeinfo for QEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QEvent
basetype:	typeinfo for Qt

7.2.1.225 Class data for QMimeSource

The virtual table for the QMimeSource class is described by Table 7-534

Table 7-534 Primary vtable for QMimeSource

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMimeSource
vfunc[0]:	QMimeSource::~~QMimeSource()
vfunc[1]:	QMimeSource::~~QMimeSource()

vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	QMimeSource::provides(char const*) const
vfunc[4]:	__cxa_pure_virtual

The Run Time Type Information for the QMimeSource class is described by Table 7-535

Table 7-535 typeinfo for QMimeSource

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QMimeSource

7.2.1.226 Class data for QIMComposeEvent

The virtual table for the QIMComposeEvent class is described by Table 7-536

Table 7-536 Primary vtable for QIMComposeEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIMComposeEvent
vfunc[0]:	QIMComposeEvent::~~QIMComposeEvent()
vfunc[1]:	QIMComposeEvent::~~QIMComposeEvent()

The Run Time Type Information for the QIMComposeEvent class is described by Table 7-537

Table 7-537 typeinfo for QIMComposeEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QIMComposeEvent
basetype:	typeinfo for QIMEvent

7.2.1.227 Class data for QTextDecoder

The virtual table for the QTextDecoder class is described by Table 7-538

Table 7-538 Primary vtable for QTextDecoder

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextDecoder
vfunc[0]:	QTextDecoder::~~QTextDecoder()

vfunc[1]:	QTextDecoder::~~QTextDecoder()
vfunc[2]:	__cxa_pure_virtual

The Run Time Type Information for the QTextDecoder class is described by Table 7-539

Table 7-539 typeinfo for QTextDecoder

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QTextDecoder

7.2.1.228 Class data for QSessionManager

The virtual table for the QSessionManager class is described by Table 7-540

Table 7-540 Primary vtable for QSessionManager

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSessionManager
vfunc[0]:	QSessionManager::metaObject() const
vfunc[1]:	QSessionManager::className() const
vfunc[2]:	QSessionManager::qt_cast(char const*)
vfunc[3]:	QSessionManager::qt_invoke(int, QUObject*)
vfunc[4]:	QSessionManager::qt_emit(int, QUObject*)
vfunc[5]:	QSessionManager::qt_property(int, int, QVariant*)
vfunc[6]:	QSessionManager::~~QSessionManag er()
vfunc[7]:	QSessionManager::~~QSessionManag er()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)

vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QSessionManager class is described by Table 7-541

Table 7-541 typeinfo for QSessionManager

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSessionManager
basetype:	typeinfo for QObject

7.2.1.229 Class data for QImageFormatType

The virtual table for the QImageFormatType class is described by Table 7-542

Table 7-542 Primary vtable for QImageFormatType

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QImageFormatType
vfunc[0]:	QImageFormatType::~~QImageFormatType()
vfunc[1]:	QImageFormatType::~~QImageFormatType()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QImageFormatType class is described by Table 7-543

Table 7-543 typeinfo for QImageFormatType

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QImageFormatType

7.2.1.230 Class data for QTextCodec

The virtual table for the QTextCodec class is described by Table 7-544

Table 7-544 Primary vtable for QTextCodec

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextCodec
vfunc[0]:	QTextCodec::~~QTextCodec()
vfunc[1]:	QTextCodec::~~QTextCodec()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	QTextCodec::mimeTypeName() const
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	QTextCodec::makeDecoder() const
vfunc[6]:	QTextCodec::makeEncoder() const
vfunc[7]:	QTextCodec::toUnicode(char const*, int) const
vfunc[8]:	QTextCodec::fromUnicode(QString const&, int&) const
vfunc[9]:	QTextCodec::canEncode(QChar) const
vfunc[10]:	QTextCodec::canEncode(QString const&) const
vfunc[11]:	__cxa_pure_virtual
vfunc[12]:	QTextCodec::heuristicNameMatch(char const*) const
vfunc[13]:	QTextCodec::fromUnicode(QString const&, int, int) const
vfunc[14]:	QTextCodec::characterFromUnicode(QString const&, int) const

The Run Time Type Information for the QTextCodec class is described by Table 7-545

Table 7-545 typeinfo for QTextCodec

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QTextCodec

7.2.1.231 Class data for QSpacerItem

The virtual table for the QSpacerItem class is described by Table 7-546

Table 7-546 Primary vtable for QSpacerItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSpacerItem
vfunc[0]:	QSpacerItem::~~QSpacerItem()
vfunc[1]:	QSpacerItem::~~QSpacerItem()
vfunc[2]:	QSpacerItem::sizeHint() const
vfunc[3]:	QSpacerItem::minimumSize() const
vfunc[4]:	QSpacerItem::maximumSize() const
vfunc[5]:	QSpacerItem::expanding() const
vfunc[6]:	QSpacerItem::setGeometry(QRect const&)
vfunc[7]:	QSpacerItem::geometry() const
vfunc[8]:	QSpacerItem::isEmpty() const
vfunc[9]:	QLayoutItem::hasHeightForWidth() const
vfunc[10]:	QLayoutItem::heightForWidth(int) const
vfunc[11]:	QLayoutItem::invalidate()
vfunc[12]:	QLayoutItem::widget()
vfunc[13]:	QLayoutItem::iterator()
vfunc[14]:	QLayoutItem::layout()
vfunc[15]:	QSpacerItem::spacerItem()
vfunc[16]:	QLayoutItem::setAlignment(int)

The Run Time Type Information for the QSpacerItem class is described by Table 7-547

Table 7-547 typeinfo for QSpacerItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSpacerItem
basetype:	typeinfo for QLayoutItem

7.2.1.232 Class data for QPrintDialog

The virtual table for the QPrintDialog class is described by Table 7-548

Table 7-548 Primary vtable for QPrintDialog

Base Offset	0
-------------	---

Virtual Base Offset	0
RTTI	typeinfo for QDialog
vfunc[0]:	QDialog::metaObject() const
vfunc[1]:	QDialog::className() const
vfunc[2]:	QDialog::qt_cast(char const*)
vfunc[3]:	QDialog::qt_invoke(int, QUObject*)
vfunc[4]:	QDialog::qt_emit(int, QUObject*)
vfunc[5]:	QDialog::qt_property(int, int, QVariant*)
vfunc[6]:	QDialog::~~QDialog()
vfunc[7]:	QDialog::~QDialog()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor)

	const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)

vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)

vfunc[82]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)

vfunc[110]:	QDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 7-549 Secondary vtable for QPrintDialog

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QPrintDialog
vfunc[0]:	non-virtual thunk to QPrintDialog::~~QPrintDialog()
vfunc[1]:	non-virtual thunk to QPrintDialog::~~QPrintDialog()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QPrintDialog class is described by Table 7-550

Table 7-550 typeinfo for QPrintDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPrintDialog
basetype:	typeinfo for QDialog

7.2.1.233 Class data for QProgressBar

The virtual table for the QProgressBar class is described by Table 7-551

Table 7-551 Primary vtable for QProgressBar

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QProgressBar
vfunc[0]:	QProgressBar::metaObject() const
vfunc[1]:	QProgressBar::className() const
vfunc[2]:	QProgressBar::qt_cast(char const*)
vfunc[3]:	QProgressBar::qt_invoke(int, QUObject*)
vfunc[4]:	QProgressBar::qt_emit(int, QUObject*)
vfunc[5]:	QProgressBar::qt_property(int, int, QVariant*)
vfunc[6]:	QProgressBar::~~QProgressBar()
vfunc[7]:	QProgressBar::~~QProgressBar()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)

vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPi xmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::F ocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QProgressBar::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()

vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QProgressBar::sizeHint() const
vfunc[59]:	QProgressBar::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)

	nt*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QFrame::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QProgressBar::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)

vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QProgressBar::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QProgressBar::setTotalSteps(int)
vfunc[119]:	QProgressBar::setProgress(int)
vfunc[120]:	QProgressBar::setIndicator(QString&, int, int)

Table 7-552 Secondary vtable for QProgressBar

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QProgressBar
vfunc[0]:	non-virtual thunk to QProgressBar::~QProgressBar()
vfunc[1]:	non-virtual thunk to QProgressBar::~QProgressBar()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const

vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QProgressBar class is described by Table 7-553

Table 7-553 typeinfo for QProgressBar

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QProgressBar
basetype:	typeinfo for QFrame

7.2.1.234 Class data for QIconViewItem

The virtual table for the QIconViewItem class is described by Table 7-554

Table 7-554 Primary vtable for QIconViewItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIconViewItem
vfunc[0]:	QIconViewItem::~~QIconViewItem()
vfunc[1]:	QIconViewItem::~~QIconViewItem()
vfunc[2]:	QIconViewItem::setRenameEnabled(bool)
vfunc[3]:	QIconViewItem::setDragEnabled(bool)
vfunc[4]:	QIconViewItem::setDropEnabled(bool)
vfunc[5]:	QIconViewItem::text() const
vfunc[6]:	QIconViewItem::pixmap() const
vfunc[7]:	QIconViewItem::picture() const
vfunc[8]:	QIconViewItem::key() const
vfunc[9]:	QIconViewItem::setSelected(bool, bool)
vfunc[10]:	QIconViewItem::setSelected(bool)
vfunc[11]:	QIconViewItem::setSelectable(bool)
vfunc[12]:	QIconViewItem::repaint()
vfunc[13]:	QIconViewItem::move(int, int)
vfunc[14]:	QIconViewItem::moveBy(int, int)

vfunc[15]:	QIconViewItem::move(QPoint const&)
vfunc[16]:	QIconViewItem::moveBy(QPoint const&)
vfunc[17]:	QIconViewItem::acceptDrop(QMime Source const*) const
vfunc[18]:	QIconViewItem::compare(QIconViewItem*) const
vfunc[19]:	QIconViewItem::setText(QString const&)
vfunc[20]:	QIconViewItem::setPixmap(QPixmap const&)
vfunc[21]:	QIconViewItem::setPicture(QPicture const&)
vfunc[22]:	QIconViewItem::setText(QString const&, bool, bool)
vfunc[23]:	QIconViewItem::setPixmap(QPixmap const&, bool, bool)
vfunc[24]:	QIconViewItem::setKey(QString const&)
vfunc[25]:	QIconViewItem::rtti() const
vfunc[26]:	QIconViewItem::removeRenameBox()
vfunc[27]:	QIconViewItem::calcRect(QString const&)
vfunc[28]:	QIconViewItem::paintItem(QPainter*, QColorGroup const&)
vfunc[29]:	QIconViewItem::paintFocus(QPainter*, QColorGroup const&)
vfunc[30]:	QIconViewItem::dropped(QDropEvent*, QList<QIconDragItem> const&)
vfunc[31]:	QIconViewItem::dragEntered()
vfunc[32]:	QIconViewItem::dragLeft()

The Run Time Type Information for the QIconViewItem class is described by Table 7-555

Table 7-555 typeinfo for QIconViewItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QIconViewItem

basetype:	typeinfo for Qt
-----------	-----------------

7.2.1.235 Class data for QDomCDATASection

The virtual table for the QDomCDATASection class is described by Table 7-556

Table 7-556 Primary vtable for QDomCDATASection

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomCDATASection
vfunc[0]:	QDomCDATASection::~~QDomCDATASection()
vfunc[1]:	QDomCDATASection::~~QDomCDATASection()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)
vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomCDATASection::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const

vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomCDATASection::isCDATASection() const
vfunc[30]:	QDomNode::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const
vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomText::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction() const
vfunc[39]:	QDomCharacterData::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const
vfunc[41]:	QDomCharacterData::substringData(unsigned long, unsigned long)
vfunc[42]:	QDomCharacterData::appendData(QString const&)
vfunc[43]:	QDomCharacterData::insertData(unsigned long, QString const&)
vfunc[44]:	QDomCharacterData::deleteData(unsigned long, unsigned long)
vfunc[45]:	QDomCharacterData::replaceData(unsigned long, unsigned long, QString const&)

vfunc[46]:	QDomCharacterData::length() const
vfunc[47]:	QDomCharacterData::data() const
vfunc[48]:	QDomCharacterData::setData(QString const&)

The Run Time Type Information for the QDomCDATASection class is described by Table 7-557

Table 7-557 typeinfo for QDomCDATASection

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomCDATASection
basetype:	typeinfo for QDomText

7.2.1.236 Class data for QTextStream

The virtual table for the QTextStream class is described by Table 7-558

Table 7-558 Primary vtable for QTextStream

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextStream
vfunc[0]:	QTextStream::~~QTextStream()
vfunc[1]:	QTextStream::~~QTextStream()

The Run Time Type Information for the QTextStream class is described by Table 7-559

Table 7-559 typeinfo for QTextStream

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QTextStream

7.2.1.237 Class data for QCheckListItem

The virtual table for the QCheckListItem class is described by Table 7-560

Table 7-560 Primary vtable for QCheckListItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCheckListItem
vfunc[0]:	QCheckListItem::~~QCheckListItem()
vfunc[1]:	QCheckListItem::~~QCheckListItem()

vfunc[2]:	QListViewItem::insertItem(QListViewItem*)
vfunc[3]:	QListViewItem::takeItem(QListViewItem*)
vfunc[4]:	QListViewItem::removeItem(QListViewItem*)
vfunc[5]:	QListViewItem::invalidateHeight()
vfunc[6]:	QCheckListItem::width(QFontMetrics const&, QListView const*, int) const
vfunc[7]:	QListViewItem::setText(int, QString const&)
vfunc[8]:	QCheckListItem::text(int) const
vfunc[9]:	QListViewItem::setPixmap(int, QPixmap const&)
vfunc[10]:	QListViewItem::pixmap(int) const
vfunc[11]:	QListViewItem::key(int, bool) const
vfunc[12]:	QListViewItem::compare(QListViewItem*, int, bool) const
vfunc[13]:	QListViewItem::sortChildItems(int, bool)
vfunc[14]:	QListViewItem::setOpen(bool)
vfunc[15]:	QCheckListItem::setup()
vfunc[16]:	QListViewItem::setSelected(bool)
vfunc[17]:	QCheckListItem::paintCell(QPainter*, QColorGroup const&, int, int, int)
vfunc[18]:	QListViewItem::paintBranches(QPainter*, QColorGroup const&, int, int, int)
vfunc[19]:	QCheckListItem::paintFocus(QPainter*, QColorGroup const&, QRect const&)
vfunc[20]:	QListViewItem::setSelectable(bool)
vfunc[21]:	QListViewItem::setExpandable(bool)
vfunc[22]:	QListViewItem::sort()
vfunc[23]:	QListViewItem::setDragEnabled(bool)
vfunc[24]:	QListViewItem::setDropEnabled(bool)
vfunc[25]:	QListViewItem::acceptDrop(QMimeSource const*) const

vfunc[26]:	QListViewItem::setRenameEnabled(int, bool)
vfunc[27]:	QListViewItem::startRename(int)
vfunc[28]:	QListViewItem::setEnabled(bool)
vfunc[29]:	QCheckListItem::rtti() const
vfunc[30]:	QListViewItem::setMultiLinesEnabled(bool)
vfunc[31]:	QListViewItem::enforceSortOrder() const
vfunc[32]:	QListViewItem::setHeight(int)
vfunc[33]:	QCheckListItem::activate()
vfunc[34]:	QListViewItem::dropped(QDropEvent*)
vfunc[35]:	QListViewItem::dragEntered()
vfunc[36]:	QListViewItem::dragLeft()
vfunc[37]:	QListViewItem::okRename(int)
vfunc[38]:	QListViewItem::cancelRename(int)
vfunc[39]:	QCheckListItem::setOn(bool)
vfunc[40]:	QCheckListItem::stateChange(bool)

The Run Time Type Information for the QCheckListItem class is described by Table 7-561

Table 7-561 typeinfo for QCheckListItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCheckListItem
basetype:	typeinfo for QListViewItem

7.2.1.238 Class data for QSignalMapper

The virtual table for the QSignalMapper class is described by Table 7-562

Table 7-562 Primary vtable for QSignalMapper

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSignalMapper
vfunc[0]:	QSignalMapper::metaObject() const
vfunc[1]:	QSignalMapper::className() const
vfunc[2]:	QSignalMapper::qt_cast(char const*)

vfunc[3]:	QSignalMapper::qt_invoke(int, QUObject*)
vfunc[4]:	QSignalMapper::qt_emit(int, QUObject*)
vfunc[5]:	QSignalMapper::qt_property(int, int, QVariant*)
vfunc[6]:	QSignalMapper::~~QSignalMapper()
vfunc[7]:	QSignalMapper::~~QSignalMapper()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QSignalMapper::setMapping(QObject const*, int)
vfunc[22]:	QSignalMapper::setMapping(QObject const*, QString const&)

The Run Time Type Information for the QSignalMapper class is described by Table 7-563

Table 7-563 typeinfo for QSignalMapper

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSignalMapper
basetype:	typeinfo for QObject

7.2.1.239 Class data for QDockArea

The virtual table for the QDockArea class is described by Table 7-564

Table 7-564 Primary vtable for QDockArea

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDockArea
vfunc[0]:	QDockArea::metaObject() const
vfunc[1]:	QDockArea::className() const
vfunc[2]:	QDockArea::qt_cast(char const*)
vfunc[3]:	QDockArea::qt_invoke(int, QUObject*)
vfunc[4]:	QDockArea::qt_emit(int, QUObject*)
vfunc[5]:	QDockArea::qt_property(int, int, QVariant*)
vfunc[6]:	QDockArea::~~QDockArea()
vfunc[7]:	QDockArea::~~QDockArea()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDockArea::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)

vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPi xmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::F ocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()

vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)

	nt*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)

vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)

Table 7-565 Secondary vtable for QDockArea

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDockArea
vfunc[0]:	non-virtual thunk to QDockArea::~~QDockArea()
vfunc[1]:	non-virtual thunk to QDockArea::~~QDockArea()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QDockArea class is described by Table 7-566

Table 7-566 typeinfo for QDockArea

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDockArea
basetype:	typeinfo for QWidget

7.2.1.240 Class data for QString

The virtual table for the QString class is described by Table 7-567

Table 7-567 Primary vtable for QString

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QString
vfunc[0]:	QString::~~QString()
vfunc[1]:	QString::~~QString()
vfunc[2]:	QMemArray<char>::detach()
vfunc[3]:	QGArray::newData()
vfunc[4]:	QGArray::deleteData(QGArray::array_data*)

The Run Time Type Information for the QString class is described by Table 7-568

Table 7-568 typeinfo for QString

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QString
basetype:	typeinfo for QMemArray<char>

7.2.1.241 Class data for QStyle

The virtual table for the QStyle class is described by Table 7-569

Table 7-569 Primary vtable for QStyle

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QStyle
vfunc[0]:	QStyle::metaObject() const
vfunc[1]:	QStyle::className() const
vfunc[2]:	QStyle::qt_cast(char const*)
vfunc[3]:	QStyle::qt_invoke(int, QUObject*)
vfunc[4]:	QStyle::qt_emit(int, QUObject*)
vfunc[5]:	QStyle::qt_property(int, int, QVariant*)
vfunc[6]:	QStyle::~~QStyle()
vfunc[7]:	QStyle::~~QStyle()
vfunc[8]:	QObject::event(QEvent*)

vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QStyle::polish(QWidget*)
vfunc[22]:	QStyle::unPolish(QWidget*)
vfunc[23]:	QStyle::polish(QApplication*)
vfunc[24]:	QStyle::unPolish(QApplication*)
vfunc[25]:	QStyle::polish(QPalette&)
vfunc[26]:	__cxa_pure_virtual
vfunc[27]:	QStyle::itemRect(QPainter*, QRect const&, int, bool, QPixmap const*, QString const&, int) const
vfunc[28]:	QStyle::drawItem(QPainter*, QRect const&, int, QColorGroup const&, bool, QPixmap const*, QString const&, int, QColor const*) const
vfunc[29]:	__cxa_pure_virtual
vfunc[30]:	__cxa_pure_virtual
vfunc[31]:	__cxa_pure_virtual
vfunc[32]:	__cxa_pure_virtual
vfunc[33]:	__cxa_pure_virtual
vfunc[34]:	__cxa_pure_virtual
vfunc[35]:	__cxa_pure_virtual
vfunc[36]:	__cxa_pure_virtual

vfunc[37]:	__cxa_pure_virtual
vfunc[38]:	__cxa_pure_virtual
vfunc[39]:	__cxa_pure_virtual
vfunc[40]:	__cxa_pure_virtual

The Run Time Type Information for the QStyle class is described by Table 7-570

Table 7-570 typeinfo for QStyle

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QStyle
basetype:	typeinfo for QObject

7.2.1.242 Class data for QXmlDTDHandler

The virtual table for the QXmlDTDHandler class is described by Table 7-571

Table 7-571 Primary vtable for QXmlDTDHandler

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlDTDHandler
vfunc[0]:	__cxa_pure_virtual
vfunc[1]:	__cxa_pure_virtual
vfunc[2]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlDTDHandler class is described by Table 7-572

Table 7-572 typeinfo for QXmlDTDHandler

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlDTDHandler

7.2.1.243 Class data for QColorDialog

The virtual table for the QColorDialog class is described by Table 7-573

Table 7-573 Primary vtable for QColorDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QColorDialog
vfunc[0]:	QColorDialog::metaObject() const
vfunc[1]:	QColorDialog::className() const

vfunc[2]:	QColorDialog::qt_cast(char const*)
vfunc[3]:	QColorDialog::qt_invoke(int, QUObject*)
vfunc[4]:	QColorDialog::qt_emit(int, QUObject*)
vfunc[5]:	QColorDialog::qt_property(int, int, QVariant*)
vfunc[6]:	QColorDialog::~~QColorDialog()
vfunc[7]:	QColorDialog::~~QColorDialog()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)

vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)

vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)

vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 7-574 Secondary vtable for QColorDialog

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QColorDialog
vfunc[0]:	non-virtual thunk to QColorDialog::~~QColorDialog()
vfunc[1]:	non-virtual thunk to QColorDialog::~~QColorDialog()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QColorDialog class is described by Table 7-575

Table 7-575 typeinfo for QColorDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QColorDialog
basetype:	typeinfo for QDialog

7.2.1.244 Class data for QGuardedPtrPrivate

The virtual table for the QGuardedPtrPrivate class is described by Table 7-576

Table 7-576 Primary vtable for QGuardedPtrPrivate

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGuardedPtrPrivate
vfunc[0]:	QGuardedPtrPrivate::metaObject()

	const
vfunc[1]:	QGuardedPtrPrivate::className() const
vfunc[2]:	QGuardedPtrPrivate::qt_cast(char const*)
vfunc[3]:	QGuardedPtrPrivate::qt_invoke(int, QIODevice*)
vfunc[4]:	QGuardedPtrPrivate::qt_emit(int, QIODevice*)
vfunc[5]:	QGuardedPtrPrivate::qt_property(int , int, QVariant*)
vfunc[6]:	QGuardedPtrPrivate::~~QGuardedPtr Private()
vfunc[7]:	QGuardedPtrPrivate::~~QGuardedPtr Private()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QGuardedPtrPrivate class is described by Table 7-577

Table 7-577 typeinfo for QGuardedPtrPrivate

Base Vtable	vtable for __cxxabiv1::__vmi_class _type_info	
-------------	---	--

Name	typeinfo name for QGuardedPtrPrivate	2
flags:	0	
basetype:	typeinfo for QObject	
basetype:	typeinfo for QShared	10242

7.2.1.245 Class data for QApplication

The virtual table for the QApplication class is described by Table 7-578

Table 7-578 Primary vtable for QApplication

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QApplication
vfunc[0]:	QApplication::metaObject() const
vfunc[1]:	QApplication::className() const
vfunc[2]:	QApplication::qt_cast(char const*)
vfunc[3]:	QApplication::qt_invoke(int, QUObject*)
vfunc[4]:	QApplication::qt_emit(int, QUObject*)
vfunc[5]:	QApplication::qt_property(int, int, QVariant*)
vfunc[6]:	QApplication::~~QApplication()
vfunc[7]:	QApplication::~~QApplication()
vfunc[8]:	QApplication::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)

vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QApplication::setMainWidget(QWidget*)
vfunc[22]:	QApplication::polish(QWidget*)
vfunc[23]:	QApplication::notify(QObject*, QEvent*)
vfunc[24]:	QApplication::x11EventFilter(_XEvent*)
vfunc[25]:	QApplication::x11ClientMessage(QWidget*, _XEvent*, bool)
vfunc[26]:	QApplication::commitData(QSessionManager&)
vfunc[27]:	QApplication::saveState(QSessionManager&)

The Run Time Type Information for the QApplication class is described by Table 7-579

Table 7-579 typeinfo for QApplication

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QApplication
basetype:	typeinfo for QObject

7.2.1.246 Class data for QListViewItem

The virtual table for the QListViewItem class is described by Table 7-580

Table 7-580 Primary vtable for QListViewItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QListViewItem
vfunc[0]:	QListViewItem::~~QListViewItem()
vfunc[1]:	QListViewItem::~~QListViewItem()
vfunc[2]:	QListViewItem::insertItem(QListViewItem*)
vfunc[3]:	QListViewItem::takeItem(QListViewItem*)
vfunc[4]:	QListViewItem::removeItem(QListViewItem*)

vfunc[5]:	QListViewItem::invalidateHeight()
vfunc[6]:	QListViewItem::width(QFontMetrics const&, QListView const*, int) const
vfunc[7]:	QListViewItem::setText(int, QString const&)
vfunc[8]:	QListViewItem::text(int) const
vfunc[9]:	QListViewItem::setPixmap(int, QPixmap const&)
vfunc[10]:	QListViewItem::pixmap(int) const
vfunc[11]:	QListViewItem::key(int, bool) const
vfunc[12]:	QListViewItem::compare(QListViewItem*, int, bool) const
vfunc[13]:	QListViewItem::sortChildItems(int, bool)
vfunc[14]:	QListViewItem::setOpen(bool)
vfunc[15]:	QListViewItem::setup()
vfunc[16]:	QListViewItem::setSelected(bool)
vfunc[17]:	QListViewItem::paintCell(QPainter*, QColorGroup const&, int, int, int)
vfunc[18]:	QListViewItem::paintBranches(QPainter*, QColorGroup const&, int, int, int)
vfunc[19]:	QListViewItem::paintFocus(QPainter*, QColorGroup const&, QRect const&)
vfunc[20]:	QListViewItem::setSelectable(bool)
vfunc[21]:	QListViewItem::setExpandable(bool)
vfunc[22]:	QListViewItem::sort()
vfunc[23]:	QListViewItem::setDragEnabled(bool)
vfunc[24]:	QListViewItem::setDropEnabled(bool)
vfunc[25]:	QListViewItem::acceptDrop(QMimeSource const*) const
vfunc[26]:	QListViewItem::setRenameEnabled(int, bool)
vfunc[27]:	QListViewItem::startRename(int)
vfunc[28]:	QListViewItem::setEnabled(bool)
vfunc[29]:	QListViewItem::rtti() const

vfunc[30]:	QListViewItem::setMultiLinesEnabled(bool)
vfunc[31]:	QListViewItem::enforceSortOrder() const
vfunc[32]:	QListViewItem::setHeight(int)
vfunc[33]:	QListViewItem::activate()
vfunc[34]:	QListViewItem::dropped(QDropEvent*)
vfunc[35]:	QListViewItem::dragEntered()
vfunc[36]:	QListViewItem::dragLeft()
vfunc[37]:	QListViewItem::okRename(int)
vfunc[38]:	QListViewItem::cancelRename(int)

The Run Time Type Information for the QListViewItem class is described by Table 7-581

Table 7-581 typeinfo for QListViewItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QListViewItem
basetype:	typeinfo for Qt

7.2.1.247 Class data for QIconView

The virtual table for the QIconView class is described by Table 7-582

Table 7-582 Primary vtable for QIconView

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIconView
vfunc[0]:	QIconView::metaObject() const
vfunc[1]:	QIconView::className() const
vfunc[2]:	QIconView::qt_cast(char const*)
vfunc[3]:	QIconView::qt_invoke(int, QUObject*)
vfunc[4]:	QIconView::qt_emit(int, QUObject*)
vfunc[5]:	QIconView::qt_property(int, int, QVariant*)
vfunc[6]:	QIconView::~~QIconView()
vfunc[7]:	QIconView::~~QIconView()
vfunc[8]:	QWidget::event(QEvent*)

vfunc[9]:	QIconView::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QScrollView::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QIconView::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QIconView::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)

vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QIconView::sizeHint() const
vfunc[59]:	QIconView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)

vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QIconView::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QIconView::focusInEvent(QFocusEvent*)
vfunc[77]:	QIconView::focusOutEvent(QFocusEvent*)
vfunc[78]:	QIconView::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QIconView::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)

vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QIconView::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QIconView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QIconView::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QScrollView::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QIconView::drawContents(QPainter*)

vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QIconView::setContentsPos(int, int)
vfunc[127]:	QIconView::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QIconView::contentsMouseEvent(QMouseEvent*)
vfunc[130]:	QIconView::contentsMouseReleaseEvent(QMouseEvent*)
vfunc[131]:	QIconView::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QIconView::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QIconView::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QIconView::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QIconView::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QIconView::contentsDropEvent(QDropEvent*)
vfunc[137]:	QScrollView::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QIconView::contentsContextMenuEvent(QContextMenuEvent*)

vfunc[139]:	QScrollView::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QScrollView::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)
vfunc[154]:	QIconView::insertItem(QIconViewItem*, QIconViewItem*)
vfunc[155]:	QIconView::takeItem(QIconViewItem*)
vfunc[156]:	QIconView::setCurrentItem(QIconViewItem*)
vfunc[157]:	QIconView::setSelected(QIconViewItem*, bool, bool)
vfunc[158]:	QIconView::setSelectionMode(QIconView::SelectionMode)
vfunc[159]:	QIconView::selectAll(bool)
vfunc[160]:	QIconView::clearSelection()

vfunc[161]:	QIconView::invertSelection()
vfunc[162]:	QIconView::repaintItem(QIconViewItem*)
vfunc[163]:	QIconView::clear()
vfunc[164]:	QIconView::setGridX(int)
vfunc[165]:	QIconView::setGridY(int)
vfunc[166]:	QIconView::setSpacing(int)
vfunc[167]:	QIconView::setItemTextPos(QIconView::ItemTextPos)
vfunc[168]:	QIconView::setItemTextBackground(QBrush const&)
vfunc[169]:	QIconView::setArrangement(QIconView::Arrangement)
vfunc[170]:	QIconView::setResizeMode(QIconView::ResizeMode)
vfunc[171]:	QIconView::setMaxItemWidth(int)
vfunc[172]:	QIconView::setMaxItemTextLength(int)
vfunc[173]:	QIconView::setAutoArrange(bool)
vfunc[174]:	QIconView::setShowToolTips(bool)
vfunc[175]:	QIconView::setItemsMovable(bool)
vfunc[176]:	QIconView::setWordWrapIconText(bool)
vfunc[177]:	QIconView::sort(bool)
vfunc[178]:	QIconView::arrangeItemsInGrid(QSize const&, bool)
vfunc[179]:	QIconView::arrangeItemsInGrid(bool)
vfunc[180]:	QIconView::updateContents()
vfunc[181]:	QIconView::doAutoScroll()
vfunc[182]:	QIconView::adjustItems()
vfunc[183]:	QIconView::slotUpdate()
vfunc[184]:	QIconView::drawRubber(QPainter*)
vfunc[185]:	QIconView::dragObject()
vfunc[186]:	QIconView::startDrag()
vfunc[187]:	QIconView::insertInGrid(QIconViewItem*)
vfunc[188]:	QIconView::drawBackground(QPainter*)

	ter*, QRect const&)
vfunc[189]:	QIconView::drawDragShapes(QPoint const&)
vfunc[190]:	QIconView::initDragEnter(QDropEvent*)

Table 7-583 Secondary vtable for QIconView

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QIconView
vfunc[0]:	non-virtual thunk to QIconView::~~QIconView()
vfunc[1]:	non-virtual thunk to QIconView::~~QIconView()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QIconView class is described by Table 7-584

Table 7-584 typeinfo for QIconView

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QIconView
basetype:	typeinfo for QScrollView

7.2.1.248 Class data for QComboBoxItem

The virtual table for the QComboBoxItem class is described by Table 7-585

Table 7-585 Primary vtable for QComboBoxItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QComboBoxItem
vfunc[0]:	QComboBoxItem::~~QComboBoxItem()
vfunc[1]:	QComboBoxItem::~~QComboBoxItem()
vfunc[2]:	QTableWidgetItem::pixmap() const
vfunc[3]:	QTableWidgetItem::text() const
vfunc[4]:	QTableWidgetItem::setPixmap(QPixmap const&)
vfunc[5]:	QTableWidgetItem::setText(QString const&)
vfunc[6]:	QTableWidgetItem::alignment() const
vfunc[7]:	QTableWidgetItem::setWordWrap(bool)
vfunc[8]:	QComboBoxItem::createEditor() const
vfunc[9]:	QComboBoxItem::setContentFromEditor(QWidget*)
vfunc[10]:	QTableWidgetItem::setReplaceable(bool)
vfunc[11]:	QTableWidgetItem::key() const
vfunc[12]:	QComboBoxItem::sizeHint() const
vfunc[13]:	QTableWidgetItem::setSpan(int, int)
vfunc[14]:	QTableWidgetItem::setRow(int)
vfunc[15]:	QTableWidgetItem::setCol(int)
vfunc[16]:	QComboBoxItem::paint(QPainter*, QColorGroup const&, QRect const&, bool)
vfunc[17]:	QTableWidgetItem::setEnabled(bool)
vfunc[18]:	QComboBoxItem::rtti() const
vfunc[19]:	QComboBoxItem::setCurrentItem(int)
vfunc[20]:	QComboBoxItem::setCurrentItem(QString const&)
vfunc[21]:	QComboBoxItem::setEditable(bool)
vfunc[22]:	QComboBoxItem::setStringList(QStringList const&)

The Run Time Type Information for the QComboBoxItem class is described by Table 7-586

Table 7-586 typeinfo for QComboBoxItem

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QComboBoxItem
basetype:	typeinfo for QTableWidgetItem

7.2.1.249 Class data for QWidget

The virtual table for the QWidget class is described by Table 7-587

Table 7-587 Primary vtable for QWidget

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWidget
vfunc[0]:	QWidget::metaObject() const
vfunc[1]:	QWidget::className() const
vfunc[2]:	QWidget::qt_cast(char const*)
vfunc[3]:	QWidget::qt_invoke(int, QUObject*)
vfunc[4]:	QWidget::qt_emit(int, QUObject*)
vfunc[5]:	QWidget::qt_property(int, int, QVariant*)
vfunc[6]:	QWidget::~~QWidget()
vfunc[7]:	QWidget::~~QWidget()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)

vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::F

	ocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)

vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette)

	const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)

Table 7-588 Secondary vtable for QWidget

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QWidget
vfunc[0]:	non-virtual thunk to QWidget::~~QWidget()
vfunc[1]:	non-virtual thunk to QWidget::~~QWidget()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QWidget class is described by Table 7-589

Table 7-589 typeinfo for QWidget

Base Vtable	vtable for __cxxabiv1::__vmi_class _type_info	2
Name	typeinfo name for QWidget	
flags:	0	
basetype:	typeinfo for QObject	
basetype:	typeinfo for QPaintDevice	10242

7.2.1.250 Class data for QDns

The virtual table for the QDns class is described by Table 7-590

Table 7-590 Primary vtable for QDns

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDns
vfunc[0]:	QDns::metaObject() const
vfunc[1]:	QDns::className() const
vfunc[2]:	QDns::qt_cast(char const*)
vfunc[3]:	QDns::qt_invoke(int, QUObject*)
vfunc[4]:	QDns::qt_emit(int, QUObject*)
vfunc[5]:	QDns::qt_property(int, int, QVariant*)
vfunc[6]:	QDns::~~QDns()
vfunc[7]:	QDns::~~QDns()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)

vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QDns::setLabel(QString const&)
vfunc[22]:	QDns::setLabel(QHostAddress const&)
vfunc[23]:	QDns::setRecordType(QDns::RecordType)

The Run Time Type Information for the QDns class is described by Table 7-591

Table 7-591 typeinfo for QDns

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDns
basetype:	typeinfo for QObject

7.2.1.251 Class data for QIODeviceSource

The virtual table for the QIODeviceSource class is described by Table 7-592

Table 7-592 Primary vtable for QIODeviceSource

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIODeviceSource
vfunc[0]:	QIODeviceSource::~~QIODeviceSource()
vfunc[1]:	QIODeviceSource::~~QIODeviceSource()
vfunc[2]:	QIODeviceSource::readyToSend()
vfunc[3]:	QIODeviceSource::sendTo(QDataSink*, int)
vfunc[4]:	QIODeviceSource::rewindable() const
vfunc[5]:	QIODeviceSource::enableRewind(bool)
vfunc[6]:	QIODeviceSource::rewind()

The Run Time Type Information for the QIODeviceSource class is described by Table 7-593

Table 7-593 typeinfo for QIODeviceSource

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QIODeviceSource
basetype:	typeinfo for QDataSource

7.2.1.252 Class data for QCanvasText

The virtual table for the QCanvasText class is described by Table 7-594

Table 7-594 Primary vtable for QCanvasText

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvasText
vfunc[0]:	QCanvasText::~~QCanvasText()
vfunc[1]:	QCanvasText::~~QCanvasText()
vfunc[2]:	QCanvasText::moveBy(double, double)
vfunc[3]:	QCanvasItem::setAnimated(bool)
vfunc[4]:	QCanvasItem::setVelocity(double, double)
vfunc[5]:	QCanvasItem::advance(int)
vfunc[6]:	QCanvasText::collidesWith(QCanvas Item const*) const
vfunc[7]:	QCanvasItem::setCanvas(QCanvas*)
vfunc[8]:	QCanvasText::draw(QPainter&)
vfunc[9]:	QCanvasItem::setVisible(bool)
vfunc[10]:	QCanvasItem::setSelected(bool)
vfunc[11]:	QCanvasItem::setEnabled(bool)
vfunc[12]:	QCanvasItem::setActive(bool)
vfunc[13]:	QCanvasText::rtti() const
vfunc[14]:	QCanvasText::boundingRect() const
vfunc[15]:	QCanvasItem::boundingRectAdvanc ed() const
vfunc[16]:	QCanvasItem::chunks() const
vfunc[17]:	QCanvasText::addToChunks()
vfunc[18]:	QCanvasText::removeFromChunks()

vfunc[19]:	QCanvasText::changeChunks()
vfunc[20]:	QCanvasText::collidesWith(QCanvasSprite const*, QCanvasPolygonalItem const*, QCanvasRectangle const*, QCanvasEllipse const*, QCanvasText const*) const

The Run Time Type Information for the QCanvasText class is described by Table 7-595

Table 7-595 typeinfo for QCanvasText

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasText
basetype:	typeinfo for QCanvasItem

7.2.1.253 Class data for QXmlInputSource

The virtual table for the QXmlInputSource class is described by Table 7-596

Table 7-596 Primary vtable for QXmlInputSource

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlInputSource
vfunc[0]:	QXmlInputSource::~~QXmlInputSource()
vfunc[1]:	QXmlInputSource::~~QXmlInputSource()
vfunc[2]:	QXmlInputSource::setData(QString const&)
vfunc[3]:	QXmlInputSource::setData(QMemArray<char> const&)
vfunc[4]:	QXmlInputSource::fetchData()
vfunc[5]:	QXmlInputSource::data()
vfunc[6]:	QXmlInputSource::next()
vfunc[7]:	QXmlInputSource::reset()
vfunc[8]:	QXmlInputSource::fromRawData(QMemArray<char> const&, bool)

The Run Time Type Information for the QXmlInputSource class is described by Table 7-597

Table 7-597 typeinfo for QXmlInputSource

Base Vtable	vtable for
-------------	------------

	__cxxabiv1::__class_type_info
Name	typeinfo name for QXmlInputSource

7.2.1.254 Class data for QDoubleValidator

The virtual table for the QDoubleValidator class is described by Table 7-598

Table 7-598 Primary vtable for QDoubleValidator

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDoubleValidator
vfunc[0]:	QDoubleValidator::metaObject() const
vfunc[1]:	QDoubleValidator::className() const
vfunc[2]:	QDoubleValidator::qt_cast(char const*)
vfunc[3]:	QDoubleValidator::qt_invoke(int, QIODevice*)
vfunc[4]:	QDoubleValidator::qt_emit(int, QIODevice*)
vfunc[5]:	QDoubleValidator::qt_property(int, int, QVariant*)
vfunc[6]:	QDoubleValidator::~~QDoubleValidat or()
vfunc[7]:	QDoubleValidator::~~QDoubleValidat or()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)

vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QDoubleValidator::validate(QString &, int&) const
vfunc[22]:	QValidator::fixup(QString&) const
vfunc[23]:	QDoubleValidator::setRange(double, double, int)

The Run Time Type Information for the QDoubleValidator class is described by Table 7-599

Table 7-599 typeinfo for QDoubleValidator

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDoubleValidator
basetype:	typeinfo for QValidator

7.2.1.255 Class data for QIODevice

The virtual table for the QIODevice class is described by Table 7-600

Table 7-600 Primary vtable for QIODevice

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIODevice
vfunc[0]:	QIODevice::~~QIODevice()
vfunc[1]:	QIODevice::~~QIODevice()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	QIODevice::at() const
vfunc[7]:	QIODevice::at(unsigned long)
vfunc[8]:	QIODevice::atEnd() const
vfunc[9]:	__cxa_pure_virtual
vfunc[10]:	__cxa_pure_virtual
vfunc[11]:	QIODevice::readLine(char*, unsigned long)
vfunc[12]:	QIODevice::readAll()

vfunc[13]:	__cxa_pure_virtual
vfunc[14]:	__cxa_pure_virtual
vfunc[15]:	__cxa_pure_virtual

The Run Time Type Information for the QIODevice class is described by Table 7-601

Table 7-601 typeinfo for QIODevice

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QIODevice

7.2.1.256 Class data for QInputDialog

The virtual table for the QInputDialog class is described by Table 7-602

Table 7-602 Primary vtable for QInputDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QInputDialog
vfunc[0]:	QInputDialog::metaObject() const
vfunc[1]:	QInputDialog::className() const
vfunc[2]:	QInputDialog::qt_cast(char const*)
vfunc[3]:	QInputDialog::qt_invoke(int, QUObject*)
vfunc[4]:	QInputDialog::qt_emit(int, QUObject*)
vfunc[5]:	QInputDialog::qt_property(int, int, QVariant*)
vfunc[6]:	QInputDialog::~~QInputDialog()
vfunc[7]:	QInputDialog::~QInputDialog()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDialog::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)

vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)

vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)

vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)

vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 7-603 Secondary vtable for QDialog

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDialog
vfunc[0]:	non-virtual thunk to QDialog::~~QDialog()
vfunc[1]:	non-virtual thunk to QDialog::~~QDialog()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPaintDeviceCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int,

	char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QInputDialog class is described by Table 7-604

Table 7-604 typeinfo for QInputDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QInputDialog
basetype:	typeinfo for QDialog

7.2.1.257 Class data for QGDict

The virtual table for the QGDict class is described by Table 7-605

Table 7-605 Primary vtable for QGDict

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QGDict
vfunc[0]:	QGDict::count() const
vfunc[1]:	QGDict::clear()
vfunc[2]:	QGDict::~~QGDict()
vfunc[3]:	QGDict::~~QGDict()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	QGDict::read(QDataStream&, void*&)
vfunc[7]:	QGDict::write(QDataStream&, void*) const

The Run Time Type Information for the QGDict class is described by Table 7-606

Table 7-606 typeinfo for QGDict

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QGDict
basetype:	typeinfo for QPtrCollection

7.2.1.258 Class data for QXmlErrorHandler

The virtual table for the QXmlErrorHandler class is described by Table 7-607

Table 7-607 Primary vtable for QXmlErrorHandler

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QXmlErrorHandler
vfunc[0]:	__cxa_pure_virtual
vfunc[1]:	__cxa_pure_virtual
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual

The Run Time Type Information for the QXmlErrorHandler class is described by Table 7-608

Table 7-608 typeinfo for QXmlErrorHandler

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QXmlErrorHandler

7.2.1.259 Class data for QWorkspace

The virtual table for the QWorkspace class is described by Table 7-609

Table 7-609 Primary vtable for QWorkspace

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWorkspace
vfunc[0]:	QWorkspace::metaObject() const
vfunc[1]:	QWorkspace::className() const
vfunc[2]:	QWorkspace::qt_cast(char const*)
vfunc[3]:	QWorkspace::qt_invoke(int, QUObject*)
vfunc[4]:	QWorkspace::qt_emit(int, QUObject*)
vfunc[5]:	QWorkspace::qt_property(int, int, QVariant*)
vfunc[6]:	QWorkspace::~~QWorkspace()
vfunc[7]:	QWorkspace::~~QWorkspace()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QWorkspace::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)

vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QWorkspace::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWorkspace::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWorkspace::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPi

	xmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWorkspace::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWi

	dget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWorkspace::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWorkspace::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLe

	aveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWorkspace::showEvent(QShowEvent*)
vfunc[94]:	QWorkspace::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWorkspace::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)

Table 7-610 Secondary vtable for QWorkspace

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QWorkspace
vfunc[0]:	non-virtual thunk to QWorkspace::~~QWorkspace()
vfunc[1]:	non-virtual thunk to QWorkspace::~~QWorkspace()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle()

	const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QWorkspace class is described by Table 7-611

Table 7-611 typeinfo for QWorkspace

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWorkspace
basetype:	typeinfo for QWidget

7.2.1.260 Class data for QTabDialog

The virtual table for the QTabDialog class is described by Table 7-612

Table 7-612 Primary vtable for QTabDialog

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTabDialog
vfunc[0]:	QTabDialog::metaObject() const
vfunc[1]:	QTabDialog::className() const
vfunc[2]:	QTabDialog::qt_cast(char const*)
vfunc[3]:	QTabDialog::qt_invoke(int, QUObject*)
vfunc[4]:	QTabDialog::qt_emit(int, QUObject*)
vfunc[5]:	QTabDialog::qt_property(int, int, QVariant*)
vfunc[6]:	QTabDialog::~~QTabDialog()
vfunc[7]:	QTabDialog::~~QTabDialog()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QDialog::eventFilter(QObject*, QEvent*)

vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::B ackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColo r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixm ap(QPixmap const&)
vfunc[31]:	QTabDialog::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QCol or const&)

vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QDialog::show()
vfunc[48]:	QDialog::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QDialog::move(int, int)
vfunc[54]:	QDialog::resize(int, int)
vfunc[55]:	QDialog::setGeometry(int, int, int, int)
vfunc[56]:	QDialog::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDialog::sizeHint() const
vfunc[59]:	QDialog::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWi

	dget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QDialog::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QTabDialog::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QTabDialog::resizeEvent(QResizeEvent*)
vfunc[83]:	QDialog::closeEvent(QCloseEvent*)
vfunc[84]:	QDialog::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)

vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QTabDialog::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDialog::done(int)
vfunc[111]:	QDialog::accept()
vfunc[112]:	QDialog::reject()

Table 7-613 Secondary vtable for QTabDialog

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QTabDialog
vfunc[0]:	non-virtual thunk to QTabDialog::~~QTabDialog()
vfunc[1]:	non-virtual thunk to QTabDialog::~~QTabDialog()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const

vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QTabDialog class is described by Table 7-614

Table 7-614 typeinfo for QTabDialog

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTabDialog
basetype:	typeinfo for QDialog

7.2.1.261 Class data for QHttpRequestHeader

The virtual table for the QHttpRequestHeader class is described by Table 7-615

Table 7-615 Primary vtable for QHttpRequestHeader

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHttpRequestHeader
vfunc[0]:	QHttpRequestHeader::~~QHttpRequestHeader()
vfunc[1]:	QHttpRequestHeader::~~QHttpRequestHeader()
vfunc[2]:	QHttpRequestHeader::toString() const
vfunc[3]:	QHttpRequestHeader::majorVersion() const
vfunc[4]:	QHttpRequestHeader::minorVersion() const
vfunc[5]:	QHttpRequestHeader::parseLine(QString const&, int)

The Run Time Type Information for the `QHttpRequestHeader` class is described by Table 7-616

Table 7-616 typeinfo for `QHttpRequestHeader`

Base Vtable	vtable for <code>__cxxabiv1::__si_class_type_info</code>
Name	typeinfo name for <code>QHttpRequestHeader</code>
basetype:	typeinfo for <code>QHttpHeader</code>

7.2.1.262 Class data for `QDragObject`

The virtual table for the `QDragObject` class is described by Table 7-617

Table 7-617 Primary vtable for `QDragObject`

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for <code>QDragObject</code>
vfunc[0]:	<code>QDragObject::metaObject() const</code>
vfunc[1]:	<code>QDragObject::className() const</code>
vfunc[2]:	<code>QDragObject::qt_cast(char const*)</code>
vfunc[3]:	<code>QDragObject::qt_invoke(int, QUObject*)</code>
vfunc[4]:	<code>QDragObject::qt_emit(int, QUObject*)</code>
vfunc[5]:	<code>QDragObject::qt_property(int, int, QVariant*)</code>
vfunc[6]:	<code>QDragObject::~~QDragObject()</code>
vfunc[7]:	<code>QDragObject::~~QDragObject()</code>
vfunc[8]:	<code>QObject::event(QEvent*)</code>
vfunc[9]:	<code>QObject::eventFilter(QObject*, QEvent*)</code>
vfunc[10]:	<code>QObject::setName(char const*)</code>
vfunc[11]:	<code>QObject::insertChild(QObject*)</code>
vfunc[12]:	<code>QObject::removeChild(QObject*)</code>
vfunc[13]:	<code>QObject::setProperty(char const*, QVariant const&)</code>
vfunc[14]:	<code>QObject::property(char const*) const</code>
vfunc[15]:	<code>QObject::timerEvent(QTimerEvent*)</code>
vfunc[16]:	<code>QObject::childEvent(QChildEvent*)</code>
vfunc[17]:	<code>QObject::customEvent(QCustomEve</code>

	nt*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QDragObject::setPixmap(QPixmap)
vfunc[22]:	QDragObject::setPixmap(QPixmap, QPoint const&)
vfunc[23]:	QDragObject::drag(QDragObject::DragMode)

Table 7-618 Secondary vtable for QDragObject

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDragObject
vfunc[0]:	non-virtual thunk to QDragObject::~~QDragObject()
vfunc[1]:	non-virtual thunk to QDragObject::~~QDragObject()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	QMimeSource::provides(char const*) const
vfunc[4]:	__cxa_pure_virtual

The Run Time Type Information for the QDragObject class is described by Table 7-619

Table 7-619 typeinfo for QDragObject

Base Vtable	vtable for __cxxabiv1::__vmi_class _type_info	2
Name	typeinfo name for QDragObject	
flags:	0	
basetype:	typeinfo for QObject	
basetype:	typeinfo for QMimeSource	10242

7.2.1.263 Class data for QToolTipGroup

The virtual table for the QToolTipGroup class is described by Table 7-620

Table 7-620 Primary vtable for QToolTipGroup

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QToolTipGroup
vfunc[0]:	QToolTipGroup::metaObject() const
vfunc[1]:	QToolTipGroup::className() const
vfunc[2]:	QToolTipGroup::qt_cast(char const*)
vfunc[3]:	QToolTipGroup::qt_invoke(int, QUObject*)
vfunc[4]:	QToolTipGroup::qt_emit(int, QUObject*)
vfunc[5]:	QToolTipGroup::qt_property(int, int, QVariant*)
vfunc[6]:	QToolTipGroup::~~QToolTipGroup()
vfunc[7]:	QToolTipGroup::~~QToolTipGroup()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QToolTipGroup class is described by Table 7-621

Table 7-621 typeinfo for QToolTipGroup

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
-------------	--

Name	typeinfo name for QToolTipGroup
basetype:	typeinfo for QObject

7.2.1.264 Class data for QDateTimeEditBase

The virtual table for the QDateTimeEditBase class is described by Table 7-622

Table 7-622 Primary vtable for QDateTimeEditBase

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDateTimeEditBase
vfunc[0]:	QDateTimeEditBase::metaObject() const
vfunc[1]:	QDateTimeEditBase::className() const
vfunc[2]:	QDateTimeEditBase::qt_cast(char const*)
vfunc[3]:	QDateTimeEditBase::qt_invoke(int, QObject*)
vfunc[4]:	QDateTimeEditBase::qt_emit(int, QObject*)
vfunc[5]:	QDateTimeEditBase::qt_property(int, int, QVariant*)
vfunc[6]:	QDateTimeEditBase::~~QDateTimeEd itBase()
vfunc[7]:	QDateTimeEditBase::~~QDateTimeEd itBase()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEve nt*)
vfunc[18]:	QObject::connectNotify(char const*)

vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)

vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)

vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)

vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	__cxa_pure_virtual
vfunc[111]:	__cxa_pure_virtual
vfunc[112]:	__cxa_pure_virtual
vfunc[113]:	__cxa_pure_virtual
vfunc[114]:	__cxa_pure_virtual
vfunc[115]:	__cxa_pure_virtual

Table 7-623 Secondary vtable for QDateTimeEditBase

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDateTimeEditBase
vfunc[0]:	non-virtual thunk to QDateTimeEditBase::~~QDateTimeEditBase()
vfunc[1]:	non-virtual thunk to QDateTimeEditBase::~~QDateTimeEditBase()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to

	QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QDateTimeEditBase class is described by Table 7-624

Table 7-624 typeinfo for QDateTimeEditBase

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDateTimeEditBase
basetype:	typeinfo for QWidget

7.2.1.265 Class data for QHTTPHeader

The virtual table for the QHTTPHeader class is described by Table 7-625

Table 7-625 Primary vtable for QHTTPHeader

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHTTPHeader
vfunc[0]:	QHTTPHeader::~~QHTTPHeader()
vfunc[1]:	QHTTPHeader::~~QHTTPHeader()
vfunc[2]:	QHTTPHeader::toString() const
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	QHTTPHeader::parseLine(QString const&, int)

The Run Time Type Information for the QHTTPHeader class is described by Table 7-626

Table 7-626 typeinfo for QHTTPHeader

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QHTTPHeader

7.2.1.266 Class data for QShowEvent

The virtual table for the QShowEvent class is described by Table 7-627

Table 7-627 Primary vtable for QShowEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QShowEvent
vfunc[0]:	QShowEvent::~~QShowEvent()
vfunc[1]:	QShowEvent::~~QShowEvent()

The Run Time Type Information for the QShowEvent class is described by Table 7-628

Table 7-628 typeinfo for QShowEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QShowEvent
basetype:	typeinfo for QEvent

7.2.1.267 Class data for QTable

The virtual table for the QTable class is described by Table 7-629

Table 7-629 Primary vtable for QTable

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTable
vfunc[0]:	QTable::metaObject() const
vfunc[1]:	QTable::className() const
vfunc[2]:	QTable::qt_cast(char const*)
vfunc[3]:	QTable::qt_invoke(int, QUObject*)
vfunc[4]:	QTable::qt_emit(int, QUObject*)
vfunc[5]:	QTable::qt_property(int, int, QVariant*)
vfunc[6]:	QTable::~~QTable()
vfunc[7]:	QTable::~~QTable()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QTable::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*,

	QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QTable::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)

vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QTable::sizeHint() const
vfunc[59]:	QScrollView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)

	useEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QTable::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QTable::focusInEvent(QFocusEvent*)
vfunc[77]:	QTable::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QTable::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QScrollView::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QTable::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)

vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QTable::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QScrollView::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QTable::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)

vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QTable::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QTable::contentsMouseEvent(QMouseEvent*)
vfunc[130]:	QTable::contentsMouseReleaseEvent(QMouseEvent*)
vfunc[131]:	QTable::contentsMouseDoubleClickEvent(QMouseEvent*)
vfunc[132]:	QTable::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QTable::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QTable::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QTable::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QTable::contentsDropEvent(QDropEvent*)
vfunc[137]:	QScrollView::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QTable::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QTable::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)

vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int, int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)
vfunc[154]:	QTable::setSelectionMode(QTable::SelectionMode)
vfunc[155]:	QTable::setItem(int, int, QTableWidgetItem*)
vfunc[156]:	QTable::setText(int, int, QString const&)
vfunc[157]:	QTable::setPixmap(int, int, QPixmap const&)
vfunc[158]:	QTable::item(int, int) const
vfunc[159]:	QTable::text(int, int) const
vfunc[160]:	QTable::pixmap(int, int) const
vfunc[161]:	QTable::clearCell(int, int)
vfunc[162]:	QTable::cellGeometry(int, int) const
vfunc[163]:	QTable::columnWidth(int) const
vfunc[164]:	QTable::rowHeight(int) const
vfunc[165]:	QTable::columnPos(int) const
vfunc[166]:	QTable::rowPos(int) const
vfunc[167]:	QTable::columnAt(int) const
vfunc[168]:	QTable::rowAt(int) const

vfunc[169]:	QTable::numRows() const
vfunc[170]:	QTable::numCols() const
vfunc[171]:	QTable::addSelection(QTableSelection const&)
vfunc[172]:	QTable::removeSelection(QTableSelection const&)
vfunc[173]:	QTable::removeSelection(int)
vfunc[174]:	QTable::currentSelection() const
vfunc[175]:	QTable::sortColumn(int, bool, bool)
vfunc[176]:	QTable::takeItem(QTableWidgetItem*)
vfunc[177]:	QTable::setCellWidget(int, int, QWidget*)
vfunc[178]:	QTable::cellWidget(int, int) const
vfunc[179]:	QTable::clearCellWidget(int, int)
vfunc[180]:	QTable::cellRect(int, int) const
vfunc[181]:	QTable::paintCell(QPainter*, int, int, QRect const&, bool)
vfunc[182]:	QTable::paintCell(QPainter*, int, int, QRect const&, bool, QColorGroup const&)
vfunc[183]:	QTable::paintFocus(QPainter*, QRect const&)
vfunc[184]:	QTable::setFocusStyle(QTable::FocusStyle)
vfunc[185]:	QTable::setNumRows(int)
vfunc[186]:	QTable::setNumCols(int)
vfunc[187]:	QTable::setShowGrid(bool)
vfunc[188]:	QTable::hideRow(int)
vfunc[189]:	QTable::hideColumn(int)
vfunc[190]:	QTable::showRow(int)
vfunc[191]:	QTable::showColumn(int)
vfunc[192]:	QTable::setColumnWidth(int, int)
vfunc[193]:	QTable::setRowHeight(int, int)
vfunc[194]:	QTable::adjustColumn(int)
vfunc[195]:	QTable::adjustRow(int)
vfunc[196]:	QTable::setColumnStretchable(int, bool)
vfunc[197]:	QTable::setRowStretchable(int, bool)

vfunc[198]:	QTable::setSorting(bool)
vfunc[199]:	QTable::swapRows(int, int, bool)
vfunc[200]:	QTable::swapColumns(int, int, bool)
vfunc[201]:	QTable::swapCells(int, int, int, int)
vfunc[202]:	QTable::setLeftMargin(int)
vfunc[203]:	QTable::setTopMargin(int)
vfunc[204]:	QTable::setCurrentCell(int, int)
vfunc[205]:	QTable::setColumnMovingEnabled(bool)
vfunc[206]:	QTable::setRowMovingEnabled(bool)
vfunc[207]:	QTable::setReadOnly(bool)
vfunc[208]:	QTable::setRowReadOnly(int, bool)
vfunc[209]:	QTable::setColumnReadOnly(int, bool)
vfunc[210]:	QTable::setDragEnabled(bool)
vfunc[211]:	QTable::insertRows(int, int)
vfunc[212]:	QTable::insertColumns(int, int)
vfunc[213]:	QTable::removeRow(int)
vfunc[214]:	QTable::removeRows(QMemArray<int> const&)
vfunc[215]:	QTable::removeColumn(int)
vfunc[216]:	QTable::removeColumns(QMemArray<int> const&)
vfunc[217]:	QTable::editCell(int, int, bool)
vfunc[218]:	QTable::dragObject()
vfunc[219]:	QTable::startDrag()
vfunc[220]:	QTable::paintEmptyArea(QPainter*, int, int, int, int)
vfunc[221]:	QTable::activateNextCell()
vfunc[222]:	QTable::createEditor(int, int, bool) const
vfunc[223]:	QTable::setCellContentFromEditor(int, int)
vfunc[224]:	QTable::beginEdit(int, int, bool)
vfunc[225]:	QTable::endEdit(int, int, bool, bool)
vfunc[226]:	QTable::resizeData(int)

vfunc[227]:	QTable::insertWidget(int, int, QWidget*)
vfunc[228]:	QTable::columnWidthChanged(int)
vfunc[229]:	QTable::rowHeightChanged(int)
vfunc[230]:	QTable::columnIndexChanged(int, int, int)
vfunc[231]:	QTable::rowIndexChanged(int, int, int)
vfunc[232]:	QTable::columnClicked(int)

Table 7-630 Secondary vtable for QTable

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QTable
vfunc[0]:	non-virtual thunk to QTable::~~QTable()
vfunc[1]:	non-virtual thunk to QTable::~~QTable()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QTable class is described by Table 7-631

Table 7-631 typeinfo for QTable

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTable
basetype:	typeinfo for QScrollView

7.2.1.268 Class data for QLocalFs

The virtual table for the QLocalFs class is described by Table 7-632

Table 7-632 Primary vtable for QLocalFs

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLocalFs
vfunc[0]:	QLocalFs::metaObject() const
vfunc[1]:	QLocalFs::className() const
vfunc[2]:	QLocalFs::qt_cast(char const*)
vfunc[3]:	QLocalFs::qt_invoke(int, QUObject*)
vfunc[4]:	QLocalFs::qt_emit(int, QUObject*)
vfunc[5]:	QLocalFs::qt_property(int, int, QVariant*)
vfunc[6]:	QLocalFs::~~QLocalFs()
vfunc[7]:	QLocalFs::~~QLocalFs()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QNetworkProtocol::setUrl(QUrlOperator*)
vfunc[22]:	QNetworkProtocol::setAutoDelete(bool, int)

vfunc[23]:	QLocalFs::supportedOperations() const
vfunc[24]:	QNetworkProtocol::addOperation(Q NetworkOperation*)
vfunc[25]:	QNetworkProtocol::clearOperationQ ueue()
vfunc[26]:	QNetworkProtocol::stop()
vfunc[27]:	QNetworkProtocol::processOperatio n(QNetworkOperation*)
vfunc[28]:	QLocalFs::operationListChildren(QN etworkOperation*)
vfunc[29]:	QLocalFs::operationMkDir(QNetwor kOperation*)
vfunc[30]:	QLocalFs::operationRemove(QNetw orkOperation*)
vfunc[31]:	QLocalFs::operationRename(QNetwo rkOperation*)
vfunc[32]:	QLocalFs::operationGet(QNetworkO peration*)
vfunc[33]:	QLocalFs::operationPut(QNetworkO peration*)
vfunc[34]:	QNetworkProtocol::operationPutChu nk(QNetworkOperation*)
vfunc[35]:	QNetworkProtocol::checkConnection (QNetworkOperation*)

The Run Time Type Information for the QLocalFs class is described by Table 7-633

Table 7-633 typeinfo for QLocalFs

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QLocalFs
basetype:	typeinfo for QNetworkProtocol

7.2.1.269 Class data for QCanvasPolygon

The virtual table for the QCanvasPolygon class is described by Table 7-634

Table 7-634 Primary vtable for QCanvasPolygon

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvasPolygon

vfunc[0]:	QCanvasPolygon::~~QCanvasPolygon()
vfunc[1]:	QCanvasPolygon::~~QCanvasPolygon()
vfunc[2]:	QCanvasPolygon::moveBy(double, double)
vfunc[3]:	QCanvasItem::setAnimated(bool)
vfunc[4]:	QCanvasItem::setVelocity(double, double)
vfunc[5]:	QCanvasItem::advance(int)
vfunc[6]:	QCanvasPolygonalItem::collidesWith(QCanvasItem const*) const
vfunc[7]:	QCanvasItem::setCanvas(QCanvas*)
vfunc[8]:	QCanvasPolygonalItem::draw(QPainter&)
vfunc[9]:	QCanvasItem::setVisible(bool)
vfunc[10]:	QCanvasItem::setSelected(bool)
vfunc[11]:	QCanvasItem::setEnabled(bool)
vfunc[12]:	QCanvasItem::setActive(bool)
vfunc[13]:	QCanvasPolygon::rtti() const
vfunc[14]:	QCanvasPolygonalItem::boundingRect() const
vfunc[15]:	QCanvasItem::boundingRectAdvanced() const
vfunc[16]:	QCanvasPolygonalItem::chunks() const
vfunc[17]:	QCanvasItem::addToChunks()
vfunc[18]:	QCanvasItem::removeFromChunks()
vfunc[19]:	QCanvasItem::changeChunks()
vfunc[20]:	QCanvasPolygonalItem::collidesWith(QCanvasSprite const*, QCanvasPolygonalItem const*, QCanvasRectangle const*, QCanvasEllipse const*, QCanvasText const*) const
vfunc[21]:	QCanvasPolygonalItem::setPen(QPen)
vfunc[22]:	QCanvasPolygonalItem::setBrush(QBrush)
vfunc[23]:	QCanvasPolygon::areaPoints() const

vfunc[24]:	QCanvasPolygonalItem::areaPointsAdvanced() const
vfunc[25]:	QCanvasPolygon::drawShape(QPainter&)

The Run Time Type Information for the QCanvasPolygon class is described by Table 7-635

Table 7-635 typeinfo for QCanvasPolygon

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvasPolygon
basetype:	typeinfo for QCanvasPolygonalItem

7.2.1.270 Class data for QDateEdit

The virtual table for the QDateEdit class is described by Table 7-636

Table 7-636 Primary vtable for QDateEdit

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDateEdit
vfunc[0]:	QDateEdit::metaObject() const
vfunc[1]:	QDateEdit::className() const
vfunc[2]:	QDateEdit::qt_cast(char const*)
vfunc[3]:	QDateEdit::qt_invoke(int, QUObject*)
vfunc[4]:	QDateEdit::qt_emit(int, QUObject*)
vfunc[5]:	QDateEdit::qt_property(int, int, QVariant*)
vfunc[6]:	QDateEdit::~QDateEdit()
vfunc[7]:	QDateEdit::~QDateEdit()
vfunc[8]:	QDateEdit::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const

vfunc[15]:	QDateEdit::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString

	const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QDateEdit::sizeHint() const
vfunc[59]:	QDateEdit::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)

vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QDateEdit::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)

vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDateEdit::setFocusSection(int)
vfunc[111]:	QDateEdit::sectionFormattedText(int)
vfunc[112]:	QDateEdit::addNumber(int, int)
vfunc[113]:	QDateEdit::removeLastNumber(int)
vfunc[114]:	QDateEdit::stepUp()
vfunc[115]:	QDateEdit::stepDown()
vfunc[116]:	QDateEdit::setDate(QDate const&)
vfunc[117]:	QDateEdit::setOrder(QDateEdit::Order)
vfunc[118]:	QDateEdit::setAutoAdvance(bool)
vfunc[119]:	QDateEdit::setMinValue(QDate const&)
vfunc[120]:	QDateEdit::setMaxValue(QDate const&)
vfunc[121]:	QDateEdit::setRange(QDate const&, QDate const&)
vfunc[122]:	QDateEdit::setSeparator(QString const&)

vfunc[123]:	QDateEdit::setYear(int)
vfunc[124]:	QDateEdit::setMonth(int)
vfunc[125]:	QDateEdit::setDay(int)
vfunc[126]:	QDateEdit::fix()
vfunc[127]:	QDateEdit::outOfRange(int, int, int) const

Table 7-637 Secondary vtable for QDateEdit

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDateEdit
vfunc[0]:	non-virtual thunk to QDateEdit::~~QDateEdit()
vfunc[1]:	non-virtual thunk to QDateEdit::~~QDateEdit()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QDateEdit class is described by Table 7-638

Table 7-638 typeinfo for QDateEdit

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDateEdit
basetype:	typeinfo for QDateTimeEditBase

7.2.1.271 Class data for QPaintEvent

The virtual table for the QPaintEvent class is described by Table 7-639

Table 7-639 Primary vtable for QPaintEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPaintEvent
vfunc[0]:	QPaintEvent::~~QPaintEvent()
vfunc[1]:	QPaintEvent::~~QPaintEvent()

The Run Time Type Information for the QPaintEvent class is described by Table 7-640

Table 7-640 typeinfo for QPaintEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPaintEvent
basetype:	typeinfo for QEvent

7.2.1.272 Class data for QAccel

The virtual table for the QAccel class is described by Table 7-641

Table 7-641 Primary vtable for QAccel

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAccel
vfunc[0]:	QAccel::metaObject() const
vfunc[1]:	QAccel::className() const
vfunc[2]:	QAccel::qt_cast(char const*)
vfunc[3]:	QAccel::qt_invoke(int, QUObject*)
vfunc[4]:	QAccel::qt_emit(int, QUObject*)
vfunc[5]:	QAccel::qt_property(int, int, QVariant*)
vfunc[6]:	QAccel::~~QAccel()
vfunc[7]:	QAccel::~~QAccel()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QAccel::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)

vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)

The Run Time Type Information for the QAccel class is described by Table 7-642

Table 7-642 typeinfo for QAccel

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAccel
basetype:	typeinfo for QObject

7.2.1.273 Class data for QCanvas

The virtual table for the QCanvas class is described by Table 7-643

Table 7-643 Primary vtable for QCanvas

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCanvas
vfunc[0]:	QCanvas::metaObject() const
vfunc[1]:	QCanvas::className() const
vfunc[2]:	QCanvas::qt_cast(char const*)
vfunc[3]:	QCanvas::qt_invoke(int, QUObject*)
vfunc[4]:	QCanvas::qt_emit(int, QUObject*)
vfunc[5]:	QCanvas::qt_property(int, int, QVariant*)
vfunc[6]:	QCanvas::~~QCanvas()
vfunc[7]:	QCanvas::~~QCanvas()
vfunc[8]:	QObject::event(QEvent*)

vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QCanvas::setTiles(QPixmap, int, int, int, int)
vfunc[22]:	QCanvas::setBackgroundPixmap(QPixmap const&)
vfunc[23]:	QCanvas::setBackgroundColors(QColor const&)
vfunc[24]:	QCanvas::setTile(int, int, int)
vfunc[25]:	QCanvas::resize(int, int)
vfunc[26]:	QCanvas::retune(int, int)
vfunc[27]:	QCanvas::setChangedChunk(int, int)
vfunc[28]:	QCanvas::setChangedChunkContaining(int, int)
vfunc[29]:	QCanvas::setAllChanged()
vfunc[30]:	QCanvas::setChanged(QRect const&)
vfunc[31]:	QCanvas::setUnchanged(QRect const&)
vfunc[32]:	QCanvas::addView(QCanvasView*)
vfunc[33]:	QCanvas::removeView(QCanvasView*)
vfunc[34]:	QCanvas::addItem(QCanvasItem*)
vfunc[35]:	QCanvas::addAnimation(QCanvasItem*)

vfunc[36]:	QCanvas::removeItem(QCanvasItem*)
vfunc[37]:	QCanvas::removeAnimation(QCanvasItem*)
vfunc[38]:	QCanvas::setAdvancePeriod(int)
vfunc[39]:	QCanvas::setUpdatePeriod(int)
vfunc[40]:	QCanvas::setDoubleBuffering(bool)
vfunc[41]:	QCanvas::advance()
vfunc[42]:	QCanvas::update()
vfunc[43]:	QCanvas::drawBackground(QPainter &, QRect const&)
vfunc[44]:	QCanvas::drawForeground(QPainter &, QRect const&)

The Run Time Type Information for the QCanvas class is described by Table 7-644

Table 7-644 typeinfo for QCanvas

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCanvas
basetype:	typeinfo for QObject

7.2.1.274 Class data for QDomDocumentFragment

The virtual table for the QDomDocumentFragment class is described by Table 7-645

Table 7-645 Primary vtable for QDomDocumentFragment

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDomDocumentFragment
vfunc[0]:	QDomDocumentFragment::~~QDomDocumentFragment()
vfunc[1]:	QDomDocumentFragment::~~QDomDocumentFragment()
vfunc[2]:	QDomNode::insertBefore(QDomNode const&, QDomNode const&)
vfunc[3]:	QDomNode::insertAfter(QDomNode const&, QDomNode const&)
vfunc[4]:	QDomNode::replaceChild(QDomNode const&, QDomNode const&)

vfunc[5]:	QDomNode::removeChild(QDomNode const&)
vfunc[6]:	QDomNode::appendChild(QDomNode const&)
vfunc[7]:	QDomNode::hasChildNodes() const
vfunc[8]:	QDomNode::cloneNode(bool) const
vfunc[9]:	QDomNode::normalize()
vfunc[10]:	QDomNode::isSupported(QString const&, QString const&) const
vfunc[11]:	QDomNode::nodeName() const
vfunc[12]:	QDomDocumentFragment::nodeType() const
vfunc[13]:	QDomNode::parentNode() const
vfunc[14]:	QDomNode::childNodes() const
vfunc[15]:	QDomNode::firstChild() const
vfunc[16]:	QDomNode::lastChild() const
vfunc[17]:	QDomNode::previousSibling() const
vfunc[18]:	QDomNode::nextSibling() const
vfunc[19]:	QDomNode::attributes() const
vfunc[20]:	QDomNode::ownerDocument() const
vfunc[21]:	QDomNode::namespaceURI() const
vfunc[22]:	QDomNode::localName() const
vfunc[23]:	QDomNode::hasAttributes() const
vfunc[24]:	QDomNode::nodeValue() const
vfunc[25]:	QDomNode::setNodeValue(QString const&)
vfunc[26]:	QDomNode::prefix() const
vfunc[27]:	QDomNode::setPrefix(QString const&)
vfunc[28]:	QDomNode::isAttr() const
vfunc[29]:	QDomNode::isCDATASection() const
vfunc[30]:	QDomDocumentFragment::isDocumentFragment() const
vfunc[31]:	QDomNode::isDocument() const
vfunc[32]:	QDomNode::isDocumentType() const

vfunc[33]:	QDomNode::isElement() const
vfunc[34]:	QDomNode::isEntityReference() const
vfunc[35]:	QDomNode::isText() const
vfunc[36]:	QDomNode::isEntity() const
vfunc[37]:	QDomNode::isNotation() const
vfunc[38]:	QDomNode::isProcessingInstruction()) const
vfunc[39]:	QDomNode::isCharacterData() const
vfunc[40]:	QDomNode::isComment() const

The Run Time Type Information for the QDomDocumentFragment class is described by Table 7-646

Table 7-646 typeinfo for QDomDocumentFragment

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDomDocumentFragment
basetype:	typeinfo for QDomNode

7.2.1.275 Class data for QDataStream

The virtual table for the QDataStream class is described by Table 7-647

Table 7-647 Primary vtable for QDataStream

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDataStream
vfunc[0]:	QDataStream::~~QDataStream()
vfunc[1]:	QDataStream::~~QDataStream()

The Run Time Type Information for the QDataStream class is described by Table 7-648

Table 7-648 typeinfo for QDataStream

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QDataStream

7.2.1.276 Class data for QJpUnicodeConv

The virtual table for the QJpUnicodeConv class is described by Table 7-649

Table 7-649 Primary vtable for QJpUnicodeConv

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QJpUnicodeConv
vfunc[0]:	QJpUnicodeConv::asciiToUnicode(unsigned int, unsigned int) const
vfunc[1]:	QJpUnicodeConv::jisx0201LatinToUnicode(unsigned int, unsigned int) const
vfunc[2]:	QJpUnicodeConv::jisx0208ToUnicode(unsigned int, unsigned int) const
vfunc[3]:	QJpUnicodeConv::jisx0212ToUnicode(unsigned int, unsigned int) const
vfunc[4]:	QJpUnicodeConv::unicodeToAscii(unsigned int, unsigned int) const
vfunc[5]:	QJpUnicodeConv::unicodeToJisx0201Latin(unsigned int, unsigned int) const
vfunc[6]:	QJpUnicodeConv::unicodeToJisx0208(unsigned int, unsigned int) const
vfunc[7]:	QJpUnicodeConv::unicodeToJisx0212(unsigned int, unsigned int) const

The Run Time Type Information for the QJpUnicodeConv class is described by Table 7-650

Table 7-650 typeinfo for QJpUnicodeConv

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QJpUnicodeConv

7.2.1.277 Class data for QPushButton

The virtual table for the QPushButton class is described by Table 7-651

Table 7-651 Primary vtable for QPushButton

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QPushButton
vfunc[0]:	QPushButton::metaObject() const
vfunc[1]:	QPushButton::className() const
vfunc[2]:	QPushButton::qt_cast(char const*)
vfunc[3]:	QPushButton::qt_invoke(int,

	QObject*)
vfunc[4]:	QPushButton::qt_emit(int, QObject*)
vfunc[5]:	QPushButton::qt_property(int, int, QVariant*)
vfunc[6]:	QPushButton::~QPushButton()
vfunc[7]:	QPushButton::~~QPushButton()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap

	ap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QPushButton::move(int, int)
vfunc[54]:	QPushButton::resize(int, int)
vfunc[55]:	QPushButton::setGeometry(int, int, int, int)
vfunc[56]:	QPushButton::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QPushButton::sizeHint() const

vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QPushButton::mousePressEvent(QMouseEvent*)
vfunc[70]:	QPushButton::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QPushButton::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QPushButton::keyPressEvent(QKeyEvent*)
vfunc[75]:	QPushButton::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QPushButton::focusInEvent(QFocusEvent*)
vfunc[77]:	QPushButton::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QPushButton::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QPushButton::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)

vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QPushButton::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QPushButton::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QPushButton::setText(QString const&)
vfunc[111]:	QPushButton::setPixmap(QPixmap const&)
vfunc[112]:	QPushButton::setAccel(QKeySequence

	const&)
vfunc[113]:	QPushButton::setDown(bool)
vfunc[114]:	QPushButton::setAutoRepeat(bool)
vfunc[115]:	QPushButton::setToggleType(QButton::ToggleType)
vfunc[116]:	QPushButton::setState(QButton::ToggleState)
vfunc[117]:	QPushButton::hitButton(QPoint const& const)
vfunc[118]:	QPushButton::drawButton(QPainter*)
vfunc[119]:	QPushButton::drawButtonLabel(QPainter*)
vfunc[120]:	QPushButton::setGroup(QButtonGroup*)
vfunc[121]:	QPushButton::setAutoDefault(bool)
vfunc[122]:	QPushButton::setDefault(bool)
vfunc[123]:	QPushButton::setIsMenuButton(bool)
vfunc[124]:	QPushButton::setOn(bool)

Table 7-652 Secondary vtable for QPushButton

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QPushButton
vfunc[0]:	non-virtual thunk to QPushButton::~~QPushButton()
vfunc[1]:	non-virtual thunk to QPushButton::~~QPushButton()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const

vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QPushButton class is described by Table 7-653

Table 7-653 typeinfo for QPushButton

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QPushButton
basetype:	typeinfo for QButton

7.2.1.278 Class data for QList

The virtual table for the QList class is described by Table 7-654

Table 7-654 Primary vtable for QList

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QList
vfunc[0]:	QPtrList<QList>::count() const
vfunc[1]:	QPtrList<QList>::clear()
vfunc[2]:	QList::~QList()
vfunc[3]:	QList::~QList()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	QPtrList<QList>::deleteItem(void*)
vfunc[6]:	QList::compareItems(void*, void*)
vfunc[7]:	QList::read(QDataStream&, void*&)
vfunc[8]:	QList::write(QDataStream&, void*) const

The Run Time Type Information for the QList class is described by Table 7-655

Table 7-655 typeinfo for QList

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QList
basetype:	typeinfo for QPtrList<QList>

7.2.1.279 Class data for QMenuData

The virtual table for the QMenuData class is described by Table 7-656

Table 7-656 Primary vtable for QMenuData

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMenuData
vfunc[0]:	QMenuData::~~QMenuData()
vfunc[1]:	QMenuData::~~QMenuData()
vfunc[2]:	QMenuData::updateItem(int)
vfunc[3]:	QMenuData::setId(int, int)
vfunc[4]:	QMenuData::activateItemAt(int)
vfunc[5]:	QMenuData::menuContentsChanged() ()
vfunc[6]:	QMenuData::menuStateChanged()
vfunc[7]:	QMenuData::menuInsPopup(QPopu pMenu*)
vfunc[8]:	QMenuData::menuDelPopup(QPopu pMenu*)

The Run Time Type Information for the QMenuData class is described by Table 7-657

Table 7-657 typeinfo for QMenuData

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QMenuData

7.2.1.280 Class data for QDataView

The virtual table for the QDataView class is described by Table 7-658

Table 7-658 Primary vtable for QDataView

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDataView
vfunc[0]:	QDataView::metaObject() const
vfunc[1]:	QDataView::className() const
vfunc[2]:	QDataView::qt_cast(char const*)
vfunc[3]:	QDataView::qt_invoke(int, QUObject*)
vfunc[4]:	QDataView::qt_emit(int, QUObject*)

vfunc[5]:	QDataView::qt_property(int, int, QVariant*)
vfunc[6]:	QDataView::~~QDataView()
vfunc[7]:	QDataView::~~QDataView()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)

vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const

vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)

	nt*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDataView::setForm(QSqlForm*)
vfunc[111]:	QDataView::setRecord(QSqlRecord*)
vfunc[112]:	QDataView::refresh(QSqlRecord*)
vfunc[113]:	QDataView::readFields()
vfunc[114]:	QDataView::writeFields()

vfunc[115]:	QDataView::clearValues()
-------------	--------------------------

Table 7-659 Secondary vtable for QDataView

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDataView
vfunc[0]:	non-virtual thunk to QDataView::~~QDataView()
vfunc[1]:	non-virtual thunk to QDataView::~~QDataView()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QDataView class is described by Table 7-660

Table 7-660 typeinfo for QDataView

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDataView
basetype:	typeinfo for QWidget

7.2.1.281 Class data for QSqlEditorFactory

The virtual table for the QSqlEditorFactory class is described by Table 7-661

Table 7-661 Primary vtable for QSqlEditorFactory

Base Offset	0
Virtual Base Offset	0

RTTI	typeinfo for QSqlEditorFactory
vfunc[0]:	QObject::metaObject() const
vfunc[1]:	QObject::className() const
vfunc[2]:	QObject::qt_cast(char const*)
vfunc[3]:	QObject::qt_invoke(int, QUObject*)
vfunc[4]:	QObject::qt_emit(int, QUObject*)
vfunc[5]:	QObject::qt_property(int, int, QVariant*)
vfunc[6]:	QSqlEditorFactory::~~QSqlEditorFactory()
vfunc[7]:	QSqlEditorFactory::~~QSqlEditorFactory()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QSqlEditorFactory::createEditor(QWidget*, QVariant const&)
vfunc[22]:	QSqlEditorFactory::createEditor(QWidget*, QSqlField const*)

The Run Time Type Information for the QSqlEditorFactory class is described by Table 7-662

Table 7-662 typeinfo for QSqlEditorFactory

Base Vtable	vtable for
-------------	------------

	__cxxabiv1::__si_class_type_info
Name	typeinfo name for QSqlEditorFactory
basetype:	typeinfo for QEditorFactory

7.2.1.282 Class data for QConnectionList

The virtual table for the QConnectionList class is described by Table 7-663

Table 7-663 Primary vtable for QConnectionList

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QConnectionList
vfunc[0]:	QPtrList<QConnection>::count() const
vfunc[1]:	QPtrList<QConnection>::clear()
vfunc[2]:	QConnectionList::~~QConnectionList()
vfunc[3]:	QConnectionList::~~QConnectionList()
vfunc[4]:	QPtrCollection::newItem(void*)
vfunc[5]:	QPtrList<QConnection>::deleteItem(void*)
vfunc[6]:	QGList::compareItems(void*, void*)
vfunc[7]:	QGList::read(QDataStream& void*&)
vfunc[8]:	QGList::write(QDataStream&, void*) const

The Run Time Type Information for the QConnectionList class is described by Table 7-664

Table 7-664 typeinfo for QConnectionList

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QConnectionList
basetype:	typeinfo for QPtrList<QConnection>

7.2.1.283 Class data for QSqlCursor

The virtual table for the QSqlCursor class is described by Table 7-665

Table 7-665 Primary vtable for QSqlCursor

Base Offset	0
Virtual Base Offset	0

RTTI	typeid for QSqlCursor
vfunc[0]:	QSqlCursor::~~QSqlCursor()
vfunc[1]:	QSqlCursor::~~QSqlCursor()
vfunc[2]:	QSqlCursor::value(int) const
vfunc[3]:	QSqlCursor::value(QString const&) const
vfunc[4]:	QSqlCursor::setValue(int, QVariant const&)
vfunc[5]:	QSqlCursor::setValue(QString const&, QVariant const&)
vfunc[6]:	QSqlCursor::setGenerated(QString const&, bool)
vfunc[7]:	QSqlCursor::setGenerated(int, bool)
vfunc[8]:	QSqlRecord::setNull(int)
vfunc[9]:	QSqlRecord::setNull(QString const&)
vfunc[10]:	QSqlCursor::append(QSqlField const&)
vfunc[11]:	QSqlCursor::insert(int, QSqlField const&)
vfunc[12]:	QSqlCursor::remove(int)
vfunc[13]:	QSqlCursor::clear()
vfunc[14]:	QSqlRecord::clearValues(bool)
vfunc[15]:	QSqlCursor::toString(QString const&, QString const&) const
vfunc[16]:	QSqlRecord::toStringList(QString const&) const
vfunc[17]:	QSqlCursor::primaryIndex(bool) const
vfunc[18]:	QSqlCursor::index(QStringList const&) const
vfunc[19]:	QSqlCursor::setPrimaryIndex(QSqlIndex const&)
vfunc[20]:	QSqlCursor::append(QSqlFieldInfo const&)
vfunc[21]:	QSqlCursor::insert(int, QSqlFieldInfo const&)
vfunc[22]:	QSqlCursor::editBuffer(bool)
vfunc[23]:	QSqlCursor::primeInsert()
vfunc[24]:	QSqlCursor::primeUpdate()

vfunc[25]:	QSqlCursor::primeDelete()
vfunc[26]:	QSqlCursor::insert(bool)
vfunc[27]:	QSqlCursor::update(bool)
vfunc[28]:	QSqlCursor::del(bool)
vfunc[29]:	QSqlCursor::setMode(int)
vfunc[30]:	QSqlCursor::setCalculated(QString const&, bool)
vfunc[31]:	QSqlCursor::setTrimmed(QString const&, bool)
vfunc[32]:	QSqlCursor::select(QString const&, QSqlIndex const&)
vfunc[33]:	QSqlCursor::setSort(QSqlIndex const&)
vfunc[34]:	QSqlCursor::setFilter(QString const&)
vfunc[35]:	QSqlCursor::setName(QString const&, bool)
vfunc[36]:	QSqlCursor::afterSeek()
vfunc[37]:	QSqlCursor::exec(QString const&)
vfunc[38]:	QSqlCursor::calculateField(QString const&)
vfunc[39]:	QSqlCursor::update(QString const&, bool)
vfunc[40]:	QSqlCursor::del(QString const&, bool)
vfunc[41]:	QSqlCursor::toString(QString const&, QSqlField*, QString const&) const
vfunc[42]:	QSqlCursor::toString(QSqlRecord*, QString const&, QString const&, QString const&) const
vfunc[43]:	QSqlCursor::toString(QSqlIndex const&, QSqlRecord*, QString const&, QString const&, QString const&) const

Table 7-666 Secondary vtable for QSqlCursor

Base Offset	-16
Virtual Base Offset	0
RTTI	typeinfo for QSqlCursor
vfunc[0]:	non-virtual thunk to

	QSqlCursor::~~QSqlCursor()
vfunc[1]:	non-virtual thunk to QSqlCursor::~~QSqlCursor()
vfunc[2]:	non-virtual thunk to QSqlCursor::exec(QString const&)
vfunc[3]:	non-virtual thunk to QSqlCursor::value(int) const
vfunc[4]:	QSqlQuery::seek(int, bool)
vfunc[5]:	QSqlQuery::next()
vfunc[6]:	QSqlQuery::prev()
vfunc[7]:	QSqlQuery::first()
vfunc[8]:	QSqlQuery::last()
vfunc[9]:	QSqlQuery::beforeSeek()
vfunc[10]:	non-virtual thunk to QSqlCursor::afterSeek()

The Run Time Type Information for the QSqlCursor class is described by Table 7-667

Table 7-667 typeinfo for QSqlCursor

Base Vtable	vtable for __cxxabiv1::__vmi_class _type_info	2
Name	typeinfo name for QSqlCursor	
flags:	0	
basetype:	typeinfo for QSqlRecord	
basetype:	typeinfo for QSqlQuery	2050

7.2.1.284 Class data for QAction

The virtual table for the QAction class is described by Table 7-668

Table 7-668 Primary vtable for QAction

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QAction
vfunc[0]:	QAction::metaObject() const
vfunc[1]:	QAction::className() const
vfunc[2]:	QAction::qt_cast(char const*)
vfunc[3]:	QAction::qt_invoke(int, QUObject*)

vfunc[4]:	QAction::qt_emit(int, QObject*)
vfunc[5]:	QAction::qt_property(int, int, QVariant*)
vfunc[6]:	QAction::~~QAction()
vfunc[7]:	QAction::~~QAction()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QAction::setIconSet(QIconSet const&)
vfunc[22]:	QAction::setText(QString const&)
vfunc[23]:	QAction::setMenuText(QString const&)
vfunc[24]:	QAction::setToolTip(QString const&)
vfunc[25]:	QAction::setStatusTip(QString const&)
vfunc[26]:	QAction::setWhatsThis(QString const&)
vfunc[27]:	QAction::setAccel(QKeySequence const&)
vfunc[28]:	QAction::setToggleAction(bool)
vfunc[29]:	QAction::addTo(QWidget*)
vfunc[30]:	QAction::removeFrom(QWidget*)

vfunc[31]:	QAction::addedTo(QWidget*, QWidget*)
vfunc[32]:	QAction::addedTo(int, QPopupMenu*)
vfunc[33]:	QAction::setOn(bool)
vfunc[34]:	QAction::setEnabled(bool)

The Run Time Type Information for the QAction class is described by Table 7-669

Table 7-669 typeinfo for QAction

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QAction
basetype:	typeinfo for QObject

7.2.1.285 Class data for QHostAddress

The virtual table for the QHostAddress class is described by Table 7-670

Table 7-670 Primary vtable for QHostAddress

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QHostAddress
vfunc[0]:	QHostAddress::~~QHostAddress()
vfunc[1]:	QHostAddress::~~QHostAddress()

The Run Time Type Information for the QHostAddress class is described by Table 7-671

Table 7-671 typeinfo for QHostAddress

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QHostAddress

7.2.1.286 Class data for QWheelEvent

The virtual table for the QWheelEvent class is described by Table 7-672

Table 7-672 Primary vtable for QWheelEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QWheelEvent
vfunc[0]:	QWheelEvent::~~QWheelEvent()

vfunc[1]:	QWheelEvent::~~QWheelEvent()
-----------	------------------------------

The Run Time Type Information for the QWheelEvent class is described by Table 7-673

Table 7-673 typeinfo for QWheelEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QWheelEvent
basetype:	typeinfo for QEvent

7.2.1.287 Class data for QDataBrowser

The virtual table for the QDataBrowser class is described by Table 7-674

Table 7-674 Primary vtable for QDataBrowser

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QDataBrowser
vfunc[0]:	QDataBrowser::metaObject() const
vfunc[1]:	QDataBrowser::className() const
vfunc[2]:	QDataBrowser::qt_cast(char const*)
vfunc[3]:	QDataBrowser::qt_invoke(int, QObject*)
vfunc[4]:	QDataBrowser::qt_emit(int, QObject*)
vfunc[5]:	QDataBrowser::qt_property(int, int, QVariant*)
vfunc[6]:	QDataBrowser::~~QDataBrowser()
vfunc[7]:	QDataBrowser::~~QDataBrowser()
vfunc[8]:	QWidget::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)

vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()

vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QWidget::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)

vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QWidget::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)

vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QDataBrowser::setSqlCursor(QSqlCursor*, bool)
vfunc[111]:	QDataBrowser::setForm(QSqlForm*)
vfunc[112]:	QDataBrowser::setConfirmEdits(bool)
vfunc[113]:	QDataBrowser::setConfirmInsert(bool)
vfunc[114]:	QDataBrowser::setConfirmUpdate(bool)
vfunc[115]:	QDataBrowser::setConfirmDelete(bool)
vfunc[116]:	QDataBrowser::setConfirmCancels(bool)
vfunc[117]:	QDataBrowser::setReadOnly(bool)
vfunc[118]:	QDataBrowser::setAutoEdit(bool)
vfunc[119]:	QDataBrowser::seek(int, bool)
vfunc[120]:	QDataBrowser::refresh()
vfunc[121]:	QDataBrowser::insert()
vfunc[122]:	QDataBrowser::update()
vfunc[123]:	QDataBrowser::del()
vfunc[124]:	QDataBrowser::first()
vfunc[125]:	QDataBrowser::last()

vfunc[126]:	QDataBrowser::next()
vfunc[127]:	QDataBrowser::prev()
vfunc[128]:	QDataBrowser::readFields()
vfunc[129]:	QDataBrowser::writeFields()
vfunc[130]:	QDataBrowser::clearValues()
vfunc[131]:	QDataBrowser::insertCurrent()
vfunc[132]:	QDataBrowser::updateCurrent()
vfunc[133]:	QDataBrowser::deleteCurrent()
vfunc[134]:	QDataBrowser::currentEdited()
vfunc[135]:	QDataBrowser::confirmEdit(QSql::Op)
vfunc[136]:	QDataBrowser::confirmCancel(QSql::Op)
vfunc[137]:	QDataBrowser::handleError(QSqlError or const&)

Table 7-675 Secondary vtable for QDataBrowser

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QDataBrowser
vfunc[0]:	non-virtual thunk to QDataBrowser::~~QDataBrowser()
vfunc[1]:	non-virtual thunk to QDataBrowser::~~QDataBrowser()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QDataBrowser class is described by Table 7-676

Table 7-676 typeinfo for QDataBrowser

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QDataBrowser
basetype:	typeinfo for QWidget

7.2.1.288 Class data for QTimeEdit

The virtual table for the QTimeEdit class is described by Table 7-677

Table 7-677 Primary vtable for QTimeEdit

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTimeEdit
vfunc[0]:	QTimeEdit::metaObject() const
vfunc[1]:	QTimeEdit::className() const
vfunc[2]:	QTimeEdit::qt_cast(char const*)
vfunc[3]:	QTimeEdit::qt_invoke(int, QUObject*)
vfunc[4]:	QTimeEdit::qt_emit(int, QUObject*)
vfunc[5]:	QTimeEdit::qt_property(int, int, QVariant*)
vfunc[6]:	QTimeEdit::~~QTimeEdit()
vfunc[7]:	QTimeEdit::~~QTimeEdit()
vfunc[8]:	QTimeEdit::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QTimeEdit::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)

vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QWidget::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::F

	ocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QTimeEdit::sizeHint() const
vfunc[59]:	QTimeEdit::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)

vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QWidget::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QTimeEdit::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QWidget::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette)

	const&)
vfunc[100]:	QWidget::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QTimeEdit::setFocusSection(int)
vfunc[111]:	QTimeEdit::sectionFormattedText(int)
vfunc[112]:	QTimeEdit::addNumber(int, int)
vfunc[113]:	QTimeEdit::removeLastNumber(int)
vfunc[114]:	QTimeEdit::stepUp()
vfunc[115]:	QTimeEdit::stepDown()
vfunc[116]:	QTimeEdit::setTime(QTime const&)
vfunc[117]:	QTimeEdit::setAutoAdvance(bool)
vfunc[118]:	QTimeEdit::setMinValue(QTime const&)
vfunc[119]:	QTimeEdit::setMaxValue(QTime const&)
vfunc[120]:	QTimeEdit::setRange(QTime const&, QTime const&)
vfunc[121]:	QTimeEdit::setSeparator(QString const&)
vfunc[122]:	QTimeEdit::outOfRange(int, int, int) const
vfunc[123]:	QTimeEdit::setHour(int)
vfunc[124]:	QTimeEdit::setMinute(int)
vfunc[125]:	QTimeEdit::setSecond(int)

Table 7-678 Secondary vtable for QTimeEdit

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QTimeEdit
vfunc[0]:	non-virtual thunk to QTimeEdit::~~QTimeEdit()
vfunc[1]:	non-virtual thunk to QTimeEdit::~~QTimeEdit()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QTimeEdit class is described by Table 7-679

Table 7-679 typeinfo for QTimeEdit

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTimeEdit
basetype:	typeinfo for QDateTimeEditBase

7.2.1.289 Class data for QIconDragItem

The virtual table for the QIconDragItem class is described by Table 7-680

Table 7-680 Primary vtable for QIconDragItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QIconDragItem
vfunc[0]:	QIconDragItem::~~QIconDragItem()

vfunc[1]:	QIconDragItem::~~QIconDragItem()
vfunc[2]:	QIconDragItem::data() const
vfunc[3]:	QIconDragItem::setData(QMemArray<char> const&)

The Run Time Type Information for the QIconDragItem class is described by Table 7-681

Table 7-681 typeinfo for QIconDragItem

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QIconDragItem

7.2.1.290 Class data for QSqlFieldInfo

The virtual table for the QSqlFieldInfo class is described by Table 7-682

Table 7-682 Primary vtable for QSqlFieldInfo

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlFieldInfo
vfunc[0]:	QSqlFieldInfo::~~QSqlFieldInfo()
vfunc[1]:	QSqlFieldInfo::~~QSqlFieldInfo()
vfunc[2]:	QSqlFieldInfo::setTrim(bool)
vfunc[3]:	QSqlFieldInfo::setGenerated(bool)
vfunc[4]:	QSqlFieldInfo::setCalculated(bool)

The Run Time Type Information for the QSqlFieldInfo class is described by Table 7-683

Table 7-683 typeinfo for QSqlFieldInfo

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QSqlFieldInfo

7.2.1.291 Class data for QFtp

The virtual table for the QFtp class is described by Table 7-684

Table 7-684 Primary vtable for QFtp

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFtp
vfunc[0]:	QFtp::metaObject() const

vfunc[1]:	QFtp::className() const
vfunc[2]:	QFtp::qt_cast(char const*)
vfunc[3]:	QFtp::qt_invoke(int, QUObject*)
vfunc[4]:	QFtp::qt_emit(int, QUObject*)
vfunc[5]:	QFtp::qt_property(int, int, QVariant*)
vfunc[6]:	QFtp::~QFtp()
vfunc[7]:	QFtp::~~QFtp()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QNetworkProtocol::setUrl(QUrlOperator*)
vfunc[22]:	QNetworkProtocol::setAutoDelete(bool, int)
vfunc[23]:	QFtp::supportedOperations() const
vfunc[24]:	QNetworkProtocol::addOperation(QNetworkOperation*)
vfunc[25]:	QNetworkProtocol::clearOperationQueue()
vfunc[26]:	QNetworkProtocol::stop()
vfunc[27]:	QNetworkProtocol::processOperation(QNetworkOperation*)
vfunc[28]:	QFtp::operationListChildren(QNetw

	orkOperation*)
vfunc[29]:	QFtp::operationMkDir(QNetworkOperation*)
vfunc[30]:	QFtp::operationRemove(QNetworkOperation*)
vfunc[31]:	QFtp::operationRename(QNetworkOperation*)
vfunc[32]:	QFtp::operationGet(QNetworkOperation*)
vfunc[33]:	QFtp::operationPut(QNetworkOperation*)
vfunc[34]:	QNetworkProtocol::operationPutChunk(QNetworkOperation*)
vfunc[35]:	QFtp::checkConnection(QNetworkOperation*)

The Run Time Type Information for the QFtp class is described by Table 7-685

Table 7-685 typeinfo for QFtp

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFtp
basetype:	typeinfo for QNetworkProtocol

7.2.1.292 Class data for QLayoutItem

The virtual table for the QLayoutItem class is described by Table 7-686

Table 7-686 Primary vtable for QLayoutItem

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QLayoutItem
vfunc[0]:	QLayoutItem::~~QLayoutItem()
vfunc[1]:	QLayoutItem::~~QLayoutItem()
vfunc[2]:	__cxa_pure_virtual
vfunc[3]:	__cxa_pure_virtual
vfunc[4]:	__cxa_pure_virtual
vfunc[5]:	__cxa_pure_virtual
vfunc[6]:	__cxa_pure_virtual
vfunc[7]:	__cxa_pure_virtual
vfunc[8]:	__cxa_pure_virtual

vfunc[9]:	QLayoutItem::hasHeightForWidth() const
vfunc[10]:	QLayoutItem::heightForWidth(int) const
vfunc[11]:	QLayoutItem::invalidate()
vfunc[12]:	QLayoutItem::widget()
vfunc[13]:	QLayoutItem::iterator()
vfunc[14]:	QLayoutItem::layout()
vfunc[15]:	QLayoutItem::spacerItem()
vfunc[16]:	QLayoutItem::setAlignment(int)

The Run Time Type Information for the QLayoutItem class is described by Table 7-687

Table 7-687 typeinfo for QLayoutItem

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QLayoutItem

7.2.1.293 Class data for QMoveEvent

The virtual table for the QMoveEvent class is described by Table 7-688

Table 7-688 Primary vtable for QMoveEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QMoveEvent
vfunc[0]:	QMoveEvent::~~QMoveEvent()
vfunc[1]:	QMoveEvent::~~QMoveEvent()

The Run Time Type Information for the QMoveEvent class is described by Table 7-689

Table 7-689 typeinfo for QMoveEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QMoveEvent
basetype:	typeinfo for QEvent

7.2.1.294 Class data for QTextEdit

The virtual table for the QTextEdit class is described by Table 7-690

Table 7-690 Primary vtable for QTextEdit

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QTextEdit
vfunc[0]:	QTextEdit::metaObject() const
vfunc[1]:	QTextEdit::className() const
vfunc[2]:	QTextEdit::qt_cast(char const*)
vfunc[3]:	QTextEdit::qt_invoke(int, QUObject*)
vfunc[4]:	QTextEdit::qt_emit(int, QUObject*)
vfunc[5]:	QTextEdit::qt_property(int, int, QVariant*)
vfunc[6]:	QTextEdit::~~QTextEdit()
vfunc[7]:	QTextEdit::~~QTextEdit()
vfunc[8]:	QTextEdit::event(QEvent*)
vfunc[9]:	QTextEdit::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QScrollView::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QTextEdit::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)

vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QTextEdit::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QTextEdit::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QScrollView::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QTextEdit::polish()

vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QScrollView::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)
vfunc[58]:	QTextEdit::sizeHint() const
vfunc[59]:	QScrollView::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QTextEdit::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QScrollView::mousePressEvent(QMouseEvent*)
vfunc[70]:	QScrollView::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QScrollView::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QScrollView::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QScrollView::wheelEvent(QWheelEvent*)
vfunc[74]:	QTextEdit::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QWidget::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)

vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QFrame::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QTextEdit::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)
vfunc[84]:	QScrollView::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QTextEdit::imStartEvent(QIMEvent*)
vfunc[86]:	QTextEdit::imComposeEvent(QIMEvent*)
vfunc[87]:	QTextEdit::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QScrollView::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QScrollView::fontChange(QFont const&)
vfunc[101]:	QTextEdit::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)

vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QTextEdit::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)
vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QTextEdit::drawContents(QPainter*)
vfunc[117]:	QScrollView::frameChanged()
vfunc[118]:	QScrollView::setResizePolicy(QScrollView::ResizePolicy)
vfunc[119]:	QScrollView::addChild(QWidget*, int, int)
vfunc[120]:	QScrollView::moveChild(QWidget*, int, int)
vfunc[121]:	QScrollView::setVScrollBarMode(QScrollView::ScrollBarMode)
vfunc[122]:	QScrollView::setHScrollBarMode(QScrollView::ScrollBarMode)
vfunc[123]:	QScrollView::setCornerWidget(QWidget*)
vfunc[124]:	QScrollView::setDragAutoScroll(bool)
vfunc[125]:	QScrollView::resizeContents(int, int)
vfunc[126]:	QScrollView::setContentsPos(int, int)
vfunc[127]:	QTextEdit::drawContents(QPainter*, int, int, int, int)
vfunc[128]:	QScrollView::drawContentsOffset(QPainter*, int, int, int, int, int, int)
vfunc[129]:	QTextEdit::contentsMouseEvent(QMouseEvent*)
vfunc[130]:	QTextEdit::contentsMouseReleaseEv

	ent(QMouseEvent*)
vfunc[131]:	QTextEdit::contentsMouseEvent(QMouseEvent*)
vfunc[132]:	QTextEdit::contentsMouseMoveEvent(QMouseEvent*)
vfunc[133]:	QTextEdit::contentsDragEnterEvent(QDragEnterEvent*)
vfunc[134]:	QTextEdit::contentsDragMoveEvent(QDragMoveEvent*)
vfunc[135]:	QTextEdit::contentsDragLeaveEvent(QDragLeaveEvent*)
vfunc[136]:	QTextEdit::contentsDropEvent(QDropEvent*)
vfunc[137]:	QTextEdit::contentsWheelEvent(QWheelEvent*)
vfunc[138]:	QTextEdit::contentsContextMenuEvent(QContextMenuEvent*)
vfunc[139]:	QScrollView::viewportPaintEvent(QPaintEvent*)
vfunc[140]:	QTextEdit::viewportResizeEvent(QResizeEvent*)
vfunc[141]:	QScrollView::viewportMousePressEvent(QMouseEvent*)
vfunc[142]:	QScrollView::viewportMouseReleaseEvent(QMouseEvent*)
vfunc[143]:	QScrollView::viewportMouseDoubleClickEvent(QMouseEvent*)
vfunc[144]:	QScrollView::viewportMouseMoveEvent(QMouseEvent*)
vfunc[145]:	QScrollView::viewportDragEnterEvent(QDragEnterEvent*)
vfunc[146]:	QScrollView::viewportDragMoveEvent(QDragMoveEvent*)
vfunc[147]:	QScrollView::viewportDragLeaveEvent(QDragLeaveEvent*)
vfunc[148]:	QScrollView::viewportDropEvent(QDropEvent*)
vfunc[149]:	QScrollView::viewportWheelEvent(QWheelEvent*)
vfunc[150]:	QScrollView::viewportContextMenuEvent(QContextMenuEvent*)
vfunc[151]:	QScrollView::setMargins(int, int, int,

	int)
vfunc[152]:	QScrollView::setHBarGeometry(QScrollBar&, int, int, int, int)
vfunc[153]:	QScrollView::setVBarGeometry(QScrollBar&, int, int, int, int)
vfunc[154]:	QTextEdit::find(QString const&, bool, bool, bool, int*, int*)
vfunc[155]:	QTextEdit::getFormat(int, int, QFont*, QColor*, QTextEdit::VerticalAlignment*)
vfunc[156]:	QTextEdit::getParagraphFormat(int, QFont*, QColor*, QTextEdit::VerticalAlignment*, int*, QStyleSheetItem::DisplayMode*, QStyleSheetItem::ListStyle*, int*)
vfunc[157]:	QTextEdit::setMimeSourceFactory(QMimeSourceFactory*)
vfunc[158]:	QTextEdit::setStyleSheet(QStyleSheet*)
vfunc[159]:	QTextEdit::scrollToAnchor(QString const&)
vfunc[160]:	QTextEdit::setPaper(QBrush const&)
vfunc[161]:	QTextEdit::setLinkUnderline(bool)
vfunc[162]:	QTextEdit::setWordWrap(QTextEdit::WordWrap)
vfunc[163]:	QTextEdit::setWrapColumnOrWidth(int)
vfunc[164]:	QTextEdit::setWrapPolicy(QTextEdit::WrapPolicy)
vfunc[165]:	QTextEdit::copy()
vfunc[166]:	QTextEdit::append(QString const&)
vfunc[167]:	QTextEdit::setText(QString const&, QString const&)
vfunc[168]:	QTextEdit::setTextFormat(Qt::TextFormat)
vfunc[169]:	QTextEdit::selectAll(bool)
vfunc[170]:	QTextEdit::setTabStopWidth(int)
vfunc[171]:	QTextEdit::zoomIn(int)
vfunc[172]:	QTextEdit::zoomIn()
vfunc[173]:	QTextEdit::zoomOut(int)
vfunc[174]:	QTextEdit::zoomOut()

vfunc[175]:	QTextEdit::zoomTo(int)
vfunc[176]:	QTextEdit::sync()
vfunc[177]:	QTextEdit::setReadOnly(bool)
vfunc[178]:	QTextEdit::undo()
vfunc[179]:	QTextEdit::redo()
vfunc[180]:	QTextEdit::cut()
vfunc[181]:	QTextEdit::paste()
vfunc[182]:	QTextEdit::pasteSubType(QCString const&)
vfunc[183]:	QTextEdit::clear()
vfunc[184]:	QTextEdit::del()
vfunc[185]:	QTextEdit::indent()
vfunc[186]:	QTextEdit::setItalic(bool)
vfunc[187]:	QTextEdit::setBold(bool)
vfunc[188]:	QTextEdit::setUnderline(bool)
vfunc[189]:	QTextEdit::setFamily(QString const&)
vfunc[190]:	QTextEdit::setPointSize(int)
vfunc[191]:	QTextEdit::setColor(QColor const&)
vfunc[192]:	QTextEdit::setVerticalAlignment(QT extEdit::VerticalAlignment)
vfunc[193]:	QTextEdit::setAlignment(int)
vfunc[194]:	QTextEdit::setParagType(QStyleShee tItem::DisplayMode, QStyleSheetItem::ListStyle)
vfunc[195]:	QTextEdit::setCursorPosition(int, int)
vfunc[196]:	QTextEdit::setSelection(int, int, int, int, int)
vfunc[197]:	QTextEdit::setSelectionAttributes(int, QColor const&, bool)
vfunc[198]:	QTextEdit::setModified(bool)
vfunc[199]:	QTextEdit::resetFormat()
vfunc[200]:	QTextEdit::setUndoDepth(int)
vfunc[201]:	QTextEdit::setFormat(QTextFormat*, int)
vfunc[202]:	QTextEdit::ensureCursorVisible()
vfunc[203]:	QTextEdit::placeCursor(QPoint const&, QTextCursor*)

vfunc[204]:	QTextEdit::moveCursor(QTextEdit::CursorAction, bool)
vfunc[205]:	QTextEdit::doKeyboardAction(QTextEdit::KeyboardAction)
vfunc[206]:	QTextEdit::removeSelectedText(int)
vfunc[207]:	QTextEdit::removeSelection(int)
vfunc[208]:	QTextEdit::setCurrentFont(QFont const&)
vfunc[209]:	QTextEdit::setOverwriteMode(bool)
vfunc[210]:	QTextEdit::scrollToBottom()
vfunc[211]:	QTextEdit::insert(QString const&, bool, bool, bool)
vfunc[212]:	QTextEdit::insertAt(QString const&, int, int)
vfunc[213]:	QTextEdit::removeParagraph(int)
vfunc[214]:	QTextEdit::insertParagraph(QString const&, int)
vfunc[215]:	QTextEdit::setParagraphBackgroundColor(int, QColor const&)
vfunc[216]:	QTextEdit::clearParagraphBackground(int)
vfunc[217]:	QTextEdit::setUndoRedoEnabled(bool)
vfunc[218]:	QTextEdit::createPopupMenu(QPoint const&)
vfunc[219]:	QTextEdit::createPopupMenu()
vfunc[220]:	QTextEdit::doChangeInterval()
vfunc[221]:	QTextEdit::linksEnabled() const
vfunc[222]:	QTextEdit::emitHighlighted(QString const&)
vfunc[223]:	QTextEdit::emitLinkClicked(QString const&)

Table 7-691 Secondary vtable for QTextEdit

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QTextEdit
vfunc[0]:	non-virtual thunk to QTextEdit::~~QTextEdit()
vfunc[1]:	non-virtual thunk to

	QTextEdit::~~QTextEdit()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDe viceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPaintDeviceCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QTextEdit class is described by Table 7-692

Table 7-692 typeinfo for QTextEdit

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QTextEdit
basetype:	typeinfo for QScrollView

7.2.1.295 Class data for QFileIconProvider

The virtual table for the QFileIconProvider class is described by Table 7-693

Table 7-693 Primary vtable for QFileIconProvider

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QFileIconProvider
vfunc[0]:	QFileIconProvider::metaObject() const
vfunc[1]:	QFileIconProvider::className() const
vfunc[2]:	QFileIconProvider::qt_cast(char const*)
vfunc[3]:	QFileIconProvider::qt_invoke(int, QUObject*)
vfunc[4]:	QFileIconProvider::qt_emit(int,

	QObject*)
vfunc[5]:	QFileIconProvider::qt_property(int, int, QVariant*)
vfunc[6]:	QFileIconProvider::~~QFileIconProvider()
vfunc[7]:	QFileIconProvider::~~QFileIconProvider()
vfunc[8]:	QObject::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QObject::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QObject::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QFileIconProvider::pixmap(QFileInfo const&)

The Run Time Type Information for the QFileIconProvider class is described by Table 7-694

Table 7-694 typeinfo for QFileIconProvider

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QFileIconProvider
basetype:	typeinfo for QObject

7.2.1.296 Class data for QSqlIndex

The virtual table for the QSqlIndex class is described by Table 7-695

Table 7-695 Primary vtable for QSqlIndex

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlIndex
vfunc[0]:	QSqlIndex::~~QSqlIndex()
vfunc[1]:	QSqlIndex::~~QSqlIndex()
vfunc[2]:	QSqlRecord::value(int) const
vfunc[3]:	QSqlRecord::value(QString const&) const
vfunc[4]:	QSqlRecord::setValue(int, QVariant const&)
vfunc[5]:	QSqlRecord::setValue(QString const&, QVariant const&)
vfunc[6]:	QSqlRecord::setGenerated(QString const&, bool)
vfunc[7]:	QSqlRecord::setGenerated(int, bool)
vfunc[8]:	QSqlRecord::setNull(int)
vfunc[9]:	QSqlRecord::setNull(QString const&)
vfunc[10]:	QSqlIndex::append(QSqlField const&)
vfunc[11]:	QSqlRecord::insert(int, QSqlField const&)
vfunc[12]:	QSqlRecord::remove(int)
vfunc[13]:	QSqlRecord::clear()
vfunc[14]:	QSqlRecord::clearValues(bool)
vfunc[15]:	QSqlRecord::toString(QString const&, QString const&) const
vfunc[16]:	QSqlRecord::toStringList(QString const&) const
vfunc[17]:	QSqlIndex::setCursorName(QString const&)
vfunc[18]:	QSqlIndex::setName(QString const&)
vfunc[19]:	QSqlIndex::append(QSqlField const&, bool)
vfunc[20]:	QSqlIndex::setDescending(int, bool)

The Run Time Type Information for the QSqlIndex class is described by Table 7-696

Table 7-696 typeinfo for QSqlIndex

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QSqlIndex
basetype:	typeinfo for QSqlRecord

7.2.1.297 Class data for QSqlField

The virtual table for the QSqlField class is described by Table 7-697

Table 7-697 Primary vtable for QSqlField

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QSqlField
vfunc[0]:	QSqlField::~~QSqlField()
vfunc[1]:	QSqlField::~~QSqlField()
vfunc[2]:	QSqlField::setValue(QVariant const&)
vfunc[3]:	QSqlField::value() const
vfunc[4]:	QSqlField::setName(QString const&)
vfunc[5]:	QSqlField::setNull()
vfunc[6]:	QSqlField::setReadOnly(bool)

The Run Time Type Information for the QSqlField class is described by Table 7-698

Table 7-698 typeinfo for QSqlField

Base Vtable	vtable for __cxxabiv1::__class_type_info
Name	typeinfo name for QSqlField

7.2.1.298 Class data for QVGroupBox

The virtual table for the QVGroupBox class is described by Table 7-699

Table 7-699 Primary vtable for QVGroupBox

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QVGroupBox
vfunc[0]:	QVGroupBox::metaObject() const
vfunc[1]:	QVGroupBox::className() const
vfunc[2]:	QVGroupBox::qt_cast(char const*)

vfunc[3]:	QVGroupBox::qt_invoke(int, QUObject*)
vfunc[4]:	QVGroupBox::qt_emit(int, QUObject*)
vfunc[5]:	QVGroupBox::qt_property(int, int, QVariant*)
vfunc[6]:	QVGroupBox::~~QVGroupBox()
vfunc[7]:	QVGroupBox::~~QVGroupBox()
vfunc[8]:	QGroupBox::event(QEvent*)
vfunc[9]:	QObject::eventFilter(QObject*, QEvent*)
vfunc[10]:	QWidget::setName(char const*)
vfunc[11]:	QObject::insertChild(QObject*)
vfunc[12]:	QObject::removeChild(QObject*)
vfunc[13]:	QObject::setProperty(char const*, QVariant const&)
vfunc[14]:	QObject::property(char const*) const
vfunc[15]:	QObject::timerEvent(QTimerEvent*)
vfunc[16]:	QGroupBox::childEvent(QChildEvent*)
vfunc[17]:	QObject::customEvent(QCustomEvent*)
vfunc[18]:	QObject::connectNotify(char const*)
vfunc[19]:	QObject::disconnectNotify(char const*)
vfunc[20]:	QObject::checkConnectArgs(char const*, QObject const*, char const*)
vfunc[21]:	QGroupBox::setEnabled(bool)
vfunc[22]:	QWidget::setMinimumSize(int, int)
vfunc[23]:	QWidget::setMaximumSize(int, int)
vfunc[24]:	QWidget::setSizeIncrement(int, int)
vfunc[25]:	QWidget::setBackgroundMode(Qt::BackgroundMode)
vfunc[26]:	QWidget::setEraseColor(QColor const&)
vfunc[27]:	QWidget::setErasePixmap(QPixmap const&)
vfunc[28]:	QWidget::setPalette(QPalette const&)
vfunc[29]:	QWidget::setPaletteBackgroundColor

	r(QColor const&)
vfunc[30]:	QWidget::setPaletteBackgroundPixmap(QPixmap const&)
vfunc[31]:	QWidget::setFont(QFont const&)
vfunc[32]:	QWidget::setCursor(QCursor const&)
vfunc[33]:	QWidget::unsetCursor()
vfunc[34]:	QWidget::setMask(QBitmap const&)
vfunc[35]:	QWidget::setMask(QRegion const&)
vfunc[36]:	QWidget::setBackgroundColor(QColor const&)
vfunc[37]:	QWidget::setBackgroundPixmap(QPixmap const&)
vfunc[38]:	QWidget::setCaption(QString const&)
vfunc[39]:	QWidget::setIcon(QPixmap const&)
vfunc[40]:	QWidget::setIconText(QString const&)
vfunc[41]:	QWidget::setMouseTracking(bool)
vfunc[42]:	QWidget::setFocus()
vfunc[43]:	QWidget::setActiveWindow()
vfunc[44]:	QWidget::setFocusPolicy(QWidget::FocusPolicy)
vfunc[45]:	QWidget::setFocusProxy(QWidget*)
vfunc[46]:	QWidget::setUpdatesEnabled(bool)
vfunc[47]:	QWidget::show()
vfunc[48]:	QWidget::hide()
vfunc[49]:	QWidget::showMinimized()
vfunc[50]:	QWidget::showMaximized()
vfunc[51]:	QWidget::showNormal()
vfunc[52]:	QWidget::polish()
vfunc[53]:	QWidget::move(int, int)
vfunc[54]:	QWidget::resize(int, int)
vfunc[55]:	QWidget::setGeometry(int, int, int, int)
vfunc[56]:	QWidget::setGeometry(QRect const&)
vfunc[57]:	QWidget::close(bool)

vfunc[58]:	QGroupBox::sizeHint() const
vfunc[59]:	QWidget::minimumSizeHint() const
vfunc[60]:	QWidget::sizePolicy() const
vfunc[61]:	QWidget::setSizePolicy(QSizePolicy)
vfunc[62]:	QWidget::heightForWidth(int) const
vfunc[63]:	QWidget::adjustSize()
vfunc[64]:	QWidget::reparent(QWidget*, unsigned int, QPoint const&, bool)
vfunc[65]:	QWidget::setAcceptDrops(bool)
vfunc[66]:	QWidget::setAutoMask(bool)
vfunc[67]:	QWidget::setBackgroundOrigin(QWidget::BackgroundOrigin)
vfunc[68]:	QWidget::customWhatsThis() const
vfunc[69]:	QWidget::mousePressEvent(QMouseEvent*)
vfunc[70]:	QWidget::mouseReleaseEvent(QMouseEvent*)
vfunc[71]:	QWidget::mouseDoubleClickEvent(QMouseEvent*)
vfunc[72]:	QWidget::mouseMoveEvent(QMouseEvent*)
vfunc[73]:	QWidget::wheelEvent(QWheelEvent*)
vfunc[74]:	QWidget::keyPressEvent(QKeyEvent*)
vfunc[75]:	QWidget::keyReleaseEvent(QKeyEvent*)
vfunc[76]:	QGroupBox::focusInEvent(QFocusEvent*)
vfunc[77]:	QWidget::focusOutEvent(QFocusEvent*)
vfunc[78]:	QWidget::enterEvent(QEvent*)
vfunc[79]:	QWidget::leaveEvent(QEvent*)
vfunc[80]:	QGroupBox::paintEvent(QPaintEvent*)
vfunc[81]:	QWidget::moveEvent(QMoveEvent*)
vfunc[82]:	QGroupBox::resizeEvent(QResizeEvent*)
vfunc[83]:	QWidget::closeEvent(QCloseEvent*)

vfunc[84]:	QWidget::contextMenuEvent(QContextMenuEvent*)
vfunc[85]:	QWidget::imStartEvent(QIMEvent*)
vfunc[86]:	QWidget::imComposeEvent(QIMEvent*)
vfunc[87]:	QWidget::imEndEvent(QIMEvent*)
vfunc[88]:	QWidget::tabletEvent(QTabletEvent*)
vfunc[89]:	QWidget::dragEnterEvent(QDragEnterEvent*)
vfunc[90]:	QWidget::dragMoveEvent(QDragMoveEvent*)
vfunc[91]:	QWidget::dragLeaveEvent(QDragLeaveEvent*)
vfunc[92]:	QWidget::dropEvent(QDropEvent*)
vfunc[93]:	QWidget::showEvent(QShowEvent*)
vfunc[94]:	QWidget::hideEvent(QHideEvent*)
vfunc[95]:	QWidget::x11Event(_XEvent*)
vfunc[96]:	QWidget::updateMask()
vfunc[97]:	QFrame::styleChange(QStyle&)
vfunc[98]:	QWidget::enabledChange(bool)
vfunc[99]:	QWidget::paletteChange(QPalette const&)
vfunc[100]:	QGroupBox::fontChange(QFont const&)
vfunc[101]:	QWidget::windowActivationChange(bool)
vfunc[102]:	QWidget::metric(int) const
vfunc[103]:	QWidget::create(unsigned long, bool, bool)
vfunc[104]:	QWidget::destroy(bool, bool)
vfunc[105]:	QWidget::setWState(unsigned int)
vfunc[106]:	QWidget::setWFlags(unsigned int)
vfunc[107]:	QWidget::focusNextPrevChild(bool)
vfunc[108]:	QWidget::setKeyCompression(bool)
vfunc[109]:	QWidget::setMicroFocusHint(int, int, int, int, bool, QFont*)
vfunc[110]:	QFrame::setFrameStyle(int)

vfunc[111]:	QFrame::setLineWidth(int)
vfunc[112]:	QFrame::setMargin(int)
vfunc[113]:	QFrame::setMidLineWidth(int)
vfunc[114]:	QFrame::setFrameRect(QRect const&)
vfunc[115]:	QFrame::drawFrame(QPainter*)
vfunc[116]:	QFrame::drawContents(QPainter*)
vfunc[117]:	QFrame::frameChanged()
vfunc[118]:	QGroupBox::setColumnLayout(int, Qt::Orientation)
vfunc[119]:	QGroupBox::setTitle(QString const&)
vfunc[120]:	QGroupBox::setAlignment(int)

Table 7-700 Secondary vtable for QVGroupBox

Base Offset	-80
Virtual Base Offset	0
RTTI	typeinfo for QVGroupBox
vfunc[0]:	non-virtual thunk to QVGroupBox::~~QVGroupBox()
vfunc[1]:	non-virtual thunk to QVGroupBox::~~QVGroupBox()
vfunc[2]:	QPaintDevice::setResolution(int)
vfunc[3]:	QPaintDevice::resolution() const
vfunc[4]:	QPaintDevice::handle() const
vfunc[5]:	QPaintDevice::x11RenderHandle() const
vfunc[6]:	QPaintDevice::setX11Data(QPaintDeviceX11Data const*)
vfunc[7]:	QPaintDevice::cmd(int, QPainter*, QPDevCmdParam*)
vfunc[8]:	non-virtual thunk to QWidget::metric(int) const
vfunc[9]:	QPaintDevice::fontMet(QFont*, int, char const*, int) const
vfunc[10]:	QPaintDevice::fontInf(QFont*, int) const

The Run Time Type Information for the QVGroupBox class is described by Table 7-701

Table 7-701 typeinfo for QVGroupBox

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QVGroupBox
basetype:	typeinfo for QGroupBox

7.2.1.299 Class data for QCloseEvent

The virtual table for the QCloseEvent class is described by Table 7-702

Table 7-702 Primary vtable for QCloseEvent

Base Offset	0
Virtual Base Offset	0
RTTI	typeinfo for QCloseEvent
vfunc[0]:	QCloseEvent::~~QCloseEvent()
vfunc[1]:	QCloseEvent::~~QCloseEvent()

The Run Time Type Information for the QCloseEvent class is described by Table 7-703

Table 7-703 typeinfo for QCloseEvent

Base Vtable	vtable for __cxxabiv1::__si_class_type_info
Name	typeinfo name for QCloseEvent
basetype:	typeinfo for QEvent

7.2.1.300 Interfaces for Qt

An LSB conforming implementation shall provide the architecture specific functions for Qt specified in Table 7-704, with the full mandatory functionality as described in the referenced underlying specification.

Table 7-704 libqt-mt - Qt Function Interfaces

_ZThn16_N10QSqlCursor4execERK7QString [qt-mt]	_ZThn16_N10QSqlCursor9afterSeekEv [qt-mt]
_ZThn16_N10QSqlCursorD0Ev [qt-mt]	_ZThn16_N10QSqlCursorD1Ev [qt-mt]
_ZThn16_N16QSqlSelectCursor4execERK7QString [qt-mt]	_ZThn16_N16QSqlSelectCursorD0Ev [qt-mt]
_ZThn16_N16QSqlSelectCursorD1Ev [qt-mt]	_ZThn16_N18QXmlDefaultHandler11errorStringEv [qt-mt]
_ZThn16_N18QXmlDefaultHandler12notationDeclERK7QStringS2_S2_ [qt-mt]	_ZThn16_N18QXmlDefaultHandler18unparsedEntityDeclERK7QStringS2_S2_S2_ [qt-mt]
_ZThn16_NK10QDropEvent11encod	_ZThn16_NK10QDropEvent6format

edDataEPKc [qt-mt]	Ei [qt-mt]
_ZThn16_NK10QDropEvent8provide sEPKc [qt-mt]	_ZThn16_NK10QSqlCursor5valueEi [qt-mt]
_ZThn200_N10QScrollBar10stepCha ngeEv [qt-mt]	_ZThn200_N10QScrollBar11rangeCh angeEv [qt-mt]
_ZThn200_N10QScrollBar11valueCh angeEv [qt-mt]	_ZThn200_N10QScrollBarD0Ev [qt- mt]
_ZThn200_N10QScrollBarD1Ev [qt- mt]	_ZThn200_N5QDial11rangeChangeE v [qt-mt]
_ZThn200_N5QDial11valueChangeE v [qt-mt]	_ZThn200_N5QDialD0Ev [qt-mt]
_ZThn200_N5QDialD1Ev [qt-mt]	_ZThn200_N7QSlider11rangeChange Ev [qt-mt]
_ZThn200_N7QSlider11valueChange Ev [qt-mt]	_ZThn200_N7QSliderD0Ev [qt-mt]
_ZThn200_N7QSliderD1Ev [qt-mt]	_ZThn200_N8QSpinBox11rangeChan geEv [qt-mt]
_ZThn200_N8QSpinBox11valueChan geEv [qt-mt]	_ZThn200_N8QSpinBoxD0Ev [qt-mt]
_ZThn200_N8QSpinBoxD1Ev [qt-mt]	_ZThn240_N10QPopupMenu10upda teItemEi [qt-mt]
_ZThn240_N10QPopupMenu12men uDelPopupEPS_ [qt-mt]	_ZThn240_N10QPopupMenu12men uInsPopupEPS_ [qt-mt]
_ZThn240_N10QPopupMenu14activ ateItemAtEi [qt-mt]	_ZThn240_N10QPopupMenu16men uStateChangedEv [qt-mt]
_ZThn240_N10QPopupMenu19men uContentsChangedEv [qt-mt]	_ZThn240_N10QPopupMenuD0Ev [qt-mt]
_ZThn240_N10QPopupMenuD1Ev [qt-mt]	_ZThn240_N8QMenuBar10updateIte mEi [qt-mt]
_ZThn240_N8QMenuBar12menuDel PopupEP10QPopupMenu [qt-mt]	_ZThn240_N8QMenuBar12menuIns PopupEP10QPopupMenu [qt-mt]
_ZThn240_N8QMenuBar14activateIt emAtEi [qt-mt]	_ZThn240_N8QMenuBar16menuStat eChangedEv [qt-mt]
_ZThn240_N8QMenuBar19menuCon tentsChangedEv [qt-mt]	_ZThn240_N8QMenuBarD0Ev [qt- mt]
_ZThn240_N8QMenuBarD1Ev [qt- mt]	_ZThn24_N18QXmlDefaultHandler1 1errorStringEv [qt-mt]
_ZThn24_N18QXmlDefaultHandler1 3resolveEntityERK7QStringS2_RP15 QXmlInputSource [qt-mt]	_ZThn32_N18QXmlDefaultHandler1 0startCDATAEv [qt-mt]
_ZThn32_N18QXmlDefaultHandler1 1errorStringEv [qt-mt]	_ZThn32_N18QXmlDefaultHandler1 1startEntityERK7QString [qt-mt]

_ZThn32_N18QXmlDefaultHandler6 endDTDEv [qt-mt]	_ZThn32_N18QXmlDefaultHandler7 commentERK7QString [qt-mt]
_ZThn32_N18QXmlDefaultHandler8 endCDATAEv [qt-mt]	_ZThn32_N18QXmlDefaultHandler8 startDTERK7QStringS2_S2_ [qt-mt]
_ZThn32_N18QXmlDefaultHandler9 endEntityERK7QString [qt-mt]	_ZThn40_N18QXmlDefaultHandler1 1errorStringEv [qt-mt]
_ZThn40_N18QXmlDefaultHandler1 3attributeDeclERK7QStringS2_S2_S2_ [qt-mt]	_ZThn40_N18QXmlDefaultHandler1 8externalEntityDeclERK7QStringS2_S2_ [qt-mt]
_ZThn40_N18QXmlDefaultHandler1 8internalEntityDeclERK7QStringS2_ [qt-mt]	_ZThn80_N10QBoxLayout10invalida teEv [qt-mt]
_ZThn80_N10QBoxLayout11setGeo metryERK5QRect [qt-mt]	_ZThn80_N10QBoxLayout8iteratorE v [qt-mt]
_ZThn80_N10QBoxLayoutD0Ev [qt- mt]	_ZThn80_N10QBoxLayoutD1Ev [qt- mt]
_ZThn80_N10QDataTableD0Ev [qt- mt]	_ZThn80_N10QDataTableD1Ev [qt- mt]
_ZThn80_N10QHGroupBoxD0Ev [qt- mt]	_ZThn80_N10QHGroupBoxD1Ev [qt- mt]
_ZThn80_N10QImageDragD0Ev [qt- mt]	_ZThn80_N10QImageDragD1Ev [qt- mt]
_ZThn80_N10QLCDNumberD0Ev [qt- mt]	_ZThn80_N10QLCDNumberD1Ev [qt- mt]
_ZThn80_N10QPopupMenuD0Ev [qt- mt]	_ZThn80_N10QPopupMenuD1Ev [qt- mt]
_ZThn80_N10QScrollBarD0Ev [qt- mt]	_ZThn80_N10QScrollBarD1Ev [qt- mt]
_ZThn80_N10QStatusBarD0Ev [qt- mt]	_ZThn80_N10QStatusBarD1Ev [qt- mt]
_ZThn80_N10QTabDialogD0Ev [qt- mt]	_ZThn80_N10QTabDialogD1Ev [qt- mt]
_ZThn80_N10QTabWidgetD0Ev [qt- mt]	_ZThn80_N10QTabWidgetD1Ev [qt- mt]
_ZThn80_N10QVGroupBoxD0Ev [qt- mt]	_ZThn80_N10QVGroupBoxD1Ev [qt- mt]
_ZThn80_N10QWorkspaceD0Ev [qt- mt]	_ZThn80_N10QWorkspaceD1Ev [qt- mt]
_ZThn80_N11QCanvasViewD0Ev [qt- mt]	_ZThn80_N11QCanvasViewD1Ev [qt- mt]
_ZThn80_N11QDockWindowD0Ev [qt- mt]	_ZThn80_N11QDockWindowD1Ev [qt- mt]
_ZThn80_N11QDragObjectD0Ev [qt- mt]	_ZThn80_N11QDragObjectD1Ev [qt- mt]

mt]	mt]
_ZThn80_N11QFileDialogD0Ev [qt-mt]	_ZThn80_N11QFileDialogD1Ev [qt-mt]
_ZThn80_N11QFontDialogD0Ev [qt-mt]	_ZThn80_N11QFontDialogD1Ev [qt-mt]
_ZThn80_N11QGridLayout10invalidateEv [qt-mt]	_ZThn80_N11QGridLayout11setGeometryERK5QRect [qt-mt]
_ZThn80_N11QGridLayout8iteratorEv [qt-mt]	_ZThn80_N11QGridLayoutD0Ev [qt-mt]
_ZThn80_N11QGridLayoutD1Ev [qt-mt]	_ZThn80_N11QHBoxLayoutD0Ev [qt-mt]
_ZThn80_N11QHBoxLayoutD1Ev [qt-mt]	_ZThn80_N11QMainWindowD0Ev [qt-mt]
_ZThn80_N11QMainWindowD1Ev [qt-mt]	_ZThn80_N11QMessageBoxD0Ev [qt-mt]
_ZThn80_N11QMessageBoxD1Ev [qt-mt]	_ZThn80_N11QPushButtonD0Ev [qt-mt]
_ZThn80_N11QPushButtonD1Ev [qt-mt]	_ZThn80_N11QScrollViewD0Ev [qt-mt]
_ZThn80_N11QScrollViewD1Ev [qt-mt]	_ZThn80_N11QSpinWidgetD0Ev [qt-mt]
_ZThn80_N11QSpinWidgetD1Ev [qt-mt]	_ZThn80_N11QStoredDragD0Ev [qt-mt]
_ZThn80_N11QStoredDragD1Ev [qt-mt]	_ZThn80_N11QToolButtonD0Ev [qt-mt]
_ZThn80_N11QToolButtonD1Ev [qt-mt]	_ZThn80_N11QVBoxLayoutD0Ev [qt-mt]
_ZThn80_N11QVBoxLayoutD1Ev [qt-mt]	_ZThn80_N12QButtonGroupD0Ev [qt-mt]
_ZThn80_N12QButtonGroupD1Ev [qt-mt]	_ZThn80_N12QColorDialogD0Ev [qt-mt]
_ZThn80_N12QColorDialogD1Ev [qt-mt]	_ZThn80_N12QDataBrowserD0Ev [qt-mt]
_ZThn80_N12QDataBrowserD1Ev [qt-mt]	_ZThn80_N12QInputDialogD0Ev [qt-mt]
_ZThn80_N12QInputDialogD1Ev [qt-mt]	_ZThn80_N12QPrintDialogD0Ev [qt-mt]
_ZThn80_N12QPrintDialogD1Ev [qt-mt]	_ZThn80_N12QTextBrowserD0Ev [qt-mt]
_ZThn80_N12QTextBrowserD1Ev [qt-mt]	_ZThn80_N12QUrlOperator4cdUpEv [qt-mt]
_ZThn80_N12QUrlOperator5parseE	_ZThn80_N12QUrlOperator5resetEv

RK7QString [qt-mt]	[qt-mt]
_ZThn80_N12QUrlOperator7setPath ERK7QString [qt-mt]	_ZThn80_N12QUrlOperatorD0Ev [qt-mt]
_ZThn80_N12QUrlOperatorD1Ev [qt-mt]	_ZThn80_N12QWidgetStackD0Ev [qt-mt]
_ZThn80_N12QWidgetStackD1Ev [qt-mt]	_ZThn80_N13QDateTimeEditD0Ev [qt-mt]
_ZThn80_N13QDateTimeEditD1Ev [qt-mt]	_ZThn80_N13QErrorMessageD0Ev [qt-mt]
_ZThn80_N13QErrorMessageD1Ev [qt-mt]	_ZThn80_N13QHBoxLayoutD0Ev [qt-mt]
_ZThn80_N13QHBoxLayoutD1Ev [qt-mt]	_ZThn80_N13QSplashScreenD0Ev [qt-mt]
_ZThn80_N13QSplashScreenD1Ev [qt-mt]	_ZThn80_N13QVButtonGroupD0Ev [qt-mt]
_ZThn80_N13QVButtonGroupD1Ev [qt-mt]	_ZThn80_N14QDesktopWidgetD0Ev [qt-mt]
_ZThn80_N14QDesktopWidgetD1Ev [qt-mt]	_ZThn80_N14QMultiLineEditD0Ev [qt-mt]
_ZThn80_N14QMultiLineEditD1Ev [qt-mt]	_ZThn80_N15QDockAreaLayout10in validateEv [qt-mt]
_ZThn80_N15QDockAreaLayout11se tGeometryERK5QRect [qt-mt]	_ZThn80_N15QDockAreaLayout8ite ratorEv [qt-mt]
_ZThn80_N15QProgressDialogD0Ev [qt-mt]	_ZThn80_N15QProgressDialogD1Ev [qt-mt]
_ZThn80_N5QDialD0Ev [qt-mt]	_ZThn80_N5QDialD1Ev [qt-mt]
_ZThn80_N6QLabelD0Ev [qt-mt]	_ZThn80_N6QLabelD1Ev [qt-mt]
_ZThn80_N6QTableD0Ev [qt-mt]	_ZThn80_N6QTableD1Ev [qt-mt]
_ZThn80_N7QButtonD0Ev [qt-mt]	_ZThn80_N7QButtonD1Ev [qt-mt]
_ZThn80_N7QDialogD0Ev [qt-mt]	_ZThn80_N7QDialogD1Ev [qt-mt]
_ZThn80_N7QHeaderD0Ev [qt-mt]	_ZThn80_N7QHeaderD1Ev [qt-mt]
_ZThn80_N7QLayout10invalidateEv [qt-mt]	_ZThn80_N7QLayout6layoutEv [qt- mt]
_ZThn80_N7QLayoutD0Ev [qt-mt]	_ZThn80_N7QLayoutD1Ev [qt-mt]
_ZThn80_N7QSliderD0Ev [qt-mt]	_ZThn80_N7QSliderD1Ev [qt-mt]
_ZThn80_N7QSocket10writeBlockEP Kcm [qt-mt]	_ZThn80_N7QSocket2atEm [qt-mt]
_ZThn80_N7QSocket4openEi [qt-mt]	_ZThn80_N7QSocket5closeEv [qt-mt]
_ZThn80_N7QSocket5flushEv [qt- mt]	_ZThn80_N7QSocket5getchEv [qt- mt]

_ZThn80_N7QSocket5putchEi [qt-mt]	_ZThn80_N7QSocket7ungetchEi [qt-mt]
_ZThn80_N7QSocket8readLineEPcm [qt-mt]	_ZThn80_N7QSocket9readBlockEPcm [qt-mt]
_ZThn80_N7QSocketD0Ev [qt-mt]	_ZThn80_N7QSocketD1Ev [qt-mt]
_ZThn80_N7QTabBarD0Ev [qt-mt]	_ZThn80_N7QTabBarD1Ev [qt-mt]
_ZThn80_N7QWidgetD0Ev [qt-mt]	_ZThn80_N7QWidgetD1Ev [qt-mt]
_ZThn80_N7QWizardD0Ev [qt-mt]	_ZThn80_N7QWizardD1Ev [qt-mt]
_ZThn80_N8QListBoxD0Ev [qt-mt]	_ZThn80_N8QListBoxD1Ev [qt-mt]
_ZThn80_N8QMenuBarD0Ev [qt-mt]	_ZThn80_N8QMenuBarD1Ev [qt-mt]
_ZThn80_N8QSpinBoxD0Ev [qt-mt]	_ZThn80_N8QSpinBoxD1Ev [qt-mt]
_ZThn80_N8QToolBarD0Ev [qt-mt]	_ZThn80_N8QToolBarD1Ev [qt-mt]
_ZThn80_N8QToolBoxD0Ev [qt-mt]	_ZThn80_N8QToolBoxD1Ev [qt-mt]
_ZThn80_N8QUriDragD0Ev [qt-mt]	_ZThn80_N8QUriDragD1Ev [qt-mt]
_ZThn80_N9QComboBoxD0Ev [qt-mt]	_ZThn80_N9QComboBoxD1Ev [qt-mt]
_ZThn80_N9QDataViewD0Ev [qt-mt]	_ZThn80_N9QDataViewD1Ev [qt-mt]
_ZThn80_N9QDateEditD0Ev [qt-mt]	_ZThn80_N9QDateEditD1Ev [qt-mt]
_ZThn80_N9QDockAreaD0Ev [qt-mt]	_ZThn80_N9QDockAreaD1Ev [qt-mt]
_ZThn80_N9QGLWidgetD0Ev [qt-mt]	_ZThn80_N9QGLWidgetD1Ev [qt-mt]
_ZThn80_N9QGridViewD0Ev [qt-mt]	_ZThn80_N9QGridViewD1Ev [qt-mt]
_ZThn80_N9QGroupBoxD0Ev [qt-mt]	_ZThn80_N9QGroupBoxD1Ev [qt-mt]
_ZThn80_N9QIconDragD0Ev [qt-mt]	_ZThn80_N9QIconDragD1Ev [qt-mt]
_ZThn80_N9QIconViewD0Ev [qt-mt]	_ZThn80_N9QIconViewD1Ev [qt-mt]
_ZThn80_N9QLineEditD0Ev [qt-mt]	_ZThn80_N9QLineEditD1Ev [qt-mt]
_ZThn80_N9QListViewD0Ev [qt-mt]	_ZThn80_N9QListViewD1Ev [qt-mt]
_ZThn80_N9QSizeGripD0Ev [qt-mt]	_ZThn80_N9QSizeGripD1Ev [qt-mt]
_ZThn80_N9QSplitterD0Ev [qt-mt]	_ZThn80_N9QSplitterD1Ev [qt-mt]
_ZThn80_N9QTextDragD0Ev [qt-mt]	_ZThn80_N9QTextDragD1Ev [qt-mt]
_ZThn80_N9QTextEditD0Ev [qt-mt]	_ZThn80_N9QTextEditD1Ev [qt-mt]
_ZThn80_N9QTextViewD0Ev [qt-mt]	_ZThn80_N9QTextViewD1Ev [qt-mt]
_ZThn80_N9QTimeEditD0Ev [qt-mt]	_ZThn80_N9QTimeEditD1Ev [qt-mt]

_ZThn80_N9QTitleBarD0Ev [qt-mt]	_ZThn80_N9QTitleBarD1Ev [qt-mt]
_ZThn80_NK10QBoxLayout11maximumSizeEv [qt-mt]	_ZThn80_NK10QBoxLayout11minimumSizeEv [qt-mt]
_ZThn80_NK10QBoxLayout14heightForWidthEi [qt-mt]	_ZThn80_NK10QBoxLayout17hasHeightForWidthEv [qt-mt]
_ZThn80_NK10QBoxLayout8sizeHintEv [qt-mt]	_ZThn80_NK10QBoxLayout9expandingEv [qt-mt]
_ZThn80_NK10QImageDrag11encodedDataEPKc [qt-mt]	_ZThn80_NK10QImageDrag6formattedEi [qt-mt]
_ZThn80_NK11QGridLayout11maximumSizeEv [qt-mt]	_ZThn80_NK11QGridLayout11minimumSizeEv [qt-mt]
_ZThn80_NK11QGridLayout14heightForWidthEi [qt-mt]	_ZThn80_NK11QGridLayout17hasHeightForWidthEv [qt-mt]
_ZThn80_NK11QGridLayout8sizeHintEv [qt-mt]	_ZThn80_NK11QGridLayout9expandingEv [qt-mt]
_ZThn80_NK11QStoredDrag11encodedDataEPKc [qt-mt]	_ZThn80_NK11QStoredDrag6formattedEi [qt-mt]
_ZThn80_NK15QDockAreaLayout11minimumSizeEv [qt-mt]	_ZThn80_NK15QDockAreaLayout14heightForWidthEi [qt-mt]
_ZThn80_NK15QDockAreaLayout17hasHeightForWidthEv [qt-mt]	_ZThn80_NK15QDockAreaLayout8sizeHintEv [qt-mt]
_ZThn80_NK7QLayout11maximumSizeEv [qt-mt]	_ZThn80_NK7QLayout11minimumSizeEv [qt-mt]
_ZThn80_NK7QLayout7isEmptyEv [qt-mt]	_ZThn80_NK7QLayout8geometryEv [qt-mt]
_ZThn80_NK7QLayout9expandingEv [qt-mt]	_ZThn80_NK7QSocket2atEv [qt-mt]
_ZThn80_NK7QSocket4sizeEv [qt-mt]	_ZThn80_NK7QSocket5atEndEv [qt-mt]
_ZThn80_NK7QWidget6metricEi [qt-mt]	_ZThn80_NK9QIconDrag11encodedDataEPKc [qt-mt]
_ZThn80_NK9QIconDrag6formattedEi [qt-mt]	_ZThn80_NK9QTextDrag11encodedDataEPKc [qt-mt]
_ZThn80_NK9QTextDrag6formattedEi [qt-mt]	_ZThn8_N18QXmlDefaultHandler10fatalErrorERK18QXmlParseException [qt-mt]
_ZThn8_N18QXmlDefaultHandler11errorStringEv [qt-mt]	_ZThn8_N18QXmlDefaultHandler5errorERK18QXmlParseException [qt-mt]
_ZThn8_N18QXmlDefaultHandler7warningERK18QXmlParseException [qt-mt]	

IV Package Information

8 Package Dependencies

8.1 Package Dependencies

The LSB runtime environment shall provide the following dependency.

lsb-graphics-ppc64 (legacy)

This dependency is used to indicate that the application is dependent on features contained in the LSB-Graphics module.

This dependency shall have a version of 3.0.

The lsb-graphics dependencies are deprecated and will be removed in a future version of this specification. Applications should no longer indicate a dependency on them.

Annex A GNU Free Documentation License (Informative)

This specification is published under the terms of the GNU Free Documentation License, Version 1.1, March 2000

Copyright (C) 2000 Free Software Foundation, Inc. 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

A.1 PREAMBLE

The purpose of this License is to make a manual, textbook, or other written document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

A.2 APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you".

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (For example, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, whose contents can be viewed and edited directly and straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup has been designed to thwart or discourage subsequent modification by readers is not Transparent. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML designed for human modification. Opaque formats include PostScript, PDF, proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

A.3 VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

A.4 COPYING IN QUANTITY

If you publish printed copies of the Document numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a publicly-accessible computer-network location containing a complete Transparent copy of the Document, free of added material, which the general network-using public has access to download anonymously at no charge using public-standard network protocols. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

A.5 MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has less than five).
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
- I. Preserve the section entitled "History", and its title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. In any section entitled "Acknowledgements" or "Dedications", preserve the section's title, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section entitled "Endorsements". Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section as "Endorsements" or to conflict in title with any Invariant Section.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties--for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

A.6 COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the

name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections entitled "History" in the various original documents, forming one section entitled "History"; likewise combine any sections entitled "Acknowledgements", and any sections entitled "Dedications". You must delete all sections entitled "Endorsements."

A.7 COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

A.8 AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, does not as a whole count as a Modified Version of the Document, provided no compilation copyright is claimed for the compilation. Such a compilation is called an "aggregate", and this License does not apply to the other self-contained works thus compiled with the Document, on account of their being thus compiled, if they are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one quarter of the entire aggregate, the Document's Cover Texts may be placed on covers that surround only the Document within the aggregate. Otherwise they must appear on covers around the whole aggregate.

A.9 TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License provided that you also include the original English version of this License. In case of a disagreement between the translation and the original English version of this License, the original English version will prevail.

A.10 TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or

rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

A.11 FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

A.12 How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

Copyright (c) YEAR YOUR NAME. Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1 or any later version published by the Free Software Foundation; with the Invariant Sections being LIST THEIR TITLES, with the Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST. A copy of the license is included in the section entitled "GNU Free Documentation License".

If you have no Invariant Sections, write "with no Invariant Sections" instead of saying which ones are invariant. If you have no Front-Cover Texts, write "no Front-Cover Texts" instead of "Front-Cover Texts being LIST"; likewise for Back-Cover Texts.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.