bus

File: bus.kicad_sch

power

File: power.kicad_sch

buffers

File: buffers.kicad_sch

fpanel

File: fpanel.kicad_sch

Z80CPU

File: Z80CPU.kicad_sch

DMA

File: DMA.kicad_sch

GALS

File: GALS.kicad_sch

IM2

File: IM2.kicad_sch

waitstate

File: waitstate.kicad_sch

mapper

File: mapper.kicad_sch

SPARE GAL FOR DEBUGGING



THROUGH HOLES FOR PATCH WIRE ROUTING ACROSS SIDES

SPARE SOCKETS FOR DEBUGGING



Sheet: /
File: processor.Z80.kicad_sch

Title:

Size: B	Date:	**Rev:**
KiCad E.D.A. kicad (6.0.11)		Id: 1/11







Sheet: /bus/
File: bus.kicad_sch

Title:

Size: B | Date: | **Rev:**
KiCad E.D.A. kicad (6.0.11) | Id: 2/11



Sheet: /DMA/		
File: DMA.kicad_sch		
Title:		
Size: B	Date:	**Rev:**
KiCad E.D.A. kicad (6.0.11)		Id: 3/11











SPARE GATES





Sheet: /power/		
File: power.kicad_sch		
Title:		
Size: B	Date:	**Rev:**
KiCad E.D.A. kicad (6.0.11)		Id: 4/11

CPU WS GAL16V8







CPU DATA DIR GAL22V10





DMA CS GAL22V10





DMA RDY GAL22V10





Sheet: /GALS/		
File: GALS.kicad_sch		
Title:		
Size: B	Date:	**Rev:**
KiCad E.D.A. kicad (6.0.11)		Id: 5/11

Z80 BUS INTERFACE

















Sheet: /buffers/	
File: buffers.kicad_sch	
Title:	
Size: B	Date:
KiCad E.D.A. kicad (6.0.11)	Id: 6/11



Sheet: /IM2/		
File: IM2.kicad_sch		
Title:		
Size: B	Date:	**Rev:**
KiCad E.D.A. kicad (6.0.11)		Id: 7/11



U33 NOTE: USE 74HCT374 TO SOURCE OR SINK ADEQUATE CURRENT TO DRIVE LEDS ON FRONT PANEL

J11 NOTE:

PINS 5, 7, 9, 11, 13, 15, 17, 19 ARE FOR LED STATUS FOR ROMWBW FRONT PANEL INDICATOR

PINS 6, 8, 10, 12, 14, 16, 18, 20 ARE FOR SWITCH INPUTS FOR ROMWBW FRONT PANEL

PINS 21, 23 ARE FOR I2C CONNECTION (SDA & SCL)

PINS 25, 27, 29, 31, 33, AND 35 ARE FOR TTL SERIAL CONNECTOR TO UART

PINS 29, 37 ARE FOR SERIAL VCC POWER ENABLE

PINS 22, 24 ARE FOR EXTERNAL RESET SWITCH

PINS 26, 28 ARE FOR IM2 CIRCUIT ENABLE

PINS 30, 32 ARE FOR INTERRUPT 0 ENABLE

PINS 34, 36 ARE FOR WAIT STATE CIRCUIT ENABLE

Sheet: /fpanel/
File: fpanel.kicad_sch

Title:

Size: B	Date:	**Rev:**
KiCad E.D.A. kicad (6.0.11)		Id: 8/11

Wait State Generator Circuit



Sheet: /waitstate/		
File: waitstate.kicad_sch		
Title:		
Size: B	Date:	**Rev:**
KiCad E.D.A. kicad (6.0.11)		Id: 9/11





Tri-state address, data, & control bus during DMA



Reset Button Circuit

Sheet: /Z80CPU/		
File: Z80CPU.kicad_sch		
Title:		
Size: B	Date:	**Rev:**
KiCad E.D.A. kicad (6.0.11)		Id: 10/11

Z80 MEMORY MAPPER AND
EXPANSION IO PORT DECODER

IO ADDRESS SELECT CIRCUIT

INTERRUPT FILTER CIRCUIT

Note: IO Address Port $50-$5F
1-2 =on - A7 (low)
3-4 =off - A6 (high)
5-6 =on - A5 (low)
7-8 =off - A4 (high)



CPU MAPPER GAL22V10





1.8432 OR 7.3728 MHz
TTL OSCILLATOR





MEMORY PAGING SRAMS







UPPER ADDRESS LINES
PULL-DOWN RESISTORS







NOTE: INTERRUPTS RELY ON 4700
OHM PULL UP RESISTOR ON PROCESSOR



Sheet: /mapper/
File: mapper.kicad_sch

Title:

Size: B | Date: | **Rev:**
KiCad E.D.A. kicad (6.0.11) | Id: 11/11