

# MacroPoint LITE Integration Documentation

## Introduction

MacroPoint (MP) LITE integration uses RESTful web services to accomplish the following tasks:

1. Post location updates to your server
2. Post order status changes to your server
3. Create new order tracking sessions
4. Stop existing order tracking sessions
5. Change existing orders

For purposes of this document, the word “order” and “load” may be used interchangeably.

Not all integration implementations require using all features.

The basic flow of integration is:

1. You place an order by calling “Add New Order”.
2. MP LITE sends you locations at regular intervals.
3. MP LITE sends you status changes as they occur.

Below is an example order status change flow:

- a. Requesting Installation (*waiting for owner of the device to install MP LITE*).
- b. Ready To Track (*MP LITE device is ready to begin sending location updates*).
- c. Tracking Now (*MP LITE service is tracking MP LITE enabled device now*).
- d. Tracking Completed Successfully (*Tracking session completed its session with successful location updates*).

Prior to receiving location updates and order status changes from MP LITE, you will supply URIs that implement the appropriate RESTful web services for each. You supply these URIs on the “Update Company Preferences” page of MacroPoint-LITE.com.

## MacroPoint LITE Integration Documentation

### Notify On Location

Description:	Provide location information to customer URI in the format:  http(s)://CustomerSpecifiedURL?ID={1}&Latitude={2}&Longitude={3}&Uncertainty={4}&Street1={5}&Street2={6}&Neighborhood={7}&City={8}&State={9}&Postal={10}&Country={11}&LocationDateTimeUTC={12}	
	ID:	Customers specific order ID.
	Latitude:	Latitude, in decimal degrees.
	Longitude:	Longitude, in decimal degrees.
	Uncertainty:	Approximate uncertainty radius, in miles.
	Street1:	Street address, if available.
	Street2:	Second street address line, if available.
	Neighborhood:	Neighborhood name, if available.
	City:	City name, if available.
	State or Province:	State name, if available.
	Postal:	Postal code, if available.
	Country:	Country, if available.
	LocationDateTimeUTC:	Date and time in ISO 8601 that location was obtained.
Direction:	MP LITE to customer.	
Return:	MP LITE expects HTTP status code 200 back on success, 400 on bad request.	
Security:	<i>Optional</i> . Recommend IP filtering.	
Notes:	All data URL encoded.	

## MacroPoint LITE Integration Documentation

The screenshot shows a web browser window titled "Update Company Preferences - Windows Internet Explorer". The address bar displays "https://macropoint-lite.com/Secure/Company.aspx". The browser's menu bar includes "File", "Edit", "View", "Favorites", "Tools", and "Help". The Favorites bar shows "Update Company Preferences". The page header features the "MACROPOINT LITE" logo and a "MAIN MENU" button. The main content area is titled "Update Company Preferences" and contains the following elements:

- A heading: "Fill out all company information if you intent to receive location updates".
- Fields for "MacroPoint ID" (value: 4177244), "Company Name" (value: Adelson Express), and "Company Verbiage for ID Number" (empty).
- A section titled "Please enter appropriate URLs for:" containing five input fields:
  - Location Updates (highlighted in yellow)
  - Order Status Changes
  - ID Number Validation
  - Order Messaging
  - Trip Event Updates
- Fields for "Location Notification Email" (highlighted in yellow), "Exception Notification Email", "Balance Notification Email", "Tracking Request Notification Email", and "Trip Event Notification Email".
- A checkbox labeled "Validate ID Numbers that I send to myself" which is checked.
- "Save" and "Cancel" buttons.

At the bottom of the form area, it says "Copyright © 2011. All Rights Reserved. [Privacy Policy](#)". The browser status bar at the bottom indicates "Internet | Protected Mode: Off" and a zoom level of "100%".

## MacroPoint LITE Integration Documentation

### Notify On Order Status Change

Description:	Provide status <i>comment</i> when order status changes:  http(s)://CustomerSpecifiedURL?ID={1}&Code={2}&Message={3}	
	ID:	Customers specific order ID.
	Code:	Order Status Code.
	Message:	Text explaining the order status code.
Direction:	MP LITE to customer.	
Return:	MP LITE expects HTTP status code 200 back on success, 400 on bad request.	
Security:	<i>Optional</i> . Recommend IP filtering.	
Notes:	<ol style="list-style-type: none"><li>1. All data URL encoded.</li><li>2. Message text may change in the future. Do not rely on literals.</li><li>3. List of current Order Status Codes (see glossary, more may be added in future)<ol style="list-style-type: none"><li>a. 1001 - Requesting Installation</li><li>b. 1020 - Ready To Track</li><li>c. 1021 - Tracking Now</li><li>d. 1022 - Tracking Completed Successfully</li><li>e. 1050 - Stopped By Creator</li><li>f. 1051 - Stopped Early By Driver</li><li>g. 1052 - Denied By Driver</li><li>h. 1053 - Location Hidden By Driver</li><li>i. 1060 - Tracking - Waiting For Update</li><li>j. 1061 - Incompatible Phone</li><li>k. 1062 - Invalid Number - Not Trackable</li><li>l. 1063 - Landline Not Trackable</li><li>m. 1064 - Driver Refused Installation</li><li>n. 1070 - Expired Without Installation</li><li>o. 1071 - Expired Without Location</li><li>p. 1110 - Trip Sheet Deployed</li><li>q. 1111 - Trip Sheet In Progress</li><li>r. 1112 - Trip Sheet Completed</li><li>s. 1113 - Trip Sheet Expired</li></ol></li></ol>	

## MacroPoint LITE Integration Documentation

The screenshot shows a web browser window titled "Update Company Preferences - Windows Internet Explorer". The address bar displays "https://macropoint-lite.com/Secure/Company.aspx". The browser's menu bar includes "File", "Edit", "View", "Favorites", "Tools", and "Help". The Favorites bar shows "Update Company Preferences". The page header features the "MACROPOINT LITE" logo and a "MAIN MENU" button. The main content area is titled "Update Company Preferences" and contains the following elements:

- A heading: "Fill out all company information if you intent to receive location updates".
- Fields for "MacroPoint ID" (value: 4177244), "Company Name" (value: Adelson Express), and "Company Verbiage for ID Number" (empty text box).
- A section titled "Please enter appropriate URLs for:" containing five text boxes:
  - Location Updates
  - Order Status Changes (highlighted in yellow)
  - ID Number Validation
  - Order Messaging
  - Trip Event Updates
- Fields for "Location Notification Email", "Exception Notification Email", "Balance Notification Email", "Tracking Request Notification Email", and "Trip Event Notification Email" (all empty text boxes).
- A checkbox labeled "Validate ID Numbers that I send to myself" which is checked.
- "Save" and "Cancel" buttons.

At the bottom of the form area, it says "Copyright © 2011. All Rights Reserved. [Privacy Policy](#)". The browser's status bar at the bottom indicates "Internet | Protected Mode: Off" and a zoom level of "100%".

# MacroPoint LITE Integration Documentation

## Notify On Event Update

Description:	<p>Provide event notification when driver confirms an event (example: arrived):</p> <p><code>http(s)://CustomerSpecifiedURL?ID={1}&amp;Stop={2}&amp;Event={3}&amp;EventDateTime={4}</code></p> <table><tr><td>LoadID:</td><td>Customer specific order ID.</td></tr><tr><td>Stop:</td><td>Name of the stop</td></tr><tr><td>Event:</td><td>Event is the “code” that goes with the event. E.g., X1 for Arrived at delivery location. X3 for arrived at pick-up location.</td></tr><tr><td>EventDateTime:</td><td>Time in ISO8601 and in UTC</td></tr></table>	LoadID:	Customer specific order ID.	Stop:	Name of the stop	Event:	Event is the “code” that goes with the event. E.g., X1 for Arrived at delivery location. X3 for arrived at pick-up location.	EventDateTime:	Time in ISO8601 and in UTC
LoadID:	Customer specific order ID.								
Stop:	Name of the stop								
Event:	Event is the “code” that goes with the event. E.g., X1 for Arrived at delivery location. X3 for arrived at pick-up location.								
EventDateTime:	Time in ISO8601 and in UTC								
Direction:	MP LITE to customer.								
Return:	MP LITE expects HTTP status code 200 back on success, 400 on bad request.								
Security:	<i>Optional.</i> Recommend IP filtering.								
Notes:	All data URL encoded.								

Update Company Preferences - Windows Internet Explorer

https://macropoint-lite.com/Secure/Company.aspx

File Edit View Favorites Tools Help

Update Company Preferences

MACROPOINT LITE

MAIN MENU

Update Company Preferences

Fill out all company information if you intent to receive location updates

MacroPoint ID 4177244

Company Name Adelson Express

Company Verbiage for ID Number

Please enter appropriate URLs for:

Location Updates

Order Status Changes

ID Number Validation

Order Messaging

Trip Event Updates

Location Notification Email

Exception Notification Email

Balance Notification Email

Tracking Request Notification Email

Trip Event Notification Email

Validate ID Numbers that I send to myself ☒

Save Cancel

Copyright © 2011. All Rights Reserved. Privacy Policy

Internet | Protected Mode: Off

## MacroPoint LITE Integration Documentation

### Add New Order

Description:	Allows customer to add new order: <a href="https://macropoint-lite.com/api/1.0/orders/createorder">https://macropoint-lite.com/api/1.0/orders/createorder</a>
Direction:	Customer to MP LITE
Return:	MP LITE returns HTTP status code 201 on order created success, 400 on bad request and 5xx on server failure.
Security:	<i>Required.</i> Basic Authentication
Notes:	<ol style="list-style-type: none"> <li>1. Use HTTP POST verb for this request. HTTP POST XML shown below</li> <li>2. Basic Authentication Required <i>We will supply user id and password</i></li> <li>3. {Number Type="?"} is required  Valid types are listed below: <ol style="list-style-type: none"> <li>a. "Mobile" <ol style="list-style-type: none"> <li>i. means cell phone number</li> <li>ii. format must be 9999999999</li> </ol> </li> <li>b. "MacroPoint" <ol style="list-style-type: none"> <li>i. means valid MacroPoint Tracking Number</li> <li>ii. format must be 12 character alphanumeric MacroPoint ID</li> </ol> </li> </ol> </li> <li>4. {TrackStartDateTime} is required and must be in the following format:  YYYY-MM-DD HH:{MM} {SupportedTimeZone}  {MM} must be [ 00   15   30   45 ]  {SupportedTimeZone} [ET   CT   Arizona   MT   PT   Alaska   Hawaii ]  Examples: 2011-03-15 8:00 ET 2011-04-12 14:45 MT 2010-12-23 23:45 PT  Please note spaces: YYYY-MM-DD {space} HH:{MM} {space} {SupportedTimeZone}</li> <li>5. {TrackDurationInHours} is required and must be one of the following values:  [ 1   2   4   8   12   18   24   48   72   96   120   144   168 ]</li> </ol>

*This table continues on the next page*

## MacroPoint LITE Integration Documentation

Notes (continued):	<ul style="list-style-type: none"><li>6. {TrackIntervalInMinutes} is required and must be one of the following values:  [ 15   30   60   120   240   480   720 ]</li><li>7. Order track start time may not be chronologically more than 15 minutes in the past.</li><li>8. At least one notification is required</li><li>9. For a notification<ul style="list-style-type: none"><li>a. {MacroPointID} is required and should be set to your MacroPoint ID if you want notifications to be sent to yourself. If you want notifications to be sent to a different company such as your customer, please ask us for their MacroPointID and you can then automatically send notices to them.</li><li>b. {IDNumber} is required</li></ul></li><li>10. Carrier is optional<ul style="list-style-type: none"><li>a. {CarrierName} is the name of the carrier.</li><li>b. {DispatcherName} is the name of the dispatcher</li><li>c. {DispatcherPhone} is the phone number of the dispatcher</li><li>d. {DispatcherEmail} is the email address of the dispatcher</li><li>e. {CarrierName}, {DispatcherName} have a 64 character maximum size.</li><li>f. {DispatcherPhone} has a 10 character maximum size and must be all numeric</li><li>g. {DispatcherEmail} has a 128 character maximum size and must be a properly formatted email address.</li></ul></li><li>11. TripSheet is optional.<ul style="list-style-type: none"><li>a. TripSheet contains many stops.</li><li>b. {StopID} is a unique value (within a tripsheet) to assign to a stop</li><li>c. {Name} is a name you give a stop (example: ABC company)</li><li>d. {StopType} is "Pickup" or "DropOff"</li><li>e. Address or {Latitude}{Longitude} combination accepted.</li><li>f. If provided, {Latitude}{Longitude} are in decimal degrees</li><li>g. If provided, Address has the following components<ul style="list-style-type: none"><li>i. {Line1} is the first line of the address</li><li>ii. {Line1} is the second line of the address</li><li>iii. {City} is the city of the address</li><li>iv. {StateOrProvince} is the state or province of the address</li><li>v. {PostalCode} is the postal code of the address</li></ul></li><li>h. {StartDateTime} Estimated Arrival Date and time in ISO 8601.</li><li>i. {EndDateTime} Estimated Departure Date and time in ISO 8601.</li><li>j. {Name}, {Line1}, {Line2},{City}, and {StateOrProvince} have a 64 character maximum size.</li><li>k. {PostalCode} has a 16 character maximum size.</li></ul></li></ul>
--------------------	---



## MacroPoint LITE Integration Documentation

### Order XML to be passed to the service in the POST Request Body

```
<Order xmlns="http://macropoint-lite.com/xml/1.0" >
  <Number Type="{Type}">{Number}</Number>
  <TrackStartDateTime>{TrackStartDateTime}</TrackStartDateTime>
  <Notifications>
    <Notification>
      <PartnerMPID>{MacroPointID}</PartnerMPID>
      <IDNumber>{IDNumber}</IDNumber>
      <TrackDurationInHours>
        {TrackDurationInHours}
      </TrackDurationInHours>
      <TrackIntervalInMinutes>
        {TrackIntervalInMinutes}
      </TrackIntervalInMinutes>
    </Notification>
  </Notifications>
  <Carrier>
    <Name>{CarrierName}</Name>
    <Dispatcher>
      <Name>{DispatcherName}</Name>
      <Phone>{DispatcherPhone}</Phone>
      <Email>{DispatcherEmail}</Email>
    </Dispatcher>
  </Carrier>
  <TripSheet>
    <Stops>
      <Stop>
        <StopID>{StopID}</StopID>
        <Name>{StopName}</Name>
        <StopType>{StopType}</StopType>
        <Address>
          <Line1>{Line1}</Line1>
          <Line2>{Line2}</Line2>
          <City>{Line2}</City>
          <StateOrProvince>
            {StateOrProvince}
          </StateOrProvince>
          <PostalCode>{PostalCode}</PostalCode>
        </Address>
        <Latitude>{Latitude}</Latitude>
        <Longitude>{Longitude}</Longitude/>
        <StartDateTime>{StartDateTime}</StartDateTime>
        <EndDateTime>{EndDateTime}</EndDateTime>
      </Stop>
    </Stops>
  </TripSheet>
</Order>
```

## MacroPoint LITE Integration Documentation

### When an order is successfully created

1. HTTP Status Code 201 is returned
2. Response Body: **OrderResult** Entity (shown below) is returned

```
<OrderResult xmlns="http://macropoint-lite.com/xml/1.0" >
  <OrderID>{OrderID}</OrderID>
  <Status>{Status}</Status>
  <Errors>
    <Error>
      <Code>{Code}</Code>
      <Message>{Message}</Message>
    </Error>
  </Errors>
</OrderResult>
```

3. {Status} will be a "Success" or "PartialSuccess".
4. If status is "Success" the **<Errors />** node will be empty or contain code 1009.
5. "PartialSuccess" will be returned if the order had multiple notifications and one or more were accepted and one or more were rejected. If status is "PartialSuccess" at least one **<Error>** node will be present for each notification that was not accepted. {Code} and {Message} are described in the "When an order is **not** successfully created" section (below).
6. {OrderID} will be a 32 digit alphanumeric code that can be referenced in the future to indicate the order.

### When an order is **not** successfully created

1. HTTP Status Code 400 is returned
2. Response Body: **OrderResult** Entity (shown below) is returned

```
<OrderResult xmlns="http://macropoint-lite.com/xml/1.0" >
  <Status>{Status}</Status>
  <Errors>
    <Error>
      <Code>{Code}</Code>
      <Message>{Message}</Message>
    </Error>
  </Errors>
</OrderResult>
```

3. {Status} will be a "Failure".
4. {Code} indicating the type of error
  - a. 1000 – All argument/domain-rule validation exceptions
  - b. 1001 – Insufficient Funds
  - c. 1002 – Possible land line or incompatible cell phone (*deprecated*)
  - d. 1003 – Phone on do not contact list
  - e. 1009 – *Custom text indicating that validation URL was unavailable*
  - f. 3000 – Feature not provisioned
  - g. 9999 – Unexpected error occurred – Administrator notified
5. {Message} is text explaining the error

### Server cannot process the request

1. HTTP Status Code 5xx is returned
2. Response Body: *{unspecified}*

## MacroPoint LITE Integration Documentation

### Stop Order

Description:	Allows customer to stop an existing order: <a href="https://macropoint-lite.com/api/1.0/orders/stoporder/{orderid}">https://macropoint-lite.com/api/1.0/orders/stoporder/{orderid}</a>
Direction:	Customer to MP LITE
Return:	MP LITE returns HTTP status code 200 on order stop success, 400 on bad request and 5xx on server failure.
Security:	<i>Required.</i> Basic Authentication
Notes:	1. Use HTTP POST verb for this request. 2. {orderid} is the 32 digit alphanumeric code returned by "Add New Order"

### When an order is successfully stopped

1. HTTP Status Code 200 is returned

### When an order is **not** successfully stopped

1. HTTP Status Code 400 is returned
2. Response Body: `OrderResult` Entity (shown below) is returned

```
<OrderResult xmlns="http://macropoint-lite.com/xml/1.0" >
  <Errors>
    <Error>
      <Code>{Code}</Code>
      <Message>{Message}</Message>
    </Error>
  </Errors>
</OrderResult>
```

7. {Code} indicating the type of error
  - a. 2000 - Order ID not valid
  - b. 2001 - Order is completed or expired
  - c. 9999 - Unexpected error occurred – Administrator notified
8. {Message} is text explaining the error

# MacroPoint LITE Integration Documentation

## Change Order

Description:	Allows customer to change an existing order: <a href="https://macropoint-lite.com/api/1.0/orders/changeorder/{orderid}">https://macropoint-lite.com/api/1.0/orders/changeorder/{orderid}</a>
Direction:	Customer to MP LITE
Return:	MP LITE returns HTTP status code 200 on order change success, 400 on bad request and 5xx on server failure.
Security:	<i>Required.</i> Basic Authentication
Notes:	1. Use HTTP POST verb for this request. 2. {orderid} is the 32 digit alphanumeric code returned by "Add New Order"

## Order XML to be passed to the service in the POST Request Body

```
<Order xmlns="http://macropoint-lite.com/xml/1.0" >
  <Notifications>
    <Notification>
      <PartnerMPID>{MacroPointID}</PartnerMPID>
      <IDNumber>{IDNumber}</IDNumber>
      <TrackDurationInHours>
        {TrackDurationInHours}
      </TrackDurationInHours>
      <TrackIntervalInMinutes>
        {TrackIntervalInMinutes}
      </TrackIntervalInMinutes>
    </Notification>
  </Notifications>
</Order>
```

## When an order is successfully changed

1. HTTP Status Code 200 is returned

## When an order is **not** successfully changed

1. HTTP Status Code 400 is returned
2. Response Body: `OrderResult` Entity (shown below) is returned

```
<OrderResult xmlns="http://macropoint-lite.com/xml/1.0" >
  <Errors>
    <Error>
      <Code>{Code}</Code>
      <Message>{Message}</Message>
    </Error>
  </Errors>
</OrderResult>
```

3. {Code} indicating the type of error
  - a. 1000 – All argument/domain-rule validation exceptions
  - b. 1001 – Insufficient Funds
  - d. 2000 - Order ID not valid

## MacroPoint LITE Integration Documentation

- e. 2001 - Order is completed or expired
  - f. 2002 - Order duration cannot be less than current duration
  - g. 9999 - Unexpected error occurred – Administrator notified
4. {Message} is text explaining the error

# MacroPoint LITE Integration Documentation

## SendMessage

Description:	Allows customer to send a two-way message: <a href="https://macropoint-lite.com/api/1.0/orders/SendMessage">https://macropoint-lite.com/api/1.0/orders/SendMessage</a>
Direction:	Customer to MP LITE
Return:	MP LITE returns HTTP status code 200 on success, 400 on bad request and 5xx on server failure.
Security:	<i>Required.</i> Basic Authentication
Notes:	<ol style="list-style-type: none"><li>1. Use HTTP POST verb for this request.</li><li>2. {OrderID} is the 32 digit alphanumeric code returned by "Add New Order"</li><li>3. {Message} is the text to send</li></ol>

### Message XML to be passed to the service in the POST Request Body

```
<Message xmlns="http://macropoint-lite.com/xml/1.0" >
  <OrderID>{OrderID}</OrderID>
  <Text>{Message}</Text>
</Message>
```

### When a message is successfully sent

HTTP Status Code 200 is returned

### When a message is **not** successfully sent

1. HTTP Status Code 400 is returned
2. Response Body: `MessageResult` Entity (shown below) is returned

```
<MessageResult xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <Errors>
    <Error>
      <Code>{Code}</Code>
      <Message>{Message}</Message>
    </Error>
  </Errors>
</MessageResult>
```

3. {Code} indicating the type of error
  - a. 2000 – OrderID Not Valid
  - b. 2005 – Order Message Feature Not Provisioned
  - c. 2006 – Order Message Url Empty
  - d. 9999 – Unexpected error occurred – Administrator notified
4. {Message} is text explaining the error

## MacroPoint LITE Integration Documentation

### Notify On Incoming Message

Description:	Relays incoming two-way message from driver for specific load:  http(s)://CustomerSpecifiedURL?OrderID={1}& Message={2}	
	OrderID:	OrderID is the 32 digit alphanumeric code returned by "Add New Order"
	Message:	Text of incoming message.
Direction:	MP LITE to customer.	
Return:	MP LITE expects HTTP status code 200 back on success, 400 on bad request.	
Security:	<i>Optional</i> . Recommend IP filtering.	
Notes:	<ol style="list-style-type: none"><li>1. All data URL encoded.</li><li>2. Data received via SMS can at times (infrequently) be disordered</li></ol>	

The screenshot shows a web browser window titled "Update Company Preferences - Windows Internet Explorer". The address bar shows the URL "https://macropoint-lite.com/Secure/Company.aspx". The page features the MacroPoint LITE logo and a "MAIN MENU" button. The main content area is titled "Update Company Preferences" and includes the instruction: "Fill out all company information if you intent to receive location updates". The form contains the following fields and options:

- MacroPoint ID: 4177244
- Company Name: Adelson Express
- Company Verbiage for ID Number: (empty text box)
- Please enter appropriate URLs for:
  - Location Updates: (empty text box)
  - Order Status Changes: (empty text box)
  - ID Number Validation: (empty text box)
  - Order Messaging: (highlighted yellow text box)
  - Trip Event Updates: (empty text box)
- Location Notification Email: (empty text box)
- Exception Notification Email: (empty text box)
- Balance Notification Email: (empty text box)
- Tracking Request Notification Email: (empty text box)
- Trip Event Notification Email: (empty text box)
- Validate ID Numbers that I send to myself: ☒

At the bottom of the form are "Save" and "Cancel" buttons. The footer of the page reads "Copyright © 2011. All Rights Reserved. Privacy Policy". The browser's status bar at the bottom indicates "Internet | Protected Mode: Off" and a zoom level of "100%".



## MacroPoint LITE Integration Documentation

### Glossary

Code	Text	Description
1001	Requesting Installation	Waiting for owner of the device to install MacroPoint LITE.
1020	Ready To Track	MacroPoint LITE device is ready to begin sending location updates.
1021	Tracking Now	MacroPoint LITE service is tracking MacroPoint LITE enabled device now.
1022	Tracking Completed Successfully	Tracking session completed its session with successful location updates.
1050	Stopped By Creator	Tracking session was ended by the account holder who originally set up the session.
1051	Stopped Early By Driver	Tracking session was ended by owner of the MacroPoint LITE enabled device.
1052	Denied By Driver	Owner of the device opted out of MacroPoint LITE and can no longer be tracked.
1053	Location Hidden By Driver	MacroPoint LITE device is currently hidden by the owner of the device.
1060	Tracking - Waiting For Update	System is waiting for the most recent location update.
1061	Incompatible Phone	Driver cell phone is not compatible with MacroPoint LITE.
1062	Invalid Number - Not Trackable	Owner of cell phone was contacted and reported wrong number (or an internal process determined it was a wrong number).
1063	Landline Not Trackable	Owner of cell phone was contacted and reported wrong number, specifically this number is a landline (or an internal process determined it was a landline).
1064	Driver Refused Installation	Owner of the device refused installation.
1070	Expired Without Installation	Owner of the device never completed the MacroPoint LITE installation process.
1071	Expired Without Location	A tracking session completed without obtaining a location update.
1110	Trip Sheet Deployed	"Trip sheet only" load session is ready to begin accepting event updates
1111	Trip Sheet In Progress	"Trip sheet only" load session in progress with event updates
1112	Trip Sheet Completed	"Trip sheet only" load session completed with successful event status updates
1113	Trip Sheet Expired	"Trip sheet only" load session completed without any event status updates