



Project Title

Optional Subtitle

Hermanni Hälvä ¹

MSc. Computational Statistics and Machine Learning

Supervisor: Prof. Bradley Love

Submission date: Day Month Year

¹**Disclaimer:** This report is submitted as part requirement for the MSc CSML degree at UCL. It is substantially the result of my own work except where explicitly indicated in the text. The report may be freely copied and distributed provided the source is explicitly acknowledged

Abstract

Summarise your report concisely.

Contents

1	Intro/Literature Review Notes	2
2	Implementation Ideas	18
3	Deep Learning in Computer Vision	19

Chapter 1

Intro/Literature Review Notes

Humans are able to extract rich semantic information from visual scenes. For instance, upon viewing a picture of a dog, we may also be able to identify it as a specific breed such as a golden retriever. Further, our understanding of the image benefits from semantic knowledge that is not captured explicitly in the visual features of a specific image. For example, we also know that the dog belongs in the category of mammals which, in turn, are animals and thus living entities. While this type of hierarchical semantic visual understanding comes to us effortlessly, it remains a challenging task for computer vision. In fact, most image classification models are trained on data sets with single, mutually exclusive labels and thus the learnt feature representations do not account, for example, for both cat and dog being four-legged animals. Why is this a problem? Generalization? An exception to this is the area of knowledge transfer and related tasks such as zero-shot learning in which the aim is to predict labels of previously unseen classes of images; a popular approach for zero-shot learning is to borrow strength from, say text data, to create a semantic space that embed all the possible labels of images including those not seen previously. Mapping between images and the semantic space is then learned using the 'seen' images. Once this mapping is learnt, it can be used to transform previously unseen images into the semantic space and then apply some distance measure to label it as the category that's closest in the embedding space. We postulate that the same idea could also be employed in the simple image classification tasks to achieve better generalization performance. In particular, we will train a deep learning model for image classification against a hierarchical semantic embedding derived from the WordNet database which, as we will show, will correspond to regularizing the model weights to account for these semantic relationships. We will use the recently developed Poincaré embeddings as the resulting embedding space can capture both the similarity between the possible labels as well as the hierarchical semantic relationships encoded by WordNet graphical model. The learnt model is then transferred to perform standard image classification by adding a final softmax classification layer and fine tuning this against the ImageNet database. Our results show ... hopefully some improvements over training the model only against ImageNet which illustrates the benefit of incorporating semantic knowledge..

Enforcing hierarchical labels should also provide more robust representations that is more akin to evidence that we represent objects by their components [?] because e.g. Dog and Cat and share

many visual similarities, thus they should borrow strength from both of them.

PAPERS ON PSYCHOLOGY OF VISUAL PERCEPTION & SEMANTICS

Basic Objects in Natural Categories [1]

Overview

The visual world that we experience consists of an infinite number of different stimuli, yet we are able to classify this environment into distinct objects. This is because there is an inherent correlative structure in real world objects. For instance, dogs never have wings and birds will not in general have a furry tail; humans are able to exploit this non-independence by grouping objects into categories based on their visual attributes. Categories in turn can be organised into hierarchical taxonomies. For instance, dogs and birds can be distinct categories but in a taxonomy can also be grouped into a higher level category of animals which are visually distinct from some other higher level category such as furnitures. In this paper the authors show that there is in general one level of abstraction in the taxonomy of visual objects at which humans naturally make the most fundamental distinction between objects i.e. they are the most differentiated at this level; this is called the basic level. The reason for this is that given infinite visual stimuli, it is more efficient to only differentiate objects that are relevant to any task at hand - the basic level represents the level of abstraction that is the most useful in most situations. Categories one level of abstraction above the basic level are called superordinate categories and they are less fundamental for separating objects as they have fewer common attributes with each other. Categories one level below the basic level are subordinate categories, and they are in turn less fundamental for separating objects because there is more sharing of visual features across contrasting subordinate categories.

Thoughts:

- DL for classification usually doesn't take account of taxonomies though one could argue that most datasets are at the basic level. Nevertheless it would be of benefit to account for entire hierarchy
- several limitations in this paper (see [2])

Pictures and Names: Making the Connection [2]

Overview

This extends the work of [1]. The authors find that the basic level is a level at which identification is fastest on average. In fact, it is found that humans will work through taxonomy by first classifying an object at basic level and after that at a subordinate level. The classification we perform is thus time-dependent. Further the authors find that the same process is used to name text and visual data, which implies that there is an important link between our perception of visual scenes and semantic knowledge. More specifically, humans are able to use semantic knowledge to generalize to superordinate categories from seen objects. For example, upon seeing an image of a chair, we can say that this belongs to a broader category of furniture even though the image alone doesn't reveal that such higher level of abstraction exists. On the other hand, upon hearing about 'an office chair with wheels' we can easily access our visual memory to imagine what this would look like. Thus there is a strong link between our visual and semantic processes. Another important contribution of this work is that whilst basic level is indeed the level where

usually identification is first made, this is not true always, especially when you have atypical examples: penguin for instance would be first identified as penguin rather than a bird which is the basic-level. In general, classification is also constrained by the subject knowledge, for instance a bird-watcher may identify a bird as a Robin but most people will just call it a 'bird'.

Thoughts:

- it is interesting that usually subordinate classification depends on the basic level. DL should thus take account of hierarchical semantic information optimally.
- in general the close relationship between semantic and visual identification corroborates our aim of using semantic embedding.
- one concern is that we are limited by the lowest level of labels in the imagenet labels, however otherwise model training, unlike humans, is not restricted by classification time and ability to recall detailed labels and thus we should be able to incorporate all the possible semantic knowledge

Learning Hierarchical Visual Representations in DNNs Using Hierarchical Linguistic Labels [3]

Overview

This paper is the only one I have found that takes a psychological perspective and tries to make a link between the above two papers ([1], [2]) and deep learning. In the paper the authors investigate whether the use of two-level hierarchical labels helps DNNs to learn better visual representations. As DNNs are typically trained against single labels, the features learned are biased by the arbitrary level of these labels; for instance, different breeds of dogs each have their own label in the widely used ImageNet data-set, but there is no information in the labels that informs the models that all the different breeds are part of a larger category of 'dogs'. In order to control for these hierarchical relationships in categories, the authors define two levels of labels for each image, called base level (top-level, e.g. 'dog') and subordinate level (original low-level label e.g. 'golden retriever'). They argue that this is much closer to how humans represent and learn object categories. To test this, they train four versions of the InceptionV3 [4] DNN architecture on the ImageNet Large Scale Visual Recognition Challenge 2012 data (ImageNet hereon): original pre-trained model that only uses subordinate-level labels, model pre-trained on the subordinate labels and fine-tuned on basic-level labels, model pre-trained on basic-level and fine tuned on subordinate labels, and finally a model trained purely on basic-level labels. Several interesting results were attained. First, the authors found that including the basic-level labels led to a much more clustered representation of the feature spaces (e.g. the features vectors of different breeds of dogs were now bundled up together whilst if trained on just subordinate labels, then there was no clustering of similar categories). Additionally, dendrogram of hierarchical clustering of the learned feature space with basic labels showed a clear separation between nature related objects 'natural images' and images of man-made objects 'artificial images', even though no such information about the two groups was given to the model *a priori*. The authors note that this is close to humans' mental representations. To further compare the model's learned representation to humans, the authors investigate how well the model is able to capture human similarity judgements. For the models, similarity between two images is measured as the inner product of their feature

representations, and this was compared to human ratings (on scale 1 to 10) of similarity of the same images. Whilst the authors found that on aggregate including basic labels improved the explanatory power of the DNN, the R^2 was not very high (0.57) and as noted, similar results have in the past been attained using only the subordinate labels. Finally, the paper also presents a generalization experiment in which the model is given just a few examples of either sub or basic level images and then told to find other images from the data set which it would predict to have the same label. The results of this few-shot generalization experiment show similar results as corresponding human studies [5] in that introducing basic-level in model training leads to basic-level bias (even if the example given is of subordinate level, the model will generalize by seeking matches in basic level).

Thoughts:

- This is probably the most relevant papers to ours, though I dont actually think it's too similar because they use only two levels of labels so focus on just basic/subordinate, so I dont really see this as hierarchical. It's quite different from how we are going to do with word2vec or some other embedding that allows a much richer relationship between the words rather than just a 'vertical' link between two categories.
- They approach quite strongly from psychology point of view and dont even talk about the accuracy of the model. I think I will have more ML focus than this and will definitely look at the models' performance
- I do like the psychology approach in that if we think of AI more generally then I suppose we wish to achieve human-like semantic understanding and one could argue that this paper perhaps has some of that going on
- I am tempted to also use InceptionV3 in case we do wish to repeat any of their experiments, and for the reason it was used here which is that it's near state-of-the-art and pretty quick to train
- Find it bit weird that they define the model's feature space to be just the final layer: '...we pose multi-level labeling problem simply as learning a set of independent softmax classifiers that are unconnected to each other and fully connected to the final representation layer of deep CNN while other alternative approaches exist for defining the network architecture and loss function, this approach provides a single embedding space for all images, which allows us to inspect the representations with classic psychological methods such as hierarchical clustering.' Not the biggest fan of this approach as would expect also hierarchy of representations through out the network (c.f. human visual cortex)
- further, with above in mind the authors only fine-tune the final layer: 'For fine-tuning models, we freeze all but the weights in the last block of the model to speed up training'. If we wish to look a representation across hierarchy of layers, we cant do this. Hopefully this wont be too much computation...
- the t-sne and dendrograms of representations i do like so might consider something similar

- their human similarity judgement experiment is nice but am not very convinced by their results. Would be cool to top them but not sure how realistic it is to get hands on that data since they collected using Amazon MTurk which costs some moneys
- Their generalization experiment with basic level bias is also unconvincing to me. They only have two levels of labels with one more general than the other, and a model where features are hierarchical so it doesnt surprise me that the higher level subsumes the lower. If they would have three levels and would generalize to the middle level, then that would be pretty cool. Need to think if this experiment is going to be relevant to us
- with regards to [1],[2] this paper also doesnt address that level of identification depends on factors such as time-limit of identification and knowledge of the subject. Thus our approach of training with full semantic embedding is superior.
- in general the technical methodology of our model will be different too

PAPERS ON SEMANTIC KNOWLEDGE TRANSFER & ZERO-SHOT LEARNING

These zero-shot learning papers are very much related to ours in the sense that they try to achieve generalization via word embeddings into unseen image classes. The DeVISE paper is probably the most similar though others relevant too. In fact, some of them already used this idea before the deep learning revolution.

Large Scale Image Annotation: Learning to Rank with Joint Word-image Embeddings [?]

Overview

This is a pre-deep learning paper, on how to handle efficiently annotation of 'new' large scale data-sets such as ImageNet. Approach is to learn to represent images and annotations jointly in a low dimensional embedding space, idea being that low-dimension at test time translated into faster model. Indeed, a pre-deep learning methods such as performing knn in image feature space suffer from the curse of dimensionality. To do this they use a loss function that allow the model to learn-to-rank i.e. to optimize precision of k-top annotations. In practice, their model performs linear mapping into joint embedding space (i.e. annotations and images are multiplied by their own matrices of equal dimensions).

Thoughts:

- while impressive at the time, no longer state-of-the-art, but their point about curse of dimensionality may still be important even for DL. Say if a DL model has a softmax of too high N, it becomes harder and harder to separate out different classes so word embedding may help here
- The model used by the authors is just a linear matrix transformation. Thus DeVISE paper can be seen as a big improvement over this.

Zero-shot Learning Through Cross-modal Transfer [?]

Overview

Motivated by the idea that humans have the ability to identify unseen objects even if they know about that object from having read about it. The authors introduce a model that can predict both seen and unseen classes: 'without having ever seen a cat the model can say whether it is indeed a cat or another category it has seen during training'. Large unsupervised text data is used to create word embeddings and then images are mapped into this space using neural networks. Prediction of unknown classes works by determining whether the test image is on the same manifold as known examples - this is based on outlier detection. One advantage over previous works is that unsupervised text corpus can be used rather than a manually constructed word embedding space.

The model used to create unsupervised word embedding is based on [?] (see above), which can be seen as earlier version of GloVe. They perform this on Wikipedia text data to create word embeddings that capture local and global context. Image features are then computed in unsupervised fashion using orthogonal matching pursuit. With the word and image feature vectors available, a two layer neural network is trained on the images with known classes into the word embedding space. The authors then use t-sne to visually illustrate that if unseen classes are fed

into the model, the predicted word vectors will not be close to the vectors of known classes (which are clustered in turn). The closest known classes to the zero-shot classes however give idea of their semantics. In practice, to accomplish above we need to first detect whether an image is of a known class or of unknown class, and for this purpose a binary novelty random variable is employed (this is because otherwise would never predict any of the unseen classes if only used training data of seen classes). An outlier detection (based on Gaussian distribution) to predict whether an image is of unseen class given its predicted word embedding vector. If image is predicted as seen, a softmax classifier is used to predict its label, whereas, if image is predicted as new, an isometric Gaussian is assumed around its word vector and its class is assigned based on likelihood i.e. distance between predicted word embedding and full-word embedding space that contains also the unseen classes (this is the classic zero-shot trick using word data). The equations in the paper make this much clearer so will add those. In training, CIFAR-10 image data is used with 2 classes omitted for testing. The results depend strongly on the threshold used to determine whether image is in an unseen or seen class.

Other interesting points: The authors show how the zero-shot learning can be framed in a fully bayesian way. They also compare the novelty detection in word embedding space as above, to doing novelty detection in image feature space and find the former superior as it adds the additional information from semantics.

Thoughts:

- the zero-shot approach here may not be fully relevant to us but I still wrote it up so have a general idea of why word embeddings are used in these papers. Further, I do find this an interesting application and if we have time, may want to consider zero-shot learning
- no deep models used here really though they do call their two layer neural network a deep model, different times ...no convolutions though
- hierarchical information is not used
- a major problem is that the threshold used to discriminate between known and unknown class creates an inherent trade-off between the ability to predict these two. The DeVISE model improves on this (see below)
- a lot of useful references to go through from this paper, and some other interesting ideas not covered above may be worth exploring later

DeVISE: A Deep Visual-Semantic Embedding Model - Frome et al. 2013

Overview

Typical object classification models treat all the categories unrelated, via N-way softmax. This leads to models that 'cannot transfer semantic information about learned labels to unseen words or phrases. Solution this paper proposes is to use both standard image data and then an unrelated large unannotated text data to learn semantic information. In particular, the model maps image inputs into this rich semantic embedding space. The results show similar performance to standard state-of-the-art DL models, but with a significant improvement in that much less 'semantically unreasonable' mistakes are made. Perhaps more importantly, they show this joint training allows

the model to generalize to 20000 visual categories, despite having trained the model on just 1000 categories.

DeViSE extends work of Weston et al. (above) as it allows non-linearities and also capture semantics from text that's not contained in the image labels, hence allowing for zero-shot generalization. It also improves on the Socher et al. paper by using a deep model and avoid the trade-off which that paper has in predicting seen and unseen classes. Socher et al. also combine several different models whilst this one uses a unified model that only uses embeddings. Several other previous papers have used WordNet to build semantic representations; they authors here use a large unannotated text data which they claim is superior.

The modelling approach begins by first training the skip-gram model which predicts the adjacent terms in the text for each word and then creates an embedding on this. This model was trained on 5.4 billion word Wikipedia data set. Image-labels were then mapped into this vector representation. Next, a DNN was used to map images into this embedding space by removing the final softmax layer and instead using a similarity metric. More precisely, a combination of dot-product similarity and hinge rank loss was used (following Weston et al.); this was found to be better than L2 loss. During model testing, image is projected into the embedding space and the nearest label is found using a hashing technique. The corresponding image-net synset is then found for this embedding.

The model is then used to perform zero-shot learning and compared against few baselines: state-of-the-art DL model and the authors' DeVISE model but using random embeddings rather than learnt word embeddings. The authors claim better results than standard DNN on standard classification task on imagenet, though I am really not convinced by this as the differences are tiny and doubt statistically significant. However, on zero-shot learning, DeVISE does really seem superior.

Thoughts:

- quite similar to our approach as we will also look to map image labels into word embedding space
- we will also follow this by removing the softmax layer from our choice of DNN and instead use some similarity metric
- we need to thus think what will be our final loss we will use, probably try several different
- need to think how to perform testing since predictions just give embedding location. Not sure if the hashing technique is the best way to do this.
- I really don't see why the use of the wikipedia data is superior to wordnet. Since wordnet seems to already correspond to how humans build a taxonomy of visual objects (see earlier 'psychology papers') then surely that would be the preferred approach? In particular, the wikipedia text is clearly larger but will have a lot of noise, and more importantly it may not be predictive of the relationship of how visual features correlate. For instance, the words 'bird' and 'sky' are likely to end up near each other based on the wikipedia data, but the two don't visually resemble each other so perhaps it's not good for them to be close if the aim is to influence what visual features are to be learnt.

Overview In previous literature, zero/few-shot learning has been achieved via knowledge transfer. Two different routes have been used for knowledge transfer. The first is to use implicit knowledge representations in the form of semantic embeddings create from some adjacent text data. According to the authors, the generalization power of semantic models is limited, partly by the mapping models themselves. Further, there is no easy way to learn semantic embeddings from structured information such as knowledge graphs. Indeed, the second approach to zero-shot learning has been to use explicit knowledge transfer of rules and relationships. A simple example given is to learn a separate classifier for different compositional categories of a visual object.

This paper’s novel contribution is to use both implicit knowledge representation (i.e. word embeddings) and explicit ones (i.e. knowledge graph) to learn a visual classifier. This is done by constructing a knowledge graph where the nodes of the knowledge graphs are the semantic word embedding representations, and are connected to each other by edges that represent the relationships between the words. The node semantic embeddings are created using GloVe. Graph Convolution is used to pass messages in the graph between the categories according to the knowledge graphs, which in one of the experiments is just the WordNet sub-graph. Essentially this approach generates a new deep logistic classifier for each object. The visual features are extracted from inception V1/Resnet50 model, depending on the experiment. The results of the paper show very large improvements over DeVISE and other state-of-the-art in zero-shot classification.

Thoughts:

- the authors say its hard to learn semantic embeddings from structured information but actually Poincare embedding should allow this since they precisely try to represent hierarchical data in embedding e.g. wordnet.
- what exactly is wordnet SUB-graph? need to check
- the performance of this model is very impressive; I wonder if it we should also attempt how our model does in zero-shot learning

PAPERS USING WORD HIERARCHIES IN IMAGE CLASSIFICATION

Learning and Using Taxonomies For Fast Visual Categorisation - Griffin and Perona 2008

Overview

Pre DL-era paper in which the authors attempt to move from linear computational cost in number of categories of one-vs-other classifier to logarithmic cost by considering a tree-like hierarchical classification. This is particularly important for large number of labels, say 10^4 . The authors conjecture that humans are able to perform fast visual categorization by moving down a hierarchical taxonomy and hence avoid considering irrelevant classes e.g. to classify an 'object' as a dog first decide if something is an animal or not and after that if the animal is a dog or a cat. To do this need to create hierarchy of categories as a binary tree. This is done using Spatial Pyramid Pooling on the images and their labels.

Thoughts:

- hierarchy here is in the classification model though the idea is similar to ours that humans hold visual categories
- the model here is very complex in that it requires several pre-processing steps e.g. with SIFT so very different from DL approach
- rather than using wordnet hierarchy they calculate hierarchy from images and their labels. Using wordnet embedding would give us the ability to draw strength from categories not necessarily in our images (though if we use imagenet, they should mostly be there?)

NLP WORD EMBEDDING PAPERS

These papers provide important background on word embeddings. Main idea is to represent words in vector space such that distance between any two vectors reflects the similarity of those two words (semantically).

Improving Word Representations via Global Context and Multiple Word Prototypes - Huang et al. 2012

Overview

Main point is that in order to cluster words vectors appropriately, need to consider both syntax and semantics. Most previous approaches have only done this in the context of the local problem, but employing a global data can provide more accurate results, as it would better capture semantics whilst still controlling also for syntax. A joint model is hence used. Indeed, the authors show that this joint model provides better correlation with human similarity judgement of words.

More specifically, 'the model jointly learns word representation while learning to discriminate the next word, given a short word sequence (local context, syntactic information) and a document of text the sequence appears in (global context, semantic information)'. Two standard neural networks are used to predict scores that reflect the likelihood of the most recent word occurring given the local and global context. Sum of the two scores creates a total score for the most recent word, which is then used to construct a hinge-loss type of function to discriminate against any other possible word that could have occurred, which is then minimized. *Thoughts:*

- This seems like a pre-cursor to GloVe

MULTI-LABEL CLASSIFICATION PAPERS

According to current plan, we are concerned with typical single-label classification. Nevertheless, multi-label image classification is relevant to us since those papers have to explicitly try to learn relationships between many related categories in objects. Different papers below approach this in different ways and have somewhat differing aims. They do share our goal of trying enforce some way of semantic understanding into DL papers. I do sometimes feel that multi-label classification is 'under rated'; it's much closer to how I imagine that humans process visual data.

YOLO 9000 - Redmon and Farhadi 2016

Overview

This is a object detection paper so in a way quite different from ours i.e. it tries to predict locations of all objects in the images and then label those. This paper is relevant to us due to its use of hierarchical labelling, which the authors use to combine distinct datasets of unequal hierarchy into one dataset, so their purpose of hierarchies is though very different from ours. More specifically, in this paper the authors combine images from classification data sets and object detection (includes localization and possible multiple objects). Problem is that imagenet has very specific labels (c.f. subordinate in above paper) whilst detection data set has only very generic labels e.g. dog (c.f. basic labels above paper). Need a coherent way to marge these different level labels, to create the joint data set. Also, say 'norfolk terrier' and 'dog' may not be mutually exclusive in photos thus cant merge using just a single softmax like in DL typically. Thus the authors instead create a hierarchical tree of the imagenet labels (which are based on WordNet). To classify with their hierarchical tree, predict conditional probabilities at each node i.e. probability of each hyponym of that synset given that synset. e.g. $P(\text{norfolk terrier} \mid \text{terrier})$, $P(\text{Yorkshire terrier} \mid \text{terrier})$. Can then calculate marginal probabilities by traversing upwards through the graph. This allows the authors to combine COCO and ImageNet data sets and efficiently do detection on over 9000 labels with only marginal performance drop. The authors also show that with the hierarchical model, the performance of the model degrades gracefully when it sees for instance a dog but isnt certain about the breed of the dog

Thoughts:

- the idea of hierarchies is more similar to us here than in the Peterson paper
- would be interesting thus compare our models performance to this one, though it may be hard given the weird training done here
- the hierarchical approach is more of a 'means' here and in itself is not much analysed. e.g. there is no discussion of representations
- Whilst how theyve built the tree from wordnet is impressive, it only captures hierarchies whilst a word emebdding space may be able to capture more complex relationships
- I find their point about graceful degradation fascinating and will look to explore that as well. Very curious if a hierarchically trained version of our model turns out to be more robust to adversarial attacks.

Overview

In reality, visual views rarely ever contain just a single object with a unique label; rather, we perceive rich semantic information in even the simplest views. Single label classification fails to capture this, hence multi-label classification. Usual approach to multi-label classification treats it as multiple single label classification problems. This fails to capture the dependency between multiple labels e.g. sky and clouds usually appear together but cars and water shouldnt. Machine vision has in the past captured these type of dependencies using markov random fields but such grid models only really control for pairwise dependencies. Cannot handle complex higher order relationships in images. To do this the authors of this paper use RNN on multi-label data and show that this significantly improves classification accuracy.

Usually CNNs share features across different classifications, but the problem here is that small objects in images are hard to classify because the features are built on classifying the whole image in the best way possible. RNN helps in this because, as the paper shows, it implicitly creates an 'attention' model where the classifier focuses on different areas of the image based on the RNN memory state. More specifically, this is done by learning joint image-label embedding to model semantic relevance, where the image embedding is the lower layer of the CNN. These are projected into same sub-space as label embeddings, and the LSTM memory thus captures higher order dependencies in this embedding space in particular. Model is best understood from figure 4. In prediction stage, beam search algorithm is used because markov property is not satisfied. And to be clear, training is done on multi-label data sets such as MS-COCO.

Results: state-of-the-art on multi-label since can weed out labels that can't possibly co-occur. On 1000 label data set the performance is poor because the DL model is trained on image net, which doesnt have concepts such as actor/actress that occur in the large multi-label data-set On MS-COCO data set poor performance with few tiny objects such as toaster/hair dryer that have little dependence on other categories. The authors also show nearest neighbours in label-image joint space to illustrate that the model indeed captures semantic similarity. They also show that (using de-convolution), there is implicit attentional mechanism where first the model focuses on entire image and then moves on to smaller parts.

Thoughts:

- A big difference between all these multi-label approaches and ours would be that here semantics are really controlled only by what's visible in images, whilst we could use entire corpus of text / ImageNet hierarchy even for a single image.
- On the other hand, our model wouldn't be able to do multi-label classification as it's hierarchical 'understanding' would derive entirely from word embeddings..
- A little like that attention here, I wonder if we could also visualize if using hierarchical model changes the regions of the image that the model focuses on vs. non-hierarchical model
- the observation about toaster/hair dryer being difficult to capture semantically is interesting.

I wonder if our word embedding approach would suffer from similar?

- bit like the nearest neighbour label prediction here, we should attempt also to predict into the embedding space after training the model. I really wonder if we could thus train on single label data but actually somehow accomplish multi-label predictions (based on predicted embedding space). I guess this would be kind of what the zero-shot learning papers (see the section on those papers) attempt to do using word embeddings.

Other relevant papers and intro stuff

Computer vision researchers have already long before the advent of deep learning, been interested in multi-label classification as it would greatly enhance our ability, for example to search and retrieve large quantities of image data [?]. Further, multilabel classification much closer corresponds to how humans perceive complex visual scenes and thus developing models with rich semantic ability would be a valuable step for development of artificial intelligence technology such as autonomous vehicles. Multi-label classification already of interest before deep learning: [?].

Similarly, word embeddings have been used extensively to capture image semantics much before deep learning. As an example [?] perform unsupervised image auto-annotation with a probabilistic model in which a joint latent space is used to represent co-occurrence of image features and words. More specifically, the authors constraint the latent space to be mainly defined by word-features as they argue that the semantic relationships between words is richer than that of image features, and second, co-occurrence of words in text is semantically more meaningful than that of visual features. The authors' first point may be less relevant for the state-of-the-art today as convolutional neural networks have shown the ability to build complex visual features. Nevertheless, if we train model that captures full semantic relationships in large sample text, this should be richer still; for instance, ImageNet is represented by a Directed Graph rather than just a tree hierarchy. The second point too remains apt, image feature co-occurrence indeed may not mean much (though deeper layer ones do probably more so in CNNs). The presence of varying background and other objects, makes it difficult to maintain semantic similarity on the basis of visual features alone.

How is multi-label classification different from semantic segmentation / object detection? Not trying to locate/bound any object but rather concerned with labeling. Why would we need something other than YOLO9000 (Redmon and Farhadi 2016). Further, in our approach we are not trying to perform multi-label classification, rather we still perform single label classification but trying to benefit from semantic dependencies in training...

Is it really a reasonable assumption that semantically similar words should be close to each other in image space. Perhaps true for e.g. cat and a dog. But what about sheep, clouds or snakes and cables. Should they be close to each other in an optimal embedding space?

In Bayesian framework, the use of embedding would probably correspond to some prior that is the wordnet graph

Chapter 2

Implementation Ideas

- which loss function to compare predicted and ground-truth embedding vectors. Dot product hinge loss as in DeVisE?
- at test time, how to predict labels i.e. to find nearest neighbour? Some tree or hashing e.g. DeVisE
- which baselines to use? Standard inception-v3, random embedding, word2vec embedding,
- what evaluations to make? resonableness of errors

Chapter 3

Deep Learning in Computer Vision

Upon observing almost any visual scene, humans are able to effortlessly cut it up into segments of distinct objects [1]. This is a remarkable ability considering that the world we live in can present us with an infinite amount of visual variation to our retinas and yet we are able to easily recognize tens of thousands of distinct categories [?] with invariance to various factors such as lighting, shade, orientation and partial occlusion [?]. Replicating this type of performance in artificial object recognition has been one of the main focuses of computer vision researchers over the past several decades.

Bibliography

- [1] E. Rosch, C. B. Mervis, W. D. Gray, D. M. Johnson, and P. Boyes-Braem, “Basic objects in natural categories,” *Cognitive Psychology*, vol. 8, no. 3, pp. 382–439, 1976.
- [2] P. Joliceur, M. A. Gluck, and S. M. Kosslyn, “Pictures and Naming: Making the Connection,” *Cognitive Psychology*, vol. 16, pp. 243–275, 1984.
- [3] J. C. Peterson, P. Soulos, A. Nematzadeh, and T. L. Griffiths, “Learning Hierarchical Visual Representations in Deep Neural Networks Using Hierarchical Linguistic Labels,” 2018.
- [4] C. Szegedy, V. Vanhoucke, S. Ioffe, J. Shlens, and Z. Wojna, “Rethinking the Inception Architecture for Computer Vision,” 2015.
- [5] F. Xu and J. B. Tenenbaum, “Word learning as Bayesian inference.,” *Proceedings of the 22nd Annual Meeting of the Cognitive Science Society*, pp. 517–522, 2000.