

The CodeVideo Framework: Event Sourcing for IDE State Representation in Educational Software

Full Stack Craft LLC

January 1, 2025

Contents

1	Introduction	3
2	CodeVideo Framework Architecture and Abstraction Layers	3
2.1	Course	3
2.2	Lesson	3
2.3	Action	4
3	Actions in Detail	4
3.1	Action Granularity and Composition	5
4	Snapshots: Capturing the Full IDE State	6
5	Validators: Deterministic Quality Assurance	6
6	Renderers: Virtual Editors and CodeVideo Studio	7
7	Recorders: Capturing Actions in the CodeVideo Framework	7
7.1	Mouse and Keylogger Recorder	7
7.2	Video Recorder	7
8	Playback Mechanisms for Automated Video Generation	8
8.1	Temporal Abstract Syntax Tree Management	8
8.1.1	Formal Definition	8
8.1.2	Implementation Strategy	9
9	Applications For Datasets Used in Large Language Mod-	

els	10
10 Conclusion	10
A Appendix A - Example JSON of a Simple Console Logging Lesson for Javascript	10
B Appendix B - List of All Possible Actions within the CodeVideo Framework	12

1 Introduction

The rapid growth of online education has transformed the software learning experience, creating unprecedented demand for high-quality, interactive software courses. As instructional video content rises, so do the demands for editing, structuring, and delivering this content at scale—a process that is both resource-intensive and technically challenging.

In this document, we present *CodeVideo*, an event-sourcing-based framework designed to streamline the creation and management of software instructional videos. By simulating every interaction (keystrokes and or mouse interactions) in an Integrated Development Environment (IDE), the framework can produce deterministic, repeatable sequences that simulate a live coding session. The result is not only the ability to generate a static snapshot of the IDE state at any given time but also the capability to generate entire instructional videos programmatically, ensuring consistency and precision across sessions.

2 CodeVideo Framework Architecture and Abstraction Layers

The CodeVideo Framework represents a modular and highly abstracted approach to IDE-based video course creation. This section provides an in-depth look at its primary abstractions and the structured hierarchy that enables reproducible, fine-grained state control over IDE interactions. The three main components are Courses, Lessons, and Actions.

2.1 Course

At the topmost level of the *CodeVideo* framework, we define a course, C , represented by:

- A unique identifier, C_{id}
- A descriptive name, C_{name}
- A sequence of instructional units or lessons, $L = \{L_1, L_2, \dots, L_n\}$

2.2 Lesson

Each lesson, L , is composed of:

- An initial state snapshot of the project workspace, $S_{initial}$
- A sequence of discrete actions $A = \{a_1, a_2, \dots, a_m\}$

- A final state snapshot S_{final} that serves as the baseline for subsequent lessons

2.3 Action

Central to the framework is the concept of an *action*, the smallest unit of interaction within the IDE. Actions, represented as a_i , encode the following elements:

$$a_i : \text{action_type} \rightarrow \text{action_value}$$

Examples of action types include text entry commands, cursor movements, file modifications, and verbal narration cues. For instance:

- **Text Entry Action:**

$$\begin{aligned} a_{type} &= \text{"enter-text"} \\ a_{value} &= \text{"console.log('Hello, world!');"} \end{aligned}$$

- **Narration Action:**

$$\begin{aligned} a_{type} &= \text{"speak-before"} \\ a_{value} &= \text{"I'm going to log a message to the console."} \end{aligned}$$

3 Actions in Detail

Actions form the foundation of the entire foundation of the CodeVideo framework. From an abstract standpoint, an action should be able to handle any basic interaction that is possible with a computer. There are limited ways of interacting with a computer, in order of most common to least common:

- Keyboard: A keyboard has a large variety of keys, but they can be broken down into 3 categories: letters, numbers, and symbols.
- Mouse: a mouse has motion sensor, 3 buttons, and a scroll wheel.
- Trackpad: which have 1 button and a touch surface.
- Audio inputs (microphones), which represent a series of points at varying amplitudes.
- Video inputs (cameras), which represent a series of images.

These methods comprise all the possible inputs to a computer.

We abstract these inputs to three main categories of actions: keyboard, mouse, and multimedia (audio and video).

Within an IDE, there are then 3 target locations where these actions can be applied: the editor, the file tree, and the terminal.

To distinguish the location of each action, the action name is suffixed with the target location. For example, a keystroke in the editor is represented as *type – editor*, a left click in the file tree is *left – click – file – tree*, and speaking about something in the terminal is *speak – terminal*.

Appendix A provides a sample of a series of actions, representing a Console Logging Lesson for JavaScript.

Appendix B provides all possible action names within the CodeVideo framework.

3.1 Action Granularity and Composition

The framework implements a hierarchical action granularity system, where the base unit of interaction can be configured according to course requirements:

- **Atomic Actions** (Default): The finest level of granularity, capturing:
 - Individual keystrokes: $a_{key} = \{key : 'a', step : n\}$
 - Single cursor movements: $a_{cursor} = \{position : (x, y), step : n\}$
 - Mouse events: $a_{mouse} = \{type : 'click', position : (x, y), step : n\}$
- **Composed Actions**: Higher-level abstractions that can be configured:
 - Line-level changes: $a_{line} = \{content : string, lineNumber : n\}$
 - Block-level modifications: $a_{block} = \{content : string, range : (start, end)\}$
 - Semantic operations: $a_{semantic} = \{type : 'function-declaration', content : string\}$

The granularity level can be adjusted dynamically, with the framework maintaining the atomic actions internally while presenting a more abstract interface when desired:

$$A_{composed} = f(a_1, a_2, \dots, a_n) \text{ where } a_i \text{ are atomic actions}$$

4 Snapshots: Capturing the Full IDE State

Snapshots represent the entire state of the IDE at a given point, allowing for precise rollback and reproducibility:

$$S = \langle \text{metadata}, \\ \text{file_structure}, \\ \text{selected_file}, \\ \text{open_files}, \\ \text{editor_content}, \\ \text{caret_position}, \\ \text{terminal_content} \rangle$$

Where:

- **Metadata** contains high-level course information.
- **File Structure** denotes the directory tree visible in the IDE.
- **Selected File** and **Open Files** track active files.
- **Editor Content** and **Caret Position** record the current text and cursor position.
- **Terminal Content** displays command-line output.

5 Validators: Deterministic Quality Assurance

Each lesson's continuity is verified through a *snapshot validator*, to confirm that the content of the given project at the end of one lesson matches the initial state of the next lesson:

$$\forall i \in [1, n - 1], \quad S_{final}(L_i) = S_{initial}(L_{i+1})$$

If any two consecutive snapshots do not match, the validator throws an error, ensuring seamless progression across lessons.

6 Renderers: Virtual Editors and CodeVideo Studio

The CodeVideo framework integrates a *virtual editor*, which emulates IDE interactions in a standalone environment:

- The virtual editor provides snapshots on demand via *getProjectSnapshot()*, allowing course authors to generate real-time previews of each state.

The rendering engine, *CodeVideo Studio* (<https://studio.codevideo.io>), provides a visual representation within the IDE, enabling authors to edit actions dynamically and validate course accuracy.

7 Recorders: Capturing Actions in the CodeVideo Framework

The framework supports a range of recorders.

7.1 Mouse and Keylogger Recorder

The first record directly records mouse, keystrokes, and microphone audio:

- Keystrokes and cursor movements are recorded in the main editor.
- Interactions within the file tree, terminal, and narration windows are recorded and transformed to action format to build the repeatable and full IDE state representation.

7.2 Video Recorder

The second is visual-based, capturing the entire screen and using computer vision to detect and interpret user interactions:

- The visual recorder captures the entire screen, including the IDE and any additional windows.
- The video is broken into individual frames, and computer vision algorithms detect and interpret user interactions.
- The detected interactions are transformed into actions and used to build the repeatable and full IDE state representation.

8 Playback Mechanisms for Automated Video Generation

CodeVideo provides multiple playback mechanisms for automated video generation:

- **CodeVideo Studio** our main editor, based on a Monaco editor along side an action editor. Includes time travel and snapshot validation.
- **Monaco Editor Driver** for localhost single editor-based video generation (beta)
- **VSCode Driver** for localhost complete IDE editor-based video generation (beta)

8.1 Temporal Abstract Syntax Tree Management

Central to the framework’s refactoring capabilities is the concept of a Temporal Abstract Syntax Tree (TAST), which extends traditional AST manipulation to include logical time as a dimension. Simply described, this is the abstract syntax tree after every moment (action) in time. The concept of TASTs are not new, and have been explored in various works [moore2022temporal].

8.1.1 Formal Definition

A Temporal AST node at logical step n is defined as:

$$TAST_{node}(n) = \langle ID, Type, Value(n), Children(n), Metadata(n) \rangle$$

Where:

- ID is a unique identifier persisting across the action sequence
- $Type$ represents the node type (e.g., Identifier, FunctionDeclaration)
- $Value(n)$ is the node’s value at step n
- $Children(n)$ represents child nodes at step n
- $Metadata(n)$ stores additional information like scope and references

When performing retrospective modifications (e.g., variable renaming), the framework uses a forward propagation algorithm:

$$\forall m > n : TAST(m) = Apply(TAST(m-1), Modification(n))$$

The modification propagation follows these principles:

1. **Identity Preservation:** Node identities remain constant across the sequence, enabling tracking of elements despite name changes:

$$ID(TAST_{node}(n)) = ID(TAST_{node}(m)) \quad \forall n, m$$

2. **Reference Integrity:** All references to modified nodes are updated while maintaining semantic correctness:

$$Refs(TAST_{node}(m)) = UpdateRefs(Refs(TAST_{node}(n)), Modification(n))$$

3. **Scope Resolution:** Modifications respect lexical scoping rules across the logical sequence:

$$Scope(TAST_{node}(m)) = ResolveScope(Scope(TAST_{node}(n)), Environment(m))$$

8.1.2 Implementation Strategy

The framework implements temporal AST modifications through a combination of:

- Forward replay with modification injection
- Lazy evaluation of affected subtrees
- Cached intermediate states for performance optimization

This approach enables complex refactoring operations while maintaining the integrity of the recorded action sequence. For example, when renaming a variable at step n , the system:

1. Captures the modification intent: $M = \{type : "rename", target : ID, newValue : name\}$
2. Identifies all subsequent steps containing references to the target: $Steps_{affected} = \{m | m \geq n \wedge HasRef(TAST(m), ID)\}$
3. Applies the modification across all affected steps while preserving other concurrent modifications

9 Applications For Datasets Used in Large Language Models

A large component of context missing from large language models and transformers is this exact travel-through-time context. By including the full correct and complete steps to creating software, either through the array of actions or a TAST to LLM training data, we can provide a more comprehensive dataset for coding training data.

10 Conclusion

The *CodeVideo* framework offers a robust, reproducible method for generating IDE-based educational content, reducing manual editing and increasing course consistency. With its event-sourcing architecture, the framework not only captures precise IDE states but also provides a platform for creating interactive, context-rich programming tutorials.

A Appendix A - Example JSON of a Simple Console Logging Lesson for Javascript

```
[
  {
    "name": "speak-before",
    "value": "Today, we're going to learn about how to
    ↪ use the console.log function in JavaScript."
  },
  {
    "name": "speak-before",
    "value": "I've already got a hello-world.js file
    ↪ prepared here - let's open it up."
  },
  {
    "name": "click-filename",
    "value": "hello-world.js"
  },
  {
    "name": "click-editor",
    "value": "1"
  },
  {
    "name": "speak-before",
```

```

    "value": "Now, to log things to your console,
    ↪ simply make a call to the console.log function,
    ↪ passing in the text you want to log."
  },
  {
    "name": "type-editor",
    "value": "console.log('Hello, world!');"
  },
  {
    "name": "save",
    "value": "1"
  },
  {
    "name": "speak-before",
    "value": "Now we'll open up a terminal and run this
    ↪ file."
  },
  {
    "name": "open-terminal",
    "value": "1"
  },
  {
    "name": "click-terminal",
    "value": "1"
  },
  {
    "name": "type-terminal",
    "value": "node hello-world.js"
  },
  {
    "name": "enter",
    "value": "1"
  },
  {
    "name": "wait",
    "value": "2000"
  },
  {
    "name": "speak-before",
    "value": "And of course we get the expected output
    ↪ - 'hello world!' printed to the console."
  },
  {

```

```

    "name": "speak-before",
    "value": "And that's about it! You now know how to
    ↪ log things to your console in JavaScript!"
  }
]

```

B Appendix B - List of All Possible Actions within the CodeVideo Framework

Key Combination	Context	Code
editor Bindings		
`	editor	Backquote-editor
Shift+{	editor	Shift+Backquote-editor
1	editor	Digit1-editor
Shift+!	editor	Shift+Digit1-editor
2	editor	Digit2-editor
Shift+@	editor	Shift+Digit2-editor
3	editor	Digit3-editor
Shift+#	editor	Shift+Digit3-editor
4	editor	Digit4-editor
Shift+\$	editor	Shift+Digit4-editor
5	editor	Digit5-editor
Shift+%	editor	Shift+Digit5-editor
6	editor	Digit6-editor
Shift+{	editor	Shift+Digit6-editor
7	editor	Digit7-editor
Shift+&	editor	Shift+Digit7-editor
8	editor	Digit8-editor
Shift+*	editor	Shift+Digit8-editor
9	editor	Digit9-editor
Shift+(editor	Shift+Digit9-editor
0	editor	Digit0-editor
Shift+)	editor	Shift+Digit0-editor
-	editor	Minus-editor
Shift+_	editor	Shift+Minus-editor
=	editor	Equal-editor
Shift++	editor	Shift+Equal-editor
q	editor	KeyQ-editor
Shift+Q	editor	Shift+KeyQ-editor
w	editor	KeyW-editor
Shift+W	editor	Shift+KeyW-editor

Key Combination	Context	Code
e	editor	KeyE-editor
Shift+E	editor	Shift+KeyE-editor
r	editor	KeyR-editor
Shift+R	editor	Shift+KeyR-editor
t	editor	KeyT-editor
Shift+T	editor	Shift+KeyT-editor
y	editor	KeyY-editor
Shift+Y	editor	Shift+KeyY-editor
u	editor	KeyU-editor
Shift+U	editor	Shift+KeyU-editor
i	editor	KeyI-editor
Shift+I	editor	Shift+KeyI-editor
o	editor	KeyO-editor
Shift+O	editor	Shift+KeyO-editor
p	editor	KeyP-editor
Shift+P	editor	Shift+KeyP-editor
[editor	BracketLeft-editor
Shift+{	editor	Shift+BracketLeft-editor
]	editor	BracketRight-editor
Shift+}	editor	Shift+BracketRight-editor
\{ }	editor	Backslash-editor
Shift+	editor	Shift+Backslash-editor
a	editor	KeyA-editor
Shift+A	editor	Shift+KeyA-editor
s	editor	KeyS-editor
Shift+S	editor	Shift+KeyS-editor
d	editor	KeyD-editor
Shift+D	editor	Shift+KeyD-editor
f	editor	KeyF-editor
Shift+F	editor	Shift+KeyF-editor
g	editor	KeyG-editor
Shift+G	editor	Shift+KeyG-editor
h	editor	KeyH-editor
Shift+H	editor	Shift+KeyH-editor
j	editor	KeyJ-editor
Shift+J	editor	Shift+KeyJ-editor
k	editor	KeyK-editor
Shift+K	editor	Shift+KeyK-editor
l	editor	KeyL-editor
Shift+L	editor	Shift+KeyL-editor
;	editor	Semicolon-editor

Key Combination	Context	Code
Shift+:	editor	Shift+Semicolon-editor
,	editor	Quote-editor
Shift+”	editor	Shift+Quote-editor
z	editor	KeyZ-editor
Shift+Z	editor	Shift+KeyZ-editor
x	editor	KeyX-editor
Shift+X	editor	Shift+KeyX-editor
c	editor	KeyC-editor
Shift+C	editor	Shift+KeyC-editor
v	editor	KeyV-editor
Shift+V	editor	Shift+KeyV-editor
b	editor	KeyB-editor
Shift+B	editor	Shift+KeyB-editor
n	editor	KeyN-editor
Shift+N	editor	Shift+KeyN-editor
m	editor	KeyM-editor
Shift+M	editor	Shift+KeyM-editor
,	editor	Comma-editor
Shift+<	editor	Shift+Comma-editor
.	editor	Period-editor
Shift+>	editor	Shift+Period-editor
/	editor	Slash-editor
Shift+?	editor	Shift+Slash-editor
	editor	Space-editor
terminal Bindings		
‘	terminal	Backquote-terminal
Shift+{ }	terminal	Shift+Backquote-terminal
1	terminal	Digit1-terminal
Shift+!	terminal	Shift+Digit1-terminal
2	terminal	Digit2-terminal
Shift+@	terminal	Shift+Digit2-terminal
3	terminal	Digit3-terminal
Shift+#	terminal	Shift+Digit3-terminal
4	terminal	Digit4-terminal
Shift+\$	terminal	Shift+Digit4-terminal
5	terminal	Digit5-terminal
Shift+%	terminal	Shift+Digit5-terminal
6	terminal	Digit6-terminal
Shift+{ }	terminal	Shift+Digit6-terminal
7	terminal	Digit7-terminal

Key Combination	Context	Code
Shift+&	terminal	Shift+Digit7-terminal
8	terminal	Digit8-terminal
Shift+*	terminal	Shift+Digit8-terminal
9	terminal	Digit9-terminal
Shift+(terminal	Shift+Digit9-terminal
0	terminal	Digit0-terminal
Shift+)	terminal	Shift+Digit0-terminal
-	terminal	Minus-terminal
Shift+_	terminal	Shift+Minus-terminal
=	terminal	Equal-terminal
Shift++	terminal	Shift+Equal-terminal
q	terminal	KeyQ-terminal
Shift+Q	terminal	Shift+KeyQ-terminal
w	terminal	KeyW-terminal
Shift+W	terminal	Shift+KeyW-terminal
e	terminal	KeyE-terminal
Shift+E	terminal	Shift+KeyE-terminal
r	terminal	KeyR-terminal
Shift+R	terminal	Shift+KeyR-terminal
t	terminal	KeyT-terminal
Shift+T	terminal	Shift+KeyT-terminal
y	terminal	KeyY-terminal
Shift+Y	terminal	Shift+KeyY-terminal
u	terminal	KeyU-terminal
Shift+U	terminal	Shift+KeyU-terminal
i	terminal	KeyI-terminal
Shift+I	terminal	Shift+KeyI-terminal
o	terminal	KeyO-terminal
Shift+O	terminal	Shift+KeyO-terminal
p	terminal	KeyP-terminal
Shift+P	terminal	Shift+KeyP-terminal
[terminal	BracketLeft-terminal
Shift+{	terminal	Shift+BracketLeft-terminal
]	terminal	BracketRight-terminal
Shift+}	terminal	Shift+BracketRight-terminal
\{ }	terminal	Backslash-terminal
Shift+	terminal	Shift+Backslash-terminal
a	terminal	KeyA-terminal
Shift+A	terminal	Shift+KeyA-terminal
s	terminal	KeyS-terminal
Shift+S	terminal	Shift+KeyS-terminal

Key Combination	Context	Code
d	terminal	KeyD-terminal
Shift+D	terminal	Shift+KeyD-terminal
f	terminal	KeyF-terminal
Shift+F	terminal	Shift+KeyF-terminal
g	terminal	KeyG-terminal
Shift+G	terminal	Shift+KeyG-terminal
h	terminal	KeyH-terminal
Shift+H	terminal	Shift+KeyH-terminal
j	terminal	KeyJ-terminal
Shift+J	terminal	Shift+KeyJ-terminal
k	terminal	KeyK-terminal
Shift+K	terminal	Shift+KeyK-terminal
l	terminal	KeyL-terminal
Shift+L	terminal	Shift+KeyL-terminal
;	terminal	Semicolon-terminal
Shift+:	terminal	Shift+Semicolon-terminal
'	terminal	Quote-terminal
Shift+”	terminal	Shift+Quote-terminal
z	terminal	KeyZ-terminal
Shift+Z	terminal	Shift+KeyZ-terminal
x	terminal	KeyX-terminal
Shift+X	terminal	Shift+KeyX-terminal
c	terminal	KeyC-terminal
Shift+C	terminal	Shift+KeyC-terminal
v	terminal	KeyV-terminal
Shift+V	terminal	Shift+KeyV-terminal
b	terminal	KeyB-terminal
Shift+B	terminal	Shift+KeyB-terminal
n	terminal	KeyN-terminal
Shift+N	terminal	Shift+KeyN-terminal
m	terminal	KeyM-terminal
Shift+M	terminal	Shift+KeyM-terminal
,	terminal	Comma-terminal
Shift+<	terminal	Shift+Comma-terminal
.	terminal	Period-terminal
Shift+>	terminal	Shift+Period-terminal
/	terminal	Slash-terminal
Shift+?	terminal	Shift+Slash-terminal
	terminal	Space-terminal
file-tree Bindings		

Key Combination	Context	Code
`	file-tree	Backquote-file-tree
Shift+{ }	file-tree	Shift+Backquote-file-tree
1	file-tree	Digit1-file-tree
Shift+!	file-tree	Shift+Digit1-file-tree
2	file-tree	Digit2-file-tree
Shift+@	file-tree	Shift+Digit2-file-tree
3	file-tree	Digit3-file-tree
Shift+#	file-tree	Shift+Digit3-file-tree
4	file-tree	Digit4-file-tree
Shift+\$	file-tree	Shift+Digit4-file-tree
5	file-tree	Digit5-file-tree
Shift+%	file-tree	Shift+Digit5-file-tree
6	file-tree	Digit6-file-tree
Shift+{ }	file-tree	Shift+Digit6-file-tree
7	file-tree	Digit7-file-tree
Shift+&	file-tree	Shift+Digit7-file-tree
8	file-tree	Digit8-file-tree
Shift+*	file-tree	Shift+Digit8-file-tree
9	file-tree	Digit9-file-tree
Shift+(file-tree	Shift+Digit9-file-tree
0	file-tree	Digit0-file-tree
Shift+)	file-tree	Shift+Digit0-file-tree
-	file-tree	Minus-file-tree
Shift+_	file-tree	Shift+Minus-file-tree
=	file-tree	Equal-file-tree
Shift++	file-tree	Shift+Equal-file-tree
q	file-tree	KeyQ-file-tree
Shift+Q	file-tree	Shift+KeyQ-file-tree
w	file-tree	KeyW-file-tree
Shift+W	file-tree	Shift+KeyW-file-tree
e	file-tree	KeyE-file-tree
Shift+E	file-tree	Shift+KeyE-file-tree
r	file-tree	KeyR-file-tree
Shift+R	file-tree	Shift+KeyR-file-tree
t	file-tree	KeyT-file-tree
Shift+T	file-tree	Shift+KeyT-file-tree
y	file-tree	KeyY-file-tree
Shift+Y	file-tree	Shift+KeyY-file-tree
u	file-tree	KeyU-file-tree
Shift+U	file-tree	Shift+KeyU-file-tree
i	file-tree	KeyI-file-tree

Key Combination	Context	Code
Shift+I	file-tree	Shift+KeyI-file-tree
o	file-tree	KeyO-file-tree
Shift+O	file-tree	Shift+KeyO-file-tree
p	file-tree	KeyP-file-tree
Shift+P	file-tree	Shift+KeyP-file-tree
[file-tree	BracketLeft-file-tree
Shift+{	file-tree	Shift+BracketLeft-file-tree
]	file-tree	BracketRight-file-tree
Shift+}	file-tree	Shift+BracketRight-file-tree
\{ }	file-tree	Backslash-file-tree
Shift+	file-tree	Shift+Backslash-file-tree
a	file-tree	KeyA-file-tree
Shift+A	file-tree	Shift+KeyA-file-tree
s	file-tree	KeyS-file-tree
Shift+S	file-tree	Shift+KeyS-file-tree
d	file-tree	KeyD-file-tree
Shift+D	file-tree	Shift+KeyD-file-tree
f	file-tree	KeyF-file-tree
Shift+F	file-tree	Shift+KeyF-file-tree
g	file-tree	KeyG-file-tree
Shift+G	file-tree	Shift+KeyG-file-tree
h	file-tree	KeyH-file-tree
Shift+H	file-tree	Shift+KeyH-file-tree
j	file-tree	KeyJ-file-tree
Shift+J	file-tree	Shift+KeyJ-file-tree
k	file-tree	KeyK-file-tree
Shift+K	file-tree	Shift+KeyK-file-tree
l	file-tree	KeyL-file-tree
Shift+L	file-tree	Shift+KeyL-file-tree
;	file-tree	Semicolon-file-tree
Shift+:	file-tree	Shift+Semicolon-file-tree
'	file-tree	Quote-file-tree
Shift+”	file-tree	Shift+Quote-file-tree
z	file-tree	KeyZ-file-tree
Shift+Z	file-tree	Shift+KeyZ-file-tree
x	file-tree	KeyX-file-tree
Shift+X	file-tree	Shift+KeyX-file-tree
c	file-tree	KeyC-file-tree
Shift+C	file-tree	Shift+KeyC-file-tree
v	file-tree	KeyV-file-tree
Shift+V	file-tree	Shift+KeyV-file-tree

Key Combination	Context	Code
b	file-tree	KeyB-file-tree
Shift+B	file-tree	Shift+KeyB-file-tree
n	file-tree	KeyN-file-tree
Shift+N	file-tree	Shift+KeyN-file-tree
m	file-tree	KeyM-file-tree
Shift+M	file-tree	Shift+KeyM-file-tree
,	file-tree	Comma-file-tree
Shift+<	file-tree	Shift+Comma-file-tree
.	file-tree	Period-file-tree
Shift+>	file-tree	Shift+Period-file-tree
/	file-tree	Slash-file-tree
Shift+?	file-tree	Shift+Slash-file-tree
	file-tree	Space-file-tree