

PRACTICAL 1

Aim: Develop the presentation layer of Library Management software application with suitable menus.

Library.java

```
import java.awt.BorderLayout;
import java.awt.EventQueue;
import javax.swing.JFrame;
import javax.swing.JPanel;
import javax.swing.border.EmptyBorder;
import javax.swing.GroupLayout;
import javax.swing.GroupLayout.Alignment;
import javax.swing.JLabel;
import java.awt.Color;
import java.awt.Font;
import javax.swing.JButton;
import javax.swing.LayoutStyle.ComponentPlacement;
import java.awt.event.ActionListener;
import java.awt.event.ActionEvent;

public class Library extends JFrame {
    static Library frame;
    private JPanel contentPane;

    /**
     * Launch the application.
     */
    public static void main(String[] args) {
        EventQueue.invokeLater(new Runnable() {
            public void run() {
                try {
                    frame= new Library();
                    frame.setVisible(true);
                } catch (Exception e) {
                    e.printStackTrace();
                }
            }
        });
    }

    /**
     * Create the frame.
     */
    public Library() {
        setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
        setBounds(100, 100, 450, 300);
        contentPane = new JPanel();
        contentPane.setBorder(new EmptyBorder(5, 5, 5, 5));
        setContentPane(contentPane);
```

```
JLabel lblLibraryManagement = new JLabel("Library Management ");
lblLibraryManagement.setFont(new Font("Tahoma", Font.PLAIN, 18));
lblLibraryManagement.setForeground(Color.GRAY);

JButton btnAdminLogin = new JButton("Admin Login");
btnAdminLogin.addActionListener(new ActionListener() {
    public void actionPerformed(ActionEvent e) {
        AdminLogin.main(new String[]{});
        frame.dispose();
    }
});
btnAdminLogin.setFont(new Font("Tahoma", Font.PLAIN, 15));

JButton btnLibrarianLogin = new JButton("Librarian Login");
btnLibrarianLogin.addActionListener(new ActionListener() {
    public void actionPerformed(ActionEvent arg0) {
        LibrarianLogin.main(new String[]{});
    }
});
btnLibrarianLogin.setFont(new Font("Tahoma", Font.PLAIN, 15));
GroupLayout gl_contentPane = new GroupLayout(contentPane);
gl_contentPane.setHorizontalGroup(
    gl_contentPane.createParallelGroup(Alignment.LEADING)
        .addGroup(gl_contentPane.createSequentialGroup()

.addGroup(gl_contentPane.createParallelGroup(Alignment.LEADING)

.addGroup(gl_contentPane.createSequentialGroup()
                    .addGap(64)

.addComponent(lblLibraryManagement))

.addGroup(gl_contentPane.createSequentialGroup()
                    .addGap(140)

.addGroup(gl_contentPane.createParallelGroup(Alignment.TRAILING, false)

.addComponent(btnLibrarianLogin, Alignment.LEADING,
GroupLayout.DEFAULT_SIZE, GroupLayout.DEFAULT_SIZE, Short.MAX_VALUE)
                    .addComponent(btnAdminLogin,
Alignment.LEADING, GroupLayout.DEFAULT_SIZE, 135, Short.MAX_VALUE))))
        .addContainerGap(95, Short.MAX_VALUE))
);
gl_contentPane.setVerticalGroup(
    gl_contentPane.createParallelGroup(Alignment.LEADING)
        .addGroup(gl_contentPane.createSequentialGroup()

.addComponent(lblLibraryManagement)
                    .addGap(32)
```

```

                                .addComponent(btnAdminLogin,
GroupLayout.PREFERRED_SIZE, 52, GroupLayout.PREFERRED_SIZE)

                                .addPreferredGap(ComponentPlacement.UNRELATED)
                                .addComponent(btnLibrarianLogin,
GroupLayout.PREFERRED_SIZE, 53, GroupLayout.PREFERRED_SIZE)
                                .addContainerGap(70, Short.MAX_VALUE))
        );
        contentPane.setLayout(gl_contentPane);
    }
}

```

AdminLogin.java

```

import java.awt.BorderLayout;
import java.awt.EventQueue;

import javax.swing.JFrame;
import javax.swing.JPanel;
import javax.swing.border.EmptyBorder;
import javax.swing.GroupLayout;
import javax.swing.GroupLayout.Alignment;
import javax.swing.JLabel;
import javax.swing.JOptionPane;

import java.awt.Font;
import java.awt.Color;
import javax.swing.JTextField;
import javax.swing.JButton;
import java.awt.event.ActionListener;
import java.awt.event.ActionEvent;
import javax.swing.JPasswordField;

public class AdminLogin extends JFrame {
    static AdminLogin frame;
    private JPanel contentPane;
    private JTextField textField;
    private JPasswordField passwordField;

    /**
     * Launch the application.
     */
    public static void main(String[] args) {
        EventQueue.invokeLater(new Runnable() {
            public void run() {
                try {
                    frame = new AdminLogin();
                    frame.setVisible(true);
                } catch (Exception e) {
                    e.printStackTrace();
                }
            }
        });
    }
}

```

```

    }
    }
    });
}

/**
 * Create the frame.
 */
public AdminLogin() {
    setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
    setBounds(100, 100, 450, 300);
    contentPane = new JPanel();
    contentPane.setBorder(new EmptyBorder(5, 5, 5, 5));
    setContentPane(contentPane);

    JLabel lblAdminLoginForm = new JLabel("Admin Login Form");
    lblAdminLoginForm.setForeground(Color.GRAY);
    lblAdminLoginForm.setFont(new Font("Tahoma", Font.PLAIN, 18));

    JLabel lblEnterName = new JLabel("Enter Name:");

    JLabel lblEnterPassword = new JLabel("Enter Password:");

    textField = new JTextField();
    textField.setColumns(10);

    JButton btnLogin = new JButton("Login");
    btnLogin.addActionListener(new ActionListener() {
        public void actionPerformed(ActionEvent e) {
            String name=textField.getText();
            String password=String.valueOf(passwordField.getPassword());
            if(name.equals("admin")&&password.equals("admin123")){
                AdminSuccess.main(new String[] {});
                frame.dispose();
            }else{
                JOptionPane.showMessageDialog(AdminLogin.this, "Sorry,
Username or Password Error", "Login Error!", JOptionPane.ERROR_MESSAGE);
                textField.setText("");
                passwordField.setText("");
            }
        }
    });

    passwordField = new JPasswordField();
    GroupLayout gl_contentPane = new GroupLayout(contentPane);
    gl_contentPane.setHorizontalGroup(
        gl_contentPane.createParallelGroup(Alignment.TRAILING)
            .addGroup(gl_contentPane.createSequentialGroup()
                .addGroup(gl_contentPane.createParallelGroup(Alignment.LEADING)
                    .add(btnLogin)
                    .add(passwordField)
                    .add(textField)
                )
            )
    );
    gl_contentPane.setVerticalGroup(
        gl_contentPane.createParallelGroup(Alignment.LEADING)
            .addGroup(gl_contentPane.createSequentialGroup()
                .add(textField)
                .add(passwordField)
                .add(btnLogin)
            )
    );
    contentPane.setLayout(gl_contentPane);
}

```

```

        .addGroup(gl_contentPane.createSequentialGroup()
                    .addGap(124)
                    .addComponent(lblAdminLoginForm))

        .addGroup(gl_contentPane.createSequentialGroup()
                    .addGap(19)

        .addGroup(gl_contentPane.createParallelGroup(Alignment.LEADING)
                    .addComponent(lblEnterName)

        .addComponent(lblEnterPassword))
                    .addGap(47)

        .addGroup(gl_contentPane.createParallelGroup(Alignment.LEADING, false)
                    .addComponent(passwordField)
                    .addComponent(textField,
 GroupLayout.DEFAULT_SIZE, 172, Short.MAX_VALUE))))
                    .addContainerGap(107, Short.MAX_VALUE))
                    .addGroup(gl_contentPane.createSequentialGroup()
                    .addContainerGap(187, Short.MAX_VALUE)
                    .addComponent(btnLogin,
 GroupLayout.PREFERRED_SIZE, 86, GroupLayout.PREFERRED_SIZE)
                    .addGap(151))
        );
        gl_contentPane.setVerticalGroup(
            gl_contentPane.createParallelGroup(Alignment.LEADING)
                .addGroup(gl_contentPane.createSequentialGroup()
                    .addComponent(lblAdminLoginForm)
                    .addGap(26)

        .addGroup(gl_contentPane.createParallelGroup(Alignment.BASELINE)
                    .addComponent(lblEnterName)
                    .addComponent(textField,
 GroupLayout.PREFERRED_SIZE, GroupLayout.DEFAULT_SIZE,
 GroupLayout.PREFERRED_SIZE))
                    .addGap(28)

        .addGroup(gl_contentPane.createParallelGroup(Alignment.BASELINE)
                    .addComponent(lblEnterPassword)
                    .addComponent(passwordField,
 GroupLayout.PREFERRED_SIZE, GroupLayout.DEFAULT_SIZE,
 GroupLayout.PREFERRED_SIZE))
                    .addGap(18)
                    .addComponent(btnLogin,
 GroupLayout.PREFERRED_SIZE, 37, GroupLayout.PREFERRED_SIZE)
                    .addContainerGap(80, Short.MAX_VALUE))
        );
        contentPane.setLayout(gl_contentPane);
    }

```

```
}
```

AdminSuccess.java

```
import java.awt.BorderLayout;
import java.awt.EventQueue;

import javax.swing.JFrame;
import javax.swing.JPanel;
import javax.swing.border.EmptyBorder;
import javax.swing.GroupLayout;
import javax.swing.GroupLayout.Alignment;
import javax.swing.JLabel;
import java.awt.Color;
import java.awt.Font;
import javax.swing.JButton;
import java.awt.event.ActionListener;
import java.awt.event.ActionEvent;
import javax.swing.LayoutStyle.ComponentPlacement;
import java.sql.*;

public class AdminSuccess extends JFrame {
    static AdminSuccess frame;
    private JPanel contentPane;

    /**
     * Launch the application.
     */
    public static void main(String[] args) {
        EventQueue.invokeLater(new Runnable() {
            public void run() {
                try {
                    frame = new AdminSuccess();
                    frame.setVisible(true);
                } catch (Exception e) {
                    e.printStackTrace();
                }
            }
        });
    }

    /**
     * Create the frame.
     */
    public AdminSuccess() {
        setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
        setBounds(100, 100, 450, 371);
        contentPane = new JPanel();
        contentPane.setBorder(new EmptyBorder(5, 5, 5, 5));
        setContentPane(contentPane);

        JLabel lblAdminSection = new JLabel("Admin Section");
```

```

lblAdminSection.setFont(new Font("Tahoma", Font.PLAIN, 22));
lblAdminSection.setForeground(Color.GRAY);

JButton btnNewButton = new JButton("Add Librarian");
btnNewButton.setFont(new Font("Tahoma", Font.PLAIN, 15));
btnNewButton.addActionListener(new ActionListener() {
    public void actionPerformed(ActionEvent e) {
        LibrarianForm.main(new String[]{});
        frame.dispose();
    }
});

JButton btnViewLibrarian = new JButton("View Librarian");
btnViewLibrarian.addActionListener(new ActionListener() {
    public void actionPerformed(ActionEvent arg0) {
        ViewLibrarian.main(new String[]{});
    }
});
btnViewLibrarian.setFont(new Font("Tahoma", Font.PLAIN, 15));

JButton btnDeleteLibrarian = new JButton("Delete Librarian");
btnDeleteLibrarian.addActionListener(new ActionListener() {
    public void actionPerformed(ActionEvent e) {
        DeleteLibrarian.main(new String[]{});
        frame.dispose();
    }
});
btnDeleteLibrarian.setFont(new Font("Tahoma", Font.PLAIN, 15));

JButton btnLogout = new JButton("Logout");
btnLogout.addActionListener(new ActionListener() {
    public void actionPerformed(ActionEvent arg0) {
        Library.main(new String[]{});
        frame.dispose();
    }
});
btnLogout.setFont(new Font("Tahoma", Font.PLAIN, 15));
GroupLayout gl_contentPane = new GroupLayout(contentPane);
gl_contentPane.setHorizontalGroup(
    gl_contentPane.createParallelGroup(Alignment.TRAILING)
        .addGroup(gl_contentPane.createSequentialGroup()
            .addContainerGap(150, Short.MAX_VALUE)
            .addComponent(lblAdminSection,
                GroupLayout.PREFERRED_SIZE, 151, GroupLayout.PREFERRED_SIZE)
            .addGap(123))
        .addGroup(Alignment.LEADING,
            gl_contentPane.createSequentialGroup()
                .addGap(134)

                .addGroup(gl_contentPane.createParallelGroup(Alignment.LEADING)

```

```

        .addComponent(btnLogout,
        GroupLayout.PREFERRED_SIZE, 181, GroupLayout.PREFERRED_SIZE)
        .addComponent(btnDeleteLibrarian,
        GroupLayout.PREFERRED_SIZE, 181, GroupLayout.PREFERRED_SIZE)
        .addComponent(btnViewLibrarian,
        GroupLayout.PREFERRED_SIZE, 181, GroupLayout.PREFERRED_SIZE)
        .addComponent(btnNewButton,
        GroupLayout.PREFERRED_SIZE, 181, GroupLayout.PREFERRED_SIZE))
        .addContainerGap(109, Short.MAX_VALUE))
    );
    gl_contentPane.setVerticalGroup(
        gl_contentPane.createParallelGroup(Alignment.LEADING)
        .addGroup(gl_contentPane.createSequentialGroup()
        .addComponent(lblAdminSection,
        GroupLayout.PREFERRED_SIZE, 40, GroupLayout.PREFERRED_SIZE)
        .addGap(11)
        .addComponent(btnNewButton,
        GroupLayout.PREFERRED_SIZE, 49, GroupLayout.PREFERRED_SIZE)
        .addGap(18)
        .addComponent(btnViewLibrarian,
        GroupLayout.PREFERRED_SIZE, 49, GroupLayout.PREFERRED_SIZE)
        .addGap(18)
        .addComponent(btnDeleteLibrarian,
        GroupLayout.PREFERRED_SIZE, 49, GroupLayout.PREFERRED_SIZE)
        .addGap(18)
        .addComponent(btnLogout,
        GroupLayout.PREFERRED_SIZE, 49, GroupLayout.PREFERRED_SIZE)
        .addContainerGap(21, Short.MAX_VALUE))
    );
    contentPane.setLayout(gl_contentPane);
}
}

```

LibrarianLogin.java

```

import java.awt.BorderLayout;
import java.awt.EventQueue;

import javax.swing.JFrame;
import javax.swing.JPanel;
import javax.swing.border.EmptyBorder;
import javax.swing.GroupLayout;
import javax.swing.GroupLayout.Alignment;
import javax.swing.JLabel;
import javax.swing.JOptionPane;

import java.awt.Font;
import java.awt.Color;
import javax.swing.JTextField;
import javax.swing.JButton;
import java.awt.event.ActionListener;

```



```

import java.awt.event.ActionEvent;
import javax.swing.JPasswordField;

public class LibrarianLogin extends JFrame {
    static LibrarianLogin frame;
    private JPanel contentPane;
    private JTextField textField;
    private JPasswordField passwordField;

    /**
     * Launch the application.
     */
    public static void main(String[] args) {
        EventQueue.invokeLater(new Runnable() {
            public void run() {
                try {
                    frame = new LibrarianLogin();
                    frame.setVisible(true);
                } catch (Exception e) {
                    e.printStackTrace();
                }
            }
        });
    }

    /**
     * Create the frame.
     */
    public LibrarianLogin() {
        setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
        setBounds(100, 100, 450, 300);
        contentPane = new JPanel();
        contentPane.setBorder(new EmptyBorder(5, 5, 5, 5));
        setContentPane(contentPane);

        JLabel lblAdminLoginForm = new JLabel("Librarian Login Form");
        lblAdminLoginForm.setForeground(Color.GRAY);
        lblAdminLoginForm.setFont(new Font("Tahoma", Font.PLAIN, 18));

        JLabel lblEnterName = new JLabel("Enter Name:");

        JLabel lblEnterPassword = new JLabel("Enter Password:");

        textField = new JTextField();
        textField.setColumns(10);

        JButton btnLogin = new JButton("Login");
        btnLogin.addActionListener(new ActionListener() {
            public void actionPerformed(ActionEvent e) {
                String name=textField.getText();
            }
        });
    }
}

```

```

        String password=String.valueOf(passwordField.getPassword());
        if(name.equals("raana")&&password.equals("raana123")){
            LibrarianSuccess.main(new String[] {});
            frame.dispose();
        }else{
            JOptionPane.showMessageDialog(LibrarianLogin.this, "Sorry,
Username or Password Error","Login Error!", JOptionPane.ERROR_MESSAGE);
            textField.setText("");
            passwordField.setText("");
        }
    }
});

passwordField = new JPasswordField();
GroupLayout gl_contentPane = new GroupLayout(contentPane);
gl_contentPane.setHorizontalGroup(
    gl_contentPane.createParallelGroup(Alignment.TRAILING)
        .addGroup(gl_contentPane.createSequentialGroup()

.addGroup(gl_contentPane.createParallelGroup(Alignment.LEADING)

.addGroup(gl_contentPane.createSequentialGroup()
                    .addGap(124)
                    .addComponent(lblAdminLoginForm))

.addGroup(gl_contentPane.createSequentialGroup()
                    .addGap(19)

.addGroup(gl_contentPane.createParallelGroup(Alignment.LEADING)
                    .addComponent(lblEnterName)

.addComponent(lblEnterPassword))
                    .addGap(47)

.addGroup(gl_contentPane.createParallelGroup(Alignment.LEADING, false)
                    .addComponent(passwordField)
                    .addComponent(textField,
GroupLayout.DEFAULT_SIZE, 172, Short.MAX_VALUE))))
        .addContainerGap(107, Short.MAX_VALUE))
        .addGroup(gl_contentPane.createSequentialGroup()
            .addContainerGap(187, Short.MAX_VALUE)
            .addComponent(btnLogin,
GroupLayout.PREFERRED_SIZE, 86, GroupLayout.PREFERRED_SIZE)
            .addGap(151))
);
gl_contentPane.setVerticalGroup(
    gl_contentPane.createParallelGroup(Alignment.LEADING)
        .addGroup(gl_contentPane.createSequentialGroup()
            .addComponent(lblAdminLoginForm)
            .addGap(26)

```

```

        .addGroup(gl_contentPane.createParallelGroup(Alignment.BASELINE)
                    .addComponent(lblEnterName)
                    .addComponent(textField,
GroupLayout.PREFERRED_SIZE, GroupLayout.DEFAULT_SIZE,
GroupLayout.PREFERRED_SIZE))
                .addGap(28)

        .addGroup(gl_contentPane.createParallelGroup(Alignment.BASELINE)
                    .addComponent(lblEnterPassword)
                    .addComponent(passwordField,
GroupLayout.PREFERRED_SIZE, GroupLayout.DEFAULT_SIZE,
GroupLayout.PREFERRED_SIZE))
                .addGap(18)
                .addComponent(btnLogin,
GroupLayout.PREFERRED_SIZE, 37, GroupLayout.PREFERRED_SIZE)
                .addContainerGap(80, Short.MAX_VALUE))
    );
    contentPane.setLayout(gl_contentPane);
}
}

```

LibrarySuccess.java

```

import java.awt.BorderLayout;
import java.awt.EventQueue;

import javax.swing.JFrame;
import javax.swing.JPanel;
import javax.swing.border.EmptyBorder;
import javax.swing.GroupLayout;
import javax.swing.GroupLayout.Alignment;
import javax.swing.JLabel;
import java.awt.Font;
import java.awt.Color;
import javax.swing.JButton;
import java.awt.event.ActionListener;
import java.awt.event.ActionEvent;

public class LibrarianSuccess extends JFrame {
    static LibrarianSuccess frame;
    private JPanel contentPane;

    /**
     * Launch the application.
     */
    public static void main(String[] args) {
        EventQueue.invokeLater(new Runnable() {
            public void run() {
                try {
                    frame = new LibrarianSuccess();

```

```

        frame.setVisible(true);
    } catch (Exception e) {
        e.printStackTrace();
    }
}

});

}

/**
 * Create the frame.
 */
public LibrarianSuccess() {
    setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
    setBounds(100, 100, 450, 433);
    contentPane = new JPanel();
    contentPane.setForeground(Color.GRAY);
    contentPane.setBorder(new EmptyBorder(5, 5, 5, 5));
    setContentPane(contentPane);

    JLabel lblLibrarianSection = new JLabel("Librarian Section - JavaTpoint");
    lblLibrarianSection.setFont(new Font("Tahoma", Font.PLAIN, 22));

    JButton btnNewButton = new JButton("Add Books");
    btnNewButton.addActionListener(new ActionListener() {
        public void actionPerformed(ActionEvent e) {
            BooksForm.main(new String[] {});
            frame.dispose();
        }
    });
    btnNewButton.setFont(new Font("Tahoma", Font.PLAIN, 13));

    JButton btnViewBooks = new JButton("View Books");
    btnViewBooks.addActionListener(new ActionListener() {
        public void actionPerformed(ActionEvent arg0) {
            ViewBooks.main(new String[] {});
        }
    });
    btnViewBooks.setFont(new Font("Tahoma", Font.PLAIN, 13));

    JButton btnIssueBook = new JButton("Issue Book");
    btnIssueBook.addActionListener(new ActionListener() {
        public void actionPerformed(ActionEvent e) {
            IssueBookForm.main(new String[] {});
            frame.dispose();
        }
    });
    btnIssueBook.setFont(new Font("Tahoma", Font.PLAIN, 13));

    JButton btnViewIssuedBooks = new JButton("View Issued Books");
    btnViewIssuedBooks.addActionListener(new ActionListener() {

```

```

        public void actionPerformed(ActionEvent e) {
            ViewIssuedBooks.main(new String[] {});
        }
    });
    btnViewIssuedBooks.setFont(new Font("Tahoma", Font.PLAIN, 13));

    JButton btnReturnBook = new JButton("Return Book");
    btnReturnBook.addActionListener(new ActionListener() {
        public void actionPerformed(ActionEvent e) {
            ReturnBook.main(new String[] {});
            frame.dispose();
        }
    });
    btnReturnBook.setFont(new Font("Tahoma", Font.PLAIN, 13));

    JButton btnLogout = new JButton("Logout");
    btnLogout.addActionListener(new ActionListener() {
        public void actionPerformed(ActionEvent e) {
            Library.main(new String[] {});
            frame.dispose();
        }
    });
    btnLogout.setFont(new Font("Tahoma", Font.PLAIN, 13));
    GroupLayout gl_contentPane = new GroupLayout(contentPane);
    gl_contentPane.setHorizontalGroup(
        gl_contentPane.createParallelGroup(Alignment.LEADING)
            .addGroup(Alignment.TRAILING,
                gl_contentPane.createSequentialGroup()
                    .addContainerGap(81, Short.MAX_VALUE)
                    .addComponent(lblLibrarianSection)
                    .addGap(54)
                    .addGroup(gl_contentPane.createSequentialGroup()
                        .addGap(132)

                        .addGroup(gl_contentPane.createParallelGroup(Alignment.LEADING)
                            .addComponent(btnLogout,
                                GroupLayout.PREFERRED_SIZE, 191, GroupLayout.PREFERRED_SIZE)
                            .addComponent(btnReturnBook,
                                GroupLayout.PREFERRED_SIZE, 191, GroupLayout.PREFERRED_SIZE)
                            .addComponent(btnViewIssuedBooks,
                                GroupLayout.PREFERRED_SIZE, 191, GroupLayout.PREFERRED_SIZE)
                            .addComponent(btnIssueBook,
                                GroupLayout.PREFERRED_SIZE, 191, GroupLayout.PREFERRED_SIZE)
                            .addComponent(btnViewBooks,
                                GroupLayout.PREFERRED_SIZE, 191, GroupLayout.PREFERRED_SIZE)
                            .addComponent(btnNewButton,
                                GroupLayout.PREFERRED_SIZE, 191, GroupLayout.PREFERRED_SIZE))
                            .addContainerGap(101, Short.MAX_VALUE))
                    );
    gl_contentPane.setVerticalGroup(

```


```

        gl_contentPane.createParallelGroup(Alignment.LEADING)
            .addGroup(gl_contentPane.createSequentialGroup()
                .addContainerGap()
                .addComponent(lblLibrarianSection)
                .addGap(18)
                .addComponent(btnNewButton,
 GroupLayout.PREFERRED_SIZE, 37, GroupLayout.PREFERRED_SIZE)
                .addGap(18)
                .addComponent(btnViewBooks,
 GroupLayout.PREFERRED_SIZE, 37, GroupLayout.PREFERRED_SIZE)
                .addGap(18)
                .addComponent(btnIssueBook,
 GroupLayout.PREFERRED_SIZE, 37, GroupLayout.PREFERRED_SIZE)
                .addGap(18)
                .addComponent(btnViewIssuedBooks,
 GroupLayout.PREFERRED_SIZE, 37, GroupLayout.PREFERRED_SIZE)
                .addGap(18)
                .addComponent(btnReturnBook,
 GroupLayout.PREFERRED_SIZE, 37, GroupLayout.PREFERRED_SIZE)
                .addGap(18)
                .addComponent(btnLogout,
 GroupLayout.PREFERRED_SIZE, 37, GroupLayout.PREFERRED_SIZE)
                .addContainerGap(16, Short.MAX_VALUE))
            );
        contentPane.setLayout(gl_contentPane);
    }
}


```

Outputs

Library.java




AdminLogin.java




A Java Swing window titled "Admin Login Form" with a blue title bar. The window has a light gray background. It contains two text labels, "Enter Name:" and "Enter Password:", each followed by a white text input field. Below the input fields is a blue button with the text "Login".

AdminSuccess.java



A Java Swing window titled "Admin Section" with a blue title bar. The window has a light gray background. It contains three blue buttons stacked vertically, with the text "Add Librarian", "View Librarian", and "Delete Librarian".

LibrarianLogin.java



A Java Swing window titled "Librarian Login Form" with a blue title bar. The window has a light gray background. It contains two text labels, "Enter Name:" and "Enter Password:", each followed by a white text input field. Below the input fields is a blue button with the text "Login".

LibrarianSuccess.java



Librarian Section - JavaTpo

Add Books

View Books

Issue Book

View Issued Books

Return Book

Practical 4

Aim: Develop Java application to store image in a database as well as retrieve image from database.

Table

Create table myimages

```
(
    ID number(2),
    Name varchar2(20),
    Description varchar2(50),
    Image longblob
);
```

Work1.java:- Store

```
import java.awt.Image;
import java.awt.event.ActionEvent;
import java.awt.event.ActionListener;
import java.sql.Connection;
import java.sql.DriverManager;
import java.sql.PreparedStatement;
import javax.swing.*;
import javax.swing.filechooser.FileNameExtensionFilter;
import java.io.File;
import java.io.FileInputStream;
import java.io.InputStream;
```

```
public class Work1 extends JFrame{
    JButton button ;
    JButton button2;
    JLabel label;
    JTextField textID;
    JTextField textNAME;
    JTextArea area;
    String s;

    public Work1(){

        super("insert image to database in java");

        button = new JButton("ADD");
        button.setBounds(200,300,100,40);

        button2 = new JButton("Browse");
        button2.setBounds(80, 300, 100, 40);

        textID = new JTextField("ID");
        textID.setBounds(320,290,100,20);
```

```

textNAME = new JTextField("Name");
textNAME.setBounds(320,330,100,20);

area = new JTextArea("DESCRIPTION",100, 100);

JScrollPane pane = new JScrollPane(area);
pane.setBounds(450, 270, 200, 100);

label = new JLabel();
label.setBounds(10,10,670,250);

//button to browse the image into jlabel
button2.addActionListener(new ActionListener(){
    @Override
    public void actionPerformed(ActionEvent e){
        JFileChooser fileChooser = new JFileChooser();
        fileChooser.setCurrentDirectory(new File(System.getProperty("user.home")));
        FileNameExtensionFilter filter = new FileNameExtensionFilter("*.IMAGE",
"jpg","gif","png");
        fileChooser.addChoosableFileFilter(filter);
        int result = fileChooser.showSaveDialog(null);
        if(result == JFileChooser.APPROVE_OPTION){
            File selectedFile = fileChooser.getSelectedFile();
            String path = selectedFile.getAbsolutePath();
            label.setIcon(ResizeImage(path));
            s = path;
        }
        else if(result == JFileChooser.CANCEL_OPTION){
            System.out.println("No Data");
        }
    }
});

//button to insert image and some data into mysql database
button.addActionListener(new ActionListener(){

    @Override
    public void actionPerformed(ActionEvent e){
        try{
            Connection con =
DriverManager.getConnection("jdbc:mysql://localhost/db_images","root","");
            PreparedStatement ps = con.prepareStatement("insert into
myimages(ID,Name,Description,Image) values(?,?,?,?)");
            InputStream is = new FileInputStream(new File(s));
            ps.setString(1, textID.getText());
            ps.setString(2, textNAME.getText());
            ps.setString(3, area.getText());
            ps.setBlob(4,is);
            ps.executeUpdate();

```

```

        JOptionPane.showMessageDialog(null, "Data Inserted");
    } catch (Exception ex) {
        ex.printStackTrace();
    }
}
});

add(label);
add(textID);
add(textNAME);
add(pane);
add(button);
add(button2);
setLayout(null);
setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
setSize(700,420);
setVisible(true);
}

public ImageIcon ResizeImage(String imgPath){
    ImageIcon MyImage = new ImageIcon(imgPath);
    Image img = MyImage.getImage();
    Image newImage = img.getScaledInstance(label.getWidth(),
label.getHeight(),Image.SCALE_SMOOTH);
    ImageIcon image = new ImageIcon(newImage);
    return image;
}

public static void main(String[] args){
    new Work1();
}
}

```

Work.java Retrieve image

```

import java.awt.Color;
import java.awt.Image;
import java.awt.event.ActionEvent;
import java.awt.event.ActionListener;
import java.sql.Connection;
import java.sql.DriverManager;
import java.sql.ResultSet;
import java.sql.Statement;
import javax.swing.*;

public class Work extends JFrame{
    JButton button ;
    JLabel label;
    JTextField jtf;

    public Work(){
        super("retrieve image from database in java");
    }
}

```

```

button = new JButton("Retrieve");
button.setBounds(250,300,100,40);

jtf = new JTextField();
jtf.setBounds(360,310,100,20);

label = new JLabel();
label.setBounds(10,10,670,250);

add(button);
add(label);
add(jtf);

button.addActionListener(new ActionListener() {

    @Override
    public void actionPerformed(ActionEvent e) {

        try{
            Connection con =
DriverManager.getConnection("jdbc:mysql://localhost/db_images","root","");
            Statement st = con.createStatement();
            ResultSet rs = st.executeQuery("select * from myimages where ID =
"+jtf.getText()+"");
            if(rs.next()){
                byte[] img = rs.getBytes("Image");

                //Resize The ImageIcon
                ImageIcon image = new ImageIcon(img);
                Image im = image.getImage();
                Image myImg = im.getScaledInstance(label.getWidth(),
label.getHeight(),Image.SCALE_SMOOTH);
                ImageIcon newImage = new ImageIcon(myImg);
                label.setIcon(newImage);
            }

            else{
                JOptionPane.showMessageDialog(null, "No Data");
            }
        }catch(Exception ex){
            ex.printStackTrace();
        }

    }
});

setLayout(null);

```



```


setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
getContentPane().setBackground(Color.decode("#bdb76b"));
setLocationRelativeTo(null);
setSize(700,400);
setVisible(true);
}

public static void main(String[] args){
    new Work();
}
}




```

Output **Insertion**





Retrieving



Practical 5

Aim: Write a Java application to demonstrate servlet life cycle.

ServletLifeCycle.java

```
import java.io.IOException;
import java.io.PrintWriter;

import javax.servlet.ServletConfig;
import javax.servlet.ServletException;
import javax.servlet.http.HttpServlet;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;

public class ServletLifeCycle extends HttpServlet
{

    public ServletLifeCycle()
    {
        System.out.println("Am from default constructor");
    }

    public void init(ServletConfig config)
    {
        System.out.println("Am from Init method...!");
    }

    public void doGet(HttpServletRequest req,HttpServletResponse res)throws
    ServletException,IOException
    {
        res.setContentType("text/html");
        PrintWriter pw = res.getWriter();
        pw.println("I am from doGet method");
        pw.close();
    }

    public void destroy()
    {
        System.out.println("Am from Destroy methods");
    }

}
```

web.xml



```
<web-app>
    <servlet>
        <servlet-name>second</servlet-name>
        <servlet-class>java4s.ServletLifeCycle</servlet-class>
        <load-on-startup>1</load-on-startup>
    </servlet>

    <servlet-mapping>
        <servlet-name>second</servlet-name>
```



```
<url-pattern>/lifecycle1</url-pattern>
</servlet-mapping>
</web-app>
```

Output



Practical 6

Aim: Design database for employee administration. Develop servlet(s) to perform CRUD operations.

Index.html

```
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Insert title here</title>
</head>
<body>

<h1>Add New Employee</h1>
<form action="SaveServlet" method="post">
<table>
<tr><td>Name:</td><td><input type="text" name="name"/></td></tr>
<tr><td>Password:</td><td><input type="password" name="password"/></td></tr>
<tr><td>Email:</td><td><input type="email" name="email"/></td></tr>
<tr><td>Country:</td><td>
<select name="country" style="width:150px">
<option>India</option>
<option>USA</option>
<option>UK</option>
<option>Other</option>
</select>
</td></tr>
<tr><td colspan="2"><input type="submit" value="Save Employee"/></td></tr>
</table>
</form>

<br/>
<a href="ViewServlet">view employees</a>

</body>
</html>
```

Emp.java

```
public class Emp {
private int id;
private String name,password,email,country;
public int getId() {
    return id;
}
public void setId(int id) {
    this.id = id;
}
public String getName() {
    return name;
}
public void setName(String name) {
```

```

        this.name = name;
    }
    public String getPassword() {
        return password;
    }
    public void setPassword(String password) {
        this.password = password;
    }
    public String getEmail() {
        return email;
    }
    public void setEmail(String email) {
        this.email = email;
    }
    public String getCountry() {
        return country;
    }
    public void setCountry(String country) {
        this.country = country;
    }
}

```

EmpDao.java

```

import java.util.*;
import java.sql.*;

public class EmpDao {

    public static Connection getConnection(){
        Connection con=null;
        try{
            Class.forName("oracle.jdbc.driver.OracleDriver");
            con=DriverManager.getConnection("jdbc:oracle:thin:@localhost:1521:xe","system","oracle");
        }catch(Exception e){System.out.println(e);}
        return con;
    }
    public static int save(Emp e){
        int status=0;
        try{
            Connection con=EmpDao.getConnection();
            PreparedStatement ps=con.prepareStatement(
                "insert into Employee(name,password,email,country) values (?, ?, ?, ?)");
            ps.setString(1,e.getName());
            ps.setString(2,e.getPassword());
            ps.setString(3,e.getEmail());
            ps.setString(4,e.getCountry());

            status=ps.executeUpdate();

            con.close();
        }catch(Exception ex){ex.printStackTrace();}

        return status;
    }
    public static int update(Emp e){

```

```

int status=0;
try{
    Connection con=EmpDao.getConnection();
    PreparedStatement ps=con.prepareStatement(
        "update Employee set name=?,password=?,email=?,country=? where id=?");
    ps.setString(1,e.getName());
    ps.setString(2,e.getPassword());
    ps.setString(3,e.getEmail());
    ps.setString(4,e.getCountry());
    ps.setInt(5,e.getId());

    status=ps.executeUpdate();

    con.close();
} catch (Exception ex){ex.printStackTrace();}

return status;
}
public static int delete(int id){
    int status=0;
    try{
        Connection con=EmpDao.getConnection();
        PreparedStatement ps=con.prepareStatement("delete from Employee where id=?");
        ps.setInt(1,id);
        status=ps.executeUpdate();

        con.close();
    } catch (Exception e){e.printStackTrace();}

    return status;
}
public static Emp getEmployeeById(int id){
    Emp e=new Emp();

    try{
        Connection con=EmpDao.getConnection();
        PreparedStatement ps=con.prepareStatement("select * from Employee where id=?");
        ps.setInt(1,id);
        ResultSet rs=ps.executeQuery();
        if(rs.next()){
            e.setId(rs.getInt(1));
            e.setName(rs.getString(2));
            e.setPassword(rs.getString(3));
            e.setEmail(rs.getString(4));
            e.setCountry(rs.getString(5));
        }
        con.close();
    } catch (Exception ex){ex.printStackTrace();}

    return e;
}
public static List<Emp> getAllEmployees(){
    List<Emp> list=new ArrayList<Emp>();

    try{
        Connection con=EmpDao.getConnection();
        PreparedStatement ps=con.prepareStatement("select * from Employee");
        ResultSet rs=ps.executeQuery();
        while(rs.next()){
            Emp e=new Emp();

```

```

        e.setId(rs.getInt(1));
        e.setName(rs.getString(2));
        e.setPassword(rs.getString(3));
        e.setEmail(rs.getString(4));
        e.setCountry(rs.getString(5));
        list.add(e);
    }
    con.close();
} catch (Exception e) {e.printStackTrace();}

return list;
}
}

```

SaveServlet.java

```

import java.io.IOException;
import java.io.PrintWriter;

import javax.servlet.ServletException;
import javax.servlet.annotation.WebServlet;
import javax.servlet.http.HttpServlet;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;
@WebServlet("/SaveServlet")
public class SaveServlet extends HttpServlet {
    protected void doPost(HttpServletRequest request, HttpServletResponse response)
        throws ServletException, IOException {
        response.setContentType("text/html");
        PrintWriter out=response.getWriter();

        String name=request.getParameter("name");
        String password=request.getParameter("password");
        String email=request.getParameter("email");
        String country=request.getParameter("country");

        Emp e=new Emp();
        e.setName(name);
        e.setPassword(password);
        e.setEmail(email);
        e.setCountry(country);

        int status=EmpDao.save(e);
        if(status>0){
            out.print("<p>Record saved successfully!</p>");
            request.getRequestDispatcher("index.html").include(request, response);
        } else {
            out.println("Sorry! unable to save record");
        }
        out.close();
    }
}

```

EditServlet.java

```

import java.io.IOException;
import java.io.PrintWriter;

```

```

import javax.servlet.ServletException;
import javax.servlet.annotation.WebServlet;
import javax.servlet.http.HttpServlet;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;
@WebServlet("/EditServlet")
public class EditServlet extends HttpServlet {
    protected void doGet(HttpServletRequest request, HttpServletResponse response)
        throws ServletException, IOException {
        response.setContentType("text/html");
        PrintWriter out=response.getWriter();
        out.println("<h1>Update Employee</h1>");
        String sid=request.getParameter("id");
        int id=Integer.parseInt(sid);

        Emp e=EmpDao.getEmployeeById(id);

        out.print("<form action='EditServlet2' method='post'>");
        out.print("<table>");
        out.print("<tr><td></td><td><input type='hidden' name='id' value='"+e.getId()+"'/></td></tr>");

        out.print("<tr><td>Name:</td><td><input type='text' name='name' value='"+e.getName()+"'/></td></tr>");
        out.print("<tr><td>Password:</td><td><input type='password' name='password' value='"+e.getPassword()+"'/></td></tr>");
        out.print("<tr><td>Email:</td><td><input type='email' name='email' value='"+e.getEmail()+"'/></td></tr>");
        out.print("<tr><td>Country:</td><td>");
        out.print("<select name='country' style='width:150px'>");
        out.print("<option>India</option>");
        out.print("<option>USA</option>");
        out.print("<option>UK</option>");
        out.print("<option>Other</option>");
        out.print("</select>");
        out.print("</td></tr>");
        out.print("<tr><td colspan='2'><input type='submit' value='Edit & Save '/></td></tr>");
        out.print("</table>");
        out.print("</form>");

        out.close();
    }
}

```

EditServlet2.java

```

import java.io.IOException;
import java.io.PrintWriter;

import javax.servlet.ServletException;
import javax.servlet.annotation.WebServlet;
import javax.servlet.http.HttpServlet;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;

```

```

@WebServlet("/EditServlet2")
public class EditServlet2 extends HttpServlet {
    protected void doPost(HttpServletRequest request, HttpServletResponse response)
        throws ServletException, IOException {
        response.setContentType("text/html");
        PrintWriter out=response.getWriter();

        String sid=request.getParameter("id");
        int id=Integer.parseInt(sid);
        String name=request.getParameter("name");
        String password=request.getParameter("password");
        String email=request.getParameter("email");
        String country=request.getParameter("country");

        Emp e=new Emp();
        e.setId(id);
        e.setName(name);
        e.setPassword(password);
        e.setEmail(email);
        e.setCountry(country);

        int status=EmpDao.update(e);
        if(status>0){
            response.sendRedirect("ViewServlet");
        }else{
            out.println("Sorry! unable to update record");
        }

        out.close();
    }
}

```

DeleteServlet.java

```

import java.io.IOException;
import javax.servlet.ServletException;
import javax.servlet.annotation.WebServlet;
import javax.servlet.http.HttpServlet;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;
@WebServlet("/DeleteServlet")
public class DeleteServlet extends HttpServlet {
    protected void doGet(HttpServletRequest request, HttpServletResponse response)
        throws ServletException, IOException {
        String sid=request.getParameter("id");
        int id=Integer.parseInt(sid);
        EmpDao.delete(id);
        response.sendRedirect("ViewServlet");
    }
}

```

ViewServlet.java

```

import java.io.IOException;
import java.io.PrintWriter;

```

```

import java.util.List;

import javax.servlet.ServletException;
import javax.servlet.annotation.WebServlet;
import javax.servlet.http.HttpServlet;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;
@WebServlet("/ViewServlet")
public class ViewServlet extends HttpServlet {
    protected void doGet(HttpServletRequest request, HttpServletResponse response)
        throws ServletException, IOException {
        response.setContentType("text/html");
        PrintWriter out=response.getWriter();
        out.println("<a href='index.html'>Add New Employee</a>");
        out.println("<h1>Employees List</h1>");

        List<Emp> list=EmpDao.getAllEmployees();

        out.print("<table border='1' width='100%'>");
        out.print("<tr><th>Id</th><th>Name</th><th>Password</th><th>Email</th><th>Country</th>");
        out.print("<th>Edit</th><th>Delete</th></tr>");
        for(Emp e:list){
            out.print("<tr><td>" + e.getId() + "</td><td>" + e.getName() + "</td><td>" + e.getPassword() + "</td>");
            out.print("<td>" + e.getEmail() + "</td><td>" + e.getCountry() + "</td><td><a href='EditServlet?id="+e.getId()+">edit</a></td>");
            out.print("<td><a href='DeleteServlet?id="+e.getId()+">delete</a></td></tr>");
        }
        out.print("</table>");

        out.close();
    }
}

```

Output

First page will look like this, fill the form and submit it.

Insert title here x

localhost:9765/CrudServlet/SaveServlet

Add New Employee

Name:

Password:

Email:

Country:

[view employees](#)

Insert title here x

localhost:9765/CrudServlet/

Add New Employee

Name:

Password:

Email:

Country:

[view employees](#)

You will get a message "Record successfully saved!".

Record saved successfully!

Add New Employee

Name:

Password:

Email:

Country:

[view employees](#)

Click on the View Employees link to see the total employees list.

[Add New Employee](#)

Employees List

ID	Name	Password	Email	Country	Edit	Delete
63	Amit Kumar	amtkmj45	amitkumar@gmail.com	India	edit	delete
61	Rahul Kumar	rahul4000	rahulkk@gmail.com	India	edit	delete
62	Sonoo Jaiswal	sonoobsk	sonoojaiswal1987@gmail.com	India	edit	delete
44	adarsh kumar	kkkkk	adarsh232@gmail.com	India	edit	delete

Click on the update link, to change the data.

localhost:9765/CrudService x

localhost:9765/CrudServlet/EditServlet?id=63

Update Employee

Name:

Password:

Email:

Country:

After changing information, submit button. You will see that information is changed.

localhost:9765/CrudService x

localhost:9765/CrudServlet/ViewServlet

[Add New Employee](#)

Employees List

Id	Name	Password	Email	Country	Edit	Delete
63	Amit Kumar Rana	amtkmj45	amitkumar12@gmail.com	India	edit	delete
61	Rahul Kumar	rahul4000	rahulkk@gmail.com	India	edit	delete
62	Sonoo Jaiswal	sonoobsk	sonoojaiswal1987@gmail.com	India	edit	delete
44	adarsh kumar	kkkkk	adarsh232@gmail.com	India	edit	delete

Now, click on the delete link to delete the record.

localhost:9765/CrudServle X

localhost:9765/CrudServlet/ViewServlet

🔍

☆

🔗

☰

[Add New Employee](#)

Employees List

Id	Name	Password	Email	Country	Edit	Delete
63	Amit Kumar Rana	amtknj45	amitkumar12@gmail.com	India	edit	delete
61	Rahul Kumar	rahul4000	rahulkk@gmail.com	India	edit	delete
62	Sonoo Jaiswal	sonoobsk	sonoojaiswal1987@gmail.com	India	edit	delete

Practical 7

Aim: Create Employees table in EMP database. Perform select, insert, update, and delete operations on Employee table using JSP.

index.jsp

```
<!DOCTYPE html>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=ISO-8859-1">
<title>JSP CRUD Example</title>
</head>
<body>
<h1>JSP CRUD Example</h1>
<a href="adduserform.jsp">Add User</a>
<a href="viewusers.jsp">View Users</a>

</body>
</html>
```

adduserform.jsp

```
<!DOCTYPE html>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=ISO-8859-1">
<title>Add User Form</title>
</head>
<body>
```

```
<jsp:include page="userform.html"></jsp:include>
```

```
</body>
```

```
</html>
```

```
userform.html
```

```
<a href="viewusers.jsp">View All Records</a><br/>
```

```
<h1>Add New User</h1>
```

```
<form action="adduser.jsp" method="post">
```

```
<table>
```

```
<tr><td>Name:</td><td><input type="text" name="name"/></td></tr>
```

```
<tr><td>Password:</td><td>
```

```
<input type="password" name="password"/></td></tr>
```

```
<tr><td>Email:</td><td><input type="email" name="email"/></td></tr>
```

```
<tr><td>Sex:</td><td>
```

```
<input type="radio" name="sex" value="male"/>Male
```

```
<input type="radio" name="sex" value="female"/>Female </td></tr>
```

```
<tr><td>Country:</td><td>
```

```
<select name="country" style="width:155px">
```

```
<option>India</option>
```

```
<option>Pakistan</option>
```

```
<option>Afghanistan</option>
```

```

<option>Berma</option>
<option>Other</option>
</select>
</td></tr>
<tr><td colspan="2"><input type="submit" value="Add User"/></td></tr>
</table>
</form>

```

adduser.jsp

```

<%@page import="com.javatpoint.dao.UserDao"%>
<jsp:useBean id="u" class="com.javatpoint.bean.User"></jsp:useBean>
<jsp:setProperty property="*" name="u"/>

<%
int i=UserDao.save(u);
if(i>0){
response.sendRedirect("adduser-success.jsp");
}else{
response.sendRedirect("adduser-error.jsp");
}
%>

```

User.java

```

package com.javatpoint.bean;
public class User {
private int id;
private String name,password,email,sex,country;
//generate getters and setters
}

```

UserDao.java

```

package com.javatpoint.dao;
import java.sql.*;
import java.util.ArrayList;
import java.util.List;
import com.javatpoint.bean.User;
public class UserDao {

public static Connection getConnection(){
    Connection con=null;
    try{
        Class.forName("com.mysql.jdbc.Driver");
        con=DriverManager.getConnection("jdbc:mysql://localhost:3306/test","","");
    }catch(Exception e){System.out.println(e);}
    return con;
}

public static int save(User u){
    int status=0;
    try{
        Connection con=getConnection();

```

```

        PreparedStatement ps=con.prepareStatement(
"insert into register(name,password,email,sex,country) values(?,?,?,?,?)");
        ps.setString(1,u.getName());
        ps.setString(2,u.getPassword());
        ps.setString(3,u.getEmail());
        ps.setString(4,u.getSex());
        ps.setString(5,u.getCountry());
        status=ps.executeUpdate();
    } catch (Exception e) {System.out.println(e);}
    return status;
}

public static int update(User u){
    int status=0;
    try{
        Connection con=getConnection();
        PreparedStatement ps=con.prepareStatement(
"update register set name=?,password=?,email=?,sex=?,country=? where id=?");
        ps.setString(1,u.getName());
        ps.setString(2,u.getPassword());
        ps.setString(3,u.getEmail());
        ps.setString(4,u.getSex());
        ps.setString(5,u.getCountry());
        ps.setInt(6,u.getId());
        status=ps.executeUpdate();
    } catch (Exception e) {System.out.println(e);}
    return status;
}

public static int delete(User u){
    int status=0;
    try{
        Connection con=getConnection();
        PreparedStatement ps=con.prepareStatement("delete from register where id=?");
        ps.setInt(1,u.getId());
        status=ps.executeUpdate();
    } catch (Exception e) {System.out.println(e);}

    return status;
}

public static List<User> getAllRecords(){
    List<User> list=new ArrayList<User>();

    try{
        Connection con=getConnection();
        PreparedStatement ps=con.prepareStatement("select * from register");
        ResultSet rs=ps.executeQuery();
        while(rs.next()){
            User u=new User();
            u.setId(rs.getInt("id"));
            u.setName(rs.getString("name"));
            u.setPassword(rs.getString("password"));

```

```

        u.setEmail(rs.getString("email"));
        u.setSex(rs.getString("sex"));
        u.setCountry(rs.getString("country"));
        list.add(u);
    }
} catch (Exception e) {System.out.println(e);}
return list;
}
public static User getRecordById(int id){
    User u=null;
    try{
        Connection con=getConnection();
        PreparedStatement ps=con.prepareStatement("select * from register where id=?");
        ps.setInt(1,id);
        ResultSet rs=ps.executeQuery();
        while(rs.next()){
            u=new User();
            u.setId(rs.getInt("id"));
            u.setName(rs.getString("name"));
            u.setPassword(rs.getString("password"));
            u.setEmail(rs.getString("email"));
            u.setSex(rs.getString("sex"));
            u.setCountry(rs.getString("country"));
        }
    } catch (Exception e) {System.out.println(e);}
    return u;
}
}
}

```

adduser-success.jsp

```

<!DOCTYPE html>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=ISO-8859-1">
<title>Add User Success</title>
</head>
<body>

<p>Record successfully saved!</p>
<jsp:include page="userform.html"></jsp:include>

</body>
</html>

```

adduser-error.jsp

```

<!DOCTYPE html>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=ISO-8859-1">
<title>Add User Error</title>

```



```

</head>
<body>

<p>Sorry, an error occurred!</p>
<jsp:include page="userform.html"></jsp:include>

</body>
</html>

```

viewusers.jsp

```

<!DOCTYPE html>

<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=ISO-8859-1">
<title>View Users</title>
</head>
<body>

<%@page import="com.javatpoint.dao.UserDao,com.javatpoint.bean.*,java.util.*"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>

<h1>Users List</h1>

<%
List<User> list=UserDao.getAllRecords();
request.setAttribute("list",list);
%>

<table border="1" width="90%">
<tr><th>Id</th><th>Name</th><th>Password</th><th>Email</th>
<th>Sex</th><th>Country</th><th>Edit</th><th>Delete</th></tr>
<c:forEach items="${list}" var="u">
<tr><td>${u.getId()}</td><td>${u.getName()}</td><td>${u.getPassword()}</td>
<td>${u.getEmail()}</td><td>${u.getSex()}</td><td>${u.getCountry()}</td>
<td><a href="editform.jsp?id=${u.getId()}">Edit</a></td>
<td><a href="deleteuser.jsp?id=${u.getId()}">Delete</a></td></tr>
</c:forEach>
</table>
<br/><a href="adduserform.jsp">Add New User</a>

</body>
</html>

```

editform.jsp

```

<!DOCTYPE html>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=ISO-8859-1">

```

```

<title>Edit Form</title>
</head>
<body>
<%@page import="com.javatpoint.dao.UserDao,com.javatpoint.bean.User"%>

<%
String id=request.getParameter("id");
User u=UserDao.getRecordById(Integer.parseInt(id));
%>

<h1>Edit Form</h1>
<form action="edituser.jsp" method="post">
<input type="hidden" name="id" value="<%=u.getId() %>"/>
<table>
<tr><td>Name:</td><td>
<input type="text" name="name" value="<%= u.getName() %>"/></td></tr>
<tr><td>Password:</td><td>
<input type="password" name="password" value="<%= u.getPassword() %>"/></td></tr>
<tr><td>Email:</td><td>
<input type="email" name="email" value="<%= u.getEmail() %>"/></td></tr>
<tr><td>Sex:</td><td>
<input type="radio" name="sex" value="male"/>Male
<input type="radio" name="sex" value="female"/>Female </td></tr>
<tr><td>Country:</td><td>
<select name="country">
<option>India</option>
<option>Pakistan</option>
<option>Afghanistan</option>
<option>Berma</option>
<option>Other</option>
</select>
</td></tr>
<tr><td colspan="2"><input type="submit" value="Edit User"/></td></tr>
</table>
</form>

</body>
</html>

```

edituser.jsp

```

<%@page import="com.javatpoint.dao.UserDao"%>
<jsp:useBean id="u" class="com.javatpoint.bean.User"></jsp:useBean>
<jsp:setProperty property="*" name="u"/>
<%
int i=UserDao.update(u);
response.sendRedirect("viewusers.jsp");
%>

```

deleteuser.jsp

```

<%@page import="com.javatpoint.dao.UserDao"%>

```

```
<jsp:useBean id="u" class="com.javatpoint.bean.User"></jsp:useBean>
<jsp:setProperty property="*" name="u"/>
<%
 UserDao.delete(u);
 response.sendRedirect("viewusers.jsp");
 %>
```

Output



sonoo

Add User Success

Record successfully saved!

[View All Records](#)

Add New User

Name:

Password:

Email:

Sex: ☐ Male ☐ Female

Country:

sonoo

View Users

localhost:8888/JSPCrud/viewusers.jsp

Users List

Id	Name	Password	Email	Sex	Country	Edit	Delete
17	arun	kumar	arun@gmail.com	Male	India	Edit	Delete
18	amit	kumar	amit@gmail.com	Male	India	Edit	Delete
19	sonoo	jaiswal	sonoo@javatpoint.com	male	India	Edit	Delete
20	Ashok	ashok	ashok@javatpoint.com	male	India	Edit	Delete

[Add New User](#)

localhost:8888/JSPCrud/editform.jsp?id=18

sonoo

Edit Form

localhost:8888/JSPCrud/editform.jsp?id=18

Edit Form

Name:

Password:

Email:

Sex: ☒ Male ☐ Female

Country:

sonoo

View Users

localhost:8888/JSPCrud/viewusers.jsp

Users List

Id	Name	Password	Email	Sex	Country	Edit	Delete
17	arun	kumar	arun@gmail.com	Male	India	Edit	Delete
18	amit kumar	kumaramit	amit@javatpoint.com	male	India	Edit	Delete
19	sonoo	jaiswal	sonoo@javatpoint.com	male	India	Edit	Delete
20	Ashok	ashok	ashok@javatpoint.com	male	India	Edit	Delete

[Add New User](#)

View Users

sonoo

localhost:8888/JSPCrud/viewusers.jsp

Users List

Id	Name	Password	Email	Sex	Country	Edit	Delete
17	arun	kumar	arun@gmail.com	Male	India	Edit	Delete
19	sonoo	jaiswal	sonoo@javatpoint.com	male	India	Edit	Delete
20	Ashok	ashok	ashok@javatpoint.com	male	India	Edit	Delete

[Add New User](#)