CodeX - REST API 1.0.0 OAS 3.0

openapi.yaml

This is the OpenAPI specification of the *REST-API* interface provided by the *CodeX Server* component.

License: GPLv3

Authorize

Authentication

Endpoints concerned with authentication, account-validation and security settings.

GET `/auth/google/login` Login via the google identity provider.

Parameters Try it out

No parameters

Responses

Code	Description	Links
200	Login successful Media type **application/json** Controls Accept header. **Example Value** Schema `{ "access_token": "string", "refresh_token": "3fa85f64-5717-4562-b3fc-2c963f66afa6" }`	*No links*

Code	Description	Links
401	Could not authenticate	*No links*

GET `/auth/google/callback` Callback for the google identity provider.

Parameters Try it out

No parameters

Responses

Code	Description	Links
200	Login successful Media type application/json Controls Accept header. **Example Value** Schema `{ "access_token": "string", "refresh_token": "3fa85f64-5717-4562-b3fc-2c963f66afa6" }`	*No links*
401	Could not authenticate	*No links*

POST `/auth/login` Login with email/username and password

Parameters Try it out

No parameters

Request body required application/json

Example Value Schema

```
{
  "email": "user@example.com",
```

```
  "username": "string",
  "password": "string"
}
```

Responses

Code	Description	Links
200	Login successful Media type **application/json** Controls Accept header. **Example Value** Schema `{ "access_token": "string", "refresh_token": "3fa85f64-5717-4562-b3fc-2c963f66afa6" }`	*No links*
400	Invalid request input (e.g., missing password or invalid email format)	*No links*
401	Invalid credentials	*No links*

POST /auth/signup Create a new account

Parameters

Try it out

No parameters

Request body required

application/json

Example Value Schema

```
{
  "email": "user@example.com",
  "username": "string",
  "password": "string"
}
```

Responses

Code	Description	Links
201	User created successfully Media type **application/json** Controls `Accept` header. **Example Value** Schema `{ "access_token": "string", "refresh_token": "3fa85f64-5717-4562-b3fc-2c963f66afa6" }`	*No links*
400	Invalid request input	*No links*
409	Email or username already exists	*No links*

POST `/auth/refresh` Refresh access token using a refresh token

Parameters Try it out

No parameters

Request body required **application/json**

Example Value Schema

```
{
  "refresh_token": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
}
```

Responses

Code	Description	Links
200	Token refreshed successfully Media type	*No links*

Code	Description	Links
	application/json Controls Accept header. **Example Value** Schema `{ "access_token": "string", "refresh_token": "3fa85f64-5717-4562-b3fc-2c963f66afa6" }`	
400	Refresh token missing or invalid format	*No links*
401	Refresh token expired or not recognized	*No links*

POST `/auth/logout` Logout from one or all sessions

If a refresh token is provided as a query parameter, only that session is logged out. If none is provided, **all** sessions for the user are logged out.

Parameters Try it out

Name	Description
refresh_token `string($uuid)` *(query)*	The refresh token to invalidate. If omitted, all sessions will be terminated. refresh_token

Responses

Code	Description	Links
204	Successfully logged out (no content)	*No links*
400	Invalid refresh token format	*No links*
401	Refresh token was invalid i.e. expired, not found, etc	*No links*

POST `/auth/request-password-reset`
Request a password-reset token to a specified email address.

Sends a password-reset token to the specified email-address, if an account exists for that email address.

Parameters Try it out

No parameters

Request body required application/json

Example Value Schema

```
{
  "email": "user@example.com"
}
```

Responses

Code	Description	Links
204	Password-reset token sent	*No links*

POST `/auth/submit-password-reset`
Submit password-reset token and set a new password

Accepts the password-reset token sent via email and a new password. Does not require the user to be logged in.

Parameters Try it out

No parameters

Request body required application/json

Example Value Schema

```
{
  "reset_token": "string",
  "new_password": "string"
}
```

Responses

Code	Description	Links
204	Password successfully reset (no content)	*No links*
400	Invalid request	*No links*
401	Reset token invalid or expired	*No links*

POST `/auth/request-email-verification` Request an email-verification token

Sends an email-verification token to the authenticated user's email.

Parameters Try it out

No parameters

Responses

Code	Description	Links
204	Verification email sent	*No links*
401	User not authenticated	*No links*
409	Email is already verified	*No links*

POST `/auth/submit-email-verification` Submit an email-verification token

Accepts the email-verification token sent to the user's email.

Parameters Try it out

No parameters

Request body required application/json

Example Value Schema

```
{
  "verification_token": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
}
```

Responses

Code	Description	Links
204	Email successfully verified	*No links*
400	Invalid request	*No links*
401	Verification token invalid or expired	*No links*

Conversations Endpoints concerned with conversations.

GET `/conversations` Get all conversations for the authenticated user

Returns a list of all conversations for the current user, without including the messages.

Parameters Try it out

No parameters

Responses

Code	Description	Links
200	List of conversations retrieved successfully Media type **application/json** Controls Accept header. **Example Value** Schema `[ { "id": "string", "name": "string", "pinned": true, "llm_model_config_id": "string", "target_language": "spice_netlist" } ]`	*No links*
401	User not authenticated	*No links*

POST `/conversations` Create a new conversation

Starts a new conversation with the given message, LLM configuration, and target language.

Parameters

Try it out

No parameters

Request body required

application/json

Example Value Schema

```
{
  "message": "string",
  "llm_model_config_id": "string",
  "target_language": "spice_netlist",
  "name": "string"
}
```


Responses

Code	Description	Links
201	Conversation created successfully Media type **application/json** Controls Accept header. **Example Value** Schema	*No links*
400	Invalid request	*No links*
401	User not authenticated	*No links*
429	Quota exceeded	*No links*


```
{
  "id": "string",
  "name": "string",
  "pinned": true,
  "llm_model_config_id": "string",
  "target_language": "spice_netlist",
  "messages": [
    {
      "id": "string",
      "message": "string",
      "generation_millis": 0,
      "response": "string",
      "response_secondary": "string"
    }
  ]
}
```


GET `/conversations/{id}` Get a specific conversation by Id

Returns a full conversation for the given conversation ID.

Parameters

Try it out

Name	Description
id * required `string` ***(path)***	Id of the conversation to retrieve id

Responses

Code	Description	Links

200	Conversation retrieved successfully
	
	Media type
	application/json
	Controls Accept header.
	
	Example Value Schema
	
	{
	"id": "string",
	"name": "string",
	"pinned": true,
	"llm_model_config_id": "string",
	"target_language": "spice_netlist",
	"messages": [
	{
	"id": "string",
	"message": "string",
	"generation_millis": 0,
	"response": "string",
	"response_secondary": "string"
	}
	]
	}
		No links

401	User not authenticated	*No links*
403	User does not have access to this conversation or conversation not found	*No links*
500	Unexpected server error	*No links*

PUT `/conversations/{id}` Update conversation metadata

Updates the `name` and `pinned` attributes of a conversation.

Parameters

Try it out

Name	Description
id * required `string` ***(path)***	ID of the conversation to update id

Request body required — application/json

Example Value Schema

```
{
  "name": "string",
  "pinned": true
}
```

Responses

Code	Description	Links
200	Conversation updated successfully Media type application/json Controls Accept header. **Example Value** Schema `{ "id": "string", "name": "string", "pinned": true, "llm_model_config_id": "string", "target_language": "spice_netlist", "messages": [ { "id": "string", "message": "string", "generation_millis": 0, "response": "string", "response_secondary": "string" } ] }`	*No links*
400	Invalid request	*No links*

Code	Description	Links
401	User not authenticated	*No links*
403	User does not have permission to update this conversation or conversation now found	*No links*

DELETE `/conversations/{id}` Delete a conversation

Deletes the conversation with the given Id.

Parameters Try it out

Name	Description
id * required `string` ***(path)***	Id of the conversation to delete id

Responses

Code	Description	Links
204	Conversation deleted successfully	*No links*
401	User not authenticated	*No links*
403	User does not have permission to delete this conversation or conversation not found	*No links*

POST `/conversations/{id}/messages`
Add a follow-up message to an existing conversation

Adds a new message to an existing conversation.

Parameters Try it out

Name	Description
id * required `integer` ***(path)***	Id of the target conversation id

Request body required — application/json

Example Value Schema

```
{
  "message": "string"
}
```

Responses

Code	Description	Links
200	Message added successfully Media type application/json Controls Accept header. **Example Value** Schema `{ "id": "string", "message": "string", "generation_millis": 0, "response": "string", "response_secondary": "string" }`	*No links*
400	Invalid request	*No links*
401	User not authenticated	*No links*
403	User does not have access to this conversation or conversation was not found	*No links*
429	Quota exceeded	*No links*

PUT `/conversations/{id}/messages` Regenerate a message.

Resend a message by providing a new prompt.

Parameters Try it out

No parameters

Request body required application/json

Example Value Schema

```
{
  "message": "string"
}
```

Responses

Code	Description	Links

200	Message changed successfully
	
	Media type
	application/json
	Controls Accept header.
	
	Example Value Schema
	
	{
	"id": "string",
	"message": "string",
	"generation_millis": 0,
	"response": "string",
	"response_secondary": "string"
	}
		No links

Quota Endpoints oncerned with the quota-system.

GET `/quota` Get current quota configuration

Returns the current quota configuration.

Parameters Try it out

No parameters

Responses

Code	Description	Links

200	Quota configuration retrieved successfully
	
	Media type
	application/json
	Controls Accept header.
	
	Example Value Schema
	
	{
	"member": 0,
	"admin": 0
	}
		No links

PUT `/quota` Update quota configuration

Updates the quota limits for members and admins. Only for admins.

Parameters Try it out

No parameters

Request body required application/json

Example Value Schema


```
{
  "member": 0,
  "admin": 0
}
```


Responses

Code	Description	Links
200	Quota configuration updated successfully Media type **application/json** Controls `Accept` header. **Example Value** Schema `{ "member": 0, "admin": 0 }`	*No links*
400	Invalid request	*No links*
401	User not authenticated or authorized	*No links*

Analytics Endpoints oncerned with the analytics.

GET `/analytics` Get current analytics

Returns the analytics. Only for Admins.

Parameters Try it out

No parameters

Responses

Code	Description	Links
200	Analytics retrieved successfully Media type **application/json** Controls `Accept` header. **Example Value** Schema `{ "requests_today": 0, "requests_this_month": 0 }`	*No links*
401	User not authenticatedor authorized	*No links*

Account

Endpoints concerned with account-data, i.e. username, email or LLM-configurations.

GET `/account` Get current authenticated user's account data

Returns the account information for the currently authenticated user.

Parameters Try it out

No parameters

Responses

Code	Description	Links
200	Account data retrieved successfully Media type **application/json** Controls `Accept` header.	*No links*

Code	Description	Links

Example Value Schema


```
{
  "id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "email": "user@example.com",
  "username": "string",
  "is_admin": true,
  "is_verified": true,
  "llm_configurations": [
    {
      "id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
      "name": "string",
      "api_url": "string",
      "api_key_set": true
    }
  ]
}
```


401	User not authenticated	*No links*

PUT `/account` Update account email and username

Updates the authenticated user's email and username.

- **Both fields must be provided**.
- If the email is changed:
  - User will be logged out from all sessions.
  - Account will be set to unverified.
  - A new email-verification email will be sent.

Parameters Try it out

No parameters

Request body required application/json

Example Value Schema


```
{
  "email": "user@example.com",
  "username": "string"
}
```


Responses

Code	Description	Links
204	Account updated successfully	*No links*
400	Invalid request	*No links*
401	User not authenticated	*No links*
409	Email or username already taken	*No links*

PUT `/account/profile-picture`
Updates the profile picture of the user that is authenticated

Updates the profile picture of the user that is authenticated

Parameters Try it out

No parameters

Request body required multipart/form-data

file
`string($binary)`

Responses

Code	Description	Links
204	Profile Picture updated successfully	*No links*
400	Invalid request	*No links*
401	User not authenticated	*No links*

GET `/account/profile-picture` Get the authenticated user's profile picture

Returns the profile picture for the authenticated user. The response is a binary image.

Parameters Try it out

No parameters

Responses

Code	Description	Links
200	Profile picture returned successfully. Media type image/png Controls Accept header. **Example Value** Schema `string`	*No links*
401	User not authenticated	*No links*

POST `/account/llm-configurations`
Add a new LLM configuration to the account

Adds a new LLM configuration for the authenticated user.

Parameters Try it out

No parameters

Request body required application/json

Example Value Schema

```
{
  "name": "string",
  "api_url": "string",
  "api_key": "string"
}
```


Responses

Code	Description	Links
201	LLM configuration added successfully	*No links*
400	Invalid request	*No links*
401	User not authenticated	*No links*

DELETE `/account/llm-configurations/{id}` Delete a specific LLM configuration

Deletes an LLM configuration of the authenticated user by its id.

Parameters

Try it out

Name	Description
id * required `string` ***(path)***	ID of the LLM configuration to delete id

Responses

Code	Description	Links
204	LLM configuration deleted successfully	*No links*
401	User not authenticated	*No links*

Code	Description	Links
404	LLM configuration not found	*No links*

PUT `/account/llm-configurations/{id}` Update a specific LLM configuration

Updates an existing LLM configuration of the authenticated user by its id.

Parameters Try it out

Name	Description
id * required `string` ***(path)***	ID of the LLM configuration to update id

Request body required application/json

Example Value Schema

```
{
  "name": "string",
  "api_url": "string",
  "api_key": "string"
}
```

Responses

Code	Description	Links
200	LLM configuration updated successfully Media type application/json Controls Accept header. **Example Value** Schema {	*No links*

Code	Description	Links
	<pre>{ "id": "3fa85f64-5717-4562-b3fc-2c963f66afa6", "name": "string", "api_url": "string", "api_key_set": true }</pre>	
400	Invalid request	*No links*
401	User not authenticated	*No links*
404	LLM configuration not found	*No links*

Schemas

LoginRequest {

email [...]

username [...]

password* [...]

}

SignupRequest {

email* [...]

username* [...]

password* [...]

}

TokenResponse {

access_token* [...]

refresh_token* [...]

}

RefreshRequest {

refresh_token* [...]

}

PasswordResetSubmitRequest {

reset_token* [...]

new_password* [...]

}

PasswordResetRequestRequest {

email* [...]

}

EmailVerificationSubmitRequest {

verification_token* [...]

}

UpdateAccountRequest {

email* [...]

username* [...]

}

AccountResponse {

id* [...]

email* [...]

username* [...]

is_admin* [...]

is_verified [...]

llm_configurations* [...]

}

LLMConfigurationResponse {

id* [...]

name* [...]

api_url* [...]

api_key_set [...]

}

LLMConfigurationRequest {

```
    name*                   [...]
    api_url*                [...]
    api_key                 [...]
}
```

QuotaConfig {

```
    member*                 [...]
    admin*                  [...]
}
```

AnalyticsResponse {

```
    requests_today*         [...]
    requests_this_month*    [...]
}
```

TargetLanguage string

Possible values hen a language is required

Enum:

```
    Array [ 3 ]
```

ConversationRequest {

```
    message*                [...]
    llm_model_config_id*    [...]
    target_language*        TargetLanguage [...]
    name*                   [...]
}
```

MessageRequest {

```
    message*                [...]
}
```

MessageResponse {

```
id*                     [...]
message*                [...]
generation_millis*      [...]
response*               [...]
response_secondary      [...]
```

}

ConversationResponse {

```
id*                     [...]
name*                   [...]
pinned                  [...]
llm_model_config_id*    [...]
target_language*        TargetLanguage [...]
messages*               [...]
```

}

ConversationWithoutMessagesResponse {

```
id*                     [...]
name*                   [...]
pinned*                 [...]
llm_model_config_id     [...]
target_language*        TargetLanguage [...]
```

}

UpdateConversationRequest {

```
name*                   [...]
pinned*                 [...]
```

}