

OIL INDIA LIMITED — DRILLING DEPARTMENT

DAILY DRILLING REPORT (DDR) · SYNTHETIC DEMONSTRATION DOCUMENT · eRTMAC-NWIS sample

Well	HGJ-02	Field	Hugrijan
Rig	CTR-Q16	Report No.	174
Report Date	2014-02-22	Spud Date	2013-09-01
Depth @ 24:00 (m MD)	3,822	Progress (m)	64
Latitude	27.3794	Longitude	95.3512
Hole Size	12-1/4"	Well Type	deviated

1. OPERATIONS SUMMARY (00:00 – 24:00 hrs)

From	To	Depth (m)	Operation
00:00	03:30	3,758	Drilled ahead 12-1/4" hole, parameters steady, monitored returns.
03:30	04:15	3,780	Connection, survey, circulated bottoms-up.
04:15	09:45	3,790	Mud Loss — see remarks. NPT 52.0 hrs.
09:45	13:00	3,790	Conditioned hole, reamed interval, circulated hi-vis sweep.
13:00	18:30	3,807	Drilled ahead at controlled parameters.
18:30	19:15	3,807	Connection, flow-check, mud properties checked.
19:15	24:00	3,822	Drilled ahead; depth at 24:00 hrs as reported.

2. MUD PROPERTIES

MW (ppg)	FV (s)	PV (cP)	YP (lb/100ft²)	pH	Solids (%)	Type
11.9	75	29	31	9.5	11.9	KCl-Polymer

3. CASING STATUS

String	Size	Shoe (m MD)	TOC (m)
Conductor	20"	89	0
Surface	13-3/8"	1,217	0
Intermediate	9-5/8"	2,995	2,446

4. DRILLING EVENTS / REMARKS

1. MUD LOSS at 3,790 m MD (SYLHET) | Severity: CRITICAL | NPT: 52.0 hrs | MW: 11.9 ppg
Total loss of returns at 3,790 m MD in fractured Sylhet limestone; loss rate exceeded 120 bbl/hr. Standpipe pressure dropped 380 psi. Well kept full with water while LCM was mixed. Mitigation: Reduced mud weight by 0.3 ppg and spotted a cross-linked LCM pill across the loss zone; cured after two attempts.
Lesson: Reduce ECD (lower flow, controlled ROP) when approaching the Sylhet loss zone; stage cross-linked pills before drilling into the limestone.

2. KICK at 3,804 m MD (SYLHET) | Severity: HIGH | NPT: 16.0 hrs | MW: 12.3 ppg
Flow observed on connection at 3,804 m MD (Sylhet) after losses reduced hydrostatic head; 9 bbl gain. Well shut in with SIDPP 310 psi. Mitigation: Flow-checked, closed BOP, circulated influx out and increased MW to 12.6 ppg with kill-line monitoring.
Lesson: Narrow window in Sylhet: manage ECD carefully to avoid losses while holding the kick off.

5. LESSONS LEARNED

- Reduce ECD (lower flow, controlled ROP) when approaching the Sylhet loss zone; stage cross-linked pills before drilling into the limestone.
- Narrow window in Sylhet: manage ECD carefully to avoid losses while holding the kick off.

Prepared by: Drilling Engineer (synthetic) · Reviewed by: Drilling Superintendent (synthetic) · This document was generated for the eRTMAC-NWIS demonstration and does not describe a real operation.