Thiagarajar Telekom Solutions (P) Limited

DUALBAND AVIONIC ANTENNA – TTSLDBSDA-20



The TTSLDBSDA-20 is a High Performance Rugged Dualband GNSS Antenna designed to operate at GPS, GLONASS, Galileo, BeiDou and the IRNSS bands making it suitable for Multi Constellation GNSS signal reception. The Antenna has a good gain in each of the bands with a low noise figure and a high rejection at out of band frequencies making it suitable for High Precision GNSS based Navigational Applications

The antenna geometrical center and the electrical phase centers of L1 and L5 are co-located in X and Y coordinates and have very minimal variations in the Z co-ordinate which helps in high precision position measurements and makes installation easier. It also includes a novel technique for suppression of multi-path signals.

The Compact design which meets the environmental conditions like marine applications the ruggedized enclosure with Aluminum Alloy (AA-2014) base and Teflon Radome. The TTSLDBSDA-20 is housed in a pre- tapped screw-hole mount, weather-proof enclosure for permanent installations.

Key Features

- Best Signal Reception in Multi - constellation mode.
- Excellent Multipath rejection
- Good Signal to Noise ratio and Out of band Rejection
- The Low Power consumption
- Lightweight with small form factor for easier integration.

This document is copyright © AUG-2024 TTSL. All rights reserved. This document has provided for information purpose only. The contents are subject to change without any notice.

Thiagarajar Telekom Solutions (P) Limited

Technical Specifications

Electrical Specifications	
IRNSS L5	1176.45 MHz (±12MHz)
GPS L1	1575 MHz (±10 MHz)
GLONASS L1	1598 MHz-1606 MHz
VSWR	≤ 2.0 :1
Passive Gain	>+3.0 dBiC
LNA Gain	30 ± 2 dB (L Band)
LNA Power Consumption	5V – 80 ±10 mA
Out of Band Rejection	> 60dB
Noise Figure	≤ 2.0 dB
Output Impedance	50 Ohms
Axial Ratio	< 3 dB
Lightening Protection	DC Grounding
Burnout Limit	+20dBm @ CW Input
Power Handling	1 Watt
Connector	TNC - (F)

Mechanical Specifications	
Dimension Excluding Connector (L x W x H)	Length 130 ±0.3mm Width 100 ±0.3mm Height 30 ±0.3 mm
Dimension Including Connector (L x W x H)	Length 130 ±0.3mm Width 100 ±0.3mm Height 46.5 ±0.3mm
Weight	< 300 grams.

Environmental Specifications	
Mounting	Standard Screw Mounting
Finish	Polyurethane Enamel
Operating Temperature	-55°C to +85°C
Storage Temperature	-55°C to +85°C
Humidity	95% RH at 45°C
MTBF	1,00,000 Hrs.

Environmental Stress Screening	
Mechanical Vibration	MIL-STD-810G / JSS 55555
Functional Shock	MIL-STD-810G / JSS 55555
Crash hazard	MIL-STD-810G / JSS 55555
Temperature and Altitude	MIL-STD-810G / JSS 55555
Humidity	MIL-STD-810G / JSS 55555
Temperature Shock	MIL-STD-810G / JSS 55555
Salt Fog	MIL-STD-810G / JSS 55555
Fungus	MIL-STD-810G / JSS 55555
Sand and Dust	MIL-STD-810G / JSS 55555
EMI & EMC	MIL-STD-461F
CATH	MIL-STD-810G

Note: All the Electrical Parameters are complying with Do-373 standards

This document is copyright © AUG-2024 TTSL. All rights reserved. This document has provided for information purpose only. The contents are subject to change without any notice.