

POS Cafe — Developer Reference & Change Guide

Version: 0.1.0 · **Generated:** September 2026 **Repository:** `codezen879/POS_CAFE` (GitHub) · **Production:** `https://pos-cafe-eight.vercel.app`

This document gives a developer everything needed to safely modify and deploy the POS Cafe application: architecture, data model, every API route, key UI flows (staff table service, kitchen display, billing, and the mobile QR ordering feature), conventions, and hard-won pitfalls.

1. Project Overview

POS Cafe is a restaurant/café **point-of-sale** web application with:

- **Back-office app** (staff): table service, order taking, kitchen display (KDS), billing with GST + service charge, payments (split supported), receipts (printable), customer loyalty + reviews, menu & add-on management, inventory, staff management, settings, tax rates, and reports.
- **Mobile ordering app** (guest): public pages at `/m` and `/m?table=<id>` where guests browse the menu, customize add-ons, add items to a cart, and send orders straight to the kitchen via Table-Service QR codes.

Stack

Layer	Technology
Framework	Next.js 15.2.8 (App Router) on Node
UI	React 19.0.1 , Tailwind CSS 3.4, shadcn-style <code>components/ui</code> , lucide-react icons
Auth	NextAuth 5.0.0-beta.25 (Credentials provider, JWT strategy)
ORM	Prisma 5.22 (dual schema — see §4) + <code>@prisma/adapter-pg</code> (driver adapters)
State (client)	Zustand (cart)
Forms / misc	react-hook-form, zod, date-fns, recharts, qrcode.react, react-hot-toast
Local dev DB	MySQL (<code>prisma/schema.prisma</code>)
Production DB	PostgreSQL on Supabase (<code>prisma/schema.postgres.prisma</code>)
Hosting	Vercel (project <code>pos-cafe</code> , account <code>codezen879</code>)

Why dual databases? Local development targets MySQL for speed and developer familiarity; the production deployment on Vercel targets a Supabase PostgreSQL instance. Nothing in application code knows which DB it is using — the Prisma client is selected at runtime (see §4).

2. Repository Layout

```

POS_CAFE/
├─ prisma/
|   ├─ schema.prisma           # MySQL schema (local dev)
|   ├─ schema.postgres.prisma  # PostgreSQL schema (Supabase/Vercel) – generator outputs to ../src/
|   ├─ seed.ts                 # MySQL seed
|   └─ seed.pg.ts              # PostgreSQL seed (idempotent upserts)
├─ public/
├─ docs/                       # this document
├─ next.config.ts              # minimal (reactStrictMode: true)
├─ tsconfig.json               # path alias "@/*" → "../src/*"
├─ .env .env.local             # NOT committed; see §5
├─ .gitignore                  # also ignores prod-server.log
├─ package.json
└─ src/
    ├─ generated/pg/           # generated Prisma client for PostgreSQL (ignored by git)
    ├─ app/
    |   ├─ layout.tsx          # root layout: <Providers> + globals.css
    |   ├─ globals.css         # Tailwind directives
    |   ├─ (auth)/login/page.tsx# PIN / password login form
    |   ├─ (app)/layout.tsx    # guarded app shell (redirects to /login)
    |   ├─ (app)/...           # dashboard, tables, kitchen, menu, orders, billing,
    |   |                       # customers, inventory, staff, settings, reports
    |   ├─ m/page.tsx          # PUBLIC mobile guest menu (the /m app)
    |   └─ api/...             # all API route handlers (see §8)
    ├─ components/
    |   ├─ ui/                 # shadcn-style primitives
    |   ├─ app-shell.tsx       # sidebar + topbar for staff app
    |   ├─ providers.tsx       # SessionProvider + ThemeProvider + Toaster
    |   ├─ pos/                # table-grid.tsx, table-terminal.tsx, bill-view.tsx,
    |   |                       # receipt.tsx, open-table-dialog.tsx, manage-tables-dialog.tsx
    |   ├─ dining/dining-menu.tsx# guest mobile ordering UI
    |   ├─ kitchen/kitchen-board.tsx
    |   ├─ billing/billing-list.tsx
    |   ├─ orders/orders-list.tsx
    |   ├─ menu/menu-manager.tsx
    |   ├─ inventory/inventory-manager.tsx
    |   ├─ staff/staff-manager.tsx
    |   ├─ customers/customers-list.tsx
    |   ├─ reports/reports.tsx
    |   ├─ settings/settings-manager.tsx
    |   └─ dashboard/dashboard.tsx
    ├─ store/cart.ts           # zustand cart store shared by ordering UIs
    ├─ config/nav.ts           # navigation tree with per-role filtering
    └─ lib/
        ├─ auth.ts             # NextAuth config (credentials, JWT, trustHost)
        └─ session.ts          # requireUser / requireRole / role helpers

```

```

└─ api.ts           # apiAuth(...roles) guard for route handlers
└─ prisma.ts        # runtime client selection (pg vs mysql)
└─ billing.ts       # computeBillForSession() – the tax engine
└─ serialize.ts     # toPlain() – Decimal/Date safe serialization
└─ utils.ts         # cn, formatCurrency, generateReference, jsonError, ...

```

3. Runtime & Toolchain

- Node **24.14.1**, npm (Vercel's build environment runs Node 22+).
- Install once: `npm install` (postinstall runs `prisma generate` for **both** schemas — this is why both clients exist).
- Verified dev commands:
- `npm run dev` — local dev server
- `npm run build` — production build (the authoritative check before committing)
- `npm run vercel-build` — the Vercel install/build: generates both Prisma clients then `next build`
- `npm run db:push` / `npm run db:push:pg` — push schema to MySQL / PostgreSQL
- `npm run db:seed` / `npm run db:seed:pg` — seed (Postgres variant requires `POSTGRES_URL`)
- `npm run generate:pg` — regenerate the PostgreSQL client
- **Linting:** there is no ESLint config; `npm run lint` (`next lint`) is effectively a no-op/deprecated. Use `npm run build` as the gate (Next runs its own type checks).

4. The Two-Backend Architecture (Important)

4.1 Two schemas, two generated clients

	Local	Production
Schema file	<code>prisma/schema.prisma</code>	<code>prisma/schema.postgres.prisma</code>
Datasource	<code>mysql</code> / <code>DATABASE_URL</code>	<code>postgresql</code> / <code>POSTGRES_URL</code>
Generated client	<code>@prisma/client</code> (in <code>node_modules</code>)	<code>../src/generated/pg</code> (custom output)
Driver	default (mysql2 under the hood)	<code>@prisma/adapter-pg</code> (driver adapters)

The PostgreSQL schema adds `previewFeatures = ["driverAdapters"]` and `output = "../src/generated/pg"` .

4.2 Runtime selection — `src/lib/prisma.ts`

```

export const prisma: PrismaClient = process.env.POSTGRES_URL
  ? createPostgresClient() // Pool + PrismaPg adapter + generated/pg client
  : new PrismaClient();    // default MySQL client

```

- The exported object is typed as the MySQL `PrismaClient` to keep compile-time field types identical; the pg client is cast.
- Selecting by the presence of `POSTGRES_URL` means: set `POSTGRES_URL` locally and the *same code* talks to Supabase — this is the pattern used by the QA scripts and local testing.
- A global cache (`globalThis.prisma`) avoids leaking connections during dev hot-reloads.

4.3 Changing the schema — the golden rule

Every model/field/enum change must be mirrored in BOTH schema files, or the MySQL and PostgreSQL apps drift. Procedure:

1. Edit `prisma/schema.prisma` and `prisma/schema.postgres.prisma` identically.
2. `npm run db:push` (MySQL) and, with `POSTGRES_URL` set, `npm run db:push:pg` (Supabase).
3. `prisma generate` runs automatically on install; or run `npm run generate:pg` for the pg client.
4. Update both seeders if you seeded sample data that should exist in both DBs.

5. Environment Variables & Secret Management

`.env` / `.env.local` are gitignored. Required variables:

Variable	Used by	Notes
<code>DATABASE_URL</code>	MySQL (schema.prisma)	Local dev only. Also present (legacy) in Vercel but ignored on the pg path.
<code>POSTGRES_URL</code>	PostgreSQL path + Supabase	The signal that selects the pg backend. On Vercel this is the transaction pooler URL.
<code>AUTH_SECRET</code>	NextAuth v5 JWT signing	Any long random string; set identically across local + Vercel.
<code>AUTH_URL</code>	NextAuth	Production URL (<code>https://pos-cafe-eight.vercel.app</code>); Vercel sets it automatically but can be forced.
<code>NEXT_PUBLIC_APP_NAME</code>	Public branding	e.g. "POS Cafe"
<code>NEXT_PUBLIC_APP_URL</code>	Public links	Production URL

Supabase connection URLs (project `nurjnwcxibvpiofgijtf`)

- **Transaction pooler** (`:6543`) — use on Vercel (serverless-safe) and inside transactions.
- **Session pooler** (`:5432`) — use for local scripts, `prisma db push`, seeds.
- The **legacy direct host is IPv6-only** and will hang/never connect — do not use it.

Deploy environment

- Vercel project `pos-cafe` (account `codezen879`). Production + Preview share the same env values.
- Deploy from the **project directory only**: `npx vercel --prod --yes` . Running `vercel` from your home directory triggers the "deploying home directory" prompt and fails.

- `trustHost: true` in `src/lib/auth.ts` is required for NextAuth v5 to trust the Vercel host (otherwise callbacks/sign-ins break).
- **Vercel blocks vulnerable Next versions:** it refused to build Next **15.2.4** ("Vulnerable version of Next.js detected", CVE-2025-66478). The lockfile pins `next@15.2.8`, `react@19.0.1`, `react-dom@19.0.1`. Never downgrade below 15.2.8 without a release, or deploys will be rejected.

Seeded credentials (both DBs)

Role	Email	Password	PIN
SUPER_ADMIN (Store Admin)	admin@poscafe.example	admin123	1234
CASHIER (Rahul)	cashier@poscafe.example	staff123	5678
KITCHEN (Chef Ayesha)	kitchen@poscafe.example	staff123	1111

6. Data Model

Enums: `Role` (SUPER_ADMIN, ADMIN, MANAGER, CASHIER, WAITER, KITCHEN) · `TableStatus` (AVAILABLE, OCCUPIED, RESERVED, CLEANING, CLOSED) · `SeatStatus` (FREE, OCCUPIED) · `SessionStatus` (OPEN, CLOSED, CANCELLED) · `OrderType` (DINE_IN, TAKEAWAY, DELIVERY, ONLINE) · `OrderStatus` (DRAFT, SENT_TO_KITCHEN, PREPARING, READY, PARTIALLY_SERVED, SERVED, CANCELLED) · `BillStatus` (DRAFT, ISSUED, PARTIALLY_PAID, PAID, VOID, REFUNDED) · `PaymentMethod` (CASH, CARD, UPI, WALLET, SPLIT, ON_ACCOUNT) · `PaymentStatus` (PENDING, COMPLETED, FAILED, REFUNDED, VOIDED) · `StockMovementType` (PURCHASE, CONSUMPTION, ADJUSTMENT, STOCKTAKE, WASTAGE) · `LoyaltyType` (EARN, REDEEM, EXPIRE, ADJUST).

Model	Table	Responsibilities / key relationships
User	users	Staff. <code>passwordHash</code> + <code>pin</code> (bcrypt). Optional <code>storeId</code> . Related to shifts/sessions/orders/payments/bills/invoices.
Store	stores	Single store is the norm (<code>store.findFirst()</code> everywhere). Holds GSTIN, address, currency, tax rates, settings, sessions, tables.
StaffShift	staff_shifts	Clock in/out with cash handling.
TaxRate	tax_rates	<code>code</code> (CGST/SGST/...), <code>rate</code> , unique <code>[storeId, code]</code> . Used for GST split.
Setting	settings	Key/value store, unique <code>[storeId, key]</code> . e.g. <code>service_charge_percent</code> , <code>loyalty_points_per_rupee</code> .
MenuCategory	menu_categories	<code>slug</code> unique; <code>icon</code> , <code>sortOrder</code> , active flag; 1→N Products.
Product	products	<code>basePrice</code> (Decimal), <code>costPrice</code> , <code>taxRateId</code> , <code>isVeg</code> , <code>isBestseller</code> , <code>isAvailable</code> , <code>prepTimeMins</code> , <code>maxOrderQty</code> , <code>image</code> , <code>sortOrder</code> . N—M with AddonOption via <code>ProductAddon</code> .
AddonOption	addon_options	Reusable add-on ("Whipped Cream", "Extra Shot") with <code>price</code> .
ProductAddon	product_addons	Join: <code>productId × addonId</code> with <code>mandatory</code> , <code>maxSelect</code> , <code>sortOrder</code> .
Floor	floors	Optional grouping for tables.
DiningTable	tables	<code>tableName</code> (T1...), <code>seatCount</code> , <code>status</code> , <code>qrCode</code> . Owns <code>seats</code> . Has many sessions.
TableSeat	table_seats	Per-table seats, unique <code>[tableId, seatNo]</code> .
Customer	customers	Loyalty: <code>loyaltyPoints</code> , <code>tier</code> . Has sessions, reviews, loyaltyTxns.
TableSession	sessions	The unit of service. <code>sessionNumber</code> (unique, e.g. <code>TAB-...</code>), <code>tableId</code> , <code>guestCount</code> , <code>customerId</code> , <code>servedById</code> , <code>status</code> (OPEN/CLOSED). Has orders; 1:1 bill.
Order	orders	<code>orderNumber</code> (unique), <code>sessionId</code> , <code>type</code> , <code>status</code> ; lifecycle timestamps <code>sentToKitchenAt</code> / <code>prepStartedAt</code> / <code>readyAt</code> / <code>servedAt</code> / <code>cancelledAt</code> .
OrderItem	order_items	Snapshot of <code>name</code> + <code>unitPrice</code> + <code>quantity</code> + <code>note</code> (price/name snapshotted so later menu edits don't rewrite history).
OrderItemAddon	order_item_addons	Addon snapshot per order item: <code>name</code> , <code>price</code> , <code>quantity</code> .
Bill	bills	<code>billNumber</code> unique, 1:1 with session. Holds computed <code>subtotal</code> / <code>discountAmount</code> / <code>taxTotal</code> / <code>serviceCharge</code> / <code>roundOff</code> / <code>total</code> / <code>paidAmount</code> / <code>dueAmount</code> , plus <code>issuedById</code> , <code>voidReason</code> , tax lines, payments, invoice 1:1, credit note 1:1.
BillTaxLine	bill_tax_lines	One row per tax code on the bill (rate, baseAmount, taxAmount).
Payment	payments	<code>method</code> , <code>amount</code> , <code>status</code> , <code>receivedById</code> , <code>paidAt</code> . Split payments = many rows against one bill.
Invoice	invoices	GST invoice snapshot (taxableValue, cgst, sgst, igst, total).
CreditNote	credit_notes	<code>noteNumber</code> , <code>amount</code> , <code>reason</code> .
LoyaltyTransaction	loyalty_transactions	points earn/redeem ledger per customer.

Model	Table	Responsibilities / key relationships
Review	reviews	Star rating + comment, optionally tied to customer/session.
Supplier	suppliers	Ingredient supplier with contact info, ideologies for movements.
Ingredient	ingredients	Stocked raw material: <code>stockQty</code> , <code>reorderLevel</code> , <code>costPerUnit</code> .
RecipeItem	recipe_items	How much of an ingredient a product consumes (<code>qtyUsed</code>).
StockMovement	stock_movements	<code>type</code> , <code>quantity</code> , <code>unitCost</code> , <code>note</code> . Ingredient stock audit trail.

Design notes to respect while coding:

- **Money is** `Decimal(10,2)` in the DB. Prisma returns `Decimal` objects that **cannot be serialized to JSON** or passed into client components directly — always wrap payloads with `toPlain()` (see §7).
- **Price/name snapshots:** `OrderItem.name/unitPrice` and `OrderItemAddon.name/price` are copied at order time. Never recompute them from `Product` on read.
- **Order lifecycle statuses** flow DRAFT → SENT_TO_KITCHEN → PREPARING → READY → (PARTIALLY_)SERVED, with `CANCELLED` a terminal state. The kitchen board only shows statuses in that pipeline.
- **Session === occupancy:** a table is "occupied" while a session with `status: OPEN` exists. Opening creates the session and sets `DiningTable.status = OCCUPIED`; paying the full bill closes the session and frees the table (see §9).

7. Server Data Plumbing & Serialization

7.1 `toPlain()` — `src/lib/serialize.ts`

Every client component receives its data as JSON over the server boundary. Prisma `Decimal` and `Date` fields break that (Next error: "Only plain objects can be passed to Client Components"). The one-liner for that is:

```
export function toPlain<T>(value: T): T {
  return JSON.parse(JSON.stringify(value, (_k, v) => {
    if (isDecimal(v)) return v.toNumber();
    if (v instanceof Date) return v.toISOString();
    if (v instanceof Map) return Object.fromEntries(v);
    if (v instanceof Set) return Array.from(v);
    return v;
  })));
}
```

Pattern: in server components/page.tsx, query with Prisma then return `<ClientComponent data={toPlain(data) as any} />`. See `src/app/m/page.tsx` and `src/app/(app)/tables/page.tsx` for live examples.

7.2 Dynamic rendering

Pages that call `auth()` or `searchParams` are inherently dynamic. The public `/m` page explicitly sets `export const dynamic = "force-dynamic"` because it must reflect live menu + table state. New public pages should do the same; new staff pages mostly inherit dynamism from `auth()`.

7.3 Helpers — `src/lib/utils.ts`

- `cn(...)` — `clsx` + `tailwind-merge` for conditional classes (use everywhere, never template strings).
- `formatCurrency(n, "INR")` — `Intl.NumberFormat("en-IN")`; returns `₹<value>` fallback. **Note: no space** — `"₹30.00"`.
- `formatDate` / `formatDateTime` / `formatTime` / `timeAgo` — en-IN locale helpers. `timeAgo` powers the KDS.
- `generateReference(prefix)` — `PREFIX-<base36 timestamp><rand4>`; used for `ORD-...`, `TAB-...`, `BILL-...`.
- `initials(name)`, `slugify(str)`.
- `jsonError(message, status=500)` — returns `Response.json({ error })`; the caller convention.

8. Authentication & Authorization

8.1 NextAuth config — `src/lib/auth.ts`

- **Provider:** Credentials only. The form submits `email` (identifier: email **or** user id, resolved with `findFirst OR`), plus either `pin` or `password`.
- **PIN login** (fast path for terminals): compares against `user.pin` via bcrypt. If `pin` is supplied, PIN wins over password.
- **Password login:** compares against `user.passwordHash`.
- **Strategy:** JWT (`session: { strategy: "jwt" }`). The `jwt` and `session` callbacks stamp `id`, `role`, `storeId` onto the token and session user.
- `pages.signIn = "/login"`, `trustHost: true`.
- Route handlers: `src/app/api/auth/[...nextauth]/route.ts` exports `{ handlers }`.

8.2 Server-side guards

- `src/lib/session.ts`:
- `getCurrentUser()` — `auth()?.user ?? null`.
- `requireUser()` — redirects to `/login`.
- `requireRole(...roles)` — redirects to `/` if role not allowed (empty = any authenticated user).
- `isManager(role)` / `canManage(role)` — `SUPER_ADMIN | ADMIN | MANAGER`.
- `isServerStaff(role)` — role is CASHIER/WAITER/MANAGER/ADMIN/SUPER_ADMIN (usable for terminal access checks).
- `src/lib/api.ts`:
- `apiAuth(...roles)` — for route handlers. Returns the `{ id, role, storeId }` user or a `Response` (401/403). **The universal route-handler pattern:**


```
export async function GET() {
  const user = await apiAuth("SUPER_ADMIN", "ADMIN", "MANAGER");
  if (user instanceof Response) return user;
  // ... do work ...
  return Response.json({ ... });
}
```

- **There is no middleware.ts** — all protection is per-page (layout) and per-route (`apiAuth`). The (app) layout redirects unauthenticated users; public paths (`/login` , `/m` , `/api/m/*` , and the endpoints intentionally listed in §8.3) are unprotected by design.

8.3 Public (unauthenticated) endpoints — intentional

Endpoint	Why public
<code>/login</code> , <code>/api/auth/*</code>	Auth entry point
<code>/m</code> , <code>/m?table=<id></code>	Guest mobile menu
<code>GET /api/m/tables</code>	Guest checkout lists open tables
<code>POST /api/m/orders</code>	Guest places an order (safe because product names/prices are re-hydrated server-side — see §10.3)

8.4 Role gating in the UI

`src/config/nav.ts` defines the sidebar; `getNavGroups(role)` filters items with an `roles` array (Menu, Inventory, Staff, Reports → manager; Settings → SUPER_ADMIN/ADMIN). Add a new page by adding a `NavItem` ; add `roles` to hide it from lower roles.

9. Staff App — Core Flows

9.1 Login (`/login`)

Client form with a PIN/Password toggle; calls `signIn("credentials", { redirect: false, ... })` , toast on error, then `router.push(callbackUrl)` .

9.2 Table Service (`/tables` → `TableGrid` → `TableTerminal`)

1. **Server query** (`(app)/tables/page.tsx`): loads tables (with floor, OPEN sessions, customer, orders with items+addons), the menu (categories → active products with taxRate + addons), store (with taxRates), and recent customers for quick attach. All payloads run through `toPlain` .
2. `TableGrid` renders colored table cards. Click behavior:
 - occupied + has session → open `TableTerminal` ;
 - otherwise → `OpenTableDialog` (guest count + optional customer); on success calls `POST /api/pos/tables/<id>/open` → creates session `TAB-...` , frees nothing, sets table OCCUPIED.

- A **Menu QR** dialog shows the generic `/m` QR and one QR per currently open table (value `/m?table=<tableId>`).
- Manager-only **Manage** dialog (PATCH/DELETE via `/api/tables/:id`).
- 1. **TableTerminal** — the ordering/billing screen for one table:
 - Category chips → product cards (veg mark, code, price, prep time). Tapping a product with add-ons opens the add-on stepper (qty per add-on); without add-ons it adds directly.
 - Cart panel (zustand `useCart`): line items with add-on lines, qty steppers, remove; **Send to kitchen** → `POST /api/pos/sessions/<id>/order` (staff-authorized), then `toast.success("Order sent to kitchen")`, clears cart, refreshes.
 - **Bill** tab → `BillView` (§9.4).
- 1. **Live order management (Placed orders)** — a panel below the cart lists every active order for the table with `orderNumber`, live status badge, and `timeAgo(placedAt)`:
 - **Editable while** `DRAFT` / `SENT_TO_KITCHEN` / `PREPARING` (`EDITABLE_STATUSES` in `table-terminal.tsx`): qty steppers (`PATCH`), per-item remove (`DELETE`), and a **Cancel** button (confirm via `window.confirm`, reuses `PATCH /api/pos/orders/<id>`). Edits lock once `READY`, showing "This order can no longer be edited."
 - **Item API** lives in `src/app/api/pos/orders/[id]/items/[itemId]/route.ts`: `PATCH { quantity }` clamps 0–99 and rejects non-editable statuses with 409; `DELETE` removes the item and **auto-cancels the order when the last item is removed**.
 - TableGrid keeps the open terminal live: a `useEffect` re-syncs `terminalTable` from the refreshed `tables` prop, so send/edit/cancel/bill updates appear without reopening the table.

9.3 Kitchen Display (`/kitchen` → `KitchenBoard`)

- Polls `GET /api/pos/kitchen/orders` every **8 s** (setInterval + `load()` callback). Endpoint returns orders with `status` in (`SENT_TO_KITCHEN`, `PREPARING`, `READY`, `PARTIALLY_SERVED`) ordered by `sentToKitchenAt`.
- Kanban columns defined in `COLUMNS`; each card lists `orderNumber`, table name, `timeAgo(sentToKitchenAt)`, items with qty + add-ons (+ note in italics/destructive), and an **advance button**: `PATCH /api/pos/orders/<id> { status }` → the `STATUS_FIELD` map stamps `prepStartedAt` / `readyAt` / `servedAt` automatically and rejects transitions on `CANCELLED`/`SERVED`.

9.4 Billing & Payment (`BillView` , `Receipt`)

1. `BillView` loads `GET /api/pos/sessions/<id>/bill-detailed` (bill + payments + taxLines + session/table/customer/orders).
2. If no bill yet: discount UI (None / ₹ flat / % off; optional "Redeem points" — see §12) → **Generate bill** → `POST /api/pos/sessions/<id>/bill`. That route reads the `service_charge_percent` Setting, calls `computeBillForSession()`, and **upserts** the Bill keyed on `sessionId`, replacing `taxLines` wholesale (`deleteMany` + `create`). Bill becomes `ISSUED` with `dueAmount = total`.
3. Payment grid (CASH / UPI / CARD / SPLIT) + amount input (defaults to due) → **Receive** → `POST /api/pos/bills/<id>/pay`:
 - Creates a `Payment` (amount, method, receivedById).
 - Updates `paidAmount` / `dueAmount`; `isPaid` when `paidAmount ≥ total - 0.01` → status `PAID` else `PARTIALLY_PAID`.

- **On full settlement inside a `$transaction`** : closes the session (`CLOSED` , `closedAt`), frees the table (`AVAILABLE`), and if a customer is attached, awards loyalty points (`loyalty_points_per_rupee` Setting, `Math.floor(total)`) + inserts an EARN `LoyaltyTransaction` .
- 1. Settled bill → `Receipt` : printable 80 mm receipt (`#receipt-print` visibility trick under `@media print`), plus "This table left a review?" star dialog (`POST /api/reviews`).

9.5 Billing math — `src/lib/billing.ts` (`computeBillForSession`)

Consumed by the bill route; single source of truth for totals:

```
lineBase      = (unitPrice + Σ addon.price×qty) × qty          // per item
subtotal      = Σ lineBase
taxBucket     = product.taxRate.rate split in two: CGST + SGST, each rate/2
taxAmount     = lineBase × (rate/2) / 100 → per bucket
discount      = if PERCENTAGE: subtotal×value/100
               if FIXED: min(value, subtotal)
taxableBase   = subtotal - discount
taxTotal      = Σ bucket × taxableBase/100 × ... (bucket applies to taxableBase)
serviceCharge = subtotal × serviceChargePercent/100
total         = taxableBase + taxTotal + serviceCharge
```

All steps `round2` (×100/100). Excludes orders with status `CANCELLED` or `DRAFT` . **When you change pricing logic, change this file — never inline the math in route handlers.**

10. Mobile QR Ordering (`/m` — the guest feature)

10.1 Route wiring

Public guest ordering lives under three pieces:

Piece	Responsibility
<code>src/app/m/page.tsx</code>	<code>force-dynamic</code> RSC. Queries store, active categories (products + addons), and if <code>?table=</code> present, resolves that table + its latest OPEN session. Passes <code>table</code> prop to the client component.
<code>src/components/dining/dining-menu.tsx</code>	All guest UX (menu grid, Customize sheet, cart sheet, table chooser, send, success banner).
<code>GET /api/m/tables</code>	Public; returns <code>{ tables: [{ id, tableName }] }</code> for tables with an OPEN session (drives the checkout "Choose your table" step).
<code>POST /api/m/orders</code>	Public; validates and creates the kitchen order (see §10.3).

10.2 UX state machine (`dining-menu.tsx`)

`const tableLocked = !!table?.id && !table?.sessions?.[0];` — a **bound-but-not-open** table (server hasn't opened the session) blocks ordering and shows "This table isn't open yet — please ask your server." Otherwise guests can always add items:

- **Item card = a full** `<button>`; `onClick` opens the Customize sheet when the product has active add-ons, else adds it directly. `active:scale-[0.98]` gives tap feedback (this replaced the earlier silently-disabled buttons — see §14).
- **Customize sheet:** add-on rows are `<button aria-pressed>` toggles; selected rows highlight, show a `<Check>` icon and `+₹<price>`. Quantity stepper (1–99). "Add N to your order" → `addItem` with chosen add-ons.
- **Cart sheet** (bottom sheet, `max-h-[85vh]`): line items with add-on line, qty steppers, remove; subtotal via `computeSummary(lines)` (tax = 0 client-side; real tax is applied server-side at billing only).
- If no table is bound (`!table?.id`), a **table picker** lists open tables from `/api/m/tables`; selecting one enables Send. Send button label switches to **"Pick your table, then send"** until chosen.
- Send → `POST /api/m/orders` with `{ tableId: targetTableId, items: [{ productId, quantity, note, addons: [{id, quantity}] }] }`.
- **Success banner:** "N item(s) sent to the kitchen for Table T2" (emerald pill), cart cleared.

Single-flight rule with `targetTableId : table?.id` (from the QR) **or** the guest-picked `guestTableId`. Never both.

10.3 Order tamper-resistance (`POST /api/m/orders`)

The guest sends only **IDs** (productId, addon ids + quantities, note) — never names or prices:

1. `tableId` must exist and have an OPEN session, else 404/400.
2. Products are re-fetched by id server-side; only `ProductAddon` links pointing at `isActive` `AddonOptions` are honored (unknown → filtered out).
3. `name`, `unitPrice = product.basePrice`, and addon `name/price` are **hydrated from the DB**, so a malicious client cannot undercut prices or spoof names.
4. Clamps: `MAX_ITEMS = 50`, `MAX_QTY = 99`, per-addon qty ≤ 9.
5. Order is created with `status: "SENT_TO_KITCHEN"`, `sentToKitchenAt: now`, `orderNumber = ORD-...` (generated on the client terminal path too, via `generateReference`), and appears on the KDS automatically.

Known constraint: guest orders are tied to the table's OPEN session; if the session closes mid-cart the send will 400 ("This table is not open yet").

11. Cart Store (`src/store/cart.ts`)

Zustand store shared by `TableTerminal` and `DiningMenu`:

- `CartLine = { key, productId, name, unitPrice, quantity, note?, addons: CartAddon[] }`; **key** is **generated per add** (`<productId>-<Date.now()-<rand4>`).
- `addItem` **merges** consecutive identical plain (no-addon) lines: same `productId + note` with both addon arrays empty → quantities added. Any add-ons always produce a fresh line (merging addon lines is deliberately not implemented).
- `updateQty` with `qty ≤ 0` removes the line.
- `computeSummary(lines)` returns `{ subtotal, tax: 0, total: subtotal }` — used only for the guest cart display; authoritative totals happen in billing.

12. Loyalty, Reviews & Customers

- **Attach customer** at table-open (OpenTableDialog selects from `/api/customers`, recent 50) or via phone in the Redeem dialog.
 - `GET /api/customers/find?phone=+91...` → customer (or `{ customer: null }`).
 - **Redeem** (`bill-view.tsx` → `/api/customers/<id>/redeem`, `POST { points }`) → `{ cashValue }`; 100 points = ₹1, applied as a **FIXED** discount before bill generation. `LoyaltyTransaction` rows track EARN/REDEEM.
 - **Earn** happens automatically on full payment for the attached customer (see §9.4).
 - **Reviews** `POST /api/reviews { customerId, rating, comment }` from the post-settlement review dialog.
-

13. Menu & Inventory Management

- `MenuManager` (manager-only `/menu`) manages categories/products/add-ons against `GET/POST /api/menu/categories` and `/api/products` + `/api/products/<id>` (PATCH supports `addonIds` replace — deletes then recreates `ProductAddon` rows). `/api/products` **intentionally has no GET handler** → a bare `GET /api/products` returns **405**; that is by design, not a bug.
 - Add-ons are global `AddonOptions`; linking them to a product creates `ProductAddon`.
 - `InventoryManager` (manager-only `/inventory`) manages `GET/POST /api/stock` (ingredients, stock movements), plus suppliers via related routes. There is **no automated stock deduction** on order placement yet — ingredients are adjusted manually.
 - `SettingsManager` (SUPER_ADMIN/ADMIN) edits `/api/settings` (key/value, e.g. `service_charge_percent`, `loyalty_points_per_rupee`). `TaxRates` editable via `/api/tax-rates`.
-

14. API Route Inventory

Conventions: helpers from `@/lib/api` (`apiAuth`), `@/lib/utils` (`jsonError`, `generateReference`). `params` is a `Promise` in Next 15 — always `await params`. Route handlers return `Response.json({...})`; errors are `{ error }` with `jsonError`.

Method	Route	Auth	Purpose
POST	/api/auth/[...nextauth]	public	NextAuth handlers
GET	/api/tables	manager	All tables + floor + <code>_count.sessions</code>
POST	/api/tables	manager	Create table (also creates <code>seatCount TableSeat</code> s)
GET	/api/tables/floors	manager	(floors for selects)
PATCH	/api/tables/:id	manager	Update name/floor/seats/status; site-aware seat add/remove
DELETE	/api/tables/:id	manager	Delete table (blocked while an OPEN session exists)
GET	/api/floors , PATCH/DELETE /api/floors/:id	manager	Floor CRUD
GET	/api/menu/categories	manager/client	Categories (+ products via include)
GET	/api/products	—	No handler (405 by design)
POST	/api/products	manager	Create product
PATCH/DELETE	/api/products/:id	manager	Update product (incl. <code>addonIds</code> replace) / delete
GET	/api/staff	manager	List staff (id/name/email/role/isActive)
POST	/api/staff	manager	Add staff (bcrypt password + generated 4-digit PIN)
GET	/api/customers	staff	Customer list
GET	/api/customers/find	staff	<code>?phone=</code> lookup
POST	/api/customers/:id/redeem	staff	Redeem <code>{ points }</code> → <code>{ cashValue }</code>
POST	/api/reviews	staff	Create review
GET	/api/tax-rates	manager	Tax rates
GET	/api/settings	admin+	Settings
GET/POST	/api/stock	manager	Inventory + stock movements
POST	/api/pos/tables/:id/open	staff	Open session (409 if occupied)
POST	/api/pos/sessions/:id/order	staff	Staff order → SENT_TO_KITCHEN (server hydrates product identity)
GET	/api/pos/sessions/:id/bill-detailed	staff	Bill detail + payments + taxLines + session tree
POST	/api/pos/sessions/:id/bill	staff	Generate/refresh bill (upsert on <code>sessionId</code>)
GET	/api/pos/kitchen/orders	staff	KDS feed (4 active statuses)
PATCH	/api/pos/orders/:id	staff	Advance status; stamps lifecycle timestamps

Method	Route	Auth	Purpose
PATCH	<code>/api/pos/orders/:id/items/:itemId</code>	staff	Update item qty (clamped 1–99); 409 unless DRAFT/SENT_TO_KITCHEN/PREPARING
DELETE	<code>/api/pos/orders/:id/items/:itemId</code>	staff	Remove item; removing the last item cancels the order
POST	<code>/api/pos/bills/:id/pay</code>	staff	Record payment; settles → closes session + frees table + loyalty
GET	<code>/api/m/tables</code>	public	Open tables for guest checkout
POST	<code>/api/m/orders</code>	public	Guest order (tamper-safe, \$10.3)

15. Conventions & Recipes for Common Changes

15.1 Add a new API route

1. Create `src/app/api/<name>/route.ts` (or `src/app/api/<name>/[id]/route.ts`).
2. Use `apiAuth(...roles)` unless it is deliberately public (like the `/api/m/*` endpoints).
3. Guarded by `params: Promise<...> → const { id } = await params;`.
4. `req.json().catch(() => ({}))` for body parsing; validate required fields; respond with `jsonError(msg, code)` on failure.
5. Wrap DB work in `try/catch` returning `jsonError(e.message)`.

15.2 Add a new page (staff)

1. Create `src/app/(app)/<name>/page.tsx` — server component: `auth()` guard (the `(app)` layout already redirects, but pages that branch on role still call `auth()`), Prisma queries, `toPlain()` the payloads, render a `"use client"` component from `src/components/`.
2. Register navigation in `src/config/nav.ts` (add `roles` to gate by role).
3. If role-conditional UI is needed server-side, use `requireRole(...)` from `@/lib/session`.

15.3 Add a public/page-less path (guest)

- Server page under `src/app/<route>/page.tsx` with `export const dynamic = "force-dynamic"`.
- Guest data endpoints under `src/app/api/m/*` and mark them explicitly public in §8.3 and §14.

15.4 Add/extend a database field

Follow §4.3 exactly (both schemas → push both → generate → seed both). Then: if it's a menu/UI-visible field, update the matching `toPlain()` consumer. **Do not forget to run `npm run generate:pg` locally or the pg import will fail to typecheck** (`vercel-build` does this automatically).

15.5 Styling

- Shadcn-style primitives in `src/components/ui/*` (Button, Dialog, Input, Label, Select, Switch, Tabs, Badge, Card, Textarea, Toaster). Use those instead of hand-rolled DOM.
- Variant classes via `cn("bg-...", cond && "...")` and inline `Record<status, class>` maps (see `statusStyle` in `table-grid.tsx`, `COLUMNS` in `kitchen-board.tsx`).
- Paper-like receipts, bottom sheets and the KDS use plain Tailwind with arbitrary values (`max-h-[85vh]`, `pb-[max(0.75rem,env(safe-area-inset-bottom))]`) — keep the safe-area padding on mobile.

15.6 Verifying changes

1. `npm run build` (does type checking).
2. Local: `npm run dev`, log in, exercise the touched flow.
3. Against production DB locally: set `POSTGRES_URL` (session pooler, `:5432`) and run the same app (the QA harnesses in §16 do this through the real origin).
4. Deploy: `npx vercel --prod --yes` **from the project directory**.

16. QA & Verification Harness

During the mobile-ordering work, browser QA was driven with `puppeteer-core` + the installed Chrome (`C:\Program Files\Google\Chrome\Application\chrome.exe`) from a scratch dir, against `$env:BASE` (`https://pos-cafe-eight.vercel.app`). Scripts live outside the repo in a temp workspace and use fetch-cookie login + real open-table flows; a `cleanup_t2.mjs` helper resets test table `T2` (closes OPEN sessions, sets AVAILABLE). Observations from that work:

- Always clean the test table between runs (an OPEN leftover session makes re-open return 409).
- Cold-start latency matters: wait for selectors rather than fixed sleeps; allow a few seconds after first request.
- Assert via **accessible state** (`aria-pressed`, rendered text, `disabled`) rather than pixel heuristics.

17. Pitfalls & Lessons Learned (read before changing anything)

1. `POSTGRES_URL` **presence switches DB backends**. Accidentally setting it locally changes everything; conversely, forgetting it on Vercel yields MySQL's client with no MySQL host → boot errors. It is the single most important env var.
2. **Never deploy without regenerating the pg client**: any schema drift breaks `src/generated/pg` typecheck in Vercel builds.
3. **Prisma relation `where` on to-one includes is disallowed**. You can filter `10` filters in the `*include*` only for to-many relations. Ordering logic that needs conditional to-one data must `findMany` then filter in JS (this shaped `/api/m/orders` addon handling).
4. **Decimal/Date must pass through `toPlain`** before crossing the RSC→client boundary. Missing it throws a hard Next serialization error.
5. **Vercel blocks Next < 15.2.8** (CVE-2025-66478). Never downgrade.
6. `vercel` **fights back if run from the wrong cwd** (home directory → "deploying home directory"). Always `npx vercel --prod --yes` inside `POS_CAFE`.

7. **Supabase legacy direct host is IPv6-only** → use poolers: `:6543` (transaction) on Vercel, `:5432` (session) for scripts/push/seed.
 8. `/api/products` **GET** → **405 is intentional**. Callers must use the category endpoint.
 9. **Money**: `₹30.00` has no space after `₹`; string-matching UIs (e.g. add-on "+₹" chips) depend on this.
 10. **Mobile UX regression guard**: item cards are full-tap `<button>`s; never reintroduce separately-disabled inner buttons without visible feedback, or "tap does nothing" returns (the exact bug that drove Round 2 of the mobile fix).
 11. **Status lifecycle**: loans on `PATCH /api/pos/orders/:id` — CANCELLED and SERVED are final; transition validation lives in the route, keep it there.
 12. **Session/table consistency**: session OPEN ↔ table OCCUPIED must always be updated together (create/open in a single request; settle path uses a `$transaction`).
-

18. Deployment & Operations Quick Reference

```
# Install & generate both clients
npm install

# Sync schema to both DBs (set POSTGRES_URL for the pg push)
npm run db:push
npm run db:push:pg

# Seed both (POSTGRES_URL required for pg)
npm run db:seed
npm run db:seed:pg

# Local
npm run dev

# Build check
npm run build

# Deploy production (must run from POS_CAFE dir)
npx vercel --prod --yes
```

Deployment URL: `https://pos-cafe-eight.vercel.app` (Vercel project `pos-cafe`). Verify a new deploy with the login flow (admin@poscafe.example / admin123), the Tables→Menu QR→table chip→Scan path, and the kitchen board.