



Smart Multilingual

Complete User Guide

A lightweight multilingual solution for WordPress. Setup, translation workflow, Elementor, WooCommerce, RTL, typography and shortcodes — all in one place.

Contents

PART 1 Getting Started

1	First Setup	3
2	Source / Default Language	4
3	Adding a New Language	5

PART 2 Translating Content

4	Translating Pages and Posts	5
5	Translation Groups	6
6	Translating Elementor Pages	7

PART 3 Headers, Footers & Menus

7	Translating Elementor Pro Headers and Footers	7
8	Elementor Header/Footer Troubleshooting	9
9	Translating Navigation Menus	9
10	Menu Translation Tool	10

PART 4 Language Switcher

11	Language Switcher	10
12	Switcher Labels	11
13	Missing Translation Behavior	11
14	Language Switcher Shortcode	12
15	Custom Switcher Layout	12
16	Custom Switcher Labels	12
17	Custom CSS Class for the Switcher	13
18	Shortcode Missing Translation Behavior	13

PART 5 Language-Based Content & Strings

19	Display Different Content by Language	14
20	Show Content Only in One Language	14
21	String Translation	15
22	Language-Only Strings	15
23	Frontend Strings	15
24	HTML Attribute Translation	16
25	Scoped String Translation	16
26	String Shortcode	17
27	Sidebar Mapping	17

PART 6 WooCommerce

28	WooCommerce Products	17
29	WooCommerce Categories and Terms	18
30	WooCommerce Attribute Labels	18

PART 7 Media & Sliders

31	Media Translation	19
----	-------------------------	----

32	Media Text Shortcode	19
33	Revolution Slider	19

PART 8 RTL & Typography

34	RTL Languages	20
35	Elementor RTL Layout	20
36	Reverse Elementor Rows in RTL	20
37	Per-Language Typography	21
38	Font Sources	21
39	Existing Fonts	22
40	Typography Targets	22
41	Language Switcher Colors	22

PART 9 Compatibility, SEO & URLs

42	Compatibility Profiles	23
43	Translated Taxonomy Routes	23
44	Translated Media Metadata	23
45	Language-Aware Lists and Archives	24
46	Elementor Header & Footer Compatibility	24
47	Legacy Compatibility Bundle	24
48	SEO and hreflang	25
49	URL Structure	25
50	Translation Slugs	25
51	When a New Language Returns 404	26

PART 10 Workflows & Best Practices

52	Recommended Workflow for a New Website	26
53	Recommended Elementor Workflow	27
54	Do Not Duplicate Pages Manually	27
55	Do Not Change Translation Group IDs	27
56	Caching	28

PART 11 RTL Testing & Custom CSS

57	Testing RTL	28
58	Language-Specific CSS	29
59	Language-Specific Visibility	29

PART 12 Troubleshooting, Updates & Final Setup

60	Common Problems	30
61	Updating Smart Multilingual	31
62	Final Recommended Configuration	31

APPENDIX Quick Reference

A	Shortcode Quick Reference	32
---	---------------------------------	----

Introduction

Smart Multilingual is a lightweight multilingual solution for WordPress designed to manage multiple languages without changing the WordPress dashboard language or forcing a specific theme structure.

It supports:

Standard WordPress content

Elementor

Elementor Pro Theme Builder

WooCommerce

Taxonomies

Menus

Media metadata

Frontend strings

RTL languages

Per-language typography

Revolution Slider

Language-aware URLs

This guide explains the complete setup and recommended workflow.

PART 1 Getting Started

1 First Setup

After activating Smart Multilingual, go to:

GO TO [WordPress Dashboard](#) → [Languages](#)

Then open:

GO TO [Languages](#) → [Manage Languages](#)

This page contains all languages available on the website.

Each language has several fields:

- **Enabled** – activates or disables the language.
- **Code** – the internal language code, such as `en`, `ar`, `tr`, `de`.
- **Name** – the English language name, for example Arabic.
- **Native Name** – the name shown in its native language, for example العربية.
- **Locale** – the WordPress locale, for example `ar` or `ar_SA`.
- **Prefix** – URL prefix used for secondary languages.
- **Direction** – LTR or RTL.
- **hreflang** – SEO language code used in alternate language links.

Example:

```
Code: ar
Name: Arabic
Native Name: العربية
Locale: ar
Prefix: ar
Direction: RTL
hreflang: ar
```

After adding or changing a language, click **Save**.

If the new language URL does not open immediately, go to:

GO TO Settings → Permalinks

and click **Save Changes**.

NOTE

You do not need to change the permalink structure.

2 Source / Default Language

Go to:

GO TO Languages → Settings → General

Under **Website languages**, select **Default / source language**.

The source language is the main language of the website. It always uses the main website URL without a language prefix.

For example, if English is the source language:

```
https://example.com/
```

Arabic could use:

```
https://example.com/ar/
```

Turkish could use:

```
https://example.com/tr/
```

Changing the source language also changes which language owns the root URL.

IMPORTANT

After changing the source language, save the settings and refresh WordPress permalinks once.

3 Adding a New Language

Go to:

GO TO Languages → Manage Languages

Click **Add Language**, enter the language information and save it.

Recommended example for Arabic:

```
Code: ar
Name: Arabic
Native: العربية
Locale: ar
Prefix: ar
Direction: RTL
hreflang: ar
```

Recommended example for German:

```
Code: de
Name: German
Native: Deutsch
Locale: de_DE
Prefix: de
Direction: LTR
hreflang: de
```

Smart Multilingual automatically uses the language code when creating translated slugs. For example:

```
about
about-ar
about-de
```

TIP

You do not need to manually add language suffixes.

PART 2 Translating Content

4 Translating Pages and Posts

Smart Multilingual does not translate content automatically. Instead, every language version is stored as a separate WordPress post or page.

This gives you complete control over:

- Content
- SEO
- Elementor design
- Images
- Custom fields
- Meta data
- WooCommerce information
- URLs

Open the page you want to translate. In the editor you will see the **Language & Translations** panel. The current page language is displayed there.

For every enabled language you will see either:

- an existing translation, or
- an option to create one.

Click **Create Translation**. Smart Multilingual creates a new translation draft and links it to the original page.

The translated page receives:

- the same translation group
- the target language
- copied content
- copied post meta
- copied Elementor data
- copied custom fields where applicable
- copied taxonomy relationships where possible

Then edit the translated page normally. For Elementor pages, click **Edit with Elementor** and translate the content.

Finally, publish the translation.

5 Translation Groups

Smart Multilingual connects translated content through a hidden translation group.

For example, these pages:

English Page
Arabic Page
German Page

can all belong to the same translation group. This tells Smart Multilingual that these pages are different language versions of the same content.

IMPORTANT

You should not manually change the translation group unless you are troubleshooting a broken translation relationship.

6 Translating Elementor Pages

Elementor translations work as independent Elementor documents. When a translation is created, Smart Multilingual copies the Elementor structure from the source page.

This includes:

- Containers
- Sections
- Widgets
- Responsive settings
- Custom CSS data
- Elementor widget settings
- Images
- HTML widgets
- Global design references where available

After creating the translation:

1. Open the translated page.
2. Click **Edit with Elementor**.
3. Replace the text with the translated content.
4. Replace images if necessary.
5. Adjust alignment for the target language if required.
6. Publish the page.

TIP

You do not need to recreate the entire Elementor design manually.

PART 3 Headers, Footers & Menus

7 Translating Elementor Pro Headers and Footers

Smart Multilingual supports Elementor Pro Theme Builder headers and footers.

This is important because Elementor Pro normally selects one Theme Builder template globally. Smart Multilingual maps that template to the correct translated version for the active language.

Recommended workflow

Go to:

GO TO [Templates](#) → [Theme Builder](#)

Open your original Header or Footer. In the WordPress editor, locate **Language & Translations** and create a translation for the target language. For example:

```
English Header
  ↓
Arabic Header
```

Then edit the new Header with Elementor and translate:

- Navigation labels
- Buttons
- Contact information
- Text
- Logos if required
- Links
- Icons if necessary

Do the same for the Footer. The templates must remain connected through the same translation group.

Important

Go to:

GO TO [Languages](#) → [Settings](#) → [Compatibility](#)

Enable **Elementor Header & Footer Builder templates**. This compatibility option also handles Elementor Theme Builder template mapping.

Once enabled, Smart Multilingual detects the current frontend language and replaces the original header/footer template with the translated version.

Example:

```
English:
Header ID 51
Footer ID 70

Arabic:
Header ID 95
Footer ID 98
```

When a visitor opens `/ar/`, Smart Multilingual automatically displays the Arabic header and footer.

TIP

No manual template selection is required per page.

8 Elementor Header/Footer Troubleshooting

If the translated page works but the original Header or Footer still appears, check the following.

First make sure the translated Header/Footer:

- is published
- belongs to the same Translation Group
- has the correct language
- was created from the original Header/Footer
- has Elementor display conditions
- is recognized as a Header or Footer template

Also verify that this option is enabled:

GO TO Languages → Settings → Compatibility → Elementor Header & Footer Builder templates

If Elementor caching is involved, also regenerate Elementor files:

GO TO Elementor → Tools → Regenerate CSS & Data

Then clear any page cache or CDN cache.

9 Translating Navigation Menus

There are two ways to manage menus.

Method 1 – Create a separate menu for each language

Go to:

GO TO Appearance → Menus

Create one menu for each language. Example:

Main Menu English
Main Menu Arabic
Main Menu German

Then go to:

GO TO Languages → Settings → General → Menus by language

Assign the correct menu to each language. Example:

```
English → Main Menu English
Arabic → Main Menu Arabic
German → Main Menu German
```

If you select **Use theme menu**, Smart Multilingual allows the active theme to decide which menu should be displayed.

10 Menu Translation Tool

Smart Multilingual also includes:

[GO TO](#) [Languages](#) → [Menus](#)

This tool can clone an existing menu into another language. When cloning a menu, Smart Multilingual attempts to replace menu items with their translated equivalents.

For example, these menu items:

```
About Us
Products
Contact
```

can be cloned into an Arabic menu and linked to the Arabic versions of those pages.

IMPORTANT

After cloning, review the menu manually before using it.

PART 4 Language Switcher

11 Language Switcher

The language switcher can be configured under:

[GO TO](#) [Languages](#) → [Settings](#) → [Switcher & RTL](#)

Choose which languages should appear in the switcher.

You can configure the layout:

- **Dropdown** – displays the languages inside a dropdown menu.
- **Inline list** – displays all languages next to each other.

12 Switcher Labels

The switcher supports three label modes.

Native Names

Example:

```
English  
العربية  
Deutsch
```

Short Codes

Example:

```
EN  
AR  
DE
```

Full Names

Uses the configured full language name.

13 Missing Translation Behavior

If a visitor changes language while viewing a page that does not have a translation, Smart Multilingual can handle it in three ways.

Language Homepage

The visitor is sent to the homepage of the selected language.

Example: `/about/` has no Arabic translation. Switching to Arabic sends the visitor to:

```
/ar/
```

Same Path

Smart Multilingual attempts to open the same URL path in the selected language.

Example: `/about/` becomes:

```
/ar/about/
```

IMPORTANT

Use this only when your website structure supports matching paths.

Hide Language

The unavailable language is not displayed in the language switcher for that page.

TIP

This is often the safest option for websites with incomplete translations.

14 Language Switcher Shortcode

The default shortcode is:

```
[sm_language_switcher]
```

You can place it inside:

- Elementor Shortcode widget
- Header
- Footer
- Sidebar
- WordPress content
- Theme templates

There is also a shorter alias:

```
[sm_switcher]
```

Both work the same way.

15 Custom Switcher Layout

Force a dropdown:

```
[sm_language_switcher layout="dropdown"]
```

Force an inline list:

```
[sm_language_switcher layout="list"]
```

16 Custom Switcher Labels

Use native language names:

```
[sm_language_switcher style="native"]
```

Use language codes:

```
[sml_language_switcher style="short"]
```

Output example:

```
EN AR DE
```

Use full language names:

```
[sml_language_switcher style="full"]
```

17 Custom CSS Class for the Switcher

You can add your own class:

```
[sml_language_switcher class="my-language-switcher"]
```

Then style it with CSS:

```
.my-language-switcher {  
  font-size: 14px;  
}
```

18 Shortcode Missing Translation Behavior

You can override the global missing translation setting directly in the shortcode.

Send the visitor to the language homepage:

```
[sml_language_switcher missing="home"]
```

Use the same path:

```
[sml_language_switcher missing="path"]
```

Hide unavailable languages:

```
[sml_language_switcher missing="hide"]
```

19 Display Different Content by Language

Use:

```
[sm1_language_value]
```

Example:

```
[sm1_language_value en="Contact Us" ar="اتصل بنا"]
```

Smart Multilingual returns the value matching the active language. You can also use the short alias:

```
[sm1_value en="Contact Us" ar="اتصل بنا"]
```

This is useful for:

- Buttons
- Small labels
- Elementor shortcode widgets
- Theme templates
- Reusable blocks

20 Show Content Only in One Language

Use:

```
[sm1_show lang="ar"]  
Arabic content here  
[/sm1_show]
```

The content is only displayed when Arabic is active.

Multiple languages are supported:

```
[sm1_show languages="ar,tr"]  
Content visible only in Arabic and Turkish.  
[/sm1_show]
```

You can separate languages with a comma `,`, a pipe `|`, or a space. For example:

```
languages="ar|tr|de"
```

21 String Translation

Some theme or plugin text is not stored inside pages. Examples include:

- Search
- Read More
- Add to Cart
- Custom theme labels
- Widget text
- Plugin-generated text

Go to:

GO TO Languages → Strings

Each secondary language has its own translation rules.

22 Language-Only Strings

This section is useful when a specific phrase should only change in one language.

Format:

```
Original text|||Translated text
```

Example:

```
Customer Service|||خدمة العملاء
```

Add one rule per line. These rules only run for the language where they are configured.

23 Frontend Strings

Frontend strings use the same format:

```
Original text|||Translation
```

Example:

```
Read More|||اقرأ المزيد
```

Use one translation per line.

24 HTML Attribute Translation

Smart Multilingual can also translate HTML attributes. Supported attributes include:

- `placeholder`
- `title`
- `aria-label`
- `aria-placeholder`
- `value`

Format:

```
attribute|||original value|||translated value
```

Example:

```
placeholder|||Search...|||بحث...
```

This is useful for:

- Search inputs
- Form fields
- Accessibility labels
- Buttons
- Theme controls

25 Scoped String Translation

Sometimes the same English phrase appears in multiple places but only one occurrence should be translated. Use a CSS selector.

Format:

```
CSS selector|||Original text|||Translation
```

Example:

```
.header-contact|||Contact|||اتصل بنا
```

Smart Multilingual will only replace *Contact* inside elements matching `.header-contact`.

TIP

This prevents unwanted global replacements.

26 String Shortcode

You can also use:

```
[sm1_string]
```

Example:

```
[sm1_string]Contact[/sm1_string]
```

Or:

```
[sm1_string key="Contact"]
```

Smart Multilingual returns the translated version for the active language.

27 Sidebar Mapping

Different sidebars can be assigned to different languages.

Format:

```
source-sidebar|||translated-sidebar
```

Example:

```
sidebar-1|||sidebar-ar
```

This is useful when a theme contains language-specific widgets or sidebar content.

PART 6 WooCommerce

28 WooCommerce Products

WooCommerce products can be translated the same way as normal posts. Open:

GO TO [Products](#) → [Edit Product](#)

Use the **Language & Translations** panel and create the translation. The new product is linked to the original product through the same translation group.

Then translate:

- Product title
- Description
- Short description
- Product images
- SEO content
- Categories
- Tags
- Attributes
- Custom fields where required

29 WooCommerce Categories and Terms

Product categories, tags and other public taxonomies support language relationships.

Edit a taxonomy term. You will see **Language & Translations**. Create the translated term. Example:

Eyeglasses
↓
نظارات

Translated taxonomy URLs can be enabled through the Compatibility settings.

30 WooCommerce Attribute Labels

Go to:

GO TO Languages → Attributes

This page allows you to translate WooCommerce attribute labels. For example:

Color
Size
Material

The label can have a different translation for every enabled language.

Attribute values themselves should be translated from the taxonomy term screen. For example:

Color
Black
Red
Blue

The label **Color** is translated in the Attributes section. The values **Black**, **Red** and **Blue** are translated as taxonomy terms.

31 Media Translation

Smart Multilingual can store language-specific metadata for WordPress media. Supported fields include:

- Alt text
- Title
- Caption
- Description

To use translated media metadata, enable:

GO TO Languages → Settings → Compatibility → Translated media metadata

The same image file can therefore have different SEO metadata in different languages.

32 Media Text Shortcode

You can output translated media metadata with:

```
[sml_media_text]
```

Example:

```
[sml_media_text id="123" field="alt"]
```

Available fields include `alt`, `title`, `caption` and `description`.

You can also request a specific language:

```
[sml_media_text id="123" field="alt" language="ar"]
```

33 Revolution Slider

Smart Multilingual includes integration for Revolution Slider. A language-specific slider can be mapped to another slider.

You can also use:

```
[sml_revslider alias="home-slider"]
```

When a translated slider mapping exists, Smart Multilingual loads the correct slider for the active language. This also works with supported Revolution Slider widgets inside Elementor.

34 RTL Languages

Smart Multilingual does not treat RTL as a specific language feature. RTL is controlled by the language configuration.

For Arabic, Hebrew or any other RTL language, set:

```
Direction: RTL
```

Smart Multilingual then generates the appropriate page direction and language classes. For example:

```
<html dir="rtl">
```

The plugin also adds language-aware frontend classes.

35 Elementor RTL Layout

Go to:

GO TO Languages → Settings → Compatibility

Enable **Elementor RTL layout helper** only if the Elementor layout needs additional RTL assistance.

This option adds RTL rendering helpers for supported Elementor layouts.

IMPORTANT

Do not enable it unless required. The Smart Multilingual core does not globally reverse or modify theme layouts by default.

36 Reverse Elementor Rows in RTL

Go to:

GO TO Languages → Settings → Switcher & RTL

Enable **Reverse horizontal Elementor rows for RTL languages** when you want horizontal Elementor layouts to reverse direction automatically on RTL pages.

Example:

```
LTR: Image | Text
RTL: Text | Image
```

NOTE

Leave this option disabled if your Elementor design already has dedicated RTL positioning.

37 Per-Language Typography

Go to:

GO TO Languages → Settings → Typography

Smart Multilingual includes a per-language **Typography Studio**.

Typography is completely optional. No typography CSS is generated unless a typography target is enabled. Each language has its own typography configuration.

38 Font Sources

For each language you can register font sources. Supported font files include **TTF** , **OTF** , **WOFF** and **WOFF2** .

You can use:

- an existing Elementor/system font
- a variable font
- individual static font files

For a variable font you can define:

- Minimum weight
- Maximum weight
- Font style
- **font-display**

Example:

```
Weight: 100–900
Style: Normal
font-display: swap
```

39 Existing Fonts

If the font already exists in Elementor or the theme, select **Existing** instead of uploading another font file. Enter the same CSS font-family name used by the theme or Elementor.

TIP

This avoids unnecessary duplicate font loading.

40 Typography Targets

Typography rules can be enabled separately. Each target can define:

- Font family
- Fallback
- Weight
- Desktop size
- Tablet size
- Mobile size
- Line height
- Letter spacing
- Word spacing
- Style
- Text transform
- Text decoration

Disabled typography targets do not affect the frontend. This makes the typography system safe to use alongside Elementor.

41 Language Switcher Colors

Under:

GO TO Languages → Settings → Switcher & RTL

you can configure:

- Text color
- Background
- Hover text color
- Hover background
- Dropdown text

- Dropdown background
- Border color
- Border radius

These settings affect the default Smart Multilingual switcher.

PART 9 Compatibility, SEO & URLs

42 Compatibility Profiles

Go to:

GO TO Languages → Settings → Compatibility

Compatibility features are opt-in.

IMPORTANT

Only enable the features your website actually needs.

43 Translated Taxonomy Routes

Enable **Translated taxonomy routes** if you use translated:

- Categories
- Tags
- Product categories
- Custom public taxonomies

This creates language-aware taxonomy routes.

NOTE

Do not enable it if you do not use translated taxonomy archives.

44 Translated Media Metadata

Enable this option when image metadata should change by language.

It applies translated:

- Alt text
- Title
- Caption

- Description

to frontend media.

45 Language-Aware Lists and Archives

Enable **Language-aware lists and archives** when widgets, archive pages and post loops should automatically display only content belonging to the active language.

This can affect:

- Blog archives
- Category pages
- Post grids
- Product lists
- Widgets
- Public taxonomy lists

NOTE

Enable it only when automatic language filtering is required.

46 Elementor Header & Footer Compatibility

Enable **Elementor Header & Footer Builder templates** when using:

- Elementor Pro Theme Builder
- supported Header/Footer Builder integrations

This allows Smart Multilingual to select the translated Header or Footer belonging to the current language.

47 Legacy Compatibility Bundle

The option **Legacy 0.9.x compatibility bundle** exists only for upgraded installations that depended on older Smart Multilingual layout behavior.

IMPORTANT

Do not enable this option on a new website.

48 SEO and hreflang

Smart Multilingual automatically generates alternate language links for translated singular content. Example:

```
<link rel="alternate" hreflang="en" href="https://example.com/about/" />
<link rel="alternate" hreflang="ar" href="https://example.com/ar/about-ar/" />
```

The source language is also used as `x-default`.

For correct SEO:

- use the correct hreflang value for each language
- publish all translations
- avoid duplicate translation groups
- use unique page titles and meta descriptions for every language

49 URL Structure

The source language uses `/`. Secondary languages use their configured prefix. Example:

```
English: /
Arabic:  /ar/
German:  /de/
```

Translated content uses the target language path automatically.

50 Translation Slugs

When a translation is created, Smart Multilingual automatically creates a unique language-aware slug. For example:

```
about
about-ar
about-de
```

or for another source slug:

```
product-name
product-name-tr
```

The suffix is based on the target language code. It is not hard-coded to a specific language.

51 When a New Language Returns 404

If a language URL returns a 404 immediately after:

- plugin installation
- adding a language
- changing the source language
- changing a language prefix

go to:

GO TO Settings → Permalinks

and click **Save Changes**. Alternatively, use the Smart Multilingual admin notice **Refresh language permalinks**.

NOTE

This only needs to be done after structural language changes.

PART 10 Workflows & Best Practices

52 Recommended Workflow for a New Website

For the most stable setup, use this order:

1. Install and activate Smart Multilingual.
2. Open **Manage Languages**.
3. Configure all required languages.
4. Choose the source language.
5. Save settings.
6. Refresh permalinks.
7. Create or assign a menu for every language.
8. Configure the language switcher.
9. Enable only required Compatibility profiles.
10. Create translations for pages.
11. Create translations for Elementor Headers and Footers.
12. Translate taxonomy terms.
13. Translate WooCommerce products if required.
14. Configure string translations for theme/plugin text.
15. Configure per-language typography only if necessary.

16. Clear site cache.
17. Test every language on desktop and mobile.

53 Recommended Elementor Workflow

For Elementor websites:

1. Finish the source-language design first.
2. Create the translation using Smart Multilingual.
3. Open the translated page with Elementor.
4. Translate only the content that must change.
5. Keep shared design structure consistent where possible.
6. Create translated Header and Footer templates.
7. Enable Header/Footer compatibility.
8. Test responsive layouts.
9. Test RTL separately if one language is RTL.
10. Regenerate Elementor CSS after major template changes.

54 Do Not Duplicate Pages Manually

Whenever possible, do not use **Duplicate Page**, **Clone Page** or **Copy to Draft** to create language translations.

Use the Smart Multilingual **Create Translation** function. This ensures that the source and translated versions share the correct Translation Group.

IMPORTANT

A manually duplicated page is not automatically recognized as a translation.

55 Do Not Change Translation Group IDs

The Translation Group ID is used internally to connect language versions. Changing it manually can break:

- Language switcher links
- Header/Footer mapping
- Taxonomy relationships
- SEO alternate links

IMPORTANT

Only change it when repairing a known broken relationship.

56 Caching

After major language changes, clear:

- WordPress cache plugin
- Server cache
- CDN cache
- Elementor CSS cache

For Elementor:

GO TO [Elementor](#) → [Tools](#) → [Regenerate CSS & Data](#)

This is especially recommended after:

- changing Header/Footer translations
- changing Elementor templates
- changing typography
- changing RTL layouts

PART 11 RTL Testing & Custom CSS

57 Testing RTL

For RTL languages such as Arabic, check:

- Header alignment
- Navigation direction
- Dropdown alignment
- Icons
- Buttons
- Forms
- WooCommerce layouts
- Elementor containers
- Footer columns
- Product galleries

TIP

If only specific Elementor rows should reverse, use the RTL settings instead of global custom CSS.

58 Language-Specific CSS

Smart Multilingual adds language and direction classes to the frontend. This allows custom CSS targeting when required. For example:

```
.sml-lang-ar .custom-title {  
    text-align: right;  
}
```

or:

```
html[dir="rtl"] .custom-menu {  
    direction: rtl;  
}
```

For LTR:

```
html[dir="ltr"] .custom-menu {  
    direction: ltr;  
}
```

NOTE

Use language-specific CSS only for exceptions that cannot be handled through the theme or Elementor settings.

59 Language-Specific Visibility

Smart Multilingual also supports direction-based helper classes. For example, content can be hidden based on LTR or RTL direction using the plugin's frontend direction classes.

For more controlled content visibility, the recommended method is the `[sml_show]` shortcode. Example:

```
[sml_show lang="ar"]  
Arabic-only content  
[/sml_show]
```

60 Common Problems

Translation exists but switcher opens the homepage

Check that both pages belong to the same Translation Group.

Translated page returns 404

Refresh WordPress permalinks.

Header remains in the source language

Check the Header translation, language assignment, Translation Group and Header/Footer compatibility option.

Wrong menu appears

Check:

GO TO Languages → Settings → Menus by language

Posts from another language appear in archives

Enable **Language-aware lists and archives**.

Arabic layout is not reversed

Confirm that **Direction = RTL** for Arabic. Then enable RTL helpers only if needed.

Font does not change

Make sure:

- the font source exists
- the typography target is enabled
- the correct font family is selected
- browser cache is cleared

Elementor styles look outdated

Run:

GO TO Elementor → Tools → Regenerate CSS & Data

61 Updating Smart Multilingual

Updating Smart Multilingual does not require recreating translations. Your translation relationships and settings are stored in WordPress.

Before updating a production website, a normal WordPress backup is still recommended.

After a major update, test:

- Homepage
- Language switcher
- Header
- Footer
- Menus
- Elementor pages
- WooCommerce pages
- RTL pages
- Taxonomy archives

62 Final Recommended Configuration

For a standard English + Arabic Elementor website, a good starting configuration is:

```
English
Code: en
Direction: LTR
Source language: Yes
URL: /
```

```
Arabic
Code: ar
Direction: RTL
Prefix: ar
URL: /ar/
```

Enable these only when the features are required:

- **Elementor Header & Footer Builder templates**
- **Language-aware lists and archives**
- **Translated taxonomy routes**

Keep **Legacy 0.9.x compatibility bundle** disabled on new websites.

For the language switcher, this is a safe configuration for most production websites:

Layout: Dropdown
Labels: Native Names
Missing Translation: Hide Language

APPENDIX Quick Reference

A Shortcode Quick Reference

SHORTCODE	WHAT IT DOES
<code>[sml_language_switcher]</code>	Language switcher.
<code>[sml_switcher]</code>	Alias of the language switcher.
<code>[sml_language_switcher layout="list"]</code>	Inline switcher.
<code>[sml_language_switcher style="short"]</code>	Language codes such as EN / AR.
<code>[sml_language_switcher missing="hide"]</code>	Hide languages without a translation.
<code>[sml_language_value en="Contact" ar="اتصل بنا"]</code>	Return a different value depending on the active language.
<code>[sml_value en="Contact" ar="اتصل بنا"]</code>	Short alias.
<code>[sml_show lang="ar"]Arabic content[/sml_show]</code>	Show content only in Arabic.
<code>[sml_show languages="ar,tr"]Content[/sml_show]</code>	Show content in multiple languages.
<code>[sml_string]Read More[/sml_string]</code>	Translate a registered frontend string.
<code>[sml_string key="Read More"]</code>	Translate a specific string key.
<code>[sml_media_text id="123" field="alt"]</code>	Return translated media metadata.
<code>[sml_revslider alias="home-slider"]</code>	Load the language-aware Revolution Slider.