

Human Teleoperation of a Laterally Mounted Robot Arm

A dissertation submitted to The University of Manchester for the degree of
Bachelor of Engineering in Electronic Engineering
in the Faculty of Science and Engineering

Year of submission

2025

Student ID

11006231

School of Engineering

Contents

Contents	2
Abstract	4
Declaration of originality	5
Copyright statement	6
Acknowledgments	7
1 Introduction	8
1.1 Background and motivation	8
1.2 Aims and objectives	9
2 Literature review	9
2.1 Introduction	9
2.2 Project requirements	10
2.3 Survey of existing tracking technologies	11
3 Methods	13
3.1 Comparison of both computer vision methods	13
3.2 Results of joint angle tracking methods	15
4 Results and discussion	17
4.1 Introduction	17
4.2 Content	17
4.2.1 Introduction	17
4.2.2 Detail	17
4.2.3 More detail	19
4.2.4 Summary	19
4.3 Summary	20
5 Conclusions and future work	20
5.1 Conclusions	20
5.2 Future work	20
References	22

Appendices 25

A Project outline 25

B Risk assessment 25

Word count:

Abstract

Abstract goes here.

Declaration of originality

I hereby confirm that no portion of the work referred to in the thesis has been submitted in support of an application for another degree or qualification of this or any other university or other institute of learning.

Copyright statement

- i The author of this thesis (including any appendices and/or schedules to this thesis) owns certain copyright or related rights in it (the “Copyright”) and s/he has given The University of Manchester certain rights to use such Copyright, including for administrative purposes.
- ii Copies of this thesis, either in full or in extracts and whether in hard or electronic copy, may be made *only* in accordance with the Copyright, Designs and Patents Act 1988 (as amended) and regulations issued under it or, where appropriate, in accordance with licensing agreements which the University has from time to time. This page must form part of any such copies made.
- iii The ownership of certain Copyright, patents, designs, trademarks and other intellectual property (the “Intellectual Property”) and any reproductions of copyright works in the thesis, for example graphs and tables (“Reproductions”), which may be described in this thesis, may not be owned by the author and may be owned by third parties. Such Intellectual Property and Reproductions cannot and must not be made available for use without the prior written permission of the owner(s) of the relevant Intellectual Property and/or Reproductions.
- iv Further information on the conditions under which disclosure, publication and commercialisation of this thesis, the Copyright and any Intellectual Property and/or Reproductions described in it may take place is available in the University IP Policy (see <http://documents.manchester.ac.uk/DocuInfo.aspx?DocID=24420>), in any relevant Thesis restriction declarations deposited in the University Library, The University Library’s regulations (see <http://www.library.manchester.ac.uk/about/regulations/>) and in The University’s policy on Presentation of Theses.

Acknowledgments

Acknowledgments go here.

1 Introduction

The goal of this project is to create a system for controlling and teleoperating a robot arm with a human arm. In order to maintain simplicity in the project scope, the robot arm is assumed to be shoulder-mounted and has the seven degrees of freedom (DoF) [1], matching that of a healthy human arm.

1.1 Background and motivation

The motivation for this project comes from articles within the books: “Human-robot teleoperation based on Imus” [2] and “Whole-body human-motion based robot teleoperation” [3], which both describe research into remote teleoperation of shoulder-mounted robot arms. Both articles describe the use of an inertial measurement unit (IMU) based solution to obtain data from the human operator. The limitation in both of these articles is that they only map the end effector position of the robot arm to the wrist position. Because the human arm has redundancy in the number of joints available [4], a robot arm only mapping the end effector position could end up with its forearm or upper arm in a position that causes collisions, even though the end effector is in the target position. This ambiguity could lead to collisions with obstacles in the environment, and lack of safety for people within the envelope of the robot arm.

Whilst not necessarily critical in the use cases that Zhou et al. and Lyu et al. describe - remote welding inspection and simple delivery and manipulation tasks for an elderly patient - a scenario that is obstacle rich would require precise control of the robot arm. One such scenario is an underwater environment where a telescopic robot arm is attempting to collect a sample. Whilst Jin et al. describes a potential autonomous solution [5], this method is comparatively slow to the prospect of remote teleoperation: ranging from five to nine seconds in the simple case where the target object and origin of the robot arm is stationary. Consequently, the complexity increase for the case where nothing is stationary, a more realistic use case, would mean that this method would be inefficient compared to the intuition of a trained operator. Additionally, Jankowski and Grabowski shows that for tasks involving teleoperation of a robot for pick and place tasks, virtual reality style mapping of head movements with arm to end effector mapping is more efficient and less error prone than a typical joystick [6].

Other potential areas of application of full arm tracking could be in the medical industry and with

surgical robots, where collisions with patients is unwanted. Likewise, nuclear decommissioning robots where absolute accuracy of matching an operator's intentions is critical.

1.2 Aims and objectives

The overall aim is to create a system for mapping the joint angles of a human arm to a shoulder-mounted robot arm.

To achieve this goal, there will be an evaluation of available arm tracking methods. Many methods currently exist for tracking the joint angles of robot arms, including: IMU based solutions discussed earlier, attitude and heading reference systems [7], computer vision based systems [8], and flex sensor based systems [9], among others. A rigorous examination of these methods will be conducted as a prerequisite to the final implementation, to understand the applicability and feasibility of each tracking system. Relevant tracking metrics will be discussed in the literature review, but include factors such as cost, accuracy, engineering complexity, etc. These metrics have been selected in order to allow for the feasible completion of this project given the time, scope and availability of resources for the final year project.

Finally, it is acknowledged that the procurement of a seven DoF robot arm is unlikely for a Bachelor's thesis. Hence, the final implementation of the tracking method will be created in the form of a simulation in CoppeliaSim. This has the advantage of being able to set up precise scenes for the evaluation of the final tracking method chosen, as well as comparison with baseline methods such as joysticks or pure end effector mapping. Likewise, the robot could be customised to match the proportions of the operator's arm perfectly, which would increase ease of use for the operator.

2 Literature review

2.1 Introduction

The measurement of human arm joint angles has been an interest of academia for several decades: with one of the first examples being demonstrated by Liu et al. In industrial settings, full body tracking has primarily been used in the film industry to map an actor's performance onto computer generated characters [11]. The main advantage of this is to save time in the creation of realistic looking movements [12], as an actor is able to portray realistic and nuanced motion that gets digitised.

Therefore, it seems logical that one should be able to combine the two applications - have a skilled operator trained in specific movement patterns to remotely control industrial robots where traditional control methods (e.g. joysticks) are unsuitable. For example, in an application that compared participants performance between a purely joystick based control method, and VR control with hand tracking, tasks were completed up to 1.8 times faster and with a quarter of the errors (1.54% compared to 8.65%) in the best cases [6].

Likewise, research from Doisy et al. also seems to indicate that the time to complete a novel teleoperation task was initially better when users had their head movements mapped to the control of the robot's vision systems [13]. However, it is important to acknowledge that this study also showed that overall performance improved with experience between trial groups, and participants with more experience controlling the robot did better when controlling the robot via joystick. The overall takeaway from this is that whether or not a novel approach to teleoperation is more effective than traditional joysticks is strongly dependent on the task. Research conducted by Zhou et al. shows that the control of a seven degree of freedom robot, could be improved via human arm teleoperation, which strengthens the justification for this project.

2.2 Project requirements

In order to compare the final system to existing systems and research, a baseline performance must be characterised. This has been categorised into three distinct goals for the final system: position based requirements, time based requirements and resource based requirements. These requirements will help to compare the existing technologies in the next subsection.

Existing research into the lower bounds of human arm accuracy shows that experienced surgeons have approximately 5° of vertical movement range on all joints when asked to hold their hand on a target, and close to 3° range for horizontal movement. The study performed by Nisky et al. was performed with novice and expert surgeons, which would imply that this range of joint movement is above average for most humans. Taking this into account, the requirements are that the final system must be able to measure joint rotation in each joint up to a resolution of 5° . Any movement measured less than this resolution is presumed to be 'noise' from human inaccuracy, and will therefore need to be smoothed out in the final implementation. This way the system is able to accurately capture the intent of the operator's movement, whilst preserving some level of accuracy.

Similar research exists for time based requirements as well, especially in the area of latency. It seems

intuitive that more delay in a teleoperation system will decrease performance - research suggests that this manifests itself within two key figures of 600 ms and 1500 ms [15]. Task performance generally decreased with latency, with task performance falling at a latency of 600 ms and any latency above 1500 ms showing the most significant drop in task performance. Therefore the final arm tracking system should aim to measure arm angles well below the 600 ms threshold. The Nyquist criterion equivalent of this threshold is used as a well informed estimate of how much latency can be present in the system, leaving a final requirement of 300 ms.

The budget for this project is £180. This means that the final solution must be cheaper to implement than this. Likewise, the time to complete this project is 30 unit credits worth of time, equating to 240 hours of time commitment, excluding time required for completing written deliverables. Both of these factors will mean that the final solution favours simpler, more complete solutions - anything novel is a potential failure point that could mean the project does not complete.

2.3 Survey of existing tracking technologies

In order to fully evaluate the myriad of arm tracking methods available, a Pugh Matrix has been created to evaluate and compare several factors between each method. Each method will score 1 – 5 in each category, with a brief comment justifying the score in each column.

Below are the decision factors of the Pugh Matrix and a brief description of how they are scored:

- **Complexity** - This is calculated based on a well reasoned estimate of the total time to build the system. Each multiple of 48 hours reduces the score by 1, e.g. 0 – 48 hours would score 5, 49 – 96 hours would score 4.
- **Cheapness** - This is calculated based on a well reasoned estimate of the total cost of building the system. Each multiple of £36 reduces the score by 1, e.g. £0 – £36 would score 5, £37 – £72 would score 4.
- **Accuracy** - This is calculated from available research on the accuracy of this method. Each multiple of 5° above 5° reduces the score by 1, e.g. an absolute accuracy of 6 – 10° would score 4, 11 – 15° would score 3.
- **Latency** - This is calculated from available research on the time it takes to obtain a single measurement of all 7 joint angles from this method. Each multiple of 100 ms above 300 ms reduces the score by 1, e.g. a latency of 301 ms – 400 ms would score 4.

Method	Complexity 1 – 5	Cheapness 1 – 5	Accuracy 1 – 5	Latency (1 – 5)	Total
IMU-based	3 100 hours inc PCB design + drift correction	4 £50 – £60	3 2.8° [16]	5 <1 ms [17]	15
Pose estimation via computer vision	5 Existing solutions reduce complexity 30 – 40 hours	5 £30 USB Camera	3 10° – 15° [18]	5 ≤ 100 ms [19]	18
Flex Sensors	2 150 hours	4 £40-60	4 10° [20]	5 ≤ 100 ms	15
Marker tracking via computer vision	5 Very complex, though can be simplified through FOSS	3 £180+ for Vicon, cheaper solutions exist	5 <5° error	5 100-200ms	18

Table 1. Pugh Matrix with detailed scoring justifications

Analysis of existing methods shows that the two computer vision approaches score similarly in terms of viability, therefore further analysis will be required to confirm the viability of each method. The accuracy advantage of the marker tracking method makes it more appealing, though this is offset by the stupendous cost of conventional Vicon camera systems. Open source software along with ArUco markers could be used to offset this cost, which will make further analysis necessary before choosing a final method. For example, Wieczorek et al. describes using ArUco markers along with standard home cameras to perform specialised kinematic analysis [21]. These will be performed in the form of accuracy and latency experiments, which will give the freedom of being able to analyse more factors than the literature - including accuracy of measuring multiple joints angles simultaneously.

3 Methods

3.1 Comparison of both computer vision methods

In order to evaluate the accuracy of both computer vision methods, a simple experiment was set up to measure the absolute accuracy on the joint angles that can be measured. A goniometer is attached to the wall at 90° , with two end positions marked at 90° and 180° . The subject will move their arm repeatedly between these markers, and the recording is captured by a camera as described in fig 1.




Fig. 1. The experimental setup, showing data capture.

The subject will then flex and extend their elbow between the two endpoints. In order to obtain a sufficient amount of data, 5 videos are recorded, each showing 10 flexion and extensions. This creates enough samples to perform ANOVA between each video, to maintain experimental integrity. In order to measure error, the graph of elbow flexion angles is extended towards the 90° and 180° endpoints. This secondary graph is then subtracted from the first graph to obtain the error value, from which we can calculate the root mean square error, and is shown in fig 2.

Upon analysis of the RMSE, it was found that this value was 25.83° , which was greater than the literature value of 10.37° [18]. Frame by frame analysis of the video showed that this discrepancy was not attributable to human error - the arm was clearly flexing and extending to the correct endpoints. Plotting the inferred joint positions frame by frame revealed the culprit - perspective! The




Fig. 2. Showing how RMSE is calculated from elbow flexion data.

machine learning model used for joint position extraction is finding extra movement in the depth axis of the video, and attributing it to roll in the elbow axis, instead of flexion. This is clearly shown in fig 3.




Fig. 3. Top view of inferred 3D joint positions.

To analyse the performance of joint angle tracking in the three dimensional case, a simple movement path is created. A 7 DoF manipulator is created from the DH parameters in table 2. These movements are then fed through a forward kinematics processing program to obtain a visualisation of this movement path, and this movement is recreated by the subject. This path is shown in

4. This movement has been selected to be easily recreated, whilst showing movement in three different joint angles simultaneously. The same data processing for the two dimensional elbow flex case is used to obtain RMSE of three different joint angle movements.

Joint	Description	θ_i	α_i	d_i	a_i
1	Shoulder abduction/adduction	q_1	$\frac{\pi}{2}$	0	0
2	Shoulder flexion/extension	q_2	$\frac{\pi}{2}$	0	0
3	Shoulder rotation	q_3	$-\frac{\pi}{2}$	0	L_u
4	Elbow flexion/extension	q_4	$\frac{\pi}{2}$	0	0
5	Forearm rotation	q_5	$-\frac{\pi}{2}$	0	L_l
6	Wrist flexion/extension	q_6	$\frac{\pi}{2}$	0	0
7	Wrist radial/ulnar deviation	q_7	0	0	0

Table 2. Denavit-Hartenberg Parameters for 7-DoF Arm (where L_u is upper arm length and L_l is lower arm length)




Fig. 4. 3D Joint Motion Path

3.2 Results of joint angle tracking methods

This section is incomplete! The results from the marker tracking experiments will also be compiled here, and section 3.3 will discuss which method to use in section 4! Table 3 shows the com-

piled RMSE errors for tracking each joint in both the two dimension elbow flexing case and the three dimension movement path.

Method	RMSE Error Elbow Flexion 2D (°)	RMSE Error Elbow Flexion 3D (°)	RMSE Error Shoulder Flexion (°)	RMSE Error Shoulder Abduction (°)
Pose estimation	25.83	7.19	6.89	11.68
Marker Tracking				

Table 3. RMSE Error Comparison for Different Tracking Methods

Whilst the two dimensional RMSE error is larger than the literature suggests, the three dimensional joint error shows better accuracy than expected. Apart from the shoulder adduction/abduction measurements, each joint being tracked is close to the 5° requirements of the project. An interesting aspect that was encountered when performing the accuracy characterisation experiments with pose estimation is shown in 5, and points to a downside not immediately apparent. The program uses machine learning to create an estimation of joint locations in an image and was ostensibly trained on a large corpus of human images. Hence, there was trouble distinguishing between real humans and pictures of humans being worn on the subject's clothing - a downside in the favour of the marker tracking method.



Fig. 5. Pose estimation software mistaking a picture of humans printed on the clothing for an actual person.

4 Results and discussion

4.1 Introduction

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

4.2 Content

4.2.1 Introduction

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

4.2.2 Detail

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed,

volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetur at, consectetur sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.

Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio, nec commodo wisi enim eget quam. Quisque libero justo, consectetur a, feugiat vitae, porttitor eu, libero. Suspendisse sed mauris vitae elit sollicitudin malesuada. Maecenas ultricies eros sit amet ante. Ut venenatis velit. Maecenas sed mi eget dui varius euismod. Phasellus aliquet volutpat odio. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Pellentesque sit amet pede ac sem eleifend consectetur. Nullam elementum, urna vel imperdiet sodales, elit ipsum pharetra ligula, ac pretium ante justo a nulla. Curabitur tristique arcu eu metus. Vestibulum lectus. Proin mauris. Proin eu nunc eu urna hendrerit faucibus. Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit ipsum dolor sed augue. Nulla nec lacus.

Suspendisse vitae elit. Aliquam arcu neque, ornare in, ullamcorper quis, commodo eu, libero. Fusce sagittis erat at erat tristique mollis. Maecenas sapien libero, molestie et, lobortis in, sodales eget, dui. Morbi ultrices rutrum lorem. Nam elementum ullamcorper leo. Morbi dui. Aliquam sagittis. Nunc placerat. Pellentesque tristique sodales est. Maecenas imperdiet lacinia velit. Cras non urna. Morbi eros pede, suscipit ac, varius vel, egestas non, eros. Praesent malesuada, diam id pretium elementum, eros sem dictum tortor, vel consectetur odio sem sed wisi.

Sed feugiat. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Ut pellentesque augue sed urna. Vestibulum diam eros, fringilla et, consectetur eu, nonummy id, sapien. Nullam at lectus. In sagittis ultrices mauris. Curabitur malesuada erat sit amet massa. Fusce blandit. Aliquam erat volutpat. Aliquam euismod. Aenean vel lectus. Nunc imperdiet justo nec dolor.

4.2.3 More detail

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

4.2.4 Summary

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida

placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

4.3 Summary

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

5 Conclusions and future work

5.1 Conclusions

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

5.2 Future work

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur

id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris. [22], [23], [24] Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur.

References

- [1] D. Nguyen Thai et al., "Biomechanical analysis of the shooter-weapon system oscillation," *2017 International Conference on Military Technologies (ICMT)*, pp. 48–53, May 2017. DOI: 10.1109/miltechs.2017.7988729 (cited on p. 8).
- [2] H. Zhou et al., "Human-robot teleoperation based on imus," *Advanced Topics in Science and Technology in China*, pp. 51–72, 2025. DOI: 10.1007/978-981-96-6139-8_3 (cited on pp. 8, 10).
- [3] H. Lyu, G. Yang, and H. Yang, "Whole-body human-motion based robot teleoperation," *Advanced Topics in Science and Technology in China*, pp. 69–93, 2025. DOI: 10.1007/978-981-96-6545-7_4 (cited on p. 8).
- [4] D. Stanev and K. Moustakas, "Modeling musculoskeletal kinematic and dynamic redundancy using null space projection," *PLOS ONE*, vol. 14, no. 1, Jan. 2019. DOI: 10.1371/journal.pone.0209171 (cited on p. 8).
- [5] H. Jin, H. Ji, and F. Yan, "An effective obstacle avoidance and motion planning design for underwater telescopic arm robots based on a tent chaotic dung beetle algorithm," *Electronics*, vol. 12, no. 19, p. 4128, Oct. 2023. DOI: 10.3390/electronics12194128 (cited on p. 8).
- [6] J. Jankowski and A. Grabowski, "Usability evaluation of vr interface for mobile robot teleoperation," *International Journal of Human-Computer Interaction*, vol. 31, no. 12, pp. 882–889, Nov. 2015. DOI: 10.1080/10447318.2015.1039909 (cited on pp. 8, 10).
- [7] E. B. Mazomenos et al., "Detecting elementary arm movements by tracking upper limb joint angles with marg sensors," *IEEE Journal of Biomedical and Health Informatics*, vol. 20, no. 4, pp. 1088–1099, Jul. 2016. DOI: 10.1109/jbhi.2015.2431472 (cited on p. 9).
- [8] L. Phuong and V. Cong, "Control the robot arm through vision-based human hand tracking," *FME Transactions*, vol. 52, no. 1, pp. 37–44, 2024. DOI: 10.5937/fme2401037p (cited on p. 9).
- [9] V. Nalam and P. Manivannan, "Development of a contact based human arm motion analysis system for virtual reality applications," *Applied Mechanics and Materials*, vol. 592–594, pp. 2139–2144, Jul. 2014. DOI: 10.4028/www.scientific.net/amm.592-594.2139 (cited on p. 9).

- [10] X. Liu et al., "Video based human motion capture," *1999 IEEE Third Workshop on Multimedia Signal Processing (Cat. No.99TH8451)*, pp. 483–488, 1999. DOI: 10.1109/mmisp.1999.793896 (cited on p. 9).
- [11] M. Crawford, *What is motion capture (mo-cap): The definitive guide*, Mar. 2025. [Online]. Available: <https://filmlifestyle.com/what-is-motion-capture/> (cited on p. 9).
- [12] B. Milling, *Motion capture: Why is it needed, and how does it work?* Jul. 2024. [Online]. Available: <https://www.americanmovieco.com/blog/motion-capture-why-is-it-needed-and-how-does-it-work> (cited on p. 9).
- [13] G. Doisy, A. Ronen, and Y. Edan, "Comparison of three different techniques for camera and motion control of a teleoperated robot," *Applied Ergonomics*, vol. 58, pp. 527–534, Jan. 2017. DOI: 10.1016/j.apergo.2016.05.001 (cited on p. 10).
- [14] I. Nisky, M. H. Hsieh, and A. M. Okamura, "Uncontrolled manifold analysis of arm joint angle variability during robotic teleoperation and freehand movement of surgeons and novices," *IEEE Transactions on Biomedical Engineering*, vol. 61, no. 12, pp. 2869–2881, Dec. 2014. DOI: 10.1109/tbme.2014.2332359 (cited on p. 10).
- [15] J. Louca et al., "Impact of haptic feedback in high latency teleoperation for space applications," *ACM Transactions on Human-Robot Interaction*, vol. 13, no. 2, pp. 1–21, Jun. 2024. DOI: 10.1145/3651993 (cited on p. 11).
- [16] L. Ricci, F. Taffoni, and D. Formica, "On the orientation error of imu: Investigating static and dynamic accuracy targeting human motion," *PLOS ONE*, vol. 11, no. 9, Sep. 2016. DOI: 10.1371/journal.pone.0161940 (cited on p. 12).
- [17] T. InvenSense, *lcm-20948 datasheet*, 2017 (cited on p. 12).
- [18] H. Wang et al., "A computer-vision method to estimate joint angles and l5/s1 moments during lifting tasks through a single camera," *Journal of Biomechanics*, vol. 129, p. 110860, Dec. 2021. DOI: 10.1016/j.jbiomech.2021.110860 (cited on pp. 12, 13).
- [19] T. Starner et al., "The perceptive workbench: Computer-vision-based gesture tracking, object tracking, and 3d reconstruction for augmented desks," *Machine Vision and Applications*, vol. 14, no. 1, pp. 59–71, Apr. 2003. DOI: 10.1007/s00138-002-0096-8 (cited on p. 12).
- [20] G. Saggio, "Bend sensor arrays for hand movement tracking in biomedical systems," *2011 4th IEEE International Workshop on Advances in Sensors and Interfaces (IWASI)*, pp. 51–54, Jun. 2011. DOI: 10.1109/iwasi.2011.6004685 (cited on p. 12).

- [21] B. Wieczorek et al., "The effects of aruco marker velocity and size on motion capture detection and accuracy in the context of human body kinematics analysis," *Technical Transactions*, pp. 1–10, 2020. DOI: 10.37705/techtrans/e2020036 (cited on p. 12).
- [22] A. J. Casson et al., "Wearable electroencephalography," *IEEE Eng. Biol. Med. Mag.*, vol. 29, no. 3, pp. 44–56, 2010 (cited on p. 21).
- [23] A. J. Casson, E. Luna, and E. Rodriguez-Villegas, "Performance metrics for the accurate characterisation of interictal spike detection algorithms," *J. Neurosci. Meth.*, vol. 177, no. 2, pp. 479–487, 2009 (cited on p. 21).
- [24] A. J. Casson and E. Rodriguez-Villegas, "Toward online data reduction for portable electroencephalography systems in epilepsy," *IEEE T. Biomed. Eng.*, vol. 56, no. 12, pp. 2816–2825, 2009 (cited on p. 21).

Appendices

A Project outline

Project outline as submitted at the start of the project is a required appendix. Put here.

B Risk assessment

Risk assessment is a required appendix. Put here.