

Service Workers and caching strategies

Service Workers and Caching Strategies in JavaScript

Service Workers are a powerful feature of modern browsers that enable **background tasks**, **offline experiences**, and **advanced caching strategies**. They're the backbone of **Progressive Web Apps (PWAs)**.

What Is a Service Worker?

A **Service Worker** is a **script that runs in the background**, separate from the main browser thread. It:

- **Intercepts network requests**
- Can **cache files** and **serve responses from cache**
- Enables **offline access**
- Can receive **push notifications** and perform **background sync**

It follows a **lifecycle**, is **event-driven**, and **runs only over HTTPS** (except on localhost).

Service Worker Lifecycle

1. Registration

Register the service worker in your app:

```
if ('serviceWorker' in navigator) {  
  navigator.serviceWorker.register('/sw.js')  
    .then(reg ⇒ console.log('Registered:', reg.scope))  
    .catch(err ⇒ console.error('Failed:', err));  
}
```

2. Installation

Triggered when the SW is first installed.

```
self.addEventListener('install', event => {
  event.waitUntil(
    caches.open('v1').then(cache =>
      cache.addAll(['/index.html', '/style.css', '/app.js'])
    )
  );
});
```

3. Activation

Cleans up old caches or updates.

```
self.addEventListener('activate', event => {
  event.waitUntil(
    caches.keys().then(keys =>
      Promise.all(
        keys.filter(key => key !== 'v1').map(key => caches.delete(key))
      )
    )
  );
});
```

4. Fetch

Intercepts network requests.

```
self.addEventListener('fetch', event => {
  event.respondWith(
    caches.match(event.request)
      .then(cached => cached || fetch(event.request))
  );
});
```

Caching Strategies

1. Cache First (Offline First)

- Try cache → fallback to network

```
 caches.match(req).then(res ⇒ res || fetch(req))
```

✓ Good for static assets

⚠ May serve outdated content

2. Network First

- Try network → fallback to cache

```
 fetch(req)
  .then(res ⇒ {
    caches.put(req, res.clone());
    return res;
  })
  .catch(() ⇒ caches.match(req));
```

✓ Great for dynamic content

⚠ Slower due to network dependency

3. Stale-While-Revalidate

- Serve cache immediately, update in background

```
 event.respondWith(
  caches.open('v1').then(cache ⇒
    cache.match(event.request).then(cachedRes ⇒ {
      const fetchPromise = fetch(event.request).then(networkRes ⇒ {
        cache.put(event.request, networkRes.clone());
        return networkRes;
      });
```

```
    return cachedRes || fetchPromise;
  })
)
);
```

✅ Combines speed and freshness

⚠️ Slightly more complex

4. Network Only

- Always use network
 - ✅ For critical live data (e.g., payments)

5. Cache Only

- Only use cache
 - ✅ For offline-only apps
 - ⚠️ Risk of missing content
-



Other Service Worker Features

- **Background Sync** – Defer actions until connectivity is back
 - **Push Notifications** – Handle and display notifications
 - **Clients API** – Communicate with pages from the service worker
-



Security Note

Service Workers require:

- **HTTPS** (except `localhost`)
 - Explicit **user permission** for notifications or background sync
-



Cleaning Up Cache (Versioning)

Use versioning to manage cache:

```
const CACHE_NAME = 'my-cache-v2';

self.addEventListener('activate', event => {
  event.waitUntil(
    caches.keys().then(keys =>
      Promise.all(
        keys.filter(key => key !== CACHE_NAME)
          .map(key => caches.delete(key))
      )
    )
  );
});
```

✓ Summary

Feature	Description
Runs in background	Handles requests, caching, and more
Enables offline	Cache assets and data
Lifecycle phases	Install → Activate → Fetch
Key APIs	<code>caches</code> , <code>fetch</code> , <code>postMessage</code> , <code>clients</code>
Common strategies	Cache First, Network First, SWR, etc.
Required protocol	HTTPS only (except localhost)

Want a real-world PWA example or a demo app using Service Workers? I can help build one from scratch.