

typeof operator and type checking

typeof Operator and Type Checking in JavaScript

The **typeof** operator in JavaScript is used to **determine the data type** of a variable or value at runtime.

Syntax

```
typeof operand
```

OR

```
typeof(operand)
```

Both are valid. It returns a **string** indicating the type.

Example Outputs

```
typeof "Abhi";    // "string"
typeof 42;        // "number"
typeof true;      // "boolean"
typeof undefined; // "undefined"
typeof null;      // "object" ! (this is a known JavaScript quirk)
typeof Symbol();  // "symbol"
typeof 10n;       // "bigint"

typeof {};        // "object"
typeof [];        // "object" (Array is an object)
typeof function(){}; // "function"
```

Detailed Type Output Table

Value	<code>typeof</code> Result
<code>"hello"</code>	<code>"string"</code>
<code>100</code>	<code>"number"</code>
<code>true</code> / <code>false</code>	<code>"boolean"</code>
<code>undefined</code>	<code>"undefined"</code>
<code>null</code>	<code>"object"</code> !
<code>Symbol("id")</code>	<code>"symbol"</code>
<code>10n</code>	<code>"bigint"</code>
<code>{}</code>	<code>"object"</code>
<code>[]</code>	<code>"object"</code>
<code>function() {}</code>	<code>"function"</code> ✓

! Quirks of `typeof`

1. `typeof null` returns `"object"`

- This is a well-known bug in JavaScript that exists for backward compatibility.
- To properly check for `null`, use:

```
value === null;
```

2. Arrays return `"object"`

- To specifically check for arrays:

```
Array.isArray([]);
```

3. `typeof NaN` is `"number"`

- `NaN` stands for "Not-a-Number", but it's still considered a number by `typeof`.

- Use `Number.isNaN(value)` for accurate checking.

Best Practices for Type Checking

✓ Strings

```
typeof value === "string";
```

✓ Numbers

```
typeof value === "number" && !Number.isNaN(value);
```

✓ Arrays

```
Array.isArray(value);
```

✓ Objects (but not arrays or null)

```
typeof value === "object" && value !== null && !Array.isArray(value);
```

✓ Functions

```
typeof value === "function";
```

Bonus: Using `instanceof`

While `typeof` works for **primitive types**, use `instanceof` for **complex types**:

```
[] instanceof Array;    // true  
{ } instanceof Object;   // true  
new Date() instanceof Date; // true
```

Summary

Use Case	Best Method
Primitive type check	<code>typeof</code>
Array check	<code>Array.isArray()</code>
Null check	<code>value === null</code>
Object (excluding null/arr)	<code>typeof val === 'object'</code> + checks
NaN check	<code>Number.isNaN(value)</code>

Let me know if you'd like a quick quiz or coding challenge to reinforce this!