

Async/await syntax and error handling

Async/Await Syntax and Error Handling in JavaScript — In Detail

What is `async/await` ?

`async/await` is **syntactic sugar** over Promises, introduced in ES2017, that allows you to write asynchronous code that looks and behaves like synchronous code — making it more readable and easier to manage.

`async` Keyword

- Declares a function as asynchronous.
- Always returns a **Promise** — even if you return a plain value.

```
async function greet() {  
  return "Hello";  
}  
  
greet().then(console.log); // "Hello"
```

`await` Keyword

- Can **only be used inside an** `async` **function**.
- Waits for the Promise to **resolve or reject**, and returns the result.

```
async function fetchData() {  
  const response = await fetch("https://api.example.com/data");  
  const data = await response.json();  
}
```

```
console.log(data);  
}
```



If the Promise is rejected, the exception is thrown at the point of await.

✓ Full Example

```
async function getUserData() {  
  try {  
    const response = await fetch("https://jsonplaceholder.typicode.com/users/  
1");  
    const data = await response.json();  
    console.log("User:", data.name);  
  } catch (error) {  
    console.error("Error fetching user:", error);  
  }  
}
```



Error Handling with try...catch

When a promise **rejects**, the `await` throws an error just like a `throw` statement. You handle it using `try...catch`.

```
async function fetchUser() {  
  try {  
    const response = await fetch("https://wrong-url.com");  
    const data = await response.json();  
    console.log(data);  
  } catch (err) {  
    console.error("Failed to fetch:", err.message);  
  }  
}
```

Comparing Promises vs Async/Await

Aspect	Promise Syntax	Async/Await Syntax
Syntax	<code>.then().catch()</code>	<code>try { await } catch {}</code>
Readability	Harder in deeply nested chains	Much easier to follow
Error Handling	<code>catch()</code>	<code>try...catch</code>
Return Value	Wrapped in Promise	Wrapped in Promise

Returning Multiple Awaits

```
async function multipleRequests() {  
  const user = await fetch("/user");  
  const posts = await fetch("/posts");  
  // Do something with both  
}
```

 **Note:** These will run **sequentially** — to run them in parallel:

```
async function parallelRequests() {  
  const [user, posts] = await Promise.all([  
    fetch("/user"),  
    fetch("/posts"),  
  ]);  
}
```

Pitfalls

1. `await` **blocks** within its async function.
2. Use `Promise.all` if you need **parallelism**.
3. Don't use `await` at the top level (except in supported environments like modern browsers or Node with top-level await).

Best Practices

- Always wrap `await` calls in `try...catch`.
 - Use `async/await` for sequential flow logic.
 - Use `Promise.all` with `await` for concurrent execution.
 - Never `await` inside a loop if not necessary — instead, gather promises and use `Promise.all`.
-

Let me know if you'd like code examples using real APIs or want to compare performance with chained promises.