

XMLHttpRequest (legacy approach)

XMLHttpRequest in JavaScript — Legacy AJAX Method Explained

What is XMLHttpRequest ?

`XMLHttpRequest` (often abbreviated as **XHR**) is a built-in JavaScript object that allows you to send **HTTP requests** to a server **without reloading the page**. It was the standard way to make AJAX requests **before the Fetch API**.

Though considered **legacy**, it's still used in some older applications or environments where backward compatibility is needed.

Basic Syntax

```
const xhr = new XMLHttpRequest();
xhr.open("GET", "https://api.example.com/data", true);

xhr.onload = function () {
  if (xhr.status >= 200 && xhr.status < 300) {
    console.log("Response:", xhr.responseText);
  } else {
    console.error("Request failed:", xhr.status);
  }
};

xhr.onerror = function () {
  console.error("Network Error");
};

xhr.send();
```

Key Methods

| Method | Description |
|---------------------------------------|---------------------------|
| <code>open(method, url, async)</code> | Initializes the request. |
| <code>send([body])</code> | Sends the request. |
| <code>setRequestHeader()</code> | Sets custom HTTP headers. |
| <code>abort()</code> | Cancel the request. |



Making a POST Request

```
const xhr = new XMLHttpRequest();
xhr.open("POST", "https://api.example.com/data", true);
xhr.setRequestHeader("Content-Type", "application/json");

xhr.onload = function () {
  if (xhr.status === 201) {
    console.log("Created:", xhr.responseText);
  }
};

xhr.send(JSON.stringify({ name: "John", age: 30 }));
```

Reading Response Data

```
xhr.responseText // Raw text response
xhr.responseXML  // Parsed XML (if response is XML)
```

Monitoring Progress

```
xhr.onprogress = function (event) {
  if (event.lengthComputable) {
```

```

    console.log(`Received ${event.loaded} of ${event.total} bytes`);
  }
};

```

⚠ Error Handling

XHR does not reject on HTTP errors (e.g., 404 or 500). You must check `xhr.status` manually in the `onload` callback.

```

xhr.onload = function () {
  if (xhr.status >= 400) {
    console.error("HTTP error:", xhr.status);
  }
};

```

🕒 Timeout Handling

```

xhr.timeout = 5000; // 5 seconds
xhr.ontimeout = () => console.log("Request timed out!");

```

🧠 Comparison with Fetch

| Feature | XMLHttpRequest | Fetch API |
|--------------------|---------------------------|-----------------------------|
| Modern/Legacy | Legacy | Modern |
| Promises | ❌ No | ✅ Yes |
| Readable Code | ❌ Verbose, callback-based | ✅ Cleaner, async/await |
| Stream API support | ❌ No | ✅ Yes |
| JSON auto-parsing | ❌ Manual | ✅ With <code>.json()</code> |

✅ Use Cases (Today)

- Supporting old browsers (e.g., IE11)

- Embedded systems or environments that don't support Fetch
 - Learning how AJAX worked before Promises
-

Example: Reusable XHR Function

```
function sendRequest(method, url, data = null) {  
  return new Promise((resolve, reject) => {  
    const xhr = new XMLHttpRequest();  
    xhr.open(method, url);  
    xhr.setRequestHeader("Content-Type", "application/json");  
  
    xhr.onload = () => {  
      if (xhr.status >= 200 && xhr.status < 300) {  
        resolve(xhr.responseText);  
      } else {  
        reject(`HTTP Error: ${xhr.status}`);  
      }  
    };  
  
    xhr.onerror = () => reject("Network Error");  
    xhr.send(data ? JSON.stringify(data) : null);  
  });  
}
```

Summary

- `XMLHttpRequest` allows asynchronous HTTP communication with servers.
 - It's verbose and callback-based, lacking Promise support.
 - Still useful in legacy systems or when Fetch is not available.
 - Best replaced with the Fetch API in modern applications.
-

Let me know if you'd like a comparison demo between `XMLHttpRequest` and `fetch()` using the same API call.