

In the Lecture Series Introduction to Database Systems

SQL and Programming Languages

***Presented
by Stéphane Bressan
and Gillian Dobbie***

Introduction to Database Management Systems

SQL and programming languages

- Procedural SQL,
- Database Connectivity, and
- Embedded SQL
- PL SQL,
- JDBC, and
- SQLj

SQL alone is not enough

- SQL is not **computationally complete**

Computational completeness is the ability to express all possible computations

- SQL is not **system complete**

System completeness is the ability to access and control the resources of the computer

Incomplete by design

SQL incompleteness makes it a simpler language

- Easy to use (for the programmer)
- Easy to optimize (for the DBMS)

Example: flight connections

flight

number	departure	arrival	origin	destination
AF235	10:15:00 AM	12:10:00 PM	CDG	VCE
GA826	1:00:00 PM	2:00:00 PM	CGK	SIN
MH364	2:30:00 PM	3:30:00 PM	SIN	LGK
NZ4319	11:00:00 PM	2:15:00 PM	LHR	SIN
SQ5051	11:55:00 AM	1:00:00 PM	HKT	SIN
SQ866	1:30:00 PM	5:00:00 PM	SIN	HKG
TG401	3:00:00 PM	5:25:00 PM	SIN	BKK
TG952	11:55:00 PM	7:00:00 AM	BKK	CDG

Example: flight connections

SELECT flight.destination
FROM flight
WHERE flight.origin='CGK'

number	departure	arrival	origin	destination
AF235	10:15:00 AM	12:10:00 PM	CDG	VCE
GA826	1:00:00 PM	2:00:00 PM	CGK	SIN
MH364	2:30:00 PM	3:30:00 PM	SIN	LGK
NZ4319	11:00:00 PM	2:15:00 PM	LHR	SIN
SQ5051	11:55:00 AM	1:00:00 PM	HKT	SIN
SQ866	1:30:00 PM	5:00:00 PM	SIN	HKG
TG401	3:00:00 PM	5:25:00 PM	SIN	BKK
TG952	11:55:00 PM	7:00:00 AM	BKK	CDG

Example: flight connections

```
SELECT f2.destination  
FROM flight f1, flight f2  
WHERE f1.origin='CGK'  
AND f2.origin=f1.destination
```

number	departure	arrival	origin	destination
AF235	10:15:00 AM	12:10:00 PM	CDG	VCE
GA826	1:00:00 PM	2:00:00 PM	CGK	SIN
MH364	2:30:00 PM	3:30:00 PM	SIN	LGK
NZ4319	11:00:00 PM	2:15:00 PM	LHR	SIN
SQ5051	11:55:00 AM	1:00:00 PM	HKT	SIN
SQ866	1:30:00 PM	5:00:00 PM	SIN	HKG
TG401	3:00:00 PM	5:25:00 PM	SIN	BKK
TG952	11:55:00 PM	7:00:00 AM	BKK	CDG

Example: flight connections

WITH RECURSIVE

**connection (origin, destination) AS
((SELECT origin, destination
FROM flight)**

UNION

**(SELECT f.origin AS origin,
c.destination AS destination
FROM flight f, connection c
WHERE c.origin = f.destination))**

**SELECT destination
FROM connection
WHERE origin = 'CGK'**

Example: flight connections

number	departure	arrival	origin	destination
AF235	10:15:00 AM	12:10:00 PM	CDG	VCE
GA826	1:00:00 PM	2:00:00 PM	CGK	SIN
MH364	2:30:00 PM	3:30:00 PM	SIN	LGK
NZ4319	11:00:00 PM	2:15:00 PM	LHR	SIN
SQ5051	11:55:00 AM	1:00:00 PM	HKT	SIN
SQ866	1:30:00 PM	5:00:00 PM	SIN	HKG
TG401	3:00:00 PM	5:25:00 PM	SIN	BKK
TG952	11:55:00 PM	7:00:00 AM	BKK	CDG

In Summary

We need to connect SQL and programming languages

Coupling approaches

- External coupling
- Internal coupling

Three solutions

- Procedural SQL
- Database Connectivity
- Embedded SQL

Program structure

- Connection (external coupling)
- Statement preparation
- Statement execution
- Collection of results
- Exception handling
- Disconnection (external coupling)

Statement preparation

- **Prepare data structures** for communication between program and DBMS
- Request DBMS to **Compile SQL statement** (if possible)

Statement execution

- **Static** SQL statements
Written in the program source
- **Dynamic** SQL statements
Build at runtime

Collection of results

- INSERT, DELETE, UPDATE statements return single values
- SELECT statements return a collection of t-uples

Cursor

If result is too big or its size unknown, a **cursor** is used to fetch individual t-uples, one at the time, while the result is kept in the database

Transactions and exception handling

- Transactions:
 - Begin
 - Commit
 - Rollback
- Exception
 - Catch

Running example

```
CREATE TABLE employee
(name VARCHAR(24) PRIMARY KEY,
 address VARCHAR(36)
           DEFAULT 'company address',
 department VARCHAR(24)
           REFERENCES department(name),
 salary NUMERIC);
```

```
CREATE TABLE department
(name VARCHAR(24) PRIMARY KEY,
 location VARCHAR(36),
 budget NUMERIC);
```

Procedural SQL

Most DBMS support a procedural extension of SQL

PL/SQL is the procedural extension of Oracle 9i

Stored procedures are written in PL/SQL

Structure of a PL/SQL program

DECLARE

/* Declarative section: variables, types, and local subprograms. */

BEGIN

/* Executable section: procedural and SQL statements go here. */

/* This is the only section of the block that is required. */

EXCEPTION

/* Exception handling section: error handling statements go here. */

END;

Preparation

DECLARE

salary NUMERIC NOT NULL;

credit_bound NUMERIC := 3000000;

date DATE;

employee_number NUMERIC := 0;

manager BOOLEAN;

Execution

```
DECLARE
my_department_name VARCHAR;
BEGIN
    my_department_name := 'sales';
    SELECT name
    FROM employee
    WHERE department = my_department_name;
END;
```

Execution: variables

```
DECLARE
```

```
    my_salary NUMERIC;
```

```
BEGIN
```

```
    SELECT salary INTO my_salary WHERE name = 'Nancy  
        Santi';
```

```
END;
```


Execution: control

```
DECLARE
  sales NUMERIC;
  sal NUMERIC;
BEGIN
  [...]
  IF sales > 50000 THEN sal := 1500;
    ELSIF sales > 35000 THEN sal := 1200;
    ELSE sal := 1000;
  END IF;
  INSERT INTO employee
  VALUES ('Tiziana Dezza', '132, via Dellatti',
          'research', sal);
END;
```

Preparation: cursor

```
CURSOR high_budget IS  
  SELECT name, budget  
  FROM department  
  WHERE budget > 10000;
```

Execution: cursor

- Open

```
OPEN high_budget;
```

- Fetch

```
FETCH [orientation] FROM high_budget  
INTO name, budget;
```

(orientation is one of **NEXT, PRIOR, FIRST, LAST,...**)

- Close

```
CLOSE high_budget;
```

Execution: cursor

```
DECLARE
name VARCHAR(24);
budget NUMERIC;

CURSOR high_budget IS
  SELECT name, budget
  FROM department
  WHERE budget > 10000;

BEGIN
  OPEN high_budget;

  LOOP
    FETCH NEXT FROM high_budget INTO name, budget;
    EXIT WHEN high_budget%NOTFOUND;
    dbmsoutput.put_line('Name: ' || name);
    dbmsoutput.put_line(' Budget: ' || budget);
  END LOOP;

  CLOSE high_budget;
END;
```

Execution: dynamic statements

EXECUTE IMMEDIATE dm;

Transactions

A transaction

- Starts implicitly
- Ends with execution, or
- COMMIT, or
- ROLLBACK

Exception Handling

```
DECLARE
    sum_bud NUMERIC;
    avg_bud NUMERIC;
BEGIN
    SELECT SUM(budget) INTO sum_bud FROM
        department;
    IF sum_bud = 0 THEN RAISE ZERO_BUDGET END IF;
    SELECT sum_bud/COUNT(*) INTO avg_bud FROM
        employee;
    EXCEPTION
        WHEN ZERO_DIVIDE
            THEN PRINT "Division by Zero";
        WHEN ZERO_BUDGET
            THEN PRINT "No budget has been assigned yet";
END;
```


Database connectivity

- Database connectivity is a programming interface called “Call Level Interface”
- The CLI is implemented as a library for the host language
- SQL-99 specifies how CLIs must be defined

Database connectivity

- ODBC:
Open Database Connectivity
- JDBC:
Java Database Connectivity

Database connectivity architecture



Connection

Driver specification:

```
Class.forName("sun.jdbc.odbc.JdbcOdbcDriver");
```

Connection:

```
Connection con =  
DriverManager.getConnection("jdbc:odbc:myDB",  
                             "myLogin", "myPassword");
```

Preparation and execution

SQL statements are strings

- They are dynamic statements

```
Statement stmt = con.createStatement();  
stmt.executeQuery("SELECT * FROM employee");
```

- They can be 'prepared'

```
PreparedStatement pstmt =  
con.prepareStatement("SELECT * FROM employee");  
pstmt.executeQuery();
```

Preparation and execution

Prepared Statements can be parameterized

```
PreparedStatement pstmt =  
    con.prepareStatement("SELECT *  
                        FROM employee  
                        WHERE department = ?");  
pstmt.setString(1, 'research');  
pstmt.executeQuery();
```

- *Parameters identified by ‘?’*
- *Values assigned to parameters by ‘setXXX’ methods*
- *Parameters identified by their position in the string*

Execution: cursor

```
Statement selstmt = con.createStatement();
```

```
String stmt = "SELECT *  
              FROM employee  
              WHERE salary > 1000";
```

```
ResultSet res = selstmt.executeQuery (stmt);
```

```
while ( res.next() )  
{  
    System.out.println (res.getString ("salary"));  
}
```

Transactions and exception handling

- Auto commit:
every connection is a transaction
- Auto commit can be turned off:
explicit commit or abort
- Exceptions can be caught:
`java.sql.SQLException`

Embedded SQL

Embedded SQL is a form of external coupling

Programming languages like C, Pascal, Fortran or Cobol are extended to the execution of SQL statements

- prefix is keyword **EXEC SQL**
- suffix is the semi-colon

SQLj is an ANSI/ISO for embedding SQL into Java

- prefix is **#sql**
- suffix is the semi-colon

Connection

```
oracle.connect("jdbc:odbc:my_DB",  
               "my_login",  
               "my_password");
```

Execution

```
#sql { INSERT INTO employee VALUES (  
    'Stefano Olivaro', 'Piazzale Roma',  
    'research',1500) };
```

Execution: variables

```
String department = 'research';  
BigDecimal my_budget;  
#sql { SELECT budget INTO :my_budget  
      FROM department  
      WHERE name = :department };
```

Execution: result and cursor

```
#sql iterator Emplter (String name, Real salary);
Emplter my_empiter = null;
#sql my_empiter = {SELECT name, salary FROM
    employee};
while (my_empiter.next())
{
    System.out.println("Name: " + my_empiter.name());
    System.out.println("Salary: " + my_empiter.salary());
}
my_empiter.close();
```

Transactions and exception handling

- Explicit COMMIT and ABORT
- Auto commit can be turned on
- Exceptions can be caught

In conclusion

- Procedural SQL,
 - Database Connectivity, and
 - Embedded SQL
- PL SQL,
 - JDBC, and
 - SQLj

Credits

The content of this lecture is based
on chapter 6 of the book
“Introduction to database
Management Systems”

By
S. Bressan and B. Catania,
McGraw Hill publisher

Animated characters are animated
using VocaliseTTS under
license from Digital Curiosity

Clipart and media are licensed from
Microsoft Office Online Clipart
and Media

Java and all Java-based marks are
trademarks or registered
trademarks of Sun
Microsystems, Inc.

JDBC is a trademark of Sun
Microsystems, Inc.

PL/SQL is a trademark of Oracle
Corporation

Oracle 9i is a trademark of Oracle
Corporation



Copyright © 2005 by Stéphane Bressan