

Data Splash!

An Educational Game about Machine Learning

Andrew Gray

445348

Submitted to Swansea University in fulfilment
of the requirements for the Degree of Master of Science



Swansea University
Prifysgol Abertawe

Department of Computer Science
Swansea University

September 20th, 2020

Declaration

This work has not been previously accepted in substance for any degree and is not being concurrently submitted in candidature for any degree.

Signed (candidate)

Date

Statement 1

This thesis is the result of my own investigations, except where otherwise stated. Other sources are acknowledged by footnotes giving explicit references. A bibliography is appended.

Signed (candidate)

Date

Statement 2

I hereby give my consent for my thesis, if accepted, to be available for photocopying and for inter-library loan, and for the title and summary to be made available to outside organisations.

Signed (candidate)

Date

*I would like to dedicate this work to the Hypnotoad.
All glory to the Hypnotoad.*

Abstract

As part of our Masters of Science accreditation, we must complete a research thesis. I have been decided upon to create an educational game centred around Machine Learning (ML), due to the authors desire to gain a deeper understanding of ML and their previous experiences as being a secondary school teacher. We have proposed a game that allows the player to interact with different key ML algorithms and models while providing mediums to help educate and teach the players the understanding of the ML and provide knowledge on how they operate. We will achieve this by creating learning research to accompany the game, as well as links to relevant scientific research to get a deeper understanding. While at the centre of it all, having a fun and engaging game, that uses ML to teach about ML. Through using Python, Pygame and industry-standard accepted libraries and packages, like Tensorflow and Sci-kit Learn. The game will provide key gameplay features that users would expect of games, which will be achieved by using fundamental gamification techniques, to create a fun and engaging game that allows the user to interact directly with the ML models.

Acknowledgements

First, I would like to thank my partner and my daughter for allowing me to pursue furthering my education. I would also like to thank my mother for all the support she has given through this adventure. Secondly, I would like to thank all the lectures that have taught me. I have much appreciated your knowledge and wisdom that you have passed on. Finally, I would like to say a massive thank you to my supervisor, Dr Michael Edwards, and my tutor, Dr Anton Setzer. An additional thanks I would like to give it to Thomas Tasioulis and Amal Abdulkader for befriending me during this MSc and all the help and support.

Contents

List of Tables	vii
List of Figures	viii
1 Introduction	1
1.1 Overview of the Problem	1
1.2 Overview of the Solution	2
1.3 Contributions	3
1.4 Thesis Overview	3
2 Background & Literature Review	5
2.1 Introduction to Edu-Games	5
2.2 Machine Learning	9
2.3 Proposed Solution	12
2.4 Summary and Overview of Proposed Solution	12
3 Methodology	13
3.1 Overview of Application	13
3.2 Overview of Specific Game Components	14
3.3 Evaluation of Application	17
4 Implementation	19
4.1 Tools	19
4.2 Frameworks	23
4.3 Packages	24
4.4 IDE	24

4.5	Intricacies of the Game Components	26
4.6	Example user stories (A UML term for case studies or example playthroughs) .	32
5	Evaluation	33
5.1	Evaluation of User Study and Approach	33
6	Conclusion & Discussion	35
6.1	Reflection on the application	35
6.2	Reflection on the evaluation	36
6.3	Reflection of the Project Development	36
6.4	Future Work	38
6.5	Summary and closing comments	39
	Bibliography	41
	Appendices	45
A	Implementation of a Relevant Algorithm	47
B	Supplementary Data	49

List of Tables

List of Figures

- 4.1 A comparison between Java, Python and C++ to print an output to the console. [1] . 20

Chapter 1

Introduction

As part of our Masters of Science accreditation, we must complete a research thesis. It has been decided upon to create an educational game centred around Machine Learning (ML), due to the authors desire to gain a deeper understanding of ML and their previous experiences as being a secondary school teacher.

1.1 Overview of the Problem

As every day goes by, machine learning is becoming more and more a part of our everyday lives. From voice assistance, predictive text suggestions, language translations, and even suggesting times to leave your home to get to your destination on time. Machine learning is very much ingrained in the tech that we use. However, machine learning gets perceived as a black box, a form of computer magic, where these unique algorithms, created by super-intelligent people, do some voodoo magical unknown thing. These naive views have led to a lot of misconceptions about the topic. Some misconceptions people have about Artificial Intelligence (AI) and ML is that 'AI does not need humans' and that 'AI is dangerous' [2]. Other misconceptions about AI and ML is that both concepts are very new, and the designed has got based on a human's brain. However, AI and ML is a technique that has been around for a long time. It is nowhere near the same as a human brain, even at the fundamental level. Another big misconception is that AI is smarter than humans and that the ML robots will come and destroy the humans. In result, leading to wiping out humanity and all life forms. However, while AI can be better at performing specific tasks, they are not genetically more intelligent than humans. AI will only do what it gets told to do, nothing more [2].

On the other hand, instead of fearing AI and ML, there is a lot of things that it is currently doing to help humankind and make things safer. For example, the RAC, one of the UK's largest motoring organisations, aims to try and detect low-speed car crashes. They do this by developing an onboard crash sensing system that uses advanced machine learning algorithms to detect low-speed collisions and distinguish these events from more common driving events, such as driving over speed bumps or potholes. Independent tests showed the RAC system to be 92% accurate in detecting test crashes, allowing them to be able to enable rapid response to roadside incidents [3].

1.2 Overview of the Solution

Our overall aim for the project is to research current techniques currently discussed within academia and methods that are used by developers and creators within the public domain. This research intention is to help us develop and create a fun and educational game about ML. The players will be, at the core of the solution, playing a game that interacts with different ML models. The player(s) will be manipulating the game board and data points to affect the decision boundary, or to figure out where the decision boundary or centre of the cluster is. The solution will get created by using GUI libraries and will have many different algorithms in the background, contributing to the main game mechanics. The aim is to achieve this by using libraries like SKLearn [4] and Tensorflow [5], to name a few.

1.2.1 Aims & Objectives

The proposed solution aims to create a fully interactive game that users will find fun and engaging, with elements of a scientific series game in certain areas within it. While, at the core of it, still providing a level of education to teach the players what the different machine learning algorithms are and how they fundamentally work. From our experience of being a teacher, learning has the most impact when the learner gets the chance to be able to fully interact with the learning subject content and see how it work first hand, rather than just being told about it and how it works.

We aim to create an educational game, that will help inform users what ML is and what it does. Which will aspire to, as a result, demystify the myths and misconceptions people have about ML and AI.

1.3 Contributions

The main contributions of this work can be seen as follows:

- **A written thesis explaining the steps and stages of the development of the project**

A document that's intention is to partner and explain aspects of the final application, explain decisions made and explain the research discovered to influence decisions.

- **An education game application about machine learning**

An application created that allows the player or user to interact with, and manipulate, different machine learning models. Additional content, in the form of a website, has additionally been provided and hosted online. This supplementary content is to help with the teaching and learning of the main ML concepts used within the application.

1.4 Thesis Overview

We will first look into the background literature related to this project. Looking into educational games, with relations to gamification generally and within education, while also looking at example applications already presented. We will also be looking into machine learning within this section and looking into its fundamentals. The fundamentals will involve looking into the required data, functions and dimensionality. While also looking into the different learning types of supervised and unsupervised learning.

Additionally, we will look at all the algorithms and models that intend to get implemented within the application. These include linear regression, logistic regression, k nearest neighbour, SVM, PCA, LDA, GMM, k-means, neural networks, [add the rest]. We will also be looking at how machine learning gets currently presented within education and how the concepts are presently getting taught and any educational games related to machine learning.

We will then go into the methodology of the project. This section will be explaining the overview of the application and its design and giving an overview of specific game components. While also providing the intended method for evaluating the application.

Next, we will be looking at how the application got implemented, explaining the languages and frameworks used. As well as the intricacies required to get each section of the application working as intended.

The final stages will be evaluating the results of the user study and the progress of the project overall. Additionally, a conclusion and a discussion reflecting on how the project went

1. Introduction

overall will get presented. At the same time, we are presenting any possible future work that could get done with the project.

Chapter 2

Background & Literature Review

2.1 Introduction to Edu-Games

2.1.1 Gamification

We wanted to find out what the context of gamification is, and how it can be used within education, to take aspects of teaching and learning that can get brought into the 21st Century. To make aspects of education more accessible to students in a manner that they are more accustomed to in their everyday lives.

Gamification, a term first coined in 2002, is an HCI technique used to add a game layer to traditional non-game like situations. The gamification aims to create extrinsic motivators for a person to be encouraged to do particular actions. Each action, upon completion, will have a little reward which, upon doing so, will release dopamine into the brain. The release of dopamine creates a good feeling within the participant's mind, which in turn is encouraging them to do it again. These rewards can be in the form of badges, achievements or progress bars, to name a few.

The term gamification first appeared in the context of software design in 2008 [6], but the term only started to get more widespread recognition within 2010. However, the term "gamification" was first coined by Nick Pelling in 2002 [7]. Its initial aim was to incorporate the social and reward features of games into the software. Gamification started to gain much attention, so much so that it got described by a venture capitalist as one of the most promising areas of gaming [8]. Gamification is now known as a powerful tool for engagement, which has, since its initial conception, now become a standard feature within software development [7]. Researchers consider gamification to be the progression of earlier work that focuses on

adopting game-design elements to non-game situations and contexts. Research in the HCI field, in regards to apps that use game-driven features for motivation and also in interface design, suggest that there is a connection between Soviet concepts of socialist competition and the American management trend of "fun at work" [8].

Jane McGonigal, in 2010, delivered a groundbreaking TED Talk titled, "Gaming Can Make a Better World" [9]. This talk gets reflected as the defining moment in the history of gamification. Within the talk, she foretells a game based utopia. Where she states that "When I look forward to the next decade, I know two things for sure: that we can make any future we can imagine, and we can play any games we want, so I say: Let the world-changing games begin [9]." Hindsight tells she was correct, as, from 2011, gamification starts to pick up steam. At a Computer-Human Interaction (CHI) conference, a workshop titled "Gamification: Using Game Design Elements in Non-Gaming Contexts [10]", which generated the Gamification Research Network (GRN) [11], in the year 2011. Through the years 2012 to 2016, gamification continues to grow. Even so, that gamification goes viral without people knowing through a game called Pokémon Go. Pokémon Go is one of the most successful applications of gamification with over 800 million downloads. People who would usually turn their nose up at badge collecting were out patrolling the streets searching for rare Pokémon. Pokémon Go is one of the most successful apps of all time. It even broke records [7, 12]. It could be said thanks to Pokémon Go, that gamification is now everywhere. Many established technology and other companies, including SAP AG, Microsoft, IBM, SAP, LiveOps, Deloitte, and other companies have started using gamification in various applications and processes [13].

The increased popularity in gamification, within some contexts, has had led to many legal restrictions be placed upon it, especially when linked to the Internet of Things (IoT) features. However, this mainly refers to the use of virtual currencies and assets, as well as data privacy, data protection and labour laws. These laws are due to its nature of being a data mining systems that spread information online, known as data aggregator [11, 14].

2.1.2 Gamification in Education

The gamification of learning is an educational approach to motivate students to learn by using game elements in a learning environment [15]. Gamification in education is very much the same thing as gamification in general, but with more of a focus on learning. However, gamification in learning has two main views within HCI academia. One side categories gamification of learning as learning that has game-like features, but only when the learning is happening

in a non-game context, like a classroom. This version would involve a range of components that get presented in a system, or game layer, which aims to happen alongside the learning in a conventional classroom. At the same time, the other half includes games that have been designed to induced learning within them [15].

Gamification, within an educational or a learning situation, has multiple advantages. It is not just about trying to improve attendance with incentives by reaching a particular score, or extra rewards for completing specific tasks within a lesson. It can aid in cognitive development in adolescents, which can increase levels of engagement and can aid with accessibility within the classroom [16]. Games that get produced for enhancing cognitive development are known as "rain games" [16]. These popular games typically are focused around a series of questions and problems for the player to solve or answer. These games develop the rate the player can sustain information and increase the brain's ability to process information. The levels of the engagement of the students' increases, when gamification has been used, within a classroom. A study performed by scientists aimed to measure the students' levels of engagement in a classroom where gamification elements are applied [17]. They assigned a point system to multiple daily activities. Every student had a measurement of the perceived level of engagement. The finding showed that the game like setting was supporting the learning within the classroom and increased productivity. Therefore, by increasing engagement levels, it also means it helps students be able to access the content of the lesson, that is or needs to be delivered better.

Even though gamification can aid teaching students of all needs, a study conducted on students who had autism using video games showed that this training package was powerful in teaching content that was age-appropriate [18]. However, gamification of learning is not something just for the classroom; its an excellent tool for learning outside the classroom. Games like Spore create a deeper understanding of life and evolution as the game simulates a world where the player's character will evolve, adapting to their surroundings through reproduction. Another game by the same creator, Will Wright, Sim City aims to teach the player key skills like [19]: Supply and demand; Budgeting; Urban planning; Managing the environment; Understanding utilities and services like transport systems and public services; Reading and maths skills.

Gamification of learning has excellent potential benefits. The benefits involve [15]: Allowing students to have ownership of their learning, as well as giving opportunities for the learner to gain a sense of their' own identity" through alternative role-playing selves. The freedom, without any negative repercussions, to fail and keep on trying again. The ability to increase

2. Background & Literature Review

fun and joy while learning. The opportunity for tasks to be differentiated. Making the learning visible and providing opportunities to inspire intrinsic motivators for learning. Also, the ability to aiding in motivating students with low levels of motivation.

Gamification in Science

Although science concepts still use more conventional styles of gamification. Science concepts will often use a type of gamification game that has a primary purpose, which is other than just for pure fun, called a 'serious' or 'applied' game. These types of games get utilised by industries like scientific exploration, education, health care, defence, emergency management, city planning, engineering and politics [20]. Although not all do, serious games tend to share aspects closely tied with simulational games. However, all serious games still have other gamification features included (see fig: ??).

Nonetheless, in regards to the field of science, serious games' role is to include crucial activities for scientists. These include outreach, teaching and research. With serious games on the increase, an emerging sub-genre is called citizen science games (CSGs) [21]. CSGs enables the user to produce as well as, or instead, analyse data for scientific use. Some examples of CSGs are GalaxyZoo, Foldit and HiRE-RNA [22,23]

Studies suggest that there are ten main rules for serious games to follow. These are [21]:

1. Define a serious goal - we must first define the purpose of the game at the beginning of its development. Is its purpose for science, outreach, teaching or a combination of all three?
2. Get the balance between entertainment and serious tasks - the game design should be implemented as a function of the objectives of the game. Therefore equilibrium and compromise need to be found between scientific accuracy and player accessibility.
3. Allow the player to interact with the scientific data - players interest increases if they can interact with the science data, enriching the learning experience. The ability for players to generate data also creates another perspective for the player, increasing interaction.
4. Promote onboarding and engagement - Expectations of players are varied. Therefore the reward system needs to be versatile. Ideally, the entry-level should be low and the difficulty altered to each player.

5. Manage Information Flow - How the information to the play gets received will impact their behaviour, either positively or negatively. So if the focusing is on the outcome, this could influence the results.
6. Provide an appropriate narrative - This is important for all games, but also crucial for serious games. The narrative should give the player context to the game, allowing them to know what to do.
7. Adapt the level design - Depending on the objective, variation on level designs needs implementing. These can include duration, tasks and difficulty.
8. Develop good graphics that are not just pleasing on the eye - High-quality graphics increase the player's immersion into the game.
9. Use all modalities, especially sound - Using just a visual channel can overload the player. Therefore it is vital to take the load of the player's vision and use several different channels — for example, sound.
10. Iteratively assess what works and what does not - However, it is vital to take into account three different perspectives for serious games. The developer, the player and the scientist as they all have different views on what they believe the game needs adapting based on their desires.

2.1.3 Example Applications

2.2 Machine Learning

2.2.1 Machine Learning Fundamentals

2.2.2 Supervised vs Unsupervised Learning

Machine learning uses two types of techniques: supervised learning, which trains a model on known input and output data so that it can predict future outputs, and unsupervised learning, which finds hidden patterns or intrinsic structures in input data [24].

Supervised:

Supervised machine learning aims to build a model that makes predictions based on evidence in the presence of uncertainty. The supervised learning algorithm takes the insights it has

gained, from a known set of input data and known responses to the data (output), also known as labels, and trains a model to generate reasonable predictions for the response to new data [3,24].

Supervised learning uses classification and regression techniques to develop predictive models. Classification is a technique that predicts discrete responses. The classification aims to classify the inputted data into different categories [3]. Some examples of this type of technique are deciding if an email is spam or not, or deciding if a patient has a benign or cancerous tumour. These types of applications include credit scoring, medical imaging and speech recognition.

On the other hand, regression techniques try to predict continuous responses [24]. An excellent example of this is to check for changes in the temperature or checking the power demands fluctuations. This kind of applications would get used for trading and forecasting electricity load [3].

Unsupervised Learning:

Unsupervised learning aims to find hidden patterns or intrinsic structures in the data [24]. In the same regards as supervised learning, unsupervised learning aims to gain insights from the data. However, whereas supervised learning has the output labels for the provided dataset, unsupervised does not, it aims to explore the data to find patterns or groupings in the data [3].

Examples of clustering applications include gene sequence analysis, market research, and object recognition [3].

2.2.3 Methods

2.2.3.1 K-Means

2.2.3.2 Gaussian Mixture Model

2.2.3.3 Neural Network

Linear regression is a model that aims to fit a line of best fit to the data provided [24, 25]. A requirement for linear regression is for a set of methods intended for regression in which the target value expects to be a linear combination of the features. In mathematical notation, if \hat{y} is the predicted value. $\hat{y}(w, x) = w_0 + w_1x_1 + \dots + w_px_p$ Across the module, we designate the vector $w = (w_1, \dots, w_p)$ as the coefficient and w_0 as the intercept [25]

LinearRegression fits a linear model with coefficients $w = (w_1, \dots, w_p)$ to minimise the residual sum of squares between the observed targets in the dataset, and the targets predicted by the linear approximation [25]. To achieve the best fit to the dataset the algorithm chooses the best overall score from the 'Root Mean Square Error' (RMSE). Therefore, to train a linear regression model, we need to find the value of w that minimises the RMSE [24]. Mathematically it solves a problem of the form [25]: $\min_w ||Xw - y||_2^2$

The coefficient estimates for linear regression rely on the independence of the features. When features are correlated, and the columns of the design matrix X have an approximate linear dependence, the design matrix becomes close to the singular, which causes the least-squares estimate to become highly sensitive to random errors in the observed target, which in turn produces a large variance. This situation of multicollinearity can arise, for example, when data get collected without an experimental design [24, 25].

2.2.3.4 Logistic Regression

Logistic regression is an algorithm that gets used for classification. Logistic regression gets used to estimate the probability that an instance belongs to a particular class. If the estimated probability is greater than 50%, the model predicts that the instance belongs to that class. If the model has predicted that the instance belongs to that class, also known as the positive class, it gets a '1' label [?].

2.2.3.5 SVM

Support Vector Machine (SVM) is a powerful and versatile ML model. The model is capable of performing linear or nonlinear classification, regression and even outlier detection [24, 26]. This model is one of the most popular ML models and is best suited for small to medium-sized datasets. The model aims to separate the data categories by using a decision boundary, with the largest margin between them. Due to the model using a large margin to separate the data, the algorithm gets known as the 'large margin classification' [24].

SVMs are a set of supervised learning methods and have many advantages, especially when working in high dimensional spaces. SVMs are also useful in situations where the number of dimensions is greater than the number of samples. Due to the model using subsets of the training points in the decision function, the model is memory efficient, and it is very versatile. The model is very versatile due to the different kernel functions that can be used [26]. Although the model does have many strengths, it does also have a few disadvantages. A disadvantage is if

the number of features is considerably greater than the number of data samples, then overfitting can happen. A way to overcome this is to choose different kernel functions, and regularisation of the term is crucial. Another disadvantage is that SVMs do not provide probability estimates. These estimates get calculated by using an expensive five-fold cross-validation [26].

2.2.3.6 Linear Discriminant Analysis

2.2.3.7 PCA

2.2.3.8 kNN

2.2.4 Machine Learning in Education

2.2.4.1 Classical Approaches

2.2.4.2 Machine Learning Edu-Games

2.3 Proposed Solution

The overall aim of the proposed solution is to create a fun, educating game about ML. The players will be, at the core of the solution, playing a game that interacts with different ML models. The player(s) will be manipulating the game board and data points to affect the decision boundary, or to figure out where the decision boundary or centre of the cluster is. The solution will get created by using Pygame and will have many different algorithms in the background, doing the main game mechanics, through using libraries like SKLearn [4] and Tensorflow [5].

2.4 Summary and Overview of Proposed Solution

Chapter 3

Methodology

3.1 Overview of Application

The application has three main segments. These segments are a game area, a learning area and an exploring area. Each area's intension is to help support the user learning and understanding of the different machine learning models using a blend of exploration, fun and interactivity as well as a more traditional teaching a learning style of quizzes and learning reading material. Although each segment has its core task, together they help give the user a rounded learning experience while creating gamification incentives to come back and use the application some more.

3.1.1 Design

With the application being about the user interacting with data, and placing (splashing) the data points around a game board, we decided upon the title "Data Splash". With the title 'Data Splash' agreed upon, a beach and sea themed colour pallet got chosen. The pallets colours contained blue, yellow, turquoise and orange. However, additional colours got used to aid the colour pallet selected, and these colours involved grey and red.

All the screens had a similar layout, with a title banner image at the top, the content in the middle and the buttons in the bottom general area. The only screens that are different are the main menu screen and the coming soon splash screen. The main menu did follow a similar structure, but the main content was the buttons, which get presented in a horizontal stage manner (see fig: ??).

Whenever a model or educational content got made available to the player, this content

was the main focus to the screen. Therefore always making sure that the user's attention was on interacting with the model or learning about them. Unless like in the Free Play area, both learning and model interaction was available, equal weighting occurred given to allow focus on interacting and learning about the machine learning models.

3.2 Overview of Specific Game Components

3.2.1 Game Arena

The 'Game Zone' was the critical area that intended to use game mechanics, and gamification, to help drive the learning of the different machine learning models. The game zone is an area that allows one on one (player vs player) game action. The game gets conducted over three rounds, with each game round having a random model generated for the players to interact. At the time of writing this report, the available models for the game zone are Linear Regression and K-Means. A Neural Network got implemented with game mechanics, but due to time restrictions, we were unable to add them to the application in time. As the research suggested, having a competitive nature to the game creates desired external motivation for the player to learn more about the ML models, to be able to have a better chance of winning. A running score is presented to the players to let them know who won the previous round and who is currently winning. The multiple forms of game stats allow the players to have an idea of what is needed to win the game potentially through using sport like game mechanics to add the layer of progress updates continuously, to create that sense of competitiveness and external motivation. Even though there were only two models implemented fully into the game, these models offered several different gaming outcomes. For example, each model had multiple datasets which would get selected at random. In terms of K-Means, a random dataset would get generated each time or a preselected dataset, but the k value would change and be a random number. So even though the dataset was a k value of 2, the challenge would be added by not knowing what k value was given to the model for the user to predict the centroid value.

We selected K-Means and Linear Regression to be implemented first due to them both having a similar game mechanic intention. Linear Regression was using the SSE metric value as the deciding factor to determine the game's winner, while K-Means was using the model's metric value of the euclidean distance to do the same thing. The neural network uses a territory-based mechanic, and this intention was to add variety in not only the models but the game times. Challenging the players understanding of how different models work.

With having multiple models available, as well as getting the models and their datasets randomly selected each time, this allows the game to feel fresh each time and not have a set pattern of motions. Therefore, by creating a sense of game mode uncertainty or randomness will keep things fresh. Thus, ultimately making sure that a critical mechanic of gamification, which is replayability, be achieved.

There were intentions for the Learning Zone to also provide example code for the user, after specific gamification actions, for example getting full marks in the quiz, were completed as bonus rewards. The intention of this was to allow the users to not only learn about the code but also see the code, to help see the mechanics in it. However, due to time restrictions and certain gamification features not being implemented, this additional feature was not added at this point.

3.2.2 Learning Zone

The learning zones aim is for the user to do the principal amount of learning about the different machine learning models. The main content gets presented to the user by using a web browser widget. This widget would link to a multipage HTML website that holds all the content about the different models with pictures. We decided to use this combination as it allowed us to update the learning content and add new content as we went along, enabling the main functionality not get affected. Also, it avoided unnecessary long developing time, because of the updates and the new content, forcing the redesign of the game screen.

With the teaching and learning getting conducted through text and images on the webpages, we decided to add a quiz. The quiz was to allow the user to assess how much they have learnt. A useful tool used by teachers to evaluate students learning is different questioning techniques. In an attempt to allow the users to test their subject knowledge, but keeping everything in a game-like manner, a quiz was implemented. The quiz, with not only challenging the user but also offers an overall score allowing the user to know how they did and will enable a form of competition to happen and also let the use sense a way of progression by observing their performance improving.

An option available to the user is not only to quiz themselves but also to have the ability to go straight to the Free Play area. When the user selected this option, the model that the user has been learning about will be preloaded into the screen, allowing them to be able to interact with it. We decided to do this as although you can learn a lot about a topic by reading about it, an effective way to truly learn about something is to be able to interact with it and see what is

happening by, in essence, trying to break it in a sort of way.

3.2.3 Free Play

The free play area is where the serious gamification style gets implemented. This area intends to allow users to be able to interact with the ML models. Initialise not only the models but also set the type of data they want to have displayed and even add additional data points. By allowing the user to add extra data points to the existing data, it will update the model and, for example with Linear Regression, will show to the user, how the additional data points will affect the model's decision making.

The most interactive model's within the FP area, at current, are the models Linear Regression, K-Means, LDA and Neural Networks. However, the models GMM and SVM are also available, but with less interactivity as the others. K-Means allows the user not only to select different data sample but also select how many clusters they want the dataset to have, but also independently change the k value of clusters. We decided upon this feature to allow the user to see, knowing how many k clusters the dataset has, to see by changing the algorithms k value how is that then affected on the dataset with its outcome. The user can click within the Matplotlib widget and see what the data points prediction values are as well. We decided to use a click in the widget functionality, as we believed having the user input x and y coordinates would make the UI look cumbersome and add unneeded fiddliness for the user, trying to figure out the exact values they want. Linear regression allows the player to be able to make predictions, as well as additional data points allowing them to see how the data can be altered and manipulate and what implications that has on the models fitting. However, Linear Regression does not provide as much control for the intricacies of the model compared to K-Means, but it does offer the parameters and outputs that the model has. For example, the intercept and the coefficients to the model. Neural Networks offer slightly less control to the user compared to the other two, but more than LDA but both of them have fully interactive models. SVM and GMM, on the other hand, do not. GMM allows the user to switch its predictions on and off, but SVM just shows the models predictions. These got implemented to help with understanding the content from the learning zone, but we decided to focus on the other models due to them having more game-like features to get used in the game area.

3.2.4 Awards Zone

The achievement area has just a title, coming soon image and a button. Once the button gets pressed, it will return the player to the main menu. This area intention was to be the central hub of where all the gamification elements of badge unlock and progress, would be displayed to the user, giving them instant feedback on unlocked prizes and game modes, as well as hints on what to do to unlock additional features. However, due to time restrictions, this was unable to be implemented within the application. The idea was to allow the users to see how or what affects the models, from little changes to significant changes like changing the number of clusters in k-Means or the main algorithm being used to fit the clustering data. The intention was to allow the user to get hands-on with the different models, to see what they have learnt from the learning zone in motion, and also try out strategies for the game zone.

The models had three data settings, a custom one and two pre-generated datasets. The pre-generated data sets allow the user to be able to change the features that are used, assigning news features to the X and y-axis.

3.3 Evaluation of Application

To gain a deeper understanding of the application, for its effectiveness and the general overall thoughts from other peoples views, a user study got conducted. The user study involved participants in interacting with the application and then fill in an online questionnaire about what they thought of it. However, due to the coronavirus pandemic, the study got done all remotely.

The user study involved [number] of participants and got done in a quantitative style, using questionnaires of a range scale. This style of questions got decided upon due to the inability to ask the candidates follow-up questions. The participants got asked to install the application and then spend a minimum of 20 minutes interacting with it. After they had spent a minimum of 20 minutes on the application, they then needed to complete a questionnaire. The questionnaire consisted of [number of] questions with the questions either a range option style question of 1 to 5 or a short paragraph explanation. The questionnaire got conducted using Google Forms, which allowed us to have all the responses appear in a spreadsheet. Therefore, allowing reflection on the user's opinions more accessible.

[What are the results?]

Chapter 4

Implementation

4.1 Tools

4.1.1 Programming Languages

For the implementation of our application, three primary programming languages deemed to be best suited for development. Apple’s Swift programming language [27] got considered early on, due to the author’s familiarisation with the programming language. The programming language gets used for creating applications for Apple’s mobile and desktop operating systems, and with 1.5 billion [28] iOS devices in circulation, that was a lot of potential users. Additionally, Apple’s iOS devices are prevalent within most educational settings, with Apple’s iPad being one of the primary go-to devices. However, due to the language not supporting key frameworks required, or providing similar alternatives, the decision to not use this language got made.

We then got presented with three main options to use, Python, R and HTML, CSS and JavaScript.

Python is a very popular programming language [29, 30], it is fast, easy-to-use, and easy-to-deploy programming language that gets widely used to develop scalable applications. Examples include YouTube, Instagram, Pinterest and SurveyMonkey [31]. The Python Software Foundation state that Python is a high-level, object-orientated (OOP), interpreted language with dynamic semantics. Due to the language being a high-level, it has many built-in data structures. These features, along with the dynamic typing and dynamic binding together make Python attractive to development teams working in a Rapid Application Development (RAD). As Python is an extracted level above the C language [32], Python can get used as the glue that

Hello World

Java:

```
// Hello World in Java
class HelloWorld {
    static public void main(String args[]) {
        System.out.println("Hello World!");
    }
}
```

C++:

```
// Hello World in C++
#include <iostream.h>
Main() {
    cout << "Hello World!" << endl;
    return 0;
}
```

Python:

```
# Hello World in Python
print("Hello World!")
```

Figure 4.1: A comparison between Java, Python and C++ to print an output to the console. [1]

connects existing components, as well as being able to be used as a scripting language [33]. Python gets considered to be easy to learn the language due to its high readability and is recommended by many exam boards as the language to use for teaching Computer Science at GCSE and A-Level level [?]. Python's simple and easy to learn syntax emphasises on readability, which, as a result, reduces the cost of program maintenance [33, 34].

Python gets compared to a lot of other languages. However, due to the requirements and expectations of the application, we will compare it to other similar style applications that can potentially do a similar job. These being Java, JavaScript and C++. In general, the choice of the programming language to use is many other real-world constraints, for example, financial cost, availability, training and even personal preferences and attachments. However, we will focus on language issues for the comparisons.

In comparison to Java, Python programs will typically take 3-5 times quicker (See fig: 4.1) to develop but will have a slower run time. The time difference gets attributed to Python's built-in data types and its dynamic typing [35]. As Java gets better characterised as a low-level implementation language, this would be the language of choice if application execution speed was the deciding factor. If this is not a factor, then there is no real benefit over Python.

What gets said about Java is also the same when comparing C++ to Python. It is often 5-10 times shorter than equivalent C++ code. Anecdotal evidence suggests that one Python programmer can finish in two months what two C++ programmers cannot complete in a year. Python shines as a glue language, used to combine components written in C++ [35].

In comparison to JavaScript (JS), Python's 'object-based' subset is very similar to JS. Python supports a programming method that uses simple variables and functions, similar to JS, that do not need class definitions. However, Python also supports writing for much larger programs, which leads to more reusable code by using an accurate OOP way while with JS, that is all that it can do [35].

Another language that presented itself to us was the R language. R is a language and environment for statistical computing and graphics. It is a GNU project which is similar to the S language and environment which was developed at Bell Laboratories (formerly AT&T, now Lucent Technologies) by John Chambers and colleagues [36]. Many users think of R as a statistics system [36]. Academics and statisticians have developed R over two decades. There are around 12000 packages available in CRAN (open-source repository). The wide variety of library makes R the first choice for statistical analysis, especially for specialised analytical work [37].

R provides a wide variety of statistical (linear and nonlinear modelling, classical statistical tests, time-series analysis, classification, clustering) and graphical techniques, and is highly extensible. One of R's strengths is the ease with which well-designed publication-quality plots can be produced, including mathematical symbols and formulae where needed [36]. The cutting-edge difference between R and the other statistical products is the output. R has fantastic tools to communicate the results. Rstudio comes with the library knitr. Communicating the findings with a presentation or a document is easy [37].

R and Python are both open-source programming languages with a large community. New libraries or tools are added continuously to their respective catalogue. R is mainly used for statistical analysis, while Python provides a more general approach to data science. R and Python are both state of the art in terms of programming language oriented towards data science. Learning both of them is, of course, the ideal solution. R and Python requires a time-investment, and such luxury is not available for everyone. Python is a general-purpose language with a readable syntax. R, however, is built by statisticians and encompasses their specific language [37].

Python can pretty much make the same tasks as R: data wrangling, engineering, feature se-

4. Implementation

lection web scrapping, creating an app, for example. Python is a tool to deploy and implement machine learning at a large-scale. Python codes are easier to maintain and more robust than R. Years ago; Python did not have many data analysis and machine learning libraries.

Recently, Python is catching up and provides cutting-edge API for machine learning or Artificial Intelligence. Most of the data science job can get done with five Python libraries: Numpy, Pandas, Scipy, Scikit-learn and Seaborn [37].

Python, on the other hand, makes replicability and accessibility easier than R., if we need to use the results of our analysis in an application or website, Python is the best choice [37].

In 2019 there was an active number of 26.66 billion devices attached to the internet [38,39], with an estimation of 35 billion in 2021 [38] and by 2025 75.44 billion [39]. Experts estimate that the IoT device market will reach \$1.1 trillion in 2026 [38]. Every Second 127 new devices get connected to the world wide web [38].

With so many devices on the internet, an important consideration we had was to make the application web-based. By creating the application for the internet, this would allow potentially many more people to be able to access the application and interact with the different ML models.

JS gets regarded as more of the language of the world-wide-web [40]. It got initially designed to be used client-side in a web browser. However, it has in more recent years started to branch out and be able to be used to create applications on, not only the front end of the web but also desktops, servers and mobile platforms natively. For example, React Native, Node.js and TypeScript. JavaScript is also incredibly useful, allowing developers to be able to create apps with audiences in the millions quickly [41].

The decision on what language to use we a close call between Python and JavaScript, this was due to the massive amounts of libraries that were on offer and the support communities that were in place. With both being open source and both having essential libraries available to interact with machine learning models and visualisation tools, both could have been a perfect fit for the intended application. However, we decided upon using Python. Python was chosen based on it being the go-to language for anything machine learning related, and its ability to be able to be used multiplatform on desktops or mobile devices. Python supports modules and packages, which encourages programs to be developed modularity and therefore allows code to get reused. The Python interpreter and the extensive standard library are available in source or binary form without charge for all major platforms and can get freely distributed [33]. There was also an additional factor that the author was more familiar with Python and its required

libraries compared to the libraries that will get required for using JavaScript.

There was the additional decision to use HTML and CSS within a small part of the project, the 'Learning Zone', based on the quickness of being able to create and host the webpages containing the learning content. It was allowing the learning content to evolve without having any impact on the overall development of the main application, allowing the learning content to be an individual entity within the main application.

4.2 Frameworks

4.2.1 GUI Framework

With the nature of the application, we needed to make the application have a Graphical User Interface (GUI). Having a GUI allowed the learning to be a lot more hands-on and allow the players to see what is happening within the models, especially when they interact with them.

Therefore, due to the GUI requirement, three GUI libraries presented themselves to us. These were Pygame, PyQt5 and Tkinter.

Pygame is a free, open-sourced library. Released under the LGPL licence, Pygame is a set of Python modules designed for writing video games. Pygame adds functionality on top of the standard Python library. Pygame allows the user to create fully featured games and multimedia programs in the python language [42].

Pygame is highly portable and runs on nearly every platform and operating system, and it gets downloaded millions of times [42].

With the main aim of the application to be a game, Pygame was a strong contender. It was providing modules that can handle a lot of the key gaming mechanics and multiple screen switching. However, it lacked some key features that were deemed essential for the application. It was unable to provide a library that could create interactable graphs to be used as data inputs for the models and be able to render HTML and CSS content for the Learning Zone. Therefore reducing the amount of flexibility, it got decided upon for using HTML and CSS for the learning content. Therefore, meaning that all the content would need to be hardcoded. If any changes were needed, a significant transformation would need to happen to the overall code, instead of just changing the web content.

PyQt is a set of Python v2 and v3 bindings for The Qt Company's Qt application framework and runs on all platforms supported by Qt including Windows, macOS, Linux, iOS and Android. PyQt5 supports Qt v5. PyQt4 supports Qt v4 and will build against Qt v5. The bindings

are implemented as a set of Python modules and contain over 1,000 classes [34]. PyQt brings together the Qt C++ cross-platform application framework and the cross-platform interpreted language Python.

Qt is more than a GUI toolkit. It includes abstractions of network sockets, threads, Unicode, regular expressions, SQL databases, SVG, OpenGL, XML, a fully functional web browser, a help system, a multimedia framework, as well as a rich collection of GUI widgets. Qt classes employ a signal/slot mechanism for communicating between objects that is type safe but loosely coupled making it easy to create re-usable software components [34]. Qt also includes Qt Designer, a graphical user interface designer. PyQt is able to generate Python code from Qt Designer. It is also possible to add new GUI controls written in Python to Qt Designer [34]. PyQt combines all the advantages of Qt and Python. A programmer has all the power of Qt but can exploit it with the simplicity of Python [34].

Tkinter is the third option. Tkinter commonly comes bundled with Python, using Tk and is Python's standard GUI framework. It is famous for its simplicity and graphical user interface. It is open-source and available under the Python License [43].

Tkinter is Python's de-facto standard GUI (Graphical User Interface) package. It is a thin object-oriented layer on top of Tcl/Tk. Tkinter is not the only GuiProgramming toolkit for Python. It is however the most commonly used one. CameronLaird calls the yearly decision to keep TkInter "one of the minor traditions of the Python world [44]." Tkinter supports functionality with Matplotlib, with Matplotlib offering libraries to allow handling the backend of the graph creation interacting with the GUI library. However, unlike QT, Tkinter does not support any GUI designer. Therefore the GUIs will have to be created programmatically, which will give more control, might involve more of a learning curve and potentially more time to implement in the initial stages.

After reviewing the different GUI libraries, PyQt was the decided library to use. We believed it would give us the ability to have

4.3 Packages

4.4 IDE

PyCharm is a dedicated Python Integrated Development Environment (IDE) providing a wide range of essential tools for Python developers, tightly integrated to create a convenient environment for productive Python, web, and data science development [45]. While PyCharm is

a very popular IDE, and one that we have had experience with before, it is not, however, one that we have had many experiences using compared to other IDEs. While it does provide much functionality and it is a lot easier to use and keep our directories organised compared to Python's provide IDE, it has, however, not been an IDE that has flowed well when we have used it.

Visual Studio Code (VS Code) is a free source-code editor made by Microsoft for Windows, Linux and macOS. Features include support for debugging, syntax highlighting, intelligent code completion, snippets, code refactoring, and embedded Git. Visual Studio Code combines the simplicity of a source code editor with powerful developer tooling, like IntelliSense code completion and debugging. First and foremost, it is an editor that gets out of the user's way. The delightfully frictionless edit-build-debug cycle means less time fiddling with the required environment, and more time executing ideas [46].

Microsoft claims that VS Code, at its heart, lightning-fast code features a lightning-fast source code editor, which is perfect for day-to-day use. With support for hundreds of languages, VS Code helps the user be instantly productive with syntax highlighting, bracket-matching, auto-indentation, box-selection, snippets, and more [46]. For serious coding, the user will often benefit from tools with more code understanding than just blocks of text. Visual Studio Code includes built-in support for IntelliSense code completion, rich semantic code understanding and navigation, and code refactoring [46]. Which we can say from experience is mostly true. However, on occasions, it has provided code completion that was not intended or needed. VS Code also allows the user to customise every feature to their liking and install any number of third-party extensions. While most scenarios work "out of the box" with no configuration, VS Code also grows with you [46]. Which, from our experience, we can say is true. VS Code has grown with us. The VS Code community has provided many extensions that have helped with our workflow.

Atom is developed and released by GitHub [47]. Atom is free, and an open-sourced code editor. Atom is a self-labelled 'a hackable text editor for the 21st century'. Atom, like VS Code, allows developers to fully customise the look, feel, and requirements to speed up their workflows. However, Atom still allows developers to use it productively without ever touching a config file. Atom comes pre-loaded with eight syntax themes and four UI, two light and two dark, but if none of them provides any interest, Atom makes it easy and quick to install customised themes created by a third-party or to create one [47]. However, apart from pre-created extensions to help with code linting and code autocomplete abilities, none of these features is of any interest to us. The main factor does the IDE have a friendly UI and does it

seem not to hinder our workflow. Which is safe to say, it does have a friendly UI and does not hinder our workflow at all.

After trailing the different IDEs, we believed that the best option going forward was the VS Code IDE. We have chosen this IDE because of two key factors. The first one being that it supported all the libraries needed, whether it was pre-installed or through downloading additional extensions, and that we have had a better familiarity with the IDE's interface from previous uses and projects.

4.5 Intricacies of the Game Components

4.5.1 Gameplay Area

The Game Zone area is the main area where the gamification and game mechanics for the models get implemented. The models that have been implemented and found within this area are K-Means and Linear Regression. These both have the same game mode style, for linear regression, it is to fit the data point on the decision line, and K-Means is to place the data point as close to the centroid of a cluster as possible.

Linear regression's gameplay provides a random dataset to the players, and the model gets fitted at this point on the random dataset. However, the decision line does not get displayed within the Maptolib widget to the players at this point. The players then need to click within the widget to place their predictions of where the line sits; once each player has made four predictions, the model calculates the data points SSE value. The decision line then gets displayed to the players, and the players receive feedback on how they have done. With the SSE scores ranked from smallest being number one and the biggest being the last place.

K-Means game mode works in a very similar manner to linear regressions. However, where linear regression is aiming to place the data point on the decision line, the k-means game aim is to place the data points as close to the cluster centroids as possible. This game mode is similar in theory to linear regressions game mode but different in the way that there are multiple cluster centres and multiple options, which opens up a different style of strategy to the game and players. Therefore creating more variation and enticing the players to come back more. Additional variety gets added by multiple different datasets getting used at random each time, so even if the game randomly selects k-means two times in a row, each game has a high chance of it being different. These datasets can also be assigned a random value for the k variable, therefore adding an extra challenge. For example, a self-generated dataset called moons by

Sci-Kit Learn will create two moon-shaped data distributions. However, because the k value can change, each time the centroids might not be in the same place as it might not be two, it could be three or four. Resulting in a more strategic approach to the game when deciding on player moves and adding those extra gamification elements and difficulty to the game.

In order to assign scores to the players, the player with the smallest euclidean distance wins the round. The game does not take into account if it is at the different clusters, which value has the lowest metric and ranks them in order. Again adding to the strategy, for example, does the player take a chance on placing data points in one area or does the player try and spread them out. If they get all the data points close to a centroid, then they could take all the points, but if their decision is wrong, they could end up taking up the lesser points. The same winning points get rewarded based on their values for each game mode. The player with the smallest metric value will receive 100 points, 80 points for the next one, then 60, 50, 40, 30, 20 and 0 respectfully for each ranking. The winner of the round also gets 100 bonus points. After each round, these points get totalled up. The overall winner is decided based on which player has the highest points. The points are updated and displayed in the top right-hand corner of the game screen. Allowing the players to know how well they are currently doing. The screen also allows the players to know where they have currently placed their data points, showing the X and y coordinates. Additionally, an overview of the points from the previous round are displayed, letting the players know who the current leader is, player one's last round score and player two's last score round. Information about the aim of the game gets displayed to the players, as well as little tip section. These pieces of information intentions are to help guide the players into what they need to do.

The game mode has a default of three rounds, with each round being a random model and data set for the available models. Each round ends when the players have made four moves each, with each round creating individual scores. A message box will appear displaying the results to that round, with each rounds scores getting added to an overall game score. This score will always get displayed to the player in the top right area of the screen. Once the game is over, another message box will appear, giving an overview of the overall game and then returning the player to the main menu.

4.5.2 Learning Zone Area

The Learning Zone (LZ) area is an area that we intend to allow the user to do most of the learning. The LZ, in terms of UI, is very basic. It has a web browser window and three buttons.

4. Implementation

The web browser window is where the HTML and CSS documents, which the created web documents, get displayed within the application.

The web document consists of a welcome page, outlining the content, a "What is Machine Learning?", "Task Driven vs Data-Driven", "Supervised and Unsupervised Learning", "Classification", "Support Vector Machines (SVM)", "k-Nearest Neighbour", "Neural Networks", "Regression", "Linear Regression", "Logistic Regression", "Clustering", "K-Means", "Gaussian Mixture Model", "Dimensionality Reduction", "Principal Component Analysis", "Linear Discriminant Analysis" and "Association Rule" web pages.

The web pages follow a similar layout design. A blue background, a yellow background layer on top with an offset grey colour behind the text. Each page contains title at the top with a dark grey background. The content of the web pages either we an overview, for example, "Clustering", which looked into clustering as a whole and what the different types were. Alternatively, a web page would explain a specific algorithm, for example, "K-Means", which explained the intricacies of how the algorithm worked and the critical mechanics behind it.

The three buttons at the bottom of the application screen trigger three different actions. All of which match to the intended buttons, a home button, to go back to the main menu, a free play button to send the player to the free play area with the intended algorithm that the user was learning about, and a quiz button which loads a multi-choice quiz.

When the player clicks the free play button, the application checks the HTML documents title tag and loads up the required model in the free play section. However, if the player clicks the button and the web page does not have a model available, within the free play section or it is just a general overview page, a message box will appear. The message box intension is to let the user know that they can not progress to the free play zone and a list of the available models (see fig: ??).

The Quiz area is an additional area to the learning zone. The Quiz area is where the user can get tested on what they learned in the LZ area, in the form of a multiple-choice quiz. When the user is viewing a topic on the LZ, and they decide to take a quiz, the user will click on the quiz button, and this will read the title tags of the HTML document and open the required quiz. The quiz questions and answers are within their text file, and the name of the file matches the title tag's content. The text file itself holds the information in the format of a 2D array, that has the question at position zero, the answer at position one and then position 2 to 5 are the multiple-choice options. This information from the text file populates a question label and four buttons, allowing the user to click what button they think is the answer. The total of correct

answers get added up and displayed to the user at the end in a message box.

4.5.3 Free Play Area

The Free Play (FP) zone is an area where the user gets to interact and play with different ML models. The models include Linear Regression, K-Means, Neural Networks, Linear Discriminant Analysis, Gaussian Mixture Models and SVM. The intension for the FP zone was to have all the models explained in the learning zone be available for the player to interact with, so it could help them fully understand how the model works by allowing the user to manipulate parameters and data points. However, due to time restrictions, there are only six models available, with 5 of the models having real interactivity but to different degrees.

When the FP zone is accessed, unless accessed through the Learning Zone, a randomly selected model gets displayed to the user from the list mentioned before. On first glance, the user has multiple areas to either interact with or present information to them. The screen has a Widget that is linked to a Matplotlib library to handle PyQt5 backend interactions. Also, a model overview is displayed next to the widget, it tells the user information about the model, for example, the type of learning it is, supervised or unsupervised, the name of the model and a brief overview of the model. Just beneath the widget and overview is a group box that contains all the settings for the model and data interaction. The model settings group box contains combo boxes, radio buttons, checkboxes, line edits and buttons, which all do different things depending on the model and data sets selected. Within the model settings group box, there are three additional group boxes. These are 'Model Attribute(s)', 'Model Parameter(s)' and 'Data Options' with each group box displaying different content depending upon the model and data options selected in the combo boxes.

The model combo box contains six values, and these are 'Please Select', 'K-Means', 'LDA', 'Linear Regression', 'GMM', 'SVM', 'Neural Networks'. Once one of these options is selected, apart from the 'Please Select', the desired model will display in the Matplotlib widget area. The Model attributes and parameters boxes will display the required information unless the models 'LDA', 'SVM' and 'GMM' are selected. Instead, a label placeholder saying, 'No Options available, yet!' will be displayed. While LDA has a fully interactive model in the Matplotlib widget, it does not present options for the user to change within the model, the user can only click on the widget and place points, which the model will then apply and create the required actions. Therefore a place holder label appears stating to click in the game widget to interact with the model. While LDA and GMM both have the ability for the model

4. Implementation

visualisations to toggle on and off, showing how the models have fit their data, GMM has little much additional functionality. GMM only allows the user to toggle on and off the visualisation, which is the model predicting the 'Iris' dataset clusters. However, SVM only displays the model's output, again using the 'Iris' data set, but the output shows the boundary lines and area that each partition covers.

While on the other hand, the Linear Regression, K-Means and Neural Network models display different options. Linear Regression displays to the user labels in the attributes group box to show them the values for the intercept, estimated coefficient and outcome. There is also a line edit available for the user to input a value and see what the model would predict out, which gets displayed in the output label. However, Linear Regression does not have any model parameters, and this is due to the values getting deemed as not having much impact on the model and limited implementational time.

When K-Means gets selected, both the attributes and parameters group boxes have information and selection options displayed to the user. The attributes group box displays the information for Inertia, the number of iterations that got performed fitting the data, prediction, which relies on the user to click within the Matplotlib widget and the X and y coordinates get displayed along with a cluster prediction label in the output label. There is also a distance from the centroid value displayed, and this value got achieved by using the SKLearn Metrics library. The model parameters group box displays multiple line edits and a combo box that allows the user to input values to the model. These will alter the K-Means k value (number of clusters), the number of initialisers, the max number of iterations and the underlying algorithm (auto, full or Elkan), that gets used. The k value is independent of the number of clusters in the data options, so they do not impact on each other. Allowing the k value to be changed independently will allow the user to be able to experiment with the model to see how two, three or other k values affect the prediction, even when known that the data may have, for example, five different clusters. K-Means also brings up an additional option, and this is to be able to switch on and off the centres of the clusters. When the checkbox gets enabled, this will lay on top of the data points an 'X' where each of the cluster centres is and when it is disabled, it will remove the 'X'.

[NN Att no. of layers/ neurons -> params set the values. Not implemented in-app yet!]

The data combo box displays the data options for the different models and depending on what option is selected depends on the information that is on offer to the user in the data options group box. If the custom data option is selected, then the group box will display different

options to the user to be able to generate custom data points to be displayed in the Matplotlib widget game screen. The only models that have this option are the Linear Regression and K-Means models. Linear Regression has the data options 'Diabetes' and 'Boston House Prices' and K-Means has the data options 'Iris' and 'Moons'. When these are selected, the data option displays radio button options for the user to select the features they would like the model to display, on the X and y-axis, and get fitted. Linear Regression's 'Custom' data option allows the user the ability to change the random generated data's settings. These settings include the number of data samples and if there are any outliers wanted, if so then an option to add the number of outliers. Whereas K-Means 'Custom' data option allows the user the ability to change the number of clusters to generate and the number of data samples wanted. The other models have a label placeholder saying, 'no data options selected yet!' and no actual data selection options. In the case of LDA and Neural Network, this is more due to the decision we made. Based on the way the model's fit function was implemented, not allowing the user to generate random data was decided. Doing so would impact on how the model gets interacted with by the user. However, in the case of the other models, it was a lack of time that impacted the inability to add this feature. Though, it was always the intention to add it.

The final aspects of the Model options group box are three buttons, a play button, a clear button and a home button. Where the home button is self-explanatory in terms of returning the user to the main menu, and the clear button resetting the Matplotlib Widget axis contents. The play button is where the primary handling of how the user interacts with the back end of the models and datasets. When the user inputs information, they are required to press the play button for these features to be implemented.

4.5.4 Achievements Area

The intentions for the Achievement Area was displaying to the user all of the gamification badges available. Providing an overview and hints on how to unlock them. The achievements were going to have a bronze, silver and gold level, and we planned to be unlocked once the user had completed specific tasks like playing the game three times or completing a quiz. However, due to time limitation, this was not possible, and the application, as it currently stands, displays a coming soon image and button for the user to navigate back to the main menu.

4.6 Example user stories (A UML term for case studies or example playthroughs)

Chapter 5

Evaluation

Within this section, we will evaluate the results from the user study. We will also assess the outcome of the app based on our initial intentions and the original plan created within our specification report for our intended approach to the project. We will also discuss and reflect on the application itself, exploring functionality that could not get implemented and areas that could get expanded. Additionally, closing this section with a general reflection of the project. This reflection involves a summary of how the application turned out by the end of the allocated time frame.

5.1 Evaluation of User Study and Approach

[Need results]

Chapter 6

Conclusion & Discussion

6.1 Reflection on the application

Although a lot of features got implemented within the application, there are a few features and little functionality that was, unfortunately, implemented within the application. One of the main pieces of functionality that are missing from the application is the 'Award Zone' and the overarching gamification unlockables and features. Although the application has some gamification techniques. For example, user competition and instant feedback. However, our intention was always for the application to have many more gamification features. These features would have been within every stage of the application with the LZ being the main hub displaying the users progress.

We intended for the use of progress bars, unlockable badges and unlockable features get used within the application. Some of the unlockable features intended were to, when the user completed certain milestones, to unlock example code of the different ML models within the learning zone and links to future reading and academic papers for the ML model. Another feature was that some models in the Free Play Zone and the Game area would be unlocked once the player had accomplished specific tasks.

Another feature that did not get implemented was to present a pregame screen to the users. This screen was going to allow the players to be able to set up the game mechanics that were selected by the player. These game choices included: choosing a gameplay playlist, for example, territory or pin the data point; how many rounds within the game the players wanted; setting the difficulty setting to the game; selecting the number of players. Another feature intended for the game area was to have more ML models implemented, especially all of the

models available in the learning zone. However, one initial model that got implemented in the learning zone but did not get implemented in the game zone was the neural network model for a territory style gameplay. This style of game intention was to add extra variation and variety to the player. A missing feature that there was an intention for the game to have is a single-player mode. Within the free play area, the design was to have additional models available for the players to interact with, and these models being kNN and logistic regression, to match up with the content in the learning zone. A feature that did get implemented, but to the desired consistency, was the level of options available to the user when interacting with the model's parameters and data options. While specific models had this implemented, a consistent level did not get established between all of the models resulting in varying amounts of interactivity.

An area where the application can get expanded is to add the feature of extra players. Although the application currently supports two players, the ability to add three or four players would add additional functionality and competition within the game area. An area that could get expanded is to have a settings option. To allow players with colour blindness change the colour scheme, as this will make sure that they can access as much of the application as possible. An additional area that could get expanded is the ability for the quiz questions to appear random and the answer get displayed in random order. Therefore, making sure the players not just to learn the locations of the answers but force them to read the options and think about the answers.

[Any other suggestions?]

6.2 Reflection on the evaluation

What did users find good/bad etc. [Need results]

6.3 Reflection of the Project Development

Overall we found that the project did follow the planned schedule pretty well. However, there were several bumps along the way. The first bump in the road happened due to an initial incorrect choice of GUI framework early on. We initially intended to use Pygame as the GUI framework, as the application's main intention was to create a game. After committing time, as planned in the project Gantt chart, to learning the intended GUI library better, after we had no previous experience of Pygame before. It got realised that, although the library would be good at creating game screens and menus, it was unable to develop or support some essential libraries

or features that are required to make all the aspects of the application. It then got decided to use the GUI library that got used on the implementation of the application. However, this led to less time getting allocated to learning the library. Therefore it led to a lot of aspects of the library getting learnt along the way. Which, we believe, is shown within some elements with the application. Resulting in the application not being as smooth with its layout and presentation as intended. For example, the screen layout has not got optimised for the changing screen sizes, even though resizing gets supported within the code. Just not as elegantly as we would have hoped.

Although prototypes would get created effectively using either Jupyter Notebooks, for ML models and Matplotlib visualisations, to help with figuring out the initial logic required to make the models. However, when trying to convert these prototypes, at first into the GUI using Matplotlib backend handlers to help implement the visualisation graphs in the GUI, a lot of issues first arose. These issues were down to the GUI, even though it could support Matplotlib, it could not support the library in the same way that we have prior experience of using it. Therefore, it forced us into learning the required backend library and rewriting how some aspects of the code worked, for the graphs to get displayed to the user. However, once this got first implemented, the other models were more comfortable to develop afterwards.

Another decision that changed from what got initially planned to what happened when the application was getting implemented. This change was it was intended for the application to have a model implemented within the Freeplay area, and then straight away into the game area. However, it then got decided to implement as many models within the Freeplay area first, when after several models had got created, then add them to the game area. This decision got made because we thought it would be a better decision to have a complete section of the application, like the learning zone if we had run out of time due to unforeseen circumstance, then to have two areas be half done. Additionally, it got also decided because a lot of the functionality required for the free play area would become the foundation of the main game section.

Although some initial intentions and ideas were intended only to get implemented within the application if there was enough time available, one key feature that was hoped for but ultimately did not get implemented was the full-on gamification techniques. These would have been within the Awards Zone. This feature always intended to get added after all the other critical aspects of the application. However, due to developing of the GUI taking longer to do than initially planned, it had a knock-on effect and didn't leave much time for the feature to get added. Although aspects of gamification did get implemented within other areas of the

application, having a real awards area we believe would have added even more motivation for players to return.

A huge unforeseen risk that occurred was the pandemic we are finding ourself in today, Covid-19. Not only did this impact on being able to conduct a user study in the intended way planned, but it also has had massive unplanned knock-on effects. For example, with lockdowns being enforced by the government and then moving restricts being put in place. These have resulted in everyday activities, not being the same, which has also had an immense impact on energy levels and focus, due to lack of active activities happening and social activities getting cancelled.

6.4 Future Work

Future work for this application is that online functionality could get included and implemented. Allowing players to be able to face off against each other online, allowing the game element to be accessible to all, without having to have someone with you.

Another area where the application could get adapted in the future is to have the quiz questions get stored in a cloud database, to allow quiz questions to be remotely updated. Therefore every time the player takes a quiz, they will be updated continuously without any updates or downloads required. Not only would this allow for fresh new content to keep the players interested, but it will also allow for when the content of the learning zone's webpages gets an update, or new models added, for the questions within the quiz to get updated as well.

As most people use tablets and mobile devices, future work that could get done to the application is to create a web GUI to the game and host the entire application online. Through making the application web-based, the application could also then be made natively on mobile devices like iOS and Android and published through their respective app stores. Though, this will require the players always to have a constant internet connection. It will, however, allow for the players to be able to access the application, from anywhere at any time, in a manner more suited to them. Which, ultimately is the most important thing, the players are interacting with the application learning about the different ML models.

Potential future work to the application is to allow players to upload their own generated datasets to the application within the free play area. This additional feature would be expanding off the serious game gamification notion of genuinely letting the users be able to interact with the data and get a vibe of the data, all within the sandbox of the application.

6.5 Summary and closing comments

Bibliography

- [1] Things Tech, “Which programming language to start with as a beginner,” 2020, [Online; accessed August 10th, 2020]. [Online]. Available: <https://thingsteck.wordpress.com/>
- [2] Quora, “What are the top 5 misconceptions surrounding artificial intelligence and machine learning?” Retrieved May 10, 2020 from: <https://www.quora.com/What-are-the-top-5-misconceptions-surrounding-Artificial-Intelligence-and-Machine-Learning>.
- [3] MathWorks, “Introducing machine learning.”
- [4] L. Buitinck, G. Louppe, M. Blondel, F. Pedregosa, A. Mueller, O. Grisel, V. Niculae, P. Prettenhofer, A. Gramfort, J. Grobler, R. Layton, J. VanderPlas, A. Joly, B. Holt, and G. Varoquaux, “API design for machine learning software: experiences from the scikit-learn project,” in *ECML PKDD Workshop: Languages for Data Mining and Machine Learning*, 2013, pp. 108–122.
- [5] M. Abadi, A. Agarwal, P. Barham, E. Brevdo, Z. Chen, C. Citro, G. S. Corrado, A. Davis, J. Dean, M. Devin, S. Ghemawat, I. Goodfellow, A. Harp, G. Irving, M. Isard, Y. Jia, R. Jozefowicz, L. Kaiser, M. Kudlur, J. Levenberg, D. Mané, R. Monga, S. Moore, D. Murray, C. Olah, M. Schuster, J. Shlens, B. Steiner, I. Sutskever, K. Talwar, P. Tucker, V. Vanhoucke, V. Vasudevan, F. Viégas, O. Vinyals, P. Warden, M. Wattenberg, M. Wicke, Y. Yu, and X. Zheng, “TensorFlow: Large-scale machine learning on heterogeneous systems,” 2015, software available from [tensorflow.org](https://www.tensorflow.org). [Online]. Available: <https://www.tensorflow.org/>
- [6] S. Walz, in *The Gameful World: Approaches, Issues, Applications*. MIT Press, 2015.
- [7] Growth Engineering. (2019) The history of gamification: From the very beginning to right now. [Online]. Available: <https://www.growthengineering.co.uk/history-of-gamification/>

- [8] Wikipedia. (2020) Gamification. [Online]. Available: <https://en.wikipedia.org/wiki/Gamification>
- [9] J. McGonigal. (2010) Gaming can make a better world. [Online]. Available: https://www.ted.com/talks/jane_mcgonigal_gaming_can_make_a_better_world?language=en#t-1184578
- [10] Gamification: Using Game-Design Elements in Non-Gaming Contexts. (2011) CHI. [Online]. Available: <http://chi2011.org/communities/games/index.html>
- [11] Wikipedia. (2020) Data aggregation. [Online]. Available: https://en.wikipedia.org/wiki/Data_aggregation
- [12] R. Swatman. (2016) Pokémon go catches five new world records. [Online]. Available: <https://www.guinnessworldrecords.com/news/2016/8/pokemon-go-catches-five-world-records-439327>
- [13] R. Silverman, “Latest game theory: Mixing work and play — companies adopt gaming techniques to motivate employees.” Wallstreet Journal, 2011.
- [14] M. Herger. (2012) Gamification and law or how to stay out of prison despite gamification. [Online]. Available: <https://web.archive.org/web/20120425121358/http://enterprise-gamification.com/index.php/en/blog/4-blog/65-gamification-and-law-or-how-to-stay-out-of-prison-despite-gamification>
- [15] Wikipedia. (2020) Gamification of learning. [Online]. Available: https://en.wikipedia.org/wiki/Gamification_of_learning
- [16] A. Deese. (2020) 5 benefits of gamification. [Online]. Available: <https://ssec.si.edu/stemvisions-blog/5-benefits-gamification>
- [17] H. Deese. (2012) Using gamification to aid in adolescent development in the classroom: Cognitive and physical processes can enhance growth. [Online]. Available: <http://www.ashleydeese.com/2012/09/26/using-gamification-to-aid-in-adolescent-development-in-the-classroom-cognitive-and-physical-processes-can-enhance-growth>
- [18] A. Blum-Dimaya, S. A. Reeve, K. F. Reeve, and H. Hoch, “Teaching children with autism to play a video game using activity schedules and game-embedded simultaneous video

- modeling,” in *Education and Treatment of Children*. West Virginia University Press, 2010, pp. 351–370.
- [19] M. Doyle. (2014) Learning with simcity: Valuable lessons kids can learn playing mayor. [Online]. Available: <https://www.brightips.com/learning-simcity-valuable-lessons-kids-learn-playing-mayor/>
- [20] Wikipedia. (2020) Serious game. [Online]. Available: https://en.wikipedia.org/wiki/Serious_game
- [21] M. Baaden, O. Delalande, N. Ferey, S. Pasquali, J. Waldispühl, and A. Taly, “Ten simple rules to create a serious game, illustrated with examples from structural biology.” Public Library of Science, 2018.
- [22] R. Follett and V. Strezov, “An analysis of citizen science based research: usage and publication patterns,” *PloS one*, vol. 10, no. 11, p. e0143687, 2015.
- [23] L. Mazzanti, S. Doutreligne, C. Gageat, P. Derreumaux, A. Taly, M. Baaden, and S. Pasquali, “What can human-guided simulations bring to rna folding?” *Biophysical journal*, vol. 113, no. 2, pp. 302–312, 2017.
- [24] A. Géron, *Hands-On Machine Learning with Scikit-Learn, Keras, and TensorFlow: Concepts, Tools, and Techniques to Build Intelligent Systems*. O’Reilly Media, 2019.
- [25] Sci-Kit Learn. (2020) Linear models. [Online]. Available: https://scikit-learn.org/stable/modules/linear_model.html#ordinary-least-squares
- [26] ——. (2020) Support vector machines. [Online]. Available: <https://scikit-learn.org/stable/modules/svm.html>
- [27] Apple Inc. (2020) Swift. [Online]. Available: <https://developer.apple.com/documentation/swift>
- [28] M. Potuck. (2020) Apple hits 1.5 billion active devices with 80iphones and ipads running ios 13. [Online]. Available: <https://9to5mac.com/2020/01/28/apple-hits-1-5-billion-active-devices-with-80-of-recent-iphones-and-ipads-running-ios-13/>
- [29] K. Finley. (2020) Python is more popular than ever. [Online]. Available: <https://www.wired.com/story/python-language-more-popular-than-ever/>

- [30] B. Popper. (2020) The 2020 developer survey results are here! [Online]. Available: <https://stackoverflow.blog/2020/05/27/2020-stack-overflow-developer-survey-results/>
- [31] A. Goel. (2020) Best programming language to learn in 2020 (for job and future). [Online]. Available: <https://hackr.io/blog/best-programming-languages-to-learn-2020-jobs-future>
- [32] Stack Overflow. (2013) Python vs cpython. [Online]. Available: <https://stackoverflow.com/questions/17130975/python-vs-cpython>
- [33] Python Software Foundation. (2020) What is python? executive summary. [Online]. Available: <https://www.python.org/doc/essays/blurb/>
- [34] Riverbank Computing. (2020) What is pyqt? [Online]. Available: <https://riverbankcomputing.com/software/pyqt/intro>
- [35] Python Software Foundation. (2020) Comparing python to other languages. [Online]. Available: <https://www.python.org/doc/essays/comparisons/>
- [36] The R Foundation. (2020) What is r? [Online]. Available: <https://www.r-project.org/about.html>
- [37] Guru 99. (2020) R vs python: What's the difference? [Online]. Available: <https://www.guru99.com/r-vs-python.html#:~:text=New%20libraries%20or%20tools%20are,general%20approach%20to%20data%20science.&text=Python%20is%20a%20general%2Dpurpose,and%20encompasses%20their%20specific%20language.>
- [38] G. D. Maayan. (2020) The iot rundown for 2020: Stats, risks, and solutions. [Online]. Available: <https://securitytoday.com/Articles/2020/01/13/The-IoT-Rundown-for-2020.aspx?Page=1>
- [39] Statista. (2020) Internet of things (iot) connected devices installed base worldwide from 2015 to 2025. [Online]. Available: <https://www.statista.com/statistics/471264/iot-number-of-connected-devices-worldwide/>
- [40] World Wide Web Foundation. (2020) History of the web. [Online]. Available: <https://webfoundation.org/about/vision/history-of-the-web/>
- [41] T. DeGroat. (2019) The history of javascript: Everything you need to know. [Online]. Available: <https://www.springboard.com/blog/history-of-javascript/>

- [42] Pygame. (2020) About. [Online]. Available: <https://www.pygame.org/wiki/about>
- [43] A. Sharma. (2020) Introduction to gui with tkinter in python. [Online]. Available: https://www.datacamp.com/community/tutorials/gui-tkinter-python?utm_source=adwords_ppc&utm_campaignid=898687156&utm_adgroupid=48947256715&utm_device=c&utm_keyword=&utm_matchtype=b&utm_network=g&utm_adposition=&utm_creative=229765585186&utm_targetid=aud-299261629574:dsa-429603003980&utm_loc_interest_ms=&utm_loc_physical_ms=1007460&gclid=Cj0KCQjwsuP5BRCoARIsAPtX_wGxaCEuqKDvDDyVASqiCw2zIKYwN2Duo3DObWGcfwQAjH3oxWK5WfoaAhafEALw_wcB
- [44] Python Software Foundation. (2020) Tkinter. [Online]. Available: <https://wiki.python.org/moin/TkInter>
- [45] PyCharm. (2020) Get started. [Online]. Available: <https://www.jetbrains.com/help/pycharm/quick-start-guide.html>
- [46] Microsoft. (2020) Why did we build visual studio code? [Online]. Available: <https://code.visualstudio.com/docs/editor/whyvscode>
- [47] CloudApp. (2020) A guide to atom text editor. [Online]. Available: <https://www.getcloudapp.com/blog/how-to-use-atom-text-editor>

Appendix A

Implementation of a Relevant Algorithm

```
1 #include <stdio.h>
2
3 int main(int argc, char *argv[]) {
4     printf("Hello world.\n");
5     return 0;
6 }
```

Listing A.1: An implementation of an important algorithm from our work.

Appendix B

Supplementary Data

The results of large ablative studies can often take up a lot of space, even with neat visualization and formatting. Consider putting full results in an appendix chapter and showing excerpts of interesting results in your chapters with detailed analysis. You can use labels and references to refer the reader here for the full data.