

La superGlobal \$\_SERVER donne accès a differente information du server

```
<html>

<head>

</head>

<body>
  <?php
    var_dump($_SERVER);
  >
</body>

</html>
```

```
array(32) { ["UNIQUE_ID"]=> string(27) "W0dNGvL4K9lM6C6jcN-fHwAAAAG" ["HTTP_HOST"]=> string(9)
"localhost" ["HTTP_CONNECTION"]=> string(10) "keep-alive" ["HTTP_UPGRADE_INSECURE_REQUESTS"]=>
string(1) "1" ["HTTP_USER_AGENT"]=> string(120) "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_13_3)
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/67.0.3396.99 Safari/537.36" ["HTTP_ACCEPT"]=> string(85)
"text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/svg+xml/*;q=0.8"
["HTTP_ACCEPT_ENCODING"]=> string(19) "gzip, deflate, br" ["HTTP_ACCEPT_LANGUAGE"]=> string(27) "fr-FR,fr;q=0.9,en-US;q=0.7,en;q=0.6"
["PATH"]=> string(32) "/usr/bin:/bin:/usr/sbin:/sbin" ["DYLD_LIBRARY_PATH"]=> string(104) "/Applications/XAMPP/xamppfiles/lib:/usr/lib" ["SERVER_SIGNATURE"]=> string(163) "Apache/2.4.33 (Ubuntu) PHP/5.6.36 mod_perl/2.0.8-dev Perl/v5.16.3"
["SERVER_NAME"]=> string(10) "localhost" ["SERVER_ADDR"]=> string(15) "127.0.0.1" ["SERVER_PORT"]=> string(3) "80"
["REMOTE_ADDR"]=> string(15) "127.0.0.1" ["DOCUMENT_ROOT"]=> string(32) "/Applications/XAMPP/xamppfiles/htdocs"
["REQUEST_SCHEME"]=> string(4) "http" ["CONTEXT_PREFIX"]=> string(0) "" ["CONTEXT_DOCUMENT_ROOT"]=> string(37)
"/Applications/XAMPP/xamppfiles/htdocs" ["SERVER_ADMIN"]=> string(25) "you@example.com" ["SCRIPT_FILENAME"]=> string(37)
"/Applications/XAMPP/xamppfiles/htdocs/index.php" ["GATEWAY_INTERFACE"]=> string(14) "CGI/1.1" ["REQUEST_METHOD"]=> string(6) "GET"
["HTTP_REFERER"]=> string(0) "" ["HTTP_COOKIE"]=> string(0) "" }
```

Exemple d'accès à une propriété de la superGlobal \$SERVER

```
</div>
<h1>Page d'accueil</h1>
<?php
    echo $_SERVER["UNIQUE_ID"];
?>
```

```
</body>
```

[ACCEUIL](#) [PROMOTION](#) [QUI SOMME-NOUS](#)

# Page d'accueil

W0dPu9iHKSZKDy7Aj-bS4AAAAAo