1135. Connecting Cities With Minimum Cost

Medium 237 10 Add to List Share

There are `N` cities numbered from 1 to `N`.

You are given `connections`, where each `connections[i] = [city1, city2, cost]` represents the cost to connect `city1` and `city2` together. (A co
and `city2` is the same as connecting `city2` and `city1`.)

Return the minimum cost so that for every pair of cities, there exists a path of connections (possibly of length 1) that connects those two cities together.
used. If the task is impossible, return -1.

Example 1:




```
Input: N = 3, connections = [[1,2,5],[1,3,6],[2,3,1]]
Output: 6
Explanation:
Choosing any 2 edges will connect all cities so we choose the minimum 2.
```

Example 2:




```
Input: N = 4, connections = [[1,2,3],[3,4,4]]
Output: -1
Explanation:
There is no way to connect all cities even if all edges are used.
```

Note:

1. `1 <= N <= 10000`
2. `1 <= connections.length <= 10000`
3. `1 <= connections[i][0], connections[i][1] <= N`
4. `0 <= connections[i][2] <= 10^5`
5. `connections[i][0] != connections[i][1]`

Accepted 11,995 Submissions 21,164

Seen this question in a real interview before? Yes No

Contributor

Companies

Related Topics

Show Hint 1

Show Hint 2

Show Hint 3

Show Hint 4