

441. Arranging Coins

March 25, 2020 | 70.2K views

PreviousNext

★★★★★

Average Rating: 4.69 (171 votes)

You have a total of n coins that you want to form in a staircase shape, where every k -th row must have exactly k coins.

Given n , find the total number of **full** staircase rows that can be formed.

n is a non-negative integer and fits within the range of a 32-bit signed integer.

Example 1:

n = 5

The coins can form the following rows:

Because the 3rd row is incomplete, we return 2.

Example 2:

n = 8

The coins can form the following rows:

Because the 4th row is incomplete, we return 3.

Solution

Approach 1: Binary Search

This question is easy in a sense that one could run an **exhaustive iteration** to obtain the result. That could work, except that it would run out of time when the input becomes too large. So let us take a step back to look at the problem, before rushing to the implementation.

Assume that the answer is k , i.e. we've managed to complete k rows of coins. These completed rows contain in total $1 + 2 + \dots + k = \frac{k(k+1)}{2}$ coins.

We could now reformulate the problem as follows:

Find the maximum k such that $\frac{k(k+1)}{2} \leq N$.

The problem seems to be one of those **search** problems. And instead of naive iteration, one could resort to another more efficient algorithm called **binary search**, as we can find in another similar problem called [search insert position](#).

Implementation

JavaPython

Copy

```
1 class Solution:
2     def arrangeCoins(self, n: int) -> int:
3         left, right = 0, n
4         while left <= right:
5             k = (right + left) // 2
6             curr = k * (k + 1) // 2
7             if curr == n:
8                 return k
9             if n < curr:
10                right = k - 1
11            else:
12                left = k + 1
13        return right
```

Complexity Analysis

- Time complexity : $\mathcal{O}(\log N)$.
- Space complexity : $\mathcal{O}(1)$.

Approach 2: Math

If we look deeper into the formula of the problem, we could actually solve it with the help of mathematics, without using any iteration.

As a reminder, the constraint of the problem can be expressed as follows:

$$k(k+1) \leq 2N$$

This could be solved by [completing the square](#) technique,

$$\left(k + \frac{1}{2}\right)^2 - \frac{1}{4} \leq 2N$$

that results in the following answer:

$$k = \left\lceil \sqrt{2N + \frac{1}{4}} - \frac{1}{2} \right\rceil$$

Implementation

JavaPython

Copy

```
1 class Solution:
2     def arrangeCoins(self, n: int) -> int:
3         return (int)((2 * n + 0.25)**0.5 - 0.5)
```

Complexity Analysis

- Time complexity : $\mathcal{O}(1)$.
- Space complexity : $\mathcal{O}(1)$.

Rate this article: ★★★★★

PreviousNext

Comments: 48

Sort By

Type comment here... (Markdown is supported)

Preview

Post

sreeramb93

★ 163

April 2, 2020 10:07 PM

Why so many down votes on this question?
It is a really good binary search problem.

81 Share Reply

SHOW 8 REPLIES

ashish8950

★ 39

June 10, 2020 11:49 AM

Why the complexity for second solution $\mathcal{O}(1)$, it takes $\mathcal{O}(\log n)$ time to calculate the square root for any number.

39 Share Reply

SHOW 7 REPLIES

Subho_Kundu

★ 26

July 1, 2020 12:47 PM

Second implementation using just math is awesome

16 Share Reply

gbgb1gbgb

★ 19

July 1, 2020 5:04 PM

```
public:
    int arrangeCoins(int n) {
        int count = 0;
        int i = 1;
```

Read More

19 Share Reply

SHOW 1 REPLY

theNoobCoder

★ 4

July 2, 2020 12:00 AM

First problem on leetcode. Took 4 mins for first submission. But Time out. Then Took 4 hours to figure out only that I was thinking too high ;D. Finally accepted.

4 Share Reply

SHOW 2 REPLIES

rkothakapu

★ 6

July 1, 2020 6:26 PM

Java - Using Recursion

```
class Solution {
    public int arrangeCoins(int n) {
        return arrangeCoins(n, 1);
```

Read More

6 Share Reply

SHOW 1 REPLY

bhruti1234bhruti

★ 8

July 1, 2020 6:11 PM

Always thought that binary search will only be used if there is "sorted " word involved in the question. Amazed to see the way binary search is used to solve this problem. very good question.

6 Share Reply

SHOW 1 REPLY

filipre

★ 14

July 1, 2020 1:32 PM

How does the second solution make sure, that we don't run into numeric issues? What happens, if for some weird edge case the `sqrt()` function returns something like `x.499999999997` ?

3 Share Reply

SHOW 5 REPLIES

Ardh1999

★ 13

July 1, 2020 1:54 PM

$(\sqrt{1+(8*n)}-1)/2$
as simple is the sol^n

4 Share Reply

SHOW 3 REPLIES

tivan

★ 8

July 1, 2020 8:28 PM

Interesting alternative solutions.

2 Share Reply

<

1

2

3

4

5

>