557. Reverse Words in a String III 🗗

April 8, 2017 | 73.6K views

Average Rating: 3.02 (46 votes)

Given a string, you need to reverse the order of characters in each word within a sentence while still preserving whitespace and initial word order.

Example 1:

```
Input: "Let's take LeetCode contest"
Output: "s'tel ekat edoCteeL tsetnoc"
```

Note: In the string, each word is separated by single space and there will not be any extra space in the string.

Solution

Approach #1 Simple Solution[Accepted]

The first method is really simple. We simply split up the given string based on whitespaces and put the individual words in an array of strings. Then, we reverse each individual string and concatenate the result. We return the result after removing the additional whitespaces at the end.

```
Java

public class Solution {
    public String reverseWords(String s) {
        String words[] = s.split(" ");
        StringBuilder res=new StringBuilder();
        for (String word: words)
            res.append(new StringBuffer(word).reverse().toString() + " ");
        return res.toString().trim();
    }
}

Complexity Analysis
```

Time constant

- Time complexity : O(n). where n is the length of the string.
- Space complexity : O(n). res of size n is used.

Algorithm

Approach #2 Without using pre-defined split and reverse function [Accepted]

Algorithm

(space) and returns the array of words. Reverse function returns the string after reversing the characters.

We can create our own split and reverse function. Split function splits the string based on the delimiter " "

```
Сору
Java
 1 public class Solution {
       public String reverseWords(String s) {
           String words[] = split(s);
           StringBuilder res=new StringBuilder();
            for (String word: words)
               res.append(reverse(word) + " ");
7
           return res.toString().trim();
9
       public String[] split(String s) {
10
           ArrayList < String > words = new ArrayList < > ();
           StringBuilder word = new StringBuilder();
11
12
           for (int i = 0; i < s.length(); i++) {
13
              if (s.charAt(i) == ' ') {
                   words.add(word.toString());
14
15
                   word = new StringBuilder();
16
17
                   word.append( s.charAt(i));
18
19
           words.add(word.toString());
           return words.toArray(new String[words.size()]);
20
21
22
       public String reverse(String s) {
23
        StringBuilder res=new StringBuilder();
24
          for (int i = 0; i < s.length(); i++)
25
             res.insert(0,s.charAt(i));
           return res.toString();
27
      }
28 }
```

• Time complexity : O(n). where n is the length of the string.

Complexity Analysis

- Space complexity : O(n). res of size n is used.

Algorithm

Approach #3 Using StringBuilder and reverse method [Accepted]

Instead of using split method, we can use temporary string word to store the word. We simply append the

characters to the word until '' character is not found. On getting '' we append the reverse of the word to the resultant string result. Also after completion of loop , we still have to append the reverse of the word(last word) to the result string.

Below code is inspired by @ApolloX.

Сору

Java
1 public class Solution {

```
public String reverseWords(String input) {
            final StringBuilder result = new StringBuilder();
            final StringBuilder word = new StringBuilder();
            for (int i = 0; i < input.length(); i++) {
                if (input.charAt(i) != ' ') {
                    word.append(input.charAt(i));
                    result.append(word.reverse());
  9
  10
                     result.append(" ");
 11
                     word.setLength(0);
  12
 13
 14
             result.append(word.reverse());
 15
             return result.toString();
  16
 17 }
Complexity Analysis
```

Time complexity: O(n). Single loop upto n is there, where n is the length of the string. Space complexity: O(n). result and word size will grow upto n.

- Space complexity : O(n). result and word size will grow upto n.
- Rate this article: * * * * *

```
O Previous
                                                                                                      Next 0
Comments: 63
                                                                                                     Sort By ▼
              Type comment here... (Markdown is supported)
              Preview
                                                                                                       Post
             abhi25 ★ 66 ② August 13, 2018 11:43 AM
             One line python code
              return " ".join([i[::-1] for i in s.split()])
             55 A V Et Share A Reply
             SHOW 3 REPLIES
             dumbleeter # 269 @ May 3, 2019 2:52 AM
             Isn't using built-in functions defeating the entire purpose of this exercise?
             Will it be acceptable in an interview setting?
             24 A V Et Share A Reply
             SHOW 3 REPLIES
             vadimtukaev * 119 ② June 17, 2018 10:22 PM
             All of these solutions are over-engineered and inefficient, IMHO. Here is a universal algorithm that can
             be transferred to any language, including those, that using immutable strings (with a few obvious
             alterations).
                                                       Read More
             17 A V & Share Share Reply
             SHOW 2 REPLIES
             cwoodrow * 10 @ July 2, 2018 7:02 PM
              Not optimal but quick Java solution :D:
              class Solution {
                  public String reverseWords(String s) {
                                                       Read More
              10 ∧ ∨ 🗈 Share 🦘 Reply
             DhruvinPatel * 11 @ January 24, 2019 7:19 AM
              Simple Python Solution: faster than 100% solutions
              def reverseWords(self, s):
                   :type s: str
                                                       Read More
             8 A V & Share A Reply
             frozenwater # 49 @ January 10, 2019 1:49 PM
             Sharing two pointers approach (Java) with O(n) time, O(n) space.
              class Solution {
                  public String reverseWords(String s) {
                       int i = 0, i = 0:
                                                       Read More
             3 A V Et Share Share
             Summon528 *3 @ February 10, 2019 5:05 PM
              Python one liner, faster than 100.00%
                   def reverseWords(self, s: 'str') -> 'str':
                       return " ".join(i[::-1] for i in s.split())
```

3 A V Et Share Share

sadykov 🛊 0 🗿 January 20, 2019 8:37 PM

(1234567)

SHOW 1 REPLY