

[< Back](#)
[my simple MS SQL Solution](#)

[📄](#)
[🔔](#)
[⚠️](#)


[TinyDad](#)
★ 35
December 20, 2019 3:54 AM
1.6K VIEWS

35

```
SELECT min(log_id) as start_id, max(log_id) as end_id
FROM
(SELECT log_id, ROW_NUMBER() OVER(ORDER BY log_id) as num
FROM Logs) a
GROUP BY log_id - num
```

inspiration from <https://leetcode.com/problems/report-contiguous-dates/discuss/407117/MSSQL-100-Simple-solution>

Comments: 9

[Best](#)
[Most Votes](#)
[Newest to Oldest](#)
[Oldest to Newest](#)

Type comment here... (Markdown is supported)

Post


[chase99](#)
★ 4
January 28, 2020 6:13 AM

the difference of (log_id - num) will change whenever a log_id is skipped. The rows with same difference (log_id - num), should be a continuous series. Then we just need to find the min, and max for that series as start/ end id. It's easier to understand if you draft it out with column log_in & row_number.

▲ 1 ▼
[Show 1 reply](#)
[👤 Reply](#)


[joyelee2019](#)
★ 10
January 3, 2020 9:25 AM

Brilliant GROUP BY, thanks for your sharing.

▲ 1 ▼
[👤 Reply](#)


[lz1800](#)
★ 0
April 10, 2020 11:26 AM

This should also work on MYSQL. Leetcode should definitely update their judging system

▲ 0 ▼
[👤 Reply](#)


[Kevinknight197](#)
★ 0
February 20, 2020 2:09 AM

Brilliant!!!