

## 03

January 23, 2024

```
[1]: %pylab inline
import torch
import sys
sys.path.append('.')
sys.path.append('../..')
from data import load
train_data, train_label = load.get_dogs_and_cats_data(resize=(32,32),
    ↪n_images=10)
device = torch.device('cuda') if torch.cuda.is_available() else torch.
    ↪device('cpu')
print('device = ', device)
```

%pylab is deprecated, use %matplotlib inline and import the required libraries.  
Populating the interactive namespace from numpy and matplotlib  
device = cuda

```
[2]: class ConvNet(torch.nn.Module):
    def __init__(self, layers=[], n_input_channels=3, kernel_size=3):
        super().__init__()
        L = []
        c = n_input_channels
        for l in layers:
            L.append(torch.nn.Conv2d(c, l, kernel_size))
            L.append(torch.nn.ReLU())
            c = l
        L.append(torch.nn.Conv2d(c, 1, kernel_size=1))
        self.layers = torch.nn.Sequential(*L)

    def forward(self, x):
        return self.layers(x).mean(dim=[1,2,3])

net = ConvNet([32,64])
```

```
[3]: print( train_data[:1].shape )
print( net(train_data[:1]).shape )
```

```
torch.Size([1, 3, 32, 32])
torch.Size([1])
```

```
[4]: net2 = ConvNet([32, 64, 128])
      print( net2(train_data[:1]).shape )
```

torch.Size([1])

```
[5]: %load_ext tensorboard
      import tempfile
      log_dir = tempfile.mkdtemp()
      %tensorboard --logdir {log_dir} --reload_interval 1
```

<IPython.core.display.HTML object>

```
[6]: from util import train
      train.train(net2, batch_size=128, resize=(32,32), log_dir=log_dir,
      ↪device=device, n_epochs=100)
```

WARNING:root:loading dataset

WARNING:root:loading done

0%| | 0/100 [00:00<?, ?it/s]

```
[ ]:
```