

---

---

---

**TAG ID: 17806**

H.P. 1.26      K.W. N/A      AMP: 2      RPM: 1140      VOLTS: 220      PHASE: 3      HZ: 60      SR# \_\_\_\_\_

<b>A. BEFORE RECONDITION</b>		DATE: 2021-02-09																																												
A1.	WINDING RESISTANCE TEST (OHMS)		INSULATION RESISTANCE TEST (MEGA-OHMS)				TESTING W/O LOAD (AMPS.)	TESTING WITH LOAD (AMPS.)																																						
			TIME	T-G @500V	T-G @1000V	T-G @2000V																																								
	T1-T2/Pri		30 SECONDS				L1	L1																																						
	T1-T3/Sec		1 MINUTE				L2	L2																																						
	T2-T3		10 MINUTES				L3	L3																																						
	REMARKS		Polarization Index				L4	L4																																						
			WINDING TEMP.		C°	ABM. TEMP.	C°	L5	L5																																					
			REMARKS:					L6	L6																																					
A2.	HIGH POTENTIAL TEST (MICRO-AMPS)				TESTING W/O LOAD (AMPS.)																																									
		T-G@500V	T-G@1000V	T-G@1500V	T-G@2000V		Pri. (Volts)	Sec. (Volts)	Pri. (Amps)	Sec (Amps.)																																				
	T1					L1																																								
	T2					L2																																								
	T3					L3																																								
	REMARKS	FAILED																																												
A3. SURGE TEST/COMPARISON TEST:					VOLTAGE INPUT: 1500																																									
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p style="text-align: center;">PHASE</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 33%;">1-2</td> <td style="width: 33%;">1-3</td> <td style="width: 33%;">2-3</td> </tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> </table> <p>TURN TO TURN SHORT COIL TO COIL SHORT REVERSED COIL CONNECTION OPEN COIL CONNECTION ARCING BETWEEN THE WINDINGS OR PHASES</p> </div> <div style="width: 45%;"> <p style="text-align: center;">PHASE</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 33%;">1-2</td> <td style="width: 33%;">1-3</td> <td style="width: 33%;">2-3</td> </tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> </table> <p>COMPLETE GROUND PARTIAL GROUND PHASE TO PHASE SHORT GOOD WINDING</p> </div> </div> <p>For Rewind                      For Recon</p>						1-2	1-3	2-3																1-2	1-3	2-3																				
						1-2	1-3	2-3																																						
1-2	1-3	2-3																																												
RECOMMENDATION:																																														
NOTE:																																														
B. AFTER RECONDITION/REWINDING					DATE: 2021-02-09																																									
B1.	WINDING RESISTANCE TEST (OHMS)		INSULATION RESISTANCE TEST (MEGA-OHMS)				TESTING W/O LOAD (AMPS.)	TESTING WITH LOAD (AMPS.)																																						
			TIME	T-G @500V	T-G @1000V	T-G @2000V																																								
	T1-T2/Pri		30 SECONDS				L1 -	L1 -																																						
	T1-T3/Sec		1 MINUTE				L2 -	L2 -																																						
	T2-T3		10 MINUTES				L3 -	L3 -																																						
	REMARKS		Polarization Index				L4	L4																																						
			WINDING TEMP.		C°	ABM. TEMP.	C°	L5	L5																																					
			REMARKS:					L6	L6																																					
B2.	HIGH POTENTIAL TEST (MICRO-AMPS)				TESTING W/O LOAD (AMPS.)																																									
		T-G@500V	T-G@1000V	T-G@1500V	T-G@2000V		Pri. (Volts)	Sec. (Volts)	Pri. (Amps)	Sec (Amps.)																																				
	T1					L1																																								
	T2					L2																																								
	T3					L3																																								
	REMARKS																																													
B3. SURGE TEST/COMPARISON TEST:					VOLTAGE INPUT: 1500																																									
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p style="text-align: center;">PHASE</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 33%;">1-2</td> <td style="width: 33%;">1-3</td> <td style="width: 33%;">2-3</td> </tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> </table> <p>TURN TO TURN SHORT COIL TO COIL SHORT REVERSED COIL CONNECTION OPEN COIL CONNECTION ARCING BETWEEN THE WINDINGS OR PHASES</p> </div> <div style="width: 45%;"> <p style="text-align: center;">PHASE</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 33%;">1-2</td> <td style="width: 33%;">1-3</td> <td style="width: 33%;">2-3</td> </tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td></tr> </table> <p>COMPLETE GROUND PARTIAL GROUND PHASE TO PHASE SHORT GOOD WINDING</p> </div> </div> <p>Remarks:</p>						1-2	1-3	2-3																1-2	1-3	2-3																				
						1-2	1-3	2-3																																						
1-2	1-3	2-3																																												
RECOMMENDATION:																																														
NOTE:																																														
TESTED BY: _____					RECEIVED BY: _____					CERTIFIED BY: _____																																				
Walter A. Oplencia																																														