

1 Summary

The purpose of this project was to determine a model for classifying the presence of a Higgs boson from background noise given a set of detector measurements. The data used for modeling was taken from the UCI Machine Learning Depository [2], which were originally produced in Reference [1]. The large data set was sampled and analyzed, and features were separated into 2 sets. 10 machine learning models were fit to the 2 feature sets and their corresponding principle components. The model with the best results was a 3-layer fully-connected deep learning model. All models including the final model produced poor results, due predominantly to the well-mixed nature of the given data.

2 Methods

All data processing, analysis, and modeling was performed with the R statistical coding language, with the following code packages:

`ggplot2` for plotting functions
`Gally` for correlation plotting functions
`ROCR` for ROC plotting
`gridExtra` for plot arrangement
`dplyr` for data manipulation functions
`tidyr` for data wrangling functions
`caTools` for AUC calculations
`caret` for machine learning functions
`H2O` for deep neural network functions

All R code will be provided in a separate file, "STAT724_cody_gilbert_exam.R." The code produces output files in the form of "Output.txt" files that contain summary outputs of the models and test results, and "*.pdf" files which contain additional plots. A large number of plots were produced for each model, and plots not related to the final model are not included within this report.

3 Data Sourcing, Screening, and Analysis

3.1 Data Sources

The data used in this calculation were taken from the UCI Machine Learning Depository [2], which were originally produced in Reference [1]. This data contains simulations of particle accelerator detectors, which either have a class of 1 for the presence of the Higgs boson, or 0 for the simulation of background noise [2]. The data originally contained 11,000,000 observations of 28 features: 21 are lower-tier simulated detector signals and 7 are parameters derived from the lower-tier features. To reduce the scale of the project, the original data set was sampled to obtain 50,000 observations on which the classification models will be run. The final neural network model used 200,000 observations.

3.2 Data Analysis

The sampled data is contained in the "HIGGSSample.csv" file. The `Class` feature was reformulated to be "H" (Higgs) for class 1, and "B" (Background) for class 0. Appendix A shows R `summary`

output and exploratory plots created from the sampled data. The summary output indicates no missing data, and a balanced number of classes.

The data was separated into 2 parts: a set of derived data features and a set of lower-tier features. The total set of features were not analyzed together, as the derived features are by definition collinear with the lower-tier features. Both data sets will be analyzed with the same set of models, and the features with the highest predictive capability will be used.

The correlation plot of a 1000 observation sample of the derived data is shown in Figure 3. The density plots show that the data are right-skewed with a number of features showing significant collinearity. The densities of the separate classes are shown on the right side of Figure 4. These densities show that the background cases and the Higgs cases are well mixed within the bulk of the data.

A correlation plot of the lower-tier features was not produced, as it would require a $21 \times 21 = 441$ facet plot which would be difficult to interpret. Manual assessment of the correlation matrix indicated little correlation between features. A density plot with separate classes was produced from the 1000 observation sample, and is shown on the left side of Figure 4. The density plots again show that the classes are well mixed, with distributions that are mostly symmetric.

The derived data show significant collinearity, which can be eliminated by modeling on the principle components (PCs). Although the lower-tier data does not show a significant level of collinearity, the PCs were calculated for completeness. The PCs were calculated using the R `prcomp` function. Biplots and class-separated density plots for the PCs of the derived data are shown in Figure 5, and for the lower-tier data are shown in Figure 6. The plots do not indicate a significant improvement in data separation, however the PCs will be modeled to determine if they improve accuracy.

4 Modeling

The following classification models were considered:

1. Logistic
2. Linear Discriminant Analysis (LDA)
3. Quadratic Discriminant Analysis (QDA)
4. K-Nearest Neighbor (KNN)
5. Random Forest
6. Boosted Forest
7. Support Vector Machines (SVMs)
8. Neural Network

The `caret` package was used to select a 75% training set and a 25% test set. A common set of 5 cross-validation folds were used across models to allow for model comparison.

4.1 Variable Selection

For each data set, derived features, lower-tier features, and the PCs for both, variable selection was performed using the `caret` package `rfe` function for Recursive Feature Elimination (RFE). This algorithm used a random forest model to perform RFE sub-setting, which identified as important all 7 derived features and their PCs, and 16 of the lower-tier features and their PCs. Because all 7 PCs of the derived data were indicated as important, the number was reduced to 5 in order to account for over 95% of the total variance.

It is assumed that the RFE algorithm using a random forest model can be generalized to account for all considered models, as the algorithm will provide a first-order indication of variable importance. This assumption can be validated by re-running the RFE algorithm with each model used, however this was not performed in this project due to computing time limitations. The highest accuracy models perform cross-validation to tune regularization parameters, therefore the likelihood of overfitting is minimal.

4.2 Logistic Model

A logistic model was prepared for all 4 feature sets with the features identified in Section 4.1. Model fitting and prediction was performed using the `caret` package's cross-validation wrapper to the `glm` function.

Features were assumed to have only a simple linear formulation with no transformations or interactions. This simple model is justified because the class-separated density plots in Figure 4 show that the data is well-mixed and a logistic model is not expected to perform with a high-level of accuracy. It is expected that this model will form a baseline level of prediction on which subsequent models can be compared. Table 1 shows the best results for each data feature set.

Table 1: Logistic Model Validation Results

Feature Set	AUC	Sensitivity	Specificity
Derived	0.648	0.438	0.792
Lower-Tier	0.582	0.396	0.702
Derived PCs	0.566	0.349	0.826
Lower-Tier PCs	0.583	0.394	0.703

4.3 LDA Model

An LDA model was prepared for all 4 feature sets with the features identified in Section 4.1. Model fitting and prediction was performed using the `caret` package's cross-validation wrapper to the `lda` function. Table 2 shows the best results for each data feature set.

Table 2: LDA Model Validation Results

Feature Set	AUC	Sensitivity	Specificity
Derived	0.647	0.417	0.808
Lower-Tier	0.582	0.395	0.703
Derived PCs	0.567	0.336	0.836
Lower-Tier PCs	0.583	0.393	0.704

4.4 QDA Model

A QDA model was prepared for all 4 feature sets with the features identified in Section 4.1. Model fitting and prediction was performed using the `caret` package's cross-validation wrapper to the `qda` function. Table 3 shows the best results for each data feature set.

Table 3: QDA Model Validation Results

Feature Set	AUC	Sensitivity	Specificity
Derived	0.693	0.358	0.856
Lower-Tier	0.631	0.449	0.724
Derived PCs	0.647	0.309	0.857
Lower-Tier PCs	0.631	0.446	0.727

4.5 KNN Model

A KNN classification model was prepared for all 4 feature sets with the features identified in Section 4.1. Model fitting and prediction was performed using the `caret` package's cross-validation wrapper to the `knn` function. The `caret` package performed 5-fold cross validation to tune the `k` parameter over values of 1, 5, 10, 20, 50, and 100. Table 4 shows the best results for each data feature set.

Table 4: KNN Model Validation Results

Feature Set	AUC	Sensitivity	Specificity	k
Derived	0.746	0.600	0.741	50
Lower-Tier	0.598	0.333	0.789	50
Derived PCs	0.709	0.531	0.758	100
Lower-Tier PCs	0.635	0.386	0.783	50

4.6 Random Forest Model

A random forest classification model was prepared for all 4 feature sets with the features identified in Section 4.1. Model fitting and prediction was performed using the `caret` package's cross-validation wrapper to the `ranger` function. The Gini index was used to determine node purity. The `caret` package performed 5-fold cross validation to tune the following parameters:

`mtry` (bootstrapped parameters): 2, \sqrt{p} , p , where p are the features
`min.node.size`: 10, 20, 50, 100

Table 5 shows the best results for each data feature set.

Table 5: Random Forest Model Validation Results

Feature Set	AUC	Sensitivity	Specificity	mtry	min.node.size
Derived	0.762	0.649	0.725	3	50
Lower-Tier	0.658	0.509	0.704	4	10
Derived PCs	0.708	0.575	0.719	3	100
Lower-Tier PCs	0.664	0.497	0.724	2	10

4.7 Boosted Tree Model

A boosted tree classification model was prepared for all 4 feature sets with the features identified in Section 4.1. Model fitting and prediction was performed using the `caret` package's cross-validation wrapper to the `gbm` function. The `caret` package performed 5-fold cross validation to tune the following parameters:

`n.tree` (number of trees): 10, 50, 100, 500, 700
`shrinkage`: 0, 0.01, 0.1
`n.minobsinnode` (minimum obs. in node): 10, 20
`interaction.depth`: 1, 5

Table 6 shows the best results for each data feature set.

Table 6: Boosted Model Validation Results							
Feature Set	AUC	Sensitivity	Specificity	n.trees	int.depth	shrinkage	m.obs
Derived	0.760	0.646	0.725	700	5	0.01	20
Lower-Tier	0.639	0.438	0.736	700	5	0.01	20
Derived PCs	0.696	0.526	0.746	100	5	0.1	20
Lower-Tier PCs	0.642	0.521	0.680	500	5	0.1	20

4.8 Support Vector Machine Models

Three SVM models discussed in class were considered: linear kernel, polynomial kernel, and radial kernel. Due to computing time restrictions, the polynomial kernel could not be used to model the final data sets. Based on the well-mixed nature of the data and the results of the Logistic, LDA, and QDA models, the polynomial kernel SVM model is not expected to provide dramatically improved results.

4.8.1 Linear Kernel

An SVM model with a linear kernel was prepared for all 4 feature sets with the features identified in Section 4.1. Model fitting and prediction was performed using the `caret` package's cross-validation wrapper to the `svmLinear` function. The `caret` package performed 5-fold cross validation to tune the cost parameter over values 10, 50, 75, and 100. Table 7 shows the best results for each data feature set.

Table 7: SVM Linear Model Validation Results				
Feature Set	AUC	Sensitivity	Specificity	Cost
Derived	0.647	0.425	0.801	50
Lower-Tier	0.580	0.359	0.734	10
Derived PCs	0.563	0.337	0.834	50
Lower-Tier PCs	0.581	0.356	0.735	100

4.8.2 Radial Kernel

An SVM model with a radial kernel was prepared for all 4 feature sets with the features identified in Section 4.1. Model fitting and prediction was performed using the `caret` package's cross-validation wrapper to the `svmRadial` function. The `caret` package performed 5-fold cross validation to tune the following parameters:

`c` (cost): 1, 10, 50, 100
`sigma`: 0.001, 0.01, 1, 5, 10

Table 8 shows the best results for each data feature set.

Table 8: SVM Linear Model Validation Results

Feature Set	AUC	Sensitivity	Specificity	Cost	Sigma
Derived	0.748	0.644	0.718	1	1
Lower-Tier	0.653	0.471	0.736	100	0.01
Derived PCs	0.705	0.593	0.707	1	1
Lower-Tier PCs	0.654	0.466	0.744	100	0.01

4.9 Neural Network Models

4.9.1 Shallow Network

A single hidden layer, fully-connected neural network classification model was prepared for all 4 feature sets with the features identified in Section 4.1. Model fitting and prediction was performed using the `caret` package's cross-validation wrapper to the `nnet` function. The `caret` package performed 5-fold cross validation to tune the following parameters:

`size` (hidden layer nodes): 10, 50, 100
`decay` (regularization parameter): 0, 0.1, 1

Table 9 shows the best results for each data feature set.

Table 9: Shallow Neural Network Model Validation Results

Feature Set	AUC	Sensitivity	Specificity	Size	decay
Derived	0.757	0.636	0.735	50	0.1
Lower-Tier	0.639	0.526	0.670	50	1
Derived PCs	0.714	0.599	0.705	10	0.1
Lower-Tier PCs	0.650	0.546	0.668	50	1

4.9.2 Deep Network

A deep, fully-connected neural network classification model was prepared with the Derived feature set. The Derived feature set was used because it performed the best of the feature sets from the above models, and computing deep neural network models for all the sets would require an unacceptable amount of computation time. Model fitting and prediction was performed using the `H2O` package. Because the `H2O` can fit a model faster than `caret` package, the sample size was increased

from 50,000 to 200,000. A separate training and test set were sampled using the `h2o.splitFrame` function. The `H2O h2o.grid` function used a random search with 5-fold cross validation to tune the following hyperparameters:

```
hidden[1] (hidden layers): 1, 2, 3
hidden[2] (hidden layer nodes): 10, 25, 50, 100, 200
input_dropout_ratio: 0, 0.5
rate: 0.01, 0.02
```

The grid tuning used a sample of 50,000 of the training observations to speed computation. After tuning, a model was fit using the entire training set with the best parameters determined from the `h2o.grid` models. This model used 3 layers of 50 nodes, a dropout ratio of 0, and a learning rate of 0.02. All other model parameters used the default options for the `h2o.deeplearning` model. This model produced a 5-fold cross validation AUC of 0.785, and an accuracy of 0.707. The model test AUC was 0.780, test accuracy was 0.704, and the model produced the following test confusion matrix:

	Test Higgs Data	
Predicted	B	H
B	10798	12780
H	3149	23282

An ROC plot of the test data is shown in Figure 1.

5 Conclusion

A graphical overview of the model AUCs is shown in Figure 2. The model with the best cross validation AUC and accuracy was the Deep Neural Network (Section 4.9.2) model assembled with the `H2O h2o.deeplearning` function. The final test AUC was 0.780, the final test accuracy was 0.704. All of the models ultimately performed rather poorly, with the worse models being the linear decision boundary models that performed only slightly better than the null model. The well-mixed nature of the data lead to an improvement in accuracy for non-linear models, but ultimately the data is difficult to separate.



Figure 1: Deep Neural Network Model Test ROC Curve




Figure 2: Final 5-fold training AUC per Model. Note that the Deep Neural Network model was only run with the Derived Feature set, with a larger data sample.

References

- [1] Baldi, P. Sadowski, P., Whiteson, D. Searching for Exotic Particles in High-Energy Physics with Deep Learning (2014). <https://arxiv.org/pdf/1402.4735.pdf> Irvine, CA: University of California, School of Information and Computer Science.
- [2] Dua, D. and Karra Taniskidou, E. (2014). UCI Machine Learning Repository, <http://archive.ics.uci.edu/ml/datasets/HIGGS>. Irvine, CA: University of California, School of Information and Computer Science.

A Appendix: Higgs Data Summaries

The first feature column contains the Class feature, "B" for Background noise and "H" for a Higgs particle. The following 21 features are detector simulations, and the final 7 are values derived from the detector outputs.

Class	lepton.pt	lepton.eta	lepton.phi		
B:23435	Min. :0.2747	Min. :-2.434976	Min. :-1.7425083		
H:26565	1st Qu.:0.5929	1st Qu.: -0.745140	1st Qu.: -0.8719308		
	Median :0.8554	Median :-0.009794	Median : 0.0054103		
	Mean :0.9912	Mean :-0.006811	Mean :-0.0007317		
	3rd Qu.:1.2346	3rd Qu.: 0.732370	3rd Qu.: 0.8732134		
	Max. :7.0003	Max. : 2.431946	Max. : 1.7432359		
missing.energy.magnitude	missing.energy.phi	jet.1.pt	jet.1.eta		
Min. :0.003158	Min. :-1.743944	Min. :0.1400	Min. :-2.968735		
1st Qu.:0.572091	1st Qu.: -0.881750	1st Qu.:0.6773	1st Qu.: -0.696157		
Median :0.888489	Median :-0.013527	Median :0.8932	Median :-0.002006		
Mean :0.993825	Mean :-0.008596	Mean :0.9876	Mean :-0.006254		
3rd Qu.:1.291927	3rd Qu.: 0.863734	3rd Qu.:1.1700	3rd Qu.: 0.687194		
Max. :6.582300	Max. : 1.743102	Max. :7.0647	Max. : 2.969674		
jet.1.phi	jet.1.b.tag	jet.2.pt	jet.2.eta		
Min. :-1.741237	Min. :0.0000	Min. :0.1890	Min. :-2.913089		
1st Qu.: -0.869759	1st Qu.:0.0000	1st Qu.:0.6586	1st Qu.: -0.694472		
Median :-0.011307	Median :1.0865	Median :0.8895	Median : 0.002003		
Mean :-0.002803	Mean :0.9955	Mean :0.9917	Mean : 0.001438		
3rd Qu.: 0.869421	3rd Qu.:2.1731	3rd Qu.:1.2000	3rd Qu.: 0.695564		
Max. : 1.741454	Max. :2.1731	Max. :8.2802	Max. : 2.912238		
jet.2.phi	jet.2.b.tag	jet.3.pt	jet.3.eta		
Min. :-1.7423717	Min. :0.000	Min. :0.2636	Min. :-2.729663		
1st Qu.: -0.8657405	1st Qu.:0.000	1st Qu.:0.6549	1st Qu.: -0.697078		
Median :-0.0002033	Median :1.107	Median :0.8978	Median : 0.001993		
Mean : 0.0007803	Mean :1.006	Mean :0.9928	Mean : 0.002306		
3rd Qu.: 0.8698727	3rd Qu.:2.215	3rd Qu.:1.2213	3rd Qu.: 0.697423		
Max. : 1.7431748	Max. :2.215	Max. :8.5099	Max. : 2.730009		
jet.3.phi	jet.3.b.tag	jet.4.pt	jet.4.eta		
Min. :-1.742069	Min. :0.000	Min. :0.3654	Min. :-2.497265		
1st Qu.: -0.861842	1st Qu.:0.000	1st Qu.:0.6173	1st Qu.: -0.721686		
Median : 0.003789	Median :0.000	Median :0.8721	Median :-0.007956		
Mean : 0.003523	Mean :1.006	Mean :0.9872	Mean :-0.005375		
3rd Qu.: 0.876942	3rd Qu.:2.548	3rd Qu.:1.2214	3rd Qu.: 0.714102		
Max. : 1.742884	Max. :2.548	Max. :7.5120	Max. : 2.498009		
jet.4.phi	jet.4.b.tag	m_jj	m_jjj	m_lv	
Min. :-1.742691	Min. :0.0000	Min. : 0.1255	Min. :0.3420	Min. :0.2668	
1st Qu.: -0.878138	1st Qu.:0.0000	1st Qu.: 0.7907	1st Qu.:0.8461	1st Qu.:0.9858	
Median :-0.005259	Median :0.0000	Median : 0.8949	Median :0.9501	Median :0.9897	
Mean :-0.003756	Mean :0.9869	Mean : 1.0319	Mean :1.0221	Mean :1.0500	
3rd Qu.: 0.863975	3rd Qu.:3.1020	3rd Qu.: 1.0254	3rd Qu.:1.0825	3rd Qu.:1.0196	
Max. : 1.743372	Max. :3.1020	Max. :16.6016	Max. :8.9401	Max. :3.9318	

m_jlv	m_bb	m_wbb	m_wbbb
Min. :0.3199	Min. : 0.06639	Min. :0.3034	Min. :0.3509
1st Qu.:0.7681	1st Qu.: 0.67453	1st Qu.:0.8199	1st Qu.:0.7696
Median :0.9175	Median : 0.87469	Median :0.9471	Median :0.8709
Mean :1.0112	Mean : 0.97412	Mean :1.0320	Mean :0.9588
3rd Qu.:1.1417	3rd Qu.: 1.14119	3rd Qu.:1.1372	3rd Qu.:1.0584
Max. :7.4426	Max. :11.99418	Max. :6.4013	Max. :4.8353

The 7 derived features are **m_jj**, **m_jjj**, **m_lv**, **m_jlv**, **m_bb**, **m_wbb**, and **m_wbbb**, and the remaining features are the lower-tier features.




Figure 3: Derived Features Correlation plot. Note that this is a plot of a 1,000 observation sample.




Figure 4: Density plots of Lower and Derived Features. Note that this is a plot of a 1,000 observation sample. The plotting windows of the Derived features were adjusted to show the distribution of the majority of data.




Figure 5: Biplot and Density plots of the Derived Features. Note that this is a plot of a 1,000 observation sample.




Figure 6: Biplot and Density plots of the Lower Features. Note that this is a plot of a 1,000 observation sample.