

Cody Eichelberger

Lab 7

11/02/2014

Part One:

1. The current spreadsheet could not translate directly to a database. The table data is not atomic. In order for a relational model to work, there cannot be groups of data within one cell. There is also a lack of a primary key because they repeat multiple times. There needs to be a way to uniquely identify a particular software installation

2.

PackID	TagNum	InstallDate	SoftwareCost
AC01	32808	09-13-1995	754.95
DB32	32808	12-03-1995	380.00
DB32	37691	06-15-1995	380.00
DB33	57772	05-27-1995	412.77
WP08	32808	01-12-1996	185.00
WP08	37691	06-15-1995	227.50
WP08	57222	05-27-1995	170.24
WP09	59836	10-30-1995	35.00
WP09	77740	05-27-1995	35.00

3. Based on the current table design, there is no definitive primary key because the entries of PackID and TagNum repeat multiple times and alone, neither is sufficient to uniquely identify a row. Therefore, assuming there are no reinstallations a Candidate Key of (PackID, TagNum) will do.

Part Two:

4.

PackID	Software Name	TagNum	Computer Model	InstallDate	SoftwareCost
AC01	Solitare	32808	Apple	09-13-1995	754.95
DB32	Adobe	32808	Apple	12-03-1995	380.00
DB32	Adobe	37691	Lenovo	06-15-1995	380.00
DB33	Office	57772	HP	05-27-1995	412.77
WP08	McAfee	32808	Apple	01-12-1996	185.00
WP08	McAfee	37691	Lenovo	06-15-1995	227.50
WP08	McAfee	57222	HP	05-27-1995	170.24
WP09	VPN	59836	Acer	10-30-1995	35.00
WP09	VPN	77740	Dell	05-27-1995	35.00

5.

Functional Dependencies	
PackID → Software Name	
TagNum → Computer Model	
PackID → Software Cost	
Software Name → PackID	
PackID, TagNum, InstallDate → SoftwareCost	

6. A candidate key such as (PackID, TagNum) could be used to uniquely identify an entry assuming the software was only installed once in a machine history, but an issue arises because the software cost is. Software cost is then NOT dependent upon the software package, nor is it dependent upon what combination of machine and software it may be.

7.

tblSoftware	
PackID	Software Name
AC01	Solitare
DB32	Adobe
DB33	Office
WP08	McAfee
WP09	VPN

tblComputer	
TagNum	Model
32808	Apple
37691	Lenovo
57772	HP
59836	Acer
77740	Dell

tblInstallationCost			
PackID	TagNum	InstallDate	SoftwareCost
AC01	32808	09-13-1995	754.95
DB32	32808	12-03-1995	380.00
DB32	37691	06-15-1995	380.00
DB33	57772	05-27-1995	412.77
WP08	32808	01-12-1996	185.00
WP08	37691	06-15-1995	227.50
WP08	57222	05-27-1995	170.24
WP09	59836	10-30-1995	35.00
WP09	77740	05-27-1995	35.00

tblInstallations					
PackID	Software Name	TagNum	Model	InstallDate	SoftwareCost
AC01	Solitaire	32808	Apple	09-13-1995	754.95
DB32	Adobe	32808	Apple	12-03-1995	380.00
DB32	Adobe	37691	Lenovo	06-15-1995	380.00
DB33	Office	57772	HP	05-27-1995	412.77
WP08	McAfee	32808	Apple	01-12-1996	185.00
WP08	McAfee	37691	Lenovo	06-15-1995	227.50
WP08	McAfee	57222	HP	05-27-1995	170.24
WP09	VPN	59836	Acer	10-30-1995	35.00
WP09	VPN	77740	Dell	05-27-1995	35.00

Primary Keys

Software Computer Installation Cost Installations
 PackID TagNum (PackID, TagNum, InstallDate) (PackID, TagNum)

8.

Functional Dependencies

Software
 PackID → Software Name
 Software Name → PackID

Computers
 TagNum → Computer Model

Installations
 PackID, TagNum → InstallDate
 PackID, TagNum, InstallDate → SoftwareCost

9. All of the tables are comprised of attributes that depend on the Primary Key. There are no longer any transitive functional dependencies.

10.

