

1. How to use DATA API via OAuth2 - technical part	2
1.1 Get country identifiers	3
1.2 Search a company (identification of a company in the database)	3
1.2.1 Search company by company info	3
1.2.2 Search company by one of the externalId	5
1.2.3 Search company by companyId	8
1.3. Request a company identification	10
1.3.1 Request the identification	10
1.3.2 Request all identifications	13
1.4. Ordering a product.....	13
1.4.1 Ordering a product for an identified company:.....	13
1.4.2 Ordering a product for a company not identified.....	15
1.5. Checking order status.....	16
1.6. Retrieving the data.....	17
1.7 Request Monitoring.....	18
1.8 Retrieving content of the report / product ordered via monitoring order	20
1.8 Retrieving monitoring notifications.....	21
2. Use cases	21
2.1 Ordering multiple products for same company	21

1. How to use DATA API via OAuth2 - technical part

The main functional flows are represented in <https://coface.github.io/v2.html#process>.

After the proper authentication, always the customer needs to:

- start with Searching and identifying a company,
- check the products availability,
- order a product,
- **check the status of the order** and
- Retrieve the data.

All functional calls below can be found in the Postman collection uploaded under <https://coface.github.io/v2.html#documentation>.

Remark!! In the sample calls which follow, the variable `{{dataAPIBaseUrl}}` = <https://icon-api-test.coface.com/dataapi-v1>

Prerequisite!! In order to perform the following calls, you should already have an user connected via AWS Dev portal. Please check this https://coface.github.io/utilities/DataAPI_UserConfiguration_SwaggerTesting.pdf, in case you do not have yet a connected and authorized user.

1.1 Get country identifiers

- Allows to obtain details of identifiers in specific countries which can be used for unique company identification (check which identifier is legal per country)
- Request can be done by specifying country ISO Code and in return customer get list of identifiers used in specific country

Request: `GET {{dataAPIBaseUrl}}/companies/repositories?countryCode=PL`

Response:

GET `{{dataAPIBaseUrl}}/companies/repositories?countryCode=PL`

Params • Authorization Headers (9) Body Pre-request Script Tests Settings

Query Params

Key	Value	Description
<input checked="" type="checkbox"/> countryCode	PL	
Key	Value	Description

body Cookies Headers (16) Test Results Status: 200

Pretty Raw Preview Visualize JSON ⌵ ⌵

```
1 {
2   {
3     "slug": "giid",
4     "isLegal": false
5   },
6   {
7     "slug": "icon",
8     "isLegal": false
9   },
10  {
11    "slug": "easy",
12    "isLegal": false
13  },
14  {
15    "slug": "registration-number",
16    "isLegal": true,
17    "isMandatoryCompanyCreation": true,
18    "repositoryFormat": "VAT number or statistical number or registration number must be entered, there are no rules for registration number"
19  },
20  {
21    "slug": "statistic-number",
22    "isLegal": true,
23    "isMandatoryCompanyCreation": true,
24    "repositoryFormat": "VAT number or statistical number or registration number must be entered, Statistical number has to be exactly 9 digits long."
25  },
26  {
27    "slug": "vat-number",
28    "isLegal": true,
29    "isMandatoryCompanyCreation": true,
30    "repositoryFormat": "VAT number or statistical number or registration number must be entered, VAT number has to be exactly 10 digits long. All"
31  }
32 }
```

1.2 Search a company (identification of a company in the database)

There are several options for searching and identification of a company:

1.2.1 Search company by company info

Allows to perform search by name and countryCode mostly. Search can be performed using **minimum** companyName (or parts of the name) and countryCode:

`GET {{dataAPIBaseUrl}}/companies?companyName=ANTALIS&countryCode=FR` => 28 companies returned

If more information is provided, like postalCode and city, more accurate the search is and company is identified:

GET `{{dataAPIBaseUrl}}/companies?companyName=ANTALIS&city=PARIS&countryCode=FR` => 6 companies returned

GET `{{dataAPIBaseUrl}}/companies?companyName=ANTALIS&postalCode=75019&city=PARIS&countryCode=FR` => 1 result returned. Company is identified.

Error case: If combination companyName + countryCode is not provided, 400 Bad request is returned:

GET `{{dataAPIBaseUrl}}/companies?city=PARIS&countryCode=FR`

Params • Authorization Headers (9) Body Pre-request Script Tests Settings

Query Params

Key	Value	Description
<input type="checkbox"/> companyId	397fb600-414c-3a55-a41a-d66bb6cfb36c	Company identifier
<input type="checkbox"/> companyName	ANTALIS	Company name
<input type="checkbox"/> postalCode	75019	Postal code, ZIP Code
<input checked="" type="checkbox"/> city	PARIS	City
<input checked="" type="checkbox"/> countryCode	FR	Country code (ISO 3166 Alpha-2)

body Cookies Headers (15) Test Results Status: 400 Bad Request Time: 1

Pretty Raw Preview Visualize JSON ⌵ ⌵

```
1  [
2    "statusCode": 400,
3    "url": "/companies",
4    "errorDate": "2023-04-06T00:56:03.450+02:00",
5    "fishtag": "40506abb-c37e-4430-8c01-a5050ed5b024",
6    "messages": [
7      {
8        "code": "missing_or_invalid_param",
9        "docUrl": "https://coface.com/documentation/codes/missing_param",
10       "message": "Missing or invalid parameter: companyName"
11     }
12   ]
13 ]
```

GET `{{dataAPIBaseUrl}}/companies?companyName=ANTALIS&city=PARIS`

Params • Authorization Headers (9) Body Pre-request Script Tests Settings

Query Params

Key	Value	Description
<input type="checkbox"/> companyId	397fb600-414c-3a55-a41a-d66bb6cfb36c	Company identifier
<input checked="" type="checkbox"/> companyName	ANTALIS	Company name
<input type="checkbox"/> postalCode	75019	Postal code, ZIP Code
<input checked="" type="checkbox"/> city	PARIS	City
<input type="checkbox"/> countryCode	FR	Country code (ISO 3166 Alpha-2)

body Cookies Headers (15) Test Results Status: 400 Bad Request Time: 1

Pretty Raw Preview Visualize JSON ⌵ ⌵

```
1  [
2    "statusCode": 400,
3    "url": "/companies",
4    "errorDate": "2023-04-06T00:57:28.149+02:00",
5    "fishtag": "62e559ab-3105-410c-9c9a-6b83e4e19bdd",
6    "messages": [
7      {
8        "code": "missing_or_invalid_param",
9        "docUrl": "https://coface.com/documentation/codes/missing_param",
10       "message": "Missing or invalid parameter: companyId / externalId + countryCode / companyName + countryCode"
11     }
12   ]
13 ]
```

Success case – Returns list of companies found with the given criteria. For each company from the list, the response includes: name, countryCode, address and externalIds.

ExternalIds can be also used further for better identification of the company, checking the availability of the products or for ordering products for that corresponding company.

The screenshot shows a REST client interface with a GET request to the endpoint `{{dataAPIBaseUrl}}/companies?companyName=ANTALIS&city=PARIS&countryCode=FR`. The request parameters are defined in a table:

Key	Value	Description
<input checked="" type="checkbox"/> companyName	ANTALIS	Company name
<input type="checkbox"/> postalCode	75019	Postal code, ZIP Code
<input checked="" type="checkbox"/> city	PARIS	City
<input checked="" type="checkbox"/> countryCode	FR	Country code (ISO 3166 Alpha-2)
<input type="checkbox"/> range	10-25	Pagination Interval ↕
<input type="checkbox"/> externalId	statistic-number%23810684000	

The response status is 200 OK, with a time of 852 ms. The response body is displayed in JSON format:

```
[
  {
    "name": "MGT.COM",
    "countryCode": "FR",
    "address": {
      "address1": "25 Boulevard de Strasbourg",
      "postalCode": "75010",
      "city": "PARIS 10",
      "countryCode": "FR"
    },
    "externalIds": [
      {
        "id": "38353034323030303140706e703d46522f373039",
        "repositorySlug": "giid"
      }
    ]
  },
  {
    "name": "ANTALIS FRANCE",
    "countryCode": "FR",
    "address": {
      "address1": "17 Avenue de la Porte des Lilas",
      "postalCode": "75019",
      "city": "PARIS 19",
      "countryCode": "FR"
    },
    "externalIds": [
      {
        "id": "34313033333037363540706e703d46522f373039",
        "repositorySlug": "giid"
      }
    ]
  },
  {
    "name": "ANTALIS SA",
    "countryCode": "FR",
    "address": {
      "address1": "127 Rue Amelot",
      "postalCode": "75011",

```

1.2.2 Search company by one of the externalId

Allows to search for a specific company by providing combination of countryCode + externalId. ExternalId can be one of the national identifiers or one of internal Coface IDs. It was either returned by previous method (using companyName + countryCode) either was already known (e.g.VAT number). Parameter **externalId** will be used with value `{repositorySlug}#{id}`.

Response returns either 1 unique result or no results.

Identifying company using giid number:

`GET {{dataAPIBaseUrl}}/companies?countryCode=FR&externalId=giid%2334313033333630363940706e703d46522f373039`

GET

{{dataAPIBaseUrl}}/companies?countryCode=FR&externalId=giid%2334313033333630363940706e703d46522f373039

Params

Authorization

Headers (9)

Body

Pre-request Script

Tests

Settings

Query Params

Key	Value	Description
<input checked="" type="checkbox"/> countryCode	FR	Country code (ISO 3166 Alpha-2)
<input checked="" type="checkbox"/> externalId	giid%2334313033333630363940706e703d46522f373039	
Key	Value	Description

ody

Cookies

Headers (17)

Test Results

Status: 200 OK

Time: 1753

Pretty

Raw

Preview

Visualize

JSON

```
1  [
2    {
3      "id": "b75e4b59-12e4-3bc6-8d30-1ac599cce69f",
4      "name": "ANTALIS",
5      "countryCode": "FR",
6      "naceCodes": [
7        {
8          "code": "7010",
9          "label": "Activities of head offices"
10        }
11      ],
12      "legalForm": {
13        "code": "999",
14        "label": "Legal form unknown"
15      },
16      "address": {
17        "address1": "8 Rue de Seine",
18        "postalCode": "92100",
19        "city": "BOULOGNE-BILLANCOURT",
20        "countryCode": "FR"
21      },
22      "emails": [
23        {
24          "value": "info.fr@antalys.com",
25          "main": true
26        }
27      ],
28      "phoneNumbers": [
29        {
30          "value": "0150042100",
31          "countryCode": "FR",
32          "main": true
33        }
34      ],
35      "websites": [
36        {
37          "url": "www.antalys.fr",
38          "main": true
39        }
40      ],
41      "externalIds": [
42        {
43          "id": "00000173905973",
44          "repositorySlug": "easy"
45        },
46        {
47          "id": "2003002119",
48          "repositorySlug": "registration-number"
49        }
50      ]
51    }
52  ]
```

Identifying company using VAT number:


`GET {{dataAPIBaseUrl}}/companies?countryCode=FR&externalId=vat-number%23FR37410336069`


GET `{{dataAPIBaseUrl}}/companies?countryCode=FR&externalId=vat-number%23FR37410336069`

Params Authorization Headers (9) Body Pre-request Script Tests Settings

Query Params

Key	Value	Description
<input checked="" type="checkbox"/> countryCode	FR	Country code (ISO 3166 Alpha-2)
<input checked="" type="checkbox"/> externalId	vat-number#FR37410336069	
Key	Value	Description

body Cookies Headers (17) Test Results  Status: 200 OK Time: 2.04 s

Pretty Raw Preview Visualize JSON 

```
1 {
2   "id": "b75e4b59-12e4-3bc6-8d30-1ac599cce69f",
3   "name": "ANTALIS",
4   "countryCode": "FR",
5   "naceCodes": [
6     {
7       "code": "7010",
8       "label": "Activities of head offices"
9     }
10  ],
11  "legalForm": {
12    "code": "999",
13    "label": "Legal form unknown"
14  },
15  "address": {
16    "address1": "8 Rue de Seine",
17    "postalCode": "92100",
18    "city": "BOULOGNE-BILLANCOURT",
19    "countryCode": "FR"
20  },
21  "emails": [
22    {
23      "value": "info.fr@antalisis.com",
24      "main": true
25    }
26  ],
27  "phoneNumbers": [
28    {
29      "value": "0150042100",
30      "countryCode": "FR",
31      "main": true
32    }
33  ],
34  "websites": [
35    {
36      "url": "www.antalisis.fr",
37  ]
38 }
```

Identifying company using ICON number:

[GET {{dataAPIBaseUrl}}/companies?countryCode=FR&externalId=icon%23138131867](#)

The screenshot shows a REST client interface with a GET request to the endpoint `GET {{dataAPIBaseUrl}}/companies?countryCode=FR&externalId=icon%23138131867`. The query parameters are `countryCode=FR` and `externalId=icon#138131867`. The response is a JSON object representing a company.

```
1 {
2   "id": "b75e4b59-12e4-3bc6-8d30-1ac599cce69f",
3   "name": "ANTALIS",
4   "countryCode": "FR",
5   "nameCodes": [
6     {
7       "code": "7810",
8       "label": "Activities of head offices"
9     }
10  ],
11  "legalForm": {
12    "code": "999",
13    "label": "Legal form unknown"
14  },
15  "address": {
16    "address1": "8 Rue de Seine",
17    "postalCode": "92100",
18    "city": "BOULOGNE-BILLANCOURT",
19    "countryCode": "FR"
20  },
21  "emails": [
22    {
23      "value": "info.fr@antal.fr",
24      "main": true
25    }
26  ],
27  "phoneNumbers": [
28    {
29      "value": "0150042100",
30      "countryCode": "FR",
31      "main": true
32    }
33  ],
34  "websites": [
35    {
36      "url": "www.antal.fr",
37      "main": true
38    }
39  ],
40  "externalIds": [
41    {
42      "id": "00000173985973",
43      "repositorySlug": "easy"
44    },
45    {
46      "id": "2003002119",
47      "repositorySlug": "registration-number"
48    },
49    {
50      "id": "138131867",
51    }
52  ]
53 }
```

1.2.3 Search company by companyId

Allows to identify a company using the internal Coface id. This Id either is known without passing the precedent searches, either is returned when identifying the company as it could be seen in the previous methods.

If companyId parameter is provided, the other fields are ignored:

[GET {{dataAPIBaseUrl}}/companies?companyId=b75e4b59-12e4-3bc6-8d30-1ac599cce69f](#)

GET ▼ `{{dataAPIBaseUrl}}/companies?companyId=b75e4b59-12e4-3bc6-8d30-1ac599cce69f`

Params ● Authorization Headers (9) Body Pre-request Script Tests ● Settings

Query Params

Key	Value	Description
<input checked="" type="checkbox"/> companyId	b75e4b59-12e4-3bc6-8d30-1ac599cce69f	

ody Cookies Headers (17) Test Results 🔍 Status: 200 OK Time: 3.63 s Size: 1.07 K

Pretty Raw Preview Visualize JSON ▼ 🔄

```

1  {
2    "id": "b75e4b59-12e4-3bc6-8d30-1ac599cce69f",
3    "name": "ANTALIS",
4    "countryCode": "FR",
5    "naceCodes": [
6      {
7        "code": "7010",
8        "label": "Activities of head offices"
9      }
10   ],
11   "legalForm": {
12     "code": "999",
13     "label": "Legal form unknown"
14   },
15   "address": {
16     "address1": "8 Rue de Seine",
17     "postalCode": "92100",
18     "city": "BOULOGNE-BILLANCOURT",
19     "countryCode": "FR"
20   },
21   "emails": [
22     {
23       "value": "info.fr@antalys.com",
24       "main": true
25     }
26   ],
27   "phoneNumbers": [
28     {
29       "value": "0160842100",
30       "countryCode": "FR",
31       "main": true
32     }
33   ],
34   "websites": [
35     {
36       "url": "www.antalys.fr",
37       "main": true
38     }
39   ],
40   "externalIds": [
41     {
42       "id": "00000173905973",
43       "repositorySlug": "easy"
44     },
45     {
46       "id": "2003B02119",
47       "repositorySlug": "registration-number"
48     },
49     {
50       "id": "138131867",
51       "repositorySlug": "registration-number"
52     }
53   ]
54 }

```

In all these cases, response should be identical. One company is uniquely identified.

Response contains information about the company requested: internal id inside ICON, name, countryCode, naceCodes, legalForms, address, emails, phoneNumbers, websites and externalIds.

Reaching this point, it means that customer either uniquely identified the company and can go to next step of checking the list of available products and order, or did not succeeded to find company.

1.3. Request a company identification

In case you did not managed to identify wanted company, you have the option to request a company identification by Coface and then to order products.

1.3.1 Request the identification

Endpoint to be used: **POST** `{{dataAPIBaseUrl}}/companies/identifications`

No parameters are required, but inside the request body, some information is required to be provided:

at least one of the externalID needs to be provided OR for some countries where no legal identifiers are needed, it is enough to provide the address.countryCode in combination with: name, address.postalCode and address.city.

In case the provided information is not correct, response will be 400 Bad Request.

Information about which countries and what legal identifiers need to be provided, is provided via endpoint: **GET** `{{dataAPIBaseUrl}}/companies/repositories?countryCode={}`.

For each identifier, there are 2 fields which show if they need to be provided for a company identification and under which format:

```
"isMandatoryCompanyCreation": true,  
"repositoryFormat": "VAT number or statistical number or registration number must be entered, there are no rules for registration number"
```

Error case: no address.countryCode

The screenshot shows a REST client interface with a POST request to `{{dataAPIBaseUrl}}/companies/identifications`. The request body is a JSON object with the following fields: `name` ("Coface SA Georgiana Test"), `address` (an object with `address1`, `address2`, `postalCode`, and `city`), `email` ("john.doe@example.com"), and `phoneNumber` ("1111111111"). The response status is 400 Bad Request. The response body is a JSON object with the following fields: `statusCode` (400), `url` ("/companies/identifications"), `fishTag` ("1a209052-7615-477a-9b59-706c6b6e71fa"), and `messages` (an array containing one message with `code` "missing_or_invalid_param" and `message` "One of the following identification parameters has to be provided: at least one externalId or (name, address.postalCode, address.city and address.countryCode)").

```
POST {{dataAPIBaseUrl}}/companies/identifications  
  
1 {  
2   "name": "Coface SA Georgiana Test",  
3   "address": {  
4     "address1": "API street",  
5     "address2": "Second API Street",  
6     "postalCode": "123",  
7     "city": "Paris"  
8   },  
9   "email": "john.doe@example.com",  
10  "phoneNumber": "1111111111"  
11 }
```

Status: 400 Bad Request Time: 97 ms Size: 957 B Save as Exa

```
1 {  
2   "statusCode": 400,  
3   "url": "/companies/identifications",  
4   "fishTag": "1a209052-7615-477a-9b59-706c6b6e71fa",  
5   "messages": [  
6     {  
7       "code": "missing_or_invalid_param",  
8       "message": "One of the following identification parameters has to be provided: at least one externalId or (name, address.postalCode, address.city and address.countryCode)"  
9     }  
10  ]  
11 }
```

Success case- Request body:


```
{  
  
  "name": "Coface SA",  
}
```

```

"address": {
  "address1": "2 rue de Siam",
  "address2": "Bâtiment B, Escalier C",
  "postalCode": "qui",
  "city": "BREST",
  "countryCode": "FR"
},
"email": "john.doe@example.com",
"phoneNumber": "0102030405",
"externalIds": [
  {
    "id": "123456",
    "repositorySlug": "easy"
  },
  {
    "id": "123456",
    "repositorySlug": "icon"
  }
]
}

```

If based on the information provided, ICON identifies the company inside its database, then the response will provide the searchedCompany info, the matchingCompanies and status:"identified":



If inside ICON there are no companies matching information provided, response will contain: id (which can be used for a future ordering), searchedCompany info (data provided in request), matchingCompanies = empty array and status:"initiated"

POST `{{dataAPIBaseUrl}}/companies/identifications`

arams Authorization Headers (11) **Body** Pre-request Script Tests Settings

none form-data x-www-form-urlencoded raw binary GraphQL JSON

```
1 {
2   "name": "Coface SA Georgiana Test",
3   "address": {
4     "address1": "API street",
5     "address2": "Second API Street",
6     "postalCode": "qui",
7     "city": "Paris",
8     "countryCode": "FR"
9   },
10  "email": "john.doe@example.com",
11  "phoneNumber": "0102030405",
12  "externalIds": [
13    {
14      "id": "123456",
15      "repositorySlug": "easy"
16    },
17    {
18      "id": "123456",
19      "repositorySlug": "easy"
20    }
21  ]
22 }
```

dy Cookies Headers (15) Test Results Status: 201 Created

Pretty Raw Preview Visualize JSON

```
1 {
2   "id": "52a2637b-4a50-4405-b578-8f4fca6a50",
3   "searchedCompany": {
4     "name": "Coface SA Georgiana Test",
5     "address": {
6       "address1": "API street",
7       "address2": "Second API Street",
8       "postalCode": "qui",
9       "city": "Paris",
10      "countryCode": "FR"
11    },
12    "email": "john.doe@example.com",
13    "phoneNumber": "0102030405",
14    "externalIds": [
15      {
16        "id": "123456",
17        "repositorySlug": "easy"
18      },
19      {
20        "id": "123456",
21        "repositorySlug": "easy"
22      }
23    ]
24  },
25   "matchingCompanies": [],
26   "status": "initiated"
27 }
```

The second step that can be done is to order the wanted product for this company, even if it is not yet identified.

See details under [1.4.2 Ordering a product for a company not identified](#)

1.3.2 Request all identifications

All requests to identify companies made on customer where you have the profile/ user are shown under endpoint:

GET `{{dataAPIBaseUrl}}/companies/identifications`

GET `{{dataAPIBaseUrl}}/companies/identifications?range=21-20`

Params Authorization Headers (9) Body Pre-request Script Tests Settings

Query Params

Key	Value	Description
<input checked="" type="checkbox"/> range	21-20	
Key	Value	Description

body Cookies Headers (19) Test Results Status: 206 Partial Content

Pretty Raw Preview Visualize JSON

```
1 [
2   {
3     "id": "ce963cd9-d609-4abc-a73c-89697fa945cc",
4     "searchedCompany": {
5       "name": "BBB888",
6       "address": {
7         "address1": "Ul. Miodawska 6/5",
8         "postalCode": "02-127",
9         "city": "Warszawa"
10      }
11    },
12    "matchingCompanies": [],
13    "status": "in-progress"
14  },
15  {
16    "id": "f9eb6d81-1b9c-4b8a-978d-2189af759a63",
17    "searchedCompany": {
18      "name": "Georgiana Test SA",
19      "address": {
20        "address1": "2 rue de Holiday",
21        "address2": "Bâtiment B, Escalier C",
22        "postalCode": "123",
23        "city": "TestingCity"
24      }
25    }
26  }
27 ]
```

1.4. Ordering a product

The structure of the request depends from the result of searching/identification of company.

1.4.1 Ordering a product for an identified company:

Remarks!!

1. Slugs and product codes


Attention: for DRAGON products (DRA, CO, AO) availability is not immediate. Therefore *processingTimeInstruction* option should have value `immediate_if_available_inquiry_otherwise` or `inquiry` with `investigationSpeedLevel: normal`.

2. Format of reports

API allows to request report in different formats such as JSON, XML, PDF or HTML. For JSON and XML it will require additional mapping on customer side to integrate structured form of data to his own system needs.

- Ordering a product can be made either using the internal companyId returned by the API in one of the previous commands (the ones for identifying the company) OR using one of the externalIds (same, returned by the API when identifying the company)

Ordering via companyId:



```
POST {{dataAPIBaseUrl}}/publications/orders

{
  "companyId": "aa272cd1-c4d1-3c4c-9df8-d99616f5ef21",
  "report": {
    "slug": "full-report",
    "language": "EN",
    "format": [
      "pdf",
      "json"
    ]
  },
  "processingTimeInstruction": "immediate"
}
```

```
{
  "id": "9f27e195-5425-4545-b25c-2bf8723eeade",
  "orderDate": "2023-05-08T01:16:20.171+02:00",
  "expectedDeliveryDate": "in-preparation",
  "status": "in-preparation",
  "publications": [
    {
      "id": "c2e1b632-fb20-49ac-9095-04c1294551bc",
      "status": "in-preparation",
      "expectedDeliveryDate": "in-preparation",
      "reportSlug": "full-report"
    }
  ]
}
```

Ordering via externalId:

POST

{{dataAPIBaseUrl}}/publications/orders

Params

Authorization

Headers (12)

Body

Pre-request Script

Tests

Settings

none

form-data

x-www-form-urlencoded

raw

binary

GraphQL

JSON

```

1 {
2   "externalId": "icon#5416240",
3   "countryCode": "PL",
4   "report": {
5     "slug": "snapshot-report",
6     "language": "EN",
7     "format": [
8       "pdf",
9       "json"
10    ],
11    "processingTimeInstruction": "immediate"
12  }
13 }

```

ody

Cookies

Headers (14)

Test Results

Pretty

Raw

Preview

Visualize

JSON

```

1 {
2   "id": "63de55be-18ab-425b-aadd-be39a4dda72c",
3   "orderDate": "2023-05-08T01:58:58.811+02:00",
4   "expectedDeliveryDate": "in-preparation",
5   "status": "in-preparation",
6   "publications": [
7     {
8       "id": "204eea7a-0088-4f49-b566-9e9eb41bb039",
9       "status": "in-preparation",
10      "expectedDeliveryDate": "in-preparation",
11      "reportSlug": "snapshot-report"
12    }
13  ]
14 }

```

1.4.2 Ordering a product for a company not identified

Prerequisite: you need to request an Identification of the company on which you need to order (See section **1.3.1 Request the identification**) so that you have the id returned by ICON.

Endpoint to be used:

POST {{dataAPIBaseUrl}}/publications/orders or

POST {{dataAPIBaseUrl}}/monitorings/orders


Request body:

```

{
  "companyIdentificationId": "52a2637b-4a50-4405-b570-8f4fc1aa6a58",
  "report": {
    "slug": "full-report",
    "language": "EN",
    "format": [
      "pdf",
      "json"
    ],
    "processingTimeInstruction": "immediate"
  }
}

```

Response is the same as when ordering for an identified company. From here, all the other steps can be performed: get status of the order and, when ready, get the content of the order.



The screenshot shows a REST client interface. The top section displays a POST request to the endpoint `{{dataAPIBaseUri}}/publications/orders`. The request body is in JSON format and contains the following fields:

```
1 {
2   "companyIdentificationId": "52a2637b-4a58-4405-b578-Sf4fc1aa6a68",
3   "report": {
4     "slug": "full-report",
5     "language": "EN",
6     "format": [
7       "pdf",
8       "json"
9     ],
10    "processingTimeInstruction": "immediate"
11  }
12 }
```

The bottom section shows the response in JSON format, with a status of 201 Created and a time of 1866 ms. The response body is:

```
1 {
2   "id": "9099ec55-9052-4609-8ac2-d934f581abae",
3   "orderDate": "2023-04-06T09:29:12.09+02:00",
4   "expectedDeliveryDate": "in-preparation",
5   "status": "in-preparation",
6   "publications": [
7     {
8       "id": "c9f920d6-6cf1-4921-b000-32a93998f49e",
9       "status": "in-preparation",
10      "expectedDeliveryDate": "in-preparation",
11      "reportSlug": "full-report"
12    }
13  ]
14 }
```

No parameters

Body of the request should contain mandatory information such as: company-id or other identifier, product code, format, language. Products available and their availability are returned previously by calling [GET /company](#) endpoint (mentioned at 4.2.2).

More details and explanation for fields that need to be present in the body, can be found behind each element from swagger, by clicking on Model and after that, on arrow down for each drop down that is available.

Swagger can be found under AWS Dev portal: <https://devportal.coface.com/apis/qves74kqv0/v1>

1.5. Checking order status

After using the POST method, customer gets as response a JSON structure containing:

- one id which allows checking the status of the order (initial status of request is “in-preparation”)
- “publications” section containing all products ordered in same order. All of them have this initial status “in-preparation”

In order to check the status of the whole order, first id value must be used for endpoint [GET /publications/orders?id](#)

GET `{{dataAPIBaseUrl}}/publications/orders?id=63de55be-18ab-425b-aadd-be39a4dda72c`

Params Authorization Headers (10) Body Pre-request Script Tests Settings

Query Params

Key	Value
<input checked="" type="checkbox"/> id	63de55be-18ab-425b-aadd-be39a4dda72c
Key	Value

ody Cookies Headers (16) Test Results

Pretty Raw Preview Visualize JSON ☐

```

1  [
2    {
3      "id": "63de55be-18ab-425b-aadd-be39a4dda72c",
4      "orderDate": "2023-05-08T01:58:58+02:00",
5      "deliveryDate": "2023-05-08T01:59:06+02:00",
6      "status": "ready",
7      "publications": [
8        {
9          "id": "204aea7a-0088-4f49-b566-9e9eb41bb039",
10         "status": "ready",
11         "reportSlug": "snapshot-report"
12       }
13     ]
14   }
15 ]

```

Status of the order will be ready if all publications of the order are ready. If one of the publication is not ready, the status of global order will be still “in-preparation”.

Attention! Only when status of the order / publication will be “ready” you will be able to retrieve the content of the corresponding product ordered (publication)

1.6. Retrieving the data

If order is finished, customer can call method `GET /publications?format={format}&{id}`
 Format and id parameters are mandatory. Format should be the one used when POST call was made and id should be the id returned in “publications” section returned by API on POST method.

GET	▼	{{dataAPIBaseUrl}}/publications?format=json&id=204eea7a-0088-4f49-b566-9e9eb41bb039
Params • Authorization Headers (10) Body Pre-request Script Tests Settings		
Query Params		
	Key	Value
<input type="checkbox"/>	language	EN
<input checked="" type="checkbox"/>	format	json
<input checked="" type="checkbox"/>	id	204eea7a-0088-4f49-b566-9e9eb41bb039
	Key	Value

Body	Cookies	Headers (15)	Test Results
Pretty Raw Preview Visualize JSON ▼			
1	{"icon": {		
2	"version": "1.0.0",		
3	"orderStatus": {		
4	"intercreditOrderNumber": "3400600",		
5	"provider": {		
6	"providerId": "4",		
7	"name": "Coface Poland Credit Management Services Sp. z o.o.",		
8	"senderId": "IC01",		
9	"city": "Warszawa",		
10	}		
11	}		
12	}		

1.7 Request Monitoring

Customer can request monitoring, by **ordering one of the combined products**: *Full Report with Monitoring, Snapshot Report with Monitoring, DRA with Monitoring, @ Credit Opinion with Monitoring, Advanced Opinion with monitoring, Country Risk Assessment with monitoring, and Sector Risk Assessment with monitoring.*

Only identified companies can be monitored.

By default Monitoring should last 12 months.

In order to order a combined product, endpoint **POST** [{{dataAPIBaseUrl}}/monitorings/orders](#) needs to be used, using the slug/product id returned by API when company was identified.

So, if I identified a company and I have the companyID, I am placing the monitoring order:

```
POST {{dataAPIBaseUrl}}/monitorings/orders

{
  "countryCode": "PL",
  "companyId": "8a4aa8e5-ed39-342d-afd4-15a609583db2",
  "startDate": "2023-01-16",
  "report": {
    "slug": "full-report",
    "language": "en",
    "format": [
      "pdf",
      "json"
    ],
    "processingTimeInstruction": "immediate",
    "investigationSpeedLevel": "normal"
  }
}
```

```
{
  "orderDate": "2023-04-21T06:09:11.295+02:00",
  "monitorings": [
    {
      "id": "ec16d6b9-777b-466a-98ad-150929e255df",
      "companyId": "8a4aa8e5-ed39-342d-afd4-15a609583db2",
      "initialDeliveryId": "ec16d6b9-777b-466a-98ad-150929e255df",
      "startDate": "2023-04-21",
      "endDate": "2024-04-21",
      "countryCode": "PL",
      "reportSlug": "full-report",
      "expectedDeliveryDate": "in-preparation",
      "status": "in-preparation"
    }
  ]
}
```

In the response I am getting some information like: Id of the monitoring order, start and end date of the monitoring, status (which is “in-preparation”) , expectedDeliveryDate, companyId, country Code and product for which monitoring was ordered.

Now, I can check the status of this order using endpoint **GET** `{{dataAPIBaseUrl}}/monitorings/:id`

```
GET {{dataAPIBaseUrl}}/monitorings/:id

Query Params
Key Value Descri
Key Value Descri

Path Variables
Key Value Descri
id ec16d6b9-777b-466a-98ad-150929e255df Descri
```

```
{
  "id": "ec16d6b9-777b-466a-98ad-150929e255df",
  "companyId": "8a4aa8e5-ed39-342d-afd4-15a609583db2",
  "externalId": "icon#121538014",
  "initialDeliveryId": "ec16d6b9-777b-466a-98ad-150929e255df",
  "startDate": "2023-04-21",
  "endDate": "2024-04-21",
  "countryCode": "PL",
  "reportSlug": "full-report",
  "status": "monitoring_active"
}
```

If the request is successful (status is “monitoring_active”) then the company starts to be monitored.

1.8 Retrieving content of the report / product ordered via monitoring order

Because a combined product was ordered, we can also retrieve the content of the product ordered.

Using the id returned by the POST monitoring order (see 1.7), we are getting the content of the product using endpoint **GET** `{{dataAPIBaseUrl}}/publications?format={}&id={orderId}`

Where orderId is the id returned the API when posting the monitoring order

Format paramter is mandatory. As we ordered in 2 formats, we can retrieve both of them (reminder: only for CCE companies)

JSON format:

```
ET  {{dataAPIBaseUrl}}/publications?format=json&id=ec16d8b9-777b-466a-98ad-150929e255df

rams  Authorization  Headers (10)  Body  Pre-request Script  Tests  Settings

Query Params
Key      Value      Description
language EN
format   json
id       ec16d8b9-777b-466a-98ad-150929e255df

Cookies  Headers (16)  Test Results  Status: 200 OK  Time: 222 ms  Size: 3.76 KB

Raw  Preview  Visualize  JSON

13  {
14  },
15  "street": "Al. Jerozolimskie",
16  "houseNumber": "142A",
17  "zipCode": "02-305"
18  },
19  "customer": {
20  "customerId": "128846659",
21  "name": "TestBDC",
22  "clientId": "",
23  "city": "Wien",
24  "country": {
25  "value": "AT",
26  "name": "Austria"
27  },
28  "street": "Sigmundgasse",
29  "houseNumber": "11/2A",
30  "zipCode": "1070"
31  },
32  "customerReference": "",
33  "purchaseOrderNumber": "",
34  "language": {
35  "value": "2",
36  "name": "English"
37  },
38  "product": {
```

Pdf format:

```
GET  {{dataAPIBaseUrl}}/publications?format=pdf&id=ec16d8b9-777b-466a-98ad-150929e255df

Params  Authorization  Headers (10)  Body  Pre-request Script  Tests  Settings

Query Params
Key      Value      Description
language EN
format   pdf
id       ec16d8b9-777b-466a-98ad-150929e255df

Cookies  Headers (16)  Test Results  Status: 200 OK  Time: 222 ms

Raw  Preview  Visualize  PDF

Full Report with Monitoring
Generated on: 21st Apr 2022

Company
COMPUTER SERVICE
Principal Address: 2, Piase
ICGN number: 12121214
Reg number: 1212121212121212
Taxp number: 47272820
VAT number: 1121212121212121
Date of Last Major Update: 2019-2020

Summary
Credit Score: 5
Recommended Maximum Credit: EUR 1500
Legal events: 1
Activity status: Active company
Main activity: NACE 6301
Registration date: 01.07.2011
```

1.8 Retrieving monitoring notifications

TBD!

2. Use cases

2.1 Ordering multiple products for same company

You want to order some products for Audi Company in DE

Searching using company name and country code, as this is what you know currently:

The screenshot shows a REST client interface with a GET request to the endpoint `{{dataAPIBaseUrl}}/companies?companyName=Audi&countryCode=DE`. The 'Params' tab is active, displaying a table of query parameters:

Key	Value
<input type="checkbox"/> companyId	397fb600-414c-3a55-a41a-d66bb6cfb36c
<input checked="" type="checkbox"/> companyName	Audi
<input type="checkbox"/> postalCode	75019
<input type="checkbox"/> city	PAris
<input checked="" type="checkbox"/> countryCode	DE
<input type="checkbox"/> range	10-25
<input type="checkbox"/> externalId	statistic-number%23810684000
Key	Value

Below the parameters, the 'Test Results' tab is active, showing the JSON response in 'Pretty' format:

```
1  [
2    {
3      "name": "AUDI Aktiengesellschaft",
4      "countryCode": "DE",
5      "address": {
6        "address1": "Auto-Union-Straße 1",
7        "postalCode": "86067",
8        "city": "Ingolstadt",
9        "countryCode": "DE"
10     },
11     "externalIds": [
12       {
13         "id": "44453030312f302f4445303038343734303640706e703d44452f373032",
14         "repositorySlug": "giid"
15       }
16     ]
17   },
18   {
19     "name": "Audi Keller",
20     "countryCode": "DE",
21     "address": {
22       "address1": "Scheffelstr. 1",
23       "postalCode": "97072",
24       "city": "Würzburg"
```

Call is sent to one of our providers (the one to which your customer profile is routed to). Provider is returning all results that it has with this name and country code. In this case, API returned 200 results. Per page we have 20 results, and pagination is in place (you can see the 206 partial content, and headers values highlighted below):

GET ▼ {{dataAPIBaseUrl}}/companies?companyName=Audi&countryCode=DE

Params ● Authorization Headers (9) Body Pre-request Script Tests Settings

key	value	description
<input type="checkbox"/> companyId	397fb600-414c-3a55-a41a-d66bb6cfb36c	Company identifier
<input checked="" type="checkbox"/> companyName	Audi	Company name
<input type="checkbox"/> postalCode	75019	Postal code, ZIP Code
<input type="checkbox"/> city	PARis	City
<input checked="" type="checkbox"/> countryCode	DE	Country code (ISO 3166 Alp
<input type="checkbox"/> range	10-25	Pagination interval ↕

ody Cookies Headers (18) Test Results ● Status: 206 Partial Content Time: 22.!

key	value
Connection	keep-alive
x-amzn-RequestId	8917b20d-40be-42df-ac14-d4ecc028fcc5
Access-Control-Allow-Origin	*
Content-Encoding	gzip
x-amzn-Remapped-Content-Length	1019
Access-Control-Allow-Headers	Content-Type, api_key, Authorization
Content-Range	0-20/200
X-RateLimit-Remaining	59
x-amz-apigw-id	DxMmVFhtCGYF6CA=
Vary	Accept-Encoding, User-Agent
X-RateLimit-Limit	60
Access-Control-Allow-Methods	GET, POST, DELETE, PUT

You have 200 results. In order to check others which are not in first page, you need to use the range parameter. We are showing max 20 results per page.

GET ▼ {{dataAPIBaseUrl}}/companies?companyName=Audi&countryCode=DE&range=10-25

Params ● Authorization Headers (9) Body Pre-request Script Tests Settings

key	value
<input type="checkbox"/> companyId	397fb600-414c-3a55-a41a-d66bb6cfb36c
<input checked="" type="checkbox"/> companyName	Audi
<input type="checkbox"/> postalCode	75019
<input type="checkbox"/> city	PARis
<input checked="" type="checkbox"/> countryCode	DE
<input checked="" type="checkbox"/> range	10-25

Now, out of 200 companies, you need to identify one of them in order to order some products.

There are 2 ways: either you choose one, and take the giid value and use it as externalId parameter and make the order with it, OR, you make one more call and uniquely identify the company and then you can order using another identifier replied by API (vat number, companyId, icon no)

GET {{dataAPIBaseUri}}/companies?countryCode=DE&externalId=giid%2344453030312f302f4445303038343734303640706e703d44452f373032

Params Authorization Headers (9) Body Pre-request Script Tests Settings

Query Params

Key	Value	Description
countryCode	DE	Country code (ISO 3166 Alpha-2)
externalId	giid%2344453030312f302f4445303038343734303640706e703d44452f373032	

body Cookies Headers (16) Test Results Status: 200 OK Time: 3.17 s Size: 1.07 KB

Pretty Raw Preview Visualize JSON

```
1 {
2   {
3     "id": "ae1463d5-3696-38d8-aac3-065589ccaf68",
4     "name": "AUDI Aktiengesellschaft",
5     "internationalName": "AUDI Aktiengesellschaft",
6     "countryCode": "DE",
7     "naacCodes": [
8       {
9         "code": "2910",
10        "label": "Manufacture of motor vehicles"
11      },
12      {
13        "code": "4831",
14        "label": "Wholesale trade of motor vehicle parts and accessories"
15      }
16    ],
17    "legalForm": [
18      {
19        "code": "325",
20        "label": "Public Limited Company"
21      }
22    ],
23    "address": {
24      "address": "Auto-Union-Straße 1",
25      "postalCode": "85067",
26      "city": "Ingolstadt",
27      "countryCode": "DE"
28    }
29  }
30 }
```

Now, company is saved into ICON, and has more identifiers associated: easy, icon nr, companyId, etc.

In this moment, you need to check and see what the available products are for this company, together with their availability (immediate or on-order):

Check assessments:

GET {{dataAPIBaseUri}}/assessments?countryCode=DE

Params Authorization Headers (10) Body Pre-request Script Tests Settings

Query Params

Key	Value	Description
countryCode	DE	

body Cookies Headers (16) Test Results Status: 200 OK Time: 671 ms Size: 1.36 KB Save as Example

Pretty Raw Preview Visualize JSON

```
1 {
2   {
3     "slug": "credit-opinion",
4     "acronym": "CO",
5     "isMonitorable": true,
6     "descriptions": [
7       {
8         "label": "Credit Opinion",
9         "full": "The @Credit Opinion recommended by Coface is an index up to 180k€ which intends to help you manage your credit decisions on your recurrent small and mid-sized transactions. The index is expressed on 5 ranges of amounts in your local currency and can be monitored.",
10        "language": "en",
11        "short": "CO"
12      }
13    ]
14  },
15  {
16    "slug": "advanced-opinion",
17    "acronym": "AO",
18    "isMonitorable": true,
19    "descriptions": [
20      {
21        "label": "Advanced Opinion",
22        "full": "The Coface Advanced Opinion enables smarter strategic decisions by providing an individual recommended amount to support your credit decisions with customers, prospects, suppliers or partners. This credit report includes a Debtor Risk Assessment and a Country Risk Assessment, giving a 360 view on the risk profile of a company. The Advanced Opinion can be monitored over time, giving you agility to improve your decisions with updated insights.",
23        "language": "en",
24        "short": "AO"
25      }
26    ]
27  }
28 }
```

Check reports:

GET `{{dataAPIBaseUrl}}/companies/reports?companyId=ae1463d5-3696-38d8-aac3-065589ccaf65&countryCode=DE`

Params • Authorization Headers (10) Body Pre-request Script Tests Settings

Query Params

Key	Value
<input checked="" type="checkbox"/> companyId	ae1463d5-3696-38d8-aac3-065589ccaf65
<input checked="" type="checkbox"/> countryCode	DE
<input type="checkbox"/> externalId	easy#00002550018258
<input type="checkbox"/> externalId	vat-number%237711391760
Key	Value

Body Cookies Headers (16) Test Results

Pretty Raw Preview Visualize JSON

```
1 [
2   {
3     "slug": "full-report",
4     "reportName": "Full Report",
5     "availability": "immediate",
6     "isMonitorable": true,
7     "format": [
8       "html",
9       "xml",
10      "pdf",
11      "txt",
12      "json"
13    ]
14  },
15  {
16    "slug": "snapshot-report",
17    "reportName": "Snapshot Report",
18    "availability": "immediate",
19    "isMonitorable": true,
20    "format": [
21      "html",
22      "xml"
23    ]
24  }
25 ]
```

Check financials:

GET `{{dataAPIBaseUrl}}/companies/financials?companyId=ae1463d5-3696-38d8-aac3-065589ccaf65`

Params • Authorization Headers (9) Body Pre-request Script Tests Settings

Query Params

Key	Value
<input checked="" type="checkbox"/> companyId	ae1463d5-3696-38d8-aac3-065589ccaf65
Key	Value

Body Cookies Headers (14) Test Results

Pretty Raw Preview Visualize JSON

```
1 [
2   {
3     "financialSlug": "global-financial",
4     "years": [
5       "2019",
6       "2018",
7       "2017",
8       "2015"
9     ]
10  },
11  {
12    "financialSlug": "local-financial",
13    "years": [
14      "2019",
15      "2018",
16      "2017",
17      "2015"
18    ]
19  }
20 ]
```


Now is time to order:

Ordering 2 assessments: Country Risk Assessment and Sector Risk Assessment:

The screenshot displays a REST client interface. At the top, a POST request is configured for the endpoint `{{dataAPIBaseUrl}}/publications/orders`. The 'Body' tab is selected, showing a JSON payload with a `companyId` placeholder and an array of two assessment objects, each with a `slug` ('country-risk-assessment' and 'sector-risk-assessment'). Below the request, the 'Test Results' tab is active, showing the 'Body' of the response in a 'Pretty' JSON format. The response is a JSON object containing an `id`, `orderDate`, `expectedDeliveryDate`, `status`, and a `publications` array with two items, each having its own `id`, `status`, `expectedDeliveryDate`, and `assessmentSlug`.

```
POST {{dataAPIBaseUrl}}/publications/orders

{
  "companyId": "{{companyId}}",
  "assessments": [
    {
      "slug": "country-risk-assessment"
    },
    {
      "slug": "sector-risk-assessment"
    }
  ]
}

Body Cookies Headers (14) Test Results
Pretty Raw Preview Visualize JSON

{
  "id": "0d7452fc-36f1-4676-abd5-db99ce0bd6f6",
  "orderDate": "2023-04-22T09:45:28.751+02:00",
  "expectedDeliveryDate": "in-preparation",
  "status": "in-preparation",
  "publications": [
    {
      "id": "fb33db98-211f-40ef-8125-2a8f00a00d74",
      "status": "in-preparation",
      "expectedDeliveryDate": "in-preparation",
      "assessmentSlug": "country-risk-assessment"
    },
    {
      "id": "db85bc66-cd6a-4c3f-b0bc-995508343aa9",
      "status": "in-preparation",
      "expectedDeliveryDate": "in-preparation",
      "assessmentSlug": "sector-risk-assessment"
    }
  ]
}
```

As we ordered 2 products in one order, in the response, we will get one global id of the order, first id from json and 2 ids corresponding to each product ordered.

Response of the POST call, will return status “in-preparation” if request is correct on first validations. But even if API returned Ids and “in-preparation” status, it might be that due to some technical or business reasons the order to not be created at all in the backoffice or to be cancelled.

If , for example we order a product with instructions :”immediate” but the product was not available immediate, the call of POST order returns ID and status “in-preparation” in first phase, but when trying to call the status of the order, it can be cancelled, or answer can be an empty array, as order was not at all created in backend.

This is why we have the status call as mandatory step after ordering::

The screenshot shows a REST client interface with a GET request to `{{dataAPIBaseUrl}}/publications/orders?id=0d7452fc-36f1-4676-abd5-db99ce0bd6f6`. The 'Query Params' section shows a single parameter 'id' with the value '0d7452fc-36f1-4676-abd5-db99ce0bd6f6'. The 'Test Results' section shows the response body in JSON format, which is a list containing one object with the following fields: 'id', 'orderDate', 'deliveryDate', 'status', and 'publications'. The 'publications' field is an array of two objects, each representing a publication with its own 'id', 'status', and 'assessmentSlug'.

```
GET {{dataAPIBaseUrl}}/publications/orders?id=0d7452fc-36f1-4676-abd5-db99ce0bd6f6

Params Authorization Headers (10) Body Pre-request Script Tests Settings
Query Params
Key Value
id 0d7452fc-36f1-4676-abd5-db99ce0bd6f6
Key Value

body Cookies Headers (16) Test Results
Pretty Raw Preview Visualize JSON
1 [
2   {
3     "id": "0d7452fc-36f1-4676-abd5-db99ce0bd6f6",
4     "orderDate": "2023-04-22T09:45:28+02:00",
5     "deliveryDate": "2023-04-22T09:45:32+02:00",
6     "status": "ready",
7     "publications": [
8       {
9         "id": "fb33db98-211f-40ef-8125-2a8f00a00d74",
10        "status": "ready",
11        "assessmentSlug": "country-risk-assessment"
12      },
13      {
14        "id": "db85bc66-cd6a-4c3f-b0bc-995508343aa9",
15        "status": "ready",
16        "assessmentSlug": "sector-risk-assessment"
17      }
18    ]
19  }
20 ]
```

As both publications are ready, CRA and SRA, you can get now the content of the products, but with a call per each product.

You can order now also reports.

We saw earlier when we checked the availability of the products that full report and snapshot report are immediate. Let's order them:

Ordering a full report:

The screenshot shows a REST client interface with a POST request to `{{dataAPIBaseUrl}}/publications/orders`. The request body is a JSON object with the following structure:

```
1 {
2   "companyId": "{{companyId}}",
3   "report": {
4     "slug": "full-report",
5     "language": "EN",
6     "format": [
7       "pdf",
8       "json"
9     ],
10    "processingTimeInstruction": "immediate"
11  }
12 }
```

The response is shown in the 'body' tab, displaying a JSON object with the following structure:

```
1 {
2   "id": "2c9a626a-1a69-44a1-95ca-0ae5145134f2",
3   "orderDate": "2023-04-24T06:36:11.716+02:00",
4   "expectedDeliveryDate": "in-preparation",
5   "status": "in-preparation",
6   "publications": [
7     {
8       "id": "5f9b3d7e-f17f-4894-a372-c74b45086d22",
9       "status": "in-preparation",
10      "expectedDeliveryDate": "in-preparation",
11      "reportSlug": "full-report"
12    }
13  ]
14 }
```

Checking the status of the order:

The screenshot shows a REST client interface with a GET request to `{{dataAPIBaseUrl}}/publications/orders?id=2c9a626a-1a69-44a1-95ca-0ae5145134f2`. The request has a query parameter 'id' with the value '2c9a626a-1a69-44a1-95ca-0ae5145134f2'. The response is shown in the 'body' tab, displaying a JSON object with the following structure:

```
1 [
2   {
3     "id": "2c9a626a-1a69-44a1-95ca-0ae5145134f2",
4     "orderDate": "2023-04-24T06:36:11+02:00",
5     "deliveryDate": "2023-04-24T06:36:43+02:00",
6     "status": "ready",
7     "publications": [
8       {
9         "id": "5f9b3d7e-f17f-4894-a372-c74b45086d22",
10        "status": "ready",
11        "reportSlug": "full-report"
12      }
13    ]
14  }
15 ]
```

Getting the content of the full-report in json:

CON Data API / 05 - Search & Retrieve publication / Publication content by its id

Save Send

Params Authorization Headers (10) Body Pre-request Script Tests Settings Cookies

Query Params

Key	Value	Description
language	EN	
format	json	
id	5f9b3d7e-f17f-4894-a372-c74b45006d22	
Key	Value	Description

dy Cookies Headers (15) Test Results Status: 200 OK Time: 206 ms Size: 15.31 KB Save as Example

Pretty Raw Preview Visualize JSON

```
1  {
2    "icon": {
3      "version": "1.0.0",
4      "orderStatus": {
5        "intercreditOrderNumber": "3399821",
6        "provider": {
7          "providerId": "4",
8          "name": "Coface Poland Credit Management Services Sp. z o.o.",
9          "senderId": "1001",
10         "city": "Warszawa",
11         "country": {
12           "value": "PL",
13           "name": "Poland"
14         },
15         "street": "Al. Jerozolimskie",
16         "houseNumber": "142A",
17         "zipCode": "02-385"
18       },
19       "customer": {
20         "customerId": "189523668",
21         "name": "Cosmeta AG - Testaccount",
22         "customerType": "B"
23       }
24     }
25   }
```

Getting the content of the full-report in pdf:

GET {{dataAPIBaseUrl}}/publications?format=pdf&id=5f9b3d7e-f17f-4894-a372-c74b45006d22

Params Authorization Headers (10) Body Pre-request Script Tests Settings

Query Params

Key	Value	Description
language	EN	
format	pdf	
id	5f9b3d7e-f17f-4894-a372-c74b45006d22	
Key	Value	Description

ody Cookies Headers (15) Test Results Status: 200 OK Time: 561 ms Size: 1.1 MB

Full Report

Generated on: 24th Apr 2023

Company

AUDI AKTIENGESELLSCHAFT




Principle Address:
Auto-Union-Straße 1
85057 Ingolstadt
Germany

Telephone: +49-49841890
Fax: +49-49841892324
Email: kundenbetreuung@audi.de
Web: www.audi.de

ICDN number: 12121499
Bany number: 0000022276064
VAT number: DE11113369

Date of Last Major Update:
28/1/2022

Summary

Credit Score  **Coface Adjustment**  **Recommended Maximum Credit** 


Now, let us order a snapshot report:


POST `{{dataAPIBaseUrl}}/publications/orders`

Params Authorization Headers (12) **Body** Pre-request Script Tests Settings

● none ● form-data ● x-www-form-urlencoded ● **raw** ● binary ● GraphQL **JSON** ▾

```
1 {
2   "companyId": "{{companyId}}",
3   "report": {
4     "slug": "snapshot-report",
5     "language": "EN",
6     "format": [
7       "pdf",
8       "json"
9     ],
10    "processingTimeInstruction": "immediate"
11  }
12 }
```

Body Cookies Headers (14) Test Results  Status: 201 Created 1

Pretty Raw Preview Visualize **JSON** ▾ 

```
1 {
2   "id": "5f2ae420-d951-4f56-97d7-1396d7afe8f3",
3   "orderDate": "2023-04-24T06:40:33.019+02:00",
4   "expectedDeliveryDate": "in-preparation",
5   "status": "in-preparation",
6   "publications": [
7     {
8       "id": "09df7d4a-8b87-45d8-a1ef-4bc41b3310f0",
9       "status": "in-preparation",
10      "expectedDeliveryDate": "in-preparation",
11      "reportSlug": "snapshot-report"
12    }
13  ]
14 }
```


Getting order status:


▾ `{{dataAPIBaseUrl}}/publications/orders?id=5f2ae420-d951-4f56-97d7-1396d7afe8f3`

Authorization Headers (10) **Body** Pre-request Script Tests Settings

rams

	Value
/	5f2ae420-d951-4f56-97d7-1396d7afe8f3
/	Value

ookies Headers (16) Test Results 

Raw Preview Visualize **JSON** ▾ 

```
{
  "id": "5f2ae420-d951-4f56-97d7-1396d7afe8f3",
  "orderDate": "2023-04-24T06:40:33+02:00",
  "deliveryDate": "2023-04-24T06:40:37+02:00",
  "status": "ready",
  "publications": [
    {
      "id": "09df7d4a-8b87-45d8-a1ef-4bc41b3310f0",
      "status": "ready",
      "reportSlug": "snapshot-report"
    }
  ]
}
```

Getting the pdf format of the snapshot-report:

GET `{{dataAPIBaseUrl}}/publications?format=pdf&id=09df7d4a-8b87-45d8-a1ef-4bc41b3310f0`

Params Authorization Headers (10) Body Pre-request Script Tests Settings

Query Params

Key	Value	Description
<input type="checkbox"/> language	EN	
<input checked="" type="checkbox"/> format	pdf	
<input checked="" type="checkbox"/> id	09df7d4a-8b87-45d8-a1ef-4bc41b3310f0	
Key	Value	Description

Body Cookies Headers (15) Test Results Status: 200 OK Time: 279 ms Size: 4

4/24/2023

coface / Business Information

Snapshot Report

© Coface Poland Credit Management Services Sp. z o.o.
e-mail: customerservice@coface.com
24.04.2023
document id: 2235622-4-506-cce_test-beacon-2.10.0.9-d62d83fe-P2

ORDER DETAILS

Order Details Customer: Cormete AO - Testaccount

Let us now order one last product, Score product, DRA- package, which is the score with 5 years history:

POST `{{dataAPIBaseUrl}}/publications/orders`

Params Authorization Headers (12) Body Pre-request Script Tests Settings

● none ● form-data ● x-www-form-urlencoded ● raw ● binary ● GraphQL JSON


```
1 {
2   "companyId": "{{companyId}}",
3   "assessments": [
4     {
5       "slug": "debtor-risk-assessment-package"
6     }
7   ]
8 }
```

Body Cookies Headers (14) Test Results (0/1)

Pretty Raw Preview Visualize JSON

```
1 {
2   "id": "1e063c1d-4851-4b82-ad2f-f108c288a70b",
3   "orderDate": "2023-04-24T06:47:08.43+02:00",
4   "expectedDeliveryDate": "in-preparation",
5   "status": "in-preparation",
6   "publications": [
7     {
8       "id": "b3431bc1-4c9d-4d1b-09a7-83be6fd0918f",
9       "status": "in-preparation",
10      "expectedDeliveryDate": "in-preparation",
11      "assessmentSlug": "debtor-risk-assessment-package"
12    }
13  ]
14 }
```

As this is not an immediate product, and can take a little bit of time until is ready, first check status is still in-preparation:



GET `{{dataAPIBaseUrl}}/publications/orders?id=1e063c1d-4851-4b82-ad2f-f108c288a70b`

Params Authorization Headers (10) Body Pre-request Script Tests Settings

Query Params


Key	Value	Description
<input checked="" type="checkbox"/> Id	1e063c1d-4851-4b82-ad2f-f108c288a70b	
Key	Value	Description

ody Cookies Headers (16) Test Results Status: 200 OK Time: 1185 ms

Pretty Raw Preview Visualize JSON

```
1 {
2   "id": "1e063c1d-4851-4b82-ad2f-f108c288a70b",
3   "orderId": "2023-04-24T06:47:00+02:00",
4   "expectedDeliveryDate": "2023-05-02T09:00:00+02:00",
5   "status": "in-preparation",
6   "publications": [
7     {
8       "id": "b3431bc1-4c9d-4d1b-89a7-83be6fd0918f",
9       "status": "in-preparation",
10      "expectedDeliveryDate": "2023-05-02T09:00:00+02:00",
11      "assessmentSlug": "debtor-risk-assessment-package"
12    }
13  ]
14 }
15
16
```

If I am trying to get the content now, via /publications endpoint, it will not be ready:



GET `{{dataAPIBaseUrl}}/publications?format=json&id=b3431bc1-4c9d-4d1b-89a7-83be6fd0918f`

Params Authorization Headers (10) Body Pre-request Script Tests Settings

Query Params

Key	Value	Description
<input type="checkbox"/> language	EN	
<input checked="" type="checkbox"/> format	json	
<input checked="" type="checkbox"/> Id	b3431bc1-4c9d-4d1b-89a7-83be6fd0918f	
Key	Value	Description

ody Cookies Headers (14) Test Results Status: 202 Accepted T

Pretty Raw Preview Visualize JSON

```
1 {
2   "httpCode": 202,
3   "url": "/publications",
4   "fishtag": "559527ee-4d84-4105-9017-00afe72cbe1e",
5   "messages": [
6     {
7       "code": "order_not_finished",
8       "message": "Order is not yet finished"
9     }
10  ]
11 }
```

But we do have the expected delivery date which is the maximum SLA for the product to be available.